

Vehicle-Carried Quick Inspection System

BACKGROUND OF THE INVENTION

5 Field of the Invention

Embodiments of the present disclosure relate to the field of security inspection, and particularly, to a vehicle-carried quick inspection system.

Description of the Related Art

10 Radiation imaging inspection technologies are necessary security inspection means for customhouses, subways, civil aviation airports and railway systems. During inspection under an existing vehicle-carried quick inspection system, an inspected vehicle needs to stop at a designated position, and all persons including a driver on the vehicle get off the vehicle and go away from a scanning region, then the inspection
15 system moves on its own at a speed so as to complete inspection on the inspected vehicle; in this scanning mode, a scanning speed is generally in a range of 0.2~0.6 m/s, and the maximum limit of inspection efficiency is 30 vehicles/hours in theory. There is a need to provide a vehicle-carried quick inspection system, which can not only keep motility and flexibility characteristics of a vehicle-carried quick inspection
20 system, but also increase the inspection rate so as to improve the inspection efficiency.

SUMMARY OF THE INVENTION

25 An object of embodiments of the present disclosure is to provide a vehicle-carried quick inspection system, which not only has motility and flexibility characteristics, but also enables quick and efficient inspection.

The present invention relates, in one aspect, to a vehicle-carried quick inspection system, comprising:

a carrying vehicle,

a foldable arm mount provided on the carrying vehicle and configured to be folded onto or within the carrying vehicle in a transportation state and to be unfolded to stride over an inspected vehicle in a working state so as to form an inspection passage through which the inspected vehicle passes during inspection;

5 an X-ray source capable of providing an adjustable radiation dose, provided on the carrying vehicle and configured to radiate X-rays of a desired dose to irradiate the inspected vehicle;

10 a detector provided on the foldable arm mount and configured to be located at a position opposite to the X-ray source and to receive information about X-rays passing through the inspected vehicle in the working state, in which the X-ray source and the detector are arranged on opposite sides of the inspection passage for the inspected vehicle and the inspected vehicle passes through the inspection passage;

a controller configured to control the X-ray source to irradiate different portions of the inspected vehicle with different doses; and

15 an additional mount and photosensors mounted on the additional mount, the photosensors being configured to transmit signals to the controller when a head portion of the inspected vehicle passes the additional mount in a direction from a head portion to a tail portion of the carrying vehicle, so that the controller actuates the X-ray source to increase radiation dose, thereby the vehicle-carried quick inspection
20 system enters into a high dose inspection state.

According to embodiments of the present disclosure, there is provided a vehicle-carried quick inspection system, for being mounted on a vehicle, the inspection system comprising: an X-ray source capable of providing an adjustable radiation dose and configured to radiate X-rays of a desired dose to irradiate the
25 inspected vehicle; a detector configured to be located at a position opposite to the X-ray source and to receive information about X-rays passing through the inspected vehicle, the X-ray source and the detector being arranged on opposite sides of an inspection passage through which the inspected vehicle moves during inspection; the vehicle-carried quick inspection system further comprises a controller configured to

control the X-ray source to radiate different portions of the inspected vehicle with different doses.

According to embodiments of the present disclosure, the vehicle-carried quick inspection system may further comprise a foldable rotation mount, on which the
5 detector is arranged. In a road travelling state, the foldable rotation mount is foldable onto or within the vehicle provided with the vehicle-carried quick inspection system; in an inspection working state, the foldable rotation mount is moved to be in a direction transverse to the inspection passage and is unfolded to form the inspection passage.

10 According to embodiments of the present disclosure, the vehicle-carried quick inspection system may further comprise one or more first sensors configured to sense a vehicle adjacent thereto so as to send a signal to the vehicle-carried quick inspection system for being ready for inspection.

According to embodiments of the present disclosure, the vehicle-carried quick
15 inspection system may further comprise a plurality of second sensor configured to sense a position of the inspected vehicle relative to the X-ray source and to transmit information about the position of the inspected vehicle to the controller.

According to embodiments of the present disclosure, the plurality of second
20 sensors may be arranged and configured to measure a relative speed between the vehicle-carried quick inspection system and the inspected vehicle.

According to embodiments of the present disclosure, the controller may be
further configured to, according to a sensing result from the second sensors, control
the X-ray source so that the X-ray irradiation dose is reduced or the irradiation is
stopped so as to avoid irradiation damage to a human body when a driver's cab of the
25 inspected vehicle passes through the X-ray beam. In one embodiment, the controller
may be further configured to, according to a sensing result from the second sensors,
control the X-ray source to irradiate a designated portion of the inspected vehicle with
an extremely low dose or to stop irradiation onto the designated portion, and to
irradiate other portions of the inspected vehicle with a working irradiation dose when

the other portions pass through the X-ray beam.

According to embodiments of the present disclosure, the controller may be arranged to perform inspection, in conjunction with the relative speed between the vehicle-carried quick inspection system and the inspected vehicle measured by the plurality of second sensors, so as to form an X-ray image.

According to embodiments of the present disclosure, the controller may be arranged to perform inspection, in conjunction with the relative speed between the vehicle-carried quick inspection system and the inspected vehicle measured by the plurality of second sensors, so as to alarm and interrupt the inspection when a relative moving speed of the inspected vehicle exceeds a maximum limit value or is below a minimum limit value.

According to embodiments of the present disclosure, the vehicle-carried quick inspection system may further comprise an indicator light device configured to display an indication to allow the inspected vehicle to pass through the inspection system when the inspection system is ready for inspection, otherwise to display a prohibition indication.

According to embodiments of the present disclosure, the first sensor may be a geomagnetic sensor, a microwave sensor, or a laser sensor.

According to embodiments of the present disclosure, the ray source may be a γ ray source or a neutron ray source.

According to another aspect of the present invention, there is provided an inspection vehicle, comprising the vehicle-carried quick inspection system as described above.

According to a further aspect of the present invention, there is provided an inspection method, comprising performing a quick inspection on a moving object by using the vehicle-carried quick inspection system as described above.

With the vehicle-carried quick inspection system according to embodiments of the present disclosure, a mobile and fully automated security inspection system is obtained and quick inspection can be achieved, while protecting the driver from being

damaged from X-ray irradiation. Compared to fixed inspection systems or mobile inspection systems in prior arts, the vehicle-carried quick inspection system according to embodiments of the present disclosure can provide more convenient and quicker inspection.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top view of a vehicle-carried quick inspection system according to an embodiment of the present disclosure;

Fig. 2 is a rear view of a vehicle-carried quick inspection system according to an
10 embodiment of the present disclosure;

Fig. 3 is a side view of a vehicle-carried quick inspection system according to an embodiment of the present disclosure, showing arrangement of a plurality of sensor;
and

Fig. 4 shows a vehicle-carried quick inspection system which is inspecting a
15 container vehicle 2.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

A vehicle-carried quick inspection system 11 according to embodiments of the
20 present disclosure, which is set up on a vehicle 1, will be described below with reference to Figs. 1-4.

The vehicle-carried quick inspection system comprises an X-ray source 12, for example, an X-ray accelerator 12 capable of providing an adjustable radiation dose, arranged on the vehicle 1 provided with the vehicle-carried quick inspection system
25 11. Preferably, the X-ray accelerator 12 is mounted on the tail portion of the vehicle 1 provided with the vehicle-carried quick inspection system. It will be appreciated that the X-ray accelerator 12 may be mounted at other positions on the vehicle 1 provided with the vehicle-carried quick inspection system. The X-ray accelerator 12 can radiate high dose X-rays when inspecting an object, for example, container/goods in a

container vehicle, and the like. However, when the head portion or other designated portion, that is, a portion where a person is located, of the container vehicle, passes in the vicinity of the X-ray accelerator 12, the X-ray accelerator 12 stops radiating X-rays, or the dose from the X-ray accelerator 12 is adjusted to a very low dose which is radiation safety to the person. The dose of X-rays may be set by those skilled in the art as desired. The X-ray accelerator 12 may radiate X-rays having other high doses. The vehicle-carried quick inspection system may be operated by an operator to implement inspection.

The vehicle-carried quick inspection system 11 may further comprise a detector 13 and a mount 16 on which the detector 13 is arranged. The mount 16 comprises a first mount arm 161 and a second mount arm 162. The mount 16 is preferably connected to and supported on the tail portion of the vehicle 1. More preferably, the mount 16 is pivotally supported on the tail portion of the vehicle 1. When the vehicle 1 travels, for example, towards a destination, the mount 16 is folded and placed on the top of the vehicle 1, or is folded within the compartment of the vehicle 1, as shown in Fig. 3. When the vehicle 1 stops and implements inspection on, for example, the container vehicle 2, the mount 16 is pivoted, so that the first mount arm 161 extends in a transverse direction of the vehicle body of the vehicle 1 provided with the vehicle-carried quick inspection system 11 and the second mount arm 162 is unfolded so as to extend in a vertical direction, thereby forming or define an inspection passage 3, in conjunction with the vehicle body, as shown in Figs. 1, 2 and 4. Preferably, electric devices such as a motor or the like, joints and hydraulic driving devices may be provided to achieve automatic pivoting and unfolding operation of the mount 16, thereby further simplifying inspection operations and improving inspection efficiency. In this case, the detector 13 mounted on the mount 16 may be arranged on a side of the inspection passage 3 opposite to the X-ray accelerator 12, that is, the X-ray accelerator 12 and the detector 13 are arranged on opposite sides of the inspection passage 3. The detector 13 may comprise a plurality of detector 13 arranged on the second mount arm 162, the detector 13 may be also arranged on the first mount arm.

The detector(s) is arranged on a side opposite to the X-ray accelerator 12 and is configured to collect X-rays emitted from the X-ray source and transmitted through the container vehicle, so that information about the container vehicle can be obtained by analyzing collected X-ray irradiation signals, for example, so as to determine whether or not there is any contraband or the like in the container.

A collimator 17 may be provided in front of the X-ray accelerator 12, and position and size of the collimator 17 may be set by those skilled in the art as required.

Compared to an inspection station fixed in position, the above arrangement enables mobility of the X-ray inspection system 11, providing great convenience in practice use; further, the foldable and extendable mount 16 is configured so that inspection operation is simple, that is, the inspection passage may be constructed quickly in field for ready to inspect a mobile object such as a vehicle or the like, and the mount may be folded and stored quickly, for leaving the field.

In order to implement security inspection, the vehicle-carried quick inspection system according to embodiments of the present disclosure may further comprise a controller 18 configured to control the X-ray accelerator 12 to radiate appropriate radiation dose as required. For example, during a period when the container vehicle 2 passes through the inspection passage 3, the head portion of the container vehicle 2 firstly enters the inspection passage, and the controller 18 controls the X-ray accelerator 12 to reduce radiation dose so as to avoid damage to the driver when the head portion passes through an X-ray radiation region. After the head portion or a designated portion of the vehicle passes through the X-ray radiation region, the container enters the X-ray radiation region, at this time, the controller 18 controls the X-ray accelerator 12 to increase the radiation dose, that is, enter into a high dose inspection state.

According to embodiments of the present disclosure, the controller 18 is provided to control the radiation dose of the X-ray accelerator 12, thereby avoiding damage to persons, which is important in safety in actual applications.

Different regions or portions of the inspected vehicle may be identified through human eyes, or may be identified by various kinds of sensors, such as a photoelectric switch, an ultrasonic switch, light curtain, a laser sensor, a ground sensing coil and the like.

5 According to another embodiment of the present disclosure, the vehicle-carried quick inspection system further comprises at least one first sensor 14 and a plurality of second sensor 15, for providing quick inspection.

10 The first sensor may be a geomagnetic sensor 14, and may be mounted, for example, in the vicinity of the X-ray accelerator 12. The geomagnetic sensor 14 may sense the vehicle based on a change in ambient magnetic field. For example, when no container vehicle is approaching, the geomagnetic sensor 14 senses a background magnetic field which is stored by the controller 18. When a container vehicle 2 is approaching, there is a change in magnetic field, which is sensed by the geomagnetic sensor 14, thereby it can be determined that the container vehicle 2 is approaching. Of course, a microwave or laser sensor may be used to achieve the function of sensing the vehicle.

15 Once the geomagnetic sensor 14 senses that the container vehicle 2 is approaching, the vehicle-carried quick inspection system enters into a state ready for inspection, thereby enabling automation operation of the vehicle-carried quick inspection system. For example, the geomagnetic sensor 14 may transmit the sensed signal to the controller 18, and controller 18 actuates the inspection system to enter into the inspection state.

20 The second sensor 15 may be, for example, a photosensor 15. When the container vehicle 2 is approaching, light (for example, irradiation light from the inspection system) reflected by the container vehicle 2 is sensed by photosensor 15, thus, a position of the vehicle may be determined through the photosensor. In an embodiment of the present disclosure, the number of the second sensor 15 may be, for example, eight; for example, sensors 155, 156, 157, 158, 159, 1510, 1511 and 1512 are provided. The photosensors 155, 156 are arranged on a side surface of the vehicle

1, are spaced apart from each other by a fixed distance, and are located at different heights, thereby portions of the vehicle body of the container vehicle 2 having different heights may be sensed. When the head portion of the container vehicle 2 begins to enter the inspection passage, the photosensors 155, 156 sense the head portion and transmit a signal indicative of the head portion to the controller 18, then the controller 18 controls the X-ray accelerator 12 to reduce radiation dose or to stop radiation; when the container portion of the container vehicle 2 begins to enter the X-ray radiation region, the photosensors 157, 158 and 159 sense and judge that the container portion enter the X-ray radiation region, and the controller 18, after receiving signals from the sensors, controls the X-ray accelerator 12 to increase radiation dose, that is, enter into a high dose inspection state.

In a further embodiment of the present disclosure, the number of the second sensor 15 may be twelve, and these photosensors 151-1512 are arranged on one side surface of the vehicle 1, spaced apart from one another, and located at different heights, so that portions of the vehicle body of the container vehicle 2 having different heights may be sensed. When the head portion of the container vehicle 2 enters the inspection passage in a direction from the head portion to the tail portion of the vehicle 1, the photosensors 157, 158, 159 sense the head portion of the container vehicle 2 and transmit a signal indicative of the head portion of the container vehicle 2 to the controller 18, and the controller 18 controls the X-ray accelerator 12 to reduce radiation dose or to stop radiation; after the head portion of the container vehicle passes through the sensors 151, 152 and 153, the container portion of the container vehicle begins to enter the X-ray radiation region, then the photosensors 151, 152 and 153, in conjunction with the sensors 154-159, sense that the container portion enters the X-ray radiation region, and the controller 18, after receiving signals from the sensors, controls the X-ray accelerator 12 to increase radiation dose, that is, enter into a high dose inspection state. When the sensors 151, 152 and 153 sense that the tail portion of the container vehicle has passed therethrough, the controller 18 receives signals from the sensors and controls the X-ray accelerator to stop irradiation so as to

finish inspection.

The second sensors 15 may be arranged so that there are a plurality of the sensors 15 within a local region. These photosensor 15 are spaced apart from one another by a known distance and configured to measure a position of one same portion of a mobile object, so that a time interval by which mobile object 2 passing through these spaced photosensors may be sensed through these photosensors, and thus a relative movement speed of the mobile object 2 may be calculated. The techniques of sensing a mobile object by using photosensors so as to determine the position of the mobile object and to measure a speed of the mobile object are well known to those skilled in the art. For example, the second sensor 15 may be camera (CCD); or the second sensor 15 may be other types of sensors, and the speed of the mobile object may be determined through cooperation of the sensor and a reference object such as a grating. If it is known that a person is locating at a position on the mobile object 2, the second sensor 15 may transmit a signal to the controller 18, so that irradiation is reduced or stopped for the region where the person is locating.

It would be advantageous to arrange a plurality of sensors on the side surface of the vehicle 1, preferably, over the side surface in a longitudinal direction of the vehicle body, so that a distance between the container vehicle 2 and the vehicle 1 may be sensed. When the container vehicle 2 deviates from the inspection passage, for example, the container vehicle 2 is too close to the vehicle-carried quick inspection system and there is a possibility of collision, the vehicle-carried quick inspection system may alarm to warn the driver to correct the vehicle body.

It is preferable that the container vehicle 2 passes through the inspection passage in a uniform rectilinear motion during inspection, and the movement speed of the container vehicle 2 may be in an appropriate range, which may be determined according to parameters of the X-ray inspection system in practice. When it is sensed that the relative speed of the container vehicle 2 is greater than an upper speed limit of the range or less than a lower speed limit of the range, the vehicle-carried quick inspection system will give an alarm and the inspection is interrupted.

Thus, the vehicle-carried quick inspection system according to embodiments of the present disclosure is integrated into a whole, and compared to existing inspection systems, has a better mobility, enables automated and quick inspection operations by means of the controller 18 as well as the first sensor 14 and the second sensor 15, and
5 can expedite inspection rate while ensuring safety of persons, thereby having important applications in practice.

According to embodiments of the present disclosure, when the vehicle provided with the vehicle-carried quick inspection system reaches a field such as a port, the mount 16 is driven to pivot and be unfolded so as to form an inspection passage.
10 When the container vehicle 2 approaches the vehicle-carried quick inspection system, the geomagnetic sensor senses a change in magnetic field, and transmits a signal to the controller 18, thereby the controller 18 starts the inspection system. When the head portion of the container vehicle 2 begins to enter the inspection passage, the photosensors sense that the vehicle head portion enters an X-ray radiation region and
15 transmit signals indicative of the position and speed of the vehicle head portion to the controller 18, and the controller 18 controls the X-ray accelerator 12 to stop working or reduce radiation dose to a safe dose. The driver drives the vehicle to travel at a constant speed, and when sensing that the container portion enters the X-ray radiation region, the photosensor transmits a signal to the controller 18, then the controller 18
20 controls the X-ray accelerator 12 to increase radiation dose. The controller 18 receives a signal indicative X-rays transmitted through the container and detected by the detector 13, and displays information about scanned objects within the container vehicle on a display in combination with the shape and speed of the container.

Thus, when the vehicle carrying the vehicle-carried quick inspection system
25 reaches an inspection field, inspection operation may be launched within several minutes, and the container vehicle 2 only needs to passes through the inspection passage at a constant speed in an appropriate range, thereby completing inspection; further, the whole inspection operation is fully automated, without any additional operations by the operator. For example, a container vehicle 2 having a length of 18

meters passes through the inspection passage at a speed of 2m/s, the inspection of the container vehicle may be completed within 10 seconds.

The container vehicle 2 may enter the inspection passage from the tail portion of the vehicle 1 provided with the vehicle-carried quick inspection system, or may enter
5 the inspection passage from the head portion of the vehicle 1.

When the container vehicle 2 enters the inspection passage from the head portion of the vehicle 1, it is required to provide an additional mount 16', which is preferably mounted on the vehicle 1, and on which photosensors 151, 152 and 153 are mounted and configured to transmit signals to the controller 18 when the head portion of the
10 container vehicle passes the additional mount 16', so that the controller 18 actuates the X-ray accelerator 12 to increase radiation dose, thereby the vehicle-carried quick inspection system enters into a high dose inspection state.

The vehicle-carried quick inspection system may further comprise an indication device. For example, the vehicle-carried quick inspection system comprises an
15 indicator light. When the container vehicle 2 moves at a constant speed to approach the vehicle-carried quick inspection system, the vehicle-carried quick inspection system displays a green indicator light, for example. In this case, the container vehicle 2 continues to pass through the inspection passage 3. When the container vehicle 2 is being located within the inspection passage, the indicator light displays a red color,
20 so that a container vehicle waiting behind is prohibited from entering the inspection passage. An alarm device may also be provided to give an alarm indication when the inspection is interrupted.

Compared to conventional combined mobile quick inspection systems, with the technique solutions provided according to the embodiments of the present disclosure,
25 a quick transfer from one field to another field may be achieved, that is, no particular field is needed, and an occupying area is small; the security inspection vehicle may be driven away after inspection, without obstructing normal use of a road. For example, if it is required to perform a quick security inspection within such a region as small as possible or within a temporary region, the technique solutions provided according to

the embodiments of the present disclosure may be applied. Further, according to the embodiments of the present disclosure, the security inspection vehicle may be driven to a section of an existing road through which a container vehicle will necessarily pass, and the driver only needs to drive the vehicle through the section of the road at a normal speed, so that the inspection is completed quickly with a high efficiency, without providing a separate security inspection field. The security inspection vehicle may stop at a parking area or garage when not working, occupying a small area; when the security inspection vehicle needs to be maintained, it may be driven to a designated repair shop for convenient and quick maintenance.

Having further described the objectives, technical solutions and advantageous effects of the present disclosure in detail in the above exemplary embodiments, it will be appreciated that the above described contents are only preferred embodiments of the present disclosure, and are not intended to limit the present disclosure. All changes, alternatives or modifications which are made the principles and spirit of the present disclosure should fall within the scopes of the present invention. Thus, the scopes of the present invention should be limited only by the claims.

Throughout this specification and the claims which follow, unless the context requires otherwise, the word “comprise”, and variations such as “comprises” and “comprising”, will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

What is claimed is:

1. A vehicle-carried quick inspection system, comprising:

5 a carrying vehicle,

a foldable arm mount provided on the carrying vehicle and configured to be folded onto or within the carrying vehicle in a transportation state and to be unfolded to stride over an inspected vehicle in a working state so as to form an inspection passage through which the inspected vehicle passes during inspection;

10 an X-ray source capable of providing an adjustable radiation dose, provided on the carrying vehicle and configured to radiate X-rays of a desired dose to irradiate the inspected vehicle;

a detector provided on the foldable arm mount and configured to be located at a position opposite to the X-ray source and to receive information about X-rays passing
15 through the inspected vehicle in the working state, in which the X-ray source and the detector are arranged on opposite sides of the inspection passage for the inspected vehicle and the inspected vehicle passes through the inspection passage;

a controller configured to control the X-ray source to irradiate different portions of the inspected vehicle with different doses; and

20

an additional mount and photosensors mounted on the additional mount, the photosensors being configured to transmit signals to the controller when a head portion of the inspected vehicle passes the additional mount in a direction from a head portion to a tail portion of the carrying vehicle, so that the controller actuates the
25 X-ray source to increase radiation dose, thereby the vehicle-carried quick inspection system enters into a high dose inspection state.

2. The vehicle-carried quick inspection system according to claim 1, further comprising a plurality of second sensors configured to sense a position of the
30 inspected vehicle relative to the X-ray source and to transmit information about the

position of the inspected vehicle to the controller.

3. The vehicle-carried quick inspection system according to claim 2, wherein the plurality of second sensors are arranged and configured to measure a relative speed between the vehicle-carried quick inspection system and the inspected vehicle.

5 4. The vehicle-carried quick inspection system according to claim 2 or claim 3, wherein the controller is further configured to, according to a sensing result from the second sensors, control the X-ray source so that the X-ray irradiation dose is reduced or the irradiation is stopped so as to avoid irradiation damage to a human body when a driver's cab of the inspected vehicle passes through the X-ray beam.

10 5. The vehicle-carried quick inspection system according to any one of claims 2 to 4, wherein the controller is further configured to, according to a sensing result from the second sensors, control the X-ray source to irradiate a designated portion of the inspected vehicle with an extremely low dose or to stop irradiation onto the designated portion, and to irradiate other portions of the inspected vehicle with a
15 working irradiation dose when the other portions pass through the X-ray beam.

6. The vehicle-carried quick inspection system according to any one of claims 3 to 5, wherein the controller is further configured to perform inspection, in conjunction with the relative speed between the vehicle-carried quick inspection system and the inspected vehicle measured by the plurality of second sensors, so as to form an X-ray
20 image.

7. The vehicle-carried quick inspection system according to any one of claims 3 to 6, wherein the controller is further configured to perform inspection, in conjunction with the relative speed between the vehicle-carried quick inspection system and the inspected vehicle measured by the plurality of second sensors, so as to alarm and
25 interrupt the inspection when a relative moving speed of the inspected vehicle exceeds a maximum limit value or is below a minimum limit value.

8. The vehicle-carried quick inspection system according to any one of claims 1 to 7, further comprising an indicator light device configured to display an indication to allow the inspected vehicle to pass through the inspection system when the

inspection system is ready for inspection, otherwise to display a prohibition indication.

9. The vehicle-carried quick inspection system according to any one of claims 1 to 8, further comprising: a first sensor configured to sense whether or not a vehicle is approaching thereto and to send a signal to the controller when it senses that a vehicle is approaching so that the controller actuates the vehicle-carried quick inspection system for being ready for inspection.

10. The vehicle-carried quick inspection system according to claim 9, wherein the first sensor is a geomagnetic sensor, a microwave sensor, or a laser sensor.

11. The vehicle-carried quick inspection system according to any one of claims 1 to 10, wherein the ray source is a γ ray source or a neutron ray source.

12. An inspection vehicle, comprising the vehicle-carried quick inspection system according to any one of claims 1 to 11.

13. An inspection method, comprising performing a quick inspection on a moving object by using the vehicle-carried quick inspection system according to any one of claims 1 to 11.