

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
30 November 2000 (30.11.2000)

PCT

(10) International Publication Number
WO 00/72457 A1

- (51) International Patent Classification⁷: H04B 1/48, H03H 7/38
- (21) International Application Number: PCT/US00/13606
- (22) International Filing Date: 18 May 2000 (18.05.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/135,467 24 May 1999 (24.05.1999) US
09/527,314 16 March 2000 (16.03.2000) US
- (71) Applicant: LEVEL ONE COMMUNICATIONS, INC.
[US/US]; 9750 Goethe Road, Sacramento, CA 95827 (US).
- (72) Inventors: MACNALLY, Donald, E.; 141 Bronte Street, San Francisco, CA 94110 (US). CHO, Thomas, B.; 356 Oleander Avenue, Alameda, CA 94502 (US).
- (74) Agent: BRUESS, Steven, C.; Merchant & Gould P.C., P.O. Box 2903, Minneapolis, MN 55402-0903 (US).
- (81) Designated States (*national*): CA, IL, SG.
- (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- Published:
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: ANTENNA INTERFACE



(57) Abstract: An antenna interface for a Time Division Duplex (TDD) radio transceiver allows a transceiver to be attached to an antenna/filter without the need for an antenna switch. The antenna interface includes a single Balun circuit to convert a single-ended signal to/from differential signals, and a single impedance matching circuit to match an impedance at an output of the single Balun circuit with an input impedance of a Low Noise Amplifier (LNA) of a receiver and to provide an output impedance of a Power Amplifier (PA) of a transmitter. The single impedance matching circuit is coupled to both the LNA and the PA. The LNA and the PA are based on CMOS technology and made within a single integrated circuit.

WO 00/72457 A1