

METHOD AND APPARATUS FOR CONSTRUCTING SEED GROUP IN PEER TO PEER APPLICATION AND METHOD OF USING SEED GROUP

Technical Field

5 The present invention relates to network communications, and particularly to a method and an apparatus for establishing a peer group and a method of using the peer group.

Background

10 Peer to Peer (P2P) technique is a basic technique widely used in current stream media communications. Management and application of peers is the core of P2P technique. In conventional solutions, peers are generally managed in a centralized manner, i.e., using a server to manage peers, and the peers have no connection with each other.

15 According to the conventional solutions, workload and costs of the server for managing the peers are huge, and peers can not be fully used. Therefore, the time taken for waiting and downloading is long, the downloading speed of stream media is low and service experience of users is also affected.

Summary

20 Embodiments of the present invention provides a method for establishing a peer group in P2P application, which establishes a more stable relationship between the peers, thus the peers can provide service promptly when network resource is needed. Thus the management workload and costs of the server are reduced, peers are more fully used, and user experience is improved.

 The method for establishing a peer group in P2P application according to embodiments may include:

25 a user terminal requests an initial peer from a peer server to make the peer server return one or more initial peers according to a configured policy;

 the user terminal establishes an initial peer group according to the initial peers returned;

the peers in the initial peer group communicate with each other to obtain information of peers in other peer groups, and establishes a new peer group according to the information of peers.

Embodiments also provide an apparatus for establishing a peer group in P2P application which may include:

an initial peer obtaining unit, configured in a user terminal, for obtaining one or more initial peers from a peer server to make the peer server return the initial peers according to a configured policy;

an initial peer group establishing unit, configured in the user terminal, for establishing an initial peer group according to the initial peers obtained by the initial peer obtaining unit; and

a new peer group establishing unit, configured in the user terminal, for obtaining information of peers in other peer groups through communication with peers in the initial peer group, and establishing a new peer group.

Embodiments still provide a method of using a peer group established according to the above method. The method may include:

a user terminal sends a resource request to a peer server to make the peer server return one or more initial peers having the resource;

an initial peer selects another peer that have the resource from a peer group to which the initial peer belongs, and provides the another peer for the user terminal;

the user terminal obtains the resource from the initial peer and the another peer.

From the above scheme it can be seen that, a user terminal firstly obtains one or more initial peers from a peer server; the peer server returns the one or more initial peers according to a configured policy; the user terminal establishes an initial peer group according to the initial peers; peers in the initial peer group communicate with each other to obtain information of other peers in other peer groups, and establish a new peer group according to the information of other peers. Therefore, a stable relationship is established among peers in the new peer group, and the peers can provide service promptly when needed. Further, management of peers is implemented in a user terminal, management pressure and costs of the server are thus reduced, peers can be more fully used, and user

experience is improved.

Brief description of the drawings

Fig. 1 is a flowchart illustrating a method for establishing a peer group according to embodiment one.

5 Fig. 2 is a schematic illustrating a peer group established in a process of embodiment one.

Fig. 3 is a flowchart illustrating a method of using a peer group in P2P application according to embodiment two.

10 Fig. 4 is a schematic illustrating a structure of an apparatus for establishing a peer group in P2P application according to embodiment three.

Detailed description of embodiments

Embodiments provide a method and an apparatus for establishing a peer group in P2P application, which can establish a stable relation among peers so that the peers can provide service promptly when needed. To make the technical scheme of the present invention more clear, some embodiments are described in detail with reference to the accompanying drawings.

Embodiment one provides a method for establishing a peer group in P2P application. Fig. 1 is a flowchart illustrating a method for establishing a peer group in P2P application of embodiment one. The method may include the following procedures.

20 In block 11, a user terminal obtains one or more initial peers from a peer server.

In this block, the user terminal may firstly log on the peer server, and sends a request to the peer server for obtaining an initial peer. At this block, a peer group has not been established in the user terminal. The initial peer refers to a node having a resource in P2P application, and the peer server refers to a managing unit having information of peers in a server.

25 In block 12, the peer server returns one or more peers according to a configured policy.

In this block, the peer server receives the request of the user terminal, returns one or more initial peers to the user terminal according to a configured policy. The configured

policy may be pre-set by an operator according to situations of resource occupation, or determined at random by the peer server according to network conditions. For example, it can be specified that the peer server returns nodes that have the required resource to the user terminal as the initial peers. For example, when five nodes have the required
5 resource, the five nodes are returned as the initial peers.

In block 13, the user terminal establishes an initial peer group according to the initial peers returned.

In this block, after receiving the initial peers returned by the peer server, the user terminal may establish the initial peer group according to the initial peers. The number of
10 peers in the initial peer group is the number of initial peers returned by the peer server.

In block 14, peers in the initial peer group communicate with each other to obtain information of peers from other peer groups, and forming respective new peer groups.

In this step, peers in the initial peer group communicate with each other to obtain information of peers in other peer groups, and obtain new peers according to the
15 information of the peers, and form new peer groups. Specifically, a peer in the initial peer group requests a peer list of a peer group to which another peer belongs. And the peer obtains information of peers in the peer list, and establishes a new peer group using peers having the same resource in the peer list according to information of the peers.

For example, Fig. 2 is a schematic illustrating a peer group established in
20 embodiment one. Fig. 2 shows three peer groups, where peer 2 is shared by peer group 1 and peer group 2, peer 3 is shared by peer group 2 and peer group 3. The peers in the peer groups are managed by themselves in a loose manner, and the management is implemented by user terminals without the peer server being involved.

In addition, the number of peers in a peer group as shown in Fig. 2 can be
25 configured by a user terminal according to network conditions or the needs. For example, when network condition is good, the upper limit of the number of peers in a peer group may be set to be 100, and when the number of peers in the peer group reaches the limit, i.e. 100, new peers will not be added into the peer group. The peer groups may be identified by different identifications, such as peer group A, peer group B, or peer group
30 C, which facilitates management of the user terminal.

Network type of peers in a peer group as shown in Fig. 2 may be set by a user

terminal, i.e., can be configured according to the needs. For example, a user terminal may configure that a peer group includes 1/3 of peers directly connected to the public network, 1/3 of peers connected to the public network via routers, and 1/3 of peers connected to the public network in other manners. The peers in the peer groups shown in Fig. 2 may have
5 the same or different resources, and the new peer group may include a number of idle peers. An idle peer refers to a peer does not have any network resource, and does not perform upload and download operations within a time period. The number of idle peers may also be configured by a user terminal.

Through the above process of establishing a peer group, a much stable relation can
10 be established between peers in the new peer group, and the peers can provide service promptly when needed. Management of the peers can be implemented by a user terminal, which reduces management pressure and costs of the server and increases utility of the peers, and thus improves experience of users.

When the number of peers in the new peer group decreases, the peers in the peer
15 group may perform further communications to obtain information of peers in other peer groups, and add new peers to the peer group according to information of the peers. For example, it can be configured that when the number of peers in a peer group decreases, or when the number of peers decreases to a specified threshold, the peers in the peer group communicate with each other to obtain information of peers in other peer groups, and add
20 new peers having the same resource to the peer group to increase the number of peers in the peer group. Therefore, the total number of peers in the peer group can be increased in response to leaving of some peers, and be kept at a certain number, which increases utility ratio of the peers.

Embodiment two provides a method of using a peer group in P2P application. Fig. 3
25 is a flowchart illustrating a method of embodiment two. The method may include the following procedures.

In block 31, a user terminal requests a resource from a peer server.

In this block , after a peer group is established according to the method of
embodiment one, when a user terminal needs a resource, the user terminal requests the
30 resource from the peer server.

In block 32, the peer server returns one or more initial peers having the resource.

In this block, the peer server receives the resource request sent by the user terminal, and returns initial peers having the resource requested. The number of initial peers returned can be determined by the peer server according to network conditions or resource occupation situations. For example, the number of nodes having the resource is 10, the peer server may return the ten nodes to the user terminal as initial peers.

In block 33, an initial peer selects another peer that have the resource from a peer group to which the initial peer belongs, and provides the another peer for the user terminal.

In this block, the initial peer may select another peer having the resource from the peer group to which the initial peer belongs to the user terminal, and each initial peer may select a peer from its peer group. And this selecting process can be implemented by a user terminal, and does not have to be implemented by the server.

In block 34, the user terminal obtains the resource from the initial peer and the another peer.

In this block, the user terminal obtains the resource from the initial peers and other peers received. Since the other peers are selected by the initial peers from respective peer groups and are not selected by the server, management presser and costs of the server is greatly reduced, and the peers can be more fully used, thus the service experience of users is also improved.

The user terminal may give priority to the initial peers as the source of the resource to guarantee the download speed.

For example, a user terminal Peer_1 requests a resource from a peer server, supposing Peer_1 is a new peer and belongs to no peer group. The peer group returns Peer_A1 and Peer_A2 which have the resource A. It is supposed that there are only two peers having the resource, and in practice, there may be multiple such peers.

Then Peer_1 requests data from Peer_A1 and Peer_A2. Peer_1 finds out the transmitting speeds of both peers are not satisfactory, and informs Peer_A1 and Peer_A2 of the situation. Peer_A1 and Peer_A2 select suitable nodes in respective peer groups, e.g., Peer_A1 selects Peer_A3 and Peer_A4 having the resource, and Peer_A2 selects Peer_A5 and Peer_A6 having the resource. Thus, Peer_1 obtains new peers, i.e., Peer_A3, Peer_A4, Peer_A5 and Peer_A6. And the process may be performed for a few times,

Peer_1 may obtain more peers, thus the downloading speed is increased. Further, the above selecting process is not performed by the server, the management workload and costs can be reduced, and service experience of users is also improved.

Embodiment three provides an apparatus for establishing a peer group in P2P application. Fig. 4 is a schematic illustrating a structure of an apparatus of embodiment three. The apparatus may include an initial peer obtaining unit, an initial peer group establishing unit and a new peer group establishing unit.

The initial peer obtaining unit is configured in a user terminal, for obtaining one or more initial peers from a peer server. The number of initial peers may be five.

The initial peer group establishing unit is configured in the user terminal, for establishing an initial peer group based on the initial peers obtained by the initial peer obtaining unit. The detailed establishing process is the same with the process described in the method of embodiment one.

The new peer group establishing unit is configured in the user terminal, for obtaining information of peers in other peer groups through communication with other peers in the initial peer group, and establishing a new peer group based on the information of peers obtained.

In addition, the apparatus may further include a configuring unit, which is configured in the user terminal and is for configuring the number of peers in the new peer group and a network type of a peer, and the number of idle peers in the new peer group. For example, it can be configured that the peer group includes 1/3 peers directly connected with a public network, and 1/3 peers connected with the public network via routers, and 1/3 other peers connected with the public network in other manners. In addition, the idle peer refers to a peer does not have network resource, and does not perform uploading and downloading operations within a specified time period. The number of idle peers may also be configured by the user terminal.

The apparatus may further include a peer adding unit, which is configured in the user terminal and is for obtaining information of peers in the other peer groups when the number of peers in the new peer group decreases, and adding new peers into the new peer group based on the information of peers obtained. For example, it can be configured that when the number of peers in a peer group decreases, or when the number of peers

decreases to a specified threshold, the peers in the peer group communicate with each other to obtain information of peers in other peer groups, and add new peers having the same resource to the peer group to increase the number of peers in the peer group. Therefore, the total number of peers in the peer group can be increased in response to
5 leaving of some peers, and be kept at a certain number, which increases utility ratio of the peers.

It should be noted that the apparatus is divided into the units by classification of functions, but the design of the units may follow other means as long as the functions can be implemented. The names of the units are merely used for identifying the units, and
10 should not be used for limiting the scope of the invention.

Those skilled in the art can understand that some or all of the steps of the methods provided by the embodiments may be implemented by hardware controlled by software. The software may be stored in a computer-readable storage medium.

Through the above process of establishing a peer group, a much stable relation can
15 be established between peers in the new peer group, and the peers can provide service promptly when needed. Management of the peers can be implemented by a user terminal, which reduces management pressure and costs of the server and increases utility of the peers, and thus improves experience of users.

The foregoing is only preferred embodiments of the present invention. The
20 protection scope of the present invention, however, is not limited to the above description. Any alteration or substitution that is within the technical scope disclosed by the present invention and can easily occur to those skilled in the art should be covered in the protection scope of the present invention. Therefore, the protection scope of the present invention should be according to the claims.

25

Claims

1. A method for establishing a peer group in a Peer to Peer (P2P) application, comprising:

requesting, by a user terminal, an initial peer from a peer server to make the peer
5 server return one or more initial peers according to a configured policy;

establishing, by the user terminal, an initial peer group based on the one or more
initial peers;

communicating, by peers in the initial peer group, with each other to obtain
information of peers in another peer group, and establishing a new peer group according
10 to the information of peers.

2. The method of claim 1, wherein communicating by peers in the initial peer group
with each other to obtain information of peers in another peer group and establishing a
new peer group according to the information of peers comprises:

acquiring, by a peer in the initial peer group, a list of peers in another peer group
15 from another peer in the initial peer group;

obtaining, by the peer, information of the peers in the list, and forming the new peer
group based on the information of the peers.

3. The method of claim 1 or 2, wherein the number of peers and network types of
peers in the new peer group are configured by the user terminal.

20 4. The method of claim 1, wherein peers in the new peer group have different
resource, the new peer group includes one or more idle peers, and the number of idle
peers in the new peer group is configured by the user terminal.

5. The method of claim 1, further comprising:

performing, by the peers in the peer group, communications with each other to
25 obtain information of peers in another peer group when the number of peers in the new
peer group decreases, and adding a new peer into the new peer group according to
information of the peers.

6. An apparatus for establishing a peer group in a Peer to Peer (P2P) application,

comprising:

an initial peer obtaining unit, configured in a user terminal, for obtaining one or more initial peers from a peer server to make the peer server return the one or more initial peers according to a configured policy;

5 an initial peer group establishing unit, configured in the user terminal, for establishing an initial peer group according to the one or more initial peers obtained by the initial peer obtaining unit; and

10 a new peer group establishing unit, configured in the user terminal, for obtaining information of peers in another peer group through communication with peers in the initial peer group, and establishing a new peer group based on the information of peers.

7. The apparatus of claim 6, further comprising:

a configuring unit, configured in the user terminal, for configuring the number of peers and network types of the peers in the new peer group, and the number of idle peers in the new peer group.

15 8. The apparatus of claim 6, further comprising:

a peer adding unit, configured in the user terminal, for obtaining information of peers in another peer group when the number of peers in the new peer group decreases, and adding a new peer into the new peer group based on the information of peers obtained.

20 9. A method of using the peer group established according to claim 1, comprising:

sending, by a user terminal, a resource request to a peer server to make the peer server return one or more initial peers having the resource;

selecting, by an initial peer, another peer that have the resource from a peer group to which the initial peer belongs, and provides the another peer for the user terminal;

25 obtaining, by the user terminal, the resource from the initial peer and the another peer.

10. The method of claim 9, wherein the user terminal gives priority to the initial peer as the source of the resource.