

DESCRIPTION

A method of manufacturing a motor vehicle

REPLACED SHEETS SG

- | | | | | | |
|-------------------------------------|-------------|---------|----------|----------|----------|
| ☒ | Description | : paged | ...1... | to paged | ...11... |
| ☒ | Claim(s) | : paged | ...12... | to paged | ...15... |
| ☒ | Drawing(s) | : paged | ...1... | to paged | ...4... |
| ☒ | Abstract | : paged | ...16... | to paged | ...7... |

The invention relates to a method of manufacturing a motor vehicle. In principle, in extreme cases, motor vehicles can be made up completely of individual parts or put together from prefabricated parts. The conventional modern method of manufacturing motor vehicles is a mixed system.

Components and sub-assemblies prefabricated to a varying extent are inserted into opened, ready-painted bodies. The disadvantage of this is that sensitive ready-painted bodies may be damaged by the wide variety of far-reaching assembly work. Damage to the outer skin during assembly will involve expensive after-treatment post final assembly. The supply and assembly of large parts is complicated and, since it is often difficult to automate, has to be performed by hand under adverse physiological conditions. Assembly of smaller parts increases the number of assembly operations on site, causes the staff to get in one another's way and lengthens the assembly time. Standardisation and model flexibility are difficult to combine.

As is known, economic advantages can be obtained if the minimum number of pre-fitted sub-assemblies are used in the manufacture of complex engineering

This Sheet Has Been Replaced



products. Recent manufacturing concepts, therefore, are based on prefabricating a vehicle in individual modules of maximum size. The individual modules can be completed separately. After being manufactured, optionally at different workplaces, they are brought on the conveyor belt for final assembly of the vehicle.

The manual by Horst Pippert "Karosserietechnik", 2nd edition, Würzburg: Vogel Buchverlag 1993, discloses various modular construction methods for rationalising the assembly of motor vehicles.

In the sub-frame method of construction, the sub-frames receive both the chassis and the drive. They are pre-assembled with these units and screwed to the self-supporting body via Silentblock-type rubber-metal connections.

It is also known, for example, to insert the entire dashboard, including the cockpit and pedals in one module, into the front part of the semifinished body and stick or screw it to the floor group.

In another embodiment the floor element has a module with ready-mounted cockpit, pedal supports and seats, can be inserted from beneath and stuck in the body bearing structure.

It is also known to separate the front region from the roof and the floor group. By

This Sheet Has Been Replaced



means of this horizontal division of the vehicle, the floor group can easily be equipped and, more especially, the drive block can easily be fitted before final assembly.

A division into a front and a rear part results in a vertically divided body. In this case a closed, rigid passenger compartment in the middle of the vehicle is connected to separately-prepared front and rear parts in steel frame construction.

All the different methods are based on the problem of prefabricating maximum-sized units. To a varying extent, however, they all have the disadvantage that they mostly optimise only one requirement, e.g. ease of assembly, but require compensating far-reaching structural changes or design changes.

Frequently it is necessary to abandon the economic method of constructing the self-supporting body from pressed parts, or new materials have to be used without a convincing amount of advantage.

WO 92/07749 discloses a method of assembling a motor vehicle wherein a front structure after completion is connected to a completed rear structure. The dividing line of the body extends centrally via the roof region. A disadvantage of the known method is that owing to the required stability it is very complicated to connect the two main parts of the body. In the case of a self-supporting body the

This Sheet Has Been Replaced



roof region is load-bearing. If the front structure is joined to the rear structure centrally in the roof region, the very thin sheet metal cannot bear loads, and consequently the floor group, which is similarly divided, has to be suitably reinforced. Such reinforcement considerably increases the weight.

JP-A-6-8851 discloses a concept wherein the body is not equatorially divided, but the vehicle comprises a number of components. The floor group like the body, which is mounted on the floor group, comprises two parts. The method disclosed in the citation emphasises the importance of the skeleton and is very close to the frame construction of cars in earlier periods. It shows the need for strong profile and auxiliary frames.

Starting from these problems, the aim of the invention is to disclose a method of manufacturing a motor vehicle suitable for economic segment construction and wherein the individual segments can be constructed substantially with conventional materials, tools and methods.

To this end, the semifinished body is pre-assembled in two main body parts (front structure and rear structure), the main body parts (front structure and rear structure) are independently equipped with the associated components, the mainly engineering components (motor, transmission, subsidiary equipment and the like) are mainly mounted in one main body part (front structure) and the mainly decorative components (seats, coverings, carpet and the like) are mainly installed

This Sheet Has Been Replaced



in the other main body part (rear structure), and after the main body parts (front and rear structure) have been at least substantially completed, they are put together and rigidly joined.

This is a means of prefabrication from only two main parts or main groups. Existing manufacturing equipment and assembly methods can largely be retained when manufacturing and completing the front and rear structure. The traditional materials can continue to be used and no design changes are necessary. The front structure and rear structure can be assembled at different places. At the final stage, they are simply brought together at the same place and riveted, stuck, screwed or welded together. The body is self- supporting as before.

The cost of having various models on offer is considerably reduced, because usually the engineering variants are basically restricted to different motorisation whereas there are much wider variations in the decoration, interior and other accessories. Further flexibility is obtained since there is wide freedom to combine the individual variants up to the final stage.

Especially advantageously, the mudguard, the bonnet, the doors and other external covering parts such as the bumper, radiator grille and the like are secured to the front structure only after the main body parts have been joined together. By this means, all the sensitive- surface parts are absent when the front part is assembled. They therefore cannot be damaged during assembly of the drive and transmission



block with the main auxiliary groups and when the cockpit and pedals are incorporated in the front part.

Also, in all model variants, the front part can be coated with a uniform paint, which is covered and therefore made invisible after the outer skin parts have been assembled. In view of the streamlining requirements on a modern motor vehicle, this modification has a further advantage because the bonnet must substantially cover the lower frame of the windscreen, e.g. so as to recess and streamline the windscreen wiper, and the A-column is covered by the windscreen or door frame, which is flush when stuck in. This provides hitherto unknown advantages in the choice of production sites, market flexibility, logistics and repairs.

To this end also it is advantageous if the components for subsequently securing to the front structure and painting in the colour of the vehicle can be painted together with the rear structure, simultaneously if necessary. This ensures that no differences in colour shade are observable in the finished vehicle.

In principle the main body parts can be joined at the level of the A-column, the connecting-places being provided on the windscreen frame and on the floor group approximately at the level of the top end of the A- column. The frame for the windscreen can be disposed either on the front structure, so that the A-column becomes part of the front structure, or on the rear structure, so that it becomes part of the rear structure. The advantage of disposing the windscreen frame on



the front structure is that the rear structure has a larger opening for fitting the interior.

When the main body parts are separated underneath the windscreen there is greater freedom to design the body segment. For example a limousine or a coupé version can both be equipped with the same front structure.

In another embodiment the front structure can comprise the entire floor group, i.e. the car floor and the running gear, by which means the advantages of the invention can also be applied to standard-drive vehicles (front or rear drive).

The invention can be used to obtain new forms of standardisation, thus improving the logistics of manufacture, use, disposal, repair and recycling. The combination of the individual advantages has an additional, decisive synergic effect compared with traditional methods. Left-hand and right-hand steering versions of vehicles can easily be constructed.

Owing to the wide opening near the middle of the hollow body member, parts can be supplied and fitted easily and simultaneously in both segments (main body parts) before final assembly.

Examples of the invention will now be explained in detail with reference to drawings, in which:

This Sheet Has Been Replaced



- Fig. 1 is a perspective view of the front part and rear part;
- Fig. 2 shows the outer covering parts for the front part;
- Fig. 3 corresponds to Fig. 1, with a modified rear part;
- Fig. 4 is a perspective view of an embodiment of the invention, and
- Fig. 5 shows part of the A-column of a streamlined modern vehicle, including the adjacent components.

According to the invention the semifinished body is pre-assembled from two main body parts, a front structure 1 and a rear structure 2. The sub-assemblies which mainly determine the engineering properties of the vehicle are disposed in the front part 1. These sub-assemblies are e.g. the engine 14, the transmission (not shown) and subsidiary units (also not shown) such as the air-conditioning system, the dynamo, radiator, etc. The front part also contains the cockpit 17 with the control components (not shown).

The front part 1 is bounded by the body nose 8, i.e. the front end of the subsequent vehicle, and the A-column 9, which is closed by the frame 10 for the windscreen 20. The floor group 12 belonging to the front part 1 ends approximately opposite the top end of the A-column 9 (vertically below it). The



front part 1 is a structure which determines the strength and collision behaviour of the vehicle and on delivery is painted in a uniform colour, not the colour of the subsequent vehicle, before the units are incorporated in the front part 1. The large opening in the middle of the semifinished body enables the cockpit 17 to be easily installed beforehand and facilitates insertion of the engine 14 and auxiliary units into the engine space from above and fitting of the axle, or the complete drive in the case of a front-engined vehicle, from beneath. After the front part 1 has been fitted with the required components, it and the rear part 2 are transported to the assembly site provided for the final stage.

The rear structure 2 is bounded by the body tail 11 and the roof attachment to the A-column 9. As Fig. 1 shows, the rear structure 2 can be fitted beforehand with the interior, the seats 13, the roof canopy (not shown), the side coverings, the safety-belts (not shown) and the floor carpet. After all the decorative parts have been fitted in the rear structure 2, it can be completed with the rear doors (not shown), the boot lid or the rear flap and then brought to the front part 1 for the final stage.

The front part 1 and rear part 2 are rigidly connected by suitable means. The drawings show simplified fastening places 18 on the roof and 19 on the floor group 12. The connection can be made by riveting, screwing, welding or sticking. Suitable methods are familiar to the skilled man.

This Sheet Has Been Replaced



After the front part 1 and rear part 2 have been fitted together, in the final stage, the standard-painted front structure 1, now the front part of the vehicle, is connected to the attached parts, i.e. the mudguard 3, the bonnet 4, the front doors 5, the bumper 6 and the radiator grille 7, which form the finish and are painted in parallel with the rear structure and are delivered in the same colour as the vehicle. The connection as before can be by riveting, screwing or sticking. Parts of the vehicle not covered by attached parts and still visible in the uniform basic paint, particularly inside the vehicle, can be concealed by soft cover parts.

Either the wheels 16 are fitted last on to the finished vehicle or they are attached during assembly of the two main body parts. Of course the vehicle must be completed by other components such as fuel and brake lines and electric connections and the like.

Fig. 4 shows a modification of the front structure 1 and rear structure 2. The frame 10 of the windscreen 20 and consequently the A-column 9 is associated with the rear structure 2. The front structure 1 therefore ends at the bottom end 9a of the A-column 9. The front structure 1 and rear structure 2 are subsequently connected via the aforementioned end 9a and the A- column 9. This embodiment has the advantage that the variability of the body is increased without affecting the front structure 1.

In another embodiment (not shown) the floor group 12 can be associated

This Sheet Has Been Replaced



completely with the front structure 1. If however the rear structure 2 needs to be provided with a floor plate and the floor group 12 forms only one running-gear frame, the advantages of the invention can also be obtained in the case of vehicles with a front engine and rear drive.

As Fig. 5 shows, in streamlined vehicles the A-column 9 is completely covered by the frame of the front door 5 and the windscreen 20 which is stuck in flush. The bonnet 4, which extends far beyond the bottom end of the windscreen 20, covers the bottom region of the window-frame.

This Sheet Has Been Replaced





CLAIMS

THIS SHEET HAS BEEN
REPLACED

1. A method of manufacturing a vehicle, wherein

- the semifinished body is pre-assembled in two main parts (front structure (1), rear structure (2)),
- the main body parts (front structure (1), rear structure (2)) are independently equipped with the associated components and
- the main body parts (front structure (1), rear structure (2)) are brought together and rigidly connected after being substantially completed,

characterised in that

- the engineering components (engine, transmission, subsidiary units and the like) are incorporated in one main body part (front structure (1)) and
- the mainly decorative components (seats, coverings, carpet and the like) are incorporated in the other main body part (rear structure (2)),

This Sheet Has Been Replaced





- the parting line between the two main body parts (front structure (1), rear structure (2)) extends at the level of the A-column (9), the upper connecting place being provided on the frame (10) of the windscreen (18) and the lower connection being provided between the A- column and the B-column, and
 - after the main body parts (front structure (1), rear structure (2)) have been connected together, the mudguard (3), the engine bonnet (4), the doors (5) and other outer covering parts (bumper (6), radiator grille (7) and the like) are secured to one main body part (front structure (1)).
2. A method according to claim 1, characterised in that the connection between the main body parts (front structure (1), rear structure (2)) is provided in the floor group (12) at the level of the upper end of the A-column (9).
 3. A method according to claim 2, characterised in that the frame (10) provided on the front structure (1) is connected to the rear structure (2).
 4. A method according to claim 2, characterised in that the frame (10) provided on the rear structure (2) is connected to the front structure (1).





- 14 -

PCT/DE 95/01494

5. A method according to one or more of the preceding claims, characterised in that the front structure (1) and rear structure (2) are connected by rivets, screwing, welding or sticking.
6. A method according to any one of the preceding claims, characterised in that the components painted in the colour of the vehicle and for fastening to one main part (front structure (1)) are painted together with the associated other main body part (rear structure (2)).
7. A semifinished body for use in the method according to any one of claims 1 to 6, characterised by a front structure (1) and a rear structure (2), with the front structure (1) being bounded by the body nose (8) and the frame (10), the windscreen (18), the A-column (9) and the rear structure (2) being bounded by the body tail (11) and the roof attachment (15) to the A-column (9), and front structure (1) and rear structure (2) being separate units.
8. A semifinished body for use in the method according to any one of claims 1 to 7, characterised by a front structure (1) and a rear structure (2), the front structure (1) being bounded by the body nose (8) and the lower attachment (9a) of the A-column (9) and the rear structure (2) being bounded by the body tail (11) and the frame (10), the windscreen (18) on the A-column (9), and front structure (1) and rear structure (2) being separate units.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 15 -

PCT/DE 95/01494

separate units.

9. A semifinished body according to claim 7 or claim 8, characterised in that the front structure (1) includes the complete floor group (12).

This Sheet Has Been Replaced

