

POLICIES FOR CONTENT DOWNLOADING AND CONTENT UPLOADING

TECHNICAL FIELD

The present invention relates to methods for a User Equipment
5 and for an IPTV controlling node of uploading/downloading IPTV
media content to or from a media content server, as well as to a
User Equipment and an IPTV controlling node.

BACKGROUND

10 An end-user may access IPTV (Internet Protocol Television)-
services from different types of UEs (User Equipments), such as
e.g. a TV, a PC (Personal Computer) or a mobile phone, for
example via the IMS (Internet Protocol Multimedia Sub-system),
provided that the UE has suitable functionality, which may be
15 specified e.g. according to the Open IPTV-Forum-specification.

Conventionally, a bandwidth can be reserved during set-up of a
session, such as e.g. a Video on Demand-session, which is using
a unicast stream, or a conventional television broadcast
20 session, which is using a multicast stream. The bandwidth
reservation will ensure that there is enough bandwidth both in
"the last mile" to the subscriber and in the aggregation network
in order to provide the user with an adequate experience,
without any disruptions or disturbances of the service. Further,
25 two sessions may together exceed the available bandwidth over
the last mile. This will cause the packets in the two sessions
to compete with each other, and result in that some packets will
be discarded in both sessions. Thus, it is important that a new
session is not allowed to affect the existing sessions, once a
30 bandwidth has been reserved for the existing sessions.

Media content can be downloaded from a media content server to a
UE, acting as a client terminal, e.g. by progressive
downloading, in which the media content is stored in a local

buffer in order to enable a play-out of the media file before the downloading is complete, by streaming downloading, in which the media content is streamed from the content server at the rate of the play-out and involving no storing, or by adaptive
5 streaming downloading, in which the content can be downloaded at different bitrates. In a similar way, media content can be uploaded from a UE to a content server, and may subsequently be shared to other users using downloading.

10 However, a conventional HTTP progressive downloading of media content only supports a best-effort Quality of Service, i.e. no guaranteed QoS, and the bandwidth may not be the maximum bandwidth. Consequently, in case the resolution of the media content is high and the network has a limited bandwidth, the
15 user experience of the play-out may be poor. For example, media content downloaded from the well-known website YouTube is displayed while it is being downloaded, using only best-effort Quality of Service. If the resolution is limited and not too high, the available bandwidth may be sufficient, and the user
20 experience of the played-out media content acceptable. However, otherwise the user experience may be poor.

Further, a correct playback of a progressively downloaded media file requires that the UE, i.e. the client terminal, is able to
25 buffer a large amount of media content.

Thus, it still presents a problem to achieve an acceptable user-experience of played-out media content.

30 SUMMARY

It is an object of embodiments described hereinafter to address at least some of the issues outlined above, and this object and others are achieved by the method and the apparatus according to

the appended independent claims, and by the embodiments according to the dependent claims.

Embodiments according to a first aspect provide a method for a
5 User Equipment of setting up a policy for downloading IPTV-
content from a Content Server, or a policy for uploading IPTV-
content to a Content Server. The User Equipment generates a
request comprising an indication of the type of content
downloading or content uploading, and transmits the request to
10 an IPTV-controlling node.

Embodiments according to a second aspect provide a method for an
IPTV-controlling node of setting up a policy for downloading
IPTV-content from a Content Server to a User Equipment, or
15 uploading IPTV-content to a Content Server from a User
Equipment. The IPTV controlling node receives a request from the
User Equipment, the request comprising an indication of the type
of content downloading or content uploading.

20 Embodiments according to a third aspect provide a User Equipment
arranged to set up a policy for downloading IPTV-content from a
Content Server, and/or for uploading IPTV-content to a Content
Server. The User Equipment comprises a communication device
provided with processing circuits, and is configured to generate
25 a request comprising an indication of the type of content
downloading and/or content uploading, and transmit the request
to an IPTV-controlling node.

Embodiments according to a fourth aspect provide an IPTV-
30 controlling node arranged to set up a policy for downloading
IPTV-content from a Content Server to a User Equipment, and/or
for uploading IPTV-content to a Content Server from a User
Equipment. The IPTV controlling node comprises a communication
device provided with processing circuits, and is configured to

receive a request from the User Equipment, and the request comprises an indication of the type of content downloading and/or content uploading.

- 5 An advantage with exemplary embodiments is to enable a reliable downloading or uploading of media content, such that the user experience of the play-out is not affected e.g. by congestion in the network.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in more detail below, and with reference to the accompanying figure, of which:

The figure 1a is a block diagram illustrating an exemplary IMS
15 IPTV-architecture for downloading and uploading of media content;

The figure 1b illustrates an OITF-enabled UE;

The figures 2a and 2b are signalling diagrams schematically illustrating exemplary UE-initiated content downloading-sessions
20 in an IMS IPTV-architecture;

The figures 2c and 2d are signalling diagrams schematically illustrating exemplary UE-initiated content downloading-sessions for plain IPTV;

The figure 3 is a flow diagram schematically illustrating a
25 method for a UE relating to content uploading or content downloading;

The figure 4 is a flow diagram schematically illustrating a method for an IPTV controlling node relating to content uploading or content downloading;

30 The figure 5 is a block diagram schematically illustrating an exemplary UE, and
the figure 6 is a block diagram schematically illustrating an exemplary IPTV controlling node.

DETAILED DESCRIPTION

In the following, the invention will be described in more detail with reference to certain embodiments and to an accompanying drawing. For the purpose of explanation and not limitation,
5 specific details are set forth, such as particular scenarios, techniques, etc., in order to provide a thorough understanding of the present invention. However, it is apparent to one skilled in the art that the present invention may be practiced in other embodiments that depart from these specific details.

10 Moreover, those skilled in the art will appreciate that the functions and means explained herein below may be implemented using software functioning in conjunction with a programmed microprocessor or general purpose computer, and/or using an
15 application specific integrated circuit (ASIC). It will also be appreciated that while the current invention is primarily described in the form of methods and devices, the invention may also be embodied in a computer program product as well as in a system comprising a computer processor and a memory coupled to
20 the processor, wherein the memory is encoded with one or more programs that may perform the functions disclosed herein.

A concept of embodiments described hereinafter is to indicate the type of content downloading or content uploading in an
25 initial request from the user equipment, in order to set up policies for downloading and/or uploading of media content, e.g. to reserve a suitable bandwidth.

According to further embodiments, the type of content
30 downloading or content uploading is indicated by a transfer type-attribute in the request, the attribute included in an SDP Offer contained in the initial request. According to another embodiment, a bandwidth attribute, proposing a bandwidth, is optionally included in the initial request.

Said transfer type-attribute indicates e.g. to the IMS and to the local transport policies that a session shall be set-up with specific requirements. For example, if the transfer type-
5 attribute indicates a streaming downloading, and a specific bandwidth is indicated in a bandwidth attribute, a streaming downloading session shall be set up, with a guaranteed bandwidth according to the bandwidth indicated in the bandwidth attribute. Thus, a bandwidth indicated in the bandwidth attribute indicates
10 an expected maximum bandwidth that is needed in order to obtain a smooth transmission.

According to a further embodiment, a request comprising a transport type-attribute and optionally a proposed bandwidth
15 will be rejected in case the bandwidth that is required for the type of transport indicated in the request is not available in the network. If so, the user equipment may include a different transport type-attribute in next request.

20 In an IMS-based IPTV solution, according to exemplary embodiments, the QoS (Quality of Service) may be ensured, e.g. as defined according to the TISpan RACS-architecture. The required signaling for linear TV and for Video-on-Demand are specified e.g. in TISpan-specification and in the OITF (Open
25 IPTV Forum)-specification.

The exemplary embodiments provide a tie between content downloading and content uploading and the above mentioned QoS-mechanisms provided e.g. by IMS/RACS, in order to ensure that a
30 minimum transmission speed is available to support an uninterrupted viewing of media content during downloading, e.g. of the types progressive downloading, streaming downloading, and adaptive streaming downloading.

Thus, according to an embodiment of the invention, the above-mentioned transfer type-attribute is included in an SDP Offer for content download, in order to set-up the policies specifically for the content download. This attribute enables a flexibility to control the local policies in IMS/RACS, such as e.g. to reserve bandwidth, to add a BGF (Border Gateway Function) in the path, or to select an appropriate priority in the access network. The RACS policies are set-up e.g. according to the standardized SPDF (Service-based Policy Decision Function).

Typically, the transport type for HTTP-content downloading is determined by the user equipment, based on the action of the end-user and the configuration of the user equipment. If the user selects a content to be viewed, and the user equipment is not configured to store the content, the content will be retrieved from the content server using streaming downloading of the content at the rate of play-out from the user equipment.

However, if the user equipment is configured to store the content, the content will be retrieved from the content server using progressive downloading, i.e. the content is stored or buffered in the user equipment, and played-out at the same time.

In adaptive streaming downloading, the end-user requests that the content shall be available as an adaptive stream, such that the content can be downloaded at different bitrates, according to a special scheme. For example, if the user equipment detects that the buffer is becoming empty, it may assume that there is a lack of bandwidth for a higher bit rate stream, and shift to a lower downloading bit rate.

As described above, the conventional HTTP content downloading is a best-effort type of transmission, and the speed of the

downloading is limited by the available bandwidth. However, in order to achieve a differentiation between the different types of content downloading and content uploading, a transfer type-attribute is included in the initial request from the user

5 equipment, according to embodiments of the invention.

The different types of content downloading are differentiated with a slightly higher QoS than the best effort QoS, since the best effort QoS has no minimum transmission requirement.

10 As stated above, the described concepts are not only applicable for downloading but could be used for uploading, e.g. of user-generated content. The uploaded content may be subsequently shared with other users using downloading, and will therefore
15 require a consistent transfer.

The figure 1a is a block diagram illustrating an exemplary IMS IPTV-architecture and the applicable protocols in IMS IPTV, i.e. the SIP (Session Initiation Protocol) and the HTTP (Hypertext
20 Transfer Protocol), for downloading media from a content server to a UE, or uploading media content to the content server. The architecture comprises an OITF-enabled UE 1, an IMS Gateway 2, an IMS Media Server or Video-on-Demand pump, as indicated by the IMS/RACS-circle 3 in the figure, an IPTV Controller 4, and a
25 Content Server 5 comprising a Media Control Function (MCF). The IPTV Controller 4 may comprise e.g. an IPTV Application Platform (IAP), as defined in the OpenIPTV Forum.

Figure 1b is a block diagram schematically illustrating an OITF-
30 enabled User Equipment 1, comprising functionality for the Declarative Application Environment (DAE), as defined in Open IPTV Forum-specification, as well as a local object code, the DAE comprising the browser of the UE.

More specifically, in an exemplary UE-initiated unicast content downloading session, an originating UE generates an initial INVITE-Request. The Request-URI (Uniform Resource Identifier) contains a downloading-content URI in a unicast locator, as well
5 as in a TO-header, said identifier being retrieved from service selection information. Further, a FROM-header indicates the public user identity of the user.

An SDP Offer is included in the INVITE Request, in accordance
10 with the media capabilities and the required bandwidth available for the content download session.

Thus, an exemplary typical SDP Offer at media level may include e.g. the following elements:

- 15 - An "m=" line for an HTTP download, e.g. of the format:
m=<media> <port> <transport> <fmt>:, with the media field having a value of "application", the port field being set to a value of 9, which is the discard port, and the transport field being set to TCP. Further, an fmt-parameter is included, and set to
20 *iptv_http*, resulting in "m=application 9 tcp *iptv_http*".
- An "a=setup" attribute set to "active", e.g. a=setup: active.
- An "a=connection" attribute set as "new", e.g.
a=connection:new.
- A "c=" line included in the network type with the value set to
25 IN, the address type set to IP4 or IP6, and IP address of the flow of the related HTTP channel, e.g. c=IN IP4 <IP_ADDRESS>).

According to an embodiment of the invention, a "b=" line of the SDP Offer may optionally contain a bandwidth attribute
30 indicating a proposed bandwidth. If the user has fetched the bandwidth required for this particular content delivery channel during a service selection procedure, the bandwidth attribute at media level is set in the "b=" line to this value, e.g.
b=AS:15000.

Accordingly, the MCF (Media Control Function) of the Content Server will receive an SDP Offer, via the IPTV controller, that may contain a transfer type-attribute, as well as bandwidth attribute indicating a proposed bandwidth (in a "b=" line). The MCF of the Content Server will assist the IPTV controller in preparing the content for downloading or uploading, and copy a received transfer type-attribute into an SDP Answer, which is forwarded to the IPTV controller.

Additionally, according to exemplary embodiments of the invention, as described above, the type of content downloading is indicated in the initial INVITE-request, e.g. by a transfer type-attribute contained in the SDP Offer, such as a "fmt:iptv_http transfer-type" attribute. According to a first embodiment of the invention, the values that are applicable for the transfer type-attribute are "progressive", and "streaming" and "adaptive".

The "progressive" content downloading-type indicates content that is viewed during download, and the content is stored or buffered in the UE, requiring a comparatively large bandwidth.

The "streaming" content downloading type, e.g. HTTP streaming, indicates content that is viewed without storing, or with a limited buffering in the UE, similar to RTSP streaming.

The "adaptive" content downloading type, e.g. HTTP adaptive streaming, indicates content that may be viewed at different bandwidth and with different quality.

The "b=" line is an optional bandwidth attribute, and indicates the bandwidth for the best quality streaming.

According to further exemplary embodiments, various other values of the transfer-type attribute could be used to indicate other proprietary types of content downloading, e.g. a=fmtp:iptv_http transfer-type = <transfer-type>.

5

Figure 2a and 2b show a signaling diagram illustrating an exemplary signaling sequence for a User Equipment 1 acting as a client terminal in an IMS IPTV-architecture. The figures illustrate the User Equipment downloading media content from a Content Server 5, the downloading involving a bandwidth reservation, according to embodiments of this invention. The figures also illustrate the logical units that may be involved.

The UE (OITF)-box 1 indicates an OITF-enabled User Equipment, comprising functionality for the Declarative Application Environment (DAE), as defined in Open IPTV Forum, as well as a local object code (LOC). Further, the IG-box 2 corresponds to an IMS Gateway, the IMS/RACS-box 3 corresponding to an IMS Media Server or a Video-on-Demand pump, and the IPTV Controller 4 comprises an IPTV Application Platform (IAP). The Content Server 5 comprises a Media Controller Function (MCF).

In the signal S11 in figure 2a, the UE 1 initiates a downloading session, which is created in signal S12. In signal S13, a SIP INVITE is forwarded from the IMS Gateway 2 to the IMS Media Server 3, and further, in signal S15, forwarded to the IPTV Controller 4, the SIP INVITE including an SDP (Session Description Protocol)-Offer, and the content is prepared for downloading, in step 16, by the IPTV Controller 4 and the Content Server 5.

In the preceding step 14, the policies for downloading are checked and applied by the IMS/RACS, and a bandwidth reservation may be performed. This involves that the network topology in the

access network is checked by the RACS in order to determine if the bandwidth required by the transport-type indicated in the SDP Offer of the SIP INVITE is available. If so, the bandwidth is reserved, and the SIP INVITE will be forwarded to the IPTV Controller, in signal S15. However, if the required bandwidth is not available, the SIP INVITE will be rejected, and not forwarded to the IPTV Controller. When the IPTV Controller receives a non-rejected SIP INVITE, the content will be prepared for downloading, in the above-mentioned step 16.

Next, in signal S17, the IPTV Controller will respond with an SDP answer, as well as with the URL to the session, which is forwarded to the IMS Gateway, in signal S19, and the bandwidth reservation is confirmed, in the preceding step 18. Thereafter, the session is created, in signal S20. The UE uses the received session URL for downloading the content from the Content Server 5, in signals S21, S22 and S23 in figure 2b. In signals S24 - S30, the downloading session is terminated, including a release of network resources, in step 26, and eventually, in signals S31 and S32, the downloaded content is played-out.

The above described figures 2a and 2b illustrate a downloading session. However, a similar signaling procedure may be used for an uploading session.

Other exemplary embodiments are directed to plain IPTV in a non-IMS network, using other protocols, e.g. the SOAP (Simple Object Access Protocol) or the DIAMETER-protocol, instead of the SIP.

Thus, the figures 2c and 2d illustrate exemplary signalling diagrams for a plain IPTV-architecture, with no IMS Gateway, using the SOAP, and having an RACS interface 3 to the IPTV Controller 4. In signal S110 in figure 2c, the UE 1 initiates a downloading session, which is created in signal S120. In signal

S130, the IPTV Controller issues a SOAP reserve bandwidth to the RACS interface. If the reservation is confirmed, in step 140, a SOAP response is sent to the IPTV controller, in signal S150. In step 160, the IPTV Controller prepares the content for
5 downloading, and the session is created, in signal S170.

The UE uses a received session URL for downloading the content from the Content Server 5, in signals S180, S190 and S200 in figure 2d. In signals S210 - S260, the downloading session is
10 terminated, including a release of network resources, in step 230, and eventually, in signals S270 and S280, the downloaded content is played-out.

Figure 3 is a flow diagram schematically illustrating a method
15 for a User Equipment of setting up a policy for uploading or downloading of media content, according to embodiments of the invention. In step 35, the UE generates a request indicating the type of content downloading or content uploading, and transmits the request to the IPTV controlling node, in step 36. According
20 to a further embodiment, the policy is a bandwidth reservation, and the type is indicated by a transport type-attribute included in an SDP Offer of the initial request. According to a still further embodiment, the transfer type-attribute has one of the values "progressive", "streaming" or "adaptive", as defined
25 above. The steps 35 and 36 in figure 3, when directed to downloading, basically correspond to the signals S11 - S15 in figure 2a.

Figure 4 is a flow diagram schematically illustrating a method
30 for an IPTV Controlling Node of setting up a policy for uploading or downloading of media content, according to embodiments of the invention. In step 41, the IPTV Controlling node receives a request from the UE, the request indicating the type of content downloading or content uploading. In step 42,

the IPTV controlling node copies the type of downloading or uploading in an SDP answer, via the MCF (Media Control Function) of the content server. According to a further embodiment, the policy is a bandwidth reservation, which is set-up according to an expected transmission speed, based on the type of content downloading or uploading, as indicated by the transport type-attribute included in an SDP Offer of the initial request received from the UE in the above-mentioned step 41. According to a still further embodiment, the value of the transfer type-attribute is e.g. progressive, streaming or adaptive.

Figure 5 is a block diagram illustrating a User Equipment 1, according to embodiments of the invention. The UE 1 is e.g. an OITF-enabled mobile phone, a PC, or a TV, comprising a suitable user interface, and it is provided with processor circuits and appropriate software e.g. corresponding to a Declarative Application Environment (DAE), as defined in Open IPTV Forum, as well as a local object code. The software is further configured to perform the method according to embodiments of the present invention. The UE is also provided with a conventional communication device 51, comprising a transmitter, a receiver and processing circuits 52, in order to communicate with IPTV Controller, e.g. via an IMS Gateway and an IMS Media Server. According to an exemplary embodiment, the UE generates and transmits a request including an SDP Offer indicating the type of content downloading and/or content uploading.

Figure 6 is a block diagram illustrating an exemplary IPTV controlling node 4, comprising an IPTV Application Platform (IAP). The IPTV controlling node is further provided with a communication device 61, comprising a transmitter, a receiver and processing circuits 62, and by means of the communication device and other appropriate hardware and software, the IPTV controlling node is configured to receive a request indicating

the type of content download or content upload from a UE, e.g. in a transfer type-attribute included in an SDP Offer. According to a further embodiment, the communication device is configured to copy the transfer type attribute into an SDP answer, via the MCF (Media Control Function) contained in the content server. According to a preferred embodiment, the policy is a bandwidth reservation, and the IPTV controlling node is arranged to set-up the session with a bandwidth according to an expected transmission speed, based on a received transfer type-attribute.

The entities and units described above with reference to the figures 5 and 6 are logical units, which do not necessarily correspond to separate physical units.

Thus, according to embodiments of a method for a User Equipment directed to **downloading** of media content, the User Equipment 1 sets up a policy for downloading IPTV-content from a server by generating a request comprising an indication of the content downloading-type, and transmitting the request to an IPTV-controller 4.

According to exemplary embodiments, the policy is a bandwidth reservation, and the content download-type is indicated by a standardized transfer type-attribute, e.g. progressive, which denotes a progressive downloading, streaming, which denotes a streaming downloading, or adaptive, which denotes an adaptive streaming downloading.

According to further exemplary embodiments, the IPTV is IMS-based, and the indication of the content download type is contained in an SDP Offer included in the request. Further, the SDP Offer may comprise a bandwidth attribute indicating a proposed bandwidth.

According to a still further embodiment, the User Equipment will receive a rejection of the request, if the bandwidth required for the transport-type indicated by the transport type-attribute is not available, and the User Equipment may generate a request comprising a different transport type-attribute upon receiving the rejection.

According to embodiments of a similar method for a User Equipment directed to **uploading**, the User Equipment 1 sets up a policy for uploading IPTV-content to a server, by generating a request comprising an indication of the content uploading-type, and transmitting the request to an IPTV-controller 4.

According to further exemplary embodiments, the policy is a bandwidth reservation, which is set up according to an expected transmission speed, and the content uploading-type is indicated by a standardized transfer type-attribute, e.g. "progressive", "streaming" or "adaptive", the attributes denoting a progressive uploading, a streaming uploading, and an adaptive streaming uploading, respectively.

According to other exemplary embodiments, the IPTV is IMS-based, and the indication of the content uploading-type is contained in an SDP Offer included in the request. Further, the SDP Offer may comprise a bandwidth attribute indicating a proposed bandwidth.

According to a still further embodiment, the User Equipment will receive a rejection of the request, if the bandwidth required for the transport-type indicated by the transport type-attribute is not available, and the User Equipment may generate a request comprising a different transport type-attribute upon receiving the rejection.

A User Equipment communicates with an IPTV-controlling node in order to set up the policies for uploading and downloading.

According to embodiments of a method for an IPTV controlling node 4 directed to **downloading**, the IPTV-controlling node 4 sets up a policy for downloading IPTV-content from the content server 5 to a User Equipment 1, the IPTV controller receiving a request from the User Equipment, the request comprising an indication of the of content download-type.

10 According to further exemplary embodiments, the policy is a bandwidth reservation, which is set up by the IPTV controlling node 4 according to an expected transmission speed, based on the received indication of the type of content downloading. Said content downloading-type is indicated by a standardized transfer
15 type-attribute, e.g. "progressive", "streaming" or "adaptive", the attributes denoting progressive uploading, streaming uploading, and an adaptive streaming uploading, respectively.

According to still other embodiments, the IPTV is IMS-based, and
20 the indication of the content download type is contained in an SDP Offer included in the request received from the UE. Further, the SDP Offer may comprise a bandwidth attribute indicating a proposed bandwidth, and the indication of the content download type may be copied into an SDP answer.

25 According to embodiments of a method for an IPTV controlling node directed to **uploading**, the IPTV-controlling node 4 sets up a policy for uploading IPTV-content from a UE 1 to a content server 5, the IPTV controller receiving a request from the User
30 Equipment, the request comprising an indication of the content uploading-type.

According to exemplary embodiments, the policy is a bandwidth reservation, which is set-up according to an expected

transmission speed, based on the received indication of the type of content uploading. Said content uploading-type is indicated by a standardized transfer type-attribute, e.g. "progressive", "streaming", or "adaptive", the attributes denoting a

5 progressive uploading, a streaming uploading, and an adaptive streaming uploading, respectively.

According to further exemplary embodiments, the IPTV is IMS-based, and the indication of the content uploading-type is
10 contained in an SDP Offer included in the request. Further, the SDP Offer comprises a bandwidth attribute indicating a proposed bandwidth, and the indication of the content upload type is copied into an SDP answer.

15 According to embodiments of a User Equipment 1, the UE is arranged to set up a policy for **downloading** IPTV-content from a content server 5, the User Equipment comprising a communication device 61 provided with processing circuits 62, and is configured to generate a request comprising an indication of the
20 content downloading-type, and transmit the request to an IPTV-controlling node 4.

Additionally, according to embodiments of a User Equipment, the User Equipment 1 is arranged to set up a policy for **uploading**
25 IPTV-content to a server 5, the User Equipment comprising a communication device 61 provided with processing circuits 62, and is configured to generate a request comprising an indication of the content uploading-type, and transmit the request to an IPTV-controlling node.

30 Thus, a User Equipment according to the invention is preferably arranged to set up policies for both downloading and uploading, but may alternatively be arranged to set up policies for either downloading or uploading.

According to further exemplary embodiments of said User Equipment, the policy is a bandwidth reservation, and the content downloading type and/or the content uploading-type is indicated by a standardized transfer type-attribute, e.g. "progressive", "streaming", or "adaptive", the attributes denoting a progressive uploading, a streaming uploading, and an adaptive streaming uploading, respectively.

According to still further exemplary embodiments, the IPTV is IMS-based, and the indication of the transfer type attribute is contained in an SDP Offer included in the request. Additionally, the SDP Offer further comprises a proposed bandwidth, and the UE is OITF-enabled.

Similarly as regarding the above-described exemplary methods, a User Equipment is configured to communicate with an IPTV-controlling node for setting up the policies for uploading and downloading. According to embodiments of an IPTV-controlling node 4, the IPTV-controlling node 4 is arranged to set up a policy for **downloading** IPTV-content from a content server 5 to a User Equipment 1, the IPTV-controlling node comprising a communication device 51 provided with processing circuits 52, and is configured to receive a request from the User Equipment, the request comprising an indication of the content downloading-type.

Additionally, according to embodiments of an IPTV-controlling node 4, the IPTV controlling node is arranged to set up a policy for **uploading** IPTV-content from a content server 5 to a User Equipment 1, said node comprising a communication device 51 provided with processing circuits 52, and is configured to receive a request from the User Equipment, the request comprising an indication of the content uploading-type.

According to another exemplary embodiment, the policy is a bandwidth reservation, and the IPTV controlling node is arranged to set up the bandwidth reservation according to an expected
5 transmission speed, based on the received indication of type of content downloading and/or content uploading. Said content downloading-type and/or content uploading-type is indicated by a standardized transfer type-attribute, e.g. "progressive", "streaming", or "adaptive", the attributes denoting a
10 progressive uploading, a streaming uploading, and an adaptive streaming uploading, respectively

According to still further exemplary embodiments, the IPTV is IMS-based, and the transfer-type attribute is contained in an
15 SDP Offer included in the request, the SDP Offer further comprising a proposed bandwidth.

The IPTV-controlling node may be further arranged to copy a received indication of the content uploading-type and/or the
20 content downloading-type into an SDP answer, via the MCF of the content server.

Thus, an IPTV-Controlling node according to the embodiments is preferably arranged to set up policies for both downloading and
25 uploading, but may alternatively be arranged to set up policies for either downloading or uploading.

As further described in connection with the figures 2c and 2d, exemplary embodiments are applicable to a non-IMS network, e.g.
30 in so-called plain or traditional IPTV. However, in case of a non-IMS network, a separate protocol, similar to the SIP, is required in order to create a session, with the backend to allocate and de-allocate the bandwidth, e.g. the SOAP or the DIAMETER-protocol. Alternatively, a new HTTP header could be

added, with a proposed bandwidth and the transfer type included, or the information could be encapsulated in a HTTP Request URI, without requiring any separate protocol.

5 Furthermore, the above mentioned and described embodiments are only given as examples and should not be limiting to the present invention. Other solutions, uses, objectives, and functions within the scope of the invention as claimed in the accompanying patent claims should be apparent for the person skilled in the
10 art.

ABBREVIATIONS

OITF = Open IPTV Forum

SDP = Session Descriptive Protocol

15 MCF = Media Control Function

IAP = IPTV Application Platform

RACS = Resource and Admission Control Sub-system

SPDF = Service-based Policy Decision Function

DAE = Declarative Application Environment

20 QoS = Quality of Service

URI = Uniform Resource Identifier

SOAP = Simple Object Access Protocol

HTTP = Hypertext Transfer Protocol

SIP = Session Initiation Protocol

Claims

1. A method for a User Equipment (1) of setting up a policy for downloading IPTV-content from a Content Server (5), or a
5 policy for uploading IPTV-content to a Content Server (5), the method comprising:
 - generating (31) a request comprising an indication of the type of content downloading or content uploading, and
 - transmitting (32) the request to an IPTV-controlling node
10 (4).
2. A method according to claim 1, wherein the policy is a bandwidth reservation.
- 15 3. A method according to claim 1 or 2, wherein the type of content downloading or content uploading is indicated by a transfer type-attribute.
- 20 4. A method according to claim 3, wherein the transfer type-attribute has one of the values progressive, streaming or adaptive.
5. A method according to any of the preceding claims, wherein the IPTV is IMS-based, and the transfer type-attribute is
25 contained in an SDP Offer included in the request.
6. A method according to claim 5, wherein the SDP Offer further comprises a proposed bandwidth.
- 30 7. A method according to any of the claims 2 - 6, further comprising the User Equipment receiving a rejection of the request, if the bandwidth required by the transport type-attribute is not available.

8. A method according to claim 7, comprising generating a request containing a different transport type-attribute, if a rejection is received.

5 9. A method for an IPTV-controlling node (4) of setting up a policy for downloading IPTV-content from a Content Server (5) to a User Equipment (1), or uploading IPTV-content to a Content Server (5) from a User Equipment (1), the method comprising:

10 - receiving (41) a request from the User Equipment, the request comprising an indication of the type of content downloading or content uploading.

10. A method according to claim 9, wherein the type of content
15 downloading or content uploading is indicated by a transfer type-attribute.

11. A method according to claim 9 or 10, wherein the policy is a bandwidth reservation, which is set up according to an
20 expected transmission speed, based on the type of content downloading or content uploading.

12. A method according to claim 10 or 11, further comprising:
- copying (42) the transfer type-attribute from an SDP Offer
25 included in the request, into an SDP answer included in a response, via an MCF (Media Control Function) of the Content Server (5).

13. A User Equipment (1) arranged to set up a policy for
30 downloading IPTV-content from a Content Server (5), and/or uploading IPTV-content to a Content Server (5), the User Equipment comprising a communication device (51) provided with processing circuits (52), and being configured to:

- generate a request comprising an indication of the type of content downloading and/or content uploading, and
- transmit the request to an IPTV-controlling node (4).

- 5 14. A UE according to claim 13, wherein the policy is a bandwidth reservation.
15. A UE according to claim 13 or 14, wherein the type of content downloading and/or content uploading is indicated by a
10 transfer type-attribute.
16. A UE according to claim 15, wherein the transfer type-attribute has one of the values progressive, streaming or adaptive.
15
17. A UE according to claim 15 or 16, wherein the IPTV is IMS-based and the transfer type-attribute is contained in an SDP Offer included in the request.
- 20 18. A UE according to claim 17, wherein the SDP Offer further comprises a proposed bandwidth.
19. An IPTV-controlling node (4) arranged to set up a policy for downloading IPTV-content from a Content Server (5) to a User
25 Equipment (1), and/or for uploading IPTV-content to a Content Server (5) from a User Equipment (1), the IPTV controlling node comprising a communication device (61) provided with processing circuits (62), and being configured to:
- receive a request from the User Equipment, the request
30 comprising an indication of the type of content downloading and/or content uploading.

20. An IPTV controlling node (4) according to claim 19, wherein the type of content downloading and/or content uploading is indicated by a transfer type-attribute
- 5 21. An IPTV controlling node according to claim 19 or 20, wherein the policy is bandwidth reservation, which is set up according to an expected transmission speed, based on the type of content downloading or content uploading.
- 10 22. An IPTV controlling node according to claim 20 or 21, further configured to copy the transfer type attribute from an SDP Offer included in the request into an SDP answer included in a response, via an MCF (Media Control Function) of the Content Server (5)