

VISUAL ANALYSER OF CONFINED PATHWAYS

5 **Field of the Invention**

[001] The present invention relates to an automatic visual analyser and in particular to a remote controlled automatic visual analyser.

[002] The invention has been developed primarily for use in remotely analysing confined pathways such as sewers and sewer access channels and will be described hereinafter
10 with reference to this application. However, it will be appreciated that the invention is not limited to this particular field of use.

Background of the Invention

[003] Investigation of confined pathways such as sewers and sewer access channels has
15 primarily consisted of a person entering down a manhole and descending a ladder mounted on the inner wall. The main reason for undertaking this action is to determine the state of the confined pathway, the integrity of the walls and whether there is any foreign material or other obstruction within the confined pathway.

[004] Therefore, people are being sent down into unknown environments with unknown
20 safety. The ladder could have rusted and readily collapse. The walls could be crumbling and therefore the ladder breaks away from the wall with the weight of the user. There could be hazardous environment or unsafe restrictions in the confined pathway that cause entrapment or injury.

[005] A light could be lowered into the confined pathway and the lit up inner surface
25 reviewed from above. However, this is limited in the effectiveness and depth and often there is a lack of perspective of depth. Further the viewer must dangerously overhang the top opening of the confined pathway which could result in slippage, or cause the opening to give way and cause debris to fall down on the light. Still further the

[006] A substantial limitation is that the supply of power is limited and any damage or
30 contact with water can cause failure of the light or possibility of electrocution to the operator.

[007] A camera could be lowered into the confined space but it is even more delicate than a light. Further control of a dangling camera is likely to swing into the walls of the confined pathway and cause entanglement on crevices or other protrusions or damage by contact.

5 [008] Further it is generally required that the camera needs to work without a light or be low resolution as

[009] Still further due to any pendulum effect it is not known what is the location of what can be seen by any suspended camera. When more than 10 metres down, a small suspension angle deviation angle at the top will effect a large lateral deviation below. This will increase at depth increases. Therefore, it is not known if you are close to wall or the
10 confined space has widened or narrowed. Substantial important information is not known. Therefore, the confined pathway remains an unknown danger risk or status risk.

[0010] Overall, these limitations means that the requirement for repair, deblocking, flushing or other treatment cannot be determined.

15 [0011] A lot of these problems are amplified when any camera engages water. The same operation at the top of the confined pathway will cause a different effect in the water at a lower position in the confined pathway. For example, the pendulum effect will have a damper element due to the drag of the water. This even further reduces the chance of interpreting what is visible by the camera and where it is.

20 [0012] A functional limitation is that copper wire is the usual usage for power and for data transfer. This severely limits any capability and therefore deep confined spaces cannot be viewed clearly and even shorter confined spaces cannot carry high resolution.

[0013] It can be seen that the known prior art has the problems of:

- a) It is unknown what type of dangerous environment is present
- b) It places operators at risk
- 25 c) It is not possible to survey deep confined pathway in detail,
- d) It is not possible to coordinate camera, lighting, and power for deep confined pathway
- e) Limitations of camera, lighting, and power means it is not possible to undertake high definition
- 30 f) There is no knowledge of clearly determining what is viewable or where it is viewable.

- g) There is no capability of use of high definition in deep and multi-fluid confined pathways.

[0014] The present invention seeks to provide an automatic visual analyser, which will overcome or substantially ameliorate at least one or more of the deficiencies of the prior art, or to at least provide an alternative.

[0015] It is to be understood that, if any prior art information is referred to herein, such reference does not constitute an admission that the information forms part of the common general knowledge in the art, in Australia or any other country.

10 Summary of the Invention

[0016] According to a first aspect of the present invention, there is provided An automatic visual analyser, for remotely analysing confined pathways such as sewers and sewer access channels, comprising a viewing body having a plurality of cameras mounted thereon in fixed related directions to allow a defined directional scan of the confined pathway; a drive line for providing a directional path along the confined pathway by which the viewing body can be driven, at least one communication system connected to the body and/or drive line for control communication of the viewing body and communication with the plurality of cameras; at least one controller for transmitting or receiving communication from the at least one communication system allowing the communication to be transmitted or received external of the confined pathways being analysed.

[0017] The automatic visual analyser can include a 3D generator for generating a digital representation of the confined pathway by the overlap known directional scans by the plurality of cameras mounted on the viewing body in fixed related directions.

[0018] The confined pathway is substantially in the range of 0.5 metres to 5 metres. The depth can be 60 metres.

[0019] The drive line preferably is a tether for a vertical gravity driven feed. This drive line can be wound in a depth spool for release of controlled lengths of tether to alter the depth of the viewing body on the tether and further includes a depth spool controller for controlling the release of the controlled lengths of tether.

[0020] The drive line can include a stabiliser for stabilising the released controlled lengths of tether to stabilise the orientation of the tether and the viewing body. The stabiliser in one form includes a momentum wheel damper unit for damping the vertical

torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit. This momentum wheel damper unit can include a flywheel, spun up to roughly 3000+rpm by a brushless DC motor (BLDC), allowing rotation in the X and Y plane, by servo motors, to impart reaction torques on the body for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.

[0021] The plurality of cameras are mounted on the viewing body in fixed related directions are mounted coplanar in a direction normal to the directional path of the driveline. The number of the plurality of cameras, are dependent on the relative location and the coplanar field of view (HFOV) of the lens of the plurality of cameras.

[0022] Each of the number of the plurality of cameras have a related light mounted adjacent on the viewing body. Preferably the mount of each related light mounted adjacent on the viewing body includes an adjustable means allowing the camera and light to substantially align with the camera line of sight. The mount can include an adjustable bracket allowing the camera and light to substantially pre-align to intersect the camera's line of sight at the required focus distance in the confined pathway.

[0023] The required focus distance in the confined pathway is related to the diametrical dimension of the wall of the confined pathway.

[0024] The automatic visual analyser can include a combination of a pressure sensor and a single point lidar in the directional path of the drive line which can be used to accurately tag the video feeds/images of the plurality of cameras and the true position within the confined pathway.

[0025] The invention also provides a method of visual analysis of confined pathways such as sewers and sewer access channels including the steps of:

- a) Providing a viewing body having a plurality of cameras mounted thereon in fixed related directions to allow a defined directional scan of the confined pathway automatic visual analyser
- b) Feeding the viewing body along a directional path in the confined pathway;
- c) Coordinating the plurality of cameras and respective lights to focus at required focus length through a triangulation of direction of camera to respective light;
- d) Coordinating other sensors with the cameras to provide a scanned image of confined pathway at known location.

[0026] The method can include using Lidars in parallel coordination with the plurality of cameras to allow a coordinated overlap of the scanned images from the camera and the Lidars.

5 [0027] Preferably the method includes using coordinated focus of cameras and respective lighting by a triangulated directional mounting of each camera and its respective light.

[0028] The power to the viewing body having a plurality of cameras can be by a staged power supply and allowing operation of the viewing body having a plurality of cameras at low voltage.

10 [0029] To control pendulum sway the method can include a stabiliser for stabilising the released controlled lengths of tether to stabilise the orientation of the tether and the viewing body. The stabiliser in one form can include a momentum wheel damper unit for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.

15 [0030] Other aspects of the invention are also disclosed.

Brief Description of the Drawings

[0031] Notwithstanding any other forms which may fall within the scope of the present invention, a preferred embodiment of the invention will now be described, by way of
20 example only, with reference to the accompanying drawings in which:

Fig. 1 is a diagrammatic overview of an automatic visual analyser for remotely analysing confined pathways such as sewers and sewer access channels in accordance with a preferred embodiment of the present invention;

25 Fig. 2 is a diagrammatic side view of a viewing body of the automatic visual analyser of Fig 1;

Fig 3 is a diagrammatic underneath perspective view of the viewing body of the automatic visual analyser of Fig 1;

Fig. 4 is a diagrammatic exploded view of the viewing body of the automatic visual analyser of Fig 1;

30 Figs 5, 6 and 7 are functional box diagrams of the components of an embodiment of an automatic visual analyser such as in Fig 1 showing the manhole unit (confined pathway unit), surface control unit (controller) and detail of the momentum wheel damper unit of Fig 5.

Fig 8 is a diagrammatic view of a method of visual analysis of confined pathways such as sewers and sewer access channels in accordance with a preferred embodiment of the present invention.

5 Figs 9, 10 and 11 are diagrammatic views of a complete view, an exploded view and a detail view of an embodiment of a momentum wheel damper unit in the form of a stabiliser 81 which uses control moment gyroscope to generate a momentum vector with direction control

Fig 12 is a diagrammatic view of a further form of the automatic visual analyser showing its modularity with attachability of other cameras

10 Fig 13 is a further exploded diagrammatic view of a still further form of automatic visual analyser showing its modularity and attachability of other working modules such as arms with working claws.

Fig 14 is a diagrammatic view of the detail of the visual analyser in location in a manhole having consistent spacing of lights, camera and Lidar to effect the triangulation field of view FOV and focus to allow the 3D imaging and location of
15 image in confined spaces.

Description of Preferred Embodiments

[0032] It should be noted in the following description that like or the same reference
20 numerals in different embodiments denote the same or similar features.

[0033] Referring to the drawings there is shown one form the invention which provides an automatic visual analyser 11, for remotely analysing confined pathways 15 such as sewers and sewer access channels.

25 [0034] The automatic visual analyser 11 comprises a viewing body 21, a drive line 24 being a tether, and a control and communication system 62, and power input 63 connected by the tether to the viewing body 21.

[0035] The viewing body 21 has a barrel section 22 with a plurality of cameras 31 mounted thereon in fixed related directions to allow a defined directional scan of the confined pathway. At a lower end of the barrel 22 is a bell skirt 23 which extends
30 outwardly with a greater diameter than the barrel 22 and the plurality of cameras 31 so as to be the most outer part of the viewing body 21 and provide protection from side engagements with the wall of the confined pathway 15.

[0036] The drive line 24 in one form is a tether for providing a vertical directional path along the confined pathway 15 by which the viewing body 21 can be driven by gravity.

[0037] The communication system is connected to the viewing body 21 by the drive line 24 for control communication of the viewing body and communication with the plurality of cameras. At least one controller for transmitting or receiving communication from the at least one communication system allowing the communication to be transmitted or received external of the confined pathways being analysed

[0038] Camera System:

10 [0039] Cameras 31 can be 180° view cameras. The objective of camera 31 placement is to make sure that the area of focus is a short distance such as 2 metres from the camera. This is to ensure the best quality image is captured. Although focus on 0.5 to 2 metres is planned the cameras will capture objects that are further away than 2 metres such as up to 5 metres.

15 [0040] The benefit of use of a monoscopic camera is that it can be digitally controlled and provide a wide-angle image such as a 180° hemispherical view. Further the images can be more readily digitally knitted together. This is particularly beneficial in providing a panoramic view at a predetermined focused distance or at a predetermined focusing time.

[0041] However, cameras to be used can be "wide angle" to the extent that they cover 20 90° to 180°. This will provide an outward hemispherical viewing angle so that the cameras can sit flat on the body of the submersible and look along the body as well as outwardly. Therefore, the camera is proud of the surface of the body but the degree of proudness is limited so as to avoid overly affecting the aerodynamics and contact points of the body. The cameras therefore extend within the footprint of the bell skirt of the body such that 25 the skirt minimizes any contact with the cameras.

[0042] Referring to Fig 1 there are shown monoscopic wide angle cameras 31. The camera 31 is mounted in respective covering optically transparent dome body and arranged for viewing throughout the entire 180° view. Each camera is located at the same diametric planar cross section at an angular 90° to each relative to the central axis of the 30 barrel of the viewing body. This ensures scanned viewing of a complete 360 degree view from only a short distance from the outer surface of the barrel 22.

[0043] There can be at least one optical device controller connector for controlling particular input of the plurality of cameras for upload to a computerised means so that there can be operational control of the cameras.

5 [0044] Cameras are located in two main locations. The main cameras 31 are mounted in the planar arrangement around the barrel 22 of the body and normal to axis of the barrel. The second location is on the underneath part of the bell skirt and facing inline to direction of travel along directional path provided by the tether 24. This camera is therefore an inline camera 32.

10 [0045] The spacing of the cameras 31 around the barrel circumference is dependent on the diameter of the circumference and the tangential effect of the 180° cameras. It is **needed to minimize “optical dead spots” by ensuring the tangential line of one camera to the other.**

[0046] In the disclosed embodiment there are 4 x standard wide angle lens cameras (UHD 4K), positioned at 90deg increments around the body of the viewing body. This
15 **Produces “360deg” vision of the entirety of a manhole** environment, with good overlap between each camera allowing for post-process stitching of the images (image mosaic creation).

[0047] The horizontal field of view (HFOV) of the lens should be proportional to the diameter of the manhole that you are working in. Smaller manholes require larger HFOV,
20 in order to still achieve satisfactory overlap between cameras. The wide angle also allows an operator to view underneath ledges.

[0048] The 1 x bottom inline camera 32 is a wide angle 4K camera. This camera captures the detail in the bottom-facing “inline” direction, to allow an operator to observe obstacles in the tunnel, or see the manhole bottom.

25 [0049] By having the cameras aligned in linear circumferential arrangement there is a physical fixed relationship between the cameras. To take advantage of this linear alignment it is also necessary to obtain time alignment or synchronicity.

[0050] Synchronicity can be achieved by the method of providing a location fixed relative location of a plurality of cameras. This is particularly provided by the
30 circumferential array of cameras 31 on the barrel 22 of the viewing body 21. However, if the operation of the cameras are not coordinated then each camera on the viewing body

will be scanning at a different location than when the other cameras were operated. This would effectively be like having a random location of cameras 31 on the viewing body 21.

[0051] It is therefore important to have synchronicity of operation of cameras 31. This cannot be achieved simply by logic switches as there is too great a variation of operation
5 due to physical limitations of electronic switching.

[0052] In operation there is the providing of control signal operation to each of the location fixed relative locations of a plurality of cameras and then each camera separately upon receipt of control signal checking with global clock. In the provided control signal operation, a time control point will be predefined.

10 [0053] Each camera can separately undertake the control action at the next predetermined particular time control point and results in images are provided that are with a fixed relative location and with a fixed relative synchronised time and thereby in allowing knitting of images with a fixed relative location and with a substantially relative synchronised time.

15 [0054] As all cameras 31 are not acting based on the time they are control instructed but instead on a particular control time point. Therefore if there is an inherent relay delay to a camera it is not affected as long as the time control point is larger than the delay and as long as each camera control, connected to the global clock. In this way synchronicity is within a +/- 4 millisecond variation.

20 [0055] This results in the knitting of images of the scans provided by the relatively located and simultaneously time operated control of the outwardly viewing multiple cameras 31 in the planar cross sectional arrangement of the barrel of the viewing body 21. In particular this can allow for providing a localised panorama formed by the optical cameras locating an object or the lack of an object in a predefined focused distance from
25 the viewing body and allowing the localised panorama for use in creating an interlinked panorama by the network of cameras.

[0056] A navigation system can be provided by this relativised panorama formed by the optical cameras locating an object or the lack of an object in a predefined focused distance from the elongated body and within a calculated time and or distance from the
30 viewing body locating an object or the lack of an object in a predefined focused distance from the elongated body allowing the localised panorama.

[0057] Housing

[0058] Housing is designed to be robust and rugged in the hazardous environments expected to be encountered within the manhole or vertical shaft. The main hull of the visual analyser is fully sealed, such that there is no transfer of fluid or gas between the
5 visual analyser housing and the environment.

[0059] In one form the housing comprises:

- a) Anodized aluminium, or other corrosion resistant material, is used to ensure robustness in the environments listed.
- 10 b) A ported pressure sensor is used, which allows the main hull of the visual analyser to remain fully sealed, whilst also allowing the detection of ambient pressure (and therefore depth). The diaphragm of the sensor is exposed, without exposing the internals.
- c) All penetrations are potted, or sealed by O-ring or other means, to ensure no transfer of fluid/gas between internal and external.

15

[0060] Lighting System:

[0061] For cameras 31 to operate they require controlled lighting. This control must be a control of direction, intensity and avoiding interference with the cameras 31 ability to scan images without interfering dispersed light. One each of a plurality of LEDs
20 is relatively in line with each camera 31, to ensure illuminating of the subject that the respective camera is viewing.

[0062] The lights are angled so that there is a triangulation of the focus of the light intersecting with the focus of the camera at the required distance from the viewing body. This provides the benefit that the camera is operating in coordination with its respective
25 light.

[0063] In a physical location of each camera 31 and its respective LED light 51 there must in reality be a spacing on the barrel 22 of the viewing body. Therefore, this angularity overcomes the It provides the benefit that the camera can operate in the central prime emanation of the light and not in a variable unknown fringe of the emanated light.

30 [0064] The lights can be adjustable so that the mount includes an adjustable bracket allowing the camera and light to substantially align with the **camera's** line of sight. This

allows the adjustment to be done prior to deployment. Preferably the adjustable bracket of the mount allows an adjustment up to 20° left to right and can allow an adjustment up to 30° in elevation. Therefore, the mount adjustable bracket allows the camera and light to substantially pre-aligned with the user's **line of sight to a required focus distance in the** water.

[0065] The LEDs 51 are also adjustable in brightness to adapt to different lighting conditions in the confined space or different fluid media such as a transition from air to water in a sewer.

10 360 Point Cloud:

[0066] As well as visual image cameras 31 the viewing body includes other light viewing technologies including Lidar, being a remote sensing method that uses light in the form of a pulsed laser to measure ranges. As shown in Figs 3 and 4 the viewing body includes two types of Lidar – a 360°Lidar 41 and a single point Lidar 43.

15 [0067] The 360 deg Lidar 43 is mounted coaxially with the axis of the barrel 22 of the viewing body 21 so that it provides a 360 since it is mounted underneath the bell skirt 23 of the viewing body the 360 degree Lidar and the plurality of cameras 31 are operating in parallel planes but will not interfere with each other due to the shadow of the bell skirt. Therefore an interaction of the data from each of these sources strengthens accuracy and eliminated discrepancies.

[0068] The 360 deg Lidar can be used to generate a 3D digital representation of the manhole, which can then be overlaid on the 360 deg camera feeds. The combination of visual image and point cloud can help to provide greater detail of tunnel features, whilst also maintaining context of the scene because of the overlaid images.

25 [0069] The single point Lidar being a downward facing Lidar forms an inline Lidar 43 that operates in the directional path provided by the drive line of the tether 24. This single point Lidar can be used in synergistic combination with the inline camera 32 and other sensors.

30 [0070] Power Supply

[0071] Streaming over distances between the remote-control location above ground and the viewing body 21 tethered is achieved by use of fibre optic cabling. This allows

the length of operation to be extended far beyond anything available to traditional copper methods. However, that distance therefore creates problems that need to be overcome. This includes the dramatic loss of power over distances, the functionality, and the importance in not hindering use in an already confined pathway below the surface.

- 5 [0072] The power supply needs to operate in the tether together with the transfer of controls and the transfer of scanned viewed imagery. The electronics collects the data from the visual image capture and is connectable by connection 12 to transfer the data to a operator computer or remote station 11.

[0073] Multiple power supplies are used:

- 10 • 48V to 12V step-down and 48V to other low voltage step-down inside splitter box in the viewing body to various elements operating in the viewing body.

[0074] As shown in Figs 6 and 7, the power system 14 for allowing the controllable use of the camera system mounted on the viewing body is connected by power line in the tether 12 to the tether spool connector to the above ground power supply.

15

[0075] Hybrid Tether:

[0076] The hybrid tether used is a OM3 multimode fibre optic cable (2 cores), allow for very high data throughput (10gbit) over extended distances (300m) - greater than that offered by traditional copper-based solutions.

- 20 [0077] The fibre cable carries data - commands sent from surface to viewing body, video and sensor feeds, and any other comms - from the surface computer to the viewing body unit. Ethernet to fibre converter on surface carries the ethernet protocol data over fibre to the viewing body, where it is converted back into ethernet via a fibre to ethernet converter. This connects into the viewing body onboard computer and 360 lidar in a local
25 network configuration.

[0078] 2-core 12awg copper cable, used to carry 48V DC from the surface down to the viewing body unit, to power the various power supplies (that step down the voltage for each respective subsystem of the unit)

- 30 [0079] Surface spool:

[0080] The surface spool 25 holds the entirety of the hybrid tether 24, and allows for easy deployment of the unit in the field. The tether spool 25 has ethernet and power connectors on the outside, which are fixed in the centre of the spool. 48V comes into the

spool, goes through a built-in slip ring and then feeds through the hybrid tether. The Ethernet cable also goes through slip ring and into an ethernet to fibre converter, which then feeds into the same hybrid tether from above (as fibre optic cable).

[0081] The slip ring mentioned above allows the spool and tether to rotate freely, without tangling the rest of the cables that are attached from the surface (ethernet and power). Hence, this slip ring is a critical aspect in allowing the efficient operation of the viewing body unit.

[0082] Controlled deployment via automated tether spooling system and sensor feedback has in one form:

- 10 a) Automated tether deployment (i.e. digital spool driven by motor) is important because any human intervention (e.g. manual lowering of Visual analyser) could introduce disturbance, which would thus cause swing and twist of the unit.
- b) Sensor feedback (from sensors like atmospheric pressure, range-to-bottom lidar, inertial measurement units (IMU), cable counter) allows the system to
15 automatically adjust for detected swing, twist, and account/counteract it by manipulation of the momentum wheel inside the Visual analyser unit, or spooling speed of the digital spool.
- c) The unit must be lowered consistently in order to prevent sudden changes in acceleration/jerk, which would introduce swing. At larger depths, this is
20 exacerbated, as the system acts like a heavy weight on a pendulum string.

Momentum Wheel Damper Unit:

[0083] As shown in Figs 4, 5 and 8 the viewing body 21 includes a stabiliser 81 for stabilising the released controlled lengths of tether 25 to stabilise the orientation of the tether and the viewing body. The stabiliser 81 includes a momentum wheel damper unit for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.

[0084] The momentum wheel damper unit includes a flywheel, spun up to roughly 3000+rpm by a brushless DC motor (BLDC), allowing rotation in the X and Y plane, by servo motors, to impart reaction torques on the body for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.

[0085] These reaction torque can be accurately controlled by an algorithm to assist in canceling and torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.

[0086] Referring to Figs 9, 10 and 11 there is shown a momentum wheel damper unit in the form of a stabiliser 81 uses control moment gyroscope to generate a momentum vector with direction control, in order to offset the angular momentum generated by natural means through the deployment of the visual analyser down a vertical shaft.

[0087] Natural disturbances can be introduced to the system, which cause swing and twist, from means such as wind or human intervention. The control moment gyroscope can be used to counteract these natural disturbances. This is controlled algorithmically, and will utilise feedback from the onboard sensors, such as pressure, IMU, cable counter, etc.

[0088] The stabiliser 81 comprises a rotating weighted flywheel 82 mounted on a first platform 83 which is pivotally mounted on larger circumventing second platform 84 which is mounted pivotally on arms 87 mounted on base 87 to form a U-shaped frame.

[0089] The flywheel is able to spin in a plane parallel to the plane of the first platform, which in one stationary position could be coplanar with the second platform and can be selectively orthogonal to the base but coplanar with the arms of the U-shaped frame.

[0090] The flywheel rotation can have an rotational dampening effect in X-Y directions and thereby stabilising the visual analyser to the vertical tether line. This is achieved by by controlling drive and controlling the relative rotation of the first platform to the second platform and to the U-shaped frame.

[0091] The interaction of the main components is facilitated by the mounting of the flywheel 82 by central spinning mount 91 on spinning axial spigot 92 located centrally on the top of the first frame 83. This frame is pivotally mounted by first opposing proud rotating mounts 93 fitting within first circular receiving mount openings 94 at corresponding inner sides of the second frame 84. This allows pivoting around the axis between the first receiving mounts 94. The second frame is mounted to the U-shaped frame by second opposing proud rotating mounts 96 fitting within second circular receiving mount openings 97 at corresponding inner sides of the upright spaced arms 97 of the U-shaped frame. second frame 84. This allows pivoting around the axis between the second receiving mounts 97 which is orthogonal to the pivoting around the axis

between the first receiving mounts 94. Thereby allowing X-Y axial control of the rotational dampening by the flywheel. Drivers 95 and 98 can drive the pivoting rotation.

Auxiliary Sensors:

5 [0092] The automatic visual analyser 11 can include other sensors which act in synergistic operation. These sensors can be mounted on or in the viewing body 21.

[0093] In one form shown in the embodiments is a bottom-facing single point lidar acting as an inline Lidar 43 to **provide 'range to bottom' data**, and to allow the operator to know the range to obstacles below the unit, or to the bottom of the manhole.

10 [0094] A pressure sensor can be mounted on the viewing body to measure depth from surface of the manhole. This is particularly advantageous in depths of water where pressure from top surface of the water can be calculated. However it is also of substantial benefit in deep confined pathways where atmospheric pressure differences are readily detected. Interlacing this sensed pressure with other sensors or scanned images will
15 provide a synergistic substantial increase in accuracy and assist in eliminating discrepancies caused by variable environments at different levels in the confined pathway.

[0095] Another sensor used in combination can be an Inertial measurement unit, or IMU, used to provide linear acceleration, angular velocity, and heading to magnetic North.
20 This data can be used to help obtain a direction within the manhole, which can be overlaid into the video feeds - providing directional context for the operator.

[0096] The IMU also feeds into the control algorithm for the pendulum motion damping of the momentum wheel damper unit. This assists in keeping the viewing body stationary in the XY plane during descent, and prevent rotation that may be imparted on the tether
25 from the surface.

[0097] Combination of pressure sensor and single point lidar can be used to accurately tag the video feeds/images to the true position within the manhole. When placing into the backend, this data is used to generate a true-to-reality digital replica of the manhole.

30 [0098] As shown in Fig 14 the visual analyser in location in a manhole has consistent spacing of light 51, camera 31 and Lidar 41 to effect the triangulation field of view FOV

and focus to allow the 3D imaging and location of image in confined spaces. As the confined spacing in a manhole can be only in the range of .5 to 10 m

[0099] It is important that there are two forms of detection and image analysis. Primarily it is the cameras and the lidar at spaced locations and acting at different angles to each other such that a triangulation location and focusing is used and allows analysis. However other sensors and cameras can be used and mounted on the visual analyser such as the different form of camera 107 mounted vertically from the below the Lidar as shown in Fig 12 and 13.

10 [00100] Flexible Form and Shape and Modularity

[00101] Therefore as shown in particular in Figs 12 and 13 compared to Figs 1 to 4 the visual analyser is NOT confined to some specific form, in order to achieve function. Cylindrical designs, box designs, spherical designs, would all suffice, as long as the relationship of LIDAR 41 to camera 31 to lighting is maintained.

15 [00102] In the modularity structure one form can have:

- a) 'Hamburger' style modularity whereby the Visual analyser can be separated into layers, which can be swapped out and modified, with a common interface line going between each layer, to allow any configuration desired.
- b) Each module is self-contained, in that it takes a universal power input and communication input, and handles internally any voltage regulation (step-up or step-down) and communication interfacing.
- c) This modularity allows for the addition or removal of sensor payloads, to cater for different applications.
- d) Daisy chaining of power and communication interface between modules.

25 [00103] Looking at modular comparison of Figs 12 and 13, In Fig 12 there is the barrel 22 including the barrel top, that houses the cameras 31 and lights above 51 and any eyebrows or shading therebetween, and is connected to a stabilising frustoconical barrel skirt 23 carrying other payload but including downward lidar 43 and cameras 32 and lights 52 for steering control as the tether 24 is extended. Within this payload can be the
30 Momentum Wheel Damper Unit 71. Connected centrally and axially beneath the barrel 52 and barrel skirt 53 is the 360 degree Lidar 41 and to which can also be attached other accessories like a further elongated camera 107.

[00104] However as shown in Fig 13 the body housing shaping does not need to have a stabilising shape as the Momentum Wheel Damper Unit can provide the active stabilisation. This also allows for protruding working arms 105 and attached working claws 106 to be available for use while maintaining full stabilising control so as to be able
5 effect the required visual analysis.

[00105] Therefore the body of the visual analyser of Fig 13 can be generally cylindrical and include different active elements which are connected in modular form. However as detailed it is important to have the consistent spacing of light 51, camera 31 and Lidar 41 to effect the triangulation field of view.

10 [00106] In the structure of Fig 13 there is the hamburger layering of modules of the head or lid module 101 covering the top of the upper torso module 102 from which extends outwardly and controllably working arms 105 and working claws 106. This module connects to the mid torso module 103 that has the set of cameras 31 spaced circumferentially around so as to ensure vision at any one segment of the 360 degree
15 view. A closing lower torso module 104 which can include other payload and other auxiliary sensors closes the bottom of the substantial cylindrical barrel body. Underneath and connected centrally and axially beneath the barrel 52 and barrel skirt 53 is the 360 degree Lidar 41 and to which can also be attached other accessories like a further elongated camera 107. By ensuring that modules are fitted in the right order, have a defined height
20 and are consistently spaced to the Lidar 41 below there is consistent and controllable triangulation for effective visual analysis and recordal in real time at determinable known fixed positions

[00107] Live data collection / visualization

25 [00108] Live generation of the manhole through point cloud is achieved with the visual analyser of the invention and with visual image/video overlay.

[00109] Virtual reality (VR) environment allows for manipulation and inspection of the **“world” in real time. Tagging and flagging points of interest** during a live deployment of Visual analyser. Live visualisation allows operators to focus on points of interest in real-
30 time, where the Visual analyser can be stopped to allow focus to be placed on this POI - for denser point cloud of higher resolution imagery. This allows an operator to perform an equivalent virtual inspection, as if they had gone in the manhole themselves. Different RGB lighting can be used to enhance visibility of certain features within an environment.

Interpretation

Embodiments:

[00110] Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, **appearances of the phrases “in one embodiment” or “in an embodiment”** in various places throughout this specification are not necessarily all referring to the same embodiment, but may. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner, as would be apparent to one of ordinary skill in the art from this disclosure, in one or more embodiments.

[00111] Similarly it should be appreciated that in the above description of example embodiments of the invention, various features of the invention are sometimes grouped together in a single embodiment, figure, or description thereof for the purpose of streamlining the disclosure and aiding in the understanding of one or more of the various inventive aspects. This method of disclosure, however, is not to be interpreted as reflecting an intention that the claimed invention requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed embodiment. Thus, the claims following the Detailed Description of Specific Embodiments are hereby expressly incorporated into this Detailed Description of Specific Embodiments, with each claim standing on its own as a separate embodiment of this invention.

[00112] Furthermore, while some embodiments described herein include some but not other features included in other embodiments, combinations of features of different embodiments are meant to be within the scope of the invention, and form different embodiments, as would be understood by those in the art. For example, in the following claims, any of the claimed embodiments can be used in any combination.

Different Instances of Objects

[00113] As used herein, unless otherwise specified the use of the ordinal adjectives “first”, “second”, “third”, etc., to describe a common object, merely indicate that different instances of like objects are being referred to, and are not intended to imply that the objects so described must be in a given sequence, either temporally, spatially, in ranking, or in any other manner.

Specific Details

[00114] In the description provided herein, numerous specific details are set forth. However, it is understood that embodiments of the invention may be practiced without these specific details. In other instances, well-known methods, structures and techniques have not been shown in detail in order not to obscure an understanding of this description.

Terminology

[00115] In describing the preferred embodiment of the invention illustrated in the drawings, specific terminology will be resorted to for the sake of clarity. However, the invention is not intended to be limited to the specific terms so selected, and it is to be understood that each specific term includes all technical equivalents which operate in a similar manner to accomplish a similar technical purpose. Terms such as "forward", "rearward", "radially", "peripherally", "upwardly", "downwardly", and the like are used as words of convenience to provide reference points and are not to be construed as limiting terms.

Comprising and Including

[00116] In the claims which follow and in the preceding description of the invention, except where the context requires otherwise due to express language or necessary implication, the word "comprise" or variations such as "comprises" or "comprising" are used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

[00117] Any one of the terms: including or which includes or that includes as used herein is also an open term that also means including at least the elements/features that follow the term, but not excluding others. Thus, including is synonymous with and means comprising.

Scope of Invention

[00118] Thus, while there has been described what are believed to be the preferred embodiments of the invention, those skilled in the art will recognize that other and further modifications may be made thereto without departing from the spirit of the invention, and it is intended to claim all such changes and modifications as fall within the scope of the

invention. For example, any formulas given above are merely representative of procedures that may be used. Functionality may be added or deleted from the block diagrams and operations may be interchanged among functional blocks. Steps may be added or deleted to methods described within the scope of the present invention.

5

[00119] Although the invention has been described with reference to specific examples, it will be appreciated by those skilled in the art that the invention may be embodied in many other forms.

10 **Industrial Applicability**

[00120] It is apparent from the above, that the arrangements described are applicable to the for remotely analysing confined pathways such as sewers and sewer access channels industries.

Claims

The claims defining the invention are as follows:

1. An automatic visual analyser, for remotely analysing confined pathways such as sewers and sewer access channels, comprising
 - 5 a. A viewing body having a plurality of cameras mounted thereon in fixed related directions to allow a defined directional scan of the confined pathway;
 - b. A drive line for providing a directional path along the confined pathway by which the viewing body can be driven
 - 10 c. At least one communication system connected to the body and/or drive line for control communication of the viewing body and communication with the plurality of cameras;
 - d. At least one controller for transmitting or receiving communication from the at least one communication system allowing the communication to be
 - 15 transmitted or received external of the confined pathways being analysed.
2. An automatic visual analyser according to claim 1 including a lidar wherein the lidar and the plurality of cameras are at fixed predetermined spacing to enable
3. An automatic visual analyser according to claim 1 or 2 including a 3D generator for generating a digital representation of the confined pathway by the overlap
- 20 known directional scans by the plurality of cameras mounted on the viewing body in fixed related directions.
4. An automatic visual analyser according to any one of the preceding claims wherein the confined pathway is substantially in the range of 0.5 metres to 10 metres.
5. An automatic visual analyser according to claim 1 wherein the drive line is a tether
- 25 for a vertical gravity driven feed.
6. An automatic visual analyser according to claim 5 wherein the drive line includes a depth spool for release of controlled lengths of tether to alter the depth of the viewing body on the tether and further includes a depth spool controller for controlling the release of the controlled lengths of tether.

7. An automatic visual analyser according to any one of the preceding claims wherein the drive line includes a stabiliser for stabilising the released controlled lengths of tether to stabilise the orientation of the tether and the viewing body.
- 5 8. An automatic visual analyser according to claim 7 wherein the stabiliser includes a momentum wheel damper unit for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.
9. An automatic visual analyser according to claim 7 or 8 wherein the stabiliser includes a momentum wheel damper unit having a flywheel, and pivoting first and second mounts allowing selectable orientation in variable X and Y plane to effect
10 stabilising rotational dampening relative to that plane.
10. An automatic visual analyser according to claim 9 wherein the momentum wheel damper unit includes a flywheel, spun up to roughly 3000+rpm by a brushless DC motor (BLDC), allowing rotation in the X and Y plane, by servo motors, to impart reaction torques on the body for damping the vertical torques (or swing) generated
15 on the viewing body, due to the pendulum-like nature of the entire unit.
11. An automatic visual analyser according to any one of the preceding claims wherein the plurality of cameras mounted on the viewing body in fixed related directions are mounted coplanar in a direction normal to the directional path of the driveline.
12. An automatic visual analyser according to claim 11 wherein the number of the
20 plurality of cameras, the relative location and the coplanar field of view (HFOV) of the lens of the plurality of cameras
13. An automatic visual analyser according to claim 11 or 12 wherein the number of the plurality of cameras each have a related light mounted adjacent on the viewing body.
- 25 14. An automatic visual analyser according to any one of the preceding claims including a plurality of different active elements which are connected in modular form.
15. An automatic visual analyser according to claim 14 wherein the selection and connection of modules provides a consistent spacing of light, camera and Lidar to
30 effect a predefined triangulation field of view.
16. An automatic visual analyser according to claim 14 or 15 wherein the mount of each related light mounted adjacent on the viewing body includes an adjustable

means allowing the camera and light to substantially align with the camera line of sight.

- 5 17. An automatic visual analyser according to claims 16 wherein the mount includes an adjustable bracket allowing the camera and light to substantially pre-align to intersect the camera's line of sight at the required focus distance in the confined pathway.
18. An automatic visual analyser according to claims 17 wherein the required focus distance in the confined pathway is the wall of the confined pathway.
- 10 19. An automatic visual analyser according to any one of the preceding claims including a combination of a pressure sensor and a single point lidar in the directional path of the drive line which can be used to accurately tag the video feeds/images of the plurality of cameras and the true position within the confined pathway.
- 15 20. A method of visual analysis of confined pathways such as sewers and sewer access channels including the steps of:
- a. Providing a viewing body having a plurality of cameras mounted thereon in fixed related directions to allow a defined directional scan of the confined pathway automatic visual analyser
 - b. Feeding the viewing body along a directional path in the confined pathway;
 - 20 c. Coordinating the plurality of cameras and respective lights to focus at required focus length through a triangulation of direction of camera to respective light;
 - d. Coordinating other sensors with the cameras to provide a scanned image of confined pathway at known location.
- 25 21. A method of visual analysis of confined pathways according to claim 20 including using Lidars in parallel coordination with the plurality of cameras to allow a coordinated overlap of the scanned images from the camera and the Lidars.
- 30 22. A method of visual analysis of confined pathways according to claim 20 or 21 including using coordinated focus of cameras and respective lighting by a triangulated directional mounting of each camera and its respective light.

23. A method of visual analysis of confined pathways according to claim 20, 21 or 22 including providing power to the viewing body having a plurality of cameras by a staged power supply and allowing operation of the viewing body having a plurality of cameras at low voltage.
- 5 24. A method of visual analysis of confined pathways according to any one of the claims 20 to 23 including controlling pendulum sway by a stabiliser for stabilising the released controlled lengths of tether to stabilise the orientation of the tether and the viewing body.
- 10 25. A method of visual analysis of confined pathways according to any one of the claims 20 to 23 wherein the stabiliser includes a momentum wheel damper unit for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit.
26. An automatic visual analyser, for remotely analysing confined pathways such as sewers and sewer access channels, comprising
- 15 a. A viewing body having
- i. a substantially a hazardous preventing structure preventing environmental, explosive or
- ii. a modular structure for allowing variable configurations including one module for
- 20 iii. a plurality of cameras mounted thereon in fixed related directions to allow a defined directional scan of the confined pathway;
- b. A drive line comprising an extendable tether for providing a directional path along a substantially vertical confined pathway by which the viewing body can be driven
- 25 c. A powering system connected to the tether allowing for supply of power in an controlled step up or stepped down configuration
- d. At least one communication system
- i. connected to the body and/or drive line for control communication of the viewing body and communication with the plurality of cameras;

- ii. able to transmit and receive communication from the at least one communication system allowing the communication to be transmitted or received external of the confined pathways being analysed.
- e. An active stabiliser including
 - 5 i. a momentum wheel damper unit for damping the vertical torques (or swing) generated on the viewing body, due to the pendulum-like nature of the entire unit
 - ii. and including pivoting first and second mounts allowing selectable orientation in variable X and Y plane to effect stabilising rotational
 - 10 dampening relative to that plane.