

Recording Medium,
Method of Configuring Control Information Thereof,
Recording and/or Reproducing Method Using the Same,
5 and Apparatus Thereof

Technical Field

The present invention relates to a method of recording control information on a recording medium, such as recordable optical disc having at least one recording layer, and more particularly, 10 to a method in which record velocity information and write strategy parameters are included in the disc control information. Also, this invention relates to a method of recording or reproducing data on or from the recording medium 15 using the writing speed information

Background Art

A high density optical recording medium, known as HD-DVD, is widely used to record and store high-definition video data, 20 large amount program data, and high-quality audio data and so one. The Blu-ray disc represents next-generation HD-DVD technology.

Technological specifications are now being established for the global standardization of the Blu-ray disc, including standards are for the write-once Blu-ray disc (BD-WO). Meanwhile, a rewritable Blu-ray disc, known as the 1x-speed BD-RE and now being discussed, should be compatible with BD-RE discs expected to have higher writing speeds, i.e., the 2x-speed BD-RE and beyond. BD-WO specifications for high recording velocity are also in progress. Efficient solutions for coping with the high writing speed of a high-density optical disc are urgently needed, and the specifications established should ensure mutual compatibility.

Disclosure of Invention

Accordingly, the present invention is directed to an optical disc control information recording method that substantially obviates one or more problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a method of recording disc control information as specified information corresponding to a plurality of recording velocities, by which recording velocity information is included in the disc control information so that the recording and reproducing of an optical

disc can be performed based on prerecorded disc information.

Another object of the present invention is to provide a data structure for configuring disc control information.

Another object of the present invention is to provide a method
5 of recording, in a specific area of an optical disc, disc control information corresponding to a plurality of recording velocities, by which information for specific recording velocities per recording layer is recorded in a specific sequence, to provide mutual compatibility between like-based
10 discs.

Another object of the present invention is to provide a recording and reproducing method and apparatus thereof, by which user data can be recorded on and reproduced from an optical disc using prerecorded disc control information.

15 Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other
20 advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these objects and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, a data structure according to the present invention includes a recording speed information
5 including a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the maximum or minimum recording speed, and a fourth information indicating a basic recording speed.

10 In another aspect of the present invention, in configuring disc control information within a management area of an optical disc, a method of recording the disc control information of the optical disc includes the step of recording a plurality of recording speed information and a plurality of write strategies
15 respectively associated with corresponding recording speeds within the disc control information wherein one of the recording speed information is a basic recording speed information.

In another aspect of the present invention, a method of
20 recording data on an optical recording medium includes the step of recording a speed information on a specific area of the optical recording medium, wherein the speed information

comprises a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the maximum or minimum recording speed, and a fourth information indicating a basic recording speed.

In another aspect of the present invention, a method of recording/reproducing data on/from an optical recording medium includes the steps of reading a speed information from a specific area of the optical recording medium wherein the speed information comprises a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the maximum or minimum recording speed, and a fourth information indicating a basic recording speed and recording data on a main data area of the optical recording medium based on the read speed information.

In another aspect of the present invention, a recording medium having a recording speed information is characterized in that the recording speed information comprises a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the

maximum or minimum recording speed, and a fourth information indicating a basic recording speed.

In another aspect of the present invention, an optical disc includes at least one recording layer provided with a recordable area and a recording-disabled or prerecorded area, wherein disc control information is separately recorded within the prerecorded area per the recording layer and wherein a plurality of recording speed information and a plurality of write strategies associated with corresponding recording speeds are recorded within the disc control information, and wherein one of the recording speed information is a basic recording speed information.

In another aspect of the present invention, an optical disc recording method includes the steps of if an optical disc having at least one recording layer is loaded, reading disc control information written within a management area of the optical disc and reading to store a plurality of recording speed information and write strategies respectively fitting corresponding recording speeds recorded within a predetermined area of the disc control information each, deciding the recording speed to be applied to each section of the optical disc by referring to a plurality of the stored speed

information and the write strategies, and performing a recording at the decided recording speed.

In another aspect of the present invention, an optical disc record playback apparatus includes a control unit delivering a recording command and a record playback unit receiving the
5 recording command, the record playback unit performing a recording in a manner of reading disc control information recorded within a management area of an optical disc, deciding a recording speed for performing the recording command on a
10 specific area by reading a maximum recording speed information, a minimum recording speed information, a basic recording speed information, a predetermined speed information different from the maximum or minimum recording speed information at least, and a write strategy fitting the corresponding recording speed,
15 and performing the recording using the write strategy fitting the decided recording speed.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are
20 intended to provide further explanation of the invention as claimed.

Brief Description of Drawings

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate
5 embodiment(s) of the invention and together with the description serve to explain the principle of the invention.

In the drawings:

FIG. 1 is a diagram of a single-layer disc applicable to the present invention;

10 FIG. 2 is a diagram of a dual-layer disc applicable to the present invention;

FIG. 3 is a diagram of a management area where disc control information of the present invention is recorded, in which a format of recording the disc information in a corresponding
15 area is schematically shown;

FIGS. 4A to 4C are diagrams of disc information recorded according to a first embodiment of the present invention;

FIGS. 5A and 5B are diagrams of a disc recording method according to the first embodiment of the present invention;

20 FIGS. 6A to 6C are diagrams of recording disc information according to a second embodiment of the present invention;

FIGS. 7A to 7D are diagrams of recording disc information

according to a third embodiment of the present invention; and
FIG. 8 is a block diagram of an optical disc recording and
reproducing apparatus using disc control information according
to the present invention.

5

Best Mode for Carrying Out the Invention

Reference will now be made in detail to the preferred
embodiments of the present invention, examples of which are
illustrated in the accompanying drawings. Wherever possible,
10 the same reference numbers will be used throughout the drawings
to refer to the same or like parts.

A Blu-ray disc is taken as an example of an optical disc
according to the present invention. Yet, the concept of the
present invention, characterized in an optical disc having its
15 disc control information recorded thereon, is applicable to
DVD-RAM, DVD-RW, DVD+RW, DVD-R, DVD+R, and similar such discs.

Although the terminology used herein is well known for the most
part, some terms have been chosen by the applicant, such that
the present invention should be understood with the intended
20 meanings of the terminology as used by the applicant. For
example, the "disc control information" of a disc is recorded
in a specified area, i.e., a recordable area of the disc or a

prerecorded area (sometimes known as an embossed areamanufacturer, in which manufacturer data is recorded and where no further recording is possible), and includes information necessary for the playback of a recorded disc.

5 Disc control information is called "disc information" or "DI" in relation to Blu-ray disc technology but is typically referred to as "physical format information" for DVD-RAM, DVD-RW, DVD+RW, DVD-R, and DVD+R discs. Hence, it should be apparent that the technical background of the present invention
10 is equally applicable to physical format information.

Moreover, the disc information according to the present invention is recorded as an unspecified unit of information, which may be counted, for example, as a first or second information.

15 FIGS. 1 and 2 illustrate the structure of optical discs according to the present invention, in which any recordable optical disc may be applicable to the present invention. The recordable disc may be, for example, a rewritable optical disc or a write-once optical disc.

20 Referring to FIG. 1, illustrating an optical disc having one recording layer, a lead-in area is provided as a management area on an inner circumference area of an optical disc, whereas

a lead-out area is provided as a management area on an outer circumference area of the optical disc. In the inner circumference area, a pre-recorded area and a rewritable (or write-once) area are provided separately. In BD-RE and BD-WO technology, the pre-recorded area is called the PIC area, where permanent information and control data is recorded, and disc information is recorded in the PIC area. A data area is made up of a user data area where user data is recorded and inner and outer spare areas ISA and OSA, which are used in the replacement of the data of a defective area. In the case of a BD-WO disc, a temporary defect management area (TDMA) is provided for recording information of a defect and for general management. The TDMA is unnecessary in the case of BD-RE discs, which have a corresponding area designated as reserved.

The present invention intends to provide a method of recording disc information (DI) as disc control information required for recording and/or reproducing of a disc in a pre-recorded or recordable are. It is apparent that a recording method in the pre-record area is differently applied to each kind of disc.

In the case of BD-RE and BD-WO discs, the pre-recorded area is the PIC area recorded using a bi-phased, high-frequency modulated signal reproduced according to a specific playback

method, to acquire the disc information.

FIG. 2 illustrates an optical disc having dual recording layers, in which an inner circumference area of the disc has a lead-in of a first recording layer (Layer 0) corresponding to a lead-out of a second recording layer (Layer 1). In this case, one PIC area is provided in each of the lead-in and lead-out areas, and the same disc information is recorded in each PIC area.

FIG. 3 illustrates a PIC area formatted according to the present invention. In configuring the disc information of the PIC area of a BD-RE or BD-WO disc, the minimum recording unit is one cluster, 544 clusters constitute one fragment as one upper record unit, and five fragments make up the PIC area. Disc information is recorded in a front head cluster of a first fragment IF0. The disc information is plurally recorded per recording layer and recording velocity permitted by the corresponding optical disc. One disc information includes 112 bytes, sometimes referred to as a DI frame. To cope with a loss of disc information, the same contents of the disc information are repeatedly recorded in each front head cluster of the remainder of the fragments.

Information representing the corresponding recording layer, information representing recording velocity, and write strategy

information corresponding to the recording velocity are included in each disc information. Such information is utilized in recording and reproducing the optical disc, to provide optimal recording power per recording layer and per
5 recording velocity.

The disc information of the present invention is characterized in providing specific recording velocity information supported by the disc and associated write strategy information, and more specifically, in providing specific recording velocity
10 supported for each recording layer and associated write strategy information via a specified method for discs having a plurality of recording layers.

The specific configuration of the disc information is for a Blu-ray disc, which may differ from the configuration of a DVD-based disc. Specifically, the recording DI volume for a
15 Blu-ray disc is 112 bytes or equivalent. By formulating the disc information of the same recording layer as one information, i.e., without repeating any common information, the write strategy configuration may differ per recording velocity.

20 In addition to a method of recording specific parameters of the write strategy, a medium property of an optical disc is generally modified by applying a laser beam to a recording

layer thereof via a pickup to perform recording. To do so, the laser beam's signal strength (recording power) and duration should be determined. Such information associated with recording is generally referred to as write strategy (WS) parameters for achieving a specific "write strategy."

FIGS. 4A-4C and 5A & 5B illustrate a first embodiment of the present invention of recording disc control information, in which various recording velocities to cope with high speed are grouped into one recording velocity group to be recorded.

The first embodiment of the present invention relates to a recording method of disc information coping with high speed, a method of recording data on an optical disc, and the like, and more particularly, to an advantageous method in coping with a constant angular velocity (CAV) system applicable to a high-speed disc. The present invention is not limited, however, to a CAV system.

In the CAV system, a disc is rotated at a constant speed such that the disc's inner and outer circumferences each have a rotational velocity corresponding to the length of the applied radius. For a Blu-ray disc, the velocity of the outer circumference is about 2.4 times greater than that of the inner circumference. Accordingly, if, for example, the recording on

the inner circumference using a CAV system is performed at 1x-speed or 4x-speed, the outer circumference recording has to be performed at about 2.4x-speed or 9.6x-speed, respectively, and conversely, a 6x-speed recording on the outer circumference means that the inner circumference recording has to be performed at about 2.5x-speed. In other words, adoption of the CAV system requires a velocity differential between the disc's inner and outer circumferences, so that an optimal recording velocity and write strategy must be selected for recording according to the applicable disc location. Moreover, such information should be provided as specified disc information to utilize the optimal recording velocity and write strategy (WS) in a corresponding system.

FIG. 4A shows one embodiment of recording disc information by an optical disc control according to the present invention, in which a disc information structure is schematically illustrated. Referring to FIG. 4A, each disc information sequence is determined by a sequence number and is recorded using one byte. For instance, the information is recorded in a fifth byte (i.e., the "DI frame sequence number in DI block," which can be represented as 00h, 01h, 02h, 03h, 04h, 05h, 06h, or 07h) of the disc information, where a fifth byte of 00h or 07h

indicates a first or eighth disc information, respectively.
In another meaning, the byte (e.g., 5th byte) deciding the
sequence of the disc information can be defined to mean not
only the sequence but also an applicable recording velocity in
5 a specific recording layer. For instance, '00h' means 1x speed
disc information of a first recording layer, '01h' means 1x
speed disc information of a second recording layer, and the
like.

Moreover, in a specific area within the disc information,
10 recording velocity information designated by the corresponding
disc information and write strategy (WS) coping with the
corresponding recording velocity are written in a previously
promised specific location. For instance, the recording
velocity information of the corresponding disc information is
15 written in Nth~(N+4)th bytes and the write strategy (WS) coping
with the corresponding recording velocity is written in
Mth~111th bytes.

Specifically, the present invention is characterized in
providing disc information coping with high recording velocity,
20 the recording velocity information and write strategy (WS) are
written for each of a plurality of recording velocity
information, namely, an optimal recording velocity V_{nom}, a

maximum recording velocity V_{max} , a minimum recording velocity V_{min} , and an intermediate recording velocity V_{int} .

At optimal recording velocity, the basic recording speed information is written, and a basic recording speed generally
5 starts at 2x-speed in a high-speed disc. As an applicable recording speed increases, so does the basic recording speed.

At maximum recording velocity, information associated with maximum recording velocity applicable by a corresponding disc is written. At minimum recording velocity, information
10 associated with recording speed found by dividing the maximum recording velocity applicable by the corresponding disc by '2.4' is written. At intermediate recording velocity, information associated with recording speed found by multiplying the minimum recording velocity by '1.7' is written.

15 A relation of determining recording velocity values of the maximum, minimum, and intermediate recording velocities is decided for convenience of explanation by considering a radius ratio between inner and outer circumferences of BD applicable to the present invention. It is apparent that such a relation
20 can be variably applied to other kinds of discs and that the recording velocity values can be set to different values according to disc characteristics despite the same BD.

Relating to the optimal recording velocity (2x speed), the same information is preferably recorded in each disc information. Preferably, the maximum, minimum, and intermediate recording velocities are differently determined according to the maximum recording velocity value applicable by the corresponding disc information.

Moreover, it is able to set up the intermediate recording velocities plurally. The present invention is characterized in having at least one intermediate recording velocity. Hence, at least four recording velocity information are included in one disc information. The more the recording velocity information exist, the more advantageous it becomes for the system operation. Hence, by utilizing a recordable area within disc information to the maximum, many intermediate recording velocity information are preferably provided thereto.

FIG. 4B shows a specific recording method for disc information having a plurality of per recording velocity information according to the present invention like FIG. 4A, in which disc information is written while maintaining compatibility with 1x-speed BD-RE disc information under discussion and in which there exists one intermediate recording velocity information for example.

Three kinds of recording velocities such as optimal recording velocity (Vnom), maximum recording velocity (Vmax), and minimum recording velocity (Vmin) are written in 32nd~35th bytes within disc information according to a predetermined definition. Write power information as write strategy (WS) for each of the three kinds of recording velocities is recorded in 48th~71st bytes. A start time of a write pulse as another write strategy (WS) coping with each of the three kinds of recording velocities is recorded in 76th~84th bytes. A start time of an erase pulse as another write strategy (WS) coping with each of the three kinds of recording velocities is recorded in 89th~97th bytes.

In addition to the basic three kinds of recording velocities Vnom, Vmax, and Vmin, the present invention further records at least one information associated with the intermediate recording velocity Vint, which is recorded using a reserved area within disc information. For instance, the intermediate recording velocity is recorded in 19th byte according to a predetermined definition, write power information is recorded as write strategy (WS) coping with the intermediate recording velocity in total 8-bytes of 20th~23rd bytes and 44th~47th bytes, a start time of a write pulse as another write strategy (WS)

coping with the intermediate recording velocity is recorded in 99th~101st bytes, and a start time of an erase pulse as another write strategy (WS) coping with the intermediate recording velocity is recorded in 102nd~104th bytes.

5 As explained in the foregoing description, if a plurality of intermediate recording velocities are intended to be recorded, information associated with another intermediate recording velocity can be recorded in a reserved area within disc information as well.

10 FIG. 4C schematically shows disc information recorded in case of recording the disc information of FIG. 4A, and more particularly, in case of a dual layer having two recording layers. The same principle can be applied to a single layer having one recording layer.

15 For instance, when an optical disc needs three different recording velocity information per recording layer, six disc information corresponding to each recording velocity are required. Each disc information allocates to record a sequence number, recording velocity information corresponding to the
20 sequence number, and a write strategy (WS) in a predetermined area.

For instance, if recording velocities to be represented are 1x-

speed, 2x-speed, and 6x-speed, first, second, and third disc information mean the disc information for the first recording layer. The 1st disc information is 1x-speed disc information of the 1st recording layer and has a sequence number of '00h'. The
5 corresponding recording velocity and write strategy are recorded in a previously promised location, whereby the recording velocity information is recorded in Nth~(N+4)th bytes and the write strategy is recorded in Mth~111th bytes.

The 2nd disc information is 2x speed disc information of the 1st
10 recording layer and has a sequence number of '01h'. The corresponding recording velocity and write strategy are recorded in a previously promised location like the 1st disc information. The third disc information is 6x speed disc information of the 1st recording layer and has a sequence
15 number of '02h'. The corresponding recording velocity and write strategy are recorded in a previously promised location like the 1st or 2nd disc information.

Meanwhile, 4th to 6th disc information mean disc information for 2nd recording layer. The 4th disc information is 1x speed disc
20 information of the 2nd recording layer and has a sequence number of '03h'. The 5th disc information is 2x speed disc information of the 2nd recording layer and has a sequence

number of '04h'. The 6th disc information is 6x speed disc information of the 2nd recording layer and has a sequence number of '05h'. The corresponding recording velocity and write strategy of each of the 4th to 6th disc information are
5 recorded in the same location.

The first embodiment of the present invention shown in FIGS. 4A to 4C is described by taking an example of recording a plurality of the recording velocity information and per recording velocity write strategies (WS) within one disc
10 information. If necessary, one write strategy (WS), associated with specific recording velocity information, may be recorded in one disc information, and the remainder recorded in another disc information.

For instance, in case that four kinds of recording velocity
15 information are required, the disc information are needed four times more than those of the above-described embodiment of the present invention. Yet, the PIC area, as shown in FIG. 3, is an area sufficient for recording a multitude of 112-bytes disc information therein so that sufficiently large amount of disc
20 information can be recorded therein if necessary. Hence, if one write strategy (WS) is recorded within the disc information, it is advantageous in allocating more areas for recording

intermediate recording velocity therein.

On the contrary, it is possible to record information commonly recorded in each disc information as common information once and to change to record the per recording velocity write
5 strategies only.

FIG. 5A and FIG. 5B are diagrams of a recording method of performing a recording on an optical disc according to the first embodiment of the present invention. FIG. 5A relates to a case of using one intermediate recording velocity, and FIG.
10 5B shows an example of using at least two intermediate recording velocities.

Namely, once an optical disc is loaded in an optical record/playback unit, write strategies respectively associated with maximum recording velocity (V_{max}), minimum recording
15 velocity (V_{min}), and intermediate recording velocity (V_{int}) are read out as disc control information within the optical disc.

A recordable area between an inner circumference and an outer circumference is virtually divided into three sections. The maximum recording velocity (V_{max}), minimum recording velocity
20 (V_{min}), and intermediate recording velocity (V_{int}) are applied to an outer circumference area, an intermediate area, and an inner circumference area, respectively, to perform a recording

thereon. This means that the recording is performed by applying an appropriate recording velocity and write strategy (WS) associated with the corresponding recording velocity to a specific area, where the recording will be performed, to adjust
5 write power, write pulse timing, and the like.

For instance, if a maximum recording velocity applicable by a disc is 6x-speed, disc information associated with 6x speed is read out. In case that the maximum recording velocity (V_{max}) is 6x-speed, 2.5x-speed for a minimum recording velocity
10 ($V_{max}/2.4$) and 4.25x speed for an intermediate recording velocity ($1.7V_{min}$) are recorded within the disc information as well as write strategies for the respective recording velocities. A record/playback unit previously confirms the recording velocity and write strategy (WS), which will be
15 applied to a specific area where a recording will be performed, thereby enabling to quickly cope with the write strategy (WS) in performing the recording on the corresponding area and to reduce probability of error occurrence using the optimal recording velocity.

20 FIG. 5B schematically shows a method of performing a recording on an optical disc in case that a plurality of intermediate recording velocities are recorded within disc information. A

recordable area of an optical disc is virtually divided into a plurality of sections as many as a number of recording velocities within disc information except V_{nom} . Maximum recording velocity (V_{max}) and minimum recording velocity (V_{min}) are applied to an outer circumference area and an inner circumference area, respectively, to perform a recording thereon. An intermediate area of the disc is divided into areas as many as the number of the set intermediate recording velocities to apply the intermediate recording velocities V_{int-1} to V_{int-n} thereto, respectively. Thus, the corresponding recording is performed on the divided areas. Hence, an optimal recording velocity to the corresponding section is determined, whereby the recording is enabled using the determined write strategy (WS) per the corresponding decided recording velocity.

FIGS. 6A to 6C illustrate a second embodiment of the present invention of recording disc control information, in which recording velocity information indicating a corresponding recording velocity and a write strategy corresponding to the recording velocity are recorded within each disc information to cope with high speed.

FIG. 6A shows one example of recording disc information of an optical disc according to a third embodiment of the present

invention, in which a disc information structure is schematically illustrated.

Referring to FIG. 6A, a sequence of each disc information is decided by a sequence number, and the corresponding sequence is written by 1-byte. For instance, the corresponding information is recorded in 5th byte within the disc information, which is named 'DI frame sequence number in DI block' field and is briefly represented by '00h, 01h, 02h,...'. Namely, the information of the 5th byte is defined in a following manner.

First of all, if the information of the 5th byte is '00h', '00h' means 1st disc information. '07h' means 8th disc information.

In a specific area within the disc information, each recording velocity information allowed by a disc is represented by a specific bit to be recorded in a previously promised specific location within the disc information. For instance, if a corresponding disc needs four different recording velocity information per recording layer, 4-bits are allocated to one recording velocity each, recording velocity information for the first recording layer (Layer 0) is recorded in Nth and (N+1)th bytes within the disc information, and recording velocity information for 2nd recording layer Layer1 is recorded in Mth

and $(M+1)^{\text{th}}$ bytes within the disc information. If the disc has a single layer, the M^{th} and $(M+1)^{\text{th}}$ bytes are set to 'zero' value. If at least four kinds of different recording velocity information are required, bytes such as N^{th} byte, $(N+1)^{\text{th}}$ byte, 5 $(N+2)^{\text{th}}$ byte, and the like are additionally allocated to use.

Therefore, the recording velocity corresponding to its sequence number, as shown in FIG. 6A, is recorded in a previously promised specific location, whereby it is facilitated to confirm the recording velocity information possessed by the 10 corresponding disc information. Moreover, the remaining bytes, e.g., 44^{th} ~ 111^{th} bytes, are utilized to record write power, write parameters, and the like in detail.

FIG. 6B schematically shows disc information recorded in case of representing the recording velocity information like FIG. 6A, 15 and more particularly, in case of a single layer. If an optical disc requires four kinds of different recording velocity information, four disc information corresponding to each recording velocity are needed. Each of the disc information is recorded by allocating 4-bits to a sequence number and 4-bits 20 to recording velocity corresponding to the sequence number.

For instance, if recording velocities to be represented are 1x speed, 2x speed, 4x speed, and 8x speed, respectively, 1st disc

information has a sequence number corresponding to '00h' to represent a corresponding recording velocity by '0001b' indicating 1x speed, 2nd disc information has a sequence number corresponding to '01h' to represent a corresponding recording velocity by '0010b' indicating 2x speed, 3rd disc information has a sequence number corresponding to '02h' to represent a corresponding recording velocity by '0100b' indicating 4x speed, and 4th disc information has a sequence number corresponding to '03h' to represent a corresponding recording velocity by '1000b' indicating 8x speed. In doing so, each recording velocity is represented by binary information. Hence, if 4-bits each is allocated, a maximum applicable recording velocity (represented by '1111b') will be 15x speed. If the maximum applicable recording velocity exceeds 16x speed, at least 5-bits each should be allocated.

Since the single layer is shown in FIG. 6B, Mth and (M+1)th bytes representing recording velocity information for 2nd recording layer Layer1 are set to 'zero' to be handled as unused information.

FIG. 6C schematically shows disc information recorded in case of representing the recording velocity information like FIG. 6A, and more particularly, in case of a dual layer. If an optical

disc requires four kinds of different recording velocity information, total eight disc information corresponding to each recording velocity are needed. Each of the disc information is recorded by allocating 4-bits to a sequence number and 4-bits
5 to recording velocity corresponding to the sequence number.

For instance, if recording velocities to be represented are 1x speed, 2x speed, 4x speed, and 8x speed, respectively, 1st disc information has a sequence number corresponding to '00h' to represent a corresponding recording velocity by '0001b'
10 indicating 1x speed, 2nd disc information has a sequence number corresponding to '01h' to represent a corresponding recording velocity by '0010b' indicating 2x speed, 3rd disc information has a sequence number corresponding to '02h' to represent a corresponding recording velocity by '0100b' indicating 4x speed,
15 and 4th disc information has a sequence number corresponding to '03h' to represent a corresponding recording velocity by '1000b' indicating 8x speed. The 1st to 4th disc information are information for the 1st recording layer (Layer0) and are recorded in Nth and (N+1)th bytes of disc information, and 4-
20 bits represent each recording velocity by binary information.

Likewise, recording velocity information can be represented for 2nd recording layer in the same manner, which is recorded in Mth

and $(M+1)^{\text{th}}$ bytes. Namely, 5^{th} disc information has a sequence number corresponding to '04h' to represent a corresponding recording velocity by '0001b' indicating 1x speed, 6^{th} disc information has a sequence number corresponding to '05h' to represent a corresponding recording velocity by '0010b' indicating 2x speed, 7^{th} disc information has a sequence number corresponding to '06h' to represent a corresponding recording velocity by '0100b' indicating 4x speed, and 8^{th} disc information has a sequence number corresponding to '07h' to represent a corresponding recording velocity by '1000b' indicating 8x speed.

In the second embodiment, write strategy for write power, write parameters, and the like fitting each recording velocity is recorded in a rest area within the disc information as well as the recording velocity information. Hence, within one disc information, a sequence number of the corresponding disc information, recording velocity information represented by the corresponding disc information, write strategy (WS) coping with the corresponding recording velocity, and the like are recorded respectively.

Besides, in representing the recording velocity information like the second embodiment, 5^{th} byte information is previously

defined as a specific recording velocity so that recording velocity information is recorded in N^{th} , $(N+1)^{\text{th}}$, M^{th} , and $(M+1)^{\text{th}}$ bytes to confirm it.

For instance, it is previously defined that '00h' of 5th byte information means '1x speed disc information of 1st recording layer' and that '07h' of 5th byte information means '8x speed disc information of 2nd recording layer'. Four bits are allocated to each of the N^{th} , $(N+1)^{\text{th}}$, M^{th} , and $(M+1)^{\text{th}}$ bytes so that an accurate recording velocity value is recorded as '0001b' (1x speed) or '0100b' (8x speed). Thus, it is reconfirmed that the corresponding disc information is 1x- or 8x-speed.

FIGS. 7A to 7D are diagrams of recording disc information according to a third embodiment of the present invention, in which applicable recording speed information is recorded to cope with high speed.

In order to acquire disc information associated with a specific writing speed of an intended specific recording layer from a plurality of existing disc information, the entire disc information should be read to take a lot of time. For instance, if there are four recording layers and eight writing speed applicable per recording layer, total thirty-two disc

information are needed. A record/playback unit should search the entire disc information amounting to thirty-two whenever a value of the disc information for the specific recording layer and writing speed is needed. Hence, the present invention is characterized in recording 'disc-applicable writing speed information' and 'recording layer information existing in a disc' within disc information to enable a disc information search by a specified method using the recorded information.

10 Namely, the 'disc-applicable writing speed information' and 'recording layer information existing in a disc' are identically recorded within each disc information in common and a sequence of a plurality of disc information is decided using these information, thereby facilitating to acquire disc information related to the specific recording layer and writing speed to be searched.

Moreover, one write strategy (WS) is recorded within each disc information and identification information for identifying a kind or type of the corresponding write strategy (WS) is separately recorded, whereby a record playback apparatus (FIG. 8) is facilitated to use the write strategy (WS). Moreover, by selecting to record one write strategy (WS) for a specific

writing speed and a specific recording layer in disc information, a disc manufacturer can be provided with convenience.

A method of recording disc information according to a third
5 embodiment of the present invention is explained by referring to FIGs. 7A to 7D as follows.

FIG. 7A shows a schematic structure of disc information for explaining a method of recording disc information according to a third embodiment of the present invention.

10 Referring to FIG. 7A, a sequence for disc information each is decided by a sequence number and is recorded by 1-byte. For instance, the information is recorded in 5th byte within disc information, is named 'DI frame sequence number in DI block' field, and is briefly represented by '00h, 01h, 02h, ...'.

15 Namely, if the information of the 5th byte is '00h', it means 1st disc information. If the information of the 5th byte is '07h', it means 8th disc information. A meaning of the sequence of the 5th byte will be decided by Nth and Lth bytes that will be explained later.

20 Writing speed information applicable by a corresponding disc is recorded in a specific area (Nth byte) within disc information which is named 'Writing speed flag' field. For instance,

whether a specific writing speed of eight kinds of writing speeds is applicable by the corresponding disc is represented by 1-bit each in the same area having 1-byte allocated thereto. Namely, it can be defined that the
5 corresponding writing speed is not applicable (supported) if a bit value is '0b' in entire bits or that the corresponding writing speed is applicable (supported) if the bit value is '1b'. Hence, each of the bits b0~b7 within 1-byte becomes flag information indicating presence or non-presence of
10 applicability of a specific writing speed.

For instance, if 1x speed is applicable by a corresponding disc only, '0000 0001' is written in Nth byte. If all of the eight kinds of writing speeds are applicable, '1111 1111' is written in the Nth byte.

15 In the above explanation, 1x and 2x speeds utilized by every disc almost are previously decided to be adopted. Yet, writing speeds decided by specification can be used as the rest writing speeds from 3rd writing speed. For instance, it is possible to set 3rd, 4th, 5th, 6th, 7th, and 8th writing speeds (3rd X, 4th X,
20 5th X, 6th X, 7th X, 8th X) to 5x, 6x, 8x, 12x, 14x, and 16x speeds, respectively.

Hence, if the corresponding disc allows the writing speeds up

to the 4th writing speed, it will be written as 'Writing speed flag = 0000 1111b'. Yet, if the corresponding disc allows not the 3rd writing speed but the 4th writing speed, 'Writing speed flag = 0000 1011b' is not allowed. Namely, in the

5 'Writing speed flag' field, if upper bits are set to '1b', the corresponding lower bits should be set to '1b'. Hence, it means that lower bits are not set to '0b' despite '1b' of upper bits. Meanwhile, recording layer information indicating the number of recording layer(s) existing within the corresponding disc is

10 recorded in another specific area (Lth byte) within the disc information, which is named 'Number of Recording Layer' field. For instance, a value meaning the number of the recording layer(s) can be represented by a binary number in the same area having 1-byte allocated thereto. In case that the recording

15 layer is the single layer in FIG. 1, '0000 0001' is written in the Lth byte. In case that the recording layer is the dual layer in FIG. 2, '0000 0010' is written in the Lth byte. In case that four recording layers exist, '0000 0100' is written in the Lth byte.

20 Since limitation is put on the number of the currently considered recording layer(s), which is currently two recording layers, 4-bits within the Lth byte are enough to represent

total fifteen recording layers (in case of '1111'). In such a case, it is apparent that other valid information can be written in the rest area (4-bits) of the L^{th} byte.

Moreover, identification information for identifying a kind of write strategy (WS) recorded in $P^{\text{th}} \sim 111^{\text{th}}$ bytes is written in another specific area (M^{th} byte) within the disc information, which is named 'Write Strategy (WS) Type' field.

Namely, in the disc information of the present invention, one write strategy (WS) is recorded for a specific writing speed and a specific recording layer and the write strategy is optionally selected from various kinds of specified write strategy types by a disc manufacturer. Hence, if the corresponding disc information is a first type write strategy WS-1, '0000 0001' is written in the M^{th} byte. If the corresponding disc information is a second type write strategy WS-2, '0000 0010' is written in the M^{th} byte. And, substantial write strategy (WS) is recorded in $P^{\text{th}} \sim 111^{\text{th}}$ bytes. Yet, the substantial write strategy (WS) will be recoded as a value interoperating with the decided write strategy (WS) type in the M^{th} byte. The write strategy (WS) type via the M^{th} byte is optionally recordable in every disc information. And, it is also possible to apply one specified write strategy (WS) type

in 1x speed disc information, which is expected to be supported by every record playback apparatus (FIG. 8), in a mandatory manner.

And, the write strategy (WS) can be recorded in various ways.

5 As a disc becomes highly densified and has higher speed, a writing speed, i.e., disc RPM) as well as medium properties of recording layer is considerably affected. Hence, a more accurate system is requested. And, the various write strategies (WS) are explained as follows for example.

10 First of all, there is a system having a write pulse smaller by '1' than a recording mark size (n) formed on a recording layer medium, which may be called '(n-1) WS'. Secondly, there is a system having a write pulse having a size amounting to a half of the recording mark size (n), which may be called 'n/2 WS'.

15 Besides, new write strategies (WS) keep being developed. Regarding the different kinds or types of write strategies (WS), when there exist the various write strategy (WS) types exist as parameters applied to the write strategies (WS) differ from each other, a disc manufacturer tests write power according to
20 the write strategy (WS) recorded in the selected Mth byte and then records a result of the test as write strategy (WS) in the Pth~111th bytes within the disc information.

From the above-recorded 'writing speed information' of the N^{th} byte and the 'recording layer information' of the L^{th} byte, the record playback apparatus (FIG. 8) recognizes how many disc information exist within the corresponding disc.

5 Namely, the number of the existing disc information is found by multiplying an applicable writing speed number by the number of recording layers. As the present invention applies one write strategy (WS) for a specific writing speed and a specific recording layer, the type and number of the write strategy (WS)
10 may not be taken into consideration in deciding the number of disc information.

The above-decided information about the number of total disc information can be recorded in a specific area (e.g., 4^{th} byte or the like) (not shown in the drawing) within the disc
15 information as well.

Hence, it is able to program a plurality of the above-decided disc information such that the sequence (which is written in the 5^{th} byte as mentioned in the foregoing description) of the disc information is decided by the sequence numbers and such
20 that each of the disc information designates the previously decided writing speed and recording layer by the sequence.

For example, by knowing that four writing speeds applicable by

a disc exist if the Nth byte is '0000 1111' and that two recording layers exist within the disc if the Lth byte is '0000 0010', total eight disc information are needed so that the sequence will be '00h~07h'. And, it is previously decided that
5 disc information of '00h', '01h', '02h', '03h', '04h', '05h', '06h', and '07h' relate to '1x speed, 1st recording layer', '2x speed, 2nd recording layer', '2x speed, 1st recording layer', '2x speed, 2nd recording layer', '3rd writing speed, 1st recording layer', '3rd writing speed, 2nd recording layer', '4th
10 writing speed, 1st recording layer', and '4th writing speed, 2nd recording layer', respectively.

In the above-explained example, the writing speed is preferentially taken into consideration. Yet, it is apparent that the recording layer can be preferentially taken into
15 consideration.

Hence, in order to acquire the disc information for a specific target writing speed and a specific target recording layer, the record playback apparatus (FIG. 8) is facilitated to check which disc information is related to the specific target
20 writing speed and recording layer from 'writing speed information' of the Nth byte and 'recording layer information' of the Lth byte commonly recorded within the respective disc

information instead of playing back to check the entire disc information.

FIG. 7B shows an example of extending the third embodiment of the present invention in FIG. 7A. In case that writing speeds applicable by a disc exceed eight kinds, the N^{th} byte ('Writing speed flag' field) in FIG. 7A is extended to indicate presence or non-presence of applicability of 1^{st} ~ 8^{th} writing speeds by a flag in $N1^{\text{th}}$ byte ('Writing speed flag1' field), and another byte is allocated to display presence or non-presence of applicability of 9^{th} ~ 16^{th} writing speeds by a flag in $N2^{\text{th}}$ byte. Contents written in the rest bytes are equivalent to those of the third embodiment of the present invention in FIG. 7A, thereby being skipped in the following description.

FIG. 7C shows an example of recording disc information by the third embodiment of the present invention in FIG. 7A. It can be known that there are two (1X, 2X) applicable writing speeds from N^{th} byte ('0000 0010b') commonly recorded in the entire disc information and that two recording layers exist within a disc from L^{th} byte ('0000 0010b').

Hence, in the example of FIG. 7C, total four disc information (two recording layers * two writing speeds) exist and a sequence of the disc information becomes '00h' (1X,L0) → '01h'

(1X,L1) → '02h' (2X,L0) → '03h' (2X,L1). This is a specified content according to a predetermined sequence and, as mentioned in the foregoing description, can be rendered into a different sequence by a specification.

5 An intrinsic write strategy (WS) is recorded in other bytes within each disc information as well as in Nth and Lth bytes. Specifically, information of a type of write strategy (WS) written in Pth~111th bytes within the corresponding disc information is recorded in Mth byte. Namely, information
10 written in the Mth byte and the Pth~111th bytes can differ in each disc information.

In the example in FIG. 7C, '00h' (1X,L0) and '01h' (1X,L1) relate to the application of a first type write strategy (WS-1) and '02h' (2X,L0) and '03h' (2X,L1) relate to the application
15 of a second type write strategy (WS-2).

FIG. 7D shows another example of recording disc information according to the third embodiment of the present invention in FIG. 7A. It can be known that there are eight (1X, 2X, ..., 16X) applicable writing speeds from Nth byte ('1111 1111b') commonly
20 recorded in the entire disc information and that four recording layers exist within a disc from Lth byte ('0000 0100b'). Hence, in the another example of FIG. 7D, total thirty-two disc

information (four recording layers * eight writing speeds) exist and a sequence of the disc information becomes '00h' (1X,L0) → '01h' (1X,L1) → '02h' (1X,L2) → '03h' (1X,L4) → '04h' (2X,L0) → ... → '31h' (16X,L4).

5 An intrinsic write strategy (WS) is recorded in other bytes within each disc information as well as in N^{th} and L^{th} bytes. Specifically, information of a type of a write strategy (WS) written in $P^{\text{th}} \sim 111^{\text{th}}$ bytes within the corresponding disc information is recorded in M^{th} byte. Namely, information
10 written in the M^{th} byte and the $P^{\text{th}} \sim 111^{\text{th}}$ bytes can differ in each disc information.

In the another example of FIG. 7D, if a record playback unit (FIG. 8) intends to search disc information related to 2x speed (2X,L0) of a first recording layer to perform a recording by
15 applying a write strategy (WS) within the corresponding disc information, it can be known from the information in the N^{th} and L^{th} bytes commonly recorded in the entire disc information that total thirty-two disc information (four recording layers * eight writing speeds) exist in the corresponding disc according
20 to the sequence of the disc information such as '00h' (1X,L0) → '01h' (1X,L1) → '02h' (1X,L2) → '03h' (1X,L4) → '04h' (2X,L0) → ... → '31h' (16X,L4).

Hence, the record playback apparatus (FIG. 8) enables to recognize that the disc information related to the 2x speed (2X,L0) of the first recording layer to be searched is '04h' and that the corresponding disc information ('04h') is recorded as the first type write strategy (WS-1_ from the write strategy (WS) type identification information ('0000 0002b') recorded in the Mth byte within the corresponding information ('04h'), thereby reading out parameter values of the first type write strategy (WS-1) via the Pth~111th bytes to utilize in the recording.

Likewise, if intending to search disc information related to 16x speed (16X,L3) of a fourth recording layer to perform recording by applying a write strategy (WS) within the corresponding disc information, the record playback unit (FIG. 8) recognizes that the corresponding disc information is '31h' via the same process and that the write strategy type (WS) is the second type (WS-2), thereby enabling to utilize them in the recording.

Therefore, if a host or a control unit ('20' in Fig. 8) intends to perform a recording on a specific recording layer at a specific writing speed, the record playback apparatus (FIG. 8) is facilitated to search the corresponding disc information,

thereby enabling to confirm the write strategy (WS) recorded within the corresponding disc information.

For reference, the information of the first and third embodiments can be recorded within the disc information (DI) together or within separate disc control information (not shown in the drawing), respectively. In this case, the applicable speed information disclosed in the third embodiment may have a priority. This is to decide by the information disclosed in the third embodiment whether a corresponding specific writing speed is applicable because a portion of maximum writing speed, minimum writing speed, nominal writing speed, and other writing speed information may not be substantially applicable.

FIG. 8 illustrates an optical disc recording and reproducing apparatus using disc control information according to the present invention. The recording and reproducing apparatus comprises a record/playback unit 10 for recording data on and reproducing data from an optical disc and a controller 20 for controlling the record/playback unit 10. The controller 20 generates a record or playback command for a specific area, and the record/playback unit 10 carries out the record/playback function for the specific area accordingly. The record/playback unit 10 includes an interface 12 for

communicating with an external device, i.e., the controller (or host); a pickup 11 for performing read and write operations with respect to the optical disc; a data processor 13 for modulating the pickup's input signal for performing a recording operation and for demodulating the pickup's output signal for performing a reproduction operation; a servo 14 for controlling the read and write operations of the pickup; a memory 15 for temporarily storing disc control information and user data to be recorded or read; and a microcomputer 16 for respectively controlling each element of the record/playback unit.

Industrial Applicability

In the above system, it is also possible to control the recording and/or reproducing of data without the control unit 20. In that case, the Microcomputer 16 may control all units in the record/playback unit 10 as performing the function of the control unit 10.

In a recording data on an optical disc according to the present invention, the optical disc recording and reproducing apparatus first reads the entire disc management area of an inserted optical disc, the read information being disc information of the present invention, which is temporarily stored in the

memory 15. Thus, the recording layer information, recording velocity information, and write strategy fitting the corresponding recording velocity are read out and temporarily stored.

5 If intending to perform a writing on a specific area within the optical disc, the controller 20 renders such an intent into a writing command and then delivers it to the record/playback unit 10 together with data for writing location information to be recorded. After receiving the writing command, the
10 microcomputer 16 decides the corresponding recording velocity applied to an intended recording layer within the optical disc from the management information stored in the memory 15 and then performs the writing command using the most optimal write strategy by referring to the determined recording velocity.

15 Specifically, in case that the recording is performed on the optical disc by the first embodiment of the present invention, the microcomputer 16 performs the recording in a manner of applying a different per writing speed write strategy (WS) to each area within the disc by considering the maximum,
20 intermediate, minimum, and other writing speeds.

Accordingly, the present invention provides various methods of providing disc control information coping with higher writing

speed in a high-density optical disc, thereby enabling to uniformly apply the standardized disc control information to efficiently cope with the record/playback of the optical disc.

It will be apparent to those skilled in the art that various
5 modifications and variations can be made in the present invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

Claims

1. A data structure comprising a recording speed information, the recording speed information comprising:
 - a first information indicating a maximum recording speed;
 - a second information indicating a minimum recording speed;
 - a third information indicating a predetermined recording speed different from the maximum and minimum recording speeds; and
 - a fourth information indicating a basic recording speed.
2. The data structure of claim 1, further comprising a plurality of recording speed parameters to be used or used to record data by the respective recording speeds.
3. The data structure of claim 1, wherein the first to fourth information are included in a recording speed group.
4. The data structure of claim 1, wherein the first to fourth information are included in each layer of a multi-layer optical recording medium.
5. The data structure of claim 1, wherein the fourth information includes at least two basic recording speeds.
6. The data structure of claim 1, further comprising

an applicable recording speed information indicating each applicable recording speed.

7. The data structure of claim 6, wherein the applicable recording speed information indicates the each applicable recording speed in a bit position.

8. The data structure of claim 7, wherein the applicable recording speed information is configured in a manner that a lower bit position is set to indicate that a lower recording speed is applicable if a higher bit position is set to indicate that a higher recording speed is applicable.

9. The data structure of claim 6, wherein the applicable recording speed information has a priority to determine an applicability of specific recording speed than the recording speed information.

10. The data structure of claim 1, further comprising a write strategy type information indicating a write strategy type applicable to a recording of data on an optical recording medium.

11. A method of recording control information of recording medium, comprising a step of:

generating the control information including a plurality of recording speed information and at least one write strategy associated with a specific recording

speed wherein one of the recording speed information is a basic recording speed information; and

recording the control information on the recording medium.

12. The method of claim 11, wherein the recording speed information further include maximum recording speed information, minimum recording speed information, at least one intermediate recording speed information indicating an intermediate recording speed between the maximum and minimum recording speeds applicable to the recording medium.

13. The method of claim 12, wherein a plurality of write strategies respectively associated with the respective recording speeds are recorded along with the recording speed information.

14. A method of recording a recording speed information on an optical recording medium, comprising the steps of
generating a recording speed information, wherein the recording speed information comprises a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the maximum or minimum recording speed, and a fourth information indicating a basic recording speed; and
recording the recording speed information on a specific area of the optical recording medium.

15. The method of claim 14, further comprising the step of recording an applicable recording speed information indicating presence of the maximum, minimum, basic, and predetermined recording speeds.

16. The method of claim 14, further comprising the step of recording a write strategy information indicating a write strategy type applicable to a recording of data on an optical recording medium.

17. The method of claim 14, further comprising the step of recording a plurality of recording speed parameters to be used to record data by the respective recording speeds.

18. The method of claim 14, further comprising the step of recording a recordable speed information indicating whether specific recording speed is applicable.

19. The method of claim 18, wherein the recordable speed information indicates the each recording speed in a bit position.

20. The method of claim 19, wherein the recordable speed information is recorded in a manner that a lower bit position is set to indicate that a lower recording speed is applicable if a higher bit position is set to indicate that a higher recording speed is applicable.

21. The method of claim 18, wherein the recordable speed information has a priority to determine the applicability of specific recording speed than the recording speed information.

22. A method of recording/reproducing data on/from an optical recording medium, comprising the steps of:

reading a speed information from a specific area of the optical recording medium, wherein the speed information comprises a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the maximum and minimum recording speed, and a fourth information indicating a basic recording speed; and

recording data on a main data area of the optical recording medium based on the read speed information.

23. The method of claim 22, wherein in the recording step, the data is recorded by using one of the read recording speeds.

24. The method of claim 22, wherein in the recording step, the data is recorded by using the basic recording speed.

25. The method of claim 23, wherein in the reading step, a plurality of recording speed parameters are further read from the specific area, and the data is recorded based on the recording speed parameters associated with to the used

recording speed.

26. The method of claim 23, wherein the recording speed parameters include write strategy type for specific recording speed.

27. The method of claim 22, wherein the speed information further comprises a recordable speed information indicating an applicability of the maximum, minimum, basic, and predetermined recording speeds to record the data using an applicable recording speed.

28. The method of claim 22, wherein the speed information further comprises a recordable speed information indicating whether a specific recording speed is applicable.

29. The method of claim 28, wherein the recordable speed information indicates the each recording speed in a bit position.

30. The method of claim 29, wherein the recordable speed information is configured in a manner that a lower bit position is set to indicate that a lower recording speed is applicable if a higher bit position is set to indicate that a higher recording speed is applicable.

31. The method of claim 28, wherein the recordable speed

information has a priority to determine the applicability of specific recording speed than the recording speed information.

32. A recording medium having a recording speed information, characterized in that the recording speed information comprises a first information indicating a maximum recording speed, a second information indicating a minimum recording speed, a third information indicating a predetermined recording speed different from the maximum and minimum recording speed, and a fourth information indicating a basic recording speed.

33. The recording medium of claim 32, further comprising a plurality of recording speed parameters to be used to record data at the respective recording speeds.

34. The recording medium of claim 32, wherein the first to fourth information are included in a recording speed group.

35. The recording medium of claim 32, wherein the first to fourth information are included in each layer of a multi-layer optical recording medium.

36. The recording medium of claim 32, wherein the fourth information includes at least two basic recording speeds.

37. The recording medium of claim 32, further comprising an

applicable recording speed information indicating whether specific recording speed is applicable.

38. The recording medium of claim 37, wherein the applicable recording speed information indicates applicability of each recording speed in a bit position.

39. The recording medium of claim 38, wherein the applicable recording speed information is configured in a manner that a lower bit position is set to indicate a lower recording speed is applicable if a higher bit position is set to indicate a higher recording speed is applicable.

40. The recording medium of claim 32, further comprising a write strategy type information indicating a write strategy type applicable to a recording of data on the recording medium.

41. An optical disc comprising at least one recording layer provided with a recordable area and a prerecorded area, wherein disc control information is separately recorded within the prerecorded area per the recording layer and wherein a plurality of recording speed information and a plurality of write strategies associated with corresponding recording speeds are recorded within the disc control information, and wherein one of the recording speed information is a basic recording speed information.

42. The optical disc of claim 41, wherein the recording speed information include maximum and minimum recording speed information applicable to the optical disc.

43. The optical disc of claim 42, wherein the recording speed information include at least one intermediate recording speed information indicating an intermediate recording speed between the maximum and minimum recording speeds applicable to the optical disc.

44. The optical disc of claim 41, wherein the optical disc is a recordable Blu-ray disc.

45. The optical disc of claim 41, wherein the optical disc is a recordable DVD.

46. An optical disc recording method comprising the steps of:
reading disc control information written within a management area of the optical disc and storing a plurality of recording speed information and write strategies respectively fitting corresponding recording speeds within the disc control information;

deciding the recording speed to be applied to the optical disc by referring to a plurality of the stored speed information and the write strategies; and

performing a recording at the decided recording speed.

47. The optical disc recording method of claim 46, wherein a plurality of the recording speed information include a basic (optimal) recording speed, an applicable maximum recording speed, an applicable minimum recording speed, and an intermediate recording speed different from the maximum and minimum recording speeds.

48. The optical disc recording method of claim 47, wherein the recording is performed on an inner circumference of the optical disc at the applicable minimum recording speed.

49. The optical disc recording method of claim 47, wherein the recording is performed on an outer circumference of the optical disc at the applicable maximum recording speed.

50. The optical disc recording method of claim 47, wherein the recording is performed between the inner and outer circumferences of the optical disc at the intermediate recording speed.

51. The optical disc recording method of claim 46, wherein the write strategies include write strategy types and wherein data is recorded at the decided recording speed according to the corresponding write strategy type.

52. An apparatus for recording or reproducing data on or from an optical disc, comprising:

a pickup unit reading or writing data ; and

a controller controlling a recording in a manner of controlling the pickup unit to read disc control information recorded within a management area of an optical disc, the disc control information including a recording speed information, the recording speed information including a maximum recording speed information, a minimum recording speed information, a basic recording speed information, a predetermined speed information different from the maximum and minimum recording speed information, deciding a recording speed from the recording speed information for the recording, and controlling the recording based on the decided recording speed.

53. The apparatus of claim 52, wherein the disc control information further includes a write strategy associated with the corresponding recording speeds, the controller controls the recording by using the write strategy associated with the decided recording speed.

54. The apparatus of claim 52, wherein the disc control information further includes a recordable speed information to indicate whether a specific recording speed is applicable, the controller decides the recording speed based on the recordable speed information.

55. A method for recording control information on a recording medium, comprising:

generating control information for controlling recording/reproducing data on/from the recording medium, wherein the control information includes a first speed

information indicating a maximum recording speed, a second speed information indicating a minimum recording speed, and a third speed information indicating one or more basic recording speeds, wherein the third speed information represents whether each of the basic recording speeds are applicable to the recording medium or not; and

recording the control information on a specific area of the recording medium.

56. An apparatus for recording control information on a recording medium, comprising:

a controller for generating control information to control recording/reproducing data on/from the recording medium, wherein the control information includes a first speed information indicating a maximum recording speed, a second speed information indicating a minimum recording speed, and a third speed information indicating one or more basic recording speeds, wherein the third speed information represents whether each of the basic recording speeds are applicable to the recording medium or not; and

a pick-up unit for recording the control information on a specific area of the recording medium.

57. A recording medium comprising:

a data area configured to record user data; and

one or more management areas configured to record control information, wherein the control information includes a first speed information indicating a maximum recording speed, a second speed information indicating a minimum

recording speed, and a third speed information indicating one or more basic recording speeds, wherein the third speed information represents whether each of the basic recording speeds are applicable to the recording medium or not.

58. A method for recording data on a recording medium, comprising:

reading control information from the recording medium, wherein the control information includes a first speed information indicating a maximum recording speed, a second speed information indicating a minimum recording speed, and a third speed information indicating one or more basic recording speeds, wherein the third speed information represents whether each of the basic recording speeds are applicable to the recording medium or not; and

recording the data on the recording medium according the read control information.

59. An apparatus for recording data on a recording medium, comprising:

a pick-up unit for reading control information from the recording medium, wherein the control information includes a first speed information indicating a maximum recording speed, a second speed information indicating a minimum recording speed, and a third speed information indicating one or more basic recording speeds, wherein the third speed information represents whether each of the basic recording speeds are applicable to the recording medium or not; and

a controller for controlling recording of the data according to the read control information.