

MOUNTING OF PRINthead IN SUPPORT MEMBER OF SIX COLOR INKJET MODULAR PRINthead

Field of the Invention

5 This invention relates to a modular printhead. More particularly, the invention relates to the assembly of such a modular printhead. Specifically, this invention relates to a mounting of a printhead in a support member of a modular printhead.

Background to the Invention

10 The applicant has previously proposed the use of a pagewidth printhead to provide photographic quality printing. However, manufacturing such a pagewidth printhead having the required dimensions is problematic in the sense that, if any nozzle of the printhead is defective, the entire printhead needs to be scrapped and replaced.

15 Accordingly, the applicant has proposed the use of a pagewidth printhead made up of a plurality of small, replaceable printhead modules which are arranged in end-to-end relationship. The advantage of this arrangement is the ability to remove and replace any defective module in a pagewidth printhead without having to scrap the entire printhead.

20 It is also necessary to accommodate thermal expansion of the individual modules in the assembly constituting the pagewidth printhead to ensure that adjacent modules maintain their required alignment with each other.

Summary of the Invention

25 According to the invention, there is provided a printhead which includes a receiving member defining a receiving zone;
at least one printhead module received in the receiving zone of the receiving member; and

30 complementary locating formations carried by the receiving member and said at least one printhead module, the locating formations enabling relative movement of the printhead module, due to expansion, in three orthogonal axes relative to the receiving member.

- 2 -

Preferably, the receiving member is a channel shaped member having opposed walls interconnected by a bridging portion to define a channel which forms the receiving zone. Accordingly, the three orthogonal axes may be an x axis, being an axis parallel to a longitudinal axis of the channel shaped member, a y axis being in the same plane as the x axis but at right angles thereto and a z axis which is at right angles to the plane.

For a pagewidth printhead, the printhead may include a plurality of printhead modules arranged in end-to-end relationship in the channel, each printhead module carrying a printhead chip and adjacent modules abutting each other such that the printhead chips of adjacent modules overlap.

Thus, each module may be elongated, may be stepped at its end and the printhead chip may be arranged at an angle to a longitudinal axis of the module. The longitudinal axis of the module may extend in the x-direction.

Each printhead module may have a set of locating formations and the channel of the channel shaped member may have a complementary set of locating formations at each module location in the channel.

The locating formations of the channel shaped member at each module location may include a pair of longitudinally spaced engaging formations arranged on one wall of the channel and a securing means arranged on an opposed wall of the channel; and the locating formations of each module may include a pair of longitudinally spaced co-operating elements arranged along one side of each module for co-operating with the engaging formations and a complementary element on an opposed side of the module for co-operating with the securing means.

One combination of engaging formation and co-operating element may serve to locate the module relative to the channel in a longitudinal, or x direction, the other combination of engaging formation and co-operating element allowing longitudinal, expansionary displacement of the module relative to the channel in the direction of the x axis.

The combinations of engaging formations and co-operating members, due to shapes of said engaging formations and co-operating members may allow expansionary displacement of the module relative to the channel in a direction normal to a plane in which the module lies, i.e. in the direction of the z axis.

A combination of the securing means and the complementary element may allow expansionary displacement of the module relative to the channel in a direction of a plane in which the module lies but normal to a longitudinal axis of the channel, i.e. in the direction of the y axis.

- 3 -

To facilitate any expansion in the direction of the y axis, a width of the module may be less than a spacing between the walls of the channel.

The securing means may be a snap release carried on a resiliently flexible arm, the resiliently flexible arm forming part of said opposed wall of the channel.

5 The complementary element may be a stepped recess defined in the module approximately midway along its length for receiving the snap release.

Each engaging formation may be in the form of a hemispherical projection which projects inwardly from said one wall of the channel. A first co-operating element may comprise a conical recess defined proximate a first end of the module and
10 a second co-operating element may comprise a slot, having a longitudinal axis extending parallel to the longitudinal axis of the channel, proximate a second end of the module, each of the conical recess and slot receiving one of the hemispherical projections therein. The slot may have a triangular cross-section when viewed in a plane normal to the longitudinal axis of the slot.

15

Brief Description of the Drawings

The invention is now described by way of example with reference to the accompanying drawings in which:-

20 Figure 1 shows a three dimensional view of a multi-module printhead, in accordance with the invention;

Figure 2 shows a three dimensional, exploded view of the printhead of Figure 1;

Figure 3 shows a three dimensional view, from one side, of a mounting member of a printhead, in accordance with the invention;

25 Figure 4 shows a three dimensional view of the mounting member, from the other side;

Figure 5 shows a three dimensional view of a single module printhead, in accordance with the invention;

Figure 6 shows a three dimensional, exploded view of the printhead of Figure 5;

Figure 7 shows a plan view of the printhead of Figure 5;

30 Figure 8 shows a side view, from one side, of the printhead of Figure 5;

Figure 9 shows a side view, from an opposed side, of the printhead of Figure 5;

Figure 10 shows a bottom view of the printhead of Figure 5;

Figure 11 shows an end view of the printhead of Figure 5;

35 Figure 12 shows a sectional end view of the printhead of Figure 5 taken along line XII-XII in Figure 7;

- 4 -

Figure 13 shows a sectional end view of the printhead of Figure 5 taken along line XIII-XIII in Figure 10;

Figure 14 shows a three dimensional, underside view of a printhead component;

Figure 15 shows a bottom view of the component, illustrating schematically the supply of fluid to a printhead chip of the component; and

Figure 16 shows a three dimensional, schematic view of a printhead assembly, including a printhead, in accordance with the invention.

Detailed Description of the Drawings

A printhead, in accordance with the invention, is designated generally by the reference numeral 10. The printhead 10 can either be a multi-module printhead, as shown in Figures 1 to 4 or a single module printhead as shown in Figures 5 to 15. In practice, the printhead is likely to be a multi-module printhead and the illustrated, single module printhead is provided more for explanation purposes.

The printhead 10 includes a mounting member in the form of a channel shaped member 12. The channel shaped member 12 has a pair of opposed side walls 14, 16 interconnected by a bridging portion or floor portion 18 to define a channel 20.

A plurality of printhead components in the form of modules or tiles 22 are arranged in end-to-end fashion in the channel 20 of the channel shaped member 12.

As illustrated, each tile 22 has a stepped end region 24 so that, when adjacent tiles 22 are butted together end-to-end, printhead chips 26 of the adjacent tiles 22 overlap. It is also to be noted that the printhead chip 26 extends at an angle relative to longitudinal sides of its associated tile 22 to facilitate the overlap between chips 26 of adjacent tiles 22. The angle of overlap allows the overlap area between adjacent chips 26 to fall on a common pitch between ink nozzles of the printhead chips 26. In addition, it will be appreciated that, by having the printhead chips 26 of adjacent tiles 22 overlapping, no discontinuity of printed matter appears when the matter is printed on print media (not shown) passing across the printhead 10.

If desired, a plurality of channel shaped members 12 can be arranged in end-to-end fashion to extend the length of the printhead 10. For this purpose, a clip 28 and a receiving formation 30 (Figure 4) are arranged at one end of the channel shaped member 12 to mate and engage with corresponding formations (not shown) of an adjacent channel shaped member 12.

Those skilled in the art will appreciate that the nozzles of the printhead chip have dimensions measured in micrometres. For example, a nozzle opening of each

- 5 -

nozzle may be about 11 or 12 micrometres. To ensure photographic quality printing, it is important that the tiles 22 of the printhead 10 are accurately aligned relative to each other and maintain that alignment under operating conditions. Under such operating conditions, elevated temperatures cause expansion of the tiles 22. It is necessary to account for this expansion while still maintaining alignment of adjacent tiles 22 relative to each other.

For this purpose, the channel shaped member 12 and each tile 22 have complementary locating formations for locating the tiles 22 in the channel 20 of the channel shaped member 12. The locating formations of the channel shaped member 12 comprise a pair of longitudinally spaced engaging or locating formations 32 arranged on an inner surface of the wall 14 of the channel shaped member 12. More particularly, each tile 22 has two such locating formations 32 associated with it. Further, the locating formations of the channel shaped member 12 include a securing means in the form of a snap release or clip 34 arranged on an inner surface of the wall 16 of the channel shaped member 12. Each tile 22 has a single snap release 34 associated with it. One of the mounting formations 32 is shown more clearly in Figure 12 of the drawings.

As shown most clearly in Figure 6 of the drawings, each tile 22 includes a first molding 36 and a second molding 38 which mates with the first molding 36. The molding 36 has a longitudinally extending channel 39 in which the printhead chip 26 is received. In addition, on one side of the channel 39, a plurality of raised ribs 40 is defined for maintaining print media, passing over the printhead chip 26 at the desired spacing from the printhead chip 26. A plurality of conductive ribs 42 is defined on an opposed side of the channel 39. The conductive ribs 42 are molded to the molding 36 by hot stamping during the molding process. These ribs 42 are wired to electrical contacts of the chip 26 for making electrical contact with the chip 26 to control operation of the chip 26. In other words, the ribs 42 form a connector 44 for connecting control circuitry, as will be described in greater detail below, to the nozzles of the chip 26.

The locating formations of the tile 22 comprise a pair of longitudinally spaced co-operating elements in the form of receiving recesses 46 and 48 arranged along one side wall 50 of the second molding 38 of the tile 22. These recesses 46 and 48 are shown most clearly in Figure 6 of the drawings.

The recesses 46 and 48 each receive one of the associated locating formations 32 therein.

The molding 36 of the tile 22 also defines a complementary element or recess 50 approximately midway along its length on a side of the molding 36 opposite the side

- 6 -

having the recesses 46 and 48. When the molding 36 is attached to the molding 38 a stepped recess portion 52 (Figure 7) is defined which receives the snap release 34 of the channel shaped member 12.

5 The locating formations 32 of the channel shaped member 12 are in the form of substantially hemispherical projections extending from the internal surface of the wall 14.

10 The recess 46 of the tile 22 is substantially conically shaped, as shown more clearly in Figure 12 of the drawings. The recess 48 is elongate and has its longitudinal axis extending in a direction parallel to that of a longitudinal axis of the channel shaped member 12. Moreover, the formation 48 is substantially triangular, when viewed in cross section normal to its longitudinal axis, so that its associated locating formation 32 is slidably received therein.

15 When the tile 22 is inserted into its assigned position in the channel 20 of the channel shaped member 12, the locating formations 32 of the channel shaped member 12 are received in their associated receiving formations 46 and 48. The snap release 34 is received in the recess 50 of the tile 22 such that an inner end of the snap release 34 abuts against a wall 54 (Figure 7) of the recess 50.

20 Also, it is to be noted that a width of the tile 22 is less than a spacing between the walls 14 and 16 of the channel shaped member 12. Consequently, when the tile 22 is inserted into its assigned position in the channel shaped member 12, the snap release 34 is moved out of the way to enable the tile 22 to be placed. The snap release 34 is then released and is received in the recess 50. When this occurs, the snap release 34 bears against the wall 54 of the recess 50 and urges the tile 22 towards the wall 14 such that the projections 32 are received in the recesses 46 and 48. The projection 32
25 received in the recess, locates the tile 22 in a longitudinal direction. However, to cater for an increase in length due to expansion of the tiles 22, in operation, the other projection 32 can slide in the slot shaped recess 48. Also, due to the fact that the snap release 34 is shorter than the recess 50, movement of that side of the tile 22 relative to the channel shaped member 12, in a longitudinal direction, is accommodated.

30 It is also to be noted that the snap release 34 is mounted on a resiliently flexible arm 56. This arm 56 allows movement of the snap release in a direction transverse to the longitudinal direction of the channel shaped member 12. Accordingly, lateral expansion of the tile 22 relative to the channel shaped member 12 is facilitated. Finally, due to the angled walls of the projections 46 and 48, a degree of vertical
35 expansion of the tile 22 relative to the floor 18 of the channel shaped member 12 is also accommodated.

- 7 -

Hence, due to the presence of these mounting formations 32, 34, 46, 48 and 50, the alignment of the tiles 22, it being assumed that they will all expand at more or less the same rate, is facilitated.

As shown more clearly in Figure 14 of the drawings, the molding 36 has a plurality of inlet openings 58 defined at longitudinally spaced intervals therein. An air supply gallery 60 is defined adjacent a line along which these openings 58 are arranged. The openings 58 are used to supply ink and related liquid materials such as fixative or varnish to the printhead chip 26 of the tile 22. The gallery 60 is used to supply air to the chip 26. In this regard, the chip 26 has a nozzle guard 61 (Figure 12) covering a nozzle layer 63 of the chip 26. The nozzle layer 63 is mounted on a silicon inlet backing 65 as described in greater detail in our co-pending application number PCT/AU00/00744. The disclosure of this co-pending application is specifically incorporated herein by cross-reference.

The opening 58 communicates with corresponding openings 62 defined at longitudinally spaced intervals in that surface 64 of the molding 38 which mates with the molding 36. In addition, openings 66 are defined in the surface 64 which supply air to the air gallery 60.

As illustrated more clearly in Figure 14 of the drawing, a lower surface 68 has a plurality of recesses 70 defined therein into which the openings 62 open out. In addition, two further recesses 72 are defined into which the openings 66 open out.

The recesses 70 are dimensioned to accommodate collars 74 standing proud of the floor 18 of the channel shaped member 12. These collars 74 are defined by two concentric annuli to accommodate movement of the tile 22 relative to the channel 20 of the channel shaped member 12 while still ensuring a tight seal. The recesses 66 receive similar collars 76 therein. These collars 76 are also in the form of two concentric annuli.

The collars 74, 76 circumscribe openings of passages 78 (Figure 10) extending through the floor 18 of the channel shaped member 12.

The collars 74, 76 are of an elastomeric, hydrophobic material and are molded during the molding of the channel shaped member 12. The channel shaped member 12 is thus molded by a two shot molding process.

To locate the molding 38 with respect to the molding 36, the molding 36 has location pegs 80 (Figure 14) arranged at opposed ends. The pegs 80 are received in sockets 82 (Figure 6) in the molding 38.

- 8 -

In addition, an upper surface of the molding 36, i.e. that surface having the chip 26, has a pair of opposed recesses 82 which serve as robot pick-up points for picking and placing the tile 22.

A schematic representation of ink and air supply to the chip 26 of the tile 22 is shown in greater detail in Figure 15 of the drawings.

Thus, via a first series of passages 78.1 cyan ink is provided to the chip 26. Magenta ink is provided via passages 78.2, yellow ink is provided via passages 78.3, and black ink is provided via passages 78.4. An ink which is invisible in the visible spectrum but is visible in the infrared spectrum is provided by a series of passages 78.5 and a fixative is provided via a series of passages 78.6. Accordingly, the chip 26, as described, is a six "color" chip 26.

To cater for manufacturing variations in tolerances on the tile 22 and the channel shaped member 12, a sampling technique is used.

Upon completion of manufacture, each tile 22 is measured to assess its tolerances. The offset from specification of the particular tile 22 relative to a zero tolerance is recorded and the tile 22 is placed in a bin containing tiles 22 each having the same offset. A maximum tolerance of approximately +10 microns or -10 microns, to provide a 20 micron tolerance band, is estimated for the tiles 22.

The storage of the tiles 22 is determined by a central limit theorem which stipulates that the means of samples from a non-normally distributed population are normally distributed and, as a sample size gets larger, the means of samples drawn from a population of any distribution will approach the population parameter.

In other words, the central limit theorem, in contrast to normal statistical analysis, uses means as variates themselves. In so doing, a distribution of means as opposed to individual items of the population is established. This distribution of means will have its own mean as well its own variance and standard deviation.

The central limit theorem states that, regardless of the shape of the original distribution, a new distribution arising from means of samples from the original distribution will result in a substantially normal bell-shaped distribution curve as sample size increases.

In general, variants on both sides of the population mean should be equally represented in every sample. As a result, the sample means cluster around the population mean. Sample means close to zero should become more common as the tolerance increases regardless of the shape of the distribution which will result in a symmetrical uni-modal, normal distribution around the zero positions.

Accordingly, upon completion of manufacture, each tile 22 is optically measured for variation between the chip 26 and the moldings 36, 38. When the tile assembly has been measured, it is laser marked or bar coded to reflect the tolerance shift, for example, +3 microns. This tile 22 is then placed in a bin of +3 micron tiles.

5 Each channel 12 is optically checked and the positions of the locating formations 32, 34 noted. These formations may be out of alignment by various amounts for each tile location or bay. For example, these locating formations 32, 34 may be out of specification by -1 micron in the first tile bay, by +3 microns in the second tile bay, by -2 microns in the third tile bay, etc.

10 The tiles 22 will be robot picked and placed according to the offsets of the locating formations 32, 34. In addition, each tile 22 is also selected relative to its adjacent tile 22.

With this arrangement, variations in manufacturing tolerances of the tiles 22 and the channel shaped member 12 are accommodated such that a zero offset mean is possible by appropriate selections of tiles 22 for their locations or bays in the channel shaped member 12.

15 A similar operation can be performed when it is desired or required to replace one of the tiles 22.

Referring now to Figure 16 of the drawings, a printhead assembly, also in accordance with the invention, is illustrated and is designated generally by the reference numeral 90. The assembly 90 includes a body member 92 defining a channel 94 in which the printhead 10 is receivable.

20 The body 92 comprises a core member 96. The core member 96 has a plurality of channel defining elements or plates 98 arranged in parallel spaced relationship. A closure member 100 mates with the core member 96 to close off channels defined between adjacent plates to form ink galleries 102. The closure member 100, on its operatively inner surface, has a plurality of raised rib-like formations 104 extending in spaced parallel relationship. Each rib-like member 104, apart from the uppermost one (i.e. that one closest to the channel 94) defines a slot 106 in which a free end of one of the plates 98 of the core member 96 is received to define the galleries 102.

25 30 35 A plurality of ink supply canals are defined in spaced parallel relationship along an operatively outer surface of the core member 96. These canals are closed off by a cover member 110 to define ink feed passages 108. These ink feed passages 108 open out into the channel 94 in communication with the passages 78 of the channel shaped member 12 of the printhead 10 for the supply of ink from the relevant galleries 102 to the printhead chip 26 of the tiles 22.

- 10 -

An air supply channel 112 is also defined beneath the channel 94 for communicating with the air supply gallery 60 of the tiles 22 for blowing air over the nozzle layer 63 of each printhead chip 26.

5 In a similar manner to the conductive ribs 42 of the tile 22, the cover member 110 of the body 92 carries conductive ribs 114 on its outer surface 116. The conductive ribs 114 are also formed by a hot stamping during the molding of the cover member 110. These conductive ribs 114 are in electrical contact with a contact pad (not shown) carried on an outer surface 118 of a foot portion 120 of the printhead assembly 90.

10 When the printhead 10 is inserted into the channel 94, the conductive ribs 42 of the connector 44 of each tile 22 are placed in electrical contact with a corresponding set of conductive ribs 114 of the body 92 by means of a conductive strip 122 which is placed between the connector 44 of each tile 22 and the sets of ribs 114 of the body 92. The strip 122 is an elastomeric strip having transversely arranged conductive paths (not shown) for placing each rib 42 in electrical communication with one of the conductive
15 ribs 114 of the cover member 110.

Accordingly, it is an advantage of the invention that a printhead 10 is provided which is modular in nature, can be rapidly assembled by robotic techniques, and in respect of which manufacturing tolerances can be taken into account to facilitate high quality printing. In addition, a printhead assembly 90 is also able to be manufactured at
20 high speed and low cost.

It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as
25 illustrative and not restrictive.

CLAIMS:

1. A printhead which includes
a receiving member defining a receiving zone;
at least one printhead module received in the receiving zone of the receiving
5 member; and
complementary locating formations carried by the receiving member and said at
least one printhead module, the locating formations enabling relative movement of said
at least one printhead module, due to expansion, in three orthogonal axes relative to the
receiving member.
- 10 2. The printhead of claim 1 in which the receiving member is a channel shaped
member having opposed walls interconnected by a bridging portion to define a channel
which forms the receiving zone.
3. The printhead of claim 2 which includes a plurality of printhead modules
arranged in end-to-end relationship in the channel, each printhead module carrying a
15 printhead chip and adjacent modules abutting each other such that the printhead chips
of adjacent modules overlap.
4. The printhead of claim 3 in which each module is elongated, is stepped at its end
and the printhead chip is arranged at an angle to a longitudinal axis of the module.
5. The printhead of claim 3 in which each printhead module has a set of locating
20 formations and in which the channel of the channel shaped member has a
complementary set of locating formations at each module location in the channel.
6. The printhead of claim 5 in which,
the locating formations of the channel shaped member at each module location
include a pair of longitudinally spaced engaging formations arranged on one wall of the
25 channel and a securing means arranged on an opposed wall of the channel; and

- 12 -

the locating formations of each module include a pair of longitudinally spaced co-operating elements arranged along one side of each module for co-operating with the engaging formations and a complementary element on an opposed side of the module for co-operating with the securing means.

5 7. The printhead of claim 6 in which one combination of engaging formation and co-operating element serves to locate the module relative to the channel in a longitudinal direction, the other combination of engaging formation and co-operating element allowing longitudinal, expansionary displacement of the module relative to the channel.

10 8. The printhead of claim 7 in which the combinations of engaging formations and co-operating members, due to shapes of said engaging formations and co-operating members allows expansionary displacement of the module relative to the channel in a direction normal to a plane in which the module lies.

15 9. The printhead of claim 6 in which a combination of the securing means and the complementary element allows expansionary displacement of the module relative to the channel in a direction of a plane in which the module lies but normal to a longitudinal axis of the channel.

10. The printhead of claim 9 in which a width of the module is less than a spacing between the walls of the channel.

20 11. The printhead of claim 6 in which the securing means is a snap release carried on a resiliently flexible arm, the resiliently flexible arm forming part of said opposed wall of the channel.

25 12. The printhead of claim 11 in which the complementary element is a stepped recess defined in the module approximately midway along its length for receiving the snap release.

13. The printhead of claim 6 in which each engaging formation is in the form of a hemispherical projection which projects inwardly from said one wall of the channel.

- 13 -

14. The printhead of claim 13 in which a first co-operating element comprises a conical recess defined proximate a first end of the module and a second co-operating element comprises a slot, having a longitudinal axis extending parallel to the longitudinal axis of the channel, proximate a second end of the module, each of the
5 conical recess and slot receiving one of the hemispherical projections therein.
15. The printhead of claim 14 in which the slot has a triangular cross-section when viewed in a plane normal to the longitudinal axis of the slot.