

TITLE

A communication system node comprising a transformation matrix

TECHNICAL FIELD

- 5 The present invention relates to a node in a wireless communication system, the node comprising at least one antenna, which is arranged to cover a first sector in a first direction and comprises a number of antenna ports, which number is at least four.
- 10 The present invention also relates to a method in a wireless communication system node using at least one antenna covering a first sector in a first direction and having a number of antenna ports being at least four.

BACKGROUND

- 15 In a node in a wireless communication system, there is sometimes a need for re-using an antenna arrangement designed for a first cellular system in a second cellular system. However, the second cellular system may have requirements on the antenna arrangement which is different from the requirements of the first cellular system.
- 20 One example of such a situation is if an SCDMA (Spatial Code Division Multiple Access) system, a first cellular system, is to be migrated to a 3GPP (3rd Generation Partnership Project) LTE (Long Term Evolution) system, a second cellular system. The SCDMA system may have been deployed with array antennas that have more antenna ports than is needed for the
- 25 transmission modes used in LTE. A possible way to reuse the antennas in such a scenario is to split the sectors in the SCDMA system into two sectors for the LTE system. The number of antenna ports per sector in the LTE system is then half the number of antenna ports per sector in the SCDMA system.

Generally, a straightforward solution to this problem is to replace existing antennas with new antennas that are designed for the second cellular system. However, replacing antennas in an entire system is a very costly operation, making reuse of existing antennas an attractive alternative.

5

There is thus a desire to reuse an existing antenna arrangement which is to be used in a second cellular system but has been designed for a first cellular system, where the second cellular system has requirements on the antenna arrangement which is different from the requirements of the first cellular system

10

SUMMARY

The object of the present invention is to reuse an existing antenna arrangement which is to be used in a second cellular system but has been designed for a first cellular system, where the second cellular system has requirements on the antenna arrangement which is different from the requirements of the first cellular system

15

Said object is obtained by means of a node in a wireless communication system, the node comprising at least one antenna, which is arranged to cover a first sector in a first direction and comprises a number of antenna ports, which number is at least four. The antenna ports are connected to a transformation matrix which is arranged for transforming the antenna ports to at least a first set of virtual antenna ports and a second set of virtual antenna ports. Each set of virtual antenna ports comprises a number of virtual antenna ports, which number is less than or equal to half the number of antenna ports, but not falling below two. The sets of virtual antenna ports correspond to virtual antennas which are arranged to cover at least a second sector and a third sector in a corresponding second direction and third direction.

20

25

30

Said object is obtained by means of a method in a wireless communication system node using at least one antenna covering a first sector in a first direction and having a number of antenna ports being at least four. The method comprises the steps: connecting the antenna ports to a transformation matrix and using the transformation matrix for transforming the antenna ports to at least a first set of virtual antenna ports and a second set of virtual antenna ports, each set of virtual antenna ports having a number of virtual antenna ports. The number of virtual antenna ports is less than or equal to half the number of antenna ports, but not falling below two.

5 The sets of virtual antenna ports correspond to virtual antennas which are used to cover at least a second sector and a third sector in a corresponding second direction and third direction.

10

In an example of the present invention, the first direction is positioned between the second direction and the third direction.

15

In another example, the transformation matrix is arranged such that the virtual antennas have essentially equal antenna radiation patterns in each sector.

20

In another example, the node further comprises a radio remote unit, RRU, which in turn comprises corresponding amplifiers which are connected to corresponding antenna ports.

25 The transformation matrix may be realized in either hardware, software or a combination of hardware and software.

Other examples are evident from the dependent claims.

30 A number of advantages is obtained by means of the present invention. For example, a solution is provided for reusing antennas from one sectorized

cellular system to another when the requirements on the number of available antenna ports per sector are different in the two systems

BRIEF DESCRIPTION OF THE DRAWINGS

- 5 The present invention will now be describe more in detail with reference to the appended drawings, where:

Figure 1 shows a schematic view of a node according to the present invention;

10

Figure 2 shows a schematic view of an antenna arrangement and radio chains according to the present invention;

Figure 3 shows a schematic view of an antenna radiation pattern;

15

Figure 4 shows a schematic view of virtual antenna radiation patterns; and

Figure 5 shows a flowchart for a method according to the present invention.

20

DETAILED DESCRIPTION

With reference to Figure 1, there is a node 1 in a wireless communication system, where the node 1 comprising an antenna 2 which comprises four antenna ports 5, 6, 7, 8. With reference also to Figure 3, the antenna 2 is arranged to cover a first sector 3 in a first direction 4.

25

With reference also to Figure 2, the antenna 2 comprises antenna elements 20, 21, 22, 23, where each antenna element is connected to a corresponding antenna port 5, 6, 7, 8. Each antenna element is shown as a single antenna element, but this is only a schematical representation; each antenna element may in fact constitute an antenna element column comprising a number of

30

physical antenna elements. When the term “antenna element” is used below, it should be understood that it may refer to a single antenna element, as shown in Figure 2, or a a number of antenna elements in an antenna element column.

5

The beams of the antenna elements all point in the same direction, typically boresight, and have a beamwidth so that the desired sector coverage of said first sector 3 is obtained.

- 10 According to the present invention, the antenna ports 5, 6, 7, 8 are connected to a transformation matrix 9 which is arranged for transforming the antenna ports 5, 6, 7, 8 to a first set S1 of virtual antenna ports 10, 11 and a second set S2 of virtual antenna ports 12, 13. In this example, each set S1, S2 of virtual antenna ports has two virtual antenna ports 10, 11; 12, 13. These sets
15 S1, S2 are preferably connected to a main unit, MU, 29.

- With reference also to Figure 4, the sets S1, S2 of virtual antenna ports 10, 11; 12, 13 correspond to virtual antennas which are arranged to cover at least a second sector 14 and a third sector 15 in a corresponding second
20 direction 16 and third direction 17.

Thus the first sector 3 has been split into the second sector 14 and the third sector 15, where the second sector 14 is covered by the first set S1 of virtual antenna elements and the third sector 15 is covered by the second set S2 of virtual antenna elements.

- 25 For such a transition to be possible, the reconfiguration network 9 applied to the antenna ports 5, 6, 7, 8 is necessary. For example, if a reconfiguration network can be designed so that the resulting antenna arrangement properties are suitable for the LTE system, this provides a smooth migration path from an SCDMA system to LTE with regard to the antenna
30 arrangement.

According to an example, the virtual antenna elements have such properties such that the first set S1 of virtual antenna elements have a beam direction and width such that the desired coverage of the second sector 14 is obtained, while at the same time interference from/to adjacent sectors is minimized. The same should hold for the second set S2 of virtual antenna elements and the third sector 15.

According to another example, the virtual antenna elements should have displaced phase centers so that, for example, beamforming and codebook based precoding can be applied in the second sector 14 and the third sector 15.

According to another example, with reference to Figure 1 and Figure 2, the node 1 also comprises a so-called remote radio unit (RRU) 24, which is connected between the antenna ports 5, 6, 7, 8 and the transformation matrix 9, and comprises corresponding amplifiers 25, 26, 27, 28. This drawing shown is a simplified drawing of an RRU where only the transmitter chains are shown, there may also be not shown receiver chains, since the antenna 2 may work reciprocally within the frame of the present invention.

When an RRU or a similar amplifier arrangement is used, the transformation matrix 9 should be designed so that all amplifiers 25, 26, 27, 28 in the transmitter chains are better or almost fully utilized.

In the following, a detailed example of the present invention will be presented with reference to Figure 2. In this example, there are four antenna elements 20, 21, 22, 23 covering a 120° sector. The transformation matrix 9 creates two sets S1, S2 of virtual antenna elements with two elements in each set. The two sets S1, S2 of virtual antenna element are arranged to cover a 60° sector each, and thus together cover the original 120° sector. The antenna elements 20, 21, 22, 23 are here co-polarized.

The transformation matrix, **W**, is constructed by stacking array weight vector as columns according to

$$\mathbf{W} = [\mathbf{w}_{B,1} \quad \mathbf{w}_{B,2} \quad \mathbf{w}_{C,1} \quad \mathbf{w}_{C,2}],$$

where each $\mathbf{w}$ is a 4x1 complex weight vector. The vector $\mathbf{w}_{B,1}$ creates beam number 1 in sector B, and so forth. The following design of weight vectors will make the transformation matrix satisfy the desired requirements:

5

$$\mathbf{w}_{B,1} = \frac{1}{\sqrt{2}} \begin{bmatrix} 0 & c e^{j2\pi d_1/\lambda \sin \varphi} & \sqrt{1-c^2} e^{j2\pi d_2/\lambda \sin \varphi} & e^{j2\pi d_3/\lambda \sin \varphi} \end{bmatrix}^T$$

$$\mathbf{w}_{B,2} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & \sqrt{1-c^2} e^{j2\pi d_1/\lambda \sin \varphi} & c e^{j2\pi d_2/\lambda \sin \varphi} & 0 \end{bmatrix}^T$$

$$\mathbf{w}_{C,1} = \frac{1}{\sqrt{2}} \begin{bmatrix} 0 & c e^{-j2\pi d_1/\lambda \sin \varphi} & \sqrt{1-c^2} e^{-j2\pi d_2/\lambda \sin \varphi} & e^{-j2\pi d_3/\lambda \sin \varphi} \end{bmatrix}^T$$

$$\mathbf{w}_{C,2} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & \sqrt{1-c^2} e^{-j2\pi d_1/\lambda \sin \varphi} & c e^{-j2\pi d_2/\lambda \sin \varphi} & 0 \end{bmatrix}^T$$

- 10 Here, d_k denotes the position along the antenna axis relative to a reference point of the k -th antenna element and λ is the carrier wavelength. Furthermore, c and φ are design parameters that control the resulting beam pattern of the virtual antenna elements. The amplitude taper coefficient, c , affects the beamwidth and sidelobe level, while the phase φ controls the
- 15 pointing direction of the beams. These design parameters can be optimized with respect to a desired criterion function. Such a criterion could include, for example, sidelobe levels and cross-over levels between adjacent sectors.

The proposed solution has the following key features, making it satisfy the desired requirements:

1. Since

$$|\mathbf{w}_{B,1,k}|^2 + |\mathbf{w}_{B,2,k}|^2 + |\mathbf{w}_{C,1,k}|^2 + |\mathbf{w}_{C,2,k}|^2 = 1, \quad k = 1, \dots, 4,$$

where $\mathbf{w}_{B,1,k}$ denotes the k-th element in $\mathbf{w}_{B,1}$, all power amplifiers are fully utilized.

5 2. Since $\mathbf{w}_{B,1,1} = \mathbf{w}_{B,2,4} = 0$ and $\mathbf{w}_{C,1,1} = \mathbf{w}_{C,2,4} = 0$ the virtual antenna elements will have displaced phase centers, enabling beamforming and codebook based precoding.

10 3. By a judicious choice of the design parameters c and φ , the beampatterns of the virtual elements can be designed so that desired coverage of the respective second sector 14 and third sector 15 is obtained.

The paragraphs (1) - (3) above are a part of the present example, and are not necessary for the present invention in its general form.

15 With reference to Figure 5, the present invention also relates to a method in a wireless communication system node using at least one antenna 2 covering a first sector 3 in a first direction 4 and having a number A of antenna ports 5, 6, 7, 8 being at least four. The method comprises the steps:

20 30: connecting the antenna ports 5, 6, 7, 8 to a transformation matrix 9; and

31: using the transformation matrix 9 for transforming the antenna ports 5, 6, 7, 8 to at least a first set S1 of virtual antenna ports 10, 11 and a second set S2 of virtual antenna ports 12, 13, each set S1, S2 of virtual antenna ports
25 having a number B of virtual antenna ports 10, 11; 12, 13, the number B of virtual antenna ports 10, 11; 12, 13 being less than or equal to half the number A of antenna ports 5, 6, 7, 8, but not falling below two, the sets S1, S2 of virtual antenna ports 10, 11; 12, 13 corresponding to virtual antennas

which are used to cover at least a second sector 14 and a third sector 15 in a corresponding second direction 16 and third direction 17.

The invention is not limited to the above examples, but may vary freely within the scope of the appended claims. For example, the example of four antenna
5 columns is just an illustration to explain the concept. As discussed previously, the number of antenna elements can be any suitable number for each column, generally the concept could be applied to an antenna with N antenna elements. The sector covered by the physical antenna elements is then split into two sectors covered by N/2 virtual antenna elements each.

10 Although described for single polarized antenna elements, the concept can also be applied to dual-polarized array antennas. The proposed transformation matrix is then applied on each polarization. Then, for a certain sector that is covered by virtual antenna elements, the virtual antenna elements of the same polarization should have different phase centers, but it
15 is not necessary that the virtual antenna elements of different polarizations or virtual antenna elements covering different sectors should have different phase centers.

The number A of antenna ports may vary, but is at least four. Each set S1,
20 S2 of virtual antenna ports have a number B of virtual antenna ports 10, 11; 12, 13, which number B of virtual antenna ports 10, 11; 12, 13 is less than or equal to half the number A of antenna ports 5, 6, 7, 8, but not falling below two.

25 The node can comprise any suitable antenna arrangement, for example a 3-sector system comprising three antennas, the beamwidth typically being 65° or 90° for a 3-sector system.

The weight vectors described are only defined by way of examples. Many
30 other weight vectors are conceivable.

It is also possible to use the present invention to reduce the number of antenna ports from N to $N/2$ without increasing the number of sectors, e.g., reconfigure 8 antenna ports in a 3-sector system to 4 antenna ports in a 3-sector system.

5

The transformation matrix may be placed in the RRU, and may be realized in hardware as well as software, or a combination of both.

10 The sets $S1$, $S2$ are preferably connected to a main unit, MU, 29, but may of course be connected to any other suitable part.

When the virtual antennas are indicated to have equal antenna radiation patterns in each sector in this context, this is not meant as those radiation patterns being mathematically exactly equal, but equal to an extent of what is
15 practically possible to achieve in this field of technology.

CLAIMS

1. A node (1) in a wireless communication system, the node (1) comprising at least one antenna (2), where the antenna (2) is arranged to cover a first sector (3) in a first direction (4) and comprises a number (A) of antenna ports (5, 6, 7, 8), which number (A) of antenna ports (5, 6, 7, 8) is at least four, **characterized in** that the antenna ports (5, 6, 7, 8) are connected to a transformation matrix (9) which is arranged for transforming the antenna ports (5, 6, 7, 8) to at least a first set (S1) of virtual antenna ports (10, 11) and a second set (S2) of virtual antenna ports (12, 13), each set (S1, S2) of virtual antenna ports comprising a number (B) of virtual antenna ports (10, 11; 12, 13), which number (B) of virtual antenna ports (10, 11; 12, 13) is less than or equal to half the number (A) of antenna ports (5, 6, 7, 8), but not falling below two, where the sets (S1, S2) of virtual antenna ports (10, 11; 12, 13) correspond to virtual antennas which are arranged to cover at least a second sector (14) and a third sector (15) in a corresponding second direction (16) and third direction (17).
2. A node according to claim 1, **characterized in** that the first direction (4) is positioned between the second direction (16) and the third direction (17).
3. A node according to any one of the claims 1 or 2, **characterized in** that the transformation matrix (9) is arranged such that the virtual antennas have equal antenna radiation patterns (18, 19) in each sector (14, 15).
4. A node according to claim 3, **characterized in** that, for each polarization, the phase centres of the virtual antennas that are arranged for covering a certain sector are separated by more than 0.4 wavelengths, where the wavelength corresponds to the centre of the frequency band used.

5. A node according to any one of the previous claims, **characterized in** that the antenna (2) comprises co-polarized antenna elements (20, 21, 22, 23).

5 6. A node according to any one of the previous claims, **characterized in** that the node (1) further comprises a radio remote unit, RRU, (24) which in turn comprises corresponding amplifiers (25, 26, 27, 28) which are connected to corresponding antenna ports (5, 6, 7, 8).

10 7. A node according to any one of the previous claims, **characterized in** that the transformation matrix (9) is realized in either hardware, software or a combination of hardware and software.

8. A node according to any one of the previous claims, **characterized in** that the transformation matrix (9) is constructed by stacking
15 array weight vector as columns according to

$$\mathbf{W} = [\mathbf{w}_{1,1} \quad \dots \quad \mathbf{w}_{k,n} \quad \dots \quad \mathbf{w}_{K,N}]$$

where each $\mathbf{w}$ is a complex weight vector and vector $\mathbf{w}_{k,n}$ creates beam number n in sector k , and where K denotes the number of sectors and N denotes the number of beams per sector.

20

9. A method in a wireless communication system node using at least one antenna (2) covering a first sector (3) in a first direction (4) and having a number (A) of antenna ports (5, 6, 7, 8) being at least four, **characterized in** that the method comprises the steps:

25 (30) connecting the antenna ports (5, 6, 7, 8) to a transformation matrix (9);
and

(31) using the transformation matrix (9) for transforming the antenna ports (5, 6, 7, 8) to at least a first set (S1) of virtual antenna ports (10, 11) and a second set (S2) of virtual antenna ports (12, 13), each set (S1, S2) of virtual

30 antenna ports having a number (B) of virtual antenna ports (10, 11; 12, 13),

the number (B) of virtual antenna ports (10, 11; 12, 13) being less than or equal to half the number (A) of antenna ports (5, 6, 7, 8), but not falling below two, the sets (S1, S2) of virtual antenna ports (10, 11; 12, 13) corresponding to virtual antennas which are used to cover at least a second sector (14) and
5 a third sector (15) in a corresponding second direction (16) and third direction (17).