

COMPACT LIQUID CONTAINER

The present invention relates to a liquid container, in particular to a liquid container system with a dispensing mechanism and to a liquid dispensing system and method of
5 using the liquid container.

Conventionally, many liquid products, for example perfume, liquid soap, moisturiser, etc., are sold in containers equipped with a delivery mechanism that dispense a controlled amount of the content of the containers, the
10 most common being a pump mechanism which, when pressed, delivers the product in its original liquid form or in the form of mist or foam. The design of the container and delivery mechanism is central to such a product, as the aesthetics of the container often draw in custom and a
15 well-designed dispensing system not only adds to the aesthetics of the product, but ensures that the optimal amount of the liquid content is delivered to the user in a desirable form.

However, it is often inconvenient for the user to
20 transport a liquid product in its "standard pack" container when travelling, for overnight stays, or, especially for perfume and after-shave, carry the product in handbags or briefcases. In some cases, it would even be impossible for the user to transport a product in its standard pack, for
25 example because of restrictions imposed on hand baggage for air travellers.

The user often resorts to transferring an amount of the liquid product from its original container to a smaller container, which is an inconvenience to the user, and often
30 results in spillage or contamination. For some products, it may not be possible for the user to transfer the content from the original container to another container, for example if the original container is sealed and the content is to be dispensed as mist or foam.

Manufacturers of liquid products may provide the products in smaller "travel packs", but it may not be cost-effective to incorporate the same delivery mechanism used in a standard pack into the smaller, and so necessarily
5 cheaper, travel pack.

The discrepancy of delivery mechanism between the standard pack and the travel pack of a product is undesirable for the manufacturers, especially for luxury brand products for which packaging is an important aspect
10 of the product. Moreover, travel packs by design are not intended for long-term use, and so are wasteful of resources.

US 7066674 (L'Oreal) discloses a device for applying a liquid product, comprising a receptacle for containing the
15 liquid, and a removable unit configured to be removably positioned on the receptacle. An application element (such as a sponge or a felt) for applying the liquid is housed within the removable unit. When the removable unit is positioned on the receptacle, the application element can
20 be loaded with the liquid from the receptacle by actuating a suitable mechanism such as a pump.

However, the removable unit of the device of US 7066674 is only able to retain a small amount of the liquid product limited by the application element. Thus, as described
25 therein, the removable unit is only capable of a few applications. Moreover, after the application element is loaded, the liquid will inevitably evaporate, and a user may find him/herself in situations where the removable unit is removed and taken away for later application without the
30 user realising that the liquid product has evaporated or the application element has not been loaded. Also, designs of this kind do not solve the problem of incorporating a dispensing unit, such as a spray, in a travel fixture.

It is therefore desirable to provide a liquid container
35 that can accommodate travel requirements, while minimising

wastage of resources and preserving the consistency of products, which is simple and convenient to use.

In their earlier application PCT/GB 2010/050205 the inventors have disclosed a two-part liquid container system that comprises a parent container for containing the main reservoir of liquid and a refillable child container for containing and dispensing liquid, which can be attached to the parent container for normal use, drawing liquid from the parent container, or for refilling, and can be detached from it for easy transport. The parent container provides a first cavity for confining a liquid, and is configured to couple detachably to the child container for refilling the child container through a supply opening in the parent container. The child container provides a second cavity for confining a liquid, and comprises a dispensing mechanism for dispensing liquid from the second cavity through a dispense opening, and a fluid transfer assembly, preferably including a valve assembly, for controlling liquid flow from the parent container into the child container through a refill opening. The first valve assembly is configured to form a channel between the first cavity and the second cavity to allow liquid flow when the parent container is coupled to the child container. The container system further includes a movable part which, in one direction of travel, urges liquid from the parent container to the child container, coupling of the child container to the parent container leading to movement of the movable part so as to cause an amount of liquid to pass from the first cavity into the second cavity, ensuring that the child container is filled when connected to the parent container.

The moving part is preferably in the child container, which preferably further comprises a restoring means that stores a restoring force as liquid is expelled from the second cavity by the dispensing mechanism. When the child container is separated from the parent container, dispensing of liquid causes the second cavity to contract,

the moving part being connected to, or forming part of the wall of, the second cavity. When the parent container and the child container are coupled together again, the restoring means releases the restoring force so as to
 5 expand the second cavity to the original state, urging the moving part back to its initial position, thereby drawing liquid from the first cavity into the second cavity.

With the earlier invention a travel or "child" container can thus be recharged a large number of times
 10 from a "parent" container containing liquid at atmospheric pressure. Moreover, this happens automatically whenever the two are coupled together. Meanwhile, the coupled container system can be used as a unit in the familiar way.

A first aspect of the present invention provides a
 15 compact dispenser for liquids, comprising a bowl or tray-shaped rigid container with an open face, the container having a refill opening, and a dispense opening, these openings being located with a spacing from each other; wherein the open face of the bowl is covered by a
 20 deformable membrane to form a closed dispense cavity adjacent to the refill opening, the volume of the cavity being reduced as the membrane is deformed inwardly so as to empty the cavity, wherein the dispenser is a free-standing container which can be connected to a supply container by
 25 way of the refill opening, and separated from it again, and the refill and dispense openings are such that if the dispenser is applied to the supply container by way of the refill opening, with the cavity initially empty, when the membrane is subsequently allowed to spring back to its rest
 30 shape it draws liquid from the parent into the cavity, while when the dispenser is separated from the supply container the refill opening is closed by a valve.

The present invention represents a further development of this idea and is concerned with a child container as
 35 claimed in claim 1. Here the moving part and the restoring means can be one and the same, namely a membrane which

partly defines the cavity in the child container ("second cavity"). The former application does disclose a membrane embodiment, namely in Figure 9. However, here the membrane 127c is so to speak radial - that is, across the direction of liquid flow from the inlet to the outlet of the (child) container. This means that it has to be penetrated by or connected to the tube or needle 123c. As a consequence, in the first place, manufacture and maintenance of a seal is not easy, and in the second place, the membrane's freedom to move and flex is considerably constrained. In the present invention, by contrast, the membrane helps to define a cavity adjacent to the refill opening; that is, the membrane is not penetrated by the liquid as the cavity is being filled from the main container.

If the cavity is of a simple shape, with no sharp angles or recesses, the membrane, if sufficiently elastic, can deform so as to empty the cavity virtually completely, reducing waste and allowing a compact format of the child container. Moreover, the seal is easy to make, being fixed, and no sliding parts are necessary.

The membrane can be made of any suitable material, such as rubber or synthetic rubber, provided that it is proof against the liquid used, and in particular the solvent, in the case of a fragrance.

The cavity can be in the form of a shallow cylinder, with the large "drum" face, or one of them occupied by the membrane stretched across it, and the liquid entering and leaving more or less across the diameter. As the container is emptied, the membrane is sucked in until it covers the floor and sides of the cavity. The edge of the drum opposite the membrane should be rounded off, to allow the membrane to lie flat against the rigid inner surface of the cavity. In general, if the cavity has a shape in which one face is larger than the other or others, i.e. a large flat face, that face should be occupied by the membrane.

Alternatively the dispenser can be spherical, half being rigid and the other half being the membrane, whose rest configuration is a sphere, like a squash ball half. The membrane is deformed inwardly before the container is
 5 applied to the parent, to suck up a defined quantity of liquid.

A second aspect of the present invention provides a container system for liquids, including a parent container and a child container, in which the parent container
 10 provides a storage cavity for confining a liquid, and is configured to couple detachably to the child container for refilling the child container through a supply opening in the parent container, and the child container is a dispense container according to any preceding claim

15 A third aspect of the present invention provides a container system for liquids, including a parent container and a child container, in which the parent container provides a storage cavity for confining a liquid, and is configured to couple detachably to the child container for
 20 refilling the child container through a supply opening in the parent container; the child container comprises a refill opening, which is kept closed by a valve unless the dispenser is connected to the parent container, and a dispense opening, these openings being located with a
 25 spacing from each other; and a dispense cavity adjacent to the refill opening, whose volume is reduced as liquid is dispensed, the refill and dispense openings being such that if the dispenser is applied to a suitable parent container by way of the refill opening, with the cavity initially
 30 empty, a resilient component draws liquid from the parent into the cavity; in which the connection between parent and child containers is magnetic.

The term "comprising" as used in this specification and claims means "consisting at least in part of". When
 35 interpreting statements in this specification and claims which include the term "comprising", other features besides

the features prefaced by this term in each statement can also be present. Related terms such as "comprise" and "comprised" are to be interpreted in a similar manner.

For a better understanding of the present invention,
 5 various examples will now be explained with reference to the accompanying drawings, in which:

Figure 1A shows a container system representing an embodiment in PCT/ GB 2010/ 50265;

10 Figure 1B shows a line drawing of the container system of Figure 1A;

Figure 2 shows the cap portion of a container system in the Figure 9 embodiment of the earlier application;

15 Figures 3A and 3B show an embodiment of the present invention;

Figures 4 and 5 show a different embodiment, with the dispense valve on the membrane;

Figure 6 shows a variant; and

Figure 7 shows a further embodiment in bottle form

20 The general scheme to which the present invention relates is shown in Figures 1A and 1B as a bottle (liquid container system) 100, comprising a main body (parent container) 110, which can be made of glass, plastic or any suitable material, and a refillable cap portion (child
 25 container) 120, which is detachably secured to the main body 110 by means of a securing mechanism 130, here a screw thread, though it could also be, say, a bayonet or clip-on mechanism

The main body 110 has an opening (supply opening) 111,
 30 which is occupied by or connected to a valve 112. When the main body 110 is separated from the cap portion 120 the valve 112 is closed, providing a sealed cavity 113 for confining a liquid therein. The cavity 113 holds a tube 114, which extends from the supply opening towards the
 35 bottom of the cavity 113, for extracting the liquid content

from the cavity 113 through the tube 114. Air flow into the main body 110 is controlled by a one-way valve 118. The sealing valve 112 and the tube 114 form a valve assembly providing a passage from the cavity 113 to outside
 5 the main body 110 through the valve 112.

The cap portion 120 comprises a casing 121, which is typically metal or plastic. The casing 121 is in several parts, secured together, and provides a support structure for mounting the components of the cap portion 120 and can
 10 be in any shape or form. In particular, it can be designed in the same style as a simple cap for a main container having a spray head.

Within the casing 121, the cap portion 120 contains a collapsible container in the form of a bellows 122a. The
 15 bellows forms a collapsible chamber or compartment that can be expanded to draw in fluid through a valve and contracted to expel it through a suitable outlet such as a spray dispenser. The upper opening (the dispense opening) of the bellows 122a is coupled to a pump mechanism 125, thus
 20 creating a sealed cavity 126 inside the bellows 122a, in which a liquid can be confined. When the pump mechanism 125 is actuated, the content of the bellows 122a is expelled through the opening, in this case as a mist.

Initially the bellows is in a filled state with liquid
 25 in the cavity 126, as shown in Figure 1B. The cap portion 120 can then be detached, whereupon the valve 124 seals. Since the bellows 122a, the valve assembly 123a and 124 and the pump mechanism 125 form a sealed system when liquid is expelled from the cavity 126 by the action
 30 of the pump mechanism 125, the decrease in the volume of liquid causes the bottom 122b of the bellows 122a to be pushed upwards into the cavity 126 under atmospheric pressure, thus causing the bellows 122a to collapse. As the bellows collapses, an expansion force is built up in
 35 the bellows 122a as it is being compressed.

When it is desirable to refill the cap portion 120, or simply convenient to use the cap portion 120 and the main body 110 as a single combined unit, the cap portion 120 is placed onto the main body 110, and screwed into position by the securing mechanism 130. When the cap portion 120 is in position, the valve 112 of the main body 110 and the valve 124 of the cap portion 120 push against each other and force the valve bodies to retreat into the respective cavities, thus opening up a channel from the cavity 113 of the main body 110 into the cavity 126 of the bellows 122a. This channel is sealed by various O rings as shown.

As a result of the valve 124 of the cap portion 120 being opened, the cavity 126 of the bellows 122a is no longer sealed. Thus, the force built up in the bellows 122a can now be released, allowing the bottom 122b of the bellows 122a to travel down and expanding the bellows 122a again, which results in a suction force that extracts liquid from the cavity 113 of the main body 110 by drawing air in through the air valve 118 in the main body 110. The liquid then travels through the tube 114, the valves 112 and 124, and the tube 123a, into the bellows 122a.

Note that the action of the bellows 122a drawing liquid from the main body 110 commences automatically as soon as the cap portion 120 is coupled to the main body 110 without further action or prompting from the user. In this way, the present invention ensures that the cap portion 120, which can be used separately from the main body 110, is always full when the user detaches the cap portion 120 from the main body 110 again. Thus, the user will never find him/herself in a situation where the cap portion 120 is taken away on holiday, only to discover that it is empty on arrival at the destination.

In addition, although the cap portion 120 can be used for dispensing the liquid product as a separate unit detached from the main body 110, it is likely to be used

more often as a combined unit 100 in which the cap portion 120 is coupled to the main body 110 for reasons of convenience and easy storage. In this case, since the tube 114, the valve 112, the valve 124 and the tube 123a
 5 form a channel between the cavity 113 of the main body 110 and the cavity 126 of the cap portion 120, as the pump mechanism 125 is actuated, liquid is drawn directly from the main body 110, in a manner similar to a conventional spray bottle. Thus, it is more convenient for the user to
 10 use the product when there is no need to detach the cap portion 120 from the main body 110, for example, when using the product at home. During such operation the bellows 122a of the cap portion 120 is always full, until the main supply is exhausted.

15 When the cap portion 120 is detached, a spring provided to each of the valves 112 and 124 returns the respective valve to its original position. Since the valves 112 and 124 are being pushed away from their respective cavities 113 and 126, a temporary vacuum/low pressure is
 20 created in the cavities, which causes any liquid droplets that may have remained on the tip of each valve to be sucked back through the valves into the cavities, thus leaving both the main body 110 and the cap portion 120 dry.

A variant to the first type is shown in Figure 2, where
 25 an elastic diaphragm 127 is attached to the inner wall of the casing 121 of the cap portion 120. The diaphragm defines a cavity 126 where liquid is confined, and the cavity 126 is sealed at one end by a valve 124 and at the other end by a pump 125. The diaphragm 127 is sealed
 30 around a central axial tube or needle 123c conducting liquid from the base region of the cap, at the valve, to the upper region. As liquid is expelled from the cavity 126 by the pump 125, the diaphragm 127 is pushed up into the cavity 126 under atmospheric pressure, thus
 35 stretching it. When the cap portion 120 is coupled to the main body 110, the valves 124 and 112 provide a sealed channel for liquid to travel freely between the cavity 113

of the main body and the cavity 126 of the cap portion 120, allowing the diaphragm 127 to release the stored elastic force, drawing liquid into the cavity 126. This corresponds to Figure 9 of the earlier application.

5 The present invention uses the same principle but with a different child container. An embodiment is shown in Figures 3A and 3B. The child container or cap portion 220 is in this purely arbitrary example in the shape of a shallow cylinder or pillbox, fluid entering at the side of
10 the cylinder (which could be at the bottom in normal use) via a refill opening 222 and exiting diagonally opposite at a dispense opening 224 via a push-button pump 225. These items can be similar to those in other embodiments.

 The child container, having this pillbox or drum shape,
15 has two large faces of which one is visible in the drawing. The far face is solid in this embodiment, but the visible face is constituted over most of its area by a circular membrane 227 held in place by an O ring 228a lying in a groove in the cylinder wall and itself pressed by a sealing
20 ring 228.

 The cavity 226 between refill and dispense openings is thus bowl-shaped. Preferably, the bottom edge of the bowl, indicated generally by the dotted line 226a, is not a sharp corner but is rounded, so that when the cavity is evacuated
25 the membrane can lie closely against the solid walls of the cavity.

 In operation, the child container 220 is filled by connecting it to the parent container (not shown here), the natural resilience of the membrane 227 serving as a
30 restoring means to suck the liquid in, provided that the child container is initially evacuated (Figure 3B) so that the membrane lies off the floor of the cavity. The dispenser, once filled as shown in Figure 3A, can then be used with the child container in situ on the parent

container. In this case, the membrane plays no significant part in the operation of the device.

However, if the child container is removed, a valve in the refill opening 222 closes and the child container
 5 operates as a stand-alone dispenser. As liquid is dispensed, the membrane is drawn in to the bowl-shaped cavity. It has been found that the cavity can be more or less completely evacuated (less than 1%) as the pump is operated.

10 When the child container is re-applied to a parent container, the non-return valve in the refill opening 222 is opened and the membrane pulls back to its flat configuration, drawing liquid into the cavity.

The example here has a separate membrane held in place
 15 by a sealing ring. However, it would be possible to mould the membrane in place in situ, which would further improve the robustness of the device.

A further variant would be to make the membrane out of a somewhat thicker material but in a "flat-bellows" form
 20 that is, having a stepped construction not unlike a Fresnel lens. This structure would be capable of deformation in a direction perpendicular to its plane so as to fulfil the same function as a stretching membrane.

The container need not be circular in shape as shown,
 25 but could be any shape as required by function or aesthetics. However, sharper internal corners should be avoided. In general, the membrane should be applied over a face of the cap portion that represents its largest dimension, so that the membrane does not have to deform
 30 perpendicularly to its face by more than, say, half its diameter.

As well as being usable as a fragrance dispenser, the simple diaphragm option would be applicable wherever it is desirable to fill a smaller container from a very large

container. For example, it is more convenient to transfer clothes washing liquid detergent from a large 5- to 10-litre container, which is difficult to lift and pour into a washing machine, into a smaller hand-sized container such as a detergent ball, which can then be put into the machine. An embodiment of this kind is shown in Figures 4 and 5.

As shown in Figure 4B, the ball has a rigid half-spherical side 321 and a domed diaphragm 327 forming the other half, sealed at the equator, so completing the spherical shape. The diaphragm 327 has mounted on it a manual valve 325 as a passive release mechanism. Theoretically this valve could be mounted in the rigid wall, but there is not much room and the design shown is more intuitive to use.

The valve 325 is made of two plastic overlapping discs, each having two holes 325a located along a diameter. The discs are mounted so as to rotate about their common axes, so that when the pairs of holes line up the valve is open and when they have no overlap (i.e. at 90°) the valve is shut.

To fill the ball the user opens the valve, and squeezes the air out to the required volume of detergent required. He then closes the valve by turning the outer disc, so that the interior of the ball is sealed. This is shown in Figure 4A. The ball is then attached to the large container, as shown in Figure 5. This attachment opens the refill opening 322, as will be described, and the resilience of the membrane fills the child container 320, the compressed diaphragm expanding so as to fill the ball with the required amount of liquid.

When the ball is removed from the parent, as shown in Figure 5 at (c), the refill opening 322 automatically closes again. The dispense opening of the ball is then opened again by turning the valve disc back, so as to allow

liquid to pass from the ball into the machine during washing.

For "coarse" applications such as washing liquid, or any high-viscosity liquid, the valves do not have to seal 100% here the valve in the refill opening can be simply in the form of a membrane covering an opening, the membrane itself having a small, perhaps star-shaped, perforation that is closed when the membrane is allowed to relax but is opened by a nose 312a of the connector piece 312 of the parent container, when the ball is applied to the connector piece.

In an alternative configuration the valve in the dispense aperture could be heat-operated and still be sealed when put into the machine, opening when it comes into contact with the warm water via a bimetallic strip opener for example, or just by the heating of the material.

It will be observed that even though the dispense opening can be in the membrane in this kind of embodiment, the refill process does not involve the liquid passing through the membrane. Thus in turn the full flexibility of the membrane can be used for the filling process.

Figure 6 shows a variant embodiment of the previous type, in which the natural resilience of the membrane 327a is at it were augmented by a spring 340. The spring extends from the refill opening to the dispense opening and urges them axially apart. The membrane 327a could even be completely flaccid, though that would probably be less acceptable from an aesthetic point of view.

If the diaphragm pack is used to fill a standard portable container from the mother, it would work in a similar manner to the fragrance pack. There would be a means to squeeze/pump/dispense the liquid out into washing machine drawer and still maintain the vacuum inside.

Such an embodiment could work for any liquid where buying larger volumes - say over 5 litres - would make it preferable to transfer cleanly into much smaller manageable packs. Liquids could include Engine Oil, Petrol, Hair
 5 Shampoos/ Conditioners, Shower Gels, Fruit Juices, Fruit Juice Concentrates etc.

By having such large parent packs and possibly a high-value child pack, the material and therefore the environmental savings would be very high.

10 Figure 7 shows a version in which the child container is a refillable bottle dispenser 420, such as can be used for soap. The generally flat body 421 has two membranes 427, one of which is visible, and a pump 425. The refill opening 422 is attached by a screw fitting on a
 15 connector piece 412 of the bottle 410, which can be similar to that of Figure 5.

Figure 8 shows a yet further embodiment in which the connection between child and parent containers is magnetic. The general format of the containers is cuboid, the
 20 horizontal cross-sections being the same, as is the case with many perfume dispensers. The connection piece 512 of the parent is a rectangular magnetic plate, matching the general contours and penetrated in the middle by a tube 513 extending from the main perfume cavity in the parent 510.
 25 With the containers separated, the tube 513 is closed by a valve, not shown.

The body of the child container 520 is of steel, with a recess for the pump 525 and a larger recess containing the collapsible cavity. The latter may be in the form of a
 30 bellows, similar to that of Figure 1, or a membrane container as in previous embodiments. Preferably the body 520 is not itself (ferro)magnetic, because otherwise it would tend to interfere with devices, such as credit cards, that are generally carried in handbags.

An advantage of a connection system of this type is its very low height compared to, say, a screw or catch connection.

In further embodiments, the main body may also be
5 wholly or partly flexible, such as a sealed collapsible plastic bag, which can be implemented as a closed system. In this case, as the liquid content is being extracted from the main body, no air is let in to replace the volume of the extracted liquid; consequently the main body collapses
10 under atmospheric pressure. This can be used as a cost-saving option for providing spill-free refill of a liquid product such as liquid soap.

It will be seen that the main body and the refillable portion do not necessarily form a single unit, and can be
15 two independent containers. For example, the refillable portion can be a stand-alone consumer product such as luxury moisturiser, and the main body can be kept at specialist shops where the owner of a refillable portion may purchase a refill.

20 Other delivery systems may be used in the refillable portion to allow automatic or actuated slow release or shot release of the content, for example in place of dishwasher tablets.

WHAT WE CLAIM IS:

1. A compact dispenser for liquids, comprising a bowl or tray-shaped rigid container with an open face, the container having a refill opening, and a dispense opening, these openings being located with a spacing from each other;

wherein the open face of the bowl is covered by a deformable membrane to form a closed dispense cavity adjacent to the refill opening, the volume of the cavity being reduced as the membrane is deformed inwardly so as to empty the cavity, wherein the dispenser is a free-standing container which can be connected to a supply container by way of the refill opening, and separated from it again, and the refill and dispense openings are such that if the dispenser is applied to the supply container by way of the refill opening, with the cavity initially empty, when the membrane is subsequently allowed to spring back to its rest shape it draws liquid from the parent into the cavity, while when the dispenser is separated from the supply container the refill opening is closed by a valve.
2. A dispenser according to claim 1, further including a pump for dispensing liquid from the dispense opening, the cavity becoming mainly or completely evacuated as the dispensing means is operated.
3. A dispenser according to claim 1 or 2, in which the rigid container is generally round in outline and the refill and dispense openings are located approximately at opposite ends of a diameter.
4. A dispenser according to any preceding claim in which the bowl has a lip defining the open face, the bowl has a groove, and the membrane is retained in this groove by a sealing ring.

5. A dispenser according to any one of claims 1 to 3, in which the membrane is integral with the bowl.
6. A dispenser according to claim 1, in which the dispenser is generally spherical, the rigid container being approximately a hemisphere and the membrane approximately the other half.
7. A dispenser according to claim 6, in which the dispense opening takes the form of a manual valve.
8. A dispenser according to claim 7, in which the valve is located on the membrane.
9. A dispenser according to any preceding claim and including an auxiliary restoring means assisting the membrane to return to the full configuration.
10. A dispenser according to claim 1 and having the form of a flat-sided bottle, one or each flat side being constituted by a membrane.
11. A container system for liquids, including a parent container and a child container, in which
 - the parent container provides a storage cavity for confining a liquid, and is configured to couple detachably to the child container for refilling the child container through a supply opening in the parent container, and
 - the child container is a dispense container according to any preceding claim
12. A container system according to claim 11, wherein the membrane urges liquid from the parent container to the child container when the child container is coupled to the parent container, so as to cause an amount of liquid to pass from the first cavity into the second cavity, ensuring that the child container is filled when connected to the parent container.

13. A container system according to claim 11 or 12, wherein the child is attached to the parent by a magnetic connection.
14. A container system for liquids, including a parent container and a child container, in which
 - the parent container provides a storage cavity for confining a liquid, and is configured to couple detachably to the child container for refilling the child container through a supply opening in the parent container;
 - the child container comprises a refill opening, which is kept closed by a valve unless the dispenser is connected to the parent container, and a dispense opening, these openings being located with a spacing from each other; and a dispense cavity adjacent to the refill opening, whose volume is reduced as liquid is dispensed, the refill and dispense openings being such that if the dispenser is applied to a suitable parent container by way of the refill opening, with the cavity initially empty, a resilient component draws liquid from the parent into the cavity;
 in which the connection between parent and child containers is magnetic.
15. A container system according to claim 13 or 14, wherein the child container does not contain a magnet.
16. A dispenser according to claim 1, substantially as herein described with reference to any embodiment disclosed.
17. A compact dispenser for liquids, substantially as herein described with reference to any embodiment shown in Figures 3A to 8.

18. A container system according to claim 11 or 14, substantially as herein described with reference to any embodiment disclosed.
19. A container system for liquids, substantially as herein described with reference to any embodiment shown in Figures 3A to 8.