

DEVICE FOR PRODUCING A STREAM OF AIR THROUGH A VOLUME OF LIQUID

Technical field

The present invention relates to the production of a stream of air
5 through a volume of liquid. It in particular applies to various fields, for
example including, but not limited to, the production of a stream of air that is
heated or cooled upon passing through said volume of liquid, the production
of a stream of air whereof the temperature is controlled and/or whereof the
absolute humidity is controlled, the humidification or dehumidification of a
10 stream of air, the cleanup or filtration of a stream of air, the heating or air-
conditioning of greenhouses, the heating or air-conditioning of industrial,
service or household sites or buildings, monitoring the hygrometry of
industrial, service or household sites or buildings. The produced stream of
air may also be used to cool, heat, humidify or dehumidify any type of
15 surface.

Prior art

The use of the thermal conductivity and latent heat of a liquid, for
example water, to heat or cool a stream of air by heat exchange between the
liquid and the stream of air, with direct placement in contact of the stream of
20 air and the liquid, is an old technique, which has the advantage of being
ecological, since it in particular avoids using heat transfer fluids such as
refrigerants. The heating or cooling of the stream of air may for example be
intended to produce a stream of air having a controlled temperature and/or
intended to produce a stream of air having a controlled absolute humidity.

25 A first known solution for carrying out this technique consists of
passing the stream of air through a curtain of fine droplets of the liquid or
through an air-permeable exchange surface containing this liquid, for
example a textile material imbibed with water. The main drawback of this
type of solution lies in the very low energy output of the heat exchange
30 between the liquid and the stream of air, and the low air flow rates that may
be obtained.

A second known solution consists of passing the stream of air

directly through a volume of liquid contained in an enclosure, by injecting the stream of air in the volume of liquid, below the surface of said volume of liquid. This type of solution is for example described in international patent application WO 2006/138287 and in American patents US 4,697,735 (figure 5 3) and US 7,549,418. This second technical solution has the advantage of making it possible to achieve higher energy performance levels of the heat exchange between the liquid and the stream of air.

Aim of the invention

One aim of the invention is to propose a new technical solution
10 making it possible to improve the production of a stream of air through a volume of liquid contained in an enclosure.

Brief description of the invention

According to a first aspect, the invention thus relates to a device for producing a stream of air comprising an enclosure, which is intended to
15 contain a volume of liquid, and which includes at least one air discharge opening, air injection means that make it possible to create and pass an incoming stream of air from the outside of the enclosure in a volume of liquid contained in the enclosure, by injecting said stream of air in said volume of liquid, below the surface of said volume of liquid, such that an outgoing
20 stream of air, treated by direct contact with the volume of liquid, is discharged outside said enclosure by passing through the air discharge opening of the enclosure. The enclosure includes one or more baffles that are positioned between the volume of liquid and said discharge opening, and that make it possible to circulate the stream of air leaving the volume of liquid
25 to the discharge opening, causing said stream of air to undergo one or more changes in direction, so as to prevent the spreading of liquid through the air discharge opening.

When the stream of air crosses through the volume of liquid, in particular depending on how the air is injected in the volume of liquid, and
30 depending on the air flow rate and the volume of liquid, more or less significant turbulence occurs in the volume of liquid that may cause spraying of drops that are driven by the stream of air. The baffles of the device

according to the invention form an obstacle on the path of these drops and make it possible to reduce the risks of these drops being driven by the stream of air to the discharge opening. It advantageously results from this that the flow rate of the stream of air may be very high and/or that the

5 volume of the enclosure may be small, which reduces the bulk of the device, while avoiding spraying drops of liquid outside the enclosure of the device.

More particularly, the device according to the invention may include the following additional and optional features, considered alone or in combination with one another:

- 10 - each baffle is a plate that is fastened inside the enclosure while being in tight contact over its entire periphery with the enclosure, and that includes at least one through opening for the passage of stream of air exiting through the plate.
- The device includes several baffles whereof the through openings
- 15 are not aligned with the air discharge opening of the enclosure.
- the enclosure includes an upper wall, a bottom wall and a side wall connecting the upper wall and the bottom wall, and in which the intake opening and the discharge opening are made in the upper wall of the enclosure.
- 20 - the device includes temperature control means that automatically make it possible to keep the temperature of said volume of liquid in the enclosure at a predefined temperature (T_{liquid}).
- the temperature control means make it possible to renew the liquid in the enclosure so as to automatically keep, in the enclosure, a
- 25 predefined volume of liquid at a predefined temperature (T_{liquid}).
- the air injection means include a tube that is positioned inside the enclosure, which is connected to the air intake opening, and which includes an air outlet submerged in the volume of liquid.
- each baffle includes a through opening for the passage of the
- 30 tube, and the tube is passed through said through opening of each baffle, while being in tight contact over its entire outer periphery with the baffle at each through opening.

- the air injection means make it possible to inject the stream of air entering the volume of liquid at a depth comprised between 20 mm and 80 mm.
- the air injection means include an air compressor, which is outside the enclosure, and the outlet of which could be connected or is connected to the air intake opening of the enclosure.
- the air injection means include an air compressor, which is outside the enclosure, and the intake of which could be connected or is connected to the air discharge opening of the enclosure.
- the air injection means include a single air compressor, which is outside the enclosure, and the device has two operating modes: a first operating mode in which the outlet of the compressor can be connected or is connected to the air intake opening of the enclosure, and a second operating mode in which the intake of the compressor can be connected or is connected to the air discharge opening of the enclosure.
- the air compressor is of the centrifugal type.
- the air compressor allows heating of the air passing through the air compressor with a temperature gradient ΔT of at least 2°C.
- the air injection means make it possible to create and introduce said stream of air with an air flow rate of at least 100 m³/h.
- the device includes means for controlling the temperature of the volume of liquid, which make it possible to adjust the temperature of the volume of liquid contained in the enclosure (10) as a function of at least one predefined hygrometry setpoint (HR_{cons}) so as to automatically adjust the absolute humidity of said stream of air (F') leaving the enclosure.
- The device includes at least one humidity sensor, the means for controlling the temperature of the volume of liquid make it possible to adjust the temperature of the volume of liquid contained in the enclosure as a function of the humidity measured by the humidity sensor and at least one predefined hygrometry setpoint (HR_{cons}).

The invention also relates to a method for producing a stream of air using the aforementioned device and in which the enclosure of the device contains a volume of liquid, and in particular a volume of water.

More particularly, the method according to the invention may include
 5 the following additional and optional features, considered alone or in combination with one another:

- the height ($H + H_1$) of the volume of liquid is below 200 mm, and preferably approximately 100 mm.
- the temperature of the volume of liquid is kept at a predefined
 10 temperature (T_{liquid}) that is different from the temperature (T_{initial}) of the stream of air (F) entering the enclosure.
- the method allows the production of a heated stream of air, and the temperature (T_{liquid}) of the liquid in the enclosure is higher than the temperature (T_{initial}) of the stream of air entering the enclosure.
- 15 - the temperature of the heated stream of air is substantially equal to or slightly higher than the temperature (T_{liquid}) of the liquid.
- The method allows the production of a cooled stream of air, and the temperature of the liquid (T_{liquid}) is lower than the temperature (T_{initial}) of the stream of air entering the enclosure.
- 20 - the temperature of the cooled stream of air is substantially equal to the temperature (T_{liquid}) of the liquid.
- the flow rate of the stream of air entering the enclosure is at least $100 \text{ m}^3/\text{h}$.
- the ratio between the air flow rate entering the enclosure and the
 25 volume of liquid contained in the enclosure is greater than 10^4 h^{-1} .
- the stream of air coming from outside the enclosure and entering the enclosure includes particles and/or pollutants, and at least part of these particles and/or pollutants are captured in the liquid contained in the enclosure.

30 The invention also relates to a use of one or several of the aforementioned devices, to heat a site or to cool a site and/or to humidify and/or dehumidify a site, and in particular a greenhouse. The facility

includes at least one aforementioned device, which is arranged such that the air that is injected in the enclosure of the device is air coming from outside the site.

More particularly, the facility according to the invention may include
5 the following additional and optional features, considered alone or in combination with one another:

- the facility makes it possible to heat or humidify a site, and further includes a heat exchanger connected to the enclosure of the device, such that the heated air coming from the enclosure crosses through
10 said heat exchanger, before being injected inside the site, and air recycling means that make it possible to supply the heat exchanger with recycled air coming from inside the site, such that the air coming from the device and crossing through a heat exchanger is heated by said recycled air coming from inside the site.
- 15 - the facility further includes an air heating device positioned between the heat exchanger and the inside of the site, so as to preheat the air coming from the device and crossing through the heat exchanger before it is introduced in the site.
- the facility makes it possible to cool or dehumidify a site, and further
20 includes a heat exchanger connected to the enclosure of the device, and air recycling means that make it possible to supply the heat exchanger with recycled air coming from inside the site, such that the air injected in the enclosure of the device is cooled beforehand, by crossing through the heat exchanger, by said recycled air coming
25 from inside the site.

The invention also relates to a use of one or several of the aforementioned devices, to heat a site or to cool a site, or to humidify a site or to dehumidify a site.

Brief description of the figures

30 The features and advantages of the invention will appear more clearly upon reading the following detailed description of specific alternative embodiments of the invention, the specific alternative embodiments being

described as non-limiting and non-exhaustive examples of the invention, and in reference to the appended drawings, in which:

- Figure 1 diagrammatically shows an alternative embodiment of a device according to the invention making it possible to produce a stream of air through a volume of liquid.
- Figure 2 is an isometric view of the device of figure 1, without the renewal means for the liquid in the enclosure.
- Figure 3 diagrammatically shows another alternative embodiment of the device of figure 1.
- Figure 4 is an isometric view of the device of figure 3, without the renewal means for the liquid in the enclosure.
- Figure 5 diagrammatically shows a facility for heating a site.
- Figure 6 diagrammatically shows a facility for cooling a site.
- Figure 7 diagrammatically shows a facility making it possible to adjust the humidity of a site.

Detailed description

In reference to the specific alternative embodiment of figures 1 to 4, the device 1 for producing a stream of air includes a closed enclosure 10, which comprises an upper wall 10a, a bottom wall 10b and a side wall 10c connecting the upper wall 10a to the bottom wall 10b.

In this particular example, the side wall 10c of the enclosure 10 has a tubular shape, but could have any other shape in the context of the invention.

The enclosure 10 contains, in the bottom, a volume of liquid V, with height H, the temperature of which is controlled. This liquid is preferably water, but it is possible to use any type of liquid in the context of the invention.

The enclosure 10 also includes an air intake opening 100 and an air discharge opening 101 positioned outside the volume of liquid V. In this alternative of figures 1 to 4, but non-limitingly with respect to the invention, the air intake opening 100 and the discharge opening 101 are made in the upper wall 10a of the enclosure 10.

The device 1 includes renewal means 11 for the liquid contained in the enclosure. These renewal means 11 serve to automatically supply the enclosure 10 with liquid, so as to maintain a predefined volume of liquid V in the enclosure 10, at a predefined temperature.

5 The device 1 also includes air injection means 12, which make it possible to create and inject, in the volume V of liquid contained in the enclosure 10, an incoming stream of air F coming from outside the enclosure 10. In the specific alternative illustrated in figures 1 to 4, these air injection means 12 more particularly include an air compressor 120, for example of
10 the fan type, and an injection tube 121.

The injection tube 121 is open at both its upper 121a and lower 121b ends. The upper open end 121a of the tube 121 is connected to the air intake opening 100 of the enclosure 10. The lower open end 121b of the tube 121 forms an air outlet and is submerged in the volume of liquid V,
15 while being positioned at a depth H_1 , which corresponds to the distance between the surface of the volume of liquid V and the air outlet 121b of the tube 121.

In this alternative embodiment, depending on the operating mode of the device (by blowing air/figures 1 and 2; by suctioning air/figures 3 and 4),
20 the air compressor 120 is connected to the air intake opening 100 of the enclosure 10 or to the air discharge opening 101 of the enclosure 10.

The device 1 also includes several plates 14, 14', 14'' serving as baffles, which are positioned between the volume of liquid V and the air discharge opening 101 of the enclosure 10. These plates 14, 14', 14'' are
25 fastened to the inside of the enclosure 10, one above the other, with a space between plates 14, so as to form several superimposed chambers E1, E2, E3 and E4. Each plate 14, 14', 14'' is in tight contact over its entire periphery with the side wall 10c of the enclosure 10. The first chamber E1 is defined by the surface of the volume of liquid V and the lower plate 14.
30 The second chamber E2 is defined by the lower plate 14 and the intermediate plate 14'. The third chamber E3 is defined by the intermediate plate 14' and the upper plate 14''. The third chamber E4 is defined by the

upper plate 14" and the upper wall 10a of the enclosure 10.

The number of plates 14, 14', 14" and of chambers E1, E2, E3 and E4 are not limiting with respect to the invention, the device 1 being able to include a single plate 14 defining two chambers or more than three plates
5 defining more than four chambers.

Each plate 14, 14', 14" includes a through opening 140 have substantially the same section as the injection tube 121. These through openings 140 are vertically aligned, and the injection tube 121 is passed through these openings 140, the tube 121 being in tight contact over its
10 entire outer periphery with each plate 14, 14', 14" at each passage opening 140 of the tube.

Each plate 14, 14', 14" also includes at least one through opening 141 making it possible to make two adjacent chambers communicate with one another, and thus allowing the passage of a stream of air F' leaving
15 the volume of liquid V, and which for example has been cooled or heated by the liquid, from one chamber to the other from the lower chamber E1 to the discharge opening 101.

These openings 141 are vertically offset relative to one another and are not aligned with the air discharge opening 101 of the enclosure
20 10, so as to cause said stream of air F' to undergo several changes of direction.

In the specific alternative of figures 1 and 3, the renewal means 11 for the liquid in the enclosure 10 include:

- an intake opening for the liquid 110 formed in the side wall 10c of
25 the enclosure 10 near the bottom wall 10b of the enclosure 10;
- a discharge opening for the liquid 111 formed in the bottom wall 10b of the enclosure;
- a discharge tubing 112 for the liquid that is connected at one end to the discharge opening 111 of the enclosure 10, and in this particular
30 example is connected at its other end to a liquid source S;
- pumping means 113, of the hydraulic pump type, that are connected to the liquid source S and the intake opening 110 of the enclosure,

and that make it possible to pump liquid in the liquid source S and inject it in the enclosure 10 through the intake opening 110, so as to renew the liquid in the enclosure.

In the context of the invention, the discharge tubing 112 of the liquid
 5 is not necessarily connected to the liquid source S.

The renewal means 11 for the liquid in the enclosure 10 for example include:

- at least one temperature sensor 114 making it possible to measure the temperature of the volume of liquid V in the enclosure 10;
- 10 - at least one low-level sensor 115a and one high-level sensor 115b making it possible to measure the level H of liquid in the enclosure;
- electronic processing means 116, for example of the industrial programmable automaton or electronic control/command board type, which are connected to the temperature sensor 114 and the level
 15 sensors 115a and 115b, and that deliver, as output, a command signal 113a making it possible to control the pumping means 113.

The electronic processing means 116 are designed, and are more particularly for example programmed, to control the pumping means 113 using the control signal 113a, for measuring signals delivered by the
 20 temperature sensor 114 and by the level sensors 115a and 115b, and as a function of minimum T_{min} and maximum T_{max} temperature setpoints, and minimum V_{min} and maximum V_{max} liquid volume (or level) setpoints, so as to constantly keep, in the enclosure 10, a volume of liquid V comprised between said minimum setpoint value (V_{min}) and said maximum setpoint
 25 value (V_{max}), and kept at a temperature T_{liquid} that is comprised between said minimum setpoint temperature (T_{min}) and said maximum setpoint temperature (T_{max}).

Figures 1 and 2 illustrate a first embodiment and operating mode of the device 1, in which the stream of air F entering the enclosure 10 is
 30 created by blowing air into the tube 121.

In this embodiment, the air discharge opening 101 of the enclosure 10 is in the open air. The outlet of the air compressor 120 is connected to the

air intake opening 100 of the enclosure 10, and the intake of the air compressor 120 is in the open air. When the air compressor 120 is operating, it suctions air coming from outside the enclosure 1 and pushes that air into the injection tube 121 through the air intake opening 100, in the
 5 form of an entering stream of air F, that is at an initial temperature T_{initial} substantially corresponding to the temperature of the ambient air outside the enclosure 10, or optionally at an initial temperature T_{initial} that may be slightly higher than the temperature of the ambient air outside the enclosure 10 due to the passage of the air in the compressor 120.

10 This stream of air F entering at the initial temperature T_{initial} is injected, at the outlet of the tube 121, directly in the volume of liquid V, below the surface of the volume of liquid V, and passes through this volume of liquid V, which is at a temperature T_{liquid} (comprised between T_{min} and T_{max}) different from the initial temperature T_{initial} . During the passage of this stream
 15 of air in the volume of liquid V, a heat exchange occurs by direct contact between the air and the liquid, such that the air (cooled or heated depending on the case) leaves the volume of liquid and a stream of cooled or heated air F' rises in the enclosure 10 to be discharged through the discharge opening 101. This stream of air F' at the outlet of the enclosure has a final
 20 temperature T_{final} close, and preferably substantially identical, to the temperature T_{liquid} of the volume of liquid V contained in the enclosure.

When the temperature of the liquid T_{liquid} is lower than the initial temperature T_{initial} , the stream of air F' after passage in the air of the volume of liquid V has been cooled. This concomitantly results in the stream of air F' leaving the device 1 having been dehumidified relative to the incoming
 25 stream of air F, the absolute humidity (water weight per volume of air) in the exiting stream of air F' being lower than the absolute humidity of the entering stream of air F. Conversely, when the temperature of the liquid T_{liquid} is higher than the initial temperature T_{initial} , the stream of air F' after passage in
 30 the air of the volume of liquid V has been heated. This concomitantly results in the stream of air F' leaving the device 1 having been humidified relative to the incoming stream of air F, the absolute humidity (water weight per volume

of air) in the exiting stream of air F' being higher than the absolute humidity of the entering stream of air F .

The stream of air F' cooled or heated to a final temperature T_{final} close, and preferably substantially identical, to the temperature T_{liquid} of the volume of liquid V , rises inside the enclosure 10 while circulating through the baffles 14, 14', 14'', and undergoing several successive changes in direction, then is discharged outside the enclosure 10 through the discharge opening 101.

Figures 3 and 4 illustrate a second embodiment and operating mode of the device 1, in which the stream of air F entering the enclosure 10 is created by suction.

In this embodiment, the air intake opening 100 of the enclosure is in the open air. The intake of the air compressor 120 is connected to the air discharge opening 101 of the enclosure 10, and the outlet of the air compressor 120 is in the open air. When the air compressor 120 is operating, a stream of air F coming from outside the enclosure 1 is created by suction in the injection tube 121 through the air intake opening 110. The initial temperature T_{initial} of this stream of air F corresponds to the temperature of the ambient air outside the enclosure 10. The stream of air F' , cooled or heated after passage of the air in the volume of liquid V , rises in the enclosure passing through the baffles 14, 14', 14'', then passes through the compressor 120 and is blown outside the enclosure 10 in the form of a stream of air cooled or heated to a final temperature T_{final} close to, and preferably substantially identical to or slightly higher than, the temperature T_{liquid} of the volume of liquid V .

In both of the aforementioned operating modes, the air flow rate entering the enclosure 10 is equal to the air flow rate leaving the enclosure 10. Turbulence occurs in the volume of liquid V that may be significant, and that may cause liquid drops to be sprayed, these drops being driven by the stream of air F' heated or cooled. The baffles 14, 14', 14'' of the device according to the invention form an obstacle on the path of these drops and make it possible, owing to the successive changes in direction of the air

imposed by the baffles, to prevent the liquid from being sprayed through the discharge opening 101 outside the enclosure at the same time as the cooled or heated stream of air F'. Owing to the baffles 14, 14', 14'', no drop of liquid is sprayed outside the enclosure. It advantageously results from this that the
5 flow rates of the streams of air F and F' may be very high and/or that the volume of the enclosure may be small, which reduces the bulk of the device, while avoiding spraying drops of liquid outside the enclosure of the device.

During the operation of the device 1, the inert and/or living particles, and in particular dust, in the air around the device 1 are advantageously
10 suctioned into the device 1 and are filtered while being captured in the volume of liquid V contained in the enclosure 10, which makes it possible to obtain cleaner air at the outlet of the device 1. Typically, all of the particles greater than 2 μm can be filtered by the device 1.

In another alternative embodiment, the device 1 according to the
15 invention may be used to filter or clean the incoming stream of air F by passing through a volume of liquid. In this application, the temperature of the volume of liquid may be higher or lower than the temperature of the incoming stream of air F, or be substantially equal to the temperature of the incoming stream of air F. When the temperature of the volume of liquid is substantially
20 equal to the temperature of the incoming stream of air F, at the outlet of the device 1, an outgoing stream F' of filtered or cleaned air is produced that has not been heated or cooled, but that is at substantially the same temperature as the incoming stream of air F.

In another alternative embodiment, the liquid renewal means 11 may
25 be replaced by heating or cooling means for the volume of liquid V, which make it possible to maintain the temperature of the volume of liquid without necessarily renewing the liquid in the enclosure.

The invention advantageously makes it possible to work with an air flow rate at the outlet of the compressor 120 that may be significant, and in
30 particular higher than 100 m^3/h . In one particular embodiment, the volume of the enclosure 10 was approximately 5 liters. The volume of liquid V in the enclosure 10 was smaller than 3 liters. The invention is not, however, limited

to these particular air flow rate and volume values.

More particularly, in the context of the invention, the ratio between the air flow rate entering the enclosure and the volume V of liquid present in the enclosure 10 may advantageously be 10^4h^{-1} . The invention thus allows a
 5 low liquid consumption and advantageously makes it possible to keep, at the required temperature, a small volume of liquid in the enclosure 10, which requires less energy compared to a larger volume.

During operation, due to the heat exchanges between the air and the liquid, the liquid cools (if $T_{\text{Liquid}} > T_{\text{Initial}}$) or heats (if $T_{\text{Liquid}} < T_{\text{Initial}}$). The
 10 liquid renewal means 11 make it possible to renew the liquid in the enclosure with new liquid at the required temperature so as, in the enclosure 10, a predefined volume of liquid V , substantially at the predefined temperature T_{liquid} .

The depth $H1$ of the air outlet of the injection tube 121 must be great
 15 enough for the treatment of the stream of air by passing through the volume of liquid V , and more particularly so that if applicable, the heat transfer between the liquid and the air injected in the volume of liquid V is effective and sufficient, and if applicable allows the stream of air F' cooled or heated by the liquid to be at a temperature close to, and preferably substantially
 20 identical to, that of the liquid. Conversely, this depth $H1$ must not be too great, so as to avoid oversizing the air compressor 121. The depth $H1$ is thus preferably comprised between 20 mm and 80 mm. Likewise, for better efficiency, the height $(H + H1)$ of the volume of liquid V must preferably not be too great, and will preferably be less than 200 mm, and more particularly
 25 approximately 100 mm. The invention is not, however, limited to these particular values.

The compressor 120 may be of any known type of air compressor making it possible to create a stream of air (centrifugal fan, axial fan, pump, etc.).

30 Nevertheless, the air compressor 120 is preferably a centrifugal air compressor, since this type of compressor advantageously makes it possible to obtain significant air flow rates, and also to obtain a significant

temperature difference ΔT of the air between the outlet of the compressor 120 and the inlet of the compressor, for example compared to an axial compressor. In practice, this temperature difference ΔT for a centrifugal air compressor is at least 2°C and may reach 4°C, the air leaving the
5 compressor being at a temperature higher than the air entering the compressor.

Preferably, the operating mode of figures 1 and 2 may be used in the summertime to perform air conditioning or dehumidification of a site, by producing one or more streams of air F' cooled using one or more devices 1,
10 from the hot air taken from outside the site. The liquid source S may advantageously be a water table or a cold water tank buried at a depth or cooled using any known cooling system.

Conversely, the operating mode of figures 3 and 4 is preferably used in the winter to heat or humidify a site, by producing one or more streams of
15 air F' heated using one or more devices 1, from the cold air taken from outside the site. The liquid source S is a hot water source in this case, for example a heated water tank, a heated outside water basin, for example using solar energy, a water table or a hot water tank. In this case, the implementation of an air compressor 120 of the centrifugal type
20 advantageously makes it possible to use a temperature differential ΔT to increase the temperature of the air leaving the compressor 120 relative to the temperature of the air at the discharge opening 101 of the enclosure 10, which improves the energy performance.

In both operating mode, the invention applies to any type of site. The
25 site may be of the industrial, household or service type. The site may also be a greenhouse or a hanger. In both operating modes, the invention advantageously allows continual renewal of the air inside the site.

The device 1 according to the invention may also produce a stream of hot air or cooled and/or humidified or dehumidified air directed over any
30 type of surface to heat or cool and/or humidify or dry that surface.

Figure 5 diagrammatically shows a facility for heating and/or humidifying a site 2. This facility includes one or more devices 1 for

producing a stream of heated air, of the type for example of the device of figure 1 working by blowing. In another alternative, it is nevertheless also possible to implement devices 1 of figure 4 working by suction. The number of devices 1 for producing a stream of heated air will in particular depend on
5 the air flow rates of the devices 1 and the volume of the site 2. The devices 1 will be carefully distributed in the volume of the site 2.

Each device 1 is arranged in the site 2 such that the air that is injected in the enclosure 10 of the device 1 is cold air coming from outside the site. The enclosure 10 of each device 1 is further connected at its outlet
10 to a heat exchanger 3, such that the heated air leaving the device 1 crosses through said heat exchanger 3, then is injected at the outlet of an air heating device, for example comprising heating electric resistances or plate exchangers. The air preheated by the air heating device 4 is next injected inside the site 2.

15 The facility also includes recycling means 5 making it possible to renew the air in the site by suctioning it and discharging it outside the site 2, so as to keep the temperature of the air inside the site at a predefined setpoint temperature. Part of this hot air coming from the site 2 (figure 5/branch 50) is recycled while being reinjected inside the site 2 downstream
20 from the heat exchanger 3. Another part of this hot air coming from the site 2 (figure 5/branch 51) is sent into the heat exchanger 3, and crosses through said heat exchanger 3, such that the air coming from the device 1 is heated by this hot air coming from the site 2. In this facility, the temperature of the liquid in the enclosure 10 of each device 1 is below the temperature of the
25 hot air coming from the site 2.

The heat exchanger 3 may be of any known type of heat exchanger allowing a heat exchange between two fluids, in particular without placing the two fluids in direct contact.

The implementation of this heat exchanger 3 advantageously allows
30 heating of the air leaving the devices 1 with hot air coming from the site, and thereby makes it possible to reuse part of the calories from this hot air and to work with a lower liquid temperature in the devices 1. The energy

consumption is thus reduced.

As a non-limiting example, in one specific alternative embodiment, the temperature of the air injected in the enclosure 10 was below 15°C and for example below 0°C, and the relative humidity level of this air was for example approximately 90%-100%. The temperature of the liquid in the enclosure 10 was kept at approximately 15°C. The temperature of the air leaving each device 1 was thus approximately 15°C. The temperature of the air leaving the air heating device 4 and entering the site 2 was approximately 22°C. The temperature of the site 2 was kept around 19°C with a relative humidity level of that air for example of approximately 60%.

Figure 6 diagrammatically shows a facility for cooling (air-conditioning) and/or dehumidifying a site 2. This facility includes one or more devices 1 for producing a stream of cooled air, of the type for example of the device of figure 1 working by blowing. In another alternative, it is nevertheless also possible to implement devices 1 of the type of figure 4 working by suction. The number of devices 1 for producing a stream of cooled air will in particular depend on the air flow rates of the devices 1 and the volume of the site 2. The devices 1 will be carefully distributed in the volume of the site 2.

Each device 1 is arranged in the site 2 such that the air that is injected in the enclosure 10 of the device 1 is hot air coming from outside the site. The facility further includes a heat exchanger 3' that is positioned between the air compressor 120 of each device and the enclosure 10 of each device 1, such that the hot air coming from outside the site 2 crosses through said heat exchanger 3', then is injected in the enclosure 10 of each device 1.

The facility also includes air recycling means 5 making it possible to renew the air in the site by suctioning it and discharging it outside the site 2, so as to keep the temperature of the air inside the site at a predefined setpoint temperature. This recycled cold air coming from the site 2 (figure 6/branch 51) is sent into the heat exchanger 3', and crosses through said heat exchanger 3, such that the hot air coming from the outside, before it is

injected in the enclosure 10 of each device 1, is cooled by this recycled cold air coming from the site 2. In this facility, the temperature of the liquid in the enclosure 10 of each device 1 is below the temperature of the cold air coming from the site 2.

- 5 The heat exchanger 3' may be of any known type of heat exchanger allowing a heat exchange between two fluids, in particular without placing the two fluids in direct contact.

 The implementation of this heat exchanger 3' advantageously allows pre-cooling of the air before it is injected in the enclosure 10 of each device 1
10 with air coming from the site 2, and thereby makes it possible to reuse part of the calories from this air. The energy consumption is thus reduced.

 As a non-limiting example, in one specific alternative embodiment, the temperature of the outside air injected in the exchanger 3' by the air compressor 120 was above 15°C, and for example approximately 32°C, and
15 the relative humidity level of this air was for example approximately 40%. The temperature of the liquid in the enclosure 10 was kept at approximately 15°C. The temperature of the air leaving each device 1 was thus approximately 15°C. The temperature of the site 2 was kept around 22°C.

 In reference to figure 7, the device 1 according to the invention may
20 also be used in a facility making it possible to control and automatically maintain the relative humidity in a site 2 or the like. The entering stream of air F is captured by the device 1 outside the site 2, passes in the device 1, so as to be humidified or dehumidified depending on the case, and the humidified or dehumidified exiting stream of air F' is injected in the site 2,
25 optionally after having been mixed with the ambient air A captured in the site 2 (figure 7/stream of air F").

 The relative humidity HR in the site is measured using at least one humidity sensor 6 of the hygrostat type, which is positioned in the site outside the incoming stream of air F' or F". The device 1 is equipped with
30 means 11 for controlling the temperature of the volume of liquid V in the device 1, which make it possible to automatically adjust the temperature of the volume of liquid V contained in the device 1 as a function of the relative

humidity (HR) measured by the humidity sensor 6 in the site 2 and a humidity setpoint (HR_{cons}). The stream of air F' leaving the device 1 is injected in the site 2, optionally while being mixed with air A coming from inside the site 2.

5 The means for controlling the temperature of the volume of liquid V are designed such that the temperature of the volume of liquid V is automatically brought to a value above the temperature of the stream of air F entering the device 1, when the relative humidity HR measured by the sensor 6 is below the humidity setpoint (HR_{cons}); a more humid stream of air
10 F' is thus produced, the absolute humidity of which (water weight per volume of air) is higher than the absolute humidity of the stream of air F entering the device 1, and the temperature of which is approximately at the temperature of the volume of liquid V and is higher than the temperature of the stream of air F entering the device 1. The entering stream of air F' thus makes it
15 possible to humidify the site 2.

 The means for controlling the temperature of the volume of liquid V are further designed such that the temperature of the volume of liquid V is automatically brought to a value below the temperature of the stream of air F entering the device 1, when the relative humidity HR measured by the
20 sensor 6 is above the humidity setpoint (HR_{cons}); a less humid stream of air F' is thus produced, the absolute humidity of which (water weight per volume of air) is lower than the absolute humidity of the stream of air F entering the device 1, and the temperature of which is approximately at the temperature of the volume of liquid V and is lower than the temperature of the stream of
25 air F entering the device 1.

 Alternatively, it is also possible for the entering stream of air F to be completely or partially captured by the device 1 inside the site 2.

 Alternatively, it is also possible to heat or cool, using any heating or cooling means, the stream of air (F' or F'') entering the site 2 without
30 modifying its absolute humidity so as to bring it to a predefined temperature.

 It is also possible to replace the sensor 6 of figure 7 with a sensor 6 positioned in the stream of air (F' or F'') entering the site 2 and measuring the

absolute humidity of said stream of air. In this case, a stream of air (F' or F'') is injected in the site 2 whereof the absolute humidity is automatically controlled relative to a humidity setpoint by automatically adjusting the temperature of the volume of liquid contained in the device 1.

CLAIMS

1. A device (1) for producing a stream of air (F') comprising an
5 enclosure (10), which is intended to contain a volume of liquid (V),
and which includes at least one air discharge opening (101), air
injection means (12) that make it possible to create and pass an
incoming stream of air (F) from the outside of the enclosure in a
volume of liquid (V) contained in the enclosure, by injecting said
10 entering stream of air (F) in said volume of liquid (V), below the
surface of said volume of liquid (V), such that an outgoing stream of
air (F'), treated by direct contact with the volume of liquid, is
discharged outside said enclosure by passing through the air
discharge opening (101) of the enclosure, characterized in that the
15 enclosure includes one or several baffles (14; 14'; 14'') that are
positioned between the volume of liquid (V) and said discharge
opening (101), that make it possible to circulate the stream of air
(F') leaving the volume of liquid (V) to the discharge opening (101),
causing it to undergo one or several changes of direction, so as to
20 prevent the spraying of liquid through the air discharge opening
(101).
2. The device according to claim 1, wherein each baffle (14, 14', 14'')
is a plate that is fastened inside the enclosure while being in tight
contact over its entire periphery with the enclosure (10), and that
25 includes at least one through opening (141) for the passage of
stream of air (F') exiting through the plate.
3. The device according to claim 2, including several baffles (14, 14',
14'') whereof the through openings (141) are not aligned with the air
discharge opening (101) of the enclosure (10).
- 30 4. The device according to any one of the preceding claims, wherein
the enclosure (10) includes an upper wall (10a), a bottom wall (10b)
and a side wall (10c) connecting the upper wall (10a) and the

bottom wall (10b), and in which the intake opening (100) and the discharge opening (101) are made in the upper wall (10a) of the enclosure (10).

- 5 5. The device according to any one of the preceding claims, including temperature control means (11) that automatically make it possible to keep the temperature of said volume of liquid (V) in the enclosure (10) at a predefined temperature (T_{liquid}).
- 10 6. The device according to claim 5, wherein the temperature control means (11) make it possible to renew the liquid in the enclosure (10), so as to automatically keep, in the enclosure (10), a predefined volume of liquid (V) at a predefined temperature (T_{liquid}).
- 15 7. The device according to any one of the preceding claims, wherein the air injection means (12) include a tube (121) that is positioned inside the enclosure (10), which is connected to the air intake opening (100), and which includes an air outlet (121b) submerged in the volume of liquid.
- 20 8. The device according to claim 6, wherein each baffle (14, 14', 14'') includes a through opening (140) for the passage of the tube (121), and the tube (121) is passed through said through opening (140) of each baffle (14, 14', 14''), while being in tight contact over its entire outer periphery with the baffle at each through opening.
- 25 9. The device according to any one of the preceding claims, wherein the air injection means (12) make it possible to inject the stream of air (F) entering the volume of liquid at a depth (H1) comprised between 20 mm and 80 mm.
- 30 10. The device according to any one of the preceding claims, wherein the air injection means (12) include an air compressor (120), which is outside the enclosure (10), and the outlet of which can be connected or is connected to the air intake opening (100) of the enclosure (10).

11. The device according to any one of the preceding claims, wherein the air injection means (12) include an air compressor (120), which is outside the enclosure (10), and the intake of which can be connected or is connected to the air discharge opening (101) of the enclosure (10).
5
12. The device according to any one of claims 1 to 9, wherein the air injection means (12) include a single air compressor (120), which is outside the enclosure (10), and the device has two operating modes: a first operating mode in which the outlet of the compressor (120) can be connected or is connected to the air intake opening (100) of the enclosure (10), and a second operating mode in which the intake of the compressor (120) can be connected or is connected to the air discharge opening (101) of the enclosure (10).
10
13. The device according to any one of claims 10 to 12, wherein the air compressor is of the centrifugal type.
15
14. The device according to any one of claims 10 to 13, wherein the air compressor (120) allows heating of the air passing through the air compressor with a temperature gradient ΔT of at least 2°C.
15. The device according to any one of the preceding claims, wherein the air injection means (12) make it possible to create and introduce said stream of air (F) with an air flow rate of at least 100 m³/h.
20
16. The device according to any one of the preceding claims, including means (11) for controlling the temperature of the volume of liquid (V), which make it possible to adjust the temperature of the volume of liquid contained in the enclosure (10) as a function of at least one predefined hygrometry setpoint (HR_{cons}) so as to automatically adjust the absolute humidity of said stream of air (F') leaving the enclosure (10).
25
17. The device according to claim 16, including at least one humidity sensor (6), and wherein the means (11) for controlling the temperature of the volume of liquid (V) make it possible to adjust the temperature of the volume of liquid contained in the enclosure
30

(10) as a function of the humidity measured by the humidity sensor (6) and at least one predefined hygrometry setpoint (HR_{cons}).

18. A method for producing a stream of air using the device (1) set out in any one of the preceding claims, wherein the enclosure (10) of the device (1) contains a volume of liquid, and in particular a volume of water.
19. The method according to claim 18, wherein the height ($H + H1$) of the volume of liquid (V) is below 200 mm, and preferably approximately 100 mm.
20. The method according to claim 18 or 19, wherein the temperature of the volume of liquid (V) is kept at a predefined temperature (T_{liquid}) that is different from the temperature ($T_{initial}$) of the stream of air (F) entering the enclosure (10).
21. The method according to claim 20, allowing the production of a heated stream of air (F'), and the temperature (T_{liquid}) of the liquid in the enclosure (10) is higher than the temperature ($T_{initial}$) of the stream of air (F) entering the enclosure (10).
22. The method according to claim 21, wherein the temperature of the heated stream of air (F') is substantially equal to or slightly higher than the temperature (T_{liquid}) of the liquid.
23. The method according to claim 20, allowing the production of a cold stream of air and wherein the temperature (T_{liquid}) is lower than the temperature ($T_{initial}$) of the stream of air (F) entering the enclosure (10).
24. The method according to claim 23, wherein the temperature of the cooled stream of air (F') is substantially equal to the temperature (T_{liquid}) of the liquid.
25. The method according to any one of claims 18 to 24, wherein the flow rate of the stream of air entering the enclosure (10) is at least 100 m³/h.

26. The method according to any one of claims 18 to 25, wherein the ratio between the air flow rate entering the enclosure (10) and the volume of liquid (V) contained in the enclosure is greater than 10^4h^{-1} .
27. The method according to any one of claims 18 to 26, wherein the
5 stream of air (F) coming from outside the enclosure (10) and entering the enclosure (10) includes particles and/or pollutants, and at least part of these particles and/or pollutants are captured in the liquid contained in the enclosure (10).
28. A facility allowing the heating and/or cooling and/or humidification
10 and/or dehumidification of a site (2), and including at least one device (1) as set out in any one of claims 1 to 17, and which is arranged such that the air that is injected in the enclosure (10) of the device (1) is air coming from outside the site (2).
29. The facility according to claim 28, for heating or humidifying a site
15 (2), further including a heat exchanger (3) connected to the enclosure (10) of the device (1), such that the heated air coming from the enclosure (10) crosses through said heat exchanger (3), before being injected inside the site (2), and air recycling means (5) that make it possible to supply the heat exchanger (3) with recycled
20 air coming from inside the site (2), such that the air coming from the device (1) and crossing through a heat exchanger (3) is heated by said recycled air coming from inside the site (2).
30. The facility according to claim 29, further including an air heating
25 device (4) positioned between the heat exchanger (3) and the inside of the site (2), so as to preheat the air coming from the device (1) and crossing through the heat exchanger (3) before it is introduced in the site (2).
31. The facility according to claim 28, for cooling or dehumidifying a
30 site (2), further including a heat exchanger (3') connected to the enclosure (10) of the device (1), and air recycling means (5) that make it possible to supply the heat exchanger (3') with recycled air coming from inside the site (2), such that the air injected in the

enclosure (10) of the device (1) is previously cooled, by passing through the heat exchanger (3'), by said recycled air coming from inside the site (2).

- 5 32. A use of one or several devices (1) set out in any one of claims 1 to 17, to heat a site or to cool a site, or to humidify a site or to dehumidify a site.
33. The use according to claim 32, wherein the site is a greenhouse.