

SUBSEA SAFETY SYSTEM HAVING A PROTECTIVE FRANGIBLE LINER AND METHOD OF OPERATING SAME

TECHNICAL FIELD OF THE INVENTION

This invention relates, in general, to equipment utilized in conjunction with operations performed in subterranean wells and, in particular, to a subsea safety system having a protective frangible liner and a method of operating same.

BACKGROUND OF THE INVENTION

Without limiting the scope of the present invention, its background will be described in relation to a safety system of a subsea well installation, as an example.

In certain subsea well installations, the safety systems may include a subsea safety tree on the lower end of a tubular string that may be positioned within the blowout preventer stack of a subsea wellhead. The subsea safety tree may include one or more shut-in valves that operate to automatically shut-in the well in the event of emergency conditions. In addition, the subsea safety tree may include a latch assembly that enables separation of the tubular string from the lower portion of the subsea safety tree, a retainer valve that prevents fluid discharge from the tubular string into the environment and a vent sleeve that provides for controlled venting of pressure trapped between the closed retainer valve and the closed shut-in valves of the subsea safety tree.

Conventionally, each of these components of the subsea safety tree, the retainer valve, the vent sleeve, the latch assembly and the shut-in valves, are controlled by fluid pressure in control lines which extend from a pressure source at the surface to the subsea safety tree. In many installations, dedicated control lines between each of the components and the surface are used, including both supply lines and return lines. In addition, the actuation of each of these components is controlled by electrical switches, such as solenoid valves, that selectively prevent and allow hydraulic pressure to operate the various components. In an emergency situation, the proper operation of these components is necessary to safely shut-in the well,

contain fluid within the tubular string, bleed off pressure between the shut-in valves and the retainer valve and cause separation of the tubular string from the subsea well installation.

It has been found, however, that certain operations such as gravel packing, fracturing or fracture packing, that require proppant laden slurry to be pumped into the well through the tubular string, may result in damage to or debris buildup within components of the subsea safety tree. This damage or debris buildup may prevent proper operation of one or more of the components of the subsea safety tree. Accordingly, a need has arisen for systems and methods of protecting the components of the subsea safety tree during operations wherein proppant laden slurry is pumped into the well through a tubular string including a subsea safety tree.

SUMMARY OF THE INVENTION

The present invention disclosed herein is directed to systems and methods of using a frangible liner to protect components of a subsea safety tree during operations wherein proppant laden slurry is pumped into the well through a tubular string including the subsea safety tree. The systems and methods of the present invention utilize a frangible liner that may be preinstalled at the surface or shifted downhole into the subsea safety tree that provides a barrier between the components of the subsea safety tree and the proppant laden slurry during treatment operations but is easily shattered or otherwise disintegrates to allow proper operation of the components of the subsea safety tree during, for example, a shut-in of the well due to emergency conditions.

In one aspect, the present invention is directed to a subsea safety system for use during a well treatment operation. The subsea safety system includes a tubular string having an inner flow passage. At least one valve assembly is positioned within the tubular string. The at least one valve assembly is operable between open and closed positions to selectively permit and prevent fluid flow therethrough. A frangible liner is disposed within the at least one valve assembly. The frangible liner is operable to protect the at least one valve assembly from particle flow during the well treatment operation and is operable to shatter responsive to closure of the at least one valve assembly, thereby allowing full operation of the at least one valve assembly.

In one embodiment, the at least one valve assembly may be a safety valve. In another embodiment, the at least one valve assembly may be a flapper valve. In a further embodiment,

the at least one valve assembly may be a ball valve. In yet another embodiment, the at least one valve assembly may include at least two valve assemblies.

In one embodiment, the frangible liner may have a smooth inner surface. In another embodiment, the frangible liner may have at least one tapered end. In a further embodiment, the frangible liner may be a retractable frangible liner. In certain embodiment, the frangible liner may be formed from a material selected from the group consisting of ceramics, fiberglass, epoxies, graphic epoxy, glass ceramics and polymers. In some embodiments, the frangible liner may have a close fitting but not fluid tight relationship with the at least one valve assembly.

In another aspect, the present invention is directed to a subsea safety system for use during a well treatment operation. The subsea safety system includes a tubular string having an inner flow passage. At least one valve assembly is positioned within the tubular string. The at least one valve assembly is operable between open and closed positions to selectively permit and prevent fluid flow therethrough. A frangible liner is disposed within the at least one valve assembly. The frangible liner has a close fitting but not fluid tight relationship with the at least one valve assembly. The frangible liner is operable to protect the at least one valve assembly from particle flow during the well treatment operation and is operable to shatter responsive to closure of the at least one valve assembly, thereby allowing full operation of the at least one valve assembly.

In a further aspect, the present invention is directed to a method of operating a subsea safety system. The method includes positioning at least one valve assembly within a tubular string having an inner flow passage, disposing a frangible liner within the at least one valve assembly, pumping a treatment fluid through the inner flow passage of the tubular string, protecting the at least one valve assembly from particles in the treatment fluid with the frangible liner, operating the at least one valve assembly from an open position to a closed position to prevent fluid flow therethrough and shattering the frangible liner in response to the closing of the at least one valve assembly, thereby allowing full operation of the at least one valve assembly.

The method may also include operating a flapper valve from an open position to a closed position, operating a ball valve from an open position to a closed position or establishing a close fitting but not fluid tight relationship between the frangible liner and the at least one valve assembly.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the features and advantages of the present invention, reference is now made to the detailed description of the invention along with the accompanying figures in which corresponding numerals in the different figures refer to corresponding parts and in which:

FIG. 1 is a schematic illustration of a subsea well installation including a subsea safety system having a protective frangible liner according to an embodiment of the present invention;

FIGS. 2A-2D are quarter sectional views of consecutive axial sections of a subsea safety system in an open configuration having a protective frangible liner according to an embodiment of the present invention; and

FIGS. 3A-3D are quarter sectional views of consecutive axial sections of a subsea safety system in a closed configuration having a partially shattered frangible liner according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

While the making and using of various embodiments of the present invention are discussed in detail below, it should be appreciated that the present invention provides many applicable inventive concepts which can be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative of specific ways to make and use the invention, and do not delimit the scope of the present invention.

Referring to FIG. 1, a subsea well installation including a subsea safety system having a protective frangible liner is schematically illustrated and generally designated **10**. In the following description, directional terms, such as above, below, upper, lower and the like are used for convenience in referring to the accompanying drawings and it is to be clearly understood that the various embodiments of the present invention described herein may be utilized in various orientations, such as inclined, inverted, horizontal, vertical and the like, without departing from the principles of the present invention.

Subsea well installation **10** includes a subsea test tree **12** that is positioned within a blowout preventer (BOP) stack **14** installed on the ocean floor. BOP stack **14** includes two pipe

rams **16** and two shear rams **18** that are configured and controlled according to conventional practice. In the illustrated embodiment, BOP stack **14** is a compact BOP stack having multiple pipe and shear rams **16**, **18**, but it is to be clearly understood that the present invention may be utilized in other types of BOP stacks and in BOP stacks having greater or fewer numbers of pipe and shear rams.

Subsea test tree **12** has been lowered into BOP stack **14** through a tubular riser **20** extending upwardly therefrom. A fluted wedge **22** attached below subsea test tree **12** permits accurate positioning of subsea test tree **12** within BOP stack **14**. In the illustrated embodiment, a retainer valve **24** is attached above subsea test tree **12** and remains within riser **20** when subsea test tree **12** is positioned within BOP stack **14**.

Subsea test tree **12** includes a latch head assembly **26**, a ramlock assembly **28** and a valve assembly **30**. Ramlock assembly **28** is interconnected axially between latch head assembly **26** and valve assembly **30** to axially separate these components from one another. As used herein, the term ramlock assembly is used to indicate one or more members which are configured in such a way as to permit sealing engagement with conventional pipe rams. For example, as shown in FIG. 1, ramlock assembly **28** is shown in sealing engagement with both of the pipe rams **16** as pipe rams **16** have been previously actuated to extend inwardly to engage ramlock assembly **28**. As illustrated, latch head assembly **26** and valve assembly **30** have diameters which are greater than that which may be sealingly engaged by conventional pipe rams, therefore, ramlock assembly **28** provides for sealing engagement of the pipe rams **16** between latch head assembly **26** and valve assembly **30**.

Valve assembly **30** is positioned between pipe rams and wedge **22** such that when pipe rams **16** are closed about ramlock assembly **28**, valve assembly **30** is isolated from an annulus **32** above pipe rams **16**. Pipe rams **16** isolate annulus **32** from an annulus **34** below pipe rams **16** and surrounding valve assembly **30**. As used herein, the term valve assembly is used to indicate an assembly including one or more valves which are operative to selectively permit and prevent fluid flow through a flow passage formed through the valve assembly. For example, valve assembly **30** of FIG. 1 includes two safety valves (not visible), which are operative to control fluid flow through a tubular string **36**. Retainer valve **24**, latch head assembly **26**, ramlock assembly **28** and valve assembly **30** are all interconnected within and are part of tubular string **36**. Tubular string **36** has a flow passage formed therethrough and the valves in valve assembly **30** may be actuated to permit or prevent fluid flow therethrough. Even though

valve assembly **30** has been described as having two safety valves, it is to be clearly understood by those skilled in the art that it is not necessary for valve assembly **30** to include multiple valves, or for the valves to be safety valves, in keeping with the principles of the present invention.

As used herein, the term latch head assembly is used to indicate one or more members which permit decoupling of one portion of tubular string **36** from another portion thereof. For example, in the representatively illustrated subsea test tree **12**, latch head assembly **26** may be actuated to decouple an upper portion **38** of tubular string **36** from a lower portion **40** of tubular string **36**. Thus, in the event of an emergency, pipe rams **16** may be closed on ramlock assembly **28**, the valves in valve assembly **30** may be closed, and upper portion **38** of tubular string **36** may be retrieved, or otherwise displaced away from lower portion **40**. Closure of pipe rams **16** on ramlock assembly **28** and closure of the valves in valve assembly **30** isolates the well therebelow from fluid communication with riser **20**.

If desired, shear rams **18** may be actuated to shear upper portion **38** of tubular string **36** above latch head assembly **26**. Upper portion **38** may be sheared at a tubular handling sub attached above latch head assembly **26**. For this reason, latch head assembly **26** is positioned between shear rams **18** and pipe rams **16**. In this manner, redundancy is preserved and safety is, therefore, enhanced in that two shear rams **18** are usable above latch head assembly **26** and two pipe rams **16** are usable below latch head assembly **26** in the compact BOP stack **14**.

Actuation of retainer valve **24**, latch head assembly **26** and valve assembly **30** is controlled via lines **42**. In the representatively illustrated embodiment shown in FIG. 1, lines **42** are hydraulic lines which extend to the earth's surface and are used for delivering pressurized fluid to subsea test tree **12** and retainer valve **24**. Those skill in the art, however, will understand that lines **42** could alternatively be one or more electrical lines and that subsea test tree **12** and/or retainer valve **24** could be electrically actuated, the lines could be replaced by one or more telemetry devices, the lines could extend to other locations in the well or the like without departing from the principles of the present invention.

Positioned within tubular string **36** and specifically within latch head assembly **26** and valve assembly **30** is a frangible liner (not visible in FIG. 1). As explained in greater detail below, the frangible liner is designed to prevent particles such as sand, gravel or proppants in a treatment fluid, from damaging or buildup within latch head assembly **26** and valve assembly **30**

but to shatter in response to the closure of the valves within valve assembly **30**, thereby allowing full operation of the valves within valve assembly **30**. Preferably, the frangible liner has a smooth inner surface, is relatively thin walled and has tapered ends to minimize its effects on the flow of treatment fluid therethrough. The frangible liner may be formed from a frangible material such as ceramics, fiberglass, epoxies, graphic epoxy, glass ceramics or polymers. Preferably, the frangible liner has a close fitting but not fluid tight relationship with tubular string **36** such that the frangible liner will not have to withstand the pressure within tubular string **36**.

Referring additionally now to FIGS. 2A-2D, a subsea test tree, such as subsea test tree **12** described in FIG. 1, which embodies principles of the present invention is representatively illustrated and generally designated **50**. Subsea test tree **50** includes a valve assembly **52** and a latch head assembly **54**. At an upper end of latch head assembly **54**, an upper sub **56** is threadedly and sealingly installed therein. Upper sub **56** may be provided with additional threads and seals at an upper end thereof in a conventional manner for interconnection of subsea test tree **50** within a tubular string, such as tubular string **36** of FIG. 1. Similarly, at a lower end of valve assembly **52**, a lower sub **58** is threadedly and sealingly installed therein. Lower sub **58** is also provided with threads and a seal for interconnection of subsea test tree **50** within a tubular string, such as tubular string **36** of FIG. 1. Thus, subsea test tree **50** may be interconnected in the tubular string **36** as parts of the upper and lower portions **38**, **40** thereof, in a manner similar to that in which subsea test tree **12** is interconnected in FIG. 1. However, it is to be clearly understood that subsea test tree **50** may be otherwise interconnected in a tubular string and may be utilized in other configurations, without departing from the principles of the present invention.

Lines, such as lines **42** shown in FIG. 1, may be connected to subsea test tree **50** at ports **60**, only one such port being visible in FIG. 2A, but it is to be understood that other ports are provided. In the illustrated embodiment, port **60** is for connection of a control line and other ports are for connection of a balance line, connection of a latch line, connection of an injection line or alternate control lines for operation of subsea test tree **50**. Of course, other ports, lines, and other numbers and combinations of lines and ports may be utilized without departing from the principles of the present invention.

From port **60**, a control line passage **64** is formed in latch head assembly **54** and extends downwardly therethrough. Control line passage **64** is in fluid communication with an annular piston **66** that is axially reciprocally and sealingly received within latch head assembly

54. Fluid pressure in control line passage **64** acts to bias piston **66** downward against an upwardly biasing force exerted by a bias member or spring **68** as well as fluid pressure from the balance line (not pictured) that acts to bias piston **66** upward. In operation, fluid in the balance line is used to balance hydrostatic pressure in control line passage **64** and pressure may be applied to the balance line passage if desired to aid spring **68** in shifting piston **66** upward.

Another piston **72** is axially reciprocably and sealingly disposed within latch head assembly **54**. Piston **72** is biased downwardly by a bias member or spring **74**. At a lower end of piston **72**, an outer tapered surface **76** is formed and is utilized to outwardly retain a set of lugs or dogs **78** in engagement with an annular profile **80** formed internally on a portion of an outer housing **82** of latch head assembly **54**. Of course, other surfaces and otherwise-shaped surfaces may be used to maintain engagement of lugs **78** in profile **80**.

It will be readily appreciated that, with piston **72** in its downwardly disposed position as shown in FIGS. 2A-2B, lugs **78** are outwardly supported by surface **76**, but when piston **72** is in an upwardly disposed position, lugs **78** are not outwardly supported and may be disengaged from profile **80**. Thus, with piston **72** in its downwardly disposed position, latch head assembly **54** is latched, and with piston **72** in its upwardly disposed position, latch head assembly **54** is unlatched. When latch head assembly **54** is unlatched, an upper portion **84** thereof may be upwardly displaced relative to a lower portion **86** thereof. When latch head assembly **54** is latched, such axial separation is prevented.

A ramlock assembly **90** is interconnected between latch head assembly **54** and valve assembly **52**. Ramlock assembly **90** axially separates latch head assembly **54** from valve assembly **52** and provides an appropriately sized and configured outer side surface **92**, which may be sealingly engaged by a conventional pipe ram. The depicted outer side surface **92** is generally cylindrical in shape, but it is to be understood that otherwise-shaped surfaces may be utilized without departing from the principles of the present invention.

In the illustrated embodiment, an upper end of ramlock assembly **90** is integrally formed with, and forms a part of, lower portion **86** of latch head assembly **54**. A lower end of ramlock assembly **90** is integrally formed with, and forms a part of, valve assembly **52**. However, it is to be clearly understood that ramlock assembly **90** may be separately formed and otherwise attached between valve assembly **52** and latch head assembly **54**, without departing from the principles of the present invention. Ramlock assembly **90** includes an outer tubular member **94**,

which has outer surface **92** formed thereon and an inner tubular member **96**. Inner tubular member **96** is axially reciprocably disposed within outer tubular member **94** and is biased upwardly by a bias member or spring **98**. Spring **98** is disposed radially between inner and outer tubular members **96**, **94**. Control line passage **64** extends downwardly through a sidewall of outer member **94**. In this manner, fluid pressure in control line **64** is available for use in valve assembly **52**, as is described in more detail below.

Spring **98** is axially compressed between a radially enlarged shoulder **100** formed externally on the inner member **96** and a shoulder **102** formed internally on outer member **94** within valve assembly **52**. Of course, spring **98** could easily be otherwise positioned. When inner member **96** is in its upwardly disposed position, it abuts a shoulder **106** internally formed on outer member **94** within latch head assembly **54**. Inner member **96** also abuts a lower end of piston **66** at location **107**. As piston **66** is displaced between its upwardly and downwardly disposed positions, inner member **96** is thereby correspondingly displaced between its upwardly and downwardly disposed positions. Spring **98** maintains engagement between piston **66** and inner member **96** between the upwardly and downwardly disposed positions and ensures that when piston **66** is displaced upwardly, inner member **96** also displaces upwardly therewith. However, note that the engagement between piston **66** and inner member **96** is releasable. When latch head assembly **54** is unlatched, piston **66** may be displaced upwardly with the remainder of upper portion **84** away from lower portion **86**. Thus, piston **66** and inner member **96** may be axially separated.

As illustrated, when inner member **96** is displaced downwardly by piston **66** in response to fluid pressure in control line passage **64**, a lower end of inner member **96** contacts and pivots a generally disc-shaped flapper **108** away from a circumferential seat **110**. When inner member **96** is in its upwardly disposed position, flapper **108** is permitted to sealingly engage seat **110**, thereby preventing fluid flow through inner flow passage **112** formed axially through subsea test tree **50**. A bias member or spring **114** biases flapper **108** toward its closed position. Flapper **108**, seat **110**, spring **114** and the lower end of inner member together constitute a flapper valve **134** in valve assembly **52**. Flapper valve **134** is in many respects similar to flapper valves well known to those skilled in the art and utilized in conventional safety valves. In addition, valve assembly **52** also includes a second safety valve depicted as ball valve **116**. Thus, valve assembly **52** has two valves disposed therein, each of the valves being safety valves. It is, however, to be understood that other numbers of valves and other types of valves may be disposed within valve assembly **52** in keeping with the principles of the present invention.

Ball valve **116** includes an annular piston **118** axially reciprocably and sealingly disposed within outer housing **120** of valve assembly **52**. Piston **118** is upwardly biased by a bias member or spring **122** and by a pressurized gas chamber **124** that preferably contains a pressurized gas such as nitrogen, that exerts an upwardly biasing force on an annular floating piston **126** which, in turn, transmits the upwardly directed force to a lower end of piston **118**. To downwardly displace piston **118**, fluid pressure is applied to control line passage **64**, which is in fluid communication with piston **118**. When piston **118** is in its downwardly displaced position, a ball **128** of ball valve **116** has an opening aligned with flow passage **112**, permitting fluid flow therethrough. When piston **118** is in its upwardly displaced position, ball **128** is in its closed position, with flow through the opening being prevented.

Axial displacement of piston **118** is translated into rotation of ball **128** by an actuator mechanism **132** of the type well known to those skilled in the art. Actuator mechanism **132** may be similar to those used in conventional ball valves. However, it is to be understood that other actuator mechanisms and other types of actuators may be used, without departing from the principles of the present invention. When it is desired to open ball valve **116**, sufficient fluid pressure is applied to control line passage **64** to displace piston **118** downward against the combined upwardly biasing forces due to fluid pressure in the balance line, spring **122** and the compressed gas in chamber **124**. When it is desired to close ball valve **116**, fluid pressure is released from control line passage **64**, permitting piston **118** to displace upwardly. If desired, fluid pressure may be applied to the balance line to assist in displacing piston **118** upwardly.

Positioned within subsea test tree **50** and extending through latch head assembly **54** and valve assembly **52** is a frangible liner **134**. Frangible liner **134** provides a protective layer between moving particles, such as sand, gravel or proppants in a treatment fluid, and the shoulders and moving components of subsea test tree **50** to prevent erosive and other damage to these components and well as to prevent buildup of these particles within subsea test tree during the treatment operation. In the illustrated embodiment, frangible liner **134** is depicted as being formed as a single liner extending from upper sub **56** to lower sub **58**, however, those skilled in the art will recognize that frangible liner **134** could be formed in multiple sections that are coupled or interconnected together or in multiple sections that are not coupled or interconnected together so long as the critical components of subsea test tree **50** are protected.

In certain embodiments, frangible liner **134** may be installed within subsea test tree **50** at the surface prior to lowering subsea test tree **50** into BOP stack **14**. Alternatively, frangible liner

134 may be positioned within a section of the tubular string above subsea test tree **50** and shifted into the illustrated position prior to a treatment operation. In either embodiment, if desired, frangible liner **134** may be retracted out of subsea test tree **50** into the section of the tubular string above subsea test tree **50** after the treatment operation. As another alternative, if desired, frangible liner **134** may be shattered, disintegrated into small fragments or pieces or otherwise removed from subsea test tree **50** by mechanical, acoustic or explosive means or through the use of a chemical process after the treatment operation.

Frangible liner **134** is formed from a thin walled tubular, preferably having a wall thickness of between about 50 and 100 thousandth of an inch and more preferably between about 60 and 70 thousandth of an inch. Frangible liner **134** may be constructed from any material that is suitable for its intended purpose including, but not limited to, ceramics, fiberglass, epoxies, graphic epoxy, glass ceramics and polymers, any of which may be chemically treated to enhance the desired properties. Frangible liner **134** preferably has a smooth inner surface and, as best seen in FIG. 2D, tapered ends to minimize its effects on the flow of a treatment fluid therethrough. Preferably, the tapered ends have a shallow angle such as between about 5 and 20 degrees and more preferably between about 8 and 12 degrees. In order to maintain a desired bore size, frangible liner **134** preferably has a close fitting relationship with the inner surfaces of subsea test tree **50**. In addition, due to its material properties and wall thickness, frangible liner **134** preferably does not have a fluid tight sealing relationship with the inner surfaces of subsea test tree **50** such that frangible liner **134** will not have to withstand the pressure within subsea test tree **50**.

Importantly, frangible liner **134** is designed and constructed such that it shatters in response to the closure of flapper valve **134** and/or ball valve **116** of valve assembly **52** in the event of an emergency condition or other event requiring closure of one or more of the valves in valve assembly **52**, as best seen in FIGS. 3A-3D. The material of frangible liner **134** will shatters into numerous pieces in response to the inwardly radially directed impact and forces applied thereto by the closure of valves such as flapper valve **134** and ball valve **116**. Upon shattering, the fragments **136** of frangible liner **134** are sufficiently small such that full and proper operation of flapper valve **134** and ball valve **116** is accomplished following the shattering process.

While this invention has been described with reference to illustrative embodiments, this description is not intended to be construed in a limiting sense. Various modifications and combinations of the illustrative embodiments as well as other embodiments of the invention will

be apparent to persons skilled in the art upon reference to the description. It is, therefore, intended that the appended claims encompass any such modifications or embodiments.

What is claimed is:

1. A subsea safety system for use during a well treatment operation, the subsea safety system comprising:
 - a tubular string having an inner flow passage;
 - at least one valve assembly positioned within the tubular string, the at least one valve assembly operable between open and closed positions to selectively permit and prevent fluid flow therethrough; and
 - a frangible liner disposed within the at least one valve assembly, the frangible liner operable to protect the at least one valve assembly from particle flow during the well treatment operation and operable to shatter responsive to closure of the at least one valve assembly, thereby allowing full operation of the at least one valve assembly.
2. The subsea safety system as recited in claim 1 wherein the at least one valve assembly further comprises a safety valve.
3. The subsea safety system as recited in claim 1 wherein the at least one valve assembly further comprises a flapper valve.
4. The subsea safety system as recited in claim 1 wherein the at least one valve assembly further comprises a ball valve.
5. The subsea safety system as recited in claim 1 wherein the at least one valve assembly further comprises at least two valve assemblies.
6. The subsea safety system as recited in claim 1 wherein the frangible liner further comprises a smooth inner surface.
7. The subsea safety system as recited in claim 1 wherein the frangible liner further comprises at least one tapered end.
8. The subsea safety system as recited in claim 1 wherein the frangible liner further comprises a material selected from the group consisting of ceramics, fiberglass, epoxies, graphic epoxy, glass ceramics and polymers.
9. The subsea safety system as recited in claim 1 wherein the frangible liner has a close fitting relationship with the at least one valve assembly.

10. A subsea safety system for use during a well treatment operation, the subsea safety system comprising:

a tubular string having an inner flow passage;

at least one valve assembly positioned within the tubular string, the at least one valve assembly operable between open and closed positions to selectively permit and prevent fluid flow therethrough; and

a frangible liner disposed within the at least one valve assembly, the frangible liner having a close fitting relationship with the at least one valve assembly, the frangible liner operable to protect the at least one valve assembly from particle flow during the well treatment operation and operable to shatter responsive to closure of the at least one valve assembly, thereby allowing full operation of the at least one valve assembly.

11. The subsea safety system as recited in claim 10 wherein the at least one valve assembly is selected from the group consisting of safety valves, flapper valves and ball valves.
12. The subsea safety system as recited in claim 10 wherein the frangible liner further comprises a smooth inner surface.
13. The subsea safety system as recited in claim 10 wherein the frangible liner further comprises at least one tapered end.
14. The subsea safety system as recited in claim 10 wherein the frangible liner further comprises a material selected from the group consisting of ceramics, fiberglass, epoxies, graphic epoxy, glass ceramics and polymers.
15. A method of operating a subsea safety system comprising:

positioning at least one valve assembly within a tubular string having an inner flow passage;

disposing a frangible liner within the at least one valve assembly;

pumping a treatment fluid through the inner flow passage of the tubular string;

protecting the at least one valve assembly from particles in the treatment fluid with the frangible liner;

operating the at least one valve assembly from an open position to a closed position to prevent fluid flow therethrough; and

shattering the frangible liner in response to the closing of the at least one valve assembly, thereby allowing full operation of the at least one valve assembly.

16. The method as recited in claim 15 wherein operating the at least one valve assembly from an open position to a closed position further comprises operating a flapper valve from an open position to a closed position.
17. The method as recited in claim 15 wherein operating the at least one valve assembly from an open position to a closed position further comprises operating a ball valve from an open position to a closed position.
18. The method as recited in claim 15 further comprising establishing a close fitting relationship between the frangible liner and the at least one valve assembly.