

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/010717 A2

(51) International Patent Classification⁷: **H04Q 1/14**

(21) International Application Number:
PCT/US2003/021545

(22) International Filing Date: 10 July 2003 (10.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/199,981 19 July 2002 (19.07.2002) US

(71) Applicant: **ADC TELECOMMUNICATIONS, INC.**
[US/US]; 13625 Technology Drive, Eden Prairie, MN
55344-2252 (US).

(72) Inventors: **NORRIS, Jeffrey, J.**; 10519 Xylon Road,
Bloomington, MN 55438 (US). **KLUEMPKE, Shari,**
K.; 14701 Portland Avenue South, Burnsville, MN 55337
(US).

(74) Agents: **BRUESS, Steven, C.** et al.; Merchant & Gould
P.C., P.O. Box 2903, Minneapolis, MN 55402-0903 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG,
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished
upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: DIGITAL SWITCHING CROSS-CONNECT MODULE

(57) Abstract: A cross-connect module is disclosed herein. The cross-connect module includes a housing having a front end and a rear end. The rear end includes a rear wall defining connector mounting openings. First and second switching jacks are positioned adjacent the front end of the housing. Rear connectors mount within the connector mounting openings. Cables electrically couple the rear connectors to the switching jacks. A tracer lamp circuit including a power connector and a pin jack are also provided. In depicted embodiments, the rear connectors, the pin jack and the power connector are secured to the rear wall of the housing by snap-fit connections. The depicted module also includes a front cover having structure for providing snap-fit connections with the switching devices.



WO 2004/010717 A2