

TITLE**"AN INK CARTRIDGE REFILLING SYSTEM AND A
METHOD OF REFILLING AN INK CARTRIDGE"**

5 The present invention relates to an ink cartridge refilling system, in particular, for refilling a conventional ink cartridge of a printer and to a method of refilling an ink cartridge.

It is common to refill a conventional ink cartridge of a printer by drilling an aperture in a wall of the ink cartridge and forcing ink through the aperture and into the cartridge by means of a syringe. Once the desired quantity of ink has been transferred to the cartridge, a plug is engaged with the aperture so as to cover the aperture and thereby prevent egress of ink from the cartridge.

10 While this method of refilling an ink cartridge is satisfactory in achieving refilling of an ink cartridge, the method is cumbersome for a user to carry out and messy in that it is likely to result in spillage of ink.

15 In addition, as it is often necessary to carry out several filling operations with the syringe before the ink cartridge is full, the above mentioned disadvantages are repeated with each filling operation. Also, carrying out repeated filling operations is time consuming.

The present invention seeks, among other things, to provide an ink cartridge refilling system which overcomes at least some of the above mentioned disadvantages.

20 In accordance with an aspect of the present invention, there is provided an ink cartridge refilling system including fluid urging means, a receiving portion adapted to receive, in use, an ink cartridge to be refilled with ink and engage in fluid communication with the ink cartridge, and connecting means for connecting the fluid urging means in fluid

communication with the receiving portion and thereby, in use, with an ink cartridge to be refilled with ink, the arrangement being such that operation of the fluid urging means causes ink to flow through the connecting means and into an ink cartridge received, in use, in the receiving portion.

5 In accordance with a further aspect of the present invention, there is provided a method of refilling an ink cartridge, said method including the steps of providing fluid urging means, connecting means and a receiving portion adapted to receive an ink cartridge to be refilled with ink, connecting the fluid urging means, in use, in fluid communication with the receiving portion through the connecting means and thereby, in use, with an ink
10 cartridge to be refilled with ink, and operating the fluid urging means so as to cause ink to flow through the connecting means and into an ink cartridge received, in use, in the receiving portion.

The present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:-

15 Figure 1 is a schematic perspective view of part of an ink cartridge refilling system in accordance with a first embodiment of the present invention, with a receiving portion of the ink cartridge refilling system engaged with an ink cartridge;

Figure 2 shows diagrammatic cross-sectional views of an ink receptacle, a gas urging means and a receiving portion of an ink cartridge refilling system in accordance with the
20 first embodiment of the present invention, with the receiving portion engaged with an ink cartridge;

Figure 3 is a schematic partially exploded perspective view of the ink cartridge refilling system in accordance with the first embodiment of the present invention, with the ink cartridge refilling system engaged with an ink cartridge; and

Figure 4 is a diagrammatic cross-sectional view of an ink cartridge refilling system in accordance with a second preferred embodiment of the present invention, with a receiving portion of the ink cartridge refilling system engaged with an ink cartridge.

Referring to Figures 1 to 3 of the drawings, there is shown a first embodiment of an ink cartridge refilling system 10 engaged with an ink cartridge 12 to be refilled with ink. The system 10 includes a receptacle 14 containing ink 16, a fluid urging means in the form of a syringe 18, first connecting means in the form of a flexible first conduit 20, second connecting means in the form of a flexible second conduit 22 and a receiving portion 24 adapted to receive and engage with the ink cartridge 12.

The ink receptacle 14 includes a receptacle body portion 26, a removable lid 28 which may be used to refill the ink receptacle 14 with ink 16 and a gas inlet nozzle 30 extending into an interior portion of the ink receptacle 14 to a location above the ink 16, the gas inlet nozzle 30 being provided with a one way valve 32 adapted to allow gas 34 to flow into the ink receptacle 14 from the gas inlet nozzle and to restrict flow of gas 34 or ink 16 into the gas inlet nozzle 30 from the ink receptacle 14. The ink receptacle 14 also includes an ink outlet nozzle 36.

The syringe 18 includes a syringe body 38 adapted to slidably receive a plunger 40.

The syringe body 38 includes a circumferential flange portion 42 extending radially of a longitudinal end of the syringe body 38, first sealing means in the form of an inwardly

extending circumferential ridge 44 and a gas outlet nozzle 46 located at a longitudinal end of the syringe body 38 remote from the flange portion 42.

The plunger 40 includes a head portion 48 which engages with the flange portion 42 to limit movement of the plunger 40 towards the syringe body 38, and second sealing means
5 50 extending outwardly of the plunger 40 towards the syringe body 38.

The first and second sealing means together ensure that the plunger 40 forms a substantially hermetic seal with the syringe body 38.

The syringe 18 may also include resiliently biasing means in the form of a spring (not shown) for biasing the plunger 40 away from the syringe body 38 and thereby the syringe
10 18 to an expanded configuration.

The receiving portion 24 includes a body 52 defining a recess portion adapted to receive an ink cartridge to be refilled with ink and restraining members 54 extending away from the recess portion from opposite sides of the body 52, the restraining members being provided with locking members 56 extending inwardly of the body 52 towards each
15 other. The arrangement of the restraining members 54 and associated locking members 56 is such that when an ink cartridge 12 is introduced into the receiving portion 24, the locking members 56 engage with a surface of the ink cartridge 12 and thereby restrain removal of the ink cartridge 12 from the receiving portion 24.

The receiving portion 24 also includes an ink inlet nozzle 58 extending into and engaging
20 with an ink outlet aperture 60 of the ink cartridge 12, the ink inlet nozzle 58 being provided with a one way valve 62 adapted to allow ink to flow from the ink inlet nozzle 58 to the ink cartridge 12 and to restrict flow of ink from the ink cartridge 12 to the ink inlet nozzle 58.

Referring to Figures 1 and 3, the scheme of interconnection of the ink receptacle 14, the syringe 18 and the receiving portion 24 is shown. A first end 64 of the first conduit 20 is connected to the gas inlet nozzle 30 of the ink receptacle 14 and a second end 66 of the first conduit 20 is connected to the gas outlet nozzle 46 of the syringe 18. A first end 68 of the second conduit 22 is connected to the ink outlet nozzle 36 of the ink receptacle 14 and a second end 70 of the second conduit 22 is connected to the ink inlet nozzle 58 of the receiving portion 24.

As shown in Figure 3, the system 10 also includes a container for holding the ink receptacle 14, the syringe 18 and the receiving portion 24 in convenient locations relative to each other. The container includes a base portion 72 and a lid portion 74.

The base portion 72 includes a first recessed portion 76 provided with a first side surface 78 of complementary shape to an outer surface of the ink receptacle 14 such that the ink receptacle 14 sits snugly into the first recessed portion 76. Likewise, the syringe 18 sits in a second recessed portion (not shown) which includes a second side surface (not shown) of complementary shape to an outer surface of the syringe 18. Likewise, the receiving portion 24 sits in a third recessed portion 80 provided with a third side surface 82 of complementary shape to an outer surface of the receiving portion 24. The first and second conduits 20, 22 are located in an interior of the base portion 72 so as to be concealed from view of a user.

In use, a user of the ink cartridge refilling system 10 places an empty ink cartridge 12 into the receiving portion 24 such that the locking members 56 of the restraining members 54 engage with the ink cartridge 12 and the ink outlet aperture 60 of the ink cartridge 12 engages with the ink inlet nozzle 58 of the receiving portion 24.

The user then operates the syringe 18 so as to force air through the first conduit 20 and into the ink receptacle 14, thereby increasing the gas pressure in the ink receptacle 14 and forcing ink 16 to pass through the second conduit 22, the ink inlet nozzle 58, the ink outlet aperture 60 and into the ink cartridge 12. This process is repeated until the ink cartridge 12 is full of ink.

Referring to Figure 4 of the drawings, there is shown a second preferred embodiment of an ink cartridge refilling system 100 engaged with an ink cartridge 12.

The ink cartridge refilling system 100 includes a fluid urging means in the form of a syringe 102, and a housing 103 including connecting means in the form of a flexible conduit 104 and a receiving portion 106 for receiving and engaging with an ink cartridge 12.

The syringe 102 includes a syringe body 108 adapted to slidably receive a plunger 110. The syringe body 108 includes a piston 112 slidably received in the syringe body 108, a nozzle portion 114 and locking means 116. The plunger 110 includes a plunger body 118 and an urging member 120. The arrangement is such that the plunger 110 is engageable with the syringe body 108 and movement of the plunger 110 towards the syringe body 108 causes the urging member 120 to urge the piston 112 towards the nozzle portion 114 and thereby discharge fluid from the syringe 102.

The housing 103 includes a housing body portion 122 having an upstanding engaging member 124 for engaging with the locking means 116 of the syringe 102 and thereby connecting the syringe 102 in fluid communication with the flexible conduit 104. The locking means 116 and the engaging member 124 together form a twist lock arrangement whereby to lock the syringe to the engaging member 124 the locking means 116 is

engaged with the engaging member 124 and the syringe 102 is rotated about a longitudinal axis of the syringe 102.

The conduit 104 is connected to the receiving portion 106 through an ink inlet nozzle 126 which may include a one way valve, the ink inlet nozzle 126 extending into and engaging
5 with an ink outlet aperture of the ink cartridge 12 when the ink cartridge 12 is engaged with the receiving portion 106.

Also provided is a lid 128 which is pivotable about a hinge 130 from a closed position as shown in Figure 4 to an open position (not shown) wherein an ink cartridge 12 is receivable in the receiving portion 106.

10 It will be appreciated that the receiving portion may include restraining members as with the first embodiment of the invention shown in Figures 1 to 3 to restrain removal of the ink cartridge 12 from the receiving portion 106.

In use, a user places an empty ink cartridge 12 into the housing 103 by opening the lid 128, engages the cartridge 12 with the receiving portion 106 such that the ink inlet nozzle
15 126 engages with the ink outlet aperture of the ink cartridge 12, and closes the lid 128.

The syringe 102 is filled with ink 132 and the syringe 102 is connected to the housing 103 by engaging the locking means 116 with the engaging member 124 and rotating the syringe 102 so as to lock the syringe 102 relative to the housing 103.

The user then operates the syringe 102 so as to cause the plunger 110 to urge the piston
20 112 towards the nozzle portion 114 and thereby force ink 132 in the syringe 102 to pass through the conduit 104, the ink inlet nozzle 126, the ink outlet aperture of the ink cartridge 12 and into the ink cartridge 12.

The user then unlocks the syringe 102 by rotating the syringe 102 and removes the syringe from the housing 103. The full ink cartridge 12 is also removed from the housing and replaced in the printer.

5 It will be appreciated that although one particular shape of receiving portion 24, 106 is shown in the drawings, other shaped receiving portions 24, 106 could be provided depending on the type of ink cartridge which is to be refilled with ink.

10 It will also be appreciated that for ink cartridges for use with colour printers, the refilling system 10, 100 may alternatively include a receiving portion having a plurality of ink inlet nozzles 58, 126, one for each ink outlet aperture of the ink cartridge 12, and a corresponding plurality of conduits, syringes and, in the case of the first embodiment shown in Figures 1 to 3, ink receptacles.

Modifications and variations as would be apparent to a skilled addressee are deemed to be within the scope of the present invention.

CLAIMS

1. An ink cartridge refilling system including fluid urging means, a receiving portion adapted to receive, in use, an ink cartridge to be refilled with ink and engage in fluid communication with the ink cartridge, and connecting means for connecting the fluid urging means in fluid communication with the receiving portion and thereby, in use, with an ink cartridge to be refilled with ink, the arrangement being such that operation of the fluid urging means causes ink to flow through the connecting means and into an ink cartridge received, in use, in the receiving portion.

2. An ink cartridge refilling system as claimed in claim 1, further including a housing including means for holding the fluid urging means and the receiving portion in locations relative to each other.

3. An ink cartridge refilling system as claimed in claim 2, wherein the housing includes an engaging member in fluid communication with the connecting means and the fluid urging means includes locking means adapted to engage with the engaging member and thereby connect the fluid urging means in fluid communication with the connecting means.

4. An ink cartridge refilling system as claimed in claim 3, wherein the engaging member and the locking means together form a twist lock arrangement.

5. An ink cartridge refilling system as claimed in claim 1, further including an ink receptacle in fluid communication with the fluid urging means and in fluid communication with the receiving portion, the arrangement being such that operation of the fluid urging means forces gas into the ink receptacle thereby effecting an increase in pressure in the ink receptacle and causing ink in the ink receptacle to flow into an ink cartridge received in the receiving portion.

6. An ink cartridge refilling system as claimed in claim 5, wherein the ink receptacle includes a gas inlet nozzle extending inwardly of the ink receptacle to a location beyond the level of ink in the ink receptacle, the gas inlet nozzle being connected in fluid communication to the fluid urging means by first connecting means and the ink receptacle being connected in fluid communication to the receiving portion by second connecting means.

7. An ink cartridge refilling system as claimed in claim 6, wherein the gas inlet nozzle includes a one way valve adapted to allow fluid to flow from the gas inlet nozzle to the ink receptacle and to restrain fluid flow from the ink receptacle to the gas inlet nozzle.

8. An ink cartridge refilling system as claimed in any one of claims 5 to 7, wherein the ink receptacle includes a removable lid.

9. An ink cartridge refilling system as claimed in any one of the preceding claims, wherein the receiving portion includes a first recessed portion adapted to receive, in use, an ink cartridge, the first recessed portion having surfaces of complementary shape to external surfaces of an ink cartridge.

5

10. An ink cartridge refilling system as claimed in claim 9, wherein the receiving portion includes restraining means adapted to releasably restrain, in use, removal of an ink cartridge from the receiving portion.

10

11. An ink cartridge refilling system as claimed in claim 10, wherein the restraining means includes a plurality of restraining members each provided with at least one inwardly extending locking member, the locking members being adapted to engage, in use, with a surface of an ink cartridge.

15

12. An ink cartridge refilling system as claimed in any one of the preceding claims, wherein the receiving portion includes an ink inlet nozzle extending, in use, into an ink cartridge received in the receiving portion, the ink inlet nozzle being provided with a one way valve adapted to allow fluid to flow from the ink inlet nozzle, in use, into an ink cartridge received in the receiving portion and to restrain fluid flow, in use, from an ink cartridge received in the receiving portion to the ink inlet nozzle.

20

13. An ink cartridge refilling system as claimed in any one of the preceding claims, wherein the fluid urging means is a syringe.

14. An ink cartridge refilling system as claimed in claim 13, wherein the syringe is resiliently biased towards an expanded configuration.

5 15. An ink cartridge refilling system as claimed in any one of the preceding claims, wherein the receiving portion is adapted to receive a multiple colour ink cartridge, the said system further including a plurality of fluid urging means, and a corresponding plurality of connecting means, each connecting means connecting a fluid urging means in fluid communication with the receiving portion and thereby, in use, with a corresponding one of a plurality of ink outlet apertures of the multiple colour ink cartridge.

10 16. A method of refilling an ink cartridge, said method including the steps of providing fluid urging means, connecting means and a receiving portion adapted to receive an ink cartridge to be refilled with ink, connecting the fluid urging means, in use, in fluid communication with the receiving portion through the connecting means and thereby, in use, with an ink cartridge to be refilled with ink, and operating the fluid
15 urging means so as to cause ink to flow through the connecting means and into an ink cartridge received, in use, in the receiving portion.

20 17. A method as claimed in claim 16, further including the steps of providing an ink receptacle, connecting the ink receptacle in fluid communication with the fluid urging means, connecting the ink receptacle in fluid communication with an ink cartridge to be refilled with ink, and operating the fluid urging means so as to effect an increase in

pressure in the ink receptacle and cause ink in the ink receptacle to flow to the ink cartridge and thereby fill the ink cartridge with ink.

18. An ink cartridge refilling system, comprising:

5 a fluid urging device,

a receiving portion for receiving an ink cartridge to be refilled with ink and engage in fluid communication with the ink cartridge;

at least one connector for connecting the fluid urging device in fluid communication with the receiving portion and with an ink cartridge inserted in said receiving portion; and

10 a housing having means for holding the fluid urging device and the receiving portion in locations relative to each other, said housing comprising an engaging member in fluid communication with the connector, wherein said fluid urging device includes a lock adapted to engage with the engaging member and thereby connect the fluid urging device with said connector;

15 wherein operation of said fluid urging device causes ink to flow through the connector and into an ink cartridge received in the receiving portion.

19. An ink cartridge refilling system as claimed in claim 18, wherein the engaging member and the lock together form a twist lock arrangement.

20

20. An ink cartridge refilling system as claimed in claim 18, wherein the receiving portion includes a first recessed portion adapted to receive an ink cartridge, the first recessed portion having surfaces of complementary shape to external surfaces of an ink cartridge.

21. An ink cartridge refilling system as claimed in claim 20, wherein the receiving portion includes restraining means adapted to releasably restrain removal of an ink cartridge from the receiving portion.

5 22. An ink cartridge refilling system as claimed in claim 21, wherein the restraining means includes a plurality of restraining members each provided with at least one inwardly extending locking member, the locking members being adapted to engage a surface of an ink cartridge.

10 23. An ink cartridge refilling system as claimed in claim 18, wherein the receiving portion includes an ink inlet nozzle extending into an ink cartridge received in the receiving portion, the ink inlet nozzle being provided with a one way valve adapted to allow fluid to flow from the ink inlet nozzle into an ink cartridge received in the receiving portion and to restrain fluid flow from an ink cartridge received in the receiving portion to the ink inlet nozzle.

15

24. An ink cartridge refilling system as claimed in claim 18 wherein the fluid urging device is a syringe.

25. An ink cartridge refilling system as claimed in claim 24, wherein the syringe is resiliently
20 biased towards an expanded configuration.

26. An ink cartridge refilling system, comprising:

a fluid urging device;

a receiving portion for receiving an ink cartridge to be refilled with ink and engage in

25 fluid communication with the ink cartridge;

at least one connector for connecting the fluid urging device in fluid communication with the receiving portion and with an ink cartridge inserted in said receiving portion;

an ink receptacle in fluid communication with the fluid urging device and in fluid communication with the receiving portion,

5 wherein operation of the fluid urging device forces gas into the ink receptacle causing an increase in pressure in the ink receptacle and causing ink in the ink receptacle to flow into an ink cartridge received in the receiving portion.

27. An ink cartridge refilling system as claimed in claim 26, wherein the ink receptacle
10 includes a gas inlet nozzle extending inwardly of the ink receptacle to a location beyond the level of ink in the ink receptacle, the gas inlet nozzle being connected in fluid communication to the fluid urging device by a first connector and the ink receptacle being connected in fluid communication to the receiving portion by a second connector.

15 28. An ink cartridge refilling system as claimed in claim 27, wherein the gas inlet nozzle includes a one way valve adapted to allow fluid to flow from the gas inlet nozzle to the ink receptacle and to restrain fluid flow from the ink receptacle to the gas inlet nozzle.

29. An ink cartridge refilling system as claimed in claim 26, wherein the ink receptacle
20 includes a removable lid.

30. A method of refilling an ink cartridge comprising the steps of:

providing an ink receptacle, a fluid urging device, at least one connector and a receiving portion adapted to receive an ink cartridge to be refilled with ink;

25 connecting the ink receptacle in fluid communication with the fluid urging device,

connecting the ink receptacle in fluid communication with an ink cartridge to be refilled with ink inserted in the receiving portion and

operating the fluid urging device to effect an increase in pressure in the ink receptacle and cause ink in the ink receptacle to flow to the ink cartridge and thereby fill the ink
5 cartridge with ink.

31. An ink cartridge refilling system, comprising:

a plurality of fluid urging devices,

a receiving portion for receiving a multiple color ink cartridge to be refilled with ink
10 and engage in fluid communication with the ink cartridge; and

a plurality of connectors, each connector connecting one of the fluid urging devices in fluid communication with the receiving portion and with a corresponding one of a plurality of ink outlet apertures of a multiple color ink cartridge inserted in the receiving portion,

wherein operation of said fluid urging devices causes ink to flow through the
15 connectors and into an ink cartridge received in the receiving portion.