

SPECIFICATIONELECTRICAL CONNECTOR WITH TERMINAL LOCKING MEANSField of the Invention

This invention generally relates to the art of electrical connectors and, particularly, to a system for locking a terminal within a connector housing.

Background of the Invention

Very generally, electrical connectors normally include a dielectric or insulating housing within which one or more conductive terminals are mounted. The terminals may be secured at a terminating end thereof to an electrical wire, for instance, with an opposite mating end of the terminal disposed within the housing for mating with a terminal of a complementary electrical connector. Quite often, various locking systems are provided for locking the terminals within the connector housing.

For instance, one type of locking system employs cantilevered locking arms which project outwardly from the terminals to lock the terminals in the connector housing. These locking arms cooperate with locking shoulders within a terminal insertion cavity of the housing to ensure that the terminal is in its proper inserted position and to prevent unintentional withdrawal of the terminal. The locking arms typically project outwardly from side walls of the terminal oblique to and opposite the insertion direction of the terminal, whereby the locking arms snap into engagement with the locking shoulders formed within the insertion cavity of the housing.

Locking systems of the character described above that employ cantilevered locking arms have various disadvantages or problems. One problem is encountered when the insertion cavity of the housing is constricted to a

degree that is only slightly larger than the terminal itself. The result is that forces greater than are desired must be overcome to insert the terminal into the cavity. That is because the locking arms engage the constricted portion of the cavity substantially at the point where the locking arms are joined to the side walls of the terminal. The locking arm at this point is substantially fixed and very rigid, requiring excessive forces to resiliently bias the locking arm inwardly. Another disadvantage of cantilevered locking arms is that the free ends of the arms, in some instances, tend to break the locking shoulders of the housing, rather than spreading apart and locking into interior corners where the shoulders join a more substantial portion of the housing.

The present invention is directed to solving the above problems and satisfying a need for an improved locking system between electrical terminals and their respective dielectric housing.

Summary of the Invention

An object, therefore, of the invention is to provide a new and improved locking means between an electrical terminal and the connector housing within which the terminal is mounted.

In the exemplary embodiment of the invention, an electrical connector includes a housing having a stamped and formed elongated terminal-receiving cavity for insertion therein of a terminal in a given insertion direction. The cavity includes a constricted opening leading to a locking shoulder facing in the insertion direction. An elongated terminal is adapted to be inserted into the cavity and includes a body portion with a cantilevered locking arm formed out of a side wall of the body portion. The locking arm has a fixed end joined to the side wall and a free end projecting outwardly from the

side wall oblique to and opposite the insertion direction, the free end being adapted to engage the locking shoulder. The housing and terminal are constructed such that, upon insertion of the terminal into the cavity, the locking arm is biased laterally inwardly and then resiliently returned to a locking position with the free end engaged with the locking shoulder.

The invention contemplates that the locking arm includes a first portion projecting inwardly from the fixed end thereof oblique to and opposite the insertion direction. A second portion projects outwardly from a juncture with the first portion beyond the side wall of the terminal to a free end of the locking arm. Therefore, with the locking arm first projecting inwardly and then back outwardly, a greater moment arm is created at a point where the locking arm engages the constricted opening of the terminal-receiving cavity, and the insertion forces on the terminal are significantly reduced.

As disclosed in the preferred embodiment herein, the terminal is stamped and formed of sheet metal material, and the locking arm includes a first bend at the fixed end thereof and a second bend at the juncture between the first and second portions thereof. Other features of the invention include the provision of a reinforcing rib formed integral with the locking arm and extending lengthwise thereof. The distal end of the locking arm, at the free end thereof, is chamfered and is adapted to engage the locking shoulder and bias the free end laterally outwardly in response to withdrawal forces on the inserted terminal opposite the insertion direction.

The invention also contemplates a terminal with a portion of the bottom wall stamped and bent adjacent the juncture of one arm between the first and second portions whereby, in response to withdrawal forces on the inserted terminal opposite the insertion direction, the juncture and

bottom wall portion will abut one another. Lastly, the invention includes a terminal having a pair of the locking arms on opposite sides of the terminal. The junctures between the first and second portions of the locking arms oppose each other and are adapted to abut each other in response to withdrawal forces on the inserted terminal opposite the insertion direction. The terminal is shown herein as a female terminal with a receptacle at a mating end thereof, with the side walls of the terminal from which the locking arms are formed defining portions of the receptacle.

Other objects, features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings.

Brief Description of the Drawings

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a perspective view of an elongated terminal embodying the concepts of the invention;

FIGURE 2 is a top plan view, on a reduced scale, of the terminal of Figure 1;

FIGURE 3 is a side elevational view of the terminal;

FIGURE 4 is a section, on an enlarged scale, taken generally along line 4-4 of Figure 3;

FIGURE 5 is a section, on an enlarged scale, taken generally along line 4-4 of Figure 3 showing an alternate embodiment;

FIGURES 6-9 are sequential views of serial positions of insertion of the terminal into a connector housing; and

FIGURE 10 is a view similar to that of Figures 6-9, but showing the configuration of the locking arms when withdrawal forces are applied to the terminal.

Detailed Description of the Preferred Embodiment

Referring to the drawings in greater detail, and first to Figures 1-3, the invention is embodied in an electrical connector which includes an elongated terminal, generally designated 10, which includes a mating end, generally designated 12, and a terminating end, generally designated 14. The terminal is a unitary structure stamped and formed of conductive sheet metal material.

Terminal 10 is constructed as a female terminal, with mating end 12 formed in a box-like configuration defining a receptacle 16 for receiving a complementary male terminal, such as a terminal pin. In essence, mating end 12 defines a body having a top wall 18, a bottom wall 20 and a pair of opposite side walls 22.

Terminating end 14 of terminal 10 includes a rear pair of crimp arms 24 and a forward pair of crimp arms 26. Crimp arms 24 are adapted for crimping onto the outer insulating cladding of an insulated electrical cable. Crimp arms 14 are adapted to crimp onto the inner conductor of the cable, all of which is generally known in the electrical connector art.

Still referring to Figures 1-3, terminal 10 includes a pair of cantilevered locking arms, generally designated 28, formed out of side walls 22 of mating end 12 of the terminal. Referring to Figure 4 in conjunction with Figures 1-3, each locking arm has a fixed end 30 joined to one of the side walls 22 and a free end 32 projecting outwardly from the respective side wall oblique to and opposite an insertion direction "A" of the terminal. As will be described in greater detail hereinafter, free ends 32 of the terminals are adapted to engage behind a pair of locking shoulders of the connector housing.

Still referring to Figure 4 in conjunction with Figures 1-3, each locking arm 28 is stamped out of an opening 34 in a respective one of the side walls 22 of the

terminal. Each locking arm includes a first portion 36 that projects inwardly from fixed end 30 oblique to and opposite the insertion direction "A" of the terminal. A second portion 38 projects outwardly from a juncture 40 with the first portion 36 beyond the respective side wall 22 to free end 32 of the locking arm. As stated above, terminal 10 preferably is stamped and formed of sheet metal material. Consequently, each locking arm 28 includes a first bend 42 at fixed end 30 and a second bend at juncture 40 between first and second portions 36 and 38, respectively, of the locking arm.

Lastly, each locking arm includes other features such as an indented reinforcing rib 44 formed integral therewith and extending lengthwise thereof on the outside of the arm. In addition, a chamfered distal end 46 of each locking arm 28 is formed at free end 32 thereof, for purposes to be described hereinafter.

Figure 5 shows a cross section of the terminal 10 having one locking arm 28 stamped from a side wall 22. Also shown is an upstanding abutment wall 39 stamped from the bottom wall 41 adjacent the sidewall 22. As a withdrawal force is placed on the terminal, locking arm 28 tends to seat further into corner 60 (Fig. 6) of locking shoulder 58. The locking arm becomes deformed or bends inwardly to an extent that juncture or bend 40 abuts abutment wall 39.

Referring to Figure 6, an electrical connector, generally designated 48, includes one or more terminals 10 insertable into one or more elongated terminal-receiving cavities 50 in a connector housing 52. Each terminal-receiving cavity has a constricted opening 54 joining a front region 56. A pair of locking shoulders 58 are defined at opposite sides of the cavity immediately forwardly of constricted opening 54. The shoulders define interior corners 60. Lastly, cavity 50 is tapered, as at

62, leading to constricted opening 54 in insertion direction "A" of terminal 10.

Referring to Figures 7-9 in conjunction with Figure 5, terminal 10 is inserted into cavity 50 in the insertion direction indicated by arrow "A" in Figure 5. Initially, the forward mating end 18 of the terminal passes through constricted opening 54 in the direction of arrow "B" as shown in Figure 7, arrow "B" corresponding to the insertion direction "A" of the terminal.

Upon further insertion of the terminal into the cavity, locking arms 28 will begin to engage tapered portions 62 of cavity 50 which bias or compress the locking arms laterally inwardly toward each other as the locking arms pass through constricted opening 54 as seen in Figure 8.

Further insertion of terminal 10 into cavity 50 of connector housing 52 in the direction of arrow "C" (Fig. 8) will cause the terminal to reach its fully inserted position as shown in Figure 9. As the terminal reaches its fully inserted position, locking arms 28 will resiliently return or "snap" laterally outwardly to positions of locking engagement behind locking shoulders 58. Withdrawal movement of the terminal opposite its insertion direction now is prevented by this interengagement of the free ends of the locking arms with the locking shoulders.

Figure 10 shows a condition of terminal 10 when a withdrawal force is applied to the terminal in the direction of arrow "D", such as forces pulling on the electrical cable that is terminated to the terminal. When such withdrawal forces are applied to the terminal, locking arms 28 tend to seat further into corners 60 (Fig. 6) of locking shoulders 58. This is facilitated by chamfered distal ends 46 (Fig. 4) of the locking arms. In addition, it can be seen in Figure 9 that the locking arms have been deformed or bent inwardly to an extent that junctures or

bends 40 (Fig. 4) abut each other, as at 70 in Figure 9. This abutment significantly shortens the effective moment arms of the locking arms and significantly increases the forces that would be required to pull or withdraw the terminal out of its fully inserted position.

In conclusion, an advantage of the "double-bend" locking arms 28 over the prior art can be understood by reference back to Figure 4. In known locking systems wherein locking arms are bent outwardly immediately at their ends fixed to the side walls of the terminal, such as bending locking arms 28 outwardly immediately at fixed ends 30, it can be understood that an extremely small moment arm is created between the fixed ends of the locking arms and the points at which the locking arms would engage constricted opening 54 in connection housing 52. By providing the double-bend configuration of locking arms 28 as described above and best shown in Figure 4, locking arms 28 engage the constricted opening at points 72 which can be seen to be spaced significantly from fixed ends 30 of the locking arms. In fact, with the depiction of Figure 4, it can be seen that the moment arms (i.e. the distance between fixed ends 30 and points 72) are almost one-third the lengths of the locking arms. Therefore, the arms are provided with significantly increased resiliency compared to prior-art locking arms, which, in turn, desirably reduces the insertion forces on the terminal to a considerable extent.

It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

CLAIMS

1. In an electrical connector (48) which includes,

a housing (52) having an elongated terminal-receiving cavity (50) with a rear constricted opening (54) joining a front region, said front region having a forwardly facing locking shoulder (58) with an interior corner adjacent the opening, and

a stamped and formed elongated terminal (10) adapted to be slidably inserted into said cavity (50) and having a body (18) with a pair of resiliently opposed rearwardly extending cantilevered locking arms (28) having free ends (32) that are normally spaced apart a distance that is greater than a given width of the opening,

whereby, when said terminal is inserted into said cavity (50), said locking arms (28) are compressed toward each other, so that the terminal can pass through the opening, and are resiliently returned when reaching the front region to define an inserted position, said free ends (32) of the arms engaging said shoulder (58) to resist a rearward terminal withdrawal force when said terminal is in its inserted position,

wherein the improvement comprises:

each locking arm (28) including,

a first portion (36) pivotally extending inwardly into the body, and

a second portion (38) pivotally extending from a juncture (40) with said first portion outwardly from said body,

the junctures (40) of both arms (28) being normally spaced apart,

whereby, when a rearward withdrawal force is applied to the terminal in its inserted position, said junctures (40) move inwardly toward each other until they touch while the free ends (32) move outwardly from the body



forcing the free ends into the interior corner of said locking shoulder (58) and allowing a larger force to be applied without causing buckling of the arms.

2. In an electrical connector as set forth in claim 1, wherein said locking arms (28) include reinforcing ribs (72) formed integral therewith and extending lengthwise thereof.

3. In an electrical connector as set forth in claim 1, wherein distal ends (32) of the locking arms (28) at the free ends thereof are chamfered (46) and adapted to engage said locking shoulders and bias the free ends laterally outwardly in response to withdrawal forces on the inserted terminal.

4. In an electrical connector as set forth in claim 1, wherein said terminal (10) is a female terminal with a receptacle (16) at a mating end (18) thereof, said body forming the receptacle.

5. In an electrical connector (48) which includes

a housing (52) having an elongated terminal-receiving cavity (50) for insertion therein of a terminal (10) in a given insertion direction (A), the cavity including a constricted opening (54) leading to locking shoulders (58) facing in said direction, and

a stamped elongated terminal adapted to be inserted into said cavity (50) and having a body portion (18) with cantilevered locking arms (28) formed out of opposite side walls (22) of the body portion, the locking arms each having a fixed end (30) joined to the respective side wall (22) and a free end (32) projecting outwardly from the side wall (22) oblique to and opposite said



insertion direction (A) and adapted to engage the respective locking shoulder (58),

the housing and terminal being constructed such that, upon insertion of the terminal (10) into the cavity (50), the locking arms (28) are biased laterally inwardly and then resiliently returned to a locking position with the free ends (32) thereof engaged with the locking shoulders (58),

wherein the improvement comprises:

said locking arms (28) each having a first portion (36) projecting inwardly from the respective fixed end oblique to and opposite said insertion direction, and a second portion (30) projecting outwardly from a juncture (40) with the first portion beyond the respective side wall to said free end (32) of the locking arm, the junctures (40) between the first and second portions (36,38) of the locking arms (28) opposing each other and adapted to abut each other in response to withdrawal forces on the inserted terminal (10) opposite said insertion direction (C).

6. In an electrical connector as set forth in claim 5, wherein each of said locking arms (28) includes a first bend (42) at the fixed end (30) thereof and a second bend at the juncture (40) between said first and second portions thereof.

7. In an electrical connector as set forth in claim 5, wherein each of said locking arms (28) includes a reinforcing rib (44) formed integral therewith and extending lengthwise thereof.





* C L M S *

8. In an electrical connector as set forth in claim 5, wherein a distal end (32) of each locking arm (28) at said free end thereof is chamfered (46) and is adapted to engage the respective locking shoulder (58) and bias the free end laterally outwardly in response to withdrawal forces on the inserted terminal opposite said insertion direction (A).

9. In an electrical connector as set forth in claim 5, wherein said terminal is a female terminal (10) with a receptacle (16) at a mating end (18) thereof, said side walls forming a part of the receptacle.








FIG. 2




FIG. 3




FIG. 5

48









FIG.6



ABSTRACT

ELECTRICAL CONNECTOR WITH TERMINAL LOCKING MEANS

An electrical connector (48) includes a housing (52) having an elongated terminal-receiving cavity (50) for insertion therein of a terminal (10) in a given insertion direction (A). The cavity includes a constricted opening (54) leading to a locking shoulder (58) facing in the insertion direction. An elongated terminal (10) is adapted to be inserted into the cavity (50) and has a body portion (18) with a cantilevered locking arm (28) formed out of a side wall (22) of the body portion. The locking arm has a fixed end (30) joined to the side wall and a free end (32) projecting outwardly from the side wall oblique to and opposite the insertion direction. The free end (32) is adapted to engage the locking shoulder (58). The housing (52) and terminal (10) are constructed such that, upon insertion of the terminal into the cavity (50), the locking arm (28) is biased laterally inwardly and then resiliently returned to a locking position with the free end (32) thereof engaged with the locking shoulder (58). The locking arm (28) has a first portion (36) bent inwardly from the fixed end (30) oblique to and opposite the insertion direction. A second portion (38) of the locking arm is bent outwardly from a juncture (40) with the first portion (36) beyond the side wall (22) to the free end (32) of the locking arm (28).

This Sheet Has Been Replaced



Date 01 APR 1996

ELECTRICAL CONNECTOR WITH TERMINAL LOCKING MEANSABSTRACT

A terminal (10) is disclosed for insertion into a terminal-receiving cavity (50) where the cavity has a locking shoulder (58) facing in the insertion direction. The terminal (10) has a cantilevered locking arm (28) formed out of a side wall (22). This arm includes a first portion and a second portion. The first portion (36) is bent inwardly from the fixed end (30). A second portion (38) of the locking arm is bent outwardly from a juncture (40) with the first portion (36) beyond the side wall (22) to the free end (32) of the locking arm (28). The free end is adapted to engage the locking shoulder (58). The juncture (40) of each terminal will contact each other after a sufficient withdrawal force is placed on the terminal.

FIG. 1

1-2321028