WHAT IS CLAIMED IS:

1. A method, comprising:

accessing a mempool of a miner of a blockchain system, the mempool containing at least a first transaction and a second transaction, wherein the first transaction and the second transaction each include a respective priority for being written into the blockchain system;

determining that the first transaction and the second transaction are related to each other;

linking, in response to the determining, the first transaction and the second transaction, wherein the linking comprises reassigning the priority of at least the first transaction or the second transaction, wherein the reassigning the priority comprises assigning a same priority to both the first transaction and the second transaction;

aggregating data associated with the first transaction and the second transaction into an aggregated data set; and

writing the aggregated data set into a single block of the blockchain system.

2. The method of claim 1, wherein the reassigning the priority comprises elevating the priority of both the first transaction and the second transaction to the same priority.

3. The method of claim 1, wherein the reassigning the priority comprises elevating the priority of at least the first transaction or the second transaction.

4. The method of claim 1, wherein the determining comprises determining that the first transaction and the second transaction share a common user, a common merchant, a common payment processor, a common location, or are performed within a predetermined time period within each other.

5. The method of claim 1, wherein the determining comprises determining that the first transaction and the second transaction originated from a same underlying event.

6. The method of claim 1, further comprising: introducing a delay for writing the first transaction or the second transaction into the blockchain system until the determining has been completed.

7. The method of claim 1, further comprising: storing transaction data from different tenants in different compartments of the mempool.

8. The method of claim 7, further comprising:

writing a name of a first tenant into a header of a selected block of the blockchain system; and

writing transaction data associated only with the first tenant into the selected block.

9. The method of claim 1, wherein the mempool further contains a third transaction and a fourth transaction, and wherein the method further comprises:

determining a first mining fee associated with mining the third transaction and a second mining fee associated with mining the fourth transaction; and

assigning a higher priority to the third transaction in response to determining that the first mining fee is greater than the second mining fee; or

assigning a higher priority to the fourth transaction in response to determining that the second mining fee is greater than the first mining fee.

10. A system, comprising:

a non-transitory memory; and

one or more hardware processors coupled to the non-transitory memory and configured to read instructions from the non-transitory memory to cause the system to perform operations comprising:

accessing a mempool of a miner of a blockchain system, the mempool containing at least a first transaction having a first priority and a second transaction having a second priority;

determining a relatedness indication between the first transaction and the second transaction based at least on one or more factors comprising: whether the first transaction and the second transaction share a common user, a common merchant, a common payment processor, or a common location, or are performed within a predetermined time period within each other;

linking, in response to the relatedness indication exceeding a predetermined threshold, the first transaction and the second transaction, wherein the linking comprises reassigning at least one of the first priority or the

second priority, wherein the reassigning the priority comprises assigning a same priority to both the first transaction and the second transaction;

aggregating data associated with the first transaction and the second transaction into an aggregated data set; and

writing the aggregated data set into a single block of the blockchain system.

11. The system of claim 10, wherein the reassigning the priority comprises elevating the first priority and the second priority to the same priority.

12. The system of claim 10, wherein the operations further comprise: postponing the first transaction or the second transaction from being written into the blockchain system until the determining has been completed.

13. The system of claim 10, wherein the operations further comprise:

storing transaction data from different tenants in different compartments of the mempool;

writing a name of a first tenant into a header of a selected block of the blockchain system; and

writing transaction data associated only with the first tenant into the selected block.

14. The system of claim 10, wherein the mempool further contains a third transaction and a fourth transaction, and wherein the operations further comprise:

determining a first mining fee associated with mining the third transaction and a second mining fee associated with mining the fourth transaction; and

assigning a higher priority to the third transaction in response to determining that the first mining fee is greater than the second mining fee; or

assigning a higher priority to the fourth transaction in response to determining that the second mining fee is greater than the first mining fee.