

SYSTEMS, METHODS, AND COMPUTER PROGRAM PRODUCTS FOR
SUPPORTING MULTIPLE APPLICATIONS AND MULTIPLE INSTANCES
OF THE SAME APPLICATION ON A WIRELESS SMART DEVICE

5

TECHNICAL FIELD

The subject matter described herein relates to effecting wireless payment and other transactions using wireless smart devices. More particularly, the subject matter described herein relates to systems, methods, and computer program products for supporting multiple applications and multiple instances of the same application on a wireless smart device.

BACKGROUND

With the success and widespread prevalence of the use of credit and debit cards for banking transactions, card issuers, such as banks and financial institutions, have turned to wireless smart devices as a means to provide their customers with a richer, more powerful set of features than is possible using a traditional magnetic stripe ("magstripe") credit card.

As used herein, the term "smart device" refers to a device with processing capabilities. A smart device may have on-board memory or other storage capacity, may be written to as well as read from, and may contain one or more applications that perform a particular function. Some smart devices may contain an operating system and/or user interface.

As used herein, the term "wireless smart device" refers to a smart device that can communicate via an electric and/or magnetic field between the device and some other entity, usually a wireless terminal or reader. One type of wireless communications that can be used between a wireless smart device and reader is near field communication (NFC). In one form of near field communication, a wireless smart device may communicate with a reader via inductive coupling of the reader antenna to the device antenna. The two loop antennas effectively form a transformer. The reader amplitude-modulates the RF field to send information to the device. The device communicates with the reader by modulating the loading on the device antenna, which also modulates the load on the reader antenna.

As used herein, the term “payment application” refers to an application that performs a payment or other financial transaction. An example payment application might respond to a request for credit card account information, for example, by providing credit card information, such as the credit card number, the name of the card holder, and the expiration date of the card – i.e., information that is typically coded onto the magnetic stripe of traditional credit cards.

Unlike magstripe cards, which are read-only devices that simply report account information to the magstripe card reader, wireless smart devices containing payment applications may have processing capability with which to perform functions, such as encryption/decryption of data, authentication, authorization, and verification of the user or of the user’s transaction, storage and/or validation of the card-holder’s identification, and so on. Wireless smart devices may interact with wireless readers to enable transactions involving the payment application. Examples of wireless smart devices containing payment applications include mobile phones, smart phones, key fobs, physical cards, personal digital assistants with interfaces to local card readers, and devices provisioned with a soft card.

As used herein, the term “soft card” refers to a software-implemented identity, security, authentication, membership, loyalty, electronic payment, or other card that is loadable onto a device with wireless communications capabilities.

An example of wireless communications commonly used by wireless smart devices is the ISO 14443 interface. The ISO/IEC 14443 specification (hereinafter referred to as the “14443 Specification”) defines a communication protocol for wireless smart devices operating at 13.56MHz in close proximity with a reader antenna. Applications are uniquely identified by an application identifier (AID), defined by the ISO/IEC 7816 specification. An AID has two parts: a 5-byte registered application provider ID (RID), which is issued by a 14443 controlling authority, and a proprietary application identifier extension (PIX), which is assigned by the registered application provider as it sees fit and which may be from one to eleven bytes.

Some applications may limit the number of instances of that application that a wireless smart device may contain. For example, the protocol for the MasterCard Worldwide (formerly MasterCard International) MasterCard PayPass[®] product, which is a contactless device used for banking transactions, defines two AIDs, one for the MasterCard[®] brand and another for the Maestro[®] brand, and does not support multiple instances of the same PayPass[®] application (i.e., with the same AID) within one wireless smart device. Other payment applications that prohibit a wireless smart device from containing more than one application of the same type include American Express[®] ExpressPaySM and JCB[®] QUICPayTM. Application types other than payment applications, such as identity, security, authentication, membership, loyalty, or other application type, may also similarly prohibit a wireless smart device from containing more than one instance of the same application.

There are advantages to allowing multiple instances of the same application on a wireless smart device. For example, it may be desirable to have multiple payment applications from a single financial institution or brand on a single wireless smart device, to allow the consumer to use a single wireless smart device as both a credit card and a debit card, as both a personal card and a corporate card, as both a card with a high credit limit and a card with a low credit limit, and so on. Another advantage is to allow the user multiple card issuer (such as MasterCard) accounts from different financial institutions. None of these advantages are available to the user of a payment or other type of application that does not support multiple instances of the same application on a single wireless smart device. It will be appreciated that the advantages associated with allowing a wireless smart device to support multiple instances of the same application are not limited to payment applications but extend to other types of applications as well.

Accordingly, there exists a need for a system, method, and computer product for providing multiple instances of the same application on a wireless smart device.

SUMMARY

According to one aspect, the subject matter described herein includes a system for supporting multiple instances of the same application. The system includes a wireless smart device for communicating with a wireless reader.

5 The wireless smart device includes multiple instances of the same application for performing wireless transactions with an external device. The wireless smart device also includes an application manager for identifying one of the instances as active, for detecting a request from the wireless reader for performing a wireless transaction, and for communicating the request to the
10 active instance.

According to another aspect, the subject matter described herein includes a system for supporting multiple applications. The system includes a wireless smart device that includes multiple applications for performing wireless transactions with an external device. The wireless smart device also includes
15 an application manager for detecting a request from a wireless reader for performing a wireless transaction, for identifying one of the applications as the target of the request, for determining that the target application is active, and, responsive to that determination, communicating the request to the target application.

20 According to another aspect, the subject matter described herein includes a method for supporting multiple instances of the same application on a wireless smart device. The method includes receiving, using an application manager residing within a wireless smart device having multiple instances of the same application for effecting wireless transactions with an external device,
25 a request from a wireless reader for effecting a transaction, and responsive to that request, identifying one of the instances as active and sending a request for effecting the transaction to the active instance. The method also includes receiving, using the active instance, the request from the application manager for effecting the transaction, and, responsive to that request, sending a
30 response to the wireless reader.

According to another aspect, the subject matter described herein includes a method for supporting multiple applications on a wireless smart

device. The method includes receiving, using an application manager residing within a wireless smart device having multiple applications for performing wireless transactions with an external device, a request from a wireless reader for effecting a transaction, and responsive to that request, identifying one of the applications as a target of that request, determining if the target application is active, and responsive to that determination, communicating the request to the target application. The method also includes receiving, using the target application, the request from the application manager for effecting the transaction, and, responsive to that request, sending a response to the wireless reader.

The subject matter described herein for providing multiple instances of the same application on a wireless smart device may be implemented in hardware, software, firmware, or any combination thereof. As such, the terms "function" or "module" as used herein refer to hardware, software, and/or firmware for implementing the feature being described. In one exemplary implementation, the subject matter described herein may be implemented using a computer program product comprising computer executable instructions embodied in a computer readable medium. Exemplary computer readable media suitable for implementing the subject matter described herein include disk memory devices, chip memory devices, programmable logic devices, application specific integrated circuits, and downloadable electrical signals. In addition, a computer program product that implements the subject matter described herein may be located on a single device or computing platform or may be distributed across multiple devices or computing platforms.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the subject matter described herein will now be explained with reference to the accompanying drawings of which:

Figure 1 is a block diagram illustrating an exemplary wireless smart device according to an embodiment of the subject matter described herein; and

Figure 2 is a message flow diagram illustrating the steps of an exemplary wireless payment transaction according to an embodiment of the subject matter therein; and

Figure 3 is a message flow diagram illustrating the steps of an exemplary payment application selection according to an embodiment of the subject matter therein.

5 DETAILED DESCRIPTION OF THE INVENTION

In accordance with the subject matter disclosed herein, systems, methods, and computer program products are provided for providing multiple instances of the same application on a wireless smart device.

Figure 1 is a block diagram illustrating an exemplary wireless smart
10 device according to an embodiment of the subject matter therein. In Figure 1, a wireless terminal or reader **100** communicates with wireless smart device **102**. Device **102** may contain one or more application managers; two are shown in Figure 1: application manager 1 **104** and application manager 2 **106**.

Each application manager may communicate with multiple applications, such
15 as applications for performing wireless transactions with an external device. Such applications may include identity, security, authentication, membership, loyalty, electronic payment, or other application type. In some embodiments, an application manager may manage multiple instances of the same application. In some embodiments, an application may manage multiple
20 different applications, which may include multiple applications of different types.

Application manager 1 **104** manages application 1 **108**, application 2 **110**, and application 3 **112**, while application manager 2 **106** manages application 4 **114** and application 5 **116**. In the exemplary embodiment illustrated in Figure 1, each application is a payment application and each payment application may
25 represent an account at a bank or other financial entity. Each account may have an account number associated with it (e.g., "AAAA BBBB CCCC DDDD").

Application manager 1 **104** may manage payment applications of a particular type, such as MasterCard PayPass[®], which has an AID of "A0 00 00 00 04 10 10". Application 1 **108**, application 2 **110**, and application 3 **112** may represent
30 multiple instances of the same type (i.e., MasterCard PayPass[®]), and each instance may represent a separate MasterCard account having a unique account number. Similarly, application manager 2 **106** may manage payment applications of another type, such as Maestro PayPass[®], which has an AID of

“A0 00 00 00 04 30 60”. Application 4 **114** and application 5 **116** may represent multiple instances of another type (i.e., Maestro PayPass®), and each instance may represent a separate Maestro account having a unique account number. In some embodiments, an application selection function **118**
5 may allow a user to select an active application and may communicate the selection to application manager 1 **104** and application manager 2 **106**.

Application manager 1 **104** and application manager 2 **106** may each have several functions. One function of application manager 1 **104** and application manager 2 **106** may be to allow a wireless smart device to contain
10 multiple instances of the same application, where the application specification prohibits multiple instances of the same application type on a single wireless smart device. In this case, compliance with the application specification requires that from the perspective of reader **100**, device **102** appears to contain only one application of that type. In Figure 1, application manager 1 **104** and
15 application manager 2 **106** each may appear to reader **100** to be an application of a particular type. Application manager 1 **104** may appear to reader **100** as a single MasterCard PayPass® application, for example, while application manager 2 **106** may appear to reader **100** as a single Maestro PayPass® application. More specifically, if a PayPass® reader **100** requests from device
20 **102** a list of payment applications available on device **102**, the list may include application manager 1 **104** (presented as a MasterCard PayPass® application) and application manager 2 **106** (presented as a Maestro PayPass® application) rather than including the actual PayPass® applications application 1 **108** through application 5 **116**. In other words, the actual PayPass® applications
25 are, in one sense, hidden behind their respective account managers – at least from discovery through normal inquiry by reader **100**. When reader **100** performs a MasterCard PayPass® transaction with device **102**, it appears to reader **100** that device **102** contains only one MasterCard PayPass® application in compliance with the PayPass® specification, when in actuality
30 there are three MasterCard PayPass® applications within device **102**. Figure 2, below, illustrates an example such transaction in detail.

Examples of other functions that may be performed by application manager 1 **104** and application manager 2 **106** include: managing multiple applications of the same type or of different types; notifying the user of completion of a transaction; disabling a wireless smart device's ability to do some (or all) types of transactions; and allowing a user to selectively activate or deactivate individual applications, regardless of type. A user may desire this feature as a means to avoid accidental or malicious transactions from occurring without the user's knowledge, or to avoid the use of a payment account which has reached its credit limit, for example.

Figure 2 is a message flow diagram illustrating the steps of an exemplary wireless payment transaction according to an embodiment of the subject matter described herein. Although Figure 2 is a simplified illustration of a wireless transaction in conformance with the 14443 Specification, the use of other communication specifications and protocols is within the scope of the subject matter described herein. Referring to Figure 2, in step **200**, wireless smart device **102** is placed within the detection field of reader **100**, which detects the presence of device **102**. In some embodiments, device **102** may power up. Device **102** may perform some initialization. Device **102** and reader **100** may perform a handshaking procedure. Reader **100** may request device **102** to provide to reader **100** information about the available applications residing on device **102**. In some embodiments, information about available applications residing within device **102** is provided at the application level. In response to that request, device **102** may return a list or a pointer to a list, or may otherwise convey to reader **100** information about the applications available on device **102**. That information may include the application type or AID for each application. For example, payment terminals may make a request to an application on device **102**, such as the payment system environment (PSE) or the PayPass[®] payment system environment (PPSE), to return a list of payment applications available on device **102**. Reader **100** may choose an appropriate application, if available, from the list. Further communication from reader **100** may be directed to the chosen application, identified by its AID. In embodiments of the subject matter described herein, in response to a request

for information about applications, device **102** may return the AID of application manager 1 **104** instead of the AIDs of application 1 **108**, application 2 **110**, or application 3 **112**. Application manager 1 **104** presents itself to reader **100** as an application of the same type as the applications that it manages (i.e., a MasterCard PayPass[®] application.) Similarly, device **102** may return the AID of application manager 2 **106** instead of the AIDs of application 4 **114** or application 5 **116**. Application manager 2 **106** presents itself to reader **100** as an application of the same type as the applications that it manages (i.e., a Maestro PayPass[®] application.)

10 In step **202**, reader **100** may issue a command to select or otherwise initiate communication with the chosen application, such as the SELECT command. Reader **100** may select application manager 1 **104**, which appears to reader **100** as a payment application. Future communication from reader **100** will be directed toward application manager 1 **104**.

15 In step **204**, application manager 1 **104** may determine which of its managed applications is the active application. Referring to Figure 1, application 1 **108** is the active application, having been previously activated or selected by application selection function **118**, which may be a user selection through a menu, for example, or prior configuration through an alternate

20 means. Each application may have its own unique internal AID, which application manager 1 **104** may use to identify and communicate with individual applications. For example, application 1 **108** may have an AID of "A0 00 00 02 99 04 10 10 57 10", application 2 **110** may have an AID of "A0 00 00 02 99 04 10 10 57 01", and application 3 **112** may have an AID of "A0 00 00 02 99 04 10

25 10 57 10". Returning to Figure 2, application manager 1 **104** may forward the SELECT command to active application 1 **108**, identifying the application by its internal AID. Alternatively, application manager 1 **104** may issue its own internal command to application 1 **108** rather than forwarding the SELECT command issued by reader **100**. Although it is theoretically possible that

30 reader **100** may attempt to bypass an application manager and contact the managed applications directly (by somehow discovering – or guessing – the AID of one of the managed applications and issuing a SELECT command to

that AID) the managed applications may be programmed to reject requests received directly from a reader. For example, application 1 **108** may be able to distinguish between a request from a reader **100** (an external request) and a request from an application manager 1 **104** (an internal request) and respond only to internal requests. An external request may be distinguished from an internal request by, for example, using a different protocol for an internal request, using a different communications path for the internal request, using a different command, command argument, or command option for an internal request, setting a flag to enable a transaction command just prior to issuing the transaction, or by other mechanisms and methods that do not depart from the scope of the subject matter described herein.

In step **206**, active application 1 **108** may respond to the SELECT command (or internal command) by sending information about itself, such as the name of application 1 **108** (e.g., "BankA Credit Card") for example, to reader **100**. The response may also include the AID of the application responding, in which case the identified application may respond, not with the application's internal AID, but with the AID of application manager 1 **104**; otherwise, reader **100** may reject the response, since from the point of view of reader **100**, the application that responded (i.e., application 1 **108**) was not the application to which the request was sent (i.e., application manager 1 **104**).

The remainder of the communication between reader **100** and device **102** may follow the same basic process: reader **100** may send a request to application manager 1 **104**; application manager 1 **104** may forward or reissue the request internally to application 1 **108**; application 1 **108** may send a response back to reader **100**. In an alternate embodiment, application 1 **108** may send a response to another entity within device **102**, such as application manager 1 **104**, which may forward or reissue the response to reader **100**. Steps **208** through **218** illustrate an example payment transaction. In steps **208**, **210**, and **212**, reader **100** may request and receive processing options in preparation for the execution of a financial transaction. In steps **214**, **216**, and **218**, reader **100** may request and receive one or more data records. The data conveyed to reader **100** may include, for example, the equivalent of the data

contained on tracks 1 and 2 of a magstripe device, such as the name of the account holder or card holder, the account number, the expiration date, etc. Steps **214** through **218** may be repeated as many times as necessary to complete the transaction. In some embodiments, the wireless smart device

5 may prompt the user for a personal identification number (PIN) or other authorization code. If reader **100** determines that the transaction is valid, it may complete the process by executing the payment transaction with the bank, financial institution, or other issuing authority of the account represented by the active payment application.

10 Figure 3 is a message flow diagram illustrating the steps of an exemplary application selection according to an embodiment of the subject matter described herein. Referring to Figure 3, user **300**, in step **302**, invokes application selection function **118** in preparation for making a transaction. Alternatively, application selection function **118** may be invoked by device **102**

15 as part of a wireless transaction, for example, to give user **300** an opportunity to verify that the desired application is currently activated. In step **304**, application selection function **118** may present to user **300** a list of available applications from which user **300** may select an application to be activated. The list may be limited to include only those types of applications that are

20 supported by reader **100** (not shown). In step **306**, user **300** may select application 2 **110**. Alternatively, application selection function **118** may determine that there is only one application of the type supported by reader **100**, and activate that application without user interaction, in which case step **302** through step **306** do not occur. In step **308**, in response to selection, by

25 user **300** or otherwise, of an application to be activated, application selection function **118** may deactivate any currently active instance of the same application, such as application 1 **108**. In step **310**, application selection function **118** may notify application manager 1 **104** that previously activated application 1 **108**, which it manages, has been deactivated. In step **312**,

30 application selection function **118** may activate the selected application, application 2 **110**. In step **314**, application selection function **118** may notify

application manager 1 **104** that previously inactive application 2 **110**, which it manages, has been activated.

It should be noted that the activation and deactivation of instances of one application may not affect the status of instances of another application.

5 Referring to Figure 1, for example, activating application 2 **110** may cause previously active application 1 **108** to be deactivated, but the status of application 4 **114** and application 5 **116** may not be affected, since they are instances of one application while application 1 **108**, application 2 **110**, and application 3 **112** are instances of another, different application. Alternatively,
10 activation of one application may cause all other applications or instances of applications, regardless of application or type, to be deactivated. For example, activating application 4 **114** may deactivate not only application 5 **116**, but also application 1 **108**, application 2 **110**, and application 3 **112**.

In an alternate embodiment, application selection function **118** may, in
15 response to selection, by user **300** or otherwise, notify application manager 1 **104** that one of its managed applications has been selected for activation. In response to receipt of that notification, application manager 1 **104**, rather than application selection function **118**, may deactivate currently active instances of the selected application and activate the selected instance of the application.
20 In embodiments where an application manager manages different applications, application manager 1 **104**, rather than application selection function **118**, may activate selected applications either with or without deactivating applications that were active prior to operation of application selection function **118**.

In embodiments where in response to a request from reader **100** for
25 information about available applications residing with device **102**, device **102** communicates a list containing a list of available applications within device **102**, that list may be dynamically modified by application selection function **118** such that when an instance or application is selected to be active, the list is changed so that the list includes the selected application. Optionally, the list may be
30 further modified to remove from the list instances or applications that were not selected. In this way, when reader **100** receives the list of available applications from device **102**, that list may be reduced or constrained to contain

only one instance or application, thus removing from reader **100** the need or ability to make its own selection process. This allows user **300**, rather than reader **100**, to control which application will be used by reader **100**. For example, for embodiments in which device **102** uses a PSE to communicate the list of available applications to reader **100**, the list returned may contain only the last instance or application activated by application selection function **118**.

It will be understood that various details of the subject matter described herein may be changed without departing from the scope of the subject matter described herein. Furthermore, the foregoing description is for the purpose of illustration only, and not for the purpose of limitation.

CLAIMS

What is claimed is:

1. A system for supporting a plurality of instances of the same application, the system comprising:
 - 5 a wireless smart device for communicating with a wireless reader, the wireless smart device including:
 - (a) a plurality of instances of an application for performing wireless transactions with an external device; and
 - (b) an application manager for identifying one of the instances as
10 active, for detecting a request from a wireless reader for performing a wireless transaction, and for communicating the request to the active instance.
2. The system of claim 1 wherein the wireless smart device comprises one of a mobile telephone, a key fob, a physical card, a personal digital
15 assistant, and a device provisioned with a soft card.
3. The system of claim 1 wherein the wireless smart device is adapted to communicate using a close-proximity wireless technology.
4. The system of claim 1 wherein the wireless smart device is adapted to communicate using a near field communications technology.
- 20 5. The system of claim 1 wherein the application comprises an application for effecting identity transactions.
6. The system of claim 1 wherein the application comprises an application for effecting security transactions.
7. The system of claim 1 wherein the application comprises an application
25 for effecting authentication transactions.
8. The system of claim 1 wherein the application comprises an application for effecting membership transactions.
9. The system of claim 1 wherein the application comprises an application for effecting loyalty transactions.
- 30 10. The system of claim 1 wherein the application comprises an application for effecting electronic payment transactions.

11. The system of claim 1 wherein the application manager, by communicating with the active instance, makes the wireless smart device comply with a specification that limits the number of instances of the application on the wireless smart device to one.
- 5 12. The system of claim 1 comprising an application selection function for selecting one of the plurality of instances to be active.
13. The system of claim 12 wherein the application selection function is adapted to present to a user a list of available instances, to receive an instance selection from the user, and in response to the selection to
- 10 activate the selected instance.
14. The system of claim 12 wherein the application selection function, in response to selecting one of the plurality of instances to be active, deactivates any instance that is not the instance selected to be active.
15. The system of claim 12 comprising an application listing function for
- 15 detecting a request from the wireless reader for a list of applications available within the wireless smart device, and responsive to detecting that request, communicating a list of available applications to the wireless reader, and wherein the application selection function is adapted to modify, in response to selecting one of the plurality of
- 20 instances to be active, the list of available applications such that the selected instance is included in the list of available applications.
16. The system of claim 15 wherein the application selection function is adapted to modify, in response to selecting one of the plurality of instances to be active, the list of available applications such that
- 25 instances that are not the selected instance are removed from the list of available applications.
17. The system of claim 15 wherein the application listing function is performed by a payment system environment (PSE) application.
18. A system for supporting a plurality of applications, the system
- 30 comprising:
a wireless smart device including:

- (a) a plurality of applications for performing wireless transactions with an external device; and
- (b) an application manager for detecting a request from a wireless reader for performing a wireless transaction, for identifying one of the applications as the target of the request, for determining that the target application is active, and, responsive to the determination, communicating the request to the target application.
19. The system of claim 18 wherein the wireless smart device comprises one of a mobile telephone, a key fob, a physical card, a personal digital assistant, and a device provisioned with a soft card.
20. The system of claim 18 wherein the wireless smart device is adapted to communicate using a close-proximity wireless technology.
21. The system of claim 18 wherein the wireless smart device is adapted to communicate using a near field communications technology.
22. The system of claim 18 wherein the plurality of applications includes an application for effecting identity transactions.
23. The system of claim 18 wherein the plurality of applications includes an application for effecting security transactions.
24. The system of claim 18 wherein the plurality of applications includes an application for effecting authentication transactions.
25. The system of claim 18 wherein the plurality of applications includes an application for effecting membership transactions.
26. The system of claim 18 wherein the plurality of applications includes an application for effecting loyalty transactions.
27. The system of claim 18 wherein the plurality of applications includes an application for effecting electronic payment transactions.
28. The system of claim 18 wherein the plurality of applications includes a plurality of applications of the same type.
29. The system of claim 18 wherein the plurality of applications includes a plurality of instances of the same application.

30. The system of claim 18 wherein the application manager, by communicating with the active application, makes the wireless smart device comply with a specification that limits the number of applications of that type on the wireless smart device to one.
- 5 31. The system of claim 18 comprising an application selection function for selecting one of the plurality of applications to be active.
32. The system of claim 31 wherein the application selection function is adapted to present to a user a list of available applications, to receive an application selection from the user, and in response to the selection to
- 10 activate the selected application.
33. The system of claim 31 wherein the application selection function, in response to selecting one of the plurality of instances to be active, deactivates any instance that is not the instance selected to be active.
34. The system of claim 31 comprising an application listing function for
- 15 detecting a request from the wireless reader for a list of applications available within the wireless smart device, and responsive to detecting that request, communicating a list of available applications to the wireless reader, and wherein the application selection function is adapted to modify, in response to selecting one of the plurality of
- 20 instances to be active, the list of available applications such that the selected instance is included in the list of available applications.
35. The system of claim 34 wherein the application selection function is adapted to modify, in response to selecting one of the plurality of instances to be active, the list of available applications such that
- 25 instances that are not the selected instance are removed from the list of available applications.
36. The system of claim 34 wherein the application listing function is performed by a payment system environment (PSE) application.
37. A method for supporting a plurality of instances of the same application
- 30 on a wireless smart device, the method comprising:

- 5 (a) using an application manager residing within a wireless smart device having a plurality of instances of the same application for effecting wireless transactions with an external device:
- i) receiving a request from a wireless reader for effecting a transaction; and
 - ii) responsive to the request from the wireless reader, identifying one of the instances residing within the wireless smart device as active, and sending a request for effecting the transaction to the active instance; and
- 10 (b) using the active instance:
- i) receiving the request from the application manager for effecting the transaction; and
 - ii) responsive to the request from the application manager, effecting the transaction.
- 15 38. The method of claim 37 wherein using the wireless smart device comprises using one of a mobile telephone, a key fob, a physical card, a personal digital assistant, and a device provisioned as a soft card.
39. The method of claim 37 wherein receiving a request from and sending a response to the wireless reader includes communicating using a close-
- 20 proximity wireless technology.
40. The method of claim 37 wherein receiving a request from and sending a response to the wireless reader includes communicating using a near field communications technology.
41. The method of claim 37 wherein the application comprises an
- 25 application for effecting identity transactions.
42. The method of claim 37 wherein the application comprises an application for effecting security transactions.
43. The method of claim 37 wherein the application comprises an application for effecting authentication transactions.
- 30 44. The method of claim 37 wherein the application comprises an application for effecting membership transactions.

45. The method of claim 37 wherein the application comprises an application for effecting loyalty transactions.
46. The method of claim 37 wherein the application comprises an application for effecting electronic payment transactions.
- 5 47. The method of claim 37 wherein receiving the request from a wireless reader includes receiving a request for effecting a wireless payment transaction.
48. The method of claim 37 wherein effecting the transaction includes sending a response to the wireless reader using the active instance.
- 10 49. The method of claim 37 wherein effecting the transaction includes sending a response to the application manager using the active instance and, in response to receiving, by the application manager, a response from the active instance, sending a response to the wireless reader using the application manager.
- 15 50. The method of claim 37 wherein, by using the application manager for communicating with the active instance, the wireless smart device complies with a specification that limits the number of instances of the application on the wireless smart device to one.
51. The method of claim 37 comprising selecting, using an application selection function, one of the plurality of instances and activating the selected instance.
- 20 52. The method of claim 51 wherein using the application selection function includes presenting to a user a list of available instances from which the user may select an instance to be activated, determining which instance is selected by the user, and responsive to the determination, activating the selected instance.
- 25 53. The method of claim 51 wherein using the application selection function includes deactivating any instance that is not the selected instance.
54. The method of claim 51 comprising detecting a request from the wireless reader for a list of applications available within the wireless smart device, and responsive to detecting that request, communicating a list of available applications to the wireless reader, and wherein using
- 30

- the application selection function includes modifying, in response to selecting one of the plurality of instances, the list of available applications to include in the list of available applications the selected instance.
- 5 55. The method of claim 54 comprising modifying, in response to selecting one of the plurality of instances, the list of available applications to remove from the list of available applications any instance that is not the selected instance.
- 10 56. The method of claim 54 including using a payment system environment (PSE) application for communicating the list of available applications to the wireless reader.
- 15 57. A method for supporting a plurality of applications on a wireless smart device, the method comprising:
- (a) using an application manager residing within a wireless smart device having a plurality of applications for performing wireless transactions with an external device:
- i) receiving a request from a wireless reader for effecting a transaction; and
- 20 ii) responsive to the request from the wireless reader, identifying one of the applications residing within the wireless smart device as a target of the request, determining that the target application is active, and, responsive to that determination, communicating the request to the target application; and
- 25 (b) using the target application:
- i) receiving the request from the application manager for effecting the transaction; and
- ii) responsive to the request from the application manager, effecting the transaction.
- 30 58. The method of claim 57 wherein using the wireless smart device comprises using one of a mobile telephone, a key fob, a physical card, a personal digital assistant, and a device provisioned as a soft card.

59. The method of claim 57 wherein receiving a request from and sending a response to the wireless reader includes communicating using a close-proximity wireless technology.
60. The method of claim 57 wherein receiving a request from and sending a response to the wireless reader includes communicating using a near field communications technology.
61. The method of claim 57 wherein the plurality of applications includes at least one application for effecting identity transactions.
62. The method of claim 57 wherein the plurality of applications includes at least one application for effecting security transactions.
63. The method of claim 57 wherein the plurality of applications includes at least one application for effecting authentication transactions.
64. The method of claim 57 wherein the plurality of applications includes at least one application for effecting membership transactions.
65. The method of claim 57 wherein the plurality of applications includes at least one application for effecting loyalty transactions.
66. The method of claim 57 wherein the plurality of applications includes at least one application for effecting electronic payment transactions.
67. The method of claim 57 wherein the plurality of applications includes a plurality of applications of the same type.
68. The method of claim 57 wherein effecting the transaction includes sending a response to the wireless reader using the target application.
69. The method of claim 57 wherein effecting the transaction includes sending a response to the application manager using the target application and, in response to receiving, by the application manager, a response from the target application, sending a response to the wireless reader using the application manager.
70. The method of claim 57 wherein, by using the application manager for communicating with the target application, the wireless smart device complies with a specification that limits the number of applications of that type on the wireless smart device to one.

71. The method of claim 57 comprising selecting, using an application selection function, one of the plurality of applications and activating the selected application.
- 5 72. The method of claim 71 wherein using the application selection function includes presenting to a user a list of available applications from which the user may select an application to be activated, determining which application is selected by the user, and responsive to the determination, activating the selected application.
- 10 73. The method of claim 71 wherein using the application function includes deactivating any application that is not the selected application.
- 15 74. The method of claim 71 comprising detecting a request from the wireless reader for a list of applications available within the wireless smart device, and responsive to detecting that request, communicating a list of available applications to the wireless reader, and wherein using the application selection function includes modifying, in response to selecting one of the plurality of applications, the list of available applications to include in the list of available applications the selected application.
- 20 75. The method of claim 74 comprising modifying, in response to selecting one of the plurality of applications, the list of available applications to remove from the list of available applications any application that is not the selected application.
- 25 76. The method of claim 74 including using a payment system environment (PSE) application for communicating the list of available applications to the wireless reader.
- 30 77. A computer program product comprising computer-executable instructions embodied in a computer-readable medium for performing steps comprising:
(a) using an application manager residing within a wireless smart device having a plurality of instances of the same application for effecting wireless transactions with an external device:

- 5
- i) receiving a request from a wireless reader for effecting a transaction; and
 - ii) responsive to the request from the wireless reader, identifying one of the instances residing within the wireless smart device as active, and sending a request for effecting the transaction to the active instance; and
- (b) using the active instance:
- i) receiving the request from the application manager for effecting the transaction; and
 - 10 ii) responsive to the request from the application manager, effecting the transaction.
78. A computer program product comprising computer-executable instructions embodied in a computer-readable medium for performing steps comprising:
- 15
- (a) using an application manager residing within a wireless smart device having a plurality of applications for performing wireless transactions with an external device:
- i) receiving a request from a wireless reader for effecting a transaction; and
 - 20 ii) responsive to the request from the wireless reader, identifying one of the applications residing within the wireless smart device as a target of the request, determining that the target application is active, and, responsive to that determination, communicating the request to the target application; and
- 25
- (b) using the target application:
- i) receiving the request from the application manager for effecting the transaction; and
 - 30 ii) responsive to the request from the application manager, effecting the transaction.