

MEDICAL DEVICES, SYSTEMS AND METHODS UTILIZING PERMANENT MAGNET AND MAGNETIZABLE FEATURE

FIELD

5

[0001] Principles and embodiments of the present disclosure relate generally to devices, systems and methods including a permanent magnet and a magnetizable feature.

BACKGROUND

10

[0002] Traditionally, penetration of a needle and catheter tubing through skin tissue to reach the vein during catheter insertion is invisible to clinicians. For this reason, they must rely on their first-hand experience with needle insertion in combination with tactile sense to successfully identify the location of the vein. This may be a difficult task when attempting to access a small vein in a deep location under the skin, increasing risk of excess pain and/or

15

injury to the patient.

20

[0003] Emerging procedural guidance systems utilize a combination of ultrasound and magnetic technologies to provide visualization of subdermal anatomy and device position in the in-plane and out-of-plane orientations. This combination of ultrasound and magnetic methods also allows for the projection or anticipation of the insertion device position relative to the patient's anatomy, and thereby improves the likelihood of successfully accessing the vasculature and completing the invasive procedure.

25

[0004] One leading technology targets the cannula as the portion of the invasive device for magnetization, while another leading technology uses a permanent magnet located on the needle hub of the device. Although a permanent magnet offers a more reliable magnetic field as it is not subject to the variation of the clinician magnetizing the needle at the point of use, it does rely more on a calculated projection of the needle tip location. The system that relies on magnetizing the cannula prior to insertion can more reliably measure the actual tip location, but this method is subject to variability on consistently magnetizing the cannula as it relies on the clinician to place the needle into a magnetic device to magnetize the needle. Both of these systems utilize a magnetic field generated by a portion of the cannula subassembly, and therefore, is not able to measure or predict relative motion between the needle hub and catheter adapter subassemblies. Understanding the relative position and motion of these two subassemblies can be used to inform a clinician of procedurally important states of the

30

insertion process, such as when the needle tip reaches the vein, when the catheter tip reaches the vein, when the catheter is advanced to cover the needle tip ("hooding the catheter") and thereby safe for further advancement. It would be desirable to provide medical devices, system and methods that could be used with devices, systems and methods to provide improved
5 visualization during penetration of a needle through a patient's skin tissue.

SUMMARY

[0005] Various embodiments are listed below. It will be understood that the embodiments listed below may be combined not only as listed below, but in other suitable combinations in
10 accordance with the scope of the disclosure. A first aspect pertains to a medical device comprising a catheter assembly, the catheter assembly including a catheter adapter subassembly and a needle subassembly, wherein one of the catheter adapter subassembly and the needle subassembly includes a permanent magnet element, and the other of the catheter subassembly and the needle subassembly includes a magnetizable feature.

15 [0006] A second aspect pertains to a system for determining relative position of a catheter adapter subassembly and a needle subassembly comprising a catheter having a catheter distal tip and a needle having a needle distal tip; a permanent magnet element associated with one of the catheter adapter subassembly and needle subassembly; a magnetizable feature associated with the other of the catheter adapter subassembly and the needle subassembly; and
20 magnetometers positioned with respect to the catheter adapter subassembly and the needle subassembly, the magnetometers configured to determine relative movement of the catheter adapter subassembly and needle subassembly.

[0007] A third aspect pertains to a method for determining a relative position of a catheter tip and a needle cannula tip, the method comprising providing a catheter adapter subassembly
25 including catheter and a needle subassembly including a needle, the catheter having a catheter distal tip and the needle having a needle distal tip; associating a permanent magnet element with one of the catheter and the needle; associating a magnetizable feature with the other of the catheter and the needle; obtaining a measured position of the permanent magnet; obtaining a measured position of the magnetizable feature to obtain a calculated position of the catheter
30 distal tip and a calculated position of the needle distal tip; and comparing the calculated position of the catheter distal tip with the calculated position of the needle distal tip to determine the relative position of the catheter distal tip and the needle distal tip.

[0008] A fourth aspect pertains to a catheter adapter subassembly comprising a magnetic feature selected from the group consisting of a metal mandrel for connecting catheter tubing to the hub, a catheter tubing adhesive, a blood control component of the catheter adapter subassembly, and a magnetic wedge on the catheter adapter body.

5

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Fig. 1 is a perspective view of a catheter assembly that can be utilized according to an embodiment;

[0010] Fig. 2 is an exploded perspective view of the catheter assembly shown in Fig. 1;

10 [0011] Fig. 3 is a top plan view of the catheter assembly shown in Fig. 1;

[0012] Fig. 4 is a top plan view of a catheter assembly according to an embodiment;

[0013] Fig. 5 shows the catheter assembly of Figure 4 with the needle subassembly and catheter adapter subassembly separated;

15 [0014] Fig. 6A is a top plan view showing a portion of a needle subassembly with the needle disconnected from the needle chamber and a magnetic feature;

[0015] Fig. 6B is a top plan view showing a portion of an alternative embodiment of a needle subassembly with the needle disconnected from the needle chamber and a magnetic feature;

[0016] Fig. 6C is a top plan view showing a portion of an alternative embodiment of a needle subassembly with the needle disconnected from the needle chamber and a magnetic feature;

20 [0017] Fig. 6D is a top plan view showing a portion of an alternative embodiment of a needle subassembly with the needle disconnected from the needle chamber and a magnetic feature;

[0018] Fig. 6E is a top plan view showing a portion of an alternative embodiment of a needle subassembly with the needle disconnected from the needle chamber and a magnetic feature;

25 [0019] Fig. 7 is a top plan view of an embodiment of a catheter assembly according to an embodiment;

[0020] Fig. 8 is a top plan view of an embodiment of a catheter assembly according to an embodiment;

[0021] Fig. 9 shows the catheter assembly of Figure 8 with the needle subassembly and catheter adapter subassembly separated;

30 [0022] Fig. 10A is a top plan view of a catheter adapter subassembly according to an embodiment;

[0023] Fig. 10B is a top plan view of a catheter adapter subassembly according to an embodiment;

[0024] Fig. 10C is a top plan view of a catheter adapter subassembly according to an embodiment;

5 [0025] Fig. 10D is a top plan view of a catheter adapter subassembly according to an embodiment;

[0026] Fig. 11 is a perspective view of a catheter assembly showing optional features;

[0027] Fig. 12A is a top plan view of an embodiment of a catheter assembly;

[0028] Fig. 12B shows the catheter assembly of Figure 12A in a first position;

10 [0029] Fig. 12C shows the catheter assembly of Figure 12A with the needle subassembly and catheter adapter subassembly moved with respect to each other;

[0030] Fig. 12D shows the catheter assembly of Figure 12A with the needle subassembly and catheter adapter subassembly moved further apart with respect to each other; and

[0031] Fig. 13 shows an embodiment of a system.

15

DETAILED DESCRIPTION

[0032] Before describing several exemplary embodiments, it is to be understood that the disclosure is not limited to the details of construction or process steps set forth in the following
20 description. The disclosure is capable of other embodiments and of being practiced or being carried out in various ways.

[0033] Reference throughout this specification to "one embodiment," "certain embodiments," "various embodiments," "one or more embodiments" or "an embodiment" means that a particular feature, structure, material, or characteristic described in connection with the
25 embodiment is included in at least one embodiment. Thus, the appearances of the phrases such as "in one or more embodiments," "in certain embodiments," "in various embodiments," "in one embodiment" or "in an embodiment" in various places throughout this specification are not necessarily referring to the same embodiment. Furthermore, the particular features, structures, materials, or characteristics may be combined in any suitable manner in one or more
30 embodiments.

[0034] Reference will now be made to figures wherein like structures will be provided with like reference designations. It is understood that the drawings are diagrammatic and schematic

representations of exemplary embodiments, and are neither limiting nor necessarily drawn to scale.

[0035] The present disclosure relates to medical devices, systems and methods for enhancing visualization of an invasive procedure requiring procedural guidance, such as providing enhanced visualization of a vascular access device during an invasive insertion procedure. In one or more embodiments, a catheter assembly is provided which includes a catheter adapter subassembly and a needle subassembly. The catheter adapter subassembly includes either a permanent magnet element or magnetizable feature and the needle subassembly includes a permanent magnet element or a magnetizable feature. Thus, in one embodiment, the catheter adapter subassembly includes a permanent magnet and the needle subassembly includes a magnetizable feature. In another embodiment, the catheter adapter subassembly includes a magnetizable feature and the needle subassembly includes a permanent magnet.

[0036] For clarity it is to be understood that the word 'proximal' refers to a direction relatively closer to a clinician using the device to be described herein, while the word "distal" refers to a direction relatively further from the clinician. For example, the end of a needle placed within the body of a patient is considered a distal end of the needle, while the needle end remaining outside the body is a proximal end of the needle. "Magnetic feature" refers to a feature that includes a permanent magnet and/or a magnetizable material that has been magnetized by an externally applied magnetic field such that the magnetic feature can be detected by an ultrasound system. A "magnetizable feature" refers to an element that can become magnetized and is detectable by an ultrasound system as described further herein.

[0037] Referring now to Figures 1-3, an exemplary embodiment of a catheter assembly 10 is shown, including a catheter adapter subassembly 12 and a needle subassembly 14. The catheter adapter subassembly 12 comprises a catheter adapter 16, catheter tubing 18 and a securement element 22, and the needle subassembly 14 further includes a needle 20, connected to a needle hub 24, at a hub distal end 23 and a vent plug 26. In other embodiments not shown, the needle 20 can be retracted into the needle hub 24 after the needle 20 has been used to prevent accidental needle sticks of a patient or a clinician.

[0038] Referring now to Figs. 4 and 5, an embodiment of a medical device 100 comprising a catheter assembly 110 is shown. The catheter assembly 110 includes a catheter adapter subassembly 112 and a needle subassembly 114. The catheter adapter subassembly 112 further includes a catheter adapter 116, catheter hub (not shown) and catheter tubing 118. The needle

subassembly 114 further includes a needle 120, connected to a needle hub (not shown), disposed within a needle hub 124 and a vent plug 126. In the embodiment shown in Figures 4 and 5, the catheter adapter subassembly 112 includes a permanent magnet element 132 and the needle subassembly 114 includes a magnetizable feature 130, in particular on the needle 120.

- 5 According to an alternative embodiment (not shown), this configuration is reversed wherein the permanent magnet element 132 is on the needle subassembly 114, in particular on the needle 120, and the magnetizable feature 130 is on the catheter adapter subassembly 112.

[0039] The use of a permanent magnet element on the catheter adapter subassembly 112 and a magnetizable feature on the needle subassembly 114 provides the ability to calculate the catheter tip position and the needle tip position based on known geometry relative to the position of permanent magnet element 132 on the catheter adapter subassembly 112 from which a calculated catheter tip position and a calculated needle tip position can be determined. The permanent magnet element 132 provides a static magnetic field, while the magnetizable feature 130 on the needle 120 can be magnetized with an externally applied magnetic field prior to insertion of the needle 120 into the patient.

[0040] In the embodiment shown in Figures 4 and 5, the magnetizable feature 130 is on the needle 120, and the catheter adapter subassembly 112 includes the permanent magnet element 132. The magnetizable feature 130 on the needle 120 can be provided in a variety of ways. In one embodiment, the needle 120 is made from a magnetizable material, for example, a steel material that has a magnetic permeability that permits the needle 120 to be magnetized by application of an external magnetic field. Stainless steel that is typically used to manufacture hypodermic needles for medical use, for example, type 304 stainless steel, may not have the magnetic permeability to be magnetized and used in a device according one or more embodiments. Type 304 stainless steel is an austenitic steel comprising at least 18% chromium, 8% nickel, and a maximum of 0.08% carbon. Type 316 stainless steel is also used in the manufacture of hypodermic needles, and type 316 stainless steel is also austenitic and non-magnetic. The nickel content of type 316 stainless steel is typically higher than type 304 stainless steel, and type 316 stainless steel also includes the addition of molybdenum.

According to one or more embodiments, the needle 120 is made from martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel.

[0041] In one or more embodiments, the magnetizable feature 130 on the needle comprises a separate feature on the needle 120. Referring now to Fig. 6A, in one embodiment, needle

adhesive 140 is placed on a proximal end 121 of the needle 120, which can be used to secure the needle 120 to the hub within the needle chamber 24. The needle adhesive 140 can be any suitable adhesive such as a curable glue containing magnetizable nanoparticles such as magnetizable metal nanoparticles or magnetizable metal oxide nanoparticles. The magnetizable metal can include iron, cobalt, nickel and alloys of iron, cobalt, and nickel. According to one or more embodiments, the size of the magnetic nanoparticles is in the range of about 1 nanometer (nm) to about 100 nm. In one embodiment, adhesive is a light-curable glue, and in another embodiment, the adhesive is a heat-curable glue.

[0042] Referring now to Fig. 6B, an embodiment is shown in which the magnetizable feature is a needle ferrule 142 adjacent the distal tip 123 of the needle 120. The needle ferrule 142 is made from a magnetizable metal such as martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel. The needle ferrule 142 provides at least a localized area of increased outer diameter. As used herein, the term "ferrule" refers to a separate member attached to the shank portion the needle 120, providing at least a localized area of increased outer diameter. The term "ferrule" includes a construction wherein the ferrule comprises an integral part of the needle, defining a one-piece monolithic construction composed of both the needle 120 and the needle ferrule 142, as well as a construction in which the needle ferrule 142 is a piece added to the needle by crimping the needle ferrule 142 onto the shank of the needle 120.

[0043] Referring now to Figure 6C, an embodiment is shown in which the magnetizable feature is a spot weld 144 adjacent the distal tip 123 of the needle 120. The spot weld 144 can be made from a magnetizable metal such as martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel.

[0044] Referring now to Figure 6D, an embodiment is shown in which the magnetizable feature is a needle safety element, for example, a metal clip, specifically, a metal cannula safety clip 146 adjacent the distal tip 123 of the needle 120. The metal clip 146 can be made from a magnetizable metal such as martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel. In other embodiments, the needle safety element can be embodied in other forms, for example, a spring, a plastic housing including a magnetizable feature, or other suitable safety elements. According to one or more embodiments, the safety element can be made from a materials that are not magnetic or magnetizable and include a magnetizable or magnetic material.

[0045] Referring now to Figure 6E, an embodiment is shown in which the magnetizable feature is a notch 148 in the needle 120, adjacent the distal tip 123 of the needle 120. The notch 148 can include an insert made from a magnetizable metal such as martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel. The insert fits inside the notch 148 to completely or partially fill the notch 148. According to one or more
5 embodiments, the insert can be a permanent magnet, magnetic adhesive or other magnetic material. The notch can be partially filled to occupy one-half the length of the notch 148.

[0046] Referring now to Figure 7, an embodiment of a medical device 200 comprising a catheter assembly 210 is shown. The catheter assembly 210 includes a catheter adapter subassembly 212 and a needle subassembly 214. The catheter adapter subassembly 212
10 includes a catheter adapter 216, catheter hub (not shown) and catheter tubing 218, and the needle subassembly 214 further includes a needle 220 connected to the needle hub 224, disposed within a needle hub 224 and a vent plug 226. In the embodiment shown in Figure 7, the catheter adapter subassembly 212 includes a permanent magnet element 232 and the needle
15 subassembly 214 includes a magnetizable feature 230, in particular on the needle 220. In the specific embodiment shown, the catheter adapter subassembly 212 includes the catheter tubing 218 and a catheter adapter 216, and a magnetic adhesive 240 attaches the catheter tubing 218 to the catheter adapter 216. The magnetic adhesive 240 can be any suitable adhesive such as a curable glue containing magnetizable nanoparticles such as magnetizable metal nanoparticles
20 or magnetizable metal oxide nanoparticles. The magnetizable metal can include iron, cobalt, nickel and alloys of iron, cobalt, and nickel. According to one or more embodiments, the size of the magnetic nanoparticles is in the range of about 1 nanometer (nm) to about 100 nm. In one embodiment, adhesive is a light-curable glue, and in another embodiment, the adhesive is a heat-curable glue.

[0047] Referring now to Figures 8 and 9, an embodiment of a medical device 300 comprising a catheter assembly 310 is shown. The catheter assembly 310 includes a catheter adapter subassembly 312 and a needle subassembly 314. The catheter adapter subassembly 312
25 includes a catheter adapter 316, catheter hub (not shown) and catheter tubing 318, and the needle subassembly 314 further includes a needle 320 connected to the needle hub 324, disposed within a needle chamber 324 and a vent plug 326. In the embodiment shown in
30 Figures 8 and 9, the catheter adapter subassembly 312 includes a magnetizable feature 330 and the needle subassembly 314 includes a permanent magnet element 332.

[0048] Figures 10A-10D show various configurations for providing the magnetizable feature 330 on the catheter adapter subassembly 312. In Figure 10A, a securement element in the form of a mandrel 342, which can be a conical mandrel for connecting the catheter tubing 318 to the catheter adapter 316, can be the magnetizable feature. According to one or more

5 embodiments, the mandrel 342 includes or is manufactured from martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel. It will be understood that in Figure 10A, the mandrel 342 is protruding from the catheter adapter 316. In other embodiments (not shown), the mandrel 342 can be recessed within the catheter adapter 316.

[0049] In Figure 10B, the securement element is shown in the form of a catheter tubing

10 adhesive 340 is shown on the catheter tubing 318, which can be used to provide the magnetizable feature. The catheter tubing adhesive 340 can be any suitable adhesive such as a curable glue containing magnetizable nanoparticles such as magnetizable metal nanoparticles or magnetizable metal oxide nanoparticles. The magnetizable metal can include iron, cobalt, nickel and alloys of iron, cobalt, and nickel. According to one or more embodiments, the size
15 of the magnetic nanoparticles is in the range of about 1 nanometer (nm) to about 100 nm. In one embodiment, adhesive is a light-curable glue, and in another embodiment, the adhesive is a heat-curable glue.

[0050] Figure 10C shows an embodiment in which a blood control component 346 shown exploded from the catheter adapter subassembly 312 to provide the magnetizable feature. In

20 the embodiment shown, the blood control component is a spring that includes a magnetic element or magnetizable material. According to one or more embodiments, the blood control component 346 includes martensitic or ferritic stainless steels, for example, type 420 or type 430 stainless steel. The blood control component (metal spring for instance) moves with the catheter adapter until fully advanced. It will be appreciated that in use the blood control
25 component 346 in the form of a spring would be located within the catheter adapter 316, and may not be visible, unless the catheter adapter was made from transparent material.

[0051] Figure 10D shows an embodiment in which a magnetic element 348 on the catheter adapter 316 provides the magnetizable feature. According to one or more embodiments, the magnetic element 348 includes or is made from martensitic or ferritic stainless steels, for
30 example, type 420 or type 430 stainless steel. A magnetic wedge can provide a controlled position on the catheter adapter subassembly 312 to provide a fixed measurement datum in a fixed location relative to the catheter distal tip and a wedge having a highly oriented grain

structure due to the cold forming used during its fabrication is also beneficial in providing a measurement datum. In one or more embodiments, the various alternatives discussed with respect to Figures 10A-10D may not have a position that is as precisely controlled. In one or more embodiments, the wedge, spring, and safety clip, would rely on catheter tip calculated
5 projection rather than positional measurement.

[0052] In specific embodiments that include a magnetic adhesive, the adhesive can include an additive selected from a paramagnetic additive, a ferromagnetic additive and combinations thereof. The additive, according to one or more embodiments, includes a component selected from powdered iron, magnetic iron oxide, magnetic titanium oxide, magnetic powdered steel,
10 and a magnetic iron alloy, and mixtures thereof. In specific embodiments, the magnetic iron alloy includes one or more of nickel, zinc, and copper. In specific embodiments, the additive further comprises a component selected from chromium, magnesium, molybdenum and combinations thereof.

[0053] In one or more embodiments, the needle subassembly includes the permanent magnet element, and the catheter adapter subassembly includes the magnetizable feature, wherein the
15 magnetizable feature includes magnetizable catheter tubing. In one or more embodiments, at least a portion of the polyurethane tubing comprises a magnetizable composition which is magnetizable by an externally applied magnetic field, the magnetizable composition comprising a magnetic material dispersed in the polyurethane. In certain embodiments, the
20 magnetic composition is dispersed in the polymeric material, for example, polyurethane, which forms the tubing. In a specific embodiment, the magnetizable composition comprises an inner layer surrounding the lumen of the catheter with an outer layer of non-magnetizable polymeric material, for example, polyurethane. In an alternative specific embodiment, the layer of magnetizable composition is an outer layer surrounding an inner layer of non-magnetizable
25 polyurethane. In one or more embodiments, the magnetizable composition forms longitudinal segments of the catheter separated by longitudinal segments of non-magnetizable polymeric material, for example, polyurethane.

[0054] In any of the foregoing embodiments of the catheter, the magnetizable composition may further comprise a radiopaque component. Alternatively, in any of the foregoing
30 embodiments, a non-magnetizable portion of catheter may comprise a radiopaque component

[0055] It will be understood that the permanent magnet element or a magnetized magnetizable feature for the embodiments described above, the orientation of the magnetic field can vary.

The permanent magnet element can have north and south poles on axis with the catheter tubing and with the needle. Alternatively, permanent magnet element or magnetized magnetizable feature can have north and south poles off axis with the catheter tubing and with the needle, for example, the north and south poles can be oriented perpendicular to the longitudinal axis of the catheter tubing and the needle. For example, in Figure 5, the magnetizable feature 130 is shown as being magnetized with the north pole 130N and south pole 130S of the magnetizable feature 130 oriented parallel of the longitudinal axis of the needle 120. The permanent magnet element 132 associated with the catheter adapter subassembly 112 is shown with the north pole 132N and south pole 132S oriented perpendicular to the longitudinal axis of the catheter tubing 118. In the configuration shown in Figure 9, the permanent magnet element 332 and the magnetizable feature 330, which has been magnetized, are shown with the poles 330N, 330S, 332N and 332S oriented parallel to the longitudinal axis of the needle 320 and the catheter tubing 318. Other variants are possible such as the permanent magnet element and the magnetizable feature which has been magnetized having their north and south poles both oriented perpendicular or orthogonal to the longitudinal axis of the needle and the catheter tubing.

[0056] An example of a vascular access device including a catheter according to any of the foregoing embodiments described above is illustrated in Fig. 11. The vascular access device 500 shown in Figure 11 comprises a catheter adapter subassembly 512 including a catheter adapter body 516 and a catheter tubing 518 and a permanent magnet element 532. A needle (not shown) within the catheter tubing includes magnetizable feature 530, which has been magnetized by application of an external magnetic field and can be any of the magnetizable features described herein. Magnetizing the magnetizable feature 530 with an externally applied magnetic field creates a magnetic field 515 in the region of magnetizable feature 530.

[0057] The vascular access device 500 may include a lateral access port 556 and may be connected to a section of an extension tube 560 for establishing fluid communication between an IV fluid source and the catheter tubing 518. In one or more embodiments, the extension tube 560 is built-in to reduce contamination and mechanical phlebitis by eliminating manipulation at the insertion site. In one or more embodiments, the extension tube 560 is compatible with high pressure injection. In one or more embodiments, the extension tube 560 provides continuous confirmation of vessel access during advancement of the catheter into the patient vein.

[0058] In one or more embodiments, a needle 511 of a needle subassembly 514 is inserted into the lumen (not show) of the catheter tubing 518. The needle subassembly 514 is shown as including finger grips 584 positioned at the sides of the needle subassembly 514 to facilitate various insertion techniques. In one or more embodiments, bumps may be present on the
5 finger grip to indicate where to the user may grip the device for needle removal. In one or more embodiments, a thumb pad 585, having a gently convex surface, is provided at the proximal end of the needle subassembly 514. A flange 586, having a gently convex surface, is provided at the proximal end of the needle subassembly 514 to provide a finger pad. A wing member 570, thumb pad 585 and flange 586 may be utilized by the user during insertion,
10 permitting the user to elect which insertion technique to employ.

[0059] In one or more embodiments, the needle subassembly 514 includes a needle shield 580. The needle shield 580 may be a design adapted to secure the tip of the needle within the shield after use. In one or more embodiments, the needle shield 580 may be activated passively. The needle tip is completely covered by the needle shield 580 in a fixed position. In one or
15 more embodiments, a ferrule, crimp or other structure may be included near the tip for engagement with a needle shield in certain applications.

[0060] A push tab 581 may be provided to facilitate catheter advancement during insertion. The push tab 581 also allows for one-handed or two-handed advancement. In one or more embodiments, the push tab 581 is removed with the needle shield 580. A clamp 582 may also
20 be included on the extension tubing to prevent blood flow when replacing the access port.

[0061] In one or more embodiments, the vascular access device 500 further includes a first luer access 572 and a second luer access 573 in fluid communication with the extension tube 560, a blood control split septum 574 associated with the first luer access 572, and an air vent 576 associated with the second luer access 573. Split septum 574 allows for a reduction in
25 catheter-related bloodstream infection (CRBSI) while providing unrestricted flow and a straight fluid path and functions as a blood control septum. In one or more embodiments, the split septum 574 may be located in an internal cavity of the catheter adapter or on the distal end of the catheter adapter. In yet another embodiment, the split septum 574 may be located on a distal end of the extension tube 560. The air vent 576 allows air to escape from the system
30 during insertion, providing continuous confirmation of vascular access while preventing leakage of blood from the system during insertion. In one or more embodiments, the air vent 576 may be at the distal end of extension tube 560.

[0062] Another aspect of the disclosure pertains to a system for determining catheter tip location when the catheter tubing is inserted in a patient. According to one or more embodiments, a system provides a way to independently measure the cannula tubing tip location by measuring the location and vector of the permanent magnet, and calculating and predicting the catheter tip location relative to the position of the magnetic sensor(s) on an ultrasound probe and the ultrasound information transmitted from the sensors on the ultrasound probe. A permanent magnet on a device with north and south poles on axis with the catheter and needle and a known geometrical relationship to one or more features fixed on the catheter assembly provides a measurement datum that is measureable by the ultrasound probe magnetic sensors. From the measurement datum based on the one or more features on the catheter assembly, the direction vector and position of the catheter tip, needle tip or other features can be calculated. A magnetized magnetizable needle or feature on the needle can then be used to independently measure the position feature and calculate the position of the needle tip. The calculated position of the needle tip or feature on the needle can then be compared relative to the calculated position of the catheter tip to provide more specific information related to the catheter placement process, such as needle and catheter tip position relative to the patient's anatomy. This information can be used to determine (a) if the catheter is properly seated and ready for insertion (i.e., no over the bevel condition), (b) when the needle tip is in the "hooded" position (needle tip just inside of the catheter tip), and (c) and (d) when the catheter is advanced to specific distances and at angles suggesting successful placement in the vein.

[0063] Referring now to Figures 12A-D, an embodiment of a medical device 600 comprising a catheter assembly 610 is shown. The catheter assembly 610 includes a catheter adapter subassembly 612 and a needle subassembly 614. The catheter subassembly 612 includes a catheter adapter 616, catheter hub (not shown) and catheter tubing 618 having a distal catheter tip, and the needle subassembly 614 further includes a needle 620 having a needle distal tip 623 connected to a needle hub 624, and a vent plug 626. In the embodiment shown in Figures 12A-D, the catheter adapter subassembly 612 includes a permanent magnet element 632 and the needle subassembly 614 includes a magnetizable feature 630. Fig. 12B shows the catheter assembly 610 in 12A in when the needle distal tip 623 is in the "hooded" position where the needle distal tip 623 is just inside of the catheter distal tip 619. Since the dimensions of the components of the needle subassembly 614 are fixed and known, placement of the permanent magnet element 632 provides a known geometrical relationship, for example, distance and

angular position, with respect to one or more features fixed on the catheter assembly, which provides a measurement datum 633.

[0064] Referring now to Figure 12C, the catheter adapter subassembly 612 has been advanced in distal direction (toward the patient and away from the clinician), and the measurement datum 633 can be used to determine the distance and angular movement of the needle 620 with respect to the measurement datum 633. Similarly, if the catheter tubing 618 or other part of the catheter adapter subassembly 612 includes a magnetizable feature, and the needle subassembly 614 includes a permanent magnet, the distance and the angular movement of the catheter tubing 618 can be determined with respect to the measurement datum. Figure 12C shows that the needle 620 has moved a distance D1, and the magnetizable feature 630 has moved a distance D1 from the catheter distal tip 619. In Figure 12D, the needle subassembly 614 has moved in a proximal direction (towards the clinician) for a distance D2, and the magnetizable feature 630 is now at a distance D2 from the catheter distal tip 619. Each sequential movement of either a permanent magnet element or magnetized magnetizable feature on a needle and/or the cannula can be measured and tracked using an ultrasound system.

[0065] The location of the magnetized magnetic feature or permanent magnet on a needle or cannula tubing can be accomplished by using a magnetometer to determine the strength of the magnetic field and its direction. As used herein, "magnetometer" refers to a device that detects a magnetic field. In specific embodiments, magnetometers may measure the strength of a magnetic field. When invasive needle or catheter is magnetic and produces a known magnetic field B at a given distance x through tissue of permeability μ_r , a mathematical correlation between the two i.e. $x = f(B, \mu_r)$ can be derived. In an embodiment, three different magnetometers are arranged in a three-dimensional grid array, orthogonal to each other, are used, and a three-dimensional (3D) correlation can be derived where $I = f(B_i \mu_r)$, where i = x or y or z along three axes. Such correlation can be extended to an array of 3-dimensional (3-D) magnetometers to obtain the precise distance to the magnetized catheter or vascular access device from the array of 3D magnetometers. If the location of the array of 3D magnetometers is known in reference to the ultrasound sensor, then the precise location of the magnetized device with respect to the ultrasound sensor can be calculated. An inferred image of the device can then be created and superimposed over the ultrasound image and displayed. An exemplary magnetic sensing method using magnetometers and a lookup table instead of a mathematical function to determine the location of a magnetized invasive device from the magnetic field

strength measured outside the body using magnetometers is shown and described in United States Patent Application Publication Number US20140257080 A1. The method described in US20140257080 A1 can be adapted as described herein, for example, a three-dimensional (3D) correlation is from a mathematical function, and the correlation is extended to an array of 3-dimensional (3-D) magnetometers, one of the magnetometers outside the patient's body, to obtain the precise distance to the magnetized catheter or vascular access device from the array of 3D magnetometers. Another exemplary method of referencing the magnetometers with respect to an ultrasound probe is described in PCT Patent Application Publication Number WO2013034175 A1, which can be adapted as described herein. For example, as shown in Fig. 13, an ultrasound system 700 is shown including a catheter adapter subassembly 712 comprising a magnetizable feature 732 that has been magnetized as described herein is shown inside of a patient's body 800. It will be appreciated that the sizes shown are not to proportion and the sizes of the catheter adapter subassembly 712 and the magnetizable feature 732 are exaggerated in size to illustrate these elements more clearly. A magnetometric detector 711 comprising an array of magnetometers 720 (which can be housed in a probe of a ultrasound system, not shown) arranged in a 3-D array can be used to sense the magnetic field 714 together with the terrestrial magnetic field and any other background magnetic field. The magnetometric detector 711 is in communication with an ultrasound processor 730 adapted to determine from the detected field the position and orientation of the magnetizable feature 732 relative to the magnetometric detector 711. This magnetically detected position is then displayed on a display 750 together with the ultrasound image.

[0066] The ultrasound system 700 can be a standard two dimensional B-mode ultrasound system with a standard ultrasound probe modified by the provision of the magnetometric detector 711. The ultrasound processor 730, which can be connected to the ultrasound probe via a cable 735, sends electrical signals to the magnetometric detector 711 to cause it to generate ultrasound pulses and interpreting the raw data received from the transducer probe housing the magnetometric detector 711, which represents echoes from the patient's body, to assemble it into an image of the patient's tissue.

[0067] The magnetometric detector 711 can be attached to the ultrasound probe and can be battery powered or powered from the ultrasound system. In specific embodiments, positioning elements are provided on the magnetometric detector 711 to ensure that it is always attached in the same well-defined position and orientation. The magnetometric detector 711

can be connected by a wireless connection to a base unit 740 which is in wireless or wired (e.g. USB) communication with the ultrasound processor 730 and the display 750. The base unit 740 can be integrated with, or some of its functions performed by, the ultrasound processor 730 or the magnetometric detector 711.

5 [0068] The base unit 740 receives normalized measurements from magnetometric detector 711 and calculates the position, or optionally the position and orientation, of magnetizable feature 732. The base unit 740 can also receive additional information such as the state of charge of the magnetometric detector's battery and information can be sent from the base unit 740 to the magnetometric detector 711, such as configuration information. The base unit 740 forwards the results of its calculations, i.e. the position and, optionally, orientation, to the ultrasound processor 730 for inclusion in the displayed ultrasound image of an image of the catheter.

10 [0069] In one or more embodiments, the base unit 740 can be integrated into the ultrasound system 700 with the ultrasound processor 730 and the magnetometric detector 711 being in direct communication with the ultrasound system 700 either via wireless link or using the same physical cable 735.

15 [0070] Thus, in one or more embodiments, the magnetizable feature is magnetized using any suitable device that can produce an magnetic field to magnetize a needle or medical device to produce a magnetic field B at a distance x through tissue of permeability μ_r , and the correlation is calculated as $x = f(B, \mu_r)$. In one or more embodiments, three magnetometers 720 are placed orthogonally to each other are used to derive a 3-dimensional correlation $I = f(B_i, \mu_r)$, wherein $i = x$ or y or z along three axes. In a specific embodiment, the distance from the magnetizable feature to the 3-dimensional array of magnetometers is calculated. In a further specific embodiment, location of the array of magnetometers in reference to an ultrasound sensor of an ultrasound imaging system is used to calculate a location of the magnetizable feature with respect to the ultrasound sensor. In another specific embodiment, the method comprises displaying an image of the magnetizable feature.

25 [0071] As described above with respect to Figures 12A-D, providing a permanent magnet on the needle subassembly and a magnetizable feature on the catheter subassembly (or a reverse configuration in which the magnetizable feature is on the needle subassembly (e.g., the needle or needle hub) and the permanent magnet is on the catheter subassembly) relative positions of a catheter tip and a needle cannula tip can be determined by utilizing an ultrasound system including a three dimensional array of magnetometers. Relative positional changes of the

30

catheter adapter subassembly and needle subassembly can be determined in three axes, x, y and z, as well relative changes in angular motion ω of the catheter adapter subassembly and the needle subassembly based on based on a known geometrical relationship to one or more features fixed on the catheter adapter assembly or needle subassembly, which provides a measurement datum that is measureable by the ultrasound probe magnetic sensors. From the measurement datum based on the one or more features, the direction vector and position of the catheter tip or other features can be calculated based on a 3-dimensional correlation $I = f(B_i, \mu_r)$, wherein $i = x$ or y or z along three axes or predict relative motion between the needle hub and catheter adapter subassemblies. Understanding the relative position and motion of these two subassemblies can be used to inform a clinician of procedurally important states of the insertion process, such as when the needle tip reaches the vein, when the catheter tip reaches the vein, when the catheter is advanced to cover the needle tip ("hooding the catheter") and thereby safe for further advancement.

[0072] Another aspect of the disclosure comprises methods that can be practiced according to any of the previously described systems. A method for determining a relative position of a catheter tip and a needle cannula tip, the method includes providing a catheter having a catheter distal tip and a needle having a needle distal tip, associating a permanent magnet element with one of the catheter and the needle, associating a magnetizable feature with the other of the catheter and the needle, obtaining a measured position of the permanent magnet, obtaining a measured position of the magnetizable feature to obtain a calculated position of the catheter distal tip, and comparing the calculated position of the catheter distal tip with the calculated position of the needle distal tip to determine the relative position of the catheter distal tip and the needle distal tip. In one embodiment, the needle includes the magnetizable feature and the catheter includes the permanent magnet and the relative position of the catheter distal tip and the needle distal tip indicates that the catheter is properly seated on the needle. In another embodiment, the relative position of the catheter distal tip and the needle distal tip indicates that the catheter is in a hooded position on the needle. In another embodiment, the relative position of the catheter distal tip and the needle distal tip indicates that the catheter distal tip is advanced a specific distance or angle.

[0073] In one embodiment of the method, the catheter adapter subassembly includes the magnetizable feature and the needle subassembly includes the permanent magnet, and relative movement of the catheter adapter subassembly and needle subassembly is determined by a

three-dimensional array of magnetometers positioned in proximity to at least one of the permanent magnet the magnetizable feature. In one embodiment of the method, the method includes magnetizing the magnetizable feature by applying an external magnetic field to the magnetizable feature. In one embodiment, the three-dimensional array of magnetometers is
5 part of an ultrasound system, and the ultrasound system derives a three-dimensional correlation to obtain a distance from the grid array to the magnetizable feature or permanent magnet. In another embodiment, the three-dimensional correlation is determined by the function $I = f(B_i \mu_r)$, where $i = x$ or y or z along three axes, x , y and z are distances in three planes, B is a known magnetic field produced by the permanent magnet or magnetizable feature, and μ_r is magnetic
10 permeability.

[0074] In another embodiment of the method, the catheter adapter subassembly includes the permanent magnet and the needle subassembly includes the magnetizable feature, and relative movement of the catheter adapter subassembly and needle subassembly is determined by a three-dimensional array of magnetometers positioned in proximity to at least one of the
15 permanent magnet the magnetizable feature. In one embodiment, the method includes magnetizing the magnetizable feature by applying an external magnetic field to the magnetizable feature. According to another embodiment, the three-dimensional array of magnetometers is part of an ultrasound system, and the ultrasound system derives a three-dimensional correlation to obtain a distance from the grid array to the magnetizable feature or
20 permanent magnet. In one embodiment, the three-dimensional correlation is determined by the function $I = f(B_i \mu_r)$, where $i = x$ or y or z along three axes, x , y and z are distances in three planes, B is a known magnetic field produced by the permanent magnet or magnetizable feature, and μ_r is magnetic permeability.

[0075] Another aspect of the disclosure pertains to a catheter adapter subassembly comprising
25 a magnetic feature selected from the group consisting of a metal mandrel for connecting catheter tubing to the hub, a catheter tubing adhesive, a blood control component of the catheter adapter subassembly, and a magnetic wedge on the catheter adapter body. The catheter adapter subassembly may further comprise magnetic catheter tubing. According to an embodiment, the metal mandrel comprises austenitic stainless steel.

30 [0076] Although the disclosure herein provided a description with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the disclosure. It will be apparent to those skilled in the art that

various modifications and variations can be made to the devices, methods and systems described in the of the present disclosure without departing from the spirit and scope thereof. Thus, it is intended that the present disclosure include modifications and variations that are within the scope of the appended claims and their equivalents.

CLAIMS

1. A medical device comprising:

a catheter assembly, the catheter assembly including a catheter adapter subassembly and a needle subassembly,

wherein one of the catheter adapter subassembly and the needle subassembly includes a permanent magnet element, and the other of the catheter subassembly and the needle subassembly includes a magnetized magnetizable feature, and wherein the permanent magnet element produces a known magnetic field and the magnetized magnetizable feature produces a known magnetic field and measurement of relative motion of the catheter adapter subassembly and the needle subassembly is measurable by a magnetometer which measures strength and direction of the magnetic field produced by the permanent magnet element and the magnetized magnetizable feature.

2. The medical device according to claim 1, wherein the needle subassembly includes the magnetized magnetizable feature and the catheter adapter subassembly includes the permanent magnet element, and the magnetized magnetizable feature of the needle subassembly is selected from the group consisting of a needle adhesive, the needle, a needle safety element, a notch, a needle ferrule, and a spot weld.

3. The medical device according to claim 1, wherein at least one of the permanent magnet element and magnetized magnetizable feature includes an adhesive.

4. The medical device according to claim 3, wherein the catheter adapter subassembly includes catheter tubing and a catheter adapter body, and the adhesive attaches the catheter tubing to the catheter adapter body.

5. The medical device according to claim 3, wherein the needle subassembly includes a cannula and a hub, and the adhesive attaches the cannula to the hub.

6. The medical device according to claim 1, wherein the needle subassembly includes the magnetized magnetizable feature, a cannula and a hub, and the catheter adapter subassembly includes a catheter adapter body, catheter tubing and the permanent magnet element, wherein the permanent magnet element is selected from the group consisting of a metal mandrel for

connecting catheter tubing to the hub, a catheter tubing adhesive, a blood control component of the catheter adapter subassembly, and a magnetic wedge on the catheter adapter body.

7. The medical device according to claim 6, wherein the permanent magnet element on the catheter adapter body is integrally molded with the catheter adapter body.

8. The medical device according to claim 1, wherein the catheter adapter subassembly includes the permanent magnet element and the needle subassembly includes the magnetized magnetizable feature and the magnetized magnetizable feature is a magnetized magnetisable needle.

9. The medical device according to claim 3, wherein the adhesive includes an additive selected from a paramagnetic additive, a ferromagnetic additive and combinations thereof.

10. The medical device according to claim 1, wherein the needle subassembly includes the permanent magnet element, and the catheter adapter subassembly includes the magnetized magnetizable feature, wherein the magnetized magnetizable feature includes magnetized magnetizable catheter tubing.

11. The medical device according to claim 1, wherein needle subassembly includes a cannula, the catheter adapter subassembly includes a catheter adapter body, catheter tubing and the permanent magnet element, and the permanent magnet element has north and south poles on axis with the catheter tubing and with the cannula.

12. The medical device according to claim 1, wherein the needle subassembly includes a cannula and the permanent magnet element, the catheter adapter subassembly includes a catheter adapter body and catheter tubing, and wherein the permanent magnet element has north and south poles on axis with the catheter tubing and with the cannula.

13. A system for determining relative position of a catheter adapter subassembly and a needle subassembly comprising: the device of any one of claims 1 to 12; and

a three dimensional grid array of magnetometers positioned with respect to the catheter adapter subassembly and the needle subassembly, the three dimensional grid array of

magnetometers as part of an ultrasound system configured to determine relative movement of the catheter adapter subassembly and needle subassembly.

14. The system of claim 13, wherein the permanent magnet element or the magnetized magnetizable feature on a fixed location on the catheter adapter subassembly or needle subassembly provides a measurement datum to determine movement of the magnetized magnetizable feature and permanent magnet element.

15. A method for determining a relative position of a catheter tip and a needle cannula tip, the method comprising:

- providing the system of claim 13 or 14;
- obtaining a measured position of the permanent magnet element;
- obtaining a measured position of the magnetized magnetizable feature to obtain a calculated position of the catheter distal tip and a calculated position of the needle distal tip; and
- comparing the calculated position of the catheter distal tip with the calculated position of the needle distal tip to determine the relative position of the catheter distal tip and the needle distal tip.

16. The method of claim 15, wherein the needle includes the magnetized magnetisable feature and the catheter includes the permanent magnet element and the relative position of the catheter distal tip and the needle distal tip indicates that the catheter is properly seated on the needle.

17. The method of claim 15, wherein the catheter adapter subassembly includes the magnetized magnetizable feature and the needle subassembly includes the permanent magnet element, and relative movement of the catheter adapter subassembly and needle subassembly indicates that the catheter distal tip is advanced a specific distance or angle.