

VEHICLE CONTROL SYSTEM, TRAVEL MANAGEMENT DEVICE, RESOURCE
MANAGEMENT DEVICE, VEHICLE CONTROL METHOD, AND PROGRAM

Technical Field

5 [0001]

The present disclosure relates to a vehicle control system, a travel management device, a resource management device, a vehicle control method, and a program.

Priority is claimed on Japanese Patent Application No. 2015-230113, filed November 25, 2015, the content of which is incorporated herein by reference.

10

Background Art

[0002]

In a railway system that performs high-density operations, an automatic train protection (ATP) device for maintaining a safe speed of trains may be adopted. In a
15 railway system adopting ATP, an interlocking device, the same as in the conventional art, is responsible for control of switching of points present at a track branch. The interlocking device performs exclusive control among vehicles in units on a course (block sections). The interlocking device controls the conversion of points while ensuring safety. An interlocking device and an ATP device are installed on a ground
20 side in the railway system, but these devices are expensive and require provision of a large equipment room. The maintenance management of an interlocking device incurs costs because a signal engineer with special skills needs to create designed materials called an “interlocking chart.”

[0003]

25 A technology for simplifying ground facilities by an on-board device performing

branch control mainly wirelessly as a unit for solving such problems is disclosed in Patent Literature 1.

Citation List

5 Patent Literature

[0004]

[Patent Literature 1]

Japanese Patent No. 5049992

10

SUMMARY

[0005]

However, a technology of Patent Literature 1 described above is a technology which can be used only in “a linear (track) constituted by repetition of an identical linear pattern”, and cannot be applied to a general urban railway having complicated linear
15 alignments.

[0006]

An object of the present invention herein is to provide a vehicle control system, a travel management device, a resource management device, a vehicle control method, and a program which can solve the above problems.

20

[0007]

According to a first aspect of the present invention, a vehicle control system includes: a travel management device which includes a reservation request unit, the reservation request unit being configured to transmit a reservation request for a block section to be reserved based on track information indicating a plurality of block sections
25 constituting a track on which a vehicle travels and a connection relationship between the

block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels; and a resource management device which includes a reservation management unit, the reservation management unit being configured to record the block section to be reserved indicated by the reservation request
5 as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle which has transmitted the reservation request at a time at which the reservation request is received.

[0008]

10 In addition, in the vehicle control system described above, the reservation management unit of the resource management device may be configured to transmit reservation completion information indicating the reserved block section of the vehicle which has transmitted the reservation request to the vehicle which is a transmission source of the reservation request, and the travel management device may include a speed
15 calculation unit configured to calculate a speed limit pattern in each block section up to the block section indicated by the reservation completion information.

[0009]

Moreover, in the vehicle control system described above, the vehicle may be mounted with the travel management device, the resource management device may be
20 installed in each predetermined range in the track, and a reservation request unit of the travel management device may be configured to transmit, to the resource management device corresponding to a range including the block section to be reserved, the reservation request for the block section to be reserved.

[0010]

25 Moreover, in the vehicle control system described above, the travel management

device may include a passage information notification unit configured to transmit a
passed block section of the vehicle to the resource management device, and the
reservation management unit of the resource management device may be configured to
update information of the passed block section from a reserved block section to an
5 unreserved block section in response to receiving the passed block section.

[0011]

Moreover, in the vehicle control system described above, the travel management
device may include a reservation abandonment unit configured to perform stop control of
the vehicle in a case of acquiring a cancellation request for the reserved block section
10 from a host device, the reservation abandonment unit being configured to transmit a
reservation abandonment of an advance block section in a travel direction in the reserved
block section to the resource management device after the vehicle stops.

[0012]

Moreover, in the vehicle control system described above, the travel management
15 device may be mounted on a vehicle.

[0013]

Moreover, in the vehicle control system described above, the resource
management device may be configured to store each block section included in a
non-branch consecutive section in which a plurality of block sections without branches
20 are continued, may be configured not to store information on whether each block section
included in the non-branch consecutive section is reserved or unreserved, and may be
configured to store a travel order of a vehicle traveling along the non-branch consecutive
section, and the travel management device may be configured to acquire, after the vehicle
mounted with the travel management device enters the non-branch consecutive section,
25 identification information of an immediately preceding vehicle traveling immediately

ahead of the vehicle from the resource management device, may be configured to detect a position of the immediately preceding vehicle by communicating with the immediately preceding vehicle, and may be configured to request braking control based on the position of the immediately preceding vehicle and a position of the vehicle mounted with the travel management device.

[0014]

Moreover, in the vehicle control system described above, the travel management device may be configured to acquire reservation status information from the resource management device in advance in order to determine a block section to be reserved.

10 [0015]

Moreover, in the vehicle control system, the resource management device may include a branch control unit configured to perform, in a case where a block section having a branch exists in the reserved block section of the vehicle, switching control for the branch based on a travel direction on the vehicle.

15 [0016]

Moreover, in the vehicle control system described above, the travel management device may include a branch control unit configured to perform, in a case where a block section having a branch exists in the reserved block section of the vehicle, switching control for the branch based on a travel direction on the vehicle.

20 [0017]

Moreover, in the vehicle control system described above, the travel management device may be configured to determine a travel start timing of a vehicle mounted with the travel management device based on a reservation time of a block section reserved by a vehicle other than the vehicle mounted with the travel management device.

25 [0018]

In addition, according to a second aspect of the present invention, a travel control method is a travel control method for a vehicle control system including a travel management device and a resource management device, the travel management device transmits a reservation request for a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels, and the resource management device records the block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle which has transmitted the reservation request at a time at which the reservation request is received.

[0019]

In addition, according to a third aspect of the present invention, a travel management device includes: a reservation request unit configured to transmit a reservation request for a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels.

[0020]

Moreover, according to a fourth aspect of the present invention, a resource management device is communicatively connected to a travel management device which includes a reservation request unit, the reservation request unit being configured to transmit a reservation request for a block section to be reserved based on track

information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels, and includes: a reservation management unit configured to record the
5 block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle which has transmitted the reservation request at a time at which the reservation request is received.

10 [0021]

Moreover, according to a fifth aspect of the present invention, in a travel control method for a vehicle control system including a travel management device and a resource management device, the travel management device transmits a reservation request for a block section to be reserved based on track information indicating a plurality of block
15 sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels, and the resource management device records the block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in
20 case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle which has transmitted the reservation request at a time at which the reservation request is received.

[0022]

Moreover, according to a sixth aspect of the present invention, a program is for a
25 computer of a travel management device in a vehicle control system including the travel

management device and a resource management device, and causes the computer to execute: a reservation request procedure of determining a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels, and transmitting a reservation request for the block section to be reserved.

[0023]

Furthermore, according to a seventh aspect of the present invention, a program is for a computer of a resource management device in a vehicle control system that includes a travel management device and the resource management device, the travel management device including a reservation request unit, the reservation request unit transmitting a reservation request for a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels, and causes the computer to execute: a resource management procedure of recording the block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle which has transmitted the reservation request at a time at which the reservation request is received.

[0024]

According to the present disclosure, it is possible to control travel of a vehicle traveling on a track without using an interlocking device or an ATP device.

BRIEF DESCRIPTION OF DRAWINGS

[0025]

Fig. 1 is a diagram which shows a configuration of a vehicle control system
5 according to a first embodiment of the present invention.

Fig. 2 is a functional block diagram of a travel management device and a
resource management device according to the first embodiment of the present invention.

Fig. 3 shows respective block sections constituting a track on which a vehicle 1
travels.

10 Fig. 4 is a diagram which shows a connection relationship between respective
block sections constituting a track on which a vehicle 1 travels.

Fig. 5 is a diagram which shows track information stored by the travel
management device.

Fig. 6 is a diagram which shows a travel route of a vehicle.

15 Fig. 7 is a diagram which shows a reservation management table stored by the
resource management device.

Fig. 8 is a diagram which shows a processing flow of the vehicle control system.

Fig. 9 is a diagram which shows a speed limit pattern and a reservation status.

Fig. 10 is a diagram which shows an installation state of a resource management
20 device according to a second embodiment.

Fig. 11 is a diagram which shows resource management device information
stored by a travel management device according to the second embodiment.

Fig. 12 is a diagram which shows a processing outline according to a third
embodiment.

25 Fig. 13 is a diagram which shows a vehicle control system according to a

seventh embodiment.

Fig. 14 is a diagram which shows a vehicle control system according to an eighth embodiment.

5 EMBODIMENTS FOR CARRYING OUT THE INVENTION

[0026]

<First embodiment>

Hereinafter, a vehicle control system according to a first embodiment of the present invention will be described with reference to the drawings.

10 Fig. 1 is a diagram which shows a configuration of the vehicle control system according to the first embodiment of the present invention.

Fig. 1 shows a vehicle control system 10. The vehicle control system 10 includes an operation management device 2, an on-board signaling device 3 mounted on a vehicle 1, and a resource management device 4 as shown in Fig. 1. The operation
15 management device 2 and the on-board signaling device 3 are connected by radio signals. The operation management device 2 outputs information for operation to the on-board signaling device 3. The on-board signaling device 3 includes a travel management device 30. The on-board signaling device 3 and the resource management device 4 are connected by radio signals. A vehicle travels on a track L. The track is constituted by
20 a plurality of block sections. The travel management device 30 of the on-board signaling device 3 transmits or receives information to or from the resource management device 4 to perform reservation management for each block section which is a resource.

[0027]

Describing in more detail, the travel management device 30 specifies a plurality
25 of block sections included in a track on which the vehicle 1 travels on the basis of track

information indicating a plurality of block sections constituting the track on which the vehicle 1 travels and a connection relationship between these block sections. The travel management device 30 determines a block section to be reserved which is positioned ahead of a block section on which a vehicle is currently present among the plurality of specified block sections. The travel management device 30 transmits a reservation request for this block section to be reserved to the resource management device 4.

The resource management device 4 determines whether the block section to be reserved which is indicated by the reservation request is reserved by vehicles other than a vehicle 1 which has transmitted the reservation request at a time at which this reservation request is received. The resource management device 4 records the block section to be reserved which is indicated by the reservation request as a reserved block section of the vehicle 1 which has transmitted the reservation request when the block section to be reserved is not reserved by vehicles other than the vehicle 1.

[0028]

Fig. 2 is a functional block diagram of the on-board signaling device, the travel management device, and the resource management device according to the first embodiment of the present invention.

The on-board signaling device 3 includes a device allowing the functions of respective processing units including a speed calculation unit 310 and a travel control unit 320, in addition to the travel management device 30 to be exhibited therein.

The travel management device 30 includes respective processing units of a travel route specification unit 31, a reservation request unit 32, a passage information notification unit 33, a reservation abandonment unit 34, a control unit 35, and a communication unit 36, and a storage unit 37.

[0029]

The resource management device 4 has respective processing units of a reservation management unit 41, a branch control unit 44, a control unit 45, and a communication unit 46, and a storage unit 47.

[0030]

- 5 The travel route specification unit 31 of the travel management device 30 specifies a plurality of block sections included in a track on which a vehicle 1 travels on the basis of track information indicating a plurality of block sections and a connection relationship between these block sections.

- The reservation request unit 32 determines a block section to be reserved
10 positioned before a block section on which the vehicle 1 is currently present among the plurality of block sections specified by the travel route specification unit 31. The reservation request unit 32 transmits a reservation request for this block section to be reserved to the resource management device 4.

[0031]

- 15 The reservation management unit 41 of the resource management device 4 determines whether a block section to be reserved which is indicated by the reservation request is reserved by vehicles other than the vehicle 1 which has transmitted the reservation request at a time when the reservation request is received. When the reservation management unit 41 determines that it is not reserved by vehicles other than
20 the vehicle 1, the block section to be reserved indicated by the reservation request is recorded as a reserved block section of the vehicle 1 which has transmitted the reservation request.

[0032]

- The speed calculation unit 310 of the on-board signaling device 3 calculates a
25 speed limit pattern in each block section up to a block section indicated by reservation

completion information.

The travel control unit 320 of the on-board signaling device 3 performs stop control such as braking on the basis of speed limit patterns and a signal from a host device.

5 [0033]

The passage information notification unit 33 of the travel management device 30 transmits a block section which a vehicle 1 has passed through to the resource management device 4.

10 The reservation abandonment unit 34 of the travel management device 30 performs stop control on a vehicle 1 when a cancellation request for a reserved block section is acquired by a host device. The reservation abandonment unit 34 transmits reservation abandonment of an advance block section in a travel direction among reserved block sections to the resource management device 4 in the reserved block section after the vehicle 1 stops.

15 [0034]

The branch control unit 44 of the resource management device 4 performs switching control for a branch (points) based on a travel direction on a vehicle when there is a block section having a branch in reserved block sections of the vehicle.

20 The control unit 45 in the resource management device 4 controls respective processing units in the device. The communication unit 46 of the resource management device 4 communicates with the on-board signaling device 3. The storage unit 47 stores information for resource management.

[0035]

25 Fig. 3 is a diagram which shows respective block sections constituting a track on which a vehicle travels.

A track on which the vehicle 1 travels is assumed to be a track constituted by respective block sections represented by identification information of A1HT, A2HT, A1WT, A2WT, A3WT, A4WT, 1T, 2T, 3T, 4T, 5T, 6T, 7T, 8T, 9T, 10T, B1WT, B2WT, B3WT, B4WT, B1HT, and B2HT. The eight block sections including A1WT, A2WT, A3WT, A4WT, B1WT, B2WT, B3WT, and B4WT have a branch. When a vehicle needs to travel along a block section having a branch in a state in which a point of the block section is set to a position on a normal position side, the identification information of this block section is indicated by adding “-N” thereto.

When a vehicle needs to travel along a block section having a branch in a state in which a point of the block section is set to a position on a reverse position side, the identification information of this block section is indicated by giving “-R” thereto. For example, when a point of the block section A1WT is controlled such that it is positioned on the normal position side and used by a vehicle 1, the identification information of this block section is represented as A1WT-N. When a point of the block section A1WT is controlled to be positioned on a reverse position side and used by a vehicle 1, the identification information of this block section is represented as A1WT-R.

[0036]

Fig. 4 is a diagram which shows connection relationships between respective block sections constituting a track on which the vehicle 1 travels.

If some of the connection relations shown in Fig. 4 are described, the block section A1WT-N has connection relationships with a block section A3WT-N and a block section A3WT-R. In addition, the block section A3WT-N has connection relations with the block section A1WT-N and the block section A1WT-R. In this manner, Fig. 4 shows an example in which block sections with a connection relation are connected by a straight line.

[0037]

Fig. 5 is a diagram which shows track information stored by the travel management device.

The storage unit 37 of the travel management device 30 stores track information
 5 indicating respective pieces of identification information of a plurality of block sections
 constituting a track on which a vehicle 1 travels and connection relations of these block
 sections. One piece of the track information is block section list information. The
 block section list information includes respective identification information (block
 section names) of a plurality of block section constituting a track. Another piece of the
 10 track information is the connection relationship between block sections (refer to Fig. 4).
 In the information on the connection relationship between block sections, each
 combination of two block section having a connection relation is held for all block
 sections of a track on which a vehicle 1 travels.

[0038]

15 Fig. 6 is a diagram which shows a travel route of a vehicle.

An arrow Y shown in Fig. 6 represents that a vehicle 1 travels along block
 sections indicated by the identification information of each of A2HT, A2WT-R, A1WT-R,
 A3WT-N, 1T, 3T, 5T, 7T, 9T, B1WT-N, B3WT-N, and B1HT in the track same as that of
 Fig. 3 in the order shown.

20 [0039]

Fig. 7 is a diagram which shows a reservation management table stored by the
 resource management device.

The resource management device 4 creates a reservation management table 71,
 registers the table in the storage unit 47, and updates the content of this reservation
 25 management table 71. The reservation management table 71, as shown in Fig. 7, is a

data table which holds at least respective pieces of information such as the identification information of a block section, a branch state, a branch request state, booking person identification information, and a management state in association with each other. The branch state is information for storing whether a point of a block section having a branch
 5 is set to the normal position side (-N) or set to the reverse position side (-R).

Information “-“ is set for a block section not having a branch in the branch state. The branch request state is information indicating a setting direction of the point of a block section having a branch among block sections that a vehicle desires to reserve. This setting direction may be designated in a reservation request by a vehicle side. The

10 booking person identification information is information which stores the identification information of a reservation source (vehicle, command place, station, and the like) from which a reservation of a block section has been made. The management state is information indicating a current block section management state of a block section (indeterminate, reservation in progress, reservation-completed, presence on line, failure).

15 “Indeterminate” in the management state indicates a status of not being reserved by a vehicle. The resource management device 4 mainly performs processing for updating information of this reservation management table 71. The resource management device 4 further stores data of track information indicating respective pieces of identification information of the block sections shown in Fig. 5 and connection relations of these block
 20 sections in the storage unit 47.

[0040]

Fig. 8 is a diagram which shows a processing flow of the vehicle control system.

Next, the processing flow of the vehicle control system will be described.

In the vehicle control system 10, the operation management device 2 first
 25 transmits track information on a track on which the vehicle 1 travels to the on-board

signaling device 3 mounted on the vehicle 1 via wireless communication. This track information may indicate respective block sections of a track on which a person in charge of command causes a vehicle 1 to travel. The on-board signaling device 3 outputs the track information to the travel management device 30. The communication unit 36 of
5 the travel management device 30 acquires the track information. The control unit 35 registers the track information acquired by the communication unit 36 in the storage unit 37 (step S101).

[0041]

In this step, the travel route specification unit 31 of the travel management
10 device 30 reads the track information from the storage unit 37. The travel route specification unit 31 specifies a plurality of block sections included in a track on which a vehicle travels on the basis of the track information (step S102). The track information may be information including the identification information of block sections constituting a track on which it has been determined in advance that a vehicle will be
15 caused to travel. Alternatively, the track information may be information including the identification information of block sections constituting each track of a plurality of routes which can be arbitrarily selected by a vehicle 1. The travel route specification unit 31 may specify block sections included in a track on a route specified using a predetermined route selection algorithm (a graph theory, a route searching technology, and the like)
20 when a plurality of routes connecting a specific starting point to a specific ending point can be selected on the basis of the identification information of a plurality of block sections included in the track information. The travel route specification unit 31 outputs the specified block sections to the reservation request unit 32. The reservation request unit 32 specifies information of acquired block sections as information of block sections
25 to be reserved. The reservation request unit 32 transmits a reservation request including

the identification information of block sections to be reserved to the resource management device 4 via wireless communication (step S103). The reservation request may include information of a block section at which a vehicle 1 is currently positioned. The reservation request unit 32 determines whether block sections included in the reservation request have a branch in accordance with information which is recorded in the storage unit 37 and synchronized with a reservation management table, and stores a branch request state indicating whether a point needs setting to the normal position side (-N) or to the reverse position side (-R) in the reservation request when there is a branch.

[0042]

10 The reservation management unit 41 of the resource management device 4 receives the reservation request. The reservation management unit 41 reads the identification information of block sections included in the reservation request. The reservation management unit 41 reads management state information for each of the read block sections from the reservation management table 71. The reservation management unit 41 specifies block sections whose management states are indeterminate among the block sections included in the reservation request. The reservation management unit 41 specifies identification information of a block section which is set in the identification information of the vehicle 1 as booking person identification information and has a management state of “presence on line” from the reservation management table 71. The reservation management unit 41 determines the identification information of this specified block section as a block section at which the vehicle 1 is currently positioned. The reservation management unit 41 specifies one or a plurality of block sections whose management states are indeterminate continuously from the block section at which the vehicle 1 is currently positioned as a reserved block section of a vehicle 1 among block sections whose management states are indeterminate out of the block sections included in

the reservation request (step S104). The reservation management unit 41 records the identification information of the vehicle 1 in a column of the booking person identification information in the reservation management table, which corresponds to the identification information of a reserved block section of the vehicle 1. The reservation management unit 41 records reservation completion in a column of the management state in the reservation management table, which corresponds to the identification information of a reserved block section of the vehicle 1. The reservation management unit 41 reads table information (the branch state, the branch request state, the booking person identification information, and the management state), which is recorded in the reservation management table 71 in association with the identification information of respective block sections included in the reservation request, on the basis of the identification information. The reservation management unit 41 transmits reservation completion information including the read table information to a communication destination (the on-board signaling device 3 mounted on the vehicle 1) specified on the basis of the identification information of the vehicle 1 via wireless communication (step S105). The reservation management unit 41 may transmit information indicating a reservation failure to the specified communication destination on the basis of the identification information of the vehicle 1 when there is a block section which has a connection relation with a block section at which the vehicle 1 is present among the block sections included in the reservation request in a management state of any one of “reservation in progress,” “reservation completion,” “presence on line,” and “failure.”

[0043]

The on-board signaling device 3 outputs reservation completion information to the travel management device 30 if the reservation completion information is received.

The travel management device 30 records the reservation completion information in the

storage unit 37. The reservation completion information may include table information of the reservation management table 71 (the branch state, the branch request state, the booking person identification information, and the management state). For this reason, the reservation completion information may include all information of block sections

5 constituting a track on which the vehicle 1 travels in the reservation management table 71. The speed calculation unit 310 of the on-board signaling device 3 acquires a reserved (reservation-completed) block section of the vehicle 1 on the basis of reservation completion information recorded in the storage unit 37. The speed calculation unit 310 calculates a speed limit pattern in the reserved block section. There are various

10 methods of calculating a speed limit pattern and there is no limitation thereto. For example, the speed calculation unit 310 may acquire a speed limit of each block section by communicating with the ATP device provided on a ground side alongside a track, and calculate a speed limit pattern in each block section (a speed limit value in each block section) on the basis of this speed limit. In addition, the speed calculation unit 310 may

15 calculate a speed limit pattern in accordance with a distance to a furthest ahead reserved block section in a travel direction. The travel control unit 320 of the on-board signaling device 3 performs speed control on the vehicle 1 such that it does not exceed a speed limit pattern on the basis of the speed limit pattern. The speed calculation unit 310 may calculate a speed limit pattern using gradient information acquired from the ATP device.

20 The speed calculation unit 310 may also calculate a speed limit pattern on the basis of information acquired from the operation management device 2 via wireless communication.

[0044]

Fig. 9 is a diagram which shows a speed limit pattern and a reservation status.

25 It is assumed that a vehicle 1 travels along A2HT, A2WT-R, A1WT-R, A3WT-N,

1T, 3T, 5T, 7T, 9T, B1WT-N, B3WT-N, and B1HT on the same track as in Fig. 3. Fig. 9 shows that each block section of A2HT, A2WT-R, A1WT-R, A3WT-N, 1T, 3T, 5T, and 7T is reservation-completed with respect to the vehicle 1 among block sections constituting the track indicated by this travel route. Reservation for each block section of 9T, B1WT-N, B3WT-N, and B1HT is indeterminate. In this case, the speed calculation unit 310 of the vehicle 1 calculates the speed limit pattern indicated by P in Fig. 9. In the drawing of Fig. 9, the vertical direction indicates a speed. Since reservation ahead of a speed block section 9T is not possible, Fig. 9 shows an example in which the speed limit pattern has a speed limit becoming zero in the middle of the block section 7T.

[0045]

The passage information notification unit 33 detects a current traveling block section of a vehicle 1 (step S106). For example, the passage information notification unit 33 may acquire information of a block section acquired from the ATP device on the ground side by the on-board signaling device 3, and may also detect a current traveling block section of a vehicle 1 on the basis of a current position of the vehicle 1 obtained from a GPS. The passage information notification unit 33 repeats processing for specifying identification information of passed block sections on the basis of information of the current traveling block section of a vehicle. The passage information notification unit 33 transmits passage information including identification information of a newly passed block section and identification information of the vehicle 1 to the resource management device 4 (step S107). The reservation management unit 41 of the resource management device 4 acquires the identification information of a block section included in the passage information. The reservation management unit 41 rewrites the information of a management state recorded in the reservation management table as

indeterminate in accordance with a combination of the identification information of a block section included in the passage information and the identification information of the vehicle 1 (step S108). The reservation management unit 41 reads table information recorded in the reservation management table 71 (the branch state, the branch request state, the booking person identification information, the management state, and so forth) in association with the identification information. The reservation management unit 41 transmits the read table information to a specified communication destination (the on-board signaling device 2 mounted on the vehicle 1) via wireless communication on the basis of the identification information of the vehicle 1.

10 [0046]

The on-board signaling device 3 outputs the table information to the travel management device 30 if the table information is received. The travel management device 30 updates the storage unit 37 on the basis of the table information. The travel management device 30 may also cause information of the reservation management table of the vehicle 1 to be synchronized with the information stored by the resource management device 4.

[0047]

The branch control unit 44 of the resource management device 4 may also control a direction of a point provided in a block section having a branch on the basis of the information of the reservation management table recorded in the storage unit 47.

The branch control unit 44 specifies a block section having a branch among block sections for which it has been determined that the management states of the reservation management table 71 have been newly updated to reservation in progress. The branch control unit 44 compares a branch request state and a branch state of a block section

25 having a branch among the block sections for which it has been determined that the

management states are newly updated to reservation in progress. The branch control unit 44 transmits an instruction for changing the direction of a point of this block section to the point such that this branch state coincides with the branch request state when the branch state does not coincide with the branch request state. As a result, the direction of the point is changed. The branch control unit 44 updates the management state of this block section to reservation in progress from indeterminate after the branch state has been made to coincide with the branch request state of the block section having a branch among the block sections for which it has been determined that the management states are newly updated to reservation in progress.

10 [0048]

The travel management device 30 may receive a cancellation signal of a reserved block section from a host device. The host device may be the operation management device 2, and may also be an emergency device installed in a station or a central control room. The travel management device 30 receives a cancellation signal from the host device (step S201). The travel management device 30 outputs a request for emergency braking to the travel control unit 320. The travel control unit 320 performs emergency or normal brake control and stops a vehicle 1. The reservation abandonment unit 34 transmits reservation abandonment information including identification information of a block section at which a vehicle 1 is positioned and the identification information of the vehicle 1 to the resource management device 4 via wireless communication (step S202). The reservation management unit 41 of the resource management device 4 acquires the identification information of the vehicle 1 and the identification information of a block section at which the vehicle 1 is currently positioned which are included in the reservation abandonment information. The reservation management unit 41 rewrites management states of other block sections other

than a management state associated with the identification information of a block section at which the vehicle 1 is currently positioned among the management states recorded in the reservation management table 71 in association with the identification information of the vehicle 1 from reservation in progress to indeterminate (step S203). As a result, the resource management device 4 can process a reservation abandonment of an advance block section in a travel direction of the vehicle 1 based on the emergency braking of the vehicle 1.

[0049]

Regarding the first embodiment of the present invention as has been described above, according to the processing described above, the vehicle control system 10 can control the management of a block section without requiring an interlocking device and the ATP device serving as ground equipment to perform processing of the management of a block section. That is, in the vehicle control system 10 described above, the resource management device 4 receives reservations of a block section in the order of vehicles whose reservation requests have made earlier in the reservation management of a block section. At this time, the resource management device manages reservations for each track independently without considering a relationship between tracks. Accordingly, since the resource management device 4 does not perform complicated logic processing and a logic design of an interlocking device requiring special skill is not necessary in maintenance of the vehicle control system 10, it is possible to construct a mechanism of vehicle control easily at low cost. At a time of locking control called an approach lock in a usual interlocking device, a time for compensating for a vehicle coming out of a specified block section is secured and, in the meantime, control is performed such that the block section is not reserved by another vehicle 1. However, since the position of a vehicle can be determined in the processing of the vehicle control system 10 described

above, it is not necessary to perform processing for securing a time for compensating for such a vehicle coming out of a specified block section, and it is possible to promptly allow a reservation by another vehicle after cancellation of a course (reservation abandonment) of a vehicle. Moreover, according to the processing described above, the vehicle control system 10 can manage a vehicle operation such as reservation control of block sections corresponding to an arbitrary travel route line.

[0050]

<Second embodiment>

Fig. 10 is a diagram which shows an installation state of a resource management device according to a second embodiment.

Fig. 11 is a diagram which shows resource management device information stored by a travel management device according to the second embodiment.

The first embodiment shows an example of a case in which the vehicle control system 10 has one resource management device 4. However, a plurality of resource management device 4 may be installed for each predetermined range in the track of a vehicle. In this case, the reservation request unit 32 of the travel management device 30 transmits a reservation request for a block section to be reserved to a resource management device 4 installed in a range including the block section to be reserved along which a vehicle mounted with the travel management device 30 currently travels among the plurality of resource management devices 4.

[0051]

For example, as shown in Fig. 10, if description is provided using the track shown in Fig. 3, the reservation request unit 32 of the travel management device 30 transmits a reservation request to a first resource management device 4#1 when the vehicle mounted with the travel management device 30 is positioned at one of six block

sections of A1HT, A2HT, A1WT, A2WT, A3WT, and A4WT.

In addition, the reservation request unit 32 transmits a reservation request to a second resource management device 4#2 when the vehicle mounted with the travel management device 30 is positioned at one of ten block sections of 1T, 2T, 3T, 4T, 5T, 6T, 7T, 8T, 9T, and 10T.

Moreover, the reservation request unit 32 transmits a reservation request to a third resource management device 4#3 when the vehicle mounted with the travel management device 30 is positioned at one of six block sections of B1WT, B2WT, B3WT, B4WT, B1HT, and B2HT.

10 [0052]

The reservation request unit 32 specifies a resource management device 4 which is a transmission destination of a reservation request using resource management device information shown in Fig. 11. The resource management device information stores an association relationship between identification information of a block section and identification information of a resource management device.

When there are a plurality of resource management devices 4 installed in a range including a block section to be reserved, the reservation request unit 32 may transmit a reservation request for block sections in each range to these plurality of resource management devices 4.

20 [0053]

According to the vehicle control system 10 of the second embodiment, since the travel management device 30 can make a reservation of a block section by communicating with a resource management device installed at a position relatively close to the position of a vehicle mounted with the travel management device 30, it is possible to improve a processing speed for reserving a block section, and as a result, the

travel management device 30 can advance a calculation timing of a speed limit pattern.

In addition, since each resource management device 4 only needs to manage information of block sections positioned in a range allocated to a corresponding resource

management device 4, it is possible to reduce an amount of processing of each resource

5 management device 4 respectively and to achieve a reduction in size. In addition, since a resource management device 4 can be installed close to a branch, the degree of freedom regarding disposition in an equipment room increases, and wiring to a branch device is also made easy.

[0054]

10 <Third embodiment>

Fig. 12 is a diagram which shows a processing outline according to a third embodiment.

The resource management device 4 stores each block section included in a non-branch consecutive section in which a plurality of block sections without a branch

15 are continued in the reservation management table 71, and may also store only a travel order of a vehicle traveling along the non-branch consecutive section without storing information on whether each block section included in this non-branch consecutive section is reserved or unreserved.

[0055]

20 In this case, the reservation management table 71 holds identification information of a non-branch consecutive section in addition to the information of Fig. 7. Block sections which do not correspond to the identification information of a non-branch consecutive section are block sections which are not included in the non-branch consecutive section. In addition, in the case of the third embodiment, the resource
25 management device 4 and the travel management device 30 store a travel order table.

The travel order table holds the identification information of a non-branch consecutive section and order information of respective vehicles positioning in the non-branch consecutive section. The resource management device 4 acquires identification information of a block section at which a vehicle 1 is positioned from the travel management device 30 periodically (at predetermined time intervals) (step S301). The reservation management unit 41 of the resource management device 4 compares the acquired identification information of a block section with the identification information of a non-branch consecutive section, thereby determining whether the block section at which a vehicle 1 is positioned is in a non-branch consecutive section. The travel management device 30 may determine whether the block section at which a vehicle 1 is positioned is in a non-branch consecutive section on the basis of the position of a vehicle 1 mounted with the travel management device 30.

[0056]

The reservation management unit 41 records the identification information of a vehicle 1, the identification information of a non-branch consecutive section, and the travel order of a vehicle 1 among vehicles traveling in this non-branch consecutive section in a travel order table when it is determined that the block section at which the vehicle 1 is positioned is in a non-branch consecutive section. The reservation management unit 41 of the resource management device 4 transmits information of the travel order table to the travel management device 30 of the vehicle 1 (step S302). As a result, the travel management device 30 may store the information of the travel order table. The travel management device 30 can detect a vehicle mounted with the travel management device 30 entering a non-branch consecutive section when it is determined that identification information of the vehicle mounted with the travel management device 30 is recorded in the travel order table on the basis of a periodic check.

[0057]

In a case of the third embodiment, the travel management device 30, after a vehicle mounted with the travel management device 30 enters a non-branch consecutive section, acquires the identification information of an immediately preceding vehicle traveling immediately ahead of the vehicle (step S303). Specifically, the travel management device 30 acquires a non-branch consecutive section and a travel order in which a vehicle mounted with the travel management device 30 travels from the travel order table recorded in the storage unit 37. The travel management device 30 acquires the identification information of another vehicle recorded in a travel order table in which information of a previous travel order to the travel order of a vehicle mounted with the travel management device 30 and the identification information of the same non-branch consecutive section are combined and associated. The acquired identification information of another vehicle is the identification information of a vehicle traveling immediately ahead of the vehicle mounted with the travel management device 30. The travel management device 30 acquires the identification information of a vehicle traveling immediately ahead and communication destination information from the storage unit 37 and communicates with the vehicle traveling immediately ahead. The travel management device 30 inquires about a position, a speed, and the like of the vehicle traveling immediately ahead on the basis of communication with an immediately preceding vehicle. If the position, speed, and the like of the vehicle traveling immediately ahead are acquired, the travel management device 30 outputs the position, the speed, and the like to the speed calculation unit 310 and requests for braking control. The speed calculation unit 310 calculates a speed limit pattern by further using information such as the position, the speed, and the like of a vehicle traveling immediately ahead. When a position at which a vehicle 1 travels is beyond a

non-branch consecutive section, the travel management device 30 may notify the resource management device 4 of this. Whether a position at which the vehicle 1 travels is beyond a non-branch consecutive section may be determined by the resource management device 4 on the basis of information and the like of a block section at which the vehicle 1 is positioned.

[0058]

According to the processing of the third embodiment, since vehicles positioning in a non-branch consecutive section communicate with each other, and perform braking control, block section reservation management of the resource management device 4 in this section is unnecessary, and an amount of processing of the resource management device 4 can be reduced. In addition, since the braking control of vehicles can be performed by communication between the vehicles positioning in the non-branch consecutive section, it is not necessary to communicate using a remote resource management device 4, and time required for communication is eliminated. As a result, it is possible to improve vehicle density in a predetermined section of a traveling vehicle and to improve transportation capacity.

[0059]

<Fourth embodiment>

The travel route specification unit 31 of the travel management device 30 may determine a block section to be reserved using information of a reservation status acquired from the resource management device 4 in advance. Specifically, the travel route specification unit 31 of the travel management device 30 detects identification information of a block section which is not reserved (indeterminate) from track information. The travel route specification unit 31 specifies a track constituted by block sections which are not reserved among tracks for a plurality of arbitrarily selectable

routes, and determines each block section included in this track as a reservation target.

[0060]

<Fifth embodiment>

The travel management device 30 may further include a branch control unit, and
5 may perform the same processing as the processing of the branch control unit 44 of the
resource management device 4. That is, when there is a block section having a branch
in the reserved block sections of a vehicle 1, the branch control unit of the travel
management device 30 may transmit a switching instruction for a point of the branch
based on a travel direction of the vehicle 1 to this point.

10 [0061]

<Sixth embodiment>

The travel management device 30 may also determine a travel start timing of a
vehicle mounted with the travel management device 30 on the basis of a reservation time
of a block section which is reserved by vehicles other than the vehicle 1 mounted with
15 the travel management device 30. In this case, the reservation time is further held in
association with the identification information of each block section in the reservation
management table 71 generated by the resource management device 4. The travel
management device 30 determines whether a predetermined number or more of pieces of
information of reservation in progress for new vehicle identification information have
20 been registered in the reservation management table 71 between a current time and a
predetermined time ago. The travel management device 30 determines that there are
many vehicles departing at the same time when a predetermined number or more of
pieces of information of reservation in progress for new vehicle identification
information have been registered in the reservation management table 71 between a
25 current time and a predetermined time ago. In this case, the travel management device

30 may determine to delay a travel start of a host vehicle which is stopped by a predetermined time. By performing such control of a travel start timing, a vehicle control system can prevent an abnormal load of electric power.

[0062]

5 <Seventh embodiment>

Fig. 13 is a diagram which shows a vehicle control system according to a seventh embodiment of the present invention.

In the vehicle control system, as shown in Fig. 13, the vehicle 1 may be mounted with each of the operation management device 2 and the on-board signaling device 3 including the travel management device 30. The processing flow between respective devices in processing in this case is the same as in the first to sixth embodiments.

[0063]

<Eighth embodiment>

Fig. 14 is a diagram which shows a vehicle control system according to an eighth embodiment of the present invention.

In the vehicle control system, as shown in Fig. 14, the travel management device 30 may be installed outside of a vehicle. In this case, even if wireless communication is needed between the on-board signaling device 3 and the travel management device 30, information flows between the operation management device 2, the on-board signaling device 3, the travel management device 30, and the resource management device 4 are the same as each other. Respective device components constituting the vehicle control system of the eighth embodiment may be applied to each embodiment except for the third embodiment.

[0064]

25 The on-board signaling device 3, the travel management device 30, and the

resource management device 4 described above each have a computer system therein.

Processes of each processing described above are stored in a computer-readable recording medium in a form of program, and the processing is performed by a computer reading and executing this program. Here, the computer-readable recording medium

5 refers to a magnetic disk, a magneto-optical disc, a CD-ROM, a DVD-ROM, a semiconductor memory, or the like. In addition, this computer program may be distributed to a computer by communication lines, and the computer which receives this distribution may execute this program.

[0065]

10 The program described above may be a program which realizes some of functions described above. The program described above may also be a so-called difference file (a difference program) which can realize the functions described above by being combined with a program which is already recorded in a computer system.

[Industrial Applicability]

15 [0066]

The present disclosure may be applied to a vehicle control system, a travel management device, a resource management device, a vehicle control method, and a program.

20 Reference Signs List

[0067]

1 Vehicle

2 Operation management device

3 On-board signaling device

25 4 Resource management device

30 Travel management device

CLAIMS

1. A vehicle control system comprising:

a travel management device which includes a reservation request unit, the
5 reservation request unit being configured to transmit a reservation request for a block
section to be reserved based on track information indicating a plurality of block sections
constituting a track on which a vehicle travels and a connection relationship between the
block sections, the block section to be reserved being among the block sections included
in the track on which the vehicle travels; and

10 a resource management device which includes a reservation management unit,
the reservation management unit being configured to record the block section to be
reserved indicated by the reservation request as a reserved block section of the vehicle
which has transmitted the reservation request in case where the block section to be
reserved indicated by the reservation request is not reserved by a vehicle other than the
15 vehicle which has transmitted the reservation request at a time at which the reservation
request is received.

2. The vehicle control system according to claim 1,

wherein the reservation management unit of the resource management device is
20 configured to transmit reservation completion information indicating the reserved block
section of the vehicle which has transmitted the reservation request to the vehicle which
is a transmission source of the reservation request, and

the travel management device includes a speed calculation unit configured to
calculate a speed limit pattern in each block section up to the block section indicated by
25 the reservation completion information.

3. The vehicle control system according to claim 1 or 2,
wherein the vehicle is mounted with the travel management device,
the resource management device is installed in each predetermined range in the
5 track, and
a reservation request unit of the travel management device is configured to
transmit, to the resource management device corresponding to a range including the
block section to be reserved, the reservation request for the block section to be reserved.
- 10 4. The vehicle control system according to any one of claims 1 to 3,
wherein the travel management device includes a passage information
notification unit configured to transmit a passed block section of the vehicle to the
resource management device, and
the reservation management unit of the resource management device is
15 configured to update information of the passed block section from a reserved block
section to an unreserved block section in response to receiving the passed block section.
5. The vehicle control system according to any one of claims 1 to 4,
wherein, the travel management device includes a reservation abandonment unit
20 configured to perform stop control of the vehicle in a case of acquiring a cancellation
request for the reserved block section from a host device, the reservation abandonment
unit being configured to transmit a reservation abandonment of an advance block section
in a travel direction in the reserved block section to the resource management device
after the vehicle stops.

6. The vehicle control system according to any one of claims 1 to 5,
wherein the travel management device is mounted on a vehicle.
7. The vehicle control system according to claim 6,
5 wherein the resource management device is configured to store each block
section included in a non-branch consecutive section in which a plurality of block
sections without branches are continued, is configured not to store information on
whether each block section included in the non-branch consecutive section is reserved or
unreserved, and is configured to store a travel order of a vehicle traveling along the
10 non-branch consecutive section, and
the travel management device is configured to acquire, after the vehicle mounted
with the travel management device enters the non-branch consecutive section,
identification information of an immediately preceding vehicle traveling immediately
ahead of the vehicle from the resource management device, is configured to detect a
15 position of the immediately preceding vehicle by communicating with the immediately
preceding vehicle, and is configured to request braking control based on the position of
the immediately preceding vehicle and a position of the vehicle mounted with the travel
management device.
- 20 8. The vehicle control system according to any one of claims 1 to 7,
wherein the travel management device is configured to acquire reservation status
information from the resource management device in advance in order to determine a
block section to be reserved.
- 25 9. The vehicle control system according to any one of claims 1 to 8,

wherein the resource management device includes a branch control unit, the branch control unit being configured to perform, in a case where a block section having a branch exists in the reserved block section of the vehicle, switching control for the branch based on a travel direction on the vehicle.

5

10. The vehicle control system according to any one of claims 1 to 7,
the travel management device includes a branch control unit, the branch control unit being configured to perform, in a case where a block section having a branch exists in the reserved block section of the vehicle, switching control for the branch based on a
10 travel direction on the vehicle.

11. The vehicle control system according to any one of claims 1 to 10,
wherein the travel management device is configured to determine a travel start timing of a vehicle mounted with the travel management device based on a reservation
15 time of a block section reserved by a vehicle other than the vehicle mounted with the travel management device.

12. A travel management device comprising:
a reservation request unit configured to transmit a reservation request for a block
20 section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the vehicle travels.

25 13. A resource management device which is communicatively connected to a travel

management device which includes a reservation request unit, the reservation request unit being configured to transmit a reservation request for a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the
5 block section to be reserved being among the block sections included in the track on which the vehicle travels, a resource management device comprising:

a reservation management unit configured to record the block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be
10 reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle which has transmitted the reservation request at a time at which the reservation request is received.

14. A travel control method for a vehicle control system including a travel
15 management device and a resource management device,

wherein the travel management device transmits a reservation request for a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block
20 sections included in the track on which the vehicle travels, and

the resource management device records the block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle
25 which has transmitted the reservation request at a time at which the reservation request is

received.

15. A program for a computer of a travel management device in a vehicle control system including the travel management device and a resource management device, the
5 program causing the computer to execute:

a reservation request procedure of determining a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on
10 which the vehicle travels, and transmitting a reservation request for the block section to be reserved.

16. A program for a computer of a resource management device in a vehicle control system that includes a travel management device and the resource management device,
15 the travel management device including a reservation request unit, the reservation request unit transmitting a reservation request for a block section to be reserved based on track information indicating a plurality of block sections constituting a track on which a vehicle travels and a connection relationship between the block sections, the block section to be reserved being among the block sections included in the track on which the
20 vehicle travels, the program causing the computer to execute:

a resource management procedure of recording the block section to be reserved indicated by the reservation request as a reserved block section of the vehicle which has transmitted the reservation request in case where the block section to be reserved indicated by the reservation request is not reserved by a vehicle other than the vehicle
25 which has transmitted the reservation request at a time at which the reservation request is

received.