

Description

This invention relates to a method and apparatus for evaluating recording characteristics of a recording medium as referred to in the preamble of claims 1 and 10.

Description of the prior art

The art of performing a variety of audio and/or video tests on various electronic information handling devices is well known. It is an additionally well-known technique to perform certain audio and/or video tests upon virgin recording mediums such as magnetic tape in order to evaluate the characteristics of the tapes for purposes of quality assurance and for grading, i.e. for categorizing the quality as to grade of the tapes exiting a production line.

However, such tests for sample testing of blank tapes in production run are performed for purposes of evaluating the magnetic characteristics of the medium only and are performed under ideal recording and playback conditions resulting in specifications for the medium per se.

Prior art devices for automatic testing of audio/video equipments such as that shown in document DE—B—2 049 259 comprise a system where a number of signal processing units is arranged in series and subjected to test signals provided by a test signal generator. Selected parameters of the test signal are measured at the outputs of the signal processing units and supplied to a comparator for comparison of the selected parameters between the input and output values of the test signals. Instead of a comparison also an analysis of the output values with respect to standards is disclosed.

Since the test procedures noted above are for evaluating the recording medium or the precessing equipments themselves, there were heretofore no procedures known for evaluating a medium which had material prerecorded on it and for subsequently comparing the results of such evaluation with the evaluation of a duplicate copy recorded on another storage medium.

Accordingly, this invention provides a method of analyzing the signal transfer characteristics of a signal processing unit comprising the steps of establishing an input signal of varying content, feeding said input signal to a signal processing unit and evaluating the output signal of said signal processing unit by comparison with said input signal, characterized by the steps of measuring selected parameters of selected parts of said input signal to produce an input signal measurement, storing the values of said input signal measurement to define a stored signature thereof, measuring the same parameters of parts of the output signal from said signal processing unit that correspond to said selected parts of said input signal to produce an output signal measurement, and comparing the values of said output signal measurement with said stored signature.

Further this invention provides an apparatus for analyzing the signal transfer characteristics of a signal processing unit comprising means for establishing an input signal of varying content, means for measuring selected parameters of selected parts of said input signal to produce an input signal measurement, an a comparator characterized by: memory means for storing the values of said input signal measurement to define a stored signature thereof; means for feeding said input signal to a signal processing unit; means for measuring the same parameters of parts of the output signal from said signal processing unit that correspond to said selected parts of said input signal to produce an output signal measurement; said comparator comparing the values of said output signal measurement with said stored signature.

According to the invention, "unit evaluation" is accomplished by establishing an input signal of known content, measuring selected parameters of selected parts of the input signal, feeding the input signal to the unit under test, measuring the parameters of parts of the output signal from the unit under test corresponding to the same selected parts of the input signal, and comparing the selected parameters of the input signal with the corresponding parameters of the output signal.

In the following discussion, the term "unit" in the phrase "unit evaluation" includes tapes, discs, audio records, electronic storage, various electronic circuits ranging from simple integrated circuits or printed circuit boards to macrosize amplifiers or other complex information handling equipment.

Since this invention is exceptionally useful in the evaluation of videodiscs, a special form of the phrase "unit evaluation" will be used throughout this application, and thus, "disc evaluation" will refer to the analysis of information retrieved from a videodisc as compared with the analysis of the recording medium (generally tape) of which the information recorded on the disc is duplicative. Thus, "tape evaluation" will refer to evaluating the contents of a master tape, while "disc evaluation" will refer to the information retrieved from a replicated disc.

Another term used through this application is "signature". The term "signature" has been used in the prior art to designate a parameter listing against which devices being tested are compared.

The term "signature" as used in this application has a degree of identity or "personality" of the unit under test, insofar as the "signature" is comprised of a multiplicity of test parameters, each parameter having limits within which comparable measurements of the unit under test must fall. Accordingly, the "signature" as used with this invention is a practical, as opposed to theoretical, model against which all further units are compared.

Brief description of the drawings

The invention will now be described in detail having reference to the appended drawings in which:

Figure 1 shows in block diagram form a complete audio/video quality monitoring system in which a common central controller cooperates with multiple interface subsystems and associated multiple audio/video test subsystems;

5 Figure 2 shows a modified version of Figure 1 in which, rather than having a central controller, the audio and video test subsystems communicate with and are under the control of an isolated and independent interface subsystem and controller;

Figure 3 is a more detailed block diagram of the audio/video quality monitoring system of Figure 1 showing the interrelationship between the central controller and one of the plurality of interface subsystems and its associated audio and video test subsystems;

10 Figure 4 is a block diagram showing a further breakdown of the audio test subsystem of Figure 3;

Figure 5 illustrates a representation of a length of video tape showing the position of lead-in, lead-out program material, and track locations for audio and control and cue tracks;

Figure 6 shows, in the upper half thereof, a spacial representation of the placement of audio test tones at the lead-in and lead-out portion of a video tape or video disc, and in the bottom half thereof, a pictorial representation of the signals in the corresponding blocks of the top half of the figure;

Figure 7 shows, in block diagram form, the audio test tone generator logic for creating the audio test tones for placement on lead-in and lead-out of the video tape or video disc;

Figure 8 is a general block diagram illustration of the audio analysis logic portion of the audio test subsystem;

20 Figure 9 illustrates a more detailed portion of the audio analysis logic, and in particular, the audio controller portion thereof;

Figure 10 shows details of a portion of the audio analysis logic, and in particular, the audio and video selector, 6734 tone detector, and time code or frame number selector;

Figure 11 shows the details of the multi-programmer portion of the audio analysis logic of Figure 8;

25 Figure 12 is a timing chart showing the relationship between the signals operative for carrying out the audio analysis according to the logic diagram of Figure 8;

Figure 13 illustrates, in block diagram form, the operative functional blocks of the video test subsystem;

Figure 14 is a waveform showing the theoretical flattened portion of the waveform of the back porch of the horizontal blanking pulse immediately following the color burst signal;

Figure 15 is a pictorial representation of the distribution of points on a video disc on which noise characteristics are measured;

Figure 16 shows, in block diagram form, the circuitry useful in measuring the noise content on the back porch of the horizontal blanking pulse of Figure 14;

35 Figure 17 is a general block diagram showing the video analysis logic associated with the video test subsystem;

Figure 18 is a general block diagram of the audio/video data evaluation subsystem;

Figure 19 is an overall procedural block diagram showing the manner in which tape evaluation is accomplished according to the present invention;

40 Figure 20 is an overall procedural block diagram showing the manner in which the disc evaluation is accomplished according to the present invention;

Figure 21 is an overall procedural block diagram showing the manner in which the throughput device evaluation is accomplished according to the present invention; and

45 Figure 22 is an overall procedural block diagram showing the manner in which the digital signature evaluation is accomplished according to the present invention.

Detailed description of the invention

Figure 1 shows a complete audio/video quality monitoring system utilizing a central controller 1 and a plurality of terminals each comprising an interface subsystem 3, an audio/video test subsystem 2, and the unit under test 4 connected to the audio/video test subsystem 2. The peripheral equipment associated with the central controller 1 comprises a memory unit 13, a keyboard 70, a data evaluation subsystem 19, and a data readout device or devices 64.

50 While Figure 1 shows a single central controller 1 with multiple interface subsystems 3, an alternative to such a "centralized" system is the arrangement of Figure 2 in which each interface subsystem 3 is inclusive of its own, perhaps less sophisticated, controller, and has its own memory unit 13, keyboard 70, and data readout devices 64. Figure 2 further shows a slightly more detailed communication link between the various components of the interface, test, and evaluation subsystems.

Figure 3 shows a greatly expanded version of the arrangement shown in Figure 1 with central controller 1 and its associated peripheral equipment connected with only a single interface subsystem 3, audio test subsystem 5, video test subsystem 7, and unit under test 4. To this point, the unit under test 4 has been treated as strictly a player-type unit capable of reproducing audio and video signals from a prerecorded tape or disc. The phrase "unit under test", however, carries with it, for the purposes of this application, a more complex arrangement comprised of a tape recorder/player 11, a disc player 9, and an audio and video selector 53 as shown within the unit under test block 4 in Figure 3. The disc player is 65 capable of outputting both video and audio signals to the selector 53 on lines 147 and 151, respectively.

Similarly, the tape recorder/player 11 outputs video on line 149, and audio on line 153. Later, it will be evident that the audio lines 151 and 153 carry two lines of audio for the purposes of accommodating a stereophonic or two channel signal.

Operation control, i.e., stop, play, reverse, fast forward, rewind, etc., is effected by operation control 117 in interface subsystem 3 via cable 133 shown in Figure 3 as a single line for simplifying the drawing. Operation control is also effective to select either audio channel, or both, and video from either the disc player 9 or tape recorder/player 11. Audio and video are thus outputted on lines 58 and 118, respectively, leaving the audio and video selector 53.

Tape position is outputted on the data channel output line of the tape player 11, and audio test tones are applied to the tape by tape recorder 11 as will be discussed in connection with more detailed figures later.

Having reference to Figures 3 and 4, the function of the audio test subsystem will now be described.

Upon receiving a customer's tape, a duplicate is made, and while the duplicate copy is properly termed a submaster, it is also referred to as a pre-mastering tape preparatory to producing a disc master. In any event, the first step in the process is to transfer the customer's program from the master tape to a submaster or pre-mastering tape. Simultaneously with the transferring of the video portion of the program to the pre-mastering tape, appropriate video test signals are inserted on lines 19 and 20 of the vertical interval. A timed sequence of audio test signals is recorded at a predetermined location on the lead-in and lead-out portions of the pre-mastering tape. The signals will be used to analyze the audio quality of the signals recorded on the tape and on the disc to be made from the tape. Details of the lead-in and lead-out audio testing will now be discussed.

In Figure 3 and 4, the data channel from the tape player 11 is outputted on line 34 and is sent to time code selector 51, a second input of which is a time code signal from time code register 116 as set up by the keyboard 70 via central controller 1. The operator thus rewinds the tape on recorder 11 to a position upstream of the start position for the test tones and sets the tape recorder into a recording mode through actuation of operation control 117 over line 133. When the time code on data channel line 34 matches the time code from register 116, the time code selector 51 sends an output compare signal to the audio controller 21 which then initiates, over line 30, test tone generator 49 to apply test tones to both channels 1 and 2 of tape recorder 11.

In a similar manner, after the test tones have been applied to the lead-in portion of the tape, the operator performs a high speed tape wind to a point corresponding to the end of the active program and enters a second beginning point for the test tones to occur, during lead-out of the tape, beginning at least 150 frames after the program end. Under control of central controller 1, when the operator permits the tape to resume normal speed prior to passing the end of active program area, a match is again detected by time code selector 51 at at least 150 frames after the program end, the tape recorder is put into record mode, and the test tone generator 49 is enabled by audio controller 21 to deposit test tones on channels 1 and 2 of the tape recorded by tape recorder 11.

It is contemplated that the present invention can be utilized to insert audio test tones in between isolated program segments, as well as during lead-in and lead-out locations.

In any event, the method of characterizing the information transfer characteristics of the recording medium basically involves recording, and simultaneously making a first measurement of, known values of one or more test signals on the recording medium, followed by playing back the recording medium and making a second measurement of the recorded test signal or signals. In the manner of establishing a "signature" as a representation of the signal transfer characteristics, and unlike prior art procedures involving merely checking properties of the medium (e.g., magnetic properties of a video tape), deviation levels from the first measurement results are set up as prescribed tolerance limits for the aforementioned second measurement, and the results of the first measurement are compared with the results of the second measurement to determine if the second measurement results are within the prescribed tolerance limits established from the first measurement results.

When testing throughput devices (such as amplifiers, printed circuit boards, microelectronic chips, etc.), or in generally applying the present invention, analyzing the signal transferring characteristics of a signal processing unit can be accomplished by establishing an input signal of known content, measuring selected parameters of selected parts of such input signal, feeding that input signal to the signal processing unit, measuring the parameters of parts of the output signal from the signal processing unit corresponding to the similar selected parts of the input signal, and comparing the selected parameters of the input signal with the corresponding parameters of the output signal. Again, the tolerance limits for the measurement of parameters of the output signal are derived as deviation levels from the measurement of the corresponding parameters of the selected parts of the input signal.

A method of analyzing the signal transfer characteristics of a signal processing unit will now be described in a slightly modified version than previously described, in that advantage is taken of an information storage device which can retain information gathered quickly from the unit under test and which can be accessed later for information analysis. In effect, the method involves establishing an input signal of known content, measuring selected parameters of selected parts of the input signal, storing the input measurement results to define a stored signature of the input signal comprising the selected parameters of selected parts of the input signal, feeding the input signal to the processing unit, measuring

the parameters of parts of the output signal from the signal processing unit corresponding to selected parts of the input signal, and subsequently comparing the parameters of the output signal with the corresponding input signature parameters. When it is desirable to carry out the actual evaluation of the output signal measurements at a later time, the method of analyzing just described can be supplemented by a further step in the evaluation process. That is, before comparing the output signal measurement with the stored selected input signature parameters, the measurements of the output signal can also be stored to define a stored signature of the output signal comprising selected parameters of selected parts of the output signal, and the comparing step would then comprise comparing the stored output signal signature with the stored input signal signature. Reference is made to Figures 3 and 4 and the following discussion for an understanding of this aspect of the invention.

A 6734 head tone is recorded and retrieved from only one channel (e.g., channel 2 of a two channel audio program). This head tone identifies the beginning of the audio test tone sequence, and the audio on line 58 (Figure 3) or line 58-2 (Figure 4) from the audio and video selector 53 is routed to the 6734 tone detector 41. The output of 6734 detector 41 is routed over line 82 to the audio controller 21 which provides, under internal process control, all of the timing functions for the remainder of the audio test subsystem 5.

Audio controller 21 is enabled preparatory to the system recognizing the 6734 tone burst by the operator, through keyboard 70, central controller 1, and interface subsystem 3 by the sending of a request to the audio subsystem to load its internal acquisition program and to activate the audio test subsystem.

At the time audio test signals were generated and applied to the tape, a SMPTE start code is entered by the tape operator to indicate the start of active program as expressed in hours and minutes. Similarly, a SMPTE end code as entered by the tape operator indicates the end of active program as expressed in hours and minutes. Thus, upon command from the operator to perform tape or disc evaluation, the central controller 1, via interface subsystem 3, enables the audio controller 21 in the audio test subsystem 5 over line 18 with an "enable" signal.

The central controller then instructs the operator to rewind and start the tape or disc from the beginning. The central controller sends the SMPTE start code minus 25 seconds to the interface subsystem 3 and loads it into time code registers 116. In the same manner as previously described with depositing the test tone sequence to the pre-mastering tape, time code selector 51 alerts the audio controller 21 over line 76 that lead-in of the tape or disc is being read. With the audio controller 21 now enabled, detection of the 6734 tone burst initiates the action of audio controller 21 to perform its timing sequences for the various analyzing functions of the audio test subsystem over line 30. One of the output control signals over line 30 is a control and trigger signal routed to the multiprogrammer 23. Upon receipt of the control and trigger signal, multiprogrammer 23 digitizes the segmented audio test tones on line 58, stores the digitized version of the test tones in memory, and under control of the audio controller 21, converts a selected segment of the audio test tones to a continuous analog representation and sends such representation over line 46 to audio signal analyzer 25 for general analysis, and to audio spectrum analyzer 27 for spectrum analysis of the lead-in and lead-out test tones. Direct audio on line 58 from the audio/video selector 53 is routed to an active program spectrum analyzer 43 and a mono/non-mono signal check 62, the former performing spectrum analysis of selected portions of the active program material, and the latter making a determination as to whether or not the two audio signals on the two audio channels of the playback audio are substantially the same or different, thereby indicating that the audio portion of the program is either monophonic or non-monophonic. The term "stereo" is not used in describing the function of the signal check block 62, since the invention is equally suited for analyzing audio signals on the two channels in the form of monophonic, stereophonic, or totally separate audio tracks.

The outputs of each of the signal analysis blocks of the audio test subsystem are routed to a data evaluation subsystem 19 which, under instructions from the operator through central controller 1 compares the audio analysis results with standards, i.e., performs a signature comparison, and outputs the results of the evaluation onto a printer 15 or visual display 17.

With specific reference to Figure 3, the video from audio and video selector 53 overline 118 is routed to the video test subsystem 7, the video signal being converted from analog to digital form by A/D converter 123, the digitized version being stored in digital memory 124 and selectively processed or analyzed in video processor 125. The output of video processor 125 is thus a video "signature" of the recovered video signal, is outputted over line 126 to the data evaluation subsystem 19, and the thus obtained output "signature" is compared with a stored signature in the data evaluation subsystem 19, the results of which is printed on printer 15 and/or displayed at display station 17.

Program start and end signals on line 76 and evaluate start on line 78, all from code or frame number selector 51, enable audio controller 21 to initiate and periodically check active audio as a result of decoding frame time codes from the vertical interval of the video received from the audio/video selector 53 on line 118.

For purposes of illustration and to insure consistency of terminology used in this specification with that normally used and accepted in the art, references made to Figure 5 which shows a schematic representation of a length of video tape containing a lead-in portion, a lead-out portion, and a program material portion sandwiched therebetween. Assuming tape motion is to the right in Figure 5, the beginning of the tape 55 has a lead-in portion 57, a test tone zone 59 on the lead-in portion, and a guard portion 65 of

lead-in, all followed by the program material portion 67. The test tone zone 59 on lead-in is comprised of two tracks of audio test tones, track 1 being represented by numeral 61 and track 2 by numeral 63.

In symmetrical fashion, following the program material portion 67, a lead-out guard portion 65 precedes test tone zone 59 comprised of audio track 1 shown at 61, audio track 2 shown at 63, and lead-out portions 57 extending to the end of the tape.

The dotted line at 66 represents a control track for use in synchronizing the tape drive of the tape recorder upon playback, among other things, and a cue track 68 upon which can be recorded a variety of signals, including time code frame numbers, editing data, additional audio, etc.

Referring to Figure 6, in order to have a known measurable set of standards upon which to qualify audio signals, a segmented signal train of appropriate test signals is recorded on both the lead-in and lead-out areas of the pre-mastering tape. In a preferred embodiment of the invention, audio test tones are recorded on both audio channels of the tape and occupy 12 vertical frame times in corresponding areas on both of the audio channels as represented by the vertical dotted lines in Figure 6. Preceding the 12 frames of test tones, on channel 2, is the 6734 test tone location signal.

The top half of Figure 6 schematically shows the two audio channels 61 and 63 with a literal designation of the type of signal contained in each frame time period of each audio channel. The bottom half of Figure 6 is a drawing of the approximate waveforms of the signal identified in the upper half of Figure 6.

When the contents of the first segment of the audio test tone train is analyzed, phase, amplitude, signal-to-noise, and harmonic distortion measurements are taken. Since the two channels contain, for the durations of segments 2 and 3, one kilohertz on one channel simultaneously with DC (i.e., no signal) on the other channel, cross talk measurements from one channel to the other are taken during segments 2 and 3.

During segments 4 and 7, each channel contains a DC level, and thus noise level measurements are taken during these time slots.

A prescribed summation of 60 HZ and 7 KHZ tones is contained on segments 5 and 6, and when analyzed with appropriate test equipment indicate the intermodulation distortion level through the recording and playback process.

Finally, segments 8—12 contain audio tones continuously sweeping through a wide range of frequencies, i.e., from 20 HZ to 20 KHZ, and the analysis of the recovered test tones in this area reflect the frequency response of the transfer characteristics.

For the purposes of this invention, the contribution to the electronics involved in the recording/playback process is considered negligible.

Turning now to Figure 7, a schematic diagram is shown which produces the audio test tones. A test tone generator and multiplexer 49 contains a plurality of function generators including a 6734 generator 73, a 1 KHZ tone generator 75, a 60 HZ tone generator 77, a 7 KHZ tone generator 79, a sweep generator 81, and a DC source 83.

In the test tone recording process, upon command from the keyboard operator, an enabling signal over line 18 is routed to audio controller 21. The tape is rewound and put into play condition, whereupon the SMPTE code derived by the central controller 1 is loaded into lead-in location register 87 and sent over line 86 to comparator 91. As the tape progress in its play mode, a position detector 85 reads the SMPTE time code off the data channel tape recorder 11 and sends the detected position information over line 84 also to comparator 91. After enabling of the audio controller 21, the controller 21 interrogates comparator 91 for detection of correspondence between the present position detected by position detector 85 and the predetermined point at which lead-in test tone signals are to be applied, the latter location information taken from lead-in location register 87. When a comparison is found, an output of the comparator 91 over line 28 initiates the subsequent multiplexing action under control of audio controller 21. Basically, audio controller 21, over line 72, selectively, and at a video vertical repetition rate, enables one or two of the function generators feeding multiplexer 71. Multiplexer 71 then sums the outputs of the selected function generators, and outputs the desired combinations shown in Figure 6 over lines 76 and 78 to be routed to the input channels 1 and 2 of tape recorder 11.

Simultaneously with detection of the compare signal on line 28, audio controller 21 outputs a record enable signal on line 80 to tape recorder 11 in order to change the recorder from the play to the record mode so that the audio test tones will be deposited, in the fashion shown in Figure 6, on the separate audio channels.

Control of forward, reverse, play, and stop motions of the tape recorder 11 are effectuated under control of audio controller 21 over the lines in cable 133. Not shown in Figure 7 are communication links between the central controller 1, interface subsystem 3, and the audio test subsystem 5 which communicate the operator's keyboard commands to the audio controller for effectuating the various motion functions of the tape recorder 11. These are typical control communication paths which can be implemented in a variety of known ways.

A general block diagram of the audio analysis logic is shown in Figure 8. In the manner described in connection with Figure 3, both a disc player 9 and a tape recorder/player 11 are shown connected to an audio selector 53 (the audio portion of audio and video selector 53) the two audio outputs of disc player 9 being carried by line 32, while the two channels out of the tape player 11 are carried by line 16. Channels 1 and 2 audio out of the audio selector 53 are carried on lines 58-1 (channel 1) and 58-2 (channel 2). It will be

noted that only channel 2 audio is sent to the 6734 detector 41, consistent with the waveforms shown in Figure 6. The audio on line 58-1 enters A/D converter 37, is digitized thereby and sent over line 36 to the digitized test tones memory 33 for storage. Under command of the audio controller 21, a control and trigger signal on line 30 is effective to cause recirculate control 99-1 to recirculate a selected test tone segment in the digitized memory 33 and output that selected tone segment in a continuous manner over line 38 to D/A converter 39. The continuous representation of the selected test tone is then routed over line 46 to the audio signal analyzer 25 and lead-in/lead-out spectrum analyzer 27 as described briefly earlier. The outputs of the two analyzers 25 and 27 are routed over lines 48 and 50 to audio analysis memory 47. The memory unit 45 thereof has information written into it by memory write gates 44 which receive outputs from multiplexer 42 in a timed manner under control of audio controller 21 over line 30. Thus, all inputs to the multiplexer 42 are sequentially acted upon to be stored in memory unit 45 for later evaluation by the evaluation subsystem.

The analysis of the appropriate locations during lead-in and lead-out for recovering audio test tones to be analyzed is controlled by outputting a signal on line 28 from comparator 91 when the appropriate frame numbers during lead-in and lead-out have been detected. Whether the audio test subsystem is analyzing the tape or the disc, present position data is received over lines 34 and 118, respectively, by position detector 85. The present position is then routed over line 84 to comparators 95 and 91. Comparators 95 and 91 operate in similar manners, i.e., a desired tape or disc position is contained in location registers, and the contents of such registers is compared with the present position data to enable the audio controller 21 at coincidence thereof. In Figure 8, the two comparators 91 and 95 are shown separately, since they perform slightly different functions in carrying out the audio analyses.

That is, comparator 95 makes a comparison of the time code contained in the video information of the active program material so as to identify program start, program end, and various points along the program material content at which active audio and/or video tests are to be carried out. On the other hand, since there is no video contained in the lead-in and lead-out portions of a tape or disc, comparator 91 must rely upon SMPTE time code detection from either the data channel out or audio out signals of the tape and disc player.

After lead-in analysis has been accomplished, the audio test subsystem proceeds to analyze active audio program material at predetermined time intervals during the active programming. Comparator 95 is thus provided with present position data from the vertical interval of the video signal, and location register 109, when matched with present position, outputs a program start signal to the audio controller 21 to ready the audio controller for subsequent active program analysis control. At the first predetermined location in the active program wherein audio is to be analyzed, location register 111 will have a position location match with present position from position detector 85, and comparator 95 will output an evaluate start signal over line 78 to audio controller 21. Control then of two additional audio analysis functions of the audio test subsystem commences under control of audio controller 21 over the control line generally designated at 30 in Figure 8.

The audio from both channels of the playback device exiting audio selector 53 enters active program two channel spectrum analyzer 43. Analyzer 43 contains two analyzer arrays, one for each of the audio channels. Since the audio to be analyzed during active program material is continuous, it is not necessary to digitize and recirculate audio segments in the multiplexer 23 as was necessary with the short segment duration test tones of the lead-in and lead-out portions of the tape or disc. Accordingly, the audio entering spectrum analyzer 43 is selected audio direct from the playback devices. Both arrays 113 and 115 of the spectrum analyzer 43 operate in identical fashion, i.e., a 45 second audio waveform from each audio channel is acquired and transformed into two frequency spectrum of 128 separate frequency points for each channel. Point spacing is in 200 HZ increments, and each value analyzed at each point is expressed in decibels. The frequency spectrum for each sample represents a unique audio "print", and the 128 points for each channel have their values contained on lines 56 and 60, respectively, and these values are multiplexed with the other analyzer signals in multiplexer 42, and ultimately stored in memory unit 45.

Another part of the "signature", and therefore another input to multiplexer 42, is a signal on line 54 indicating whether or not the audio portion of the program is monophonic or non-monophonic. The signal is developed in the mono/non-mono signal check block 62. Channel 1 and channel 2 audio are received by block 62 over lines 58-1 and 58-2, respectively, these two signals being compared with each other in amplitude comparator 105. Mono/non-mono testing is performed at intervals throughout the active programs areas of the tape or disc. Each test consists of 65,536 measurements, the measurements being spaced one millisecond apart.

Block 62 illustrates a preferred embodiment of the mono/non-mono check in which the amplitudes of the two audio channels are continuously compared in comparator 105 with the difference between the two audio channels being outputted on line 84. If the amplitudes are within 5% of each other, threshold detector 107 does not react to the signal on line 84, there is no output on line 86, and a 1 KHZ clock 103 is applied over line 88 to the mono/non-mono counter 101. Without an input on line 86, i.e. the amplitudes of the audio on both audio channels are within 5% of one another, counter 101 is incremented by 1 count. One millisecond later, as determined by the pulse recurrent rate of 1 KHZ clock 103, counter 101 is again incremented if the amplitudes are again within 5% of one another. This procedure continues in like manner until the measured amplitudes between the two audio channels are greater than 5% in difference, at which

time threshold detector 107 outputs a step waveform on line 86 to inhibit counter 101 from incrementing one count. As a result, after counter 101 permits 65,536 clock pulses to increment or not increment the counter, the accumulated count is sent over line 54 to multiplexer 42 and stored in memory unit 45 by memory write gate 44 to become a part of the "signature" for the unit tested.

Obviously, in the printout of the analysis performed by the audio test subsystem, the greater the number count on line 54, i.e. the closer the accumulated count is to 65,536, the more definite it is that the two audio signals on the two audio channels are the same, i.e. the audio program is monophonic.

An alternate implementation of the mono/non-mono check block 62 is represented by the dotted line 88' from 1 KHZ clock 103 to amplitude comparator 105. In this embodiment, the amplitude of the audio on the two channels 58-1 and 58-2 are not compared continuously, but rather are compared under the gating action of the 1 KHZ clock, that is, a comparison is made every millisecond. Comparator 105 is then arranged such that, when the amplitudes of the signals of the two audio input lines 58-1 and 58-2 are within 5% of one another, an output pulse is routed to threshold detector 107 along line 84. The output of threshold detector 107 is then a step when the amplitudes on the two audio channels are within 5% of one another and DC when the amplitudes are greater than 5% of one another. Since comparator 105 is clocked at a 1 KHZ rate, the maximum frequency step signal out of threshold detector 107 is also 1 KHZ, and when a stereophonic or non-monophonic program is being and counter 101 is incremented fewer times. Again, assuming that amplitude comparisons are made in comparator 105 65,536 times, this embodiment of the mono/non-mono signal check merely counts the number of times that the amplitudes of the samples from the two audio channels are within a prescribed percentage tolerance of one another (5%) to provide information regarding whether or not the signals on the two channels are substantially similar in informational content.

Figure 9 is a more detailed diagram of the audio controller 21, showing that it is basically comprised of a processor 29 and read-only memory 31. Read-only memory 31 can take on any of various forms of memory such as tape cassette, hard wired or burned in micro chips, and the like. The purpose of the memory is to set up the control functions of the audio controller in a prescribed manner upon enablement by the central controller 1 and/or interface subsystem and line 18, the processor instructs the read-only memory 31 to prepare the processor 29 for outputting its control logic on line 30, (representing a plurality of actual signal lines) depending upon subsequent signals received by processor 29.

In Figure 10, there is shown, in more detail than before, signal routing associated with the audio and video selector 53 and time code or frame number selector 51.

The lead-in and lead-out identification signal, herein referred to as the 6734 tone or code signal, can, in a simplified system be comprised of a non-standard frequency such as 6734 HZ lasting the time of one picture frame preceding the sequence of test tones of the lead-in and lead-out portions of the tape or disc. However, a better identification signal is preferably a coded form for a sequence of numerical digits such as 6, 7, 3, and 4. The code is a self-clocking digital representation of the number series 6734 which is chosen so as to remove from chance (for all practical purposes) the possibility that any other randomly recovered signal from tape or disc would falsely appear to be the identification signal. The coded digits are represented in binary by switching between two square wave source tones, a 1 KHZ tone and a 2.5 KHZ tone, according to 1 and 0 binary states, respectively. Upon detection by 6734 detector 41, the transitions attributed to the 1 KHZ tone are interpreted as logical 1's, while the transitions attributed to the 2.5 KHZ tone are interpreted as logical 0's. Upon detection of a proper combination of 1's and 0's making up the binary representations of 6, 7, 3, and 4, detector 41 outputs a "match" signal to indicate that the series of lead-in and lead-out test signals follow.

Although the discussion so far has involved processing, analyzing, and evaluating audio program material, video signals are utilized in the audio test subsystem for the purpose of determining when active audio is to be analyzed, and such information is derived from the frame number codes in the vertical interval of the video signal. Accordingly, the video from disc player on line 147 and the video from tape player on line 149 are routed to selector 53, and depending upon which program is to be analyzed, disc or tape, an output video signal on line 118 is routed to frame number selector 51. When the predetermined frame code from the interface subsystem on line 18-2 is compared with the video frame number code in selector 51, a "program start" signal is generated on line 76 upon coincidence of the first frame of the active video program with the predetermined frame code number, and subsequently an "evaluate start" signal is generated on line 78 upon coincidence of the predetermined points of analyzing the active audio portion of the program with predetermined frame codes. Since audio analyzing is accomplished in a rather short period of time as compared with the length of most programs (e.g. 45 seconds for spectrum analysis and 65.5 seconds for mono/non-mono check), a number of predetermined frame codes on line 18-2 received by selector 51 will result on a plurality of spaced "evaluate start" signals on line 78.

Details of the multiprogrammer 23 is shown in Figure 11. The purpose of the multiprogrammer 23 is to receive audio in on line 58 from the lead-in and lead-out portion of the program and to output a continuous version of the audio on line 46. Additionally, multiprogrammer receives a control and trigger on line 30 for synchronizing the inner workings of the multiprogrammer, and outputs a 1 KHZ clock as the one millisecond timing signal for mono/non-mono signal check 62.

The segmented audio test signal train is received on line 58 and converted to digital form by A/D

converter 37. Upon sensing the 6734 tone in detector 41, audio controller 21 sends control and trigger signals along line 30 to the program storage 35, A/D converter 37, and timer spacer 103.

Control to program storage 35 merely resets the internal program of the multiprogrammer so as to acquire, recirculate, and output audio at the appropriate times. The trigger on line 30 to pulser 97 and pacer 103 is generated upon detection of the 6734 start tone. Typically, pulser 97 outputs a 32 KHZ square wave for activation of the A/D converter 37, while pacer 103 outputs a 64 KHZ square wave for digital-to-analog conversion timing in D/A converter 39. The 1 KHZ clock output on line 88a is the basic timing source for the mono/non-mono check block 62. In this connection, the 1 KHZ clock circuit 103 in Figure 8 shapes the clock for distribution within the mono/non-mono check block 62.

With the digitizing pulses configured as described above, A/D converter 37 converts the real-time audio in on line 58 and stores it in acquisition storage 33. It should be recalled that, subsequent to the 6734 start tone, twelve segments of audio test tones are received by multiprogrammer 23, and at a 30 frame per second rate, all twelve frames will be written into acquisition storage 33 in 0.4 seconds.

In order to analyze a continuous form of each segment of the audio test train in lead-in and lead-out, program storage 35, under control of audio controller 21, retrieves, in turn, each selected segment of the audio test tone train, recirculates it via control of recircular control 99 over line 80, and causes a continuous form of the particular selected segment to be outputted over line 38. D/A converter 39, timed by pacer 103, then outputs a continuous analog version of the selected audio test tone segment over line 46 for analyzing by the signal analyzer 25 and spectrum analyzer 27 shown in Figures 4 and 8.

The functioning of the audio test subsystem has been described in terms of signal routing between circuit blocks of the foregoing figures. Figure 12 should serve to clarify the signal routing details and provide a timing analysis of the many signals described only verbally heretofore. The audio waveform of channel 1 is shown schematically at 90 in Figure 12, while the channel 2 waveform is shown at 92. The beginning of the tape or disc is to the left in Figure 12. Both channels 1 and 2 show the test tones in lead-in, followed by program material, followed by lead-out test tones.

Since only lead-in and lead-out test tones are acquired from the recording medium of a rate too fast for analyzing, only these test signals need to be digitized, stored, and recalled for further analysis at a later time. Accordingly, digitized audio waveform 94 indicates that multiprogrammer 23 is performing its digitizing under control of audio controller 21 only during lead-in and lead-out time. As explained earlier, analysis of the program material is accomplished in real-time and need no digitizing technique applied.

"Program start" waveform 96 occurs as a single pulse at the beginning of the program material. As explained earlier, this pulse is sent to the audio controller 21 to clear and reset the internal audio processor preparatory to taking active audio samples for analysis.

On the other hand, "evaluate start" waveform 98, occurs periodically throughout the program material and is shown by way of example in Figure 12 as occurring four times. Since the longest active analyzing time is approximately 65.5 seconds, it is obvious that "evaluate start" pulses could occur at a corresponding or slightly lower rate.

Figure 12 shows an "evaluate start" pulse at the beginning of program material, and as a result, the count from counter 101 (Figure 8) begins to be accumulated. Waveform 100a shows a plurality of counts occurring at a 1 KHZ rate, and assuming that a theoretical monophonic signal has been recorded in both audio channels 1 and 2, most, or all of the 65,536 samplings are shown to exist, thereby indicating the presence of a monophonic program on the two audio channels. On the other hand, waveform 100b illustrates the effect of acquiring and analyzing a non-monophonic audio program on the two channels, and only occasional 1 KHZ pulses are present to be accumulated, and the scarcity of counter pulses will accumulate, after 65.536 seconds, to a small number indicating the existence of a non-monophonic program on the two audio channels. It should be appreciated that, due to spacial limitations, the pulses indicated at 102a and 102b of waveforms 100a and 100b, respectively, are only schematic representations of the actual waveforms when viewed on an oscilloscope.

Audio controller 21, over line 80, creates waveform 104 having "save accumulated count and clear counter" pulses 106 applied to mono/non-mono counter 101 so as to output the accumulated count over line 54 to be analyzed by audio analysis memory 47, having reference again to Figure 8.

In a similar manner, audio controller 21 creates the approximate 45 second enabling pulse 110 of waveform 108 to activate the spectrum analyzer 43, and during the relaxation time after the 45 second analysis pulse 110, a pulse 114 shown on waveform 112 is effective to cause spectrum analyzer 43 to output the test results from the spectrum analyzer, such results being referred to "spectral print" to become a part of the signature after evaluation.

Shown in Figure 13 is the video test subsystem. The video subsystem 7 comprises essentially two logical units, an acquisition unit 119 and a processing unit 125. Acquisition unit 119 has the capability to acquire a video signal in a controlled manner, convert it from analog signal to digital values in A/D converter 123 and store a digitized signal in acquisition digital memory 124 over line 130. Typically, digital memory 124 has 32K bytes of acquisition memory, and an analog-to-digital conversion results in an 8 bit byte. One of the 525 lines in a frame is represented by 910 conversions or bytes, converted in real-time, each Each picture horizontal line being 63.5 microseconds in duration. The video test signals are encoded during vertical intervals in lines 19 and 20, and under program control of processing unit 125, selected lines

or portions of lines from a frame or from consecutive frames may be converted and stored until the 32K bytes of acquisition storage is filled.

Control of the acquisition unit 119 and computation of the acquired data is performed by processing unit 125. The processing unit 125 features a microprocessor computer 120, processing storage 121, and a real-time clock 122. Having acquired and stored the selected video test signals, control of processing unit 125 is effected by a control line 135 from interface subsystem 3. In a manner of control analogous to that associated with the audio test subsystem discussed earlier, microprocessor computer 120 accesses over line 128 the digitized and stored video test signal from digital memory 124 over line 127. Time based from real-time clock 122 over line 129, computer 120 and processing storage 121 interplay to output over line 126 the analog equivalent of the video test signal or portion thereof being processed and route same to the data evaluation subsystem to become a part of the "signature" of the tape or disc being evaluated.

Lines 19 and 20 preceding the recurrence of the video picture information in a standard NTSC video signal are made available to contain the aforementioned video test signals. A composite VITS test signal is located in each frame in field 1, line 20 and with appropriate measuring devices can provide some 15 measurements of different video parameters.

A combination VITS video test signal is located on each frame in field 2, line 20 and provides some 11 measurable parameters.

Finally, a VIRS test signal is located in each frame in both vertical fields on line 19 to provide some 9 additional measurable parameters. Modern video test equipment can be used to measure substantially all of the VITS and VIRS test signals.

An exception lines in the noise test which is generally carried out during vertical interval times of a broadcast program.

A standard test procedure for evaluating noise levels is to measure the peak-to-peak amplitude of the noise deviation during the horizontal sync pulse which is theoretically to be at a DC level for approximately 4 microseconds. On a video disc, and especially on one which uses a constant angular velocity (CAV) format, if the noise test was taken only during vertical interval, only a small percentage of the disc's surface area would be contributory to the noise measurement. This is illustrated in Figure 15 which shows, schematically, the two vertical interval V-shaped portions 207, and assuming the disc rotates in a counterclockwise direction, the dotted line 208 represents the position at which noise tests would normally be taken, i.e., on a given horizontal sync tip at a given line number of each vertical interval. Even if such a noise test were taken during each vertical interval between alternate fields, it can be appreciated by reference to Figure 15 that only a very slim localized area of the disc would be evaluated by the noise test. Accordingly, and consistent with one of the objects of the present invention to perform evaluation tests on video discs, the noise test according to the present invention is taken on each horizontal blanking pulse of any desirable portion of video program. As shown in Figure 14, the back porch 201 of the horizontal blanking pulse following the color burst 180 has a theoretically flat shape during the time indicated by arrow 202. According to the present invention, a noise evaluation is made during the time indicated by arrow 202, and since this is accomplished on each horizontal blanking pulse, substantially the entire area of the disc can be tested for noise problems, and this is shown in Figure 15 wherein, rather than the radial line of evaluation shown at 208, noise figures are taken from the disc at each of the dash lines 209. Although only two rows of dash lines 209 are shown represented in Figure 15, it can be appreciated that each of some 54,000 circles of dashed lines 209 would show on a full scale drawing, and therefore it can be appreciated that any blemishes on a disc outside the vertical interval will be taken into account in the noise measurement. This represents a substantial improvement in videodisc quality assurance as compared with the normal noise tests taken only on a single horizontal sync tip 200 as seen in Figure 14, and then only during vertical interval occurrences.

A block diagram of the circuitry used for effectuating the unique noise test according to the aforescribed procedure is shown in Figure 16. Figure 16 should be analyzed with a view to Figure 13 wherein like numbers represent like functional blocks of the two diagrams. In the noise test arrangement of Figure 16 video in over line 118 is digitized in analog/digital converter 123 and advanced to a sample and hold circuit 137. Sample and hold circuit 137 makes eight samples of the waveform portion 202, shown in Figure 14, and stores the results in digital memory 124. The processing of the noise test data is accomplished in separate fields of the video signal. It should also be noted that, since it is necessary for the sampling of the circuit 137 to sample identical parts of adjacent horizontal blanking signals, only the horizontal blanking signals outside the vertical interval are noise tested. Accordingly, typically about 480 lines per frame are sampled for the noise test measurement.

The video of field 1 is routed to mean detector 139-1 which calculates the mean value for the eight samples, and the variance detector 141-1 outputs the variance from the mean, such variance being forwarded to the averaging circuit 152. In like manner, the sampled noise of field 2 is routed to mean detector 139-2, the variance from the mean thereof being detected by variance detector 141-2, and the results also sent to averaging circuit 152. The average of the two noise figures are thus outputted on line 126 as measurement data out, and such measurement data is sent to the data evaluation subsystem to be discussed later.

With reference to Figure 17, the video analysis logic is shown. Because the testing of different sources of video program material required different control of the sample points for making measurements, a

memory 138 is provided to contain a list of frames to be measured. Upon receiving an "enable" signal from interface subsystem 3, controller 142 initiates forward, reverse, stop, and play functions of the disc player 9 or tape player 11 to ultimately cause one of these devices to output its video information over lines 147 and 149, respectively, to video selector 53. In the meantime, controller 142 clears over line 161 counter 140, and the first frame number to be measured is outputted from memory 138 over line 169 to comparator 136. When the video on line 118 out of video selector 53 is decoded as to frame number by frame decoder 134, a comparison in comparator 136 is made, and a "take measurement" signal on line 157 is routed to controller 142. Controller 142 then initiates the testing of the video test subsystem 7 by outputting an "enable" signal on line 175. Simultaneously, controller 142 enables memory write gates 144 so that the video test data on line 126 out of video test subsystem 7 can be stored over lines 167 into video analysis memory 146. The position in memory 146 to which each test analysis signal is to be written is controlled by address bus 165 having coincidence with the frame number under test.

Upon conclusion of memory storage for one sampling of video test signal, the second in the list of frames to be measured is outputted from memory 138 over line 169, and another comparison is made in comparator 136 with present frame number in order to again instruct controller 142 to "take measurement" over line 157. Controller 142 uninhibits memory gates 144 to again write the new test data analysis in memory 146 at the address from counter 140 over address bus 165. Again, controller 142 increments over line 163 counter 140 so that the next frame number to be measured is read out of memory 138.

This process continues until all of the test samples have been taken for analysis by video test subsystem 7 and written into memory 146. The output of memory 146, as discussed earlier, is routed over line 126 to the evaluation subsystem.

Figure 18 shows a block diagram of the audio/video data evaluation subsystem. As explained in connection with Figures 3, 4, 8, 13, and 16, all of the audio and video analysis data from either tape, disc, or throughput device, is sent to the data evaluation subsystem. Prior to processing in the evaluation subsystem 19, the analytical processing by the electronics has been referred to supra as "analysis". In this specification, the term "evaluation" has the special meaning of processing the "analysis" information in such a manner so as to "evaluate" the unit under test, and in a specific practical application of the invention, such evaluation is tantamount to a pass or fail statement for the unit under test.

Although throughput devices have been described earlier as being evaluable using the concepts of this invention, Figure 18 shows the typical evaluation of audio and video from a copy of a master program. A block numbered 211 represents the audio analysis data from the master source of program material, while block 212 represents the analysis of corresponding data from the copy made from the master. Similarly, master video analysis is represented by block 213, while corresponding video analysis of the copy is represented by block 214. An audio comparator 215 compares the master and copy analysis data, and the differences are routed to a printer 15 to enable visual and permanent storage of the list of differences. Similarly, video comparator 216 processes the differences in video analysis between master and copy and prints the results in the list of differences. As will be seen in subsequent figures, the audio and video comparators 215 and 216 do more than make mere line-for-line comparisons of the signals from master and copy, but rather involve the unique concept of comparing "signatures" as hereinbefore defined.

Figures 19—22 illustrate different "evaluation" schemes utilizing the concepts of the present invention. The first of these figures, Figure 19, "tape evaluation", shows that a video tape 154 is prepared by recording on program tape recorder 145 the picture and/or sound from a program source 143. Generally, the picture and sound program source is that of a customer's master video tape or a motion picture film. In either case, tape 154 is prepared from the customer's tape or film program source for the purposes of using tape 154 as a pre-mastering tape for eventual use in preparing the disc master. At the time the program is recorded on tape 154 by recorder 145, appropriate video test signals from test signal generator 148 are recorded during the vertical interval portions of the program. In preparing the pre-mastering tape 154, sufficient time is left before the program material and after the program material on the tape so as to allow for insertion of the lead-in and lead-out audio test tones. Thus, at the time the program is recorded on the pre-mastering tape 154, or at a later time, as desired, audio test tones are recorded on tape recorder 150 (or tape recorder 145 if desired), and the resulting tape 154 now contains lead-in test tones, program material, and lead-out test tones.

A player 156 outputs the audio and video signals to their respective analyzer 158, and the characteristics of the test parameters measured by analyzer 158 form parameter list 164 which can take the form of a visual display or hard copy readout. At this point, other than the application of audio test tones during lead-in and lead-out, "tape analyzing" has been accomplished, and the character of the tape is reflected in the analysis of the tested parameters listed in parameter list 164, and this type of analyzing is not uncommon in the tape manufacturing field. The present invention, however, goes beyond mere analysis of a signal source in that, from the parameter list 164, parameter deviation limits are set, either manually or under computer control by limits setter 166. The range of parameter deviations permitted by limits setter 166 can be established by applying a percentage figure to the measured parameter of the parameter list 164 and storing the deviation limits so derived in a signature store 168. Desirably, prior to the listing of the parameter analyzed in parameter list 164, a fixed standards table 162 is used as a common (e.g. NTSC, PAL, or SECAM) standard for comparing the output of the analyzer 158 in comparator 160. For

example, where the Federal Communications Commission, SMPTE, EIA, or other standards group has established precise parameter tolerance limitations on audio and video signals, comparator 160 ensures that the parameters listed in parameter list 164 are within such industry standards. On the other hand, limits setter 166 is more in line with acceptable limits permitted by the particular process involved in a particular manufacturer's recording process. Thus, when a copy is made of pre-mastering tape 154, corresponding signals from master and copy are analyzed in analyzer 158 and evaluated in evaluator 171 by comparing the signature in signature store 168 with the output of analyzer 158. The quality of the copy is thus compared against essentially two standards, the industry accepted standards according to standards table 162, and an internal manufacturer's standards set by limits setter 166. As a result, the signal evaluated by evaluator 171 is not merely weighted against fixed industry standards as has been done in the past, but is rather compared against a "signature" which is representative of the character of the recording process which should be repeatable within certain limitations. In this way, the degradation of the copying process can be evaluated against a more realistic reference, i.e., against a previously recorded signal using the same kind of tape, same recorder, and same signal source so that these latter items can be nullified as to their contributory effects.

As compared with analyzing processes which evaluate a recovered tape signal against fixed, often calculated, standards, evaluating a copy, or similar recorded program, against a "signature" permits the manufacturer to pinpoint smaller out-of-tolerance deviations and thus allow isolation of the problem areas of a process so that corrective action can be taken. Similarly, comparing against a "signature" characteristic can show the degrading effect of a process even when the signal retrieved from the second and subsequent recordings are within tolerances as compared to fixed standards. In other words, it is conceivable that for a particular recording process, the test results of analyzing a particular parameter is within extremely tight limits and of more optimum value than industry standards requires. As a result, the signature will reflect an unusually high standard for that particular parameter. This is a result of setting the limits on the basis of prior test results and not industry standards. Thus, as some part of the recording process degrades, for example, in the production of the tape itself, evaluator 171 may fail a tested unit because the parameter of interest lies outside the limits set by limits setter 166, even though analysis of that parameter shows that it is within acceptable industry standards according to standards table 162. Knowing the relationship between the manufacturing process for the tape and the particular parameter tested, immediate corrective action can be taken. Otherwise, such a defect, especially in combination with other defects, could render the product (tape in this example) unusable, and such knowledge would come to the attention of the manufacturer after the fact, i.e., after receiving many complaints by its customers.

Evaluator 171 may be implemented in some form of sophisticated comparator in which each of a large number of parameter values from analyzer 158 is compared with a pair of numbers for each such value stored in signature store 168, the two values from signature store 168 being upper and lower limits within which the parameter being evaluated must fall. The evaluation output signal is then a printed table of data showing a list of parameters, the tolerances established by limits setter 166, the value of each parameter being evaluated by evaluator 171, and out-of-tolerance limits information. A sample of a table so constructed is shown in Tables I, II, and III which are more closely associated with the "disc evaluation" shown in Figure 20.

Referring to Figure 20, the "disc evaluation" scheme is represented. Here, the same components are shown as were shown in Figure 19 with the addition of the disc mastering recorder 173 and associated functional blocks. In this scheme, evaluator 171 evaluates the tape signature stored in signature store 168 relative to the corresponding disc signature stored in signature store 231. When pre-mastering tape 154 is played in player 156, assuming that a tape "signature" has been acquired as described in connection with Figure 19, the program material and test tones are transferred to video disc 177 by disc mastering recorder 173. It is to be noted that both lead-in and lead-out signals are transferred to the video disc 177 along with program material in order that analysis of a disc can be performed using the same test signal sources as those associated with the pre-mastering tape. Blocks 217 through 223 represents the major process steps in the production of a video disc from exposure and development in block 217 through applying adhesive and putting together the two disc halves to form a completed two-sided disc in block 223. A disc player 224 then plays the completed disc, and the results are analyzed in analyzer 226 in a manner similar to that of analyzer 158. Again, it is preferable to compare the output of analyzer 226 with fixed standards from a standard's table 227 in a comparator 225. This kind of preliminary checking eliminates those discs which might contain defects causing the parameters tested to be very far out of acceptable industry standard limits. Additionally, and common to all evaluation schemes in Figures 19-22 performing this initial analysis against "world" standards is a check on the quality of a customer's original material, and this can be of great benefit when deviations from such "world" standards can be detected early, e.g., before disc mastering is initiated.

In any event, assuming the results of analyzer 226 are tolerable against fixed industry standards, the analyzer results are sent to signature table 229 and stored in signature store 231. Recalling that the lead-in and lead-out test tones are accumulated in real time in less than one-half second and that certain audio and video tests are performed on the active program material, under manual or computer control, evaluator 171 recalls the tape signature from store 168 and the disc signature from store 231 and compares parameter-for-parameter the two signatures. Again, a visual display or hard print readout is available to

show how well the particular disc has performed against its pre-mastering counterpart (reference again Tables I, II and III).

The importance of measuring like parts of the copy and master has been mentioned previously, and the logic and wisdom of this is rather obvious. Accordingly, in addition to the "signature" containing parameter analysis results and tolerance range limits, it is essential that the "tape signature" comprise in its make-up the particular frame numbers at which video and audio active program analysis is to take place. In this manner, the "personality" of a "signature" is totally characterized with all of the information to make a signature comparison at any time and at any step in the process, in Figure 20, for example, the master disc has a photoresist layer at point A in the process, is exposed and developed at point B, metalized at point C, made into a stamper at point D to produce a one-sided (1x) plastic replica at point E, provided with a reflective coating at point F, and a protective coating at point G, and finally, combined with a second-half disc to form a completed disc (2x) at point H.

It is important to note at this point that, as with any replicating process, some degradation of the program material through each step of the process can be expected at points A—H. Furthermore, the degradation to be expected between points A and B may be less than that expected between points B and C, etc. Accordingly, an application of the present invention concerns playing the disc from any point in the process and establishing a "signature" for each of the points A through H. The invention thus provides substantially "real-time" evaluation for correlation with "in process" activities to cause supervisory personnel to shut down or modify equipment before any great loss of material and employee time. Additionally, out-of-tolerance parameter trends can be readily sensed, and the information gathered by comparing process signatures at each step in the process, so as to improve specific manufacturing processes or process steps due to the highly accurate and repetitive objective testing capabilities that "signature" testing provides. Such trend information can be used to foresee potential problems, even though on an absolute scale, the parameters tested are within acceptable limits. Finally, by varying the process parameters at each major step in the process, product improvement can be enhanced by observing the "signature" comparisons when temperatures, pressures, process times, etc., are varied.

Concerning "disc evaluation", in view of the fact that video disc players are of recent design, the present invention can be used in evaluating player consistency. For example, instead of changing discs in Figure 20, the same disc can be played back on a number of disc players 224, and a "signature" of the players can be developed and compared with the "signature" established from a known good player.

The use of this invention with "throughput" devices, such as audio and video amplifiers and special effects devices, i.e., echo units, distribution amplifiers, limiters, and the like, has been mentioned earlier. Figure 21 shows such a scheme.

Since the evaluation procedure requires preparing a "signature" of a throughout reference unit 234, a separate path for a throughput under test 235 is shown in Figure 21. The unit under test is shown to have its own analyzer 226, signature table 229, and signature store 231. Of course, in the interest of economy, a scheme similar to that of Figure 19 could also have been used, wherein analyzer 158 could be time shared with the referenced unit 234 and unit under test 235. In such a case, analyzer 226, signature table 229, and signature store 231 would be unnecessary.

Likewise, in case of need, rather than taking the output of analyzer 158 in Figure 19 directly to evaluator 171, a separate analyzer, signature table, and signature store as in Figure 21 could have been used.

Finally, Figure 22 illustrates the manner in which digital signature evaluation is accomplished. The same analogy follows in this figure insofar as forming a signature in store 168. However, whether the signal to be evaluated is audio or video, a player, termed device under test 238, outputs its signal to the A/D converter 237, and the digital form of the signal is stored in digital memory 233. If necessary, as was with the audio test tones during lead-in and lead-out, a recirculate control 240 feeds back the selected digital portion of the stored signal in a loop around fashion so as to output a continuous version of the stored signal to D/A converter 239. The analog version of the signal is then analyzed in analyzer 226, a signature table is established, and the analyzing results are stored in signature store 231 for later evaluation in comparator 171.

Table I is a printout of the results of "signature" evaluation during lead-in of a video disc. The selected parameters analyzed for the disc example used are listed in the lefthand column, and the "signature" comparison is shown in the two groups of three columns each, one group for audio channel 1 and another group for audio channel 2. The center column for each channel lists the value of the disc analysis measurement for each parameter, while the two values on either side of the center column indicate the "signature" limits set by limits setter 166 of Figure 20.

Table II shows similar evaluation comparison results for lead-out of the disc under test.

In like manner, Table III shows the video evaluation test results. Here, an additional column of information is shown, that of the actual tape analysis measurements from which upper and lower limits for the "signature" comparison were generated in limits setter block 166.

In this connection, the twelve segments of audio lead-in tones are retrieved at the rate of 30 segments per second (vertical frame rate), and instruments such as the Hewlett Packard 8903A Audio Analyzer are available which can measure a given parameter in typically 2.5 seconds or less. Since each segment of the lead-in test tones is used for more than one audio measurement, it is recirculated, as explained earlier, to

produce a continuous version thereof for the length of time necessary to perform all audio measurements by the analyzer before going on to retrieving and continuously looping the second test segment.

Since a large number of measurements may be made at any one test frame, and since the available analyzer can perform its analysis in 2.5 seconds or less, the maximum length of time necessary for the analyzer to make say as many as 11 measurements in test frame 1 is about 27.5 seconds. Accordingly, the recirculate control 99 shown in Figures 8 and 11 need only recirculate the tone segment for a maximum time of 27.5 seconds. Furthermore, and although the present invention is not limited to the specific tests listed above, to complete all 23 audio test measurements would require no more than 57.5 seconds. Conservatively then, the repetition rate at which the complete audio measurement cycle is repeated can be one cycle every minute. Then, since the longest active program test is the mono/non-mono check, and since this check can be completed each 65.5 seconds, it is clear that advantage can be taken of the AVQMS system to weed out defective discs in only a few minutes of recording/playing time. This concept can be carried out on video discs produced by the method illustrated in Figure 20 (as opposed to the direct read-after-write process) so as to be able to detect defective discs at any point along the process in only a few minutes. Of course, defects not contained close to the lead-in portion of the disc being evaluated will not show up instantaneously, but process defects which cause uniform parameter degradation throughout the video disc will be caught in the first couple of minutes of playing time. Furthermore, the speed at which information can be analyzed with the AVQMS eliminates much time taken in manually observing and/or manually taking measurements under prior techniques. Then again, all subjective evaluation of the disc is eliminated.

Only preferred embodiments of the invention have been described above. One skilled in the art, however, will recognize that where audio signal measurements were made in the manner of Figures 7-11, clearly video signal measurements, custom or standard, can be performed in a similar manner. Accordingly, the blocks labelled with "audio" designations merely need being renamed to illustrate the equivalent manner of multiplexing and subsequent analyzing of the lead-in and lead-out for video qualities (with appropriate changes of signal sources and timing figures, of course).

Similarly, the manner in which video parameter analysis and evaluation have been described herein could, with like analogy, apply to the analysis and evaluation of audio parameters.

TABLE I

AUDIO/VIDEO QUALITY MONITORING SYSTEM AUDIO DATA ANALYSIS FOR DISC

DISC ID—050148010

AUDIO TEST (LEAD OUT)		UNITS	LOWER TAPE1	CH1 DISC	UPPER TAPE1
TEST FRAME 1					
FREQUENCY	HZ	900.00	990	1100.00	
AC LEVEL	DBV	.18	.38	.53	
SINAD	DB	20.14	27.17	30.20	
SINAD WITH FILTER	DB	24.45	29.27	29.89	
TOTAL HARMONIC DISTORTION	%	2.16	4.4	2.64	
DC LEVEL	VOLTS	-.01	-.007	-.01	
PHASE ANGLE AT 1 KHZ	DEG	5.76	5.28	5.76	
TEST FRAMES 2 AND 3					
CROSSTALK					
CROSSTALK FREQUENCY	HZ	710.60	913	785.40	
CROSSTALK AC LEVEL	DB	-39.64	-36.56	-32.44	
TEST FRAMES 4 AND 7					
SIGNAL/NOISE RATIO	DB	40.70	37.41	49.74	
SIGNAL/NOISE RATIO WITH FILTER	DB	47.40	46.27	57.94	
TEST FRAMES 5 AND 6					
INTERMODULATION DISTORTION					
AMPLITUDE 7KHZ	DB	-22.22	-20.1	-18.18	
AMPLITUDE 7KHZ+60 HZ	DB	-43.34	-39.0	-35.46	
AMPLITUDE 7KHZ-60 HZ	DB	-42.90	-38.3	-35.10	

0 117 908

TABLE I (continued)

AUDIO/VIDEO QUALITY MONITORING SYSTEM
AUDIO DATA ANALYSIS FOR DISC

DISC ID—050148010

5	AUDIO TEST (LEAD OUT)	UNITS	LOWER TAPE2	CH2 DISC	UPPER TAPE2
	TEST FRAME 1				
10	FREQUENCY	HZ	900.00	991	1100.00
	AC LEVEL	DBV	-11.75	-7.79	-3.92
	SINAD	DB	21.03	26.42	31.55
	SINAD WITH FILTER	DB	25.73	28.79	31.45
	TOTAL HARMONIC DISTORTION	%	2.07	4.8	2.53
15	DC LEVEL	VOLTS	.02	.024	.03
	PHASE ANGLE AT 1 KHZ	DEG	2.03	2.03	2.03
	TEST FRAMES 2 AND 3				
20	CROSSTALK				
	CROSSTALK FREQUENCY	HZ	38.95	149	43.05
	CROSSTALK AC LEVEL	DB	-35.05	-34.62	-28.67
25	TEST FRAME 4 AND 7				
	SIGNAL/NOISE RATIO	DB	42.54	35.34	52.00
	SIGNAL/NOISE RATIO WITH FILTER	DB	50.00	47.59	61.12
30	TEST FRAMES 5 AND 6				
	INTERMODULATION DISTORTION				
	AMPLITUDE 7KHZ	DB	-23.21	-21.1	-18.99
35	AMPLITUDE 7KHZ+60 HZ	DB	-45.76	-41.4	-37.44
	AMPLITUDE 7KHZ-60 HZ	DB	-45.54	-40.2	-37.26

40

45

50

55

60

65

TABLE II

AUDIO/VIDEO QUALITY MONITORING SYSTEM
AUDIO DATA ANALYSIS FOR DISC

DISC ID—050148010

5	AUDIO TEST (LEAD IN)	UNITS	LOWER TAPE1	CH1 DISC	UPPER TAPE1
	TEST FRAME 1				
10	FREQUENCY	HZ	900.00	991	1100.00
	AC LEVEL	DBV	-12.21	-7.79	-4.07
	SINAD	DB	22.70	28.28	34.06
	SINAD WITH FILTER	DB	27.94	31.04	34.14
	TOTAL HARMONIC DISTORTION	%	1.80	3.8	2.20
15	DC LEVEL	VOLTS	-.01	-.008	-.01
	PHASE ANGLE AT 1 KHZ	DEG	2.61	1.57	2.61
	TEST FRAMES 2 AND 3				
20	CROSSTALK				
	CROSSTALK FREQUENCY	HZ	831.25	904	918.75
	CROSSTALK AC LEVEL	DB	-39.87	-28.36	-32.63
25	TEST FRAMES 4 AND 7				
	SIGNAL/NOISE RATIO	DB	41.43	38.85	50.63
	SIGNAL/NOISE RATIO WITH FILTER	DB	50.57	47.56	61.81
30	TEST FRAMES 5 AND 6				
	INTERMODULATION DISTORTION				
	AMPLITUDE 7KHZ	DB	-21.34	-19.4	-17.46
35	AMPLITUDE 7KHZ+60 HZ	DB	-52.14	-46.6	-42.66
	AMPLITUDE 7KHZ-60 HZ	DB	-47.63	-43.1	-38.97
40					
45					
50					
55					
60					
65					

0 117 908

TABLE II (continued)

AUDIO/VIDEO QUALITY MONITORING SYSTEM
AUDIO DATA ANALYSIS FOR DISC

DISC ID—050148010

5	AUDIO TEST	(LEAD IN)	UNITS	LOWER TAPE2	CH2 DISC	UPPER TAPE2
	TEST FRAME 1					
10	FREQUENCY		HZ	900.00	999	1100.00
	AC LEVEL		DBV	-12.11	-8.07	-4.04
	SINAD		DB	12.00	15.00	18.00
	SINAD WITH FILTER		DB	14.40	16.00	17.60
	TOTAL HARMONIC DISTORTION		%	2.43	18.1	2.97
15	DC LEVEL		VOLTS	.03	.029	.03
	PHASE ANGLE AT 1 KHZ		DEG	2.03	1.07	2.03
	TEST FRAMES 2 AND 3					
20	CROSSTALK					
	CROSSTALK FREQUENCY		HZ	38.95	41	43.05
	CROSSTALK AC LEVEL		DB	-39.02	-36.44	-31.92
25	TEST FRAMES 4 AND 7					
	SIGNAL/NOISE RATIO		DB	33.03	37.09	40.37
	SIGNAL/NOISE RATIO WITH FILTER		DB	44.02	48.18	53.80
30	TEST FRAMES 5 AND 6					
	INTERMODULATION DISTORTION					
	AMPLITUDE 7KHZ		DB	-23.65	-21.5	-19.35
35	AMPLITUDE 7KHZ+60 HZ		DB	-51.81	-46.0	-42.39
	AMPLITUDE 7KHZ-60 HZ		DB	-50.05	-45.0	-40.95

TABLE III

AUDIO/VIDEO QUALITY MONITORING SYSTEM
VIDEO DATA ANALYSIS FOR DISC

DISC ID—050148010001

STARTING
FRAME #

810 AV6 PIC LEVEL

COMPOSITE VITS

UNITS	TAPE LOWER	DISC ACTUAL	TAPE UPPER	TAPE ACTUAL	EXCEPTION
% FRAME	19.80	22.00	24.20	22.00	
IRE	95.95	100.00	106.05	101.00	
% BAR	-39.05	-35.00	-31.95	-35.50	
% BAR	10.70	24.40	32.10	21.40	
%	-39.00	-25.50	-13.00	-26.00	
%	2.70	16.10	8.10	5.40	***
DEG	3.50	25.89	10.50	7.00	***
%	12.10	38.80	36.30	24.20	***
DEG	4.59	17.30	5.61	5.10	***
%	5.75	17.90	17.25	11.50	***
NSEC	57.50	120.00	172.50	115.00	
%	2.16	2.70	3.24	2.70	
%	2.79	3.90	3.41	3.10	***
% KF	1.75	3.40	5.25	3.50	
% BAR	11.00	26.40	33.00	22.00	
% BAR	8.50	16.40	25.50	17.00	

BAR AMP

SYNC AMP

BURST AMP

CHRO-LUM GAIN

RELATIVE BURST GAIN

RELATIVE BURST PHASE

DIFF GAIN

DIFF PHASE

LUM NON-LINEAR DISTORTION

CHRO-LUM DELAY

LINE-TIME DIST

PULSE TO BAR RATIO

2T-PULSE RINGING

T-STEP RINGING LD

T-STEP RINGING TR

TABLE III (continued)

STARTING FRAME #	DISC ID—050148010001	COMBINATION VITS	UNITS	AUDIO/VIDEO QUALITY MONITORING SYSTEM VIDEO DATA ANALYSIS FOR DISC			
				TAPE LOWER	DISC ACTUAL	TAPE UPPER	TAPE ACTUAL
		WHITE FLAG AMP	IRE	88.83	99.90	108.57	98.70
		MB 500 KHZ	% FLAG	45.90	53.00	62.10	54.00
		MB 1.0 MHZ	% FLAG	39.95	49.00	54.05	47.00
		MB 2.0 MHZ	% FLAG	39.10	45.00	52.90	46.00
		MB 3.0 MHZ	% FLAG	35.70	42.00	48.30	42.00
		MB 3.58 MHZ	% FLAG	28.90	29.00	39.10	34.00
		MB 4.2 MHZ	% FLAG	18.70	21.00	25.30	22.00
		CHRO NON-LIN GAIN 20 IRE CHROMA	IRE	20.43	18.70	24.97	22.70
		CHRO NON-LIN GAIN 80 IRE CHROMA	IRE	38.43	39.20	46.97	42.70
		CHRO NON-LIN PHASE	DEG	95.15	77.00	285.45	190.30
		CHRO-LUM INTERMOD	IRE	.45	.90	1.35	.90

TABLE III (continued)

STARTING FRAME #	DISC ID—050148010001	AUDIO/VIDEO QUALITY MONITORING SYSTEM VIDEO DATA ANALYSIS FOR DISC				
		UNITS	TAPE LOWER	DISC ACTUAL	TAPE UPPER	TAPE ACTUAL
VIRS						EXCEPTION
VIRS SET UP LEVEL		IRE	3.55	6.80	10.65	7.10
VIRS BLANKING LEVEL		% CARR				
VIRS WHITE LEVEL		% CARR				
HORIZ BLANKING WIDTH		USEC	10.22	11.33	12.48	11.35
HORIZ SYNC WIDTH		USEC	4.29	4.69	5.23	4.76
HORIZ SYNC RISE TIME		NSEC	140.00	250.00	420.00	280.00
HORIZ SYNC FALL TIME		NSEC	24.64	180.00	73.92	49.28
SYNC SETUP		USEC	8.68	9.53	10.60	9.64
FRONT PORCH DURATION		USEC	1.28	1.49	1.56	1.42
SYNC TO BURST START DURATION		USEC	4.96	5.43	6.06	5.51
COLOR BURST WIDTH		CYCLES	8.10	8.50	9.90	9.00
MISCELLANEOUS						
VERTICAL BLANKING WIDTH FLD 1		LINES	16.92	18.79	20.66	18.79
VERTICAL BLANKING WIDTH FLD 2		LINES	16.92	18.79	20.66	18.79
EQUALIZING PULSE WIDTH		USEC	2.07	2.30	2.53	2.30
SERRATION WIDTH		USEC	4.14	4.65	5.06	4.60
SIGNAL TO NOISE-FRAME		DB	-63.45	-33.94	-21.15	-42.30
SIGNAL TO NOISE-FIELD 1		DB	-62.56	-33.97	-20.86	-41.71
SIGNAL TO NOISE-FIELD 2		DB	-63.90	-33.90	-21.30	-42.60



Claims

1. A method of analyzing the signal transfer characteristics of a signal processing unit comprising the steps of establishing an input signal of varying content, feeding said input signal to a signal processing unit and evaluating the output signal of said signal processing unit by comparison with said input signal, characterized by the steps of measuring selected parameters of selected parts of said input signal to produce an input signal measurement, storing the values of said input signal measurement to define a stored signature thereof, measuring the same parameters of parts of the output signal from said signal processing unit that correspond to said selected parts of said input signal to produce an output signal measurement, and comparing the values of said output signal measurement with said stored signature.
2. The method as claimed in Claim 1, characterized by, before said comparing step, the step of storing the values of said output signal measurement to define a stored signature thereof; and in that said comparing step includes comparing said stored input signal signature with said stored output signal signature.
3. The method as claimed in Claim 1, characterized by the steps of establishing prescribed tolerance limits for the values of said output signal measurement as deviation levels from the values of said input signal measurement; and in that said comparing step includes the step of comparing the results of the values of said output signal measurement with said stored signature to determine if the values of said output signal measurement are within said prescribed tolerance limits.
4. The method as claimed in Claim 1, characterized in that: said input signal measuring step includes performing a spectrum analysis of the input signal; and said output signal measuring step includes performing a spectrum analysis of the output signal from said signal processing unit.
5. The method as claimed in Claim 1, characterized by, before said storing step, the step of comparing the values of said input signal measurement of said selected parameters against fixed standard values.
6. The method as claimed in Claim 2, including the step of displaying the results of comparing said stored input and output signal signatures on a display device.
7. The method as claimed in Claim 1, wherein: said step of establishing an input signal comprises the step of providing a timed sequence of test signals; and each said measuring step comprises the step of sequentially measuring parameters of each test signal in said timed sequence.
8. The method as claimed in Claim 7, wherein the time interval between test signals in said timed sequence corresponds to a synchronization timing interval of a standard television signal.
9. The method as claimed in Claim 1, wherein said test signals are in analog format, and said storing step includes the steps of: (a) converting said analog test signals to digital test signals; (b) storing said digital test signals in a digital memory; (c) converting said digital test signals to analog test signals; and wherein said measurements are performed on the converted analog test signals.
10. Apparatus for analyzing the signal transfer characteristics of a signal processing unit comprising means (148) for establishing an input signal of varying content, means (158) for measuring selected parameters of selected parts of said input signal to produce an input signal measurement, and a comparator (171), characterized by: memory means (168) for storing the values of said input signal measurement to define a stored signature thereof; means (58, 118) for feeding said input signal to a signal processing unit; means (226) for measuring the same parameters of parts of the output signal from said signal processing unit that correspond to said selected parts of said input signal to produce an output signal measurement; said comparator (171) comparing the values of said output signal measurement with said stored signature.
11. The apparatus as claimed in Claim 10, characterized by a second memory means (231) for storing the values of said output signal measurement to define a stored signature thereof; and in that said comparator (171) includes means for comparing said stored input signal signature with said stored output signal signature.
12. The apparatus as claimed in Claim 10, characterized by means (166) for establishing prescribed tolerance limits for the values of said output signal measurement as deviation levels from the values of said input signal measurement; and in that said comparator (171) includes means for comparing the results of the values of said output signal measurement with said stored signature to determine if the values of said output signal measurement are within said prescribed tolerance limits.
13. The apparatus as claimed in Claim 10, characterized in that: said input signal measuring means (158) includes a spectrum analyzer (25, 28) for performing a spectrum analysis of the input signal fed to said processing unit, and for performing a spectrum analysis of the output signal from said signal processing unit.
14. The apparatus as claimed in Claim 10, characterized by means (160, 162) for comparing the values of said input signal measurement of said selected parameters against fixed standard values.
15. The apparatus as claimed in Claim 11, characterized by a display device, and means (15, 64) for displaying the results of comparing said stored input and output signal signatures on said display device.
16. The apparatus as claimed in Claim 10, characterized in that said means (148) for establishing an input signal comprises means (49) for providing a timed sequence of test signals; and said first-mentioned and said second measuring means (226, 158) comprise means (99-1, 35) for sequentially measuring parameters of each test signal in said timed sequence.



17. The apparatus as claimed in Claim 16, characterized in that the time interval between test signals in said timed sequence corresponds to a synchronization timing interval of a standard television signal.

18. The apparatus as claimed in Claim 10, characterized in that said memory means (168) is a digital memory; said test signals are in analog format; and said apparatus includes: means (37) for converting said analog test signals to digital test signals; means (33) for storing said digital test signals in said digital memory; means (39) for converting said digital test signals to analog test signals; and wherein said measurements are performed by said measuring means (158, 226) on the converted analog test signals.

10 Patentansprüche

1. Ein Verfahren zum Analysieren der Signalübertragungscharakteristiken einer Signalverarbeitungseinheit, in dem die Schritte enthalten sind: Aufbauen eines Eingangssignals mit sich änderndem Inhalt, Zuführen des genannten Eingangssignals zu einer Signalverarbeitungseinheit und
15 Bewerten des Ausgangssignals der genannten Signalverarbeitungseinheit durch Vergleich mit dem genannten Eingangssignal, gekennzeichnet durch die Schritte: Messen ausgewählter Parameter von ausgewählten Teilen des genannten Eingangssignals, um eine Eingangssignalmessung zu erzeugen, Speichern der Werte der genannten Eingangssignalmessung, um eine gespeicherte Signatur davon zu definieren, Messen der gleichen Parameter von Teilen des Ausgangssignals der genannten
20 Signalverarbeitungseinheit, die den genannten ausgewählten Teilen des genannten Eingangssignals entsprechen, um eine Ausgangssignalmessung zu erzeugen, und Vergleichen der Werte der genannten Ausgangssignalmessung mit der genannten gespeicherten Signatur.

2. Das Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß vor dem genannten Vergleichsschritt der Schritt des Speicherns der Werte der genannten Ausgangssignalmessung durchgeführt wird, um eine
25 gespeicherte Signatur davon zu definieren; und daß der genannte Vergleichsschritt den Vergleich der genannten gespeicherten Eingangssignalsignatur mit der genannten gespeicherten Ausgangssignalsignatur enthält.

3. Das Verfahren nach Anspruch 1, gekennzeichnet durch die Schritte der Festlegung vorgeschriebener Toleranzgrenzen für die Werte der genannten Ausgangssignalmessung als Abweichpegel von den Werten der genannten Eingangssignalmessung; und dadurch, daß der genannte Vergleichsschritt den Schritt des
30 Vergleichens der Ergebnisse der Werte der genannten Ausgangssignalmessung mit der genannten gespeicherten Signatur enthält, um festzustellen, ob die Werte der genannten Ausgangssignalmessung innerhalb der genannten vorgeschriebenen Toleranzgrenzen liegen.

4. Das Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß der genannte Eingangssignalmessschritt das Durchführen einer Spektralanalyse des Eingangssignals enthält und daß der genannte Ausgangssignalmessschritt das Durchführen einer Spektralanalyse des Ausgangssignals der genannten Signalverarbeitungseinheit enthält.

5. Das Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß vor dem genannten Speicherschritt der Schritt des Vergleichens der Werte der genannten Eingangssignalmessung der genannten
40 ausgewählten Parameter gegenüber festen Standardwerten durchgeführt wird.

6. Das Verfahren nach Anspruch 2, in dem der Schritt des Anzeigens der Ergebnisse des Vergleichens der genannten gespeicherten Eingangs- und Ausgangssignalsignaturen auf einem Anzeigegerät enthalten ist.

7. Das Verfahren nach Anspruch 1, bei dem der genannte Schritt des Aufbaus eines Eingangssignals den Schritt der Erzeugung einer zeitlichen Folge von Prüfsignalen enthält und jeder genannte Meßschritt den Schritt der sequentiellen Messung von Parametern jedes Prüfsignals in der genannten zeitlichen Folge enthält.

8. Das Verfahren nach Anspruch 7, bei dem das Zeitintervall zwischen den Prüfsignalen in der genannten zeitlichen Folge einem Synchronisierzeitintervall eines Standardfernsehsignals entspricht.

9. Das Verfahren nach Anspruch 1, bei dem die genannten Testsignale in analogem Format vorliegen und der genannte Speicherschritt die Schritte enthält: (a) Umsetzen der genannten analogen Prüfsignale in digitale Prüfsignale; (b) Speichern der genannten digitalen Prüfsignale in einem Digitalspeicher; (c) Umsetzen der genannten Digitalprüfsignale in analoge Prüfsignale; und bei dem die genannten Messungen an den umgesetzten analogen Prüfsignalen durchgeführt werden.

10. Gerät zum Analysieren der Signalübertragungscharakteristiken einer Signalverarbeitungseinheit, in dem enthalten sind: Vorrichtungen (148) zum Aufbauen eines Eingangssignals mit sich änderndem Inhalt, Vorrichtungen (158) zur Messung ausgewählter Parameter von ausgewählten Teilen des genannten Eingangssignals, um eine Eingangssignalmessung zu erzeugen, und ein Vergleichs- (171), gekennzeichnet durch: Speichervorrichtungen (168) zur Speicherung der Werte der genannten Eingangssignalmessung, um eine gespeicherte Signatur davon zu definieren; Vorrichtungen (58, 118) zum Zuführen des genannten Eingangssignals zu einer Signalverarbeitungseinheit; Vorrichtungen (226) zum Messen der gleichen Parameter von Teilen des Ausgangssignals aus der genannten Signalverarbeitungseinheit, die den genannten ausgewählten Teilen des genannten Eingangssignals entsprechen, um eine
60 Ausgangssignalmessung zu erzeugen; wobei der genannte Vergleichs- (171) die Werte der genannten Ausgangssignalmessung mit der genannten gespeicherten Signatur vergleicht.



11. Das Gerät nach Anspruch 10, gekennzeichnet durch zweite Speichervorrichtungen (231) zum Speichern der Werte der genannten Ausgangssignalmessung, um eine gespeicherte Signatur davon zu definieren; und daß der genannte Vergleicher (171) Vorrichtungen enthält, mit denen die genannte gespeicherte Eingangssignalsignatur mit der genannten gespeicherten Ausgangssignalsignatur verglichen wird.

12. Das Gerät nach Anspruch 10, gekennzeichnet durch Vorrichtungen (166) zur Festlegung vorgeschriebener Toleranzgrenzen für die Werte der genannten Ausgangssignalmessung als Abweichpegel von den Werten der genannten Eingangssignalmessung; und dadurch, daß der genannte Vergleicher (171) Vorrichtungen enthält, mit denen die Ergebnisse der Werte der genannten Ausgangssignalmessung mit der genannten gespeicherten Signatur verglichen werden, um festzustellen, ob die Werte der genannten Ausgangssignalmessung innerhalb der genannten vorgeschriebenen Toleranzgrenzen liegen.

13. Das Gerät nach Anspruch 10, dadurch gekennzeichnet, daß die genannten Vorrichtungen (158) zur Eingangssignalmessung einen Spektralanalysator (25, 28) enthalten, der eine Spektralanalyse des der genannten Verarbeitungseinheit zugeführten Eingangssignals durchführt und der eine Spektralanalyse des Ausgangssignals aus der genannten Signalverarbeitungseinheit durchführt.

14. Das Gerät nach Anspruch 10, gekennzeichnet durch Vorrichtungen (160, 162) zum Vergleichen der Werte der genannten Eingangssignalmessung der genannten ausgewählten Parameter gegenüber festen Standardwerten.

15. Das Gerät nach Anspruch 11, gekennzeichnet durch ein Anzeigegerät und Vorrichtungen (15, 64) zur Anzeige der Ergebnisse des Vergleichs der genannten gespeicherten Eingangs- und Ausgangssignalsignaturen auf dem genannten Anzeigegerät.

16. Das Gerät nach Anspruch 10, dadurch gekennzeichnet, daß die genannten Vorrichtungen (148) zum Aufbau eines Eingangssignals Vorrichtungen (49) enthalten, mit denen eine zeitliche Folge von Prüfsignalen erzeugt wird; und daß die genannten an erster Stelle erwähnten und die genannten an zweiter Stelle erwähnten Meßvorrichtungen (226, 158) Vorrichtungen (99-1, 35) enthalten, mit denen sequentiell Parameter an jedem Prüfsignal in der genannten zeitlichen Folge gemessen werden.

17. Das Gerät nach Anspruch 16, dadurch gekennzeichnet, daß das Zeitintervall zwischen den Prüfsignalen in der genannten zeitlichen Folge einem Synchronisierzeitintervall eines Standardfernsehsignals entspricht.

18. Das Gerät nach Anspruch 10, dadurch gekennzeichnet, daß die genannten Speichervorrichtungen (168) einen Digitalspeicher darstellen; daß die genannten Prüfsignale in analogem Format vorliegen; und daß das genannte Gerät enthält: Vorrichtungen (37) zum Umsetzen der genannten analogen Prüfsignale in digitale Prüfsignale; Vorrichtungen (33) zum Speichern der genannten digitalen Prüfsignale in dem genannten Digitalspeicher; Vorrichtungen (39) zum Umsetzen der genannten digitalen Prüfsignale in analoge Prüfsignale; und worin die genannten Messungen durch die genannten Meßvorrichtungen (158, 226) an den umgesetzten analogen Prüfsignalen durchgeführt werden.

Revendications

1. Procédé d'analyse des caractéristiques de transfert de signaux d'une unité de traitement de signaux comprenant les étapes d'établir un signal d'entrée d'un contenu variable, d'appliquer ledit signal d'entrée à une unité de traitement de signaux et d'évaluer le signal à la sortie de ladite unité de traitement de signaux par comparaison avec ledit signal d'entrée, caractérisé par les étapes de mesurer des paramètres choisis de parties choisies dudit signal d'entrée pour produire une mesure du signal d'entrée, de stocker les valeurs de ladite mesure du signal d'entrée pour définir sa signature stockée, de mesurer les mêmes paramètres de parties du signal de sortie de ladite unité de traitement de signaux qui correspondent auxdites parties choisies dudit signal d'entrée pour produire une mesure du signal de sortie et de comparer les valeurs de ladite mesure du signal de sortie à ladite signature stockée.

2. Procédé selon la revendication 1, caractérisé par, avant ladite étape de comparaison, l'étape de stocker les valeurs de la mesure du signal de sortie pour définir sa signature stockée; et en ce que ladite étape de comparaison consiste à comparer ladite signature stockée de signaux d'entrée à ladite signature stockée de signaux de sortie.

3. Procédé selon la revendication 1, caractérisé par les étapes d'établir des limites prescrites de tolérance pour les valeurs de ladite mesure du signal de sortie en tant que niveaux d'écart des valeurs de ladite mesure du signal d'entrée; et en ce que ladite étape de comparaison comprend l'étape de comparer les résultats des valeurs de ladite mesure du signal de sortie à ladite signature stockée pour déterminer si les valeurs de ladite mesure du signal de sortie sont dans lesdites limites prescrites de tolérance.

4. Procédé selon la revendication 1, caractérisé en ce que ladite étape de mesurer le signal d'entrée consiste à accomplir une analyse du spectre dudit signal d'entrée; et ladite étape de mesure du signal de sortie consiste à accomplir une analyse du spectre du signal à la sortie de ladite unité de traitement de signaux.

5. Procédé selon la revendication 1, caractérisé par, avant ladite étape de stockage, l'étape de comparer les valeurs de la mesure du signal d'entrée desdits paramètres choisis à des valeurs standards fixes.



6. Procédé selon la revendication 2, comprenant l'étape de visualiser les résultats de la comparaison desdites signatures stockées de signaux d'entrée et de sortie sur un dispositif de visualisation.

7. Procédé selon la revendication 1, où ladite étape d'établir un signal d'entrée comprend l'étape de produire une séquence temporisée de signaux de test; et chaque étape de mesure comprend l'étape de mesurer séquentiellement des paramètres de chaque signal de test dans ladite séquence temporisée.

8. Procédé selon la revendication 7, où l'intervalle de temps entre des signaux de test dans ladite séquence temporisée correspond à un intervalle de temporisation de synchronisation d'un signal standard de télévision.

9. Procédé selon la revendication 1, où lesdits signaux de test sont sous format analogique et ladite étape de stockage comprend les étapes de: (a) convertir lesdits signaux analogiques de test en signaux numériques de test; (b) stocker lesdits signaux numériques de test dans une mémoire numérique; (c) convertir lesdits signaux numériques de test en signaux analogiques de test; et où lesdites mesures sont accomplies sur les signaux analogiques convertis de test.

10. Appareil pour analyser les caractéristiques de transfert de signaux d'une unité de traitement de signaux comprenant un moyen (148) pour établir un signal d'entrée d'un contenu variable, un moyen (158) pour mesurer des paramètres choisis de parties choisies dudit signal d'entrée pour produire une mesure du signal d'entrée, et un comparateur (171), caractérisé par un moyen formant mémoire (168) pour stocker les valeurs de la mesure du signal d'entrée pour définir sa signature stockée; un moyen (58, 118) pour appliquer ledit signal d'entrée à une unité de traitement de signaux; un moyen (226) pour mesurer les mêmes paramètres de parties du signal à la sortie de ladite unité de traitement de signaux qui correspondent auxdites parties choisies dudit signal d'entrée pour produire une mesure du signal de sortie; ledit comparateur (171) comparant les valeurs de la mesure du signal de sortie à ladite signature stockée.

11. Appareil selon la revendication 10, caractérisé par un second moyen formant mémoire (231) pour stocker les valeurs de la mesure du signal de sortie pour définir sa signature stockée; et en ce que ledit comparateur (171) contient un moyen pour comparer ladite signature stockée du signal d'entrée à ladite signature stockée du signal de sortie.

12. Appareil selon la revendication 10, caractérisé par un moyen (166) pour établir des limites prescrites de tolérance pour les valeurs de la mesure du signal de sortie sous la forme de niveaux d'écart par rapport aux valeurs de la mesure du signal d'entrée; et en ce que ledit comparateur (171) comprend un moyen pour comparer les résultats des valeurs de la mesure du signal de sortie à ladite signature stockée pour déterminer si les valeurs de la mesure du signal de sortie sont dans les limites prescrites de tolérance.

13. Appareil selon la revendication 10, caractérisé en ce que: ledit moyen de mesure du signal d'entrée (158) comprend un analyseur de spectre (25, 28) pour accomplir une analyse du spectre du signal d'entrée appliqué à ladite unité de traitement et pour accomplir une analyse du spectre du signal à la sortie de ladite unité de traitement de signaux.

14. Appareil selon la revendication 10, caractérisé par un moyen (160, 162) pour comparer les valeurs de la mesure du signal d'entrée de paramètres choisis à des valeurs standards fixes.

15. Appareil selon la revendication 11, caractérisé par un dispositif de visualisation, et un moyen (15, 64) pour visualiser les résultats de la comparaison des signatures stockées des signaux d'entrée et de sortie sur ledit dispositif de visualisation.

16. Appareil selon la revendication 10, caractérisé en ce que ledit moyen (48) pour établir un signal d'entrée comprend un moyen (49) pour produire une séquence temporisée de signaux de test; et ledit premier moyen mentionné de mesure et ledit second moyen de mesure (226, 158) comprennent des moyens (99-1, 35) pour mesurer séquentiellement des paramètres de chaque signal de test dans ladite séquence temporisée.

17. Appareil selon la revendication 16, caractérisé en ce que l'intervalle de temps entre des signaux de test dans ladite séquence temporisée correspond à un intervalle de temporisation de synchronisation d'un signal standard de télévision.

18. Appareil selon la revendication 10, caractérisé en ce que ledit moyen formant mémoire (168) est une mémoire numérique; lesdits signaux de test sont sous format analogique; et ledit appareil comprend: un moyen (37) pour convertir lesdits signaux analogiques de test en signaux numériques de test; un moyen (33) pour stocker lesdits signaux numériques de test dans ladite mémoire numérique; un moyen (39) pour convertir lesdits signaux numériques de test en signaux analogiques de test; et où lesdites mesures sont accomplies par ledit moyen de mesure (158, 226) sur les signaux analogiques convertis de test.