SG 9701580-4

RTMP COPY

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G06F 13/00 — A1

(11) International Publication Number: WO 96/13776

(43) International Publication Date: 9 May 1996 (09.05.96)

(21) International Application Number: PCT/US95/14243

(22) International Filing Date: 31 October 1995 (31.10.95)

(30) Priority Data:
08/332,573 31 October 1994 (31.10.94) US

(71) Applicant: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).


(72) Inventors: MORRISS, Jeff, Charles; 900 Elsie Mae Drive, Boulder Creek, CA 95006 (US). KNOLL, Shaun; 1006 N.W. 18th Avenue, Portland, OR 97209 (US). NIZAR, Puthiya, Kottal; 1762 Darwin Way, El Dorado Hills, CA 95762 (US). HASLAM, Richard, M.; 3057 S.E. Willow Drive, Hillsboro, OR 97123 (US). BHATT, Ajay, V.; 1254 Downieville Drive, El Dorado Hills, CA 95762 (US). CADAMBI, Sudarshan, Bala; 14905 N.W. Dominion Drive, Portland, OR 97229 (US).

(74) Agents: MALLIE, Michael, J. et al.; Blakely, Sokoloff, Taylor & Zafman, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025-1026 (US).

(81) Designated States: AL, AM (Utility model), AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).


Published
With international search report.

(54) Title: M & A FOR EXCHANGING DATA, STATUS, AND COMMANDS OVER A HIERARCHICAL SERIAL BUS ASSEMBLY USING COMMUNICATION PACKETS



(57) Abstract

Logic is provided for a bus controller (14), a number of 1:n bus signal distributors (18), and a number of bus interfaces (22) of a hierarchical bus assembly (26) for conducting data communication transactions between bus agents interconnected to the hierarchical bus assembly (26). The hierarchical bus assembly (26) is used to serially interface a number of isochronous and asynchronous peripherals (16c-f) to the system unit (12) of a computer system (10). These serial bus elements implement a number of elemental packets and a number of transaction protocols, employing a master/slave model of transaction flow control. Data communication transactions are conducted using the elemental packets and in accordance with the transaction protocols. In some embodiments, these serial bus elements are also used to conduct connection management transactions between the serial bus elements. The connection management transactions are conducted in like manner as the data communication transactions.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	**GB**	United Kingdom	**MR**	Mauritania
AU	Australia	**GE**	Georgia	**MW**	Malawi
BB	Barbados	**GN**	Guinea	**NE**	Niger
BE	Belgium	**GR**	Greece	**NL**	Netherlands
BF	Burkina Faso	**HU**	Hungary	**NO**	Norway
BG	Bulgaria	**IE**	Ireland	**NZ**	New Zealand
BJ	Benin	**IT**	Italy	**PL**	Poland
BR	Brazil	**JP**	Japan	**PT**	Portugal
BY	Belarus	**KE**	Kenya	**RO**	Romania
CA	Canada	**KG**	Kyrgystan	**RU**	Russian Federation
CF	Central African Republic	**KP**	Democratic People's Republic of Korea	**SD**	Sudan
CG	Congo			**SE**	Sweden
CH	Switzerland	**KR**	Republic of Korea	**SI**	Slovenia
CI	Côte d'Ivoire	**KZ**	Kazakhstan	**SK**	Slovakia
CM	Cameroon	**LI**	Liechtenstein	**SN**	Senegal
CN	China	**LK**	Sri Lanka	**TD**	Chad
CS	Czechoslovakia	**LU**	Luxembourg	**TG**	Togo
CZ	Czech Republic	**LV**	Latvia	**TJ**	Tajikistan
DE	Germany	**MC**	Monaco	**TT**	Trinidad and Tobago
DK	Denmark	**MD**	Republic of Moldova	**UA**	Ukraine
ES	Spain	**MG**	Madagascar	**US**	United States of America
FI	Finland	**ML**	Mali	**UZ**	Uzbekistan
FR	France	**MN**	Mongolia	**VN**	Viet Nam
GA	Gabon				

9701580-4

M&A For Exchanging Data, Status And Commands Over An Hierarchical Serial Bus Assembly Using Communication Packets

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to the field of computer systems. More specifically, the present invention relates to serial buses for connecting peripherals to the system units of computer systems, including the associated controllers and interfaces.

2. Background Information

A number of interrelated considerations is making it desirable to have a single, relatively fast, bi-directional, isochronous, low-cost, and dynamically configurable serial bus for simultaneously connecting isochronous as well as asynchronous peripherals to the system unit of a desktop computer system. Isochronous peripherals are peripherals that generate real time natural data such as voice, motion video, and the like. These interrelated considerations include:

Connection of the Telephone to the Desktop Computer

It is expected that the merging of computing and communication will be the basis of the next generation of productivity applications on desktop computers. The movement of machine oriented and human oriented data types from one location or environment to another depends on ubiquitous and cheap connectivity. Unfortunately, the computing and communication industries have evolved independently. As a result, a wide range of desktop computer and telephone interconnects have to be supported.

Ease of Use

The lack of flexibility in reconfiguring desktop computers has been acknowledged as its Achilles heel to it's further development. The combination of user friendly graphical interfaces and the hardware and software mechanisms associated with the new generation of system bus architectures have made desktop computers less confrontational and easier to reconfigure. However, from the enduser point of view, the desktop computer's I/O interfaces such as serial/parallel ports, keyboard/mouse/joystick interfaces, still lack the attributes of plug and play or too limiting in terms of the type of I/O devices that can be live attached/detached.

Port Expansion

The addition of external peripherals to desktop computers continues to be constrained by port availability. The lack of a bi-directional, low-cost, low to mid speed peripheral bus has held back the proliferation of peripherals like telephone/fax/modem adapters, answering machines, scanners, personal digital assistants (PDA), keyboards, mouses, etc. Existing interconnects are optimized for one or two point products. As each new function or capability is added to the desktop computer, typically a new interface has been defined to address this need.

In other words, this desired serial bus is expected to provide low cost simultaneous connectivity for the relatively low speed 10-100 kbps interactive devices such as keyboard, mouse, stylus, game peripherals, virtual reality peripherals, and monitors, as well as the moderate speed 500 - 5000 kbps isochronous devices such as ISDN, PBX, POTS, and other audio devices. A multiplicity of both types of devices are expected to be connected and active at the same time, and yet the latter type of devices are provided with guaranteed latencies and bandwidths. Furthermore, the devices are expected to be hot attached and detached, with the serial interface being able to dynamically reconfigure itself without interrupting operation of the desktop computer system.

There are several technologies that are commonly considered to be serial buses for connecting peripherals to system units of computer systems. Each of these buses is designed to handle a specific range of communications between system units and peripherals. Particular examples of these buses include:

Apple® Desktop Bus (ADB): ADB is a proprietary bus of Apple Computer Inc. It is a minimalist serial bus that provides a simple read/write protocol to up to 16 devices. Only basic functions are required of the controller and interface hardware. Thus, the implementation cost is expected to be low. However, ADB supports data rates only up to 90 kbps, just enough to communicate with asynchronous desktop devices such as keyboards and mouses. It is not capable of simultaneously supporting the moderate speed isochronous devices discussed earlier.

Access.bus (A.b): A.b is developed by the Access.bus Industry Group. It is based on the I^2C technology of Philips Corporation and a software model of Digital Equipment Corporation (DEC). A.b is also designed primarily for asynchronous devices such as keyboards and mouses. However A.b is generally considered to be more versatile than ADB. A.b's protocol has well defined specifications for dynamic attach, arbitration, data packets, configuration and software interface. Moderate amount of functions are required of the controller and interface hardware. Thus, the implementation cost is only marginally competitive for the desired desktop application. While addressing is provided for up to 127 devices, the practical loading is limited by cable lengths and power distribution considerations. Revision 2.2 specifies the bus for 100 kbps operation, but the technology has headroom to go up to 400 kbps using the same separate clock and data wires. However, at 400 kbps, A.b still falls short in meeting the requirements of the moderate speed isochronous devices.

IEEE's P1394 Serial Bus Specification (aka FireWire): FireWire is a high performance serial bus. It is designed primarily for hard disk and video peripherals, which may require bus bandwidth in excess of 100 Mbps. It's protocol supports both isochronous and asynchronous transfers over the same set of 4 signal wires, broken up as differential pairs of clock and data signals. Thus, it is capable of simultaneously meeting the requirements of low speed interactive as well as moderate speed isochronous devices. However, elaborate functions are required of the controller and interface hardware, rendering FireWire to be non-price competitive for the desired desktop application. Moreover, the first generation of devices, based on FireWire's specification, are only just becoming available in the market.

The Concentration Highway Interface (CHI): CHI is developed by American Telephone & Telegraph Corporation (AT&T) for terminals and digital switches. It is a full duplex time division multiplexed serial interface for digitized voice transfer in a communication system. The protocol consists of a number of fixed time slots that can carry voice data and control information. The current specification supports data transfer rates up to 4,096 Mbps. The CHI bus has 4 signal wires: Clock, Framing, Receive Data, and Transmit Data. Both, the Framing and the Clock signals are generated centrally (i.e. PBX switch). Thus, it is also capable of simultaneously meeting the requirements of low speed interactive as well as the moderate speed isochronous devices. Similar to FireWire, elaborate functions are also required of the controller and interface hardware. As a result, CHI is also non-price competitive for the desired desktop application.

As will be disclosed in more detail below, the present invention provides the desired serial bus assembly, including its associated controller, bridging connectors and interfaces, that advantageously overcomes the limitations of the prior art serial buses in a novel manner.

SUMMARY OF THE INVENTION

The present invention includes circuitry and complementary logic provided to a bus controller, a number of 1:n bus signal distributors, and a number of bus interfaces of an hierarchical bus assembly for conducting data communication transactions between bus agents interconnected to the hierarchical bus assembly. The hierarchical serial bus assembly is used to serially interface a number of isochronous and asynchronous peripherals to the system unit of a computer system. These circuitry and complementary logic of the serial bus elements implement a number of elemental packets and a number of transaction protocols, employing a master/slave model of transaction flow control. Data communication transactions are conducted using the elemental packets and in accordance to the transaction protocols. In some embodiments, these circuitry and complementary logic of the serial bus elements are also used to conduct connection management transactions between the serial bus elements. The connection management transactions are conducted in like manner as the data communication transactions.

Typically, the bus controller is disposed in the system unit, and interconnected to a number of 1:n bus signal distributors and a number of bus interfaces. The bus interfaces are disposed in the connecting peripherals, one bus interface per connecting peripheral. The peripherals, through their bus interfaces, are generally connected to the system unit, through the bus controller, using one or more of the bus signal distributors. A bus interface is always a termination point. Only a bus signal distributor may have one or more bus signal distributor(s) and/or bus interface(s) connected upstream to it. Together, the system unit, the serial bus elements, and the peripherals form an hierarchy of interconnected devices.

A connecting peripheral may be an isochronous or an asynchronous peripheral. Typically, the isochronous peripherals

operate with data rates in the range of 500 - 5000 kbps, whereas the asynchronous peripherals operate with data rates in the range of 10 - 100 kbps. Furthermore, a connecting peripheral may be a multi-function peripheral, i.e. multiple functions being mapped to a single bus connection point serviced by a single bus interface.

The elemental packets include a token packet, a handshake packet, and a data packet. Each packet includes a packet identifier identifying the packet type and nature of the packet. Preferably, each packet further includes a leading sync field to aid the interconnected devices in receiving the packet. The transaction protocols include protocols for transactions between the system unit and any one of the functions of the interconnected peripherals, between any two functions of the interconnected peripherals, and between the system unit and any one of the interconnected devices. The elemental packets and transaction protocols are adaptable for data communication as well as connection management transactions employing the master/slave model of flow control.

In embodiments where the various devices are physically interconnected together using low cost two signal wire cables, and electrical signals are propagated between the interconnected devices over the two signal wires in a differential manner, preferably the beginning and the end of a packet is denoted by the "fault" condition of zero difference. In embodiments where the interconnected devices jointly implement geographical addressing for the devices and logical addressing for the functions of the interconnected peripherals, the elemental packets and the transaction protocols further support transactions conducted in either the geographical address space or the logical address space.

BRIEF DESCRIPTION OF DRAWINGS

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote similar elements, and in which:

Figure 1 illustrates an exemplary computer system incorporating the serial bus teachings of the present invention;

Figures 2 illustrates one embodiment of the serial bus assembly of **Figure 1** in further detail;

Figure 3 illustrates a master/slave model of flow control employed by the present invention for serially interfacing the interconnected peripherals to the system unit and controlling transaction flows;

Figure 4 illustrates a frame based polling schedule of the present invention implemented by some embodiments for polling the slave "devices";

Figure 5 illustrates geographical and logical addressing of the present invention implemented by some embodiments for addressing serial bus elements and functions of bus agents;

Figure 6 illustrates the essential elements of communication packets of the present invention implemented by some embodiments for conducting transactions employing the master/slave model of flow control;

Figure 7 illustrates one embodiment of the cables physically connecting the serial bus elements under the present invention;

Figures 8-9 illustrate one embodiment of the bus controller of the present invention including its associated software;

Figures 10-11 illustrate one embodiment of the 1:n bus signal distributor of the present invention including its port circuitry;

Figures 12-13 illustrate one embodiment of the bus interface of the present invention including its connector circuitry;

Figure 14a - 14b illustrate one embodiment of the elemental packets of the present invention;

Figure 15 illustrates one embodiment of the packet identifiers of the elemental packets including the packet types they identify;

Figures 16a - 16c and **17a - 17d** illustrate one embodiment of the packet fields of the packet identifiers and their corresponding meanings;

Figures 18a - 18c illustrate one embodiment of connection management transaction protocols;

Figure 19a - 19k illustrate one embodiment of data communication transaction protocols;

Figure 20 illustrates one embodiment of a state machine provided to the bus controller for implementing the above described protocols;

Figure 21 illustrates one embodiment of a state machine provided to a bus signal distributor for implementing the above described protocols;

Figure 22 illustrates one embodiment of a state machine provided to a bus interface for implementing the above described protocols.

DETAILED DESCRIPTION

In the following description for purposes of explanation, specific numbers, materials and configurations are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without the specific details. In other instances, well known systems are shown in diagrammatic or block diagram form in order not to obscure the present invention.

Hierarchical Serial Bus Assembly for Serially Interfacing Isochronous and Asynchronous Peripherals to a System Unit of a Computer System

Referring now to **Figure 1**, a block diagram illustrating an exemplary computer system incorporating the serial bus teachings of the present invention is shown. Exemplary computer system **10** comprises system unit **12** having serial bus controller **14** of the present invention, 1:n bus signal distributors **18** of the present invention, each having n+1 ports **24**, and peripherals **16** having bus interfaces **22** of the present invention. Peripherals **16** are coupled to bus controller **14** of system unit **12** through 1:n bus signal distributors **18** and preferably cables **20**. Collectively, bus controller **14**, bus signal distributors **18**, bus interfaces **22**, and cables **20** form a serial bus assembly **26** interconnecting bus agents, i.e. system unit **12** and peripherals **16** to each other.

Cables **20** are preferably low cost two signal wires cables **48** and **50** (as illustrated in **Fig. 7**). However, cable **20** are capable of supporting data transfer rates up to 5 Mbps. Furthermore, when such low cost cables **20** are employed, electrical signals are preferably propagated over the two signal wires **48** and **50** between the interconnected devices **14**, **18** and **22** in a differential manner. For examples, a negative voltage differential represents a 1-bit and a positive voltage differential represents a 0-bit. Electrical signals are

preferably also used to signal a number of information. For further description of electrical signalling, see US Patent Application, serial number 08/332,337, entitled Method And Apparatus For Serial Bus Elements Of An Hierarchical Serial Bus To Electrically Represent Data And Control States To Each Other, which is hereby fully incorporated by reference.

Except for bus controller **14**, system unit **12** is intended to represent a broad category of system units of computer systems whose constitutions and functions are well known, and will not be otherwise further described. Similarly, except for bus interfaces **22**, peripherals **16** are intended to represent a broad category of desktop peripherals, such as keyboards, mouses, monitors, speakers, microphone, telephones, whose constitutions and functions are also well known, and will not be otherwise further described either. Bus controller **14**, bus signal distributors **18** and bus interfaces **22** will be described in more detail below with additional references to the remaining figures.

Figure 2 illustrates one embodiment of the serial bus assembly of **Figure 1** in further detail. For this embodiment, serial bus assembly **26'** includes serial bus controller **14**, standalone 1:n bus signal distributor **18a**, integrated 1:n bus signal distributor **18b**, and bus interfaces **22a - 22f**. The serial bus assembly **26'** interconnects bus agents telephone **16a**, compound keyboard **16b** including keyboard, pen and mouse functions, monitor circuitry **16c** of monitor **28**, speakers **16d-16e** and microphone **16f** to system unit **12**. Together, the system unit **12**, the serial bus elements **14**, **18a-18b** and **22a-22f**, and the interconnected peripherals **16a-16f** form an hierarchy of interconnected devices.

Under the present invention, a bus interface **22a - 22f** is always a termination point. Only a bus signal distributor, e.g. **18a**, may have one or more bus signal distributors, e.g. **18b**, and/or one or more bus interfaces, e.g. **22a**, coupled upstream to it. For the purpose of this

disclosure, upstream means "towards the bus controller". Thus, except for the degenerate case where the serial bus assembly **26** has only one connecting peripheral **16**, typically it is a bus signal distributor, such as **18a**, that is connected upstream to the bus controller **14**.

Furthermore, under the present invention, a connecting peripheral may be an isochronous peripheral, such as telephone **16a**, speakers **16d-16e**, and microphone **16f**, or asynchronous peripherals, such as compound keyboard **16b** and monitor **16c**. The isochronous peripherals may operate with a data transfer rate as high as 5 Mbps, while the asynchronous peripherals may operate with a data transfer rate as high as 100 kbps. Furthermore, a connecting peripheral **16a - 16f** may be a multiple function peripheral, i.e. multiple functions mapping to a single bus connection point serviced by a bus interface, e.g. **22b**. Similarly, although not shown, the system unit **12** may support multiple clients.

Figure 3 illustrates a master/slave model of flow control employed by the present invention for serially interfacing the interconnected peripherals to the system unit and controlling transaction flow. As illustrated, the bus controller **14**, the signal bus distributors **18**, and the bus interfaces **22** cooperate to implement the master/slave model of flow control. The bus controller **14** serves as the master, and the signal bus distributors **18** as well as the bus interfaces **22** behave as slave devices to the bus controller **14**.

Under the master/slave model, the bus controller **14** provides flow control for all data communication transactions between the bus agents at their respective operating speeds. The bus interfaces **22** engage in data communication transactions on behalf of the functions of the peripherals **16**. However, the bus interfaces **22** accept or transmit data only if they have been authorized or instructed (aka "polled") to do so by the bus controller **14**. The bus signal distributors **18** serve strictly as signal distributors. They are merely transparent

conduits when data communication transactions are conducted by the bus controller **14** and the bus interfaces **22** on behalf of the bus agents. Thus, the bus signal distributors **18** never actively participate in data communication transactions, accept data or respond with data.

The bus controller **14** systematically polls the functions of the interconnected peripherals **16** through their bus interfaces **22** for data communication transactions in accordance to a polling schedule which guarantees latencies and bandwidths to the isochronous functions of the interconnected peripherals **16**. Polling of the isochronous functions of the interconnected peripherals **16** for data communication transactions are prioritized over for all other polling and as frequent as they are necessary to meet the guaranty. Polling of the asynchronous functions of the interconnected peripherals **16** through their bus interfaces **22** for data communication transactions are scheduled around the polling of the isochronous functions of the interconnected peripherals **16** for data communication transactions. Preferably, the polling schedule is dynamically adapted to the interconnected peripherals **16** actually present.

In some embodiments, the bus controller **14**, the bus signal distributors **18** and the bus interfaces **22** further engage in connection management transactions employing the same master/slave model for flow control. Similarly, the bus controller **14** provides flow control for conducting the connection management transactions at the serial bus elements' respective operating speeds. The bus signal distributors **18** and the bus interfaces **22** respond to the connection management transactions, replying with control/status information as appropriate. The bus controller **14**, during operation, polls the bus signal distributors **18** and the bus interfaces **22** for such transactions. Polling of the bus signal distributors **18** and the bus interfaces **22** for connection management transactions are also scheduled around polling of the isochronous functions of the interconnected peripherals **16** for data communication transactions. Preferably, the expanded

polling schedule is also dynamically adapted to the serial bus elements actually present.

Figure 4 illustrate a frame based polling scheduling of the present invention implemented by some embodiments for conducting the various transactions employing the master/slave model of flow control. As illustrated, the polling schedule **30**, also referred to a super frame, comprises of a number of sub-schedules **32**, also referred to as soft frames. An isochronous function **34a** or **34b** of an interconnected peripheral **16** is polled as frequent as it is necessary in one or more soft frames **32** of the super frame **30** to guarantee its latency and bandwidth. However, an asynchronous function **36a** or **36b** is polled only once in one soft frame **32** of the super frame **30** for data communication transaction. Similarly, an interconnected device **38a** or **38b** is also polled only once in one soft frame **32** of the super frame **30** for connection management transaction.

Preferably, all isochronous functions **34a - 34b** are polled within a first percentage portion (P1) of a soft frame **32** to ensure the latency and bandwidth guaranties are met. Isochronous functions that cannot be accommodated within P1 are preferably rejected for insufficient capacity. The upper delimiter (M1) of P1 is also referred to as the isochronous watermark. Similarly, all polling are preferably performed within a second percentage portion (P2) of a soft frame **32** to ensure reliability of operation. Multiple soft frames **32** are employed if necessary to accommodate all asynchronous function and serial bus element polling. The upper delimiter (M2) of P2 is also referred to as the frame watermark.

Various manners in which such frame based polling schedule may be dynamically generated and updated, are described in the copending application, serial number 08/331,727, entitled Method And Apparatus For Dynamically Generating And Maintaining Frame

Based Polling Schedules That Guaranty Latencies And Bandwidths To Isochronous Functions, which is hereby fully incorporated by reference.

Figure 5 illustrates geographical and logical addressing of the present invention implemented by some embodiments for addressing the serial bus elements and functions of bus agents. For ease of explanation, the same exemplary serial bus assembly of **Figure 2** is used. However, the bus controller **14** is labeled as Host, also referred to as Hub0. The bus signal distributors **18a-18b** are labeled as Hub1 and Hub2. The peripherals **16a - 16f** including their corresponding bus interfaces **22a - 22f** are jointly labeled as Node0 through Node6. The functions of peripherals **16a - 16f** are labeled as FN0, FN1, etc.

As illustrated, the serial bus elements and functions of the bus agents are assigned geographical as well as logical addresses (GEO ADDR & LOG ADDR) of a geographical and a logical address space. More specifically, the Hubs **14**, **18a - 18b** and the Nodes **22a - 22f** are assigned GEO ADDRes, whereas the functions of the Nodes **16a - 16f** are assigned LOG ADDRes. Preferably, the Hub identity as well as the upstream port of the Hub may be inferred from the GEO ADDR of a Hub **14**, and **18a - 18b**, and the connecting Hub as well as the connecting port of the connecting Hub may be inferred from the GEO ADDR of a Node **22a - 22f**. In one embodiment, the LOG ADDRes are assigned to the functions of the Nodes **16a - 16f** in a chronological manner.

For examples, in the illustrated exemplary application, Hub1 and Hub2 **18a** and **18b** are assigned the GEO ADDRes of "Hub1:Port0" and "Hub2:Port0" respectively, identifying the Hubs **18a** and **18b** as "Hub1" and "Hub2" respectively, and in each case, the upstream port being "Port0". Node1 and Node4 **22b** and **22e** are assigned the GEO ADDRes of "Hub1:Port2" and "Hub2:Port3" respectively, identifying the connecting Hubs **18a** and **18b** as "Hub1"

and "Hub2" respectively, and the connecting ports of connecting Hubs **18a** and **18b** as "Port2" and "Port3" respectively. The functions of Node1 **16b** are assigned the LOG ADDRes of "LA1", "LA2" and "LA3", whereas the function of Node4 **16e** is assigned the LOG ADDR of "LA6".

Preferably, the GEO ADDRes and the LOG ADDRes are dynamically assigned at power on or reset, and updated in response to live detachment of interconnected devices or attachment of additional devices, by the bus controller **14** in cooperation with the bus signal distributors **18** and the bus interfaces **22**. A particular implementation of such dynamic connection management is described in the copending application, serial number 08/332,375, entitled Method And Apparatus For Dynamically Determining And Managing Connection Topology Of An Hierarchical Serial Bus Assembly, which is hereby fully incorporated by reference.

For these embodiments, the GEO ADDRes are used to conduct connection management transactions among the serial bus element, whereas the LOG ADDRes are used to conduct data communication transactions among the functions of the bus agents The separation of the two types of transactions into the two separate address spaces facilitate dynamic connection management of the serial bus elements, without having to interrupt services to the functions of the bus agents.

Figure 6 illustrates the essential elements of communication packets of the present invention implemented by some embodiments for conducting the various transactions employing the master/slave model of flow control. For these embodiments, packet identifiers **44** are employed to differentiate control packets from data packets. Control packets are packets employed by the bus controller **14** to authorize or instruct the bus signal distributors **18** and the bus interfaces **22** to engage in transactions. Control packets may also

include packets employed by the bus signal distributors **18** and the bus interfaces **22** to acknowledge authorizations or instructions from the bus controller **14**. Furthermore, addresses **46** are employed as appropriate to identify the transaction parties. As will be appreciated that under the master/slave model of flow control, the bus controller **14** as a transaction participant may often be inferred, and therefore its address may be omitted.

Preferably, transaction flow, such as from bus controller **14** to a function, from a first function to a second function, may be inferred from the packet identifiers **44**. Preferably, either geographical or logical addresses **46**, i.e. "HubX:PortY" or "LAz", may be specified to accommodate those embodiments that support connection management transactions and implement both types of addresses.

A particular implementation of employing such communication packets to conduct the various transactions will be described in more detail below.

Figures 8-9 illustrate one embodiment of the bus controller of the present invention. In this embodiment, the bus controller **14** includes a control state machine and circuitry **52**, control/status registers **54**, data buffers **56**, and bus controller software services **58**. The control/status registers **54** are used to store the various control and status data. For examples, the serial bus elements present, their interconnection topology, the functions of the various interconnected peripherals, the geographical addresses assigned to the serial bus elements, the logical addresses assigned to the functions of the interconnected peripherals. The data buffers **56** are used to buffer the data of the data communication transactions between the bus agents. The control state machine and circuitry **52** operates the hardware, controlling data communication transactions and employing the above described master/slave model of flow control, under the programming of the bus controller software services **58**. For some

embodiments, the control state machine and circuitry **52** further operates the hardware, controlling connection management transactions, implementing the master/slave model of flow control with frame based polling schedule, employing geographical and logical addressing, supporting communication packet based transactions, and/or inference of data and control states from states of the propagation electrical signals. In particular, the control and state machine circuitry **52** causes the bus controller **14** to cooperate with the bus signal distributors **18** and the bus interfaces **22**, and conduct the various transactions using the elemental packets and protocols of the present invention, which will be decribed in more detail below.

The bus controller software services **58** program the control state machine and circuitry **52** responsive to the operating system **60** and other software such as device and configuring software **62** and **64** of the system unit **12**. In particular, the services include connection management such as detection of serial bus elements present, detection of their interconnection topology, detection of the functions of the interconnected peripherals, and assignment of the geographical and logical addresses. The services further include transaction management such as generation and maintenance of the polling schedule, polling of the serial bus elements and functions of the bus agents, acknowledgment of certain responses of the serial bus elements and functions of the bus agents, and exchange of data with functions of the bus agents.

For a more detailed descriptions of the bus controller hardware and the bus controller software services **58**, refer to the incorporated by reference copending applications, serial numbers 08/332,375, 08/332,727, 08/332,337. It should be noted that the allocation of functions to the hardware and software services of the bus controller **14** is implementation dependent. The present invention may be practiced with any number of allocations, ranging from minimal hardware usage to minimal employment of software services.

Figures 10-11 illustrate one embodiment of the bus signal distributor of the present invention. The illustrated embodiment is a 1:7 bus signal distributor **18'** having control circuitry **66**, control registers **68**, and 8 ports **24**. Port 0 **24** is used to connect the bus signal distributor **18'** upstream to the bus controller **14** or another bus signal distributor **18**. Ports 1 - 7 are used to connect up to a total of 7 bus signal distributors **18** and/or bus interfaces **22** to itself. The control registers **68** are used to store its own control and status information such as whether a port **24** has a bus interface **22** connected to it or not, and whether the port **24** is turned ON/OFF. The control circuitry **66** operates the bus signal distributor **18'** responsive to instructions from the bus controller **14**. In particular, the control circuitry **66** causes the bus signal distributor **18** to cooperate with the bus controller **14**, and conduct the various transactions using the elemental packets and protocols of the present invention, which will be decribed in more detail below.

In embodiments where the low cost two signal wire cables **20** are used to interconnect the serial bus elements, and electrical signals are preferably propagated in a differential manner, each port **24** comprises two differential amplifiers **70** and **72** for generating the differential signals. Preferably, each port **24** further having two resistors **74** coupled to ground as shown, pulling the signals on the two wires to ground, thereby allowing the absence or presence of a connected bus interface **22** to be discernible. The appropriate values of resistors **74** may be determined empirically depending on individual implementations.

For a more detailed descriptions of the control circuitry **64** and its cooperative relationship with the bus controller **14**, refer to the incorporated by reference copending application, serial number 08/332,375.

Figures 12-13 illustrate one embodiment of the bus interfaces of the present invention. For this embodiment, the bus interface **22** comprises control circuitry **80**, control/status registers **82**, a Hub interface **84** and two FIFOs **76 - 78**, a Receive FIFO **76** and a Send FIFO **78**. Receive and Send FIFOs **76 - 78** are used to stage the receive and send data for data communication transactions. The control/status registers **68** are used to store its own control and status information such as its assigned geographical address, functions of its "host" peripheral, and their assigned logical addresses. The control circuitry **66** operates the bus interface **22** on behalf of the "host" peripheral and the "host" peripheral's functions, responsive to authorizations and instructions from the bus controller **14**. In particular, the control circuitry **80** causes the bus interface **22** to cooperate with the bus controller **14**, and conduct the various transactions using the elemental packets and protocols of the present invention, which will be decribed in more detail below.

In embodiments where the low cost two signal wire cables **20** are used to interconnect the serial bus elements, and electrical signals are preferably propagated in a differential manner, the connector interface **84** comprises two differential amplifiers **86** and **88** for generating the differential signals. Preferably, the connector interface **84** further includes two resistors **90** coupled to Vcc as shown, pulling the signals on the two wires to Vcc complementary to the port circuitry of a connecting bus signal distributor **18**. The appropriate values of resistors **90** may also be determined empirically depending on individual implementations.

For a more detailed description of the bus interface **22**, refer to the incorporated by reference copending applications, serial numbers 08/332,375, 08/331,727, 08/332,337.

Data Communication Transactions and Connection Management Transactions

Having now described the hierarchical serial bus assembly **26** and the manner its element cooperate to serially interface the isochronous and asynchronous peripherals **16** to the system unit **12** of the exemplary computer system **10**, the elemental packets and protocols employed under the present invention to conduct the various transactions will now be described in detail.

Figure 14a - 14b illustrate one embodiment of the elemental packets of the present invention. As shown, the elements packets include token packets **502 - 506**, handshake packets **508** and data packets **510 - 512**. For embodiments that support geographical addressing and logical addressing, different packet formats are provided for geographically addressed token packets **502** and logically addressed token packets **504 - 506**. Furthermore, separate packet formats are provided for logically addressed host-function token packet **504** and logically addressed function-function token packet **506**. Similarly, different packet formats are provided for geographically addressed data packets **510** and logically addressed data packets **512**.

Each packet **502 - 512** includes a leading Sync field to facilitate receipt of the packet **502 - 512** by a serial bus element. Each packet **502 - 512** further includes a packet identifier field (PID) for identifying the packet type and the nature of the packet. Each token/data packet **502 - 506** or **510 - 512** further includes at least one geographic/logical address identifying the recipient serial bus element. A geographically addressed data packet **510** further includes an Offset field identifying a specific storage location of the recipient serial bus element, whereas a logically addressed data packet **512** further includes a Source field identifying the source serial bus element. Each data packet **510 - 512** further includes a data length field and the data themselves. Lastly, a logically addressed data packet **512** may further include a CRC check field.

Figure 15 illustrates one embodiment of the packet identifiers of the elemental packets including the packet types they identify. For the illustrated embodiment, each packet identifier (PID) includes a packet type field (PT) and a parameter field (PF). In one embodiment, PT is 3 bits wide, identifying exemplary packet types, such as logical data packet (LOGD), geographical data packet (GEOD). **Figures 16a - 16c** and **17a - 17d** illustrate one embodiment of the packet fields of the packet identifiers and their corresponding meanings. In one embodiment, PF is also 3 bits wide, identifying exemplary meanings, such as receive buffer cannot accept data (RCVNACK) for a handshake packet, enable port N (PENB) for a geographically addressed token packet, global function reset for a logically addressed token packet, isochronous block data packet for a logically addressed function to function token packet, host source packet for a geographically addressed host to function token packet, assign geographical address for a geographically addressed data packet, and perform CRC check for a logically addressed data packet.

Figures 18a - 18c illustrate one embodiment of connection management transaction protocols. As shown, for the illustrated embodiment, connection management transaction protocols include a non-responsive geographical transfer protocol **518**, a responsive geographical write transfer protocol **520**, and a responsive geographical read transfer protocol **522**. Under the non-responsive geographical transfer protocol **518**, the bus controller **14** broadcasts a non-responsive geographical token packet. Each interconnected bus signal distributor **18** or bus interface **22** decodes the token packet and provides no response. Under the responsive geographical write transfer protocol **520**, the bus controller **14** broadcasts a geographical token packet having a destination address. Each bus signal distributor **18** or bus interface **22** decodes the token packet. If the addressed bus signal distributor **18** or bus interface **22** can accept data, it transmits an acknowledgment handshake packet. The bus controller **12** decodes

the acknowledgment handshake packet, and sends the data. The addressed bus signal distributor **18** or bus interface **22** then accepts the data. Under the responsive geographical read transfer protocol **522**, the bus controller **14** broadcasts a geographical token packet having a destination address. Each bus signal distributor **18** or bus interface **22** decodes the token packet. If the addressed bus signal distributor **18** or bus interface **22** can send data, it transmits the data. The bus controller **12** then accepts the data.

Figure 19a - 19k illustrate one embodiment of data communication transaction protocols. As shown, for the illustrated embodiment, data communication transaction protocols include host-function transfer protocols for sending and accepting data, with or without CRC checking, **524 - 534**, host sending attention request protocol **536**, and function-function transfer protocols for sending and accepting data, with or without CRC checking **538**. For example, under the host-function accept data no CRC checking protocol **524**, the bus controller **14** broadcasts a logically addressed token packet having a destination address. Each function decodes the token packet. If the function can accept data, it transmits an acknowledgment handshake packet. The bus controller **12** decodes the acknowledgment handshake packet, and sends the data. The function then accepts the data. As a further example, under the host sending attention request protocol **536**, the bus controller **14** broadcasts a logically addressed token packet having a destination address. Each function decodes the token packet. The function then transmits a NULL or ATTN handshake packet. The bus controller **12** decodes the NULL or ATTN handshake packet. As yet another example, under the host-function accept data no CRC checking protocol **538**, the bus controller **14** broadcasts a logically addressed token packet having a source and a destination address. Each function decodes the token packet. The source function waits for an acknowledgment handshake packet, whereas if the destionation function can accept data, it transmits an acknowledgment handshake packet to the source function. The source function decodes

the acknowledgment handshake packet, and sends the data. The destination function then accepts the data.

Figure 20 illustrates one embodiment of a state machine **600** provided to the bus controller **14** for implementing the above described protocols. State machine **600** comprises ten states **602 - 620** and twenty seven state transitional rules or events (EV1 - EV27). At power on or reset (EV1), state machine **600** enters idle state **602**, and stays in idle state **602**, as long as there is no transaction to be conducted among bus controller **14**, bus signal distributor **18**, and bus interfaces **22** (including the functions interfaced), and it is not time to poll the next bus signal distributor **18**, bus interface **22** or function (EV2).

On the other hand, if it is time to poll, and there is at least one transaction to be performed (EV3, EV12 or EV19), state machine **600** enters either the state of authorizing a transaction from the bus controller **14** to a function, state **604**, or authorizing a transaction from a function to bus controller **14**, state **610**, or authorizing a transaction between two functions, state **616**, depending on the nature of the transaction to be performed.

While in state **604**, state machine **600** authorizes a function to receive data from bus controller **14**. State machine **600** then either stays in the state if a reply with respect to the readiness of the function to accept data has not been received, and time for receiving the reply has not expired (EV4), or returns to idle state **602** if the function replies that it cannot accept data, or time for receiving reply has expired (EV5), or enters the state of sending control/status or data **606**, if the function replies to the effect that it is ready to accept data (EV6).

While in state **606**, state machine **600** sends data to the destination function. State machine **600** then either stays in the state if indication denoting whether CRC checking is to be performed has not

been output yet, and time for outputting the indication has not expired (EV7), or returns to idle state **602** if indication denoting no CRC checking has been output, or time for outputting the indication has expired (EV8), or enters the state of waiting for CRC acknowledgment **608** if indication denoting CRC has been output.

While in state **608**, state machine **600** waits for the CRC checking results. State machine **600** either stays in the state if the destination function has not replied with either CRC pass or failed, and time for reply has not expired (EV10), or returns to idle state **602** if the destination function has replied with either CRC pass or CRC failed, or time for reply has expired (EV11).

While in state **610**, state machine **600** authorizes a source function to send data to bus controller **14**. State machine **600** then either stays in the state if the source function has provided neither data or a null, and time for providing data/null has not expired (EV13), or returns to idle state **602** if the source function has provided a null, or time for providing data or a null has expired (EV14), or enters the state of receiving control/status or data **612**, if the source function has provided a data packet (EV15).

While in state **612**, state machine **600** completes the transaction. State machine **600** then either stays in the state if source function has output an indication on whether CRC checking is necessary or not, and time for outputting the indication has not expired (EV16), or returns to idle state **602** if the source function has output an indication of no CRC checking, or time for outputting the indication has expired (EV18), or enters the state of issuing CRC acknowledgment **614** if the source function has outputting an indication of CRC checking (EV17).

While in state **614**, state machine **600** issues the CRC acknowledgment and then returns to idle state **602**.

While in state **616**, state machine **600** authorizes a source function to send data to a destination function. State machine **600** then either stays in the state if the destination function has not responded with a "can accept data" or "cannot accept data" response, and time for providing the response has not expired (EV20), or returns to idle state **602** if the destination function responded with "cannot accept data" or time to respond has expired (EV22), or enters the state waiting for data **618**, if the destination function responded with "can accept data" (EV21).

While in state **618**, state machine **600** waits for data transfer from the source function to the destination function to complete. State machine **600** then either stays in the state if indication for CRC or no CRC checking has not been output by the source function, and time for outputting such indication has not expired (EV23), or returns to idle state **602** if indication for no CRC checking has been output, or time for outputting the indication has expired (EV25), or enters the state of issuing CRC acknowledgment **620** if indication for CRC checking has been output by the source function (EV24).

While in state **620**, state machine **600** monitors for issuance of a CRC acknowledgment by the destination function. State machine **600** stays in the state if the destination function has not output either CRC pass or CRC failed, and time for outputting CRC pass/failed has not expired (EV26), or returns to idle state **602** if the destination function has output either CRC pass or failed (EV27).

Figure 21 illustrates one embodiment of a state machine **630** provided to a bus signal distributor **18** for implementing the above described protocols. State machine **630** comprises four states **632 - 638** and six state transitional rules or events (EV1 - EV6). At power on or reset (EV1), state machine **630** enters idle state **632**. State machine **630** either stays in idle state **632** if bus signal distributor **18** is not

addressed (geographically) (EV2). Otherwise, state machine **630** either enters the state of sending control/status, state **634**, or the state of sending receive acknowledgment, state **636**, if bus signal distributor **18** is addressed (geographically), depending on the reason it is addressed (geographically).

State machine **630** enters state **634** if it receives a query/configuration verify request (EV3). While in state **634**, bus signal distributor **18** replies with the requested information, and then returns to idle state **632**. State machine **630** enters state **636** if it receives an instruction from bus controller **14** to receive control/status (EV4). While in state **634**, bus signal distributor **18** replies with an acknowledgment, and then enters the state of receiving control/status, state **638**. While in state **634**, state machine **603** either remains in the state if it has not received the control/status from bus controller **14**, and time to receive the control/status has not expired (EV5), or returns to idle state **632** if the control/status has been received or the time to receive has expired (EV6).

Figure 22 illustrates one embodiment of a state machine **640** provided to a bus interface **22** for implementing the above described protocols. State machine **640** comprises nine states **642 - 658** and fifteen state transitional rules or events (EV1 - EV15). At power on or reset (EV1), state machine **640** enters idle state **642**. State machine **640** either stays in idle state **642** if bus interface **22** is not addressed (logically) for transactions or addressed (logically) but no response is required (EV2). Otherwise, state machine **640** either enters the state of sending control/status or data, state **644**, or the state of sending null/attention, state **646**, or the state of sending "cannot accept data", state **648**, or the state of sending "can accept data", state **650**, or the state of waiting for a "can accept data" reply, state **658**, if bus interface **22** is addressed (logically), depending on the reason it is addressed (logically).

State machine **640** enters state **644** if it is addressed (logically) for a function to bus controller **14** transaction, and the addressed function is ready to transmit (EV3). While in state **644**, bus interface **22** sends the requested control/status or data, and then returns to idle state **642**. State machine **640** enters state **646** if it is addressed for a function to bus controller **14** transaction and the addressed function is not ready to transmit (EV4). While in state **646**, bus interface **22** sends a null/attention reply, and then returns to idle state **642**.

State machine **640** enters state **648** if it is addressed for a bus controller **14** to function transaction and the addressed function cannot accept data (EV5). While in state **648**, bus interface **22** sends a "cannot accept data" reply, and then returns to idle state **642**. State machine **640** enters state **650** if it is addressed for a bus controller **14** to function transaction and the addressed function "can accept data" (EV6). While in state **650**, bus interface **22** sends a "can accept data" reply, and then enters the state of receiving data, state **652**.

While at state **652**, state machine **640** receives data. State machine **640** either remains in the state if bus controller **14** has not output an indication for CRC or no CRC checking, and time for outputting the indication has not expired (EV7), or returns to idle state **642** if all data has been received, or time for receiving data has expired (EV8), or enters the state of sending CRC pass, state **654**, if CRC pass is to be replied, and time to reply has not expired (EV9), or enters the state of sending CRC failed, state **656**, if CRC failed is to be replied, and time to reply has not expired (EV10).

State machine **640** enters state **658** if bus interface **22** is addressed (logically) as a source for a function to function transaction (EV11). While in state **658**, state machine **640** remains in the state if no "can accept data" or "cannot accept date" has been received, and time for receiving the reply has not expired (EV12), or simply returns the idle state **642** if either the destination function replied with "cannot accept

data", or time for receiving the reply has expired (EV13), or returns to idle state **642** after sending null/attention first if the destination function replied with "can accept data" but the source function is not ready to transmit, and time for sending data has not expired (EV14), or returns to idle state **642** after sending control/status or data first if the destination function replied with "can accept data", the source function is ready to transmit, and time for sending the reply has not expired (EV15).

Thus, a method and apparatus for exchanging data, status and commands between serial bus elements of an hierarchy serial bus assembly using communication packets has been described. For additional information about the method and apparatus of the present invention, refer to the enclosed Appendices.

While the present invention has been described in terms of the above embodiments, those skilled in the art will recognize that the invention is not limited to the embodiments described. The method and apparatus of the present invention can be practiced with modification and alteration within the spirit and scope of the appended claims. The description is thus to be regarded as illustrative instead of limiting on the present invention.

THIS SHEET HAS BEEN REPLACED

CLAIMS

What is claimed is:

1. (New) A bus controller comprising logic for serially formulating and transmitting token packets of at least a first and a second type to one or more bus signal distributors and one or more bus interfaces, each of the bus interfaces being disposed in a peripheral having one or more functions, for serially authorizing management and data transactions with selected ones of the bus signal distributor(s), the bus interface(s) and the function(s),

the bus controller, the one or more bus signal distributors and the one or more bus interfaces being coupled to each other in an hierarchical tree like manner, with each bus interface directly coupled to a bus signal distributor, and each bus signal distributor coupled another bus signal distributor, except for one of the one or more bus signal distributors, which is directly coupled to the bus controller,

each token packet having identification information identifying whether the token packet is of the first or the second type,

each token packet of the first type being used to authorize either one of the one or more bus signal distributors or one of the one or more bus interfaces to conduct a management transaction with the bus controller, each token packet of the first type further having an address of a first type that identifies the authorized bus signal distributor/interface, each address of the first type being partitioned having a first portion identifying a bus signal distributor, and a second portion identifying either the identified bus signal distributor or a bus interface coupled to the identified bus signal distributor,

each token packet of the second type being used to authorize a function to conduct a data transaction with the bus controller, each token packet of the second type further having an address of a second type that identifies the authorized function, each address of the second type being unpartitioned.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

TH IS SHEET EEN P' EN

* C L M S *

2. (New) The bus controller as set forth in Claim 1, wherein the bus controller further comprises logic for serially exchanging data packets of a first type with the authorized bus signal distributors/interfaces and data packets of a second type with the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type,

each data packet of the first type further having an address of the first type identifying the authorized bus signal distributor/interface, and

each data packet of the second type further having an address of the second type identifying the authorized function.

3. (New) The bus controller as set forth in Claim 1, wherein the bus controller further comprises logic for serially formulating and transmitting token packets of a third type to the functions for serially authorizing data transactions to be conducted between selected twos of the functions,

each token packet of the third type also having identification information identifying the token packet as of the third type,

each token packet of the third type further having two addresses of the second type identifying two functions as the authorized functions of the data transaction.

4. (New) The bus controller as set forth in Claim 3, wherein the bus controller further comprises logic for serially exchanging data packets of a first type with the authorized bus signal distributors/interfaces and data packets of a second type with the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type,

each data packet of the first type further having an address of the first type identifying the authorized bus signal distributor/interface, and

each data packet of the second type further having at least one address of the second type identifying at least one function as the authorized function.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

* C L M S *

5. (New) A bus signal distributor comprising logic for serially receiving token packets of at least a first and a second type from a bus controller, and forwarding the received token packets to zero or more other bus signal distributors coupled to the bus signal distributor and/or zero or more bus interfaces coupled to the bus signal distributor, each of the bus interfaces being disposed in a peripheral having one or more functions, for serially facilitating authorization by the bus controller of management and data transactions between the bus controller and selected ones of the bus signal distributor(s), the bus interface(s) and the function(s),

each bus interface being directly coupled to a bus signal distributor, which in turn is coupled upstream to either another bus signal distributor or the bus controller,

each token packet having identification information identifying whether the token packet is of the first or the second type,

each token packet of the first type being used to authorize either one of the bus signal distributors or one of the one or more bus interfaces to conduct a management transaction with the bus controller, each token packet of the first type further having an address of a first type that identifies the authorized bus signal distributor/interface, each address of the first type being partitioned having a first portion identifying a bus signal distributor, and a second portion identifying either the identified bus signal distributor or a bus interface coupled to the identified bus signal distributor,

each token packet of the second type being used to authorize a function to conduct a data transaction with the bus controller, each token packet of the second type further having an address of a second type that identifies the authorized function, each address of the second type being unpartitioned.

6. (New) The bus signal distributor as set forth in Claim 5, wherein the bus signal distributor further comprises logic for serially exchanging data packets of a first type with the bus controller, and facilitating exchanges of data packets of the first type between the bus controller

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

* C L M S *

and other authorized bus signal distributors/interfaces, as well as data packets of a second type between the bus controller and the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type,

each data packet of the first type further having an address of the first type identifying the authorized bus signal distributor/interface, and

each data packet of the second type further having an address of the second type identifying the authorized function.

7. (New) The bus signal distributor as set forth in Claim 5, wherein the bus signal distributor further comprises logic for serially receiving and forwarding token packets of a third type to the functions for serially facilitating authorization by the bus controller for data transactions between the authorized functions,

each token packet of the third type also having identification information identifying the token packet as of the third type,

each token packet of the third type further having two addresses of the second type identifying two authorized functions.

8. (New) The bus signal distributor as set forth in Claim 7, wherein the bus signal distributor further comprises logic for serially exchanging data packets of a first type with the bus controller, and facilitating exchanges of data packets of the first type between the bus controller and other authorized bus signal distributors/interfaces, as well as data packets of a second type between the bus controller and the authorized functions or between authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type,

each data packet of the first type further having an address of the first type identifying the bus signal distributor or an authorized bus interface, and

each data packet of the second type further having at least one address of the second type identifying at least one authorized function.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED



9. (New) A bus interface comprising logic for serially receiving token packets of at least a first and a second type from a bus controller, each of the bus interfaces being disposed in a peripheral having one or more functions, for serially facilitating authorization by the bus controller of management and data transactions between the bus controller and selected ones of the bus interface(s) and the function(s),

each bus interface being directly coupled to a bus signal distributor, which in turn is coupled upstream to either another bus signal distributor or the bus controller,

each token packet having identification information identifying whether the token packet is of the first or the second type,

each token packet of the first type being used to authorize either the bus signal distributor or the bus interface to conduct a management transaction with the bus controller, each token packet of the first type further having an address of a first type that identifies the authorized bus signal distributor/interface, each address of the first type being partitioned having a first portion identifying the bus signal distributor, and a second portion identifying either the identified bus signal distributor or the bus interface,

each token packet of the second type being used to authorize a function to conduct a data transaction with the bus controller, each token packet of the second type further having an address of a second type that identifies the authorized function, each address of the second type being unpartitioned.

10. (New) The bus interface as set forth in Claim 9, wherein the bus signal distributor further comprises logic for serially exchanging data packets of a first type with the bus controller, or facilitating exchanges of data packets of a second type between the bus controller and the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type,

This Sheet Has Been Replaced



THIS SHEET HAS BEEN REPLACED

* C L M S *

each data packet of the first type further having an address of the first type identifying the bus signal distributor/interface, and

each data packet of the second type further having an address of the second type identifying the authorized function.

11. (New) The bus interface as set forth in Claim 9, wherein the bus interface further comprises logic for serially receiving token packets of a third type for serially facilitating authorization by the bus controller for data transactions between the authorized functions,

each token packet of the third type also having identification information identifying the token packet as of the third type,

each token packet of the third type further having two addresses of the second type identifying two authorized functions.

12. (New) The bus interface as set forth in Claim 11, wherein the bus interface further comprises logic for serially exchanging data packets of a first type with the bus controller, or facilitating exchanges of data packets of a second type between the bus controller and authorized functions, and between authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type,

each data packet of the first type further having an address of the first type identifying the bus interface, and

each data packet of the second type further having at least one address of the second type identifying at least one authorized function.

13. (New) In a computer system having a bus controller, at least one bus signal distributor, and at least one peripheral, wherein each peripheral has a bus interface and at least one function, each bus interface being coupled to a bus signal distributor, and each bus signal distributor being coupled to another bus signal distributor, except for one of the at least one bus signal distributor which is coupled to the bus controller, a method for operating the computer system, the method comprising the steps of:

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

* C L M S *

a) authorizing a management transaction with either a bus signal distributor or a bus interface using a token packet of a first type by the bus controller, or authorizing a data transaction with a function using a token packet of a second type by the bus controller, the token packet having identification information identifying whether the token packet is of the first type or the second type, and the token packet further having an address of a first type if the token packet is of the first type or an address of a second type if the token packet is of the second type, wherein if the address is of the first type, the address is a partitioned address having a first portion identifying a bus signal distributor, and a second portion identifying either the identified bus signal distributor or a bus interface coupled to the identified bus signal distributor, and if the address is of the second type, the address is an unpartitioned address identifying a function;

b) receiving the token packet by the at least one bus signal distributor and the at least one bus interface in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the token packet to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

c) notifying one of the at least one function by one of the at least one receiving bus interface if the token packet is of the second type, the notified function being the addressee of the token packet of the second type and a function of the notifying bus interface's peripheral.

14. (New) The computer system as set forth in claim 13, wherein the method further comprises the steps of:

d) transmitting either a data packet of a first type to an authorized bus signal distributor/interface or a data packet of a second type to an authorized function by the bus controller, the data packet having identification information identifying whether the data packet is of the first or the second type, the data packet further having an address of the first type if the data packet is of the first type, or an address of the second type if the data packet is of the second type;

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

* C L M S *

e) receiving the data packet by the at least one bus signal distributor and the at least one bus interface in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the data packet to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

f) notifying one of the at least one function by one of the at least one receiving bus interface if the data packet is of the second type, the notified function being the addressee of the data packet of the second type and a function of the notifying bus interface's peripheral.

15. (New) The computer system as set forth in claim 13, wherein the method further comprises the steps of:

d) transmitting a data packet of the first type to the bus controller by an authorized bus signal distributor/interface or transmitting a data packet of the second type to the bus controller by an authorized function;

e) receiving the data packet by the transmitting function's bus interface, and forwarding the data packet to the bus interface's coupled bus signal distributor, if the data packet is of the second type;

f) receiving the data packet by zero or more intervening ones of the at least one bus signal distributor in a serial manner in accordance to the manner they are coupled, with each of the receiving bus signal distributor forwarding the data packet to the upstream bus signal distributor; and

g) receiving the data packet by the bus signal distributor coupled to the bus controller and forwarding the data packet to the bus controller.

16. (New) The computer system as set forth in claim 13, wherein

the computer system has at least two peripherals, each of the at least two peripherals having a bus interface and at least one function;

the method further comprises the steps of:

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

d) authorizing a data transaction between two functions of two of the at least two peripherals using a token packet of a third type by the bus controller, the token packet having identification information identifying the token packet as being of the third type, and the token packet further having two addresses of the second type identifying the two functions;

e) receiving the token packet of the third type by the at least one bus signal distributor and the at least two bus interfaces in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the token packet of the third type to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

f) notifying two functions of the at least two peripherals by two of the at least two receiving bus interfaces, the two notified functions being the addressees of the token packet of the third type and functions of the notifying bus interfaces' peripherals.

17. (New) The computer system as set forth in claim 16, wherein the method further comprises the steps of:

g) transmitting either a data packet of a first type to an authorized bus signal distributor/interface by the bus controller or a data packet of a second type to a first authorized function by either the bus controller or a second authorized function, the data packet having identification information identifying whether the data packet is of the first or the second type, the data packet further having an address of the first type if the data packet is of the first type, or an address of the second type if the data packet is of the second type;

h) receiving the data packet by the at least one bus signal distributor and the at least one bus interface in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the data packet to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

i) notifying one of the at least two functions by one of the at least two receiving bus interfaces if the data packet is of the second type, the notified function being the addressee of the data packet of the second type and a function of the notifying bus interface's peripheral.

18. (New) The computer system as set forth in claim 16, wherein the method further comprises the steps of:

g) transmitting a data packet of the first type to the bus controller by an authorized bus signal distributor/interface or transmitting a data packet of the second type to either the bus controller or a first authorized function by a second authorized function;

e) receiving the data packet by the transmitting function's bus interface, and forwarding the data packet to the bus interface's coupled bus signal distributor, if the data packet is of the second type;

f) receiving the data packet by zero or more intervening ones of the at least one bus signal distributor in a serial manner in accordance to the manner they are coupled, with each of the receiving bus signal distributor forwarding the data packet to the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

g) receiving the data packet by either the bus signal distributor coupled to the bus controller and forwarding the data packet to the bus controller, or by the bus interface disposed on the peripheral of the first authorized function and notifying the first authorized function.

This Sheet Has Been Replaced



26
20
24
18
1:n bus signal distributors
20
22
Bus Interfaces
16
Keyboard, Mouse, Monitor, Speakers, MIC, Phone, etc.
24
24
20
12
14
Serial Bus Controller
System Unit
10

Figure 1



Upstream
Phone
22a
16a
22b
16b
Compound Keyboard With Pen & Mouse Functions
26'
18a
14
Bus Controller
24
Stand Along 1:n Bus Signal Distribution
24
24
18b
Integrated 1:n Bus Signal Distributors
24
24
24
24
22d
Speaker
16d
22f
MIC
16f
22e
Speaker
16e
22c
Monitor Circuitry
16c
28
Montior

Figure 2



12
System Unit
Bus Controller
(Master)
14
Auth/
Instr
CTRL/Status,
Data (Peripheral only)
Bus Signal Distr & INTF
(Slave)
18 & 22
Peripherals
16
Data
(Peripheral only)

Figure 3



30
32
32
32
32
32
32
32
Spare
40b
• • •
DEV 2
38b
Async FN 2
36b
ISO FN 2
34b
ISO FN 1
34a
Spare
40a
• • •
DEV 1
38a
Async FN 1
36a
ISO FN 2
34b
ISO FN 1
34a
P1
P2
M2
M1
P1
P2
M2
M1

Figure 4



14
HOST (HUB 0)
GEO ADDR = HUB 0: Port 0
24
18a
HUB 1
GEO ADDR = HUB 1: Port 0
24
24
22a
16a
Node 0 (FN 0)
GEO ADDR = HUB 1: Port 1 Log ADDR = { LA0}
22b
16b
Node 1 (FN 0, FN1, FN2)
GEO ADDR = HUB 1: Port 2 Log ADDR = {LA1, LA2, LA3}
16d
Node 5 (FN 0)
GEO ADDR = HUB 2: Port 1 Log ADDR = {LA4}
22d
26'
24
GEO ADDR = HUB 2: Port 0
HUB 2
24
24
24
22f
16f
Node 6 (FN 0)
GEO ADDR = HUB 2: Port 2 Log ADDR = { LA5}
22c
16c
Node 3 (FN 0)
:O ADDR = HUB 2: Port 4 Log ADDR = { LA7}
22e
16e
Node 4 (FN 0)
3EO ADDR = HUB 2: Port 3 Log ADDR = { LA6}

Figure 5




Figure 6




Figure 7




Figure 8




Figure 9



24
24
24
PORT #1
PORT #2
PORT #3
18'
1:7 Signal Distributor
66
Control Circuitry
68
Control Registers
24
PORT #0
PORT #4
24
PORT #7
PORT #6
PORT #5
24
24
24

Figure 10




Figure 11




Figure 13



22
To Rest Of Node
From Rest Of Node
80
Control Circuitry
76
Receive FIFO
82
Control/Status Registers
78
Send FIFO
HUB INTF
84

Figure 12

Packet Format: Geographical Addressing




Figure 14a

Packet Format: Logical Addressing






Figure 14b



PT <0.2>	Abbrev	Packet Type
000	LOGD	Logical data packet
100	GEOD	Geographical data packet
101	TKFF	Token between logical functions
110	TKHF	Logical token between host and function
010	GEOT	Geographical token packet
001	HSHK	Handshake packet
011	CTRL	Special control packet
111	RSVD	Reserved


Figure 15



PF<0:2> = 0	Receive buffer cannot accept data (RCVNACK)
PF<0:2> = 1	Receive buffer can accept data (RCVACK)
PF<0:2> = 2	CRC check fails (CRCNACK)
PF<0:2> = 3	CRC check passes (CRCACK)
PF<0:2> = 4	Source cannot send data (NULL)
PF<0:2> = 5	Attention Request (ATTN)
PF<0:2> = 6	Logical function not finished reset
PF<0:2> = 7	Logical function completed reset

Figure 16a


Control Token Packet: Geographical Addressing



Value	Abbrev	Function
PF = 000	GRST	Global reset
PF = 001	GNRS	Global node reset
PF = 010	SNRS	Single node reset
PF = 011	HSGP	Host sending GEO data packet
PF = 100	PENB	Enable port N
PF = 101	PDIS	Disable port N
PF = 110	PENQ	Presence query
PF = 111	GCVF	Geographical Configuration Verify

Figure 16b


Control Token Packet: Logical Addressing



PF<0:2> = 0	Global function reset
PF<0:2> = 1	Single function reset
PF<0:2> = 2	Function Status request
PF<0:2> = 3	Attention request
PF<0:2> = 4	Reserved
PF<0:2> = 5	Reserved
PF<0:2> = 6	Reserved
PF<0:2> = 7	Reserved

Figure 16c


Function To FunctionToken Packet: Logical Addressing



PF<0> = 0
PF<1:2> = 0 Asynchronous control packet
PF<1:2> = 1 Asynchronous/Isochronous block data packet
PF<1:2> = 2 Reserved
PF<1:2> = 3 Isochronous data packet

Figure 17a


Host To Function Token Packet: Geographical Addressing



PF<0> = 0 Host sources packet
PF<0> = 1 Function sources packet
PF<1:2> = 0 Asynchronous control packet
PF<1:2> = 1 Asynchronous data/Isochronous block packet
PF<1:2> = 2 Reserved
PF<1:2> = 3 Isochronous data packet

Figure 17b


Data Packet: Geographical Addressing



PF<0:2> = 0	Assign Logical Address
PF<0:2> = 1	Assign geographical address
PF<0:2> = 2	Geographical data packet
PF<0:2> = 3	Reserved
PF<0:2> = 4	Reserved
PF<0:2> = 5	Reserved
PF<0:2> = 6	Reserved
PF<0:2> = 7	Reserved

Figure 17c

Data Packet: Logical Addressing



PF<0> = 0	Do not perform CRC generate/check
PF<0> = 1	Perform CRC generate/check
PF<1:2> = 0	Asynchronous control packet
PF<1:2> = 1	Asynchronous data/Isochronous block packet
PF<1:2> = 2	Reserved
PF<1:2> = 3	Isochronous data packet

Figure 17d




Figure 18a




Figure 18b



Response Geographical Transfer: Read
Host
Hub or Node
Host broadcasts token: Source ADDR = B
Token
Hub/node decodes ADDR field
522
Host receives data
Data
Hub/node sends data
Host issues next token
Next Token

Figure 18c




Figure 19a




Figure 19b




Figure 19c




Figure 19d




Figure 19e




Figure 19f



Host Sending An Attention Request Token
(Logical Addressing)
Host
Function B
Host broadcasts token: Source ADDR = B
Token
Function decodes ADDR field
536
Host decodes handshake
Handshake
Function sends NULL or ATTN handshake
Host issues next token
Next Token

Figure 19g



538
Successful Function To Function Transfer, No CRC Check
(Logical Addressing)
Host
Function B
Function C
Host broadcasts token: Source = B, Destination = C
Token
Function B decodes SRC field and waits for handshake
Token
Function C decodes DEST field
Function B decodes Receive ACK
Handshake
Function C can accept data and issues Receive ACK
Function B sends data
Data
Function C accepts data
Host decodes a CRC handshake
Next Token
Host issues next token

Figure 19h



Successful Function To Function Transfer, No CRC Checking
(Logical Addressing)
Host
Function B
Function C
540
Host broadcasts token: Source = B, Destination = C
Token
Function B decodes SRC field and waits for handshake
Token
Function C decodes ADDR field
Function B decodes Receive ACK
Handshake
Function C can accept data and issues Receive ACK
Function B sends data and CRC
Data
Node C accepts data and performs CRC check
Function B decodes results of CRC ACK
Handshake
Results of CRC check are issued as CRC ACK
Host decodes a CRC handshake
Handshake
Host issues next token
Next Token

Figure 19i



Function To Function Transfer: Destination Can't Accept Data
(Logical Addressing)
Host
Function B
Function C
Host broadcasts token: Source = B, Destination = C
Token
Function B decodes SRC field and waits for handshake
Token
Function C decodes DEST field
Handshake
Function C can't accept data and issues a Receive NACK
Function B decodes Receive NACK and sends no data
542
Host Receive NACK handshake
Next Token
Host issues next token

Figure 19j



Function To Function Transfer: Source Cannot Send Data
(Logical Addressing)
Host
Function B
Function C
Host broadcasts token: Source = B, Destination = C
Token
Function B decodes SRC field and waits for handshake
Token
Function B decodes ADDR field
Handshake
Function B decodes Receive ACK
Handshake
Function C can accept data and issues Receive NACK
Handshake
Function B can't send data and issues a NULL handshake
Handshake
Function C decodes a NULL handshake
Host decodes a NACK handshake
Next Token
Host issues next token
544

Figure 19k



600
Idle
602
EV1
EV2
EV3
EV4
EV5
EV6
EV7
EV8
EV9
EV10
EV11
EV12
EV14
EV15
EV16
EV17
EV18
EV19
EV20
EV21
EV22
EV23
EV24
EV25
EV26
EV27
Idle
Authorize A Node Host
604
Idle
Send Control/Status or Data
606
Idle
Wait For CRC ACk
608
Idle
Authorize A Node Host
610
Idle
Receive Control/Status or Data
612
Idle
Issue CRC ACk
614
Idle
Authorize Node i Node j
616
Idle
Wait For Data
618
Idle
Issue CRC ACk
620
Idle

Figure 20



630
EV1
Idle
632
EV2
EV3
Send Control/Status
634
Idle
EV4
Send RCV ACK
636
EV5
RCV Control/Status
638
EV6
Idle

Figure 21



640
Idle
642
EV1
EV2
Send RCV NACK
648
EV5
Send Null/Attn
646
EV4
Send CTRl/ Status or Data
644
EV3
Send RCV ACK
650
EV6
Wait For RCV ACK
658
EV11
Send Ctrl/Status or Data
EV15
Send Null/ Attn
EV14
Idle
EV13
RCV Data
652
EV10
Send CRC NACK
656
Idle
EV9
Send CRC ACK
654
Idle
EV8
Idle
EV7

Figure 22

REPLACEMENT SHEET
Date :...16 APR 1998..

* C L M S *

CLAIMS

1. A bus controller comprising logic for serially formulating and transmitting token packets of at least a first and a second type to one or more bus signal distributors and one or more bus interfaces, each of the bus interfaces being disposed in a peripheral having one or more functions, for serially authorizing management and data transactions with selected ones of the bus signal distributor(s), the bus interface(s) and the function(s),

the bus controller, the one or more bus signal distributors and the one or more bus interfaces being coupled to each other in an hierarchical tree like manner, with each bus interface directly coupled to a bus signal distributor, and each bus signal distributor coupled another bus signal distributor, except for one of the one or more bus signal distributors, which is directly coupled to the bus controller,

the management transactions being used for dynamically configuring the bus controller, the one or more bus signal distributors and the one or more bus interfaces in accordance with the manner in which the bus controller, the one or more bus signal distributors and the one or more bus interfaces are coupled to each other,

each token packet having identification information identifying whether the token packet is of the first or the second type, and first address information,

each token packet of the first type being used to authorize either one of the one or more bus signal distributors or one of the one or more bus interfaces to conduct a management transaction with the bus controller, and the first address information of each token packet of the first type ~~further having an address of a first type that identifies the authorized bus signal distributor/interface, each address of the first type~~ being decoded in a

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

partitioned manner ~~having~~ including a first portion for identifying a bus signal distributor, and a second portion for identifying either the identified bus signal distributor as the authorized bus signal distributor or a bus interface coupled to the identified bus signal distributor as the authorized bus interface,

each token packet of the second type being used to authorize a function to conduct a data transaction with the bus controller, and the first address information of each token packet of the second type ~~further having an address of a second type that identifies the authorized function, each address of the second type~~ being decoded in an unpartitioned manner for identifying the first authorized function.

2. The bus controller as set forth in Claim 1, wherein the bus controller further comprises logic for serially exchanging data packets of a first type with the authorized bus signal distributors/interfaces and data packets of a second type with the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type, and second address information,

the second address information of each data packet of the first type ~~further having an address of the first type~~ being decoded in the first partitioned manner for identifying the authorized bus signal distributor/interface, and

the second address information of each data packet of the second type ~~further having an address of the second type~~ being decoded in the second unpartitioned manner for identifying the authorized function.

3. The bus controller as set forth in Claim 1, wherein

the identification information of each token packet identifies the token packet as the first, the second or a third type instead, and each token packet further includes second address information.

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

the bus controller further comprises logic for serially formulating and transmitting token packets of ~~a~~ the third type to the functions for serially authorizing data transactions to be conducted between selected twos of the functions,

~~each token packet of the third type also having identification information identifying the token packet as of the third type,~~

both the first and the second address information of each token packet of the third type ~~further having two addresses of the second type~~ being decoded in the second unpartitioned manner for identifying two functions as the authorized functions of the data transaction.

4. The bus controller as set forth in Claim 3, wherein the bus controller further comprises logic for serially exchanging data packets of a first type with the authorized bus signal distributors/interfaces and data packets of a second type with the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type, and at least third address information,

the third address information of each data packet of the first type ~~further having an address of the first type~~ being decoded in the first partitioned manner for identifying the authorized bus signal distributor/interface, and

the third address information of each data packet of the second type ~~further having at least one address of the second type~~ being decoded in the second unpartitioned manner for identifying at least one function as the authorized function.

5. A bus signal distributor comprising logic for serially receiving token packets of at least a first and a second type from a bus controller, and forwarding

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

the received token packets to zero or more other bus signal distributors coupled to the bus signal distributor and/or zero or more bus interfaces coupled to the bus signal distributor, each of the bus interfaces being disposed in a peripheral having one or more functions, for serially facilitating authorization by the bus controller of management and data transactions between the bus controller and selected ones of the bus signal distributor(s), the bus interface(s) and the function(s),

each bus interface being directly coupled to a bus signal distributor, which in turn is coupled upstream to either another bus signal distributor or the bus controller,

the management transactions being used for dynamically configuring the bus controller, the one or more bus signal distributors and the one or more bus interfaces in accordance with the manner in which the bus controller, the one or more bus signal distributors and the one or more bus interfaces are coupled to each other;

each token packet having identification information identifying whether the token packet is of the first or the second type, and first address information,

each token packet of the first type being used to authorize either one of the bus signal distributors or one of the one or more bus interfaces to conduct a management transaction with the bus controller, and the first address information of each token packet of the first type ~~further having an address of a first type that identifies the authorized bus signal distributor/interface, each address of the first type~~ being decoded in a partitioned manner ~~having~~ including a first portion for identifying a bus signal distributor, and a second portion for identifying either the identified bus signal distributor as the authorized bus signal distributor or a bus interface coupled to the identified bus signal distributor as the authorized bus interface,

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
16 APR 1998
Date :.....

each token packet of the second type being used to authorize a function to conduct a data transaction with the bus controller, and the first address information of each token packet of the second type ~~further having an address of a second type that identifies the authorized function, each address of the second type~~ being decoded in an unpartitioned manner for identifying the first authorized function.

6. The bus signal distributor as set forth in Claim 5, wherein the bus signal distributor further comprises logic for serially exchanging data packets of a first type with the bus controller, and facilitating exchanges of data packets of the first type between the bus controller and other authorized bus signal distributors/interfaces, as well as data packets of a second type between the bus controller and the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type, and second address information,

the second address information of each data packet of the first type ~~further having an address of the first type~~ being decoded in the first manner for identifying the authorized bus signal distributor/interface, and

the second address information of each data packet of the second type ~~further having an address of the second type~~ being decoded in the second unpartitioned manner for identifying the authorized function.

7. The bus signal distributor as set forth in Claim 5, wherein

the identification information of each token packet identifies the token packet as the first, the second or a third type, and each token packet further includes second address information,

the bus signal distributor further comprises logic for serially receiving and

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

forwarding token packets of ~~a~~ the third type to the functions for serially facilitating authorization by the bus controller for data transactions between the first authorized function ~~a~~ and a second authorized function,

~~each token packet of the third type also having identification information identifying the token packet as of the third type~~,

both the first and the second address information of each token packet of the third type ~~further having two addresses of the second type~~ being decoded in the second unpartitioned manner for identifying two authorized functions.

8. The bus signal distributor as set forth in Claim 7, wherein the bus signal distributor further comprises logic for serially exchanging data packets of a first type with the bus controller, and facilitating exchanges of data packets of the first type between the bus controller and other authorized bus signal distributors/interfaces, as well as data packets of a second type between the bus controller and the authorized functions or between authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type, and at least third address information,

the at least third address information of each data packet of the first type ~~further having an address of the first type~~ being decoded in the first partitioned manner for identifying the bus signal distributor or an authorized bus interface, and

the at least third address information of each data packet of the second type ~~further having at least one address of the second type~~ being decoded in the second unpartitioned manner for identifying at least one authorized function.

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

9. A bus interface comprising logic for serially receiving token packets of at least a first and a second type from a bus controller, each of the bus interfaces being disposed in a peripheral having one or more functions, for serially facilitating authorization by the bus controller of management and data transactions between the bus controller and selected ones of the bus interface(s) and the function(s),

each bus interface being directly coupled to a bus signal distributor, which in turn is coupled upstream to either another bus signal distributor or the bus controller,

the management transactions including configuration transactions for dynamically configuring the bus interface, the bus signal distributor(s), and the bus controller in accordance with the manner in which the bus interface, the bus signal distributor(s) and the bus controller are coupled to each other,

each token packet having identification information identifying whether the token packet is of the first or the second type, and first address information,

each token packet of the first type being used to authorize either the bus signal distributor or the bus interface to conduct a management transaction with the bus controller, and the first address information of each token packet of the first type ~~further having an address of a first type that identifies the authorized bus signal distributor/interface, each address of the first type~~ being decoded in a partitioned manner ~~having~~ including a first portion for identifying the bus signal distributor, and a second portion for identifying either the identified bus signal distributor as the authorized bus signal distributor or the bus interface as the authorized bus interface,

each token packet of the second type being used to authorize a function to conduct a data transaction with the bus controller, and the first address information of each token packet of the second type ~~further having an address of a second type that identifies the authorized function, each address of the~~

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

~~second type~~ being decoded in an unpartitioned manner for identifying the first authorized function.

10. (New) The bus interface as set forth in Claim 9, wherein the bus signal distributor further comprises logic for serially exchanging data packets of a first type with the bus controller, or facilitating exchanges of data packets of a second type between the bus controller and the authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type, and second address information,

the second address information of each data packet of the first type ~~further having an address of the first type~~ being decoded in the first partitioned manner for identifying the bus signal distributor/interface, and

the second address information of each data packet of the second type ~~further having an address of the second type~~ being decoded in the second unpartitioned manner for identifying the authorized function.

11. The bus interface as set forth in Claim 9, wherein

the identification information of each token packet identifies the token packet as the first, the second, or a third type, and each token packet further includes second address information,

the bus interface further comprises logic for serially receiving token packets of ~~a~~ the third type for serially facilitating authorization by the bus controller for data transactions between the authorized functions,

~~each token packet of the third type also having identification information identifying the token packet as of the third type,~~

both the first and the second address information of each token packet of the third type ~~further having two addresses of the second type~~ being decoded in the second unpartitioned manner for identifying two authorized functions.

AMENDED SHEET

REPLACEMENT SHEET
Date : 16 APR 1998

12. The bus interface as set forth in Claim 11, wherein the bus interface further comprises logic for serially exchanging data packets of a first type with the bus controller, or facilitating exchanges of data packets of a second type between the bus controller and authorized functions, and between authorized functions,

each data packet having identification information identifying whether the data packet is of the first or the second type, and at least third address information,

the at least third address information of each data packet of the first type ~~further having an address of the first type~~ being decoded in the first partitioned manner for identifying the bus interface, and

the at least third address information of each data packet of the second type ~~further having at least one address of the second type~~ being decoded in the second unpartitioned manner for identifying at least one authorized function.

13. In a computer system having a bus controller, at least one bus signal distributor, and at least one peripheral, wherein each peripheral has a bus interface and at least one function, each bus interface being coupled to a bus signal distributor, and each bus signal distributor being coupled to another bus signal distributor, except for one of the at least one bus signal distributor which is coupled to the bus controller, a method for operating the computer system, the method comprising the steps of:

a) authorizing a management transaction with either a bus signal distributor or a bus interface to dynamically configure the bus signal distributor/interface in accordance with the manner in which the bus signal distributor/interface is coupled, the authorization is provided using a token

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

packet of a first type by the bus controller, or authorizing a data transaction with a function using a token packet of a second type by the bus controller, the token packet having identification information identifying whether the token packet is of the first type or the second type, and the token packet further having ~~an~~ first address information of either a first type ~~if the token packet is of the first type~~ or ~~an address of~~ a second type ~~if the token packet is of the second type~~, wherein if the ~~address~~ token packet is of the first type, the first address information is decoded in a partitioned manner including a first portion for ~~address having a first portion~~ identifying a bus signal distributor, and a second portion for identifying either the identified bus signal distributor as the authorized bus signal distributor or a bus interface coupled to the identified bus signal distributor as the authorized bus interface, and if the address is of the second type, the first address information is decoded in an unpartitioned manner for ~~address~~ for identifying a first function as the authorized function;

b) receiving the token packet by the at least one bus signal distributor and the at least one bus interface in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the token packet to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

c) notifying one of the at least one function by one of the at least one receiving bus interface if the token packet is of the second type, the notified function being the addressee of the token packet of the second type and a function of the notifying bus interface's peripheral.

14. The computer system as set forth in claim 13, wherein the method further comprises the steps of:

d) transmitting either a data packet of a first type to an authorized bus signal distributor/interface or a data packet of a second type to an authorized function by the bus controller, the data packet having identification information identifying whether the data packet is of the first or the second type, the data

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

packet further having ~~an~~ second address information of ~~the~~ either a first type decoded in the first partitioned manner for identifying the authorized bus signal distributor/interface if the data packet is of the first type, or ~~an address of the~~ a second type decoded in the second unpartitioned manner if the data packet is of the second type;

e) receiving the data packet by the at least one bus signal distributor and the at least one bus interface in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the data packet to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

f) notifying one of the at least one function by one of the at least one receiving bus interface if the data packet is of the second type, the notified function being the addressee of the data packet of the second type and a function of the notifying bus interface's peripheral.

15. The computer system as set forth in claim 13, wherein the method further comprises the steps of:

d) transmitting a data packet of ~~the~~ a first type to the bus controller by an authorized bus signal distributor/interface or transmitting a data packet of ~~the~~ a second type to the bus controller by an authorized function, the data packet having identification information identifying whether the data packet is of the first or the second type, the data packet further having second address information of a first type decoded in the first partitioned manner for identifying the bus controller, or a second type decoded in the second unpartitioned manner for identifying the bus controller;

e) receiving the data packet by the transmitting function's bus interface, and forwarding the data packet to the bus interface's coupled bus signal distributor, if the data packet is of the second type;

f) receiving the data packet by zero or more intervening ones of the at

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date :....16 APR 1998

least one bus signal distributor in a serial manner in accordance to the manner they are coupled, with each of the receiving bus signal distributor forwarding the data packet to the upstream bus signal distributor; and

g) receiving the data packet by the bus signal distributor coupled to the bus controller and forwarding the data packet to the bus controller.

16. (New) The computer system as set forth in claim 13, wherein

the computer system has at least two peripherals, each of the at least two peripherals having a bus interface and at least one function;

the method further comprises the steps of:

d) authorizing a data transaction between two functions of two of the at least two peripherals using a token packet of a third type by the bus controller, the token packet having identification information identifying the token packet as being of the third type, and the token packet further having ~~two~~ second address ~~es~~ information of the second type decoded in the second unpartitioned manner for identifying the two functions;

e) receiving the token packet of the third type by the at least one bus signal distributor and the at least two bus interfaces in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the token packet of the third type to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

f) notifying two functions of the at least two peripherals by two of the at least two receiving bus interfaces, the two notified functions being the addressees of the token packet of the third type and functions of the notifying bus interfaces' peripherals.

17. The computer system as set forth in claim 16, wherein the method further

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date : 16 APR 1998

comprises the steps of:

g) transmitting either a data packet of a first type to an authorized bus signal distributor/interface by the bus controller or a data packet of a second type to a first authorized function by either the bus controller or a second authorized function, the data packet having identification information identifying whether the data packet is of the first or the second type, the data packet further having ~~an~~ address information of either the first type decoded in the first partitioned manner for identifying the authorized buys signal distributor/interfcae if the data packet is of the first type, or ~~an address of~~ the second type decoded in the second unpartitioned manner for identifying the second authorized function if the data packet is of the second type;

h) receiving the data packet by the at least one bus signal distributor and the at least one bus interface in a substantially serial manner in accordance to the manner they are coupled to each other, with each of the at least one receiving signal distributor forwarding the data packet to each of the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

i) notifying one of the at least two functions by one of the at least two receiving bus interfaces if the data packet is of the second type, the notified function being the addressee of the data packet of the second type and a function of the notifying bus interface's peripheral.

18. The computer system as set forth in claim 16, wherein the method further comprises the steps of:

~~d~~ d) transmitting a data packet of the first type to the bus controller by an authorized bus signal distributor/interface or transmitting a data packet of the second type to either the bus controller or ~~a~~ the first authorized function by ~~a~~ the second authorized function;

AMENDED SHEET

* C L M S *

REPLACEMENT SHEET
Date :.....16 APR 1998

e) receiving the data packet by the transmitting second function's bus interface, and forwarding the data packet to the bus interface's coupled bus signal distributor, if the data packet is of the second type;

f) receiving the data packet by zero or more intervening ones of the at least one bus signal distributor in a serial manner in accordance to the manner they are coupled, with each of the receiving bus signal distributor forwarding the data packet to the other bus signal distributor/interface coupled to the receiving bus signal distributor; and

g) receiving the data packet by either the bus signal distributor coupled to the bus controller and forwarding the data packet to the bus controller, or by the bus interface disposed on the peripheral of the first authorized function and notifying the first authorized function.

AMENDED SHEET