

PATENT SPECIFICATION

(11)

1 395 374

1 395 374

- (21) Application No. 35178/72 (22) Filed 27 July 1972
 (31) Convention Application No. 168 221 (32) Filed 2 Aug. 1971 in
 (33) United States of America (US)
 (44) Complete Specification published 29 May 1975
 (51) INT. CL.² G03B 19/18
 (52) Index at acceptance
 G2E A12 A20A1 A20C1 A20C2 A20C5 A20C7 A20C8
 (72) Inventors GERALD LEE JENKINS
 VERNON HENRY JUNGJOHANN
 EDGAR SAMUEL MARVIN
 NEIL GILBERT SEELY



(54) DRIVE MECHANISMS FOR A PHOTOGRAPHIC CAMERA

(71) We, EASTMAN KODAK COMPANY, a Company organized under the Laws of the State of New Jersey, United States of America of 343 State Street, Rochester, New York 14650, United States of America do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to a drive mechanism for a motion picture camera, particularly a drive mechanism which utilizes a single motor for simultaneously or independently driving both the film advancing mechanism and an adjustable zoom lens system.

It is an object of the present invention to provide an improved drive mechanism, for a motion picture camera, having a single motor wherein a zoom lens system and a film advance means in a camera may be selected for operation independently or simultaneously.

According to the present invention, there is provided a drive mechanism, for a motion picture camera, comprising a motor, first gear means drivable by the motor and selectively movable to provide an output for driving a cam to operate a pull-down claw, second gear means drivable by the motor and selectively movable to provide an output in either of two opposite directions for driving a lens element of a variable focus lens, either, neither or both of the outputs being selectable.

There is further provided a motion picture camera including a drive mechanism as above.

The invention will be described further, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is a fragmentary elevation view of a motion picture camera illustrating a drive mechanism according to the present inven-

[Price 33p]

tion and showing the parts of the mechanism in their rest position, i.e., when neither the film advance means nor the drive for the zoom lens system is being operated from the motor;

Fig. 2 is a view similar to Fig. 1 but showing certain parts in a position to which they are moved by the engagement of a camera operating means;

Fig. 3 is a view similar to Fig. 2 but showing the parts in the position assumed after further movement of the camera operating means;

Fig. 4 is a view similar to Fig. 1 but illustrates a coupling of the motor to the zoom lens adjusting apparatus;

Fig. 5 is a view similar to Fig. 1 but showing the gears for the film advance means in a position that occasionally occurs;

Fig. 6 is a perspective view of certain elements of the drive mechanism of the invention;

Fig. 7 is an electrical schematic diagram of a control circuit for the mechanism of the invention; and

Figs. 8-10 are fragmentary views illustrating a second embodiment of a drive mechanism of the invention.

As motion picture cameras are well known, the present description will be directed in particular to elements forming part of, or cooperating more directly with, the drive mechanism of the present invention, elements not specifically shown or described herein being understood to be selectable from those known in the art.

Referring now to the drawings in detail, a motion picture camera incorporating a drive mechanism of the present invention comprises casing or mechanism plates generally designated 10 and 11. Plate 10 supports a suitable zoom lens system generally designated 12. The lens systems illustrated by way of example comprises

50

55

60

65

75

80

85

90

three lens elements 14, 16, 18 which define an optical axis 20. The lens element 14 is normally stationary during adjustment of the zoom lens system but may be movable for focusing and certain manufacturing adjustments, if desired. At least one of the elements of the lens systems, for example the element 16, is supported by a lens mount 22 for movement along the optical axis 20 in each of two opposite directions for varying the magnification of the lens system. Lens mount 22 comprises a rack shown generally at 24 and having a plurality of teeth which are adapted to engage with teeth of a gear 26 mounted on a shaft 28. Also mounted on shaft 28 is a second gear 30 which is adapted to be driven from a suitable motor, such as an electric motor 32. The coupling of the motor to the gear 30 is effected by a plurality of gears including a gear 34 mounted on motor shaft 36 which is adapted to mesh with a relatively large gear 38 carried by a shaft 40. Shaft 40 is carried by a generally triangular rocker plate 42 which also carries two shafts 44 and 46 for gears 48 and 50, respectively. Gears 48 and 50 are in meshing engagement with each other, and gear 48 is adapted to be driven from a gear 52 which is mounted on shaft 40 and thereby driven from gear 38. Plate 42 is pivotably movable about the axis of shaft 40 to bring either gear 48 or gear 50 into engagement with gear 30 on shaft 28. Because gear 48 and gear 50 are in engagement with each other, they rotate in opposite directions so that the zoom lens system can be driven in either of two directions by selectively engaging gear 48 or gear 50 with gear 30. A clutch (not shown) can be provided in the gear train between the motor and the adjustable lens element 16 to permit the drive for the element 16 to remain engaged after the element has reached the extreme limits of its movement.

The pivotal movement of plate 42 is controlled by means of a rod 56 which has one end portion thereof pivotally connected at 58 to plate 42 in spaced relation to the axis of shaft 40. The other end portion of rod 56 is connected at 60 to an end portion of a lens operating control member 62, the latter being pivoted at 64 to mechanism plate 10. Thus, as shown in Fig. 4, when the right portion of the control member 62 is depressed the plate 42 swings about the axis of shaft 40 to bring gear 48 into engagement with gear 30 to drive the lens element 16 in one direction. Similarly, depression of the left portion of lens control member 62 swings plate 42 in the opposite direction to bring the gear 52 into engagement with the gear 30 thereby to reverse the movement of the movable lens element. Motor 32 can be energized to adjust the lens system

independently of operation of the film advance mechanism by closing of a normally open switch designated SW-1. Switch SW-1 includes a movable contact member 70 which is carried by a mid portion of rod 56 and is movable with the rod into engagement with either one of two stationary contacts 72a or 72b. Contacts 72a and 72b are electrically connected so that a circuit (described later) can be closed to the motor each time movable contact 70 is brought into engagement with either of the stationary contacts. Switch SW-1 is held in its normally open position by any suitable means, such as by a leaf spring 74 which engages the lens control member 62 to hold it in position shown in Fig. 1, thereby holding the switch in its open position.

The film advance mechanism for the camera includes a cam member shown generally at 80 which is positioned between mechanism plates 10 and 11 and is rotatably mounted on a cam shaft 82. In a manner well known in the art, one face of the cam (the face opposite from that shown in Figs. 1-6) can include both an edge cam surface 84 and a face cam surface (not shown). The face and edge cams are used for driving a claw in a generally rectangular path so that the claw enters a perforation of a film strip, advances the film strip a predetermined distance relative to an exposure aperture, and then withdraws from the film perforation and cycles to enter the next perforation, thereby intermittently advancing the film past the exposure aperture camera. Cam 80 has a plurality of teeth 86 about its outer periphery which are adapted to be engaged with gears for driving the cam from motor 32. The face of cam 80 opposite from the face and edge cams has a recess 88 formed therein comprising a generally circular portion 88a which is coaxial with shaft 82 and an elongate extension or projecting portion 88b which communicates with portion 88a but is spaced from the axis of shaft 82 by a distance greater than the radius of circular portion of 88a. The purpose of the recess will be described later.

Cam 80 is couplable to motor 32 by a gear train including two identical gears 90 and 92 which are rotatably mounted on a plate 94 pivotal about the axis of shaft 36. The gears are spaced from each other so that they are not in meshing engagement with each other. Gear 90 meshes with gear 34 on the motor shaft 36 and gear 92 meshes with a smaller gear 96 on the motor shaft. Gears 90 and 92 are aligned in a common plane with the teeth 86 on cam 80 so that either gear 90 or gear 92 can be brought into meshing engagement with the teeth on the cam in response to pivotal movement of plate 94. Because gear 96 is smaller in diameter than the gear 34, cam

80 is rotated at a faster rate by gear 90 than by gear 92. Of course, the particular number of rpm's imparted to the cam by each gear can be determined by the gear ratios and motor speed. In a preferred embodiment, cams 90 and 92 are driven at rates which rotate cams 80 to effect operation of the associated film pull down claw (not shown) at rates of either 9 frames per second or 18 frames per second, respectively. Both gears 90 and 92 can be disengaged from gear teeth 86 as shown in Fig. 1 when the camera is not in operation or when film is not being advanced, thereby permitting the single motor 32 to be used for driving the zoom lens mechanism as described hereinbefore. Also, it will be apparent that the zoom lens mechanism can be operated in the manner described even when film is being advanced through the camera since the coupling of the motor to the cam 80 is totally independent of the coupling of the motor to the zoom lens drive system.

25 Plate 94 has two tabs for lugs 95 and 97 which project outwardly away from the face of the plate opposite from the gears 90 and 92. These tabs are located at the ends of fingers on the plate. A speed control member, generally designated 100, is substantially C-shaped in configuration, having a substantially semi-circular opening 100a. Notches 102 and 104 in the speed control member face into opening 100a from opposite sides thereof, and are of sufficient size to receive the tabs 95 and 97, respectively. As is apparent in Figs. 1-5, the size of the opening 100a is sufficiently large so that only one tab 95 or 97 at a time can be positioned in its respective notch in the control member. However, the control member is adjustable in an up-and-down direction (as viewed in the drawings) so that either of the tabs can be selectively positioned in its respective notch. The mounting of the control member which permits such movement comprises a pair of elongate guide slots 106 and 108 in the control member which receive guide pins 110 and 112 respectively.

50 The guide pins are mounted on and project upwardly from a face of a slider assembly generally designated 114. Control member 100 can be held in either of its two adjusted positions by means of a flexible, generally V-shaped member 116 which is mounted on the slider assembly 114 and which is adapted to engage each of a plurality of notches or detents 118 in a side edge of the control member. The control member can be manually moved by means of a integral knob portion 120 that is conveniently located at the exterior of the camera. Suitable indicators 122 and 124 may be provided to designate to the camera operator the speed at which the camera is set to operate.

Control member 100 and slider assembly 114 are located above the upper surface of mechanism plate 11. Slider assembly 114 is mounted on mechanism plate 11 by means of two spaced guide pins 130 and 132 which project from plate 11 into two elongate guide slots 134 and 136, respectively in the slider assembly. This mounting permits the entire assembly 114 with the control member 100 thereon to be shifted to the right from the position shown in Fig. 1 through the position shown in Fig. 2 to the position shown in Fig. 3. During such movement of assembly 114 control member 100 engages one or the other of the tabs 95 or 97 to effect pivotal movement of plate 94 and thereby bringing one of the gears 90 or 92 into meshing engagement with the gear teeth 86 on the cam. This is illustrated in Figs. 1-3 for movement of gear 92 into engagement with cam gear teeth. Gear 90 is moved into engagement with the cam gear teeth by shifting control member 100 downwardly from its Fig. 1 position and then moving slider assembly 114 to the right.

In order to initiate advancement of film through the camera the camera operator moves a trigger lever 140 to the right as viewed in the drawings. This can be effected by manually depressing the left end portion of the lever which is conveniently located at the exterior of the camera. Lever 140 is mounted for sliding movement with respect to the mechanism plate 11 by a pair of mounting pins 142 and 144 on plate 11 which project upwardly into elongate slots 146 and 148, respectively, in lever 140. Lever 140 is urged to the position as shown in Fig. 1 by a tension spring 150 which is stretched between the pin 142 and a tab 152 on the lever.

Lever 140 has a finger portion 154 at its right end that is offset upwardly from other portions of the lever, and a lug 156 on the finger is adapted to engage one side edge of a cooperating, downwardly projecting finger portion 158 on the slider assembly 114. Thus the biasing force of spring 150 is imparted through lug 156 to finger 158 to urge the slider assembly 114 into the position illustrated in Fig. 1. Lever 140 and assembly 114 are resiliently connected together for movement to the right from the Fig. 1 position to the Fig. 3 position by means of a tension spring 160 which is connected to and stretched between the finger portion 154 of lever 140 and the finger portion 158 of assembly 114. Thus depression of trigger 140 (movement to the right) produces a biasing force urging the assembly 114 to the right; however, lever 140 can be moved to the right by the operator without corresponding movement of assembly 114 by simply stretching or fur-

ther tensioning spring, 160.

As is well known in the art, it is desirable to stop the shutter (not shown) of the camera in a position for blocking passage of light from the lens system to film located in the exposure plane of the camera, thereby avoiding continuous exposure of film when the camera is not in use. The illustrated structure for accomplishing this comprises a lever 162 which is mounted on pin 132 beneath slider 114 for pivotal movement about the axis of the pin. Projecting downwardly from one side edge of the lever 162 is a lug 164 which extends through an opening 165 in plate 11 and into the straight portion 88b of the recess in the cam 80 when the parts are positioned as illustrated in Fig. 1. The stop 164 interferes with rotation of the cam, thereby preventing rotation of shaft 82 on which the shutter is mounted. However, movement of stop 164 to the position shown in Fig. 3, where it is in alignment with the circular portion 88a of the recess in the cam, permits unrestricted rotation of the cam (and thus shaft 82) for advancement of the film through the camera. Lever 162 normally is biased to the position shown in Fig. 1 by a spring 166 which is connected to the lever and to plate 11. However, the lever can be swung counterclockwise about the axis of pin 132 in response to engagement between the finger portion of 154 of the trigger lever 140 and a flange portion 168 on the end portion of lever 162 opposite from stop 164. This movement is best illustrated by comparison of the phantom-line and solid-line positions for lever 162 in Fig. 3.

When trigger 140 is released to terminate a filming sequence, rotation of the cam should be continued until the shutter returns to a position along the light path between the lens system of the camera and the film plane. Also, motor 32 should be de-energized when stop 164 is in recess portion 88b. This is accomplished by cooperation between stop 164 and the circular recess 88a, and by operation of a second switch SW-2. Switch SW-2 comprises a first contact member 170 formed by a flange on the end portion of lever 162 and by a flexible switch contact 172 which is connected in a circuit to the motor and to a power source as explained later. The contact members 170 and 172 are positioned with respect to each other so that switch SW-2 is closed as stop 164 moves from the recess portion 88b into the circular recess portion 88a so that the switch SW-2 can complete a circuit to the motor to initiate operation of the motor and rotation of the cam at approximately the same time the stop enters the circular recess portion. Operation of the motor will continue until 65 switch SW-2 is opened, and this occurs

when (1) trigger finger 154 moves to the left (away from flange 168), and (2) the cam rotates to a position where stop 164 is aligned with the recess 88b, thereby permitting movement of the stop into the elongated recess portion 88b under the biasing force of spring 166.

While stop 164 maintains switch SW-2 in a closed condition until the shutter returns to the correct position for terminating exposure of the film, it is also necessary to maintain engagement between one of the gears 90 and 92 and the gear teeth 86 on the cam after the trigger lever 140 has been released by the camera operator. Failure to do this would result in the motor remaining energized because switch SW-2 was closed, but the motor would be ineffective to continue driving of the cam to bring the stop to the position where it can return to the elongated portion of the recess and thereby shut off the switch in the motor. Engagement between one of the gears 90 and 92 and the gear teeth 86 is assured by maintaining the slider assembly 114 in the position illustrated in Fig. 3. This is accomplished by providing a cam location interlock flange or lug 176 on slider assembly 114 which projects downward from its bottom surface (as illustrated in Fig. 1-4), and by the provision of a cooperating latching surface 178 on an edge of the lever 162. The lug 176 and latch surface 178 are located with respect to each other so that the slider assembly can be moved freely from the position shown in Fig. 1 to the position shown in Fig. 2 when the lever is in the position illustrated in those views wherein the stop 164 is in the elongate portion 88b of the recess. However, when the lever 162 moves to the position illustrated in Fig. 3, the latch surface 178 swings into the path of movement of the lug 176 to prevent return movement of the slider assembly 114 to the position shown in Fig. 1. This blocking relation ends when the lever 162 returns to its Fig. 1 position, thereby moving surface 178 out of the path of lug 176.

Lever 162 has an edge 177 adjacent latch surface 178 which is positioned with respect to lug 176 to prevent movement of the lever to its Fig. 3 position until the slider moves part of the way from its Fig. 1 position to its Fig. 3 position. This ensures the closing of a switch SW-3 (described later) before lever 162 can move to close switch SW-2.

Fig. 7 illustrates an electrical schematic diagram suitable for interconnecting the various electrically controlled portions of the camera to effect the mode of operation described herein. Current is provided from a suitable source of electric power, such as a battery 190. A circuit is coupled from 130

the battery through motor 32 whenever switch SW-2 is closed. Assuming an exposure control system is provided for the camera, it is desirable to energize the exposure control system prior to the time switch SW-2 is closed to begin operation of the pull down mechanism. The switch designated SW-3 is provided for this purpose. The switch is connected in a circuit including battery 190 and the exposure control system designated 192, the circuit being connected in parallel to motor 32 and switch SW-2. The desired sequence of operation is effected by providing for closure of switch SW-3 shortly before closing of switch SW-2. As illustrated in Figs. 1-4, switch SW-3 includes a fixed contact 194 and a movable contact 196, the switch normally being open when the camera is not being operated due to engagement between the left end of slider assembly 114 and the movable contact 196. As the slider assembly begins its movement from its Fig. 1 to its Fig. 2 position, and before the assembly reaches a position where lug 176 is out of the way of edge 177 of lever 162, the movable contact 196 is closed to the fixed contact 194 to complete the circuit to the exposure control system. This permits correct exposure of the first frame of film.

Switch SW-1 is connected in parallel to switches SW-2 and SW-3 and to the exposure control system 192. Switch SW-1 is connected in a circuit which includes motor 32 and battery 190 so that the closing of switch SW-1 normally operates the motor to drive the gears that can be coupled to the zoom drive mechanism.

In order to facilitate engagement between the gears 90 or 92 and the gear teeth 86 on the cam, it is preferred that the gears not be rotated during the engagement of such gears. Thus, of course, requires that the motor be de-energized. This is assured by the provision of a switch designated SW-4 in Figs. 1-5 and 7 which is normally closed but can be opened just prior to engagement of gears 90 or 92 with the gear teeth on the cam. As shown in Figs. 1-4, this is accomplished by utilizing the movable contact 196 forming part of switch SW-3 and another fixed contact designated 198, and locating the contact 198 with respect to movable contact 196 so that switch SW-4 is normally closed when the slider assembly is in its Fig. 1 position. Switch SW-4 will remain closed until the slider assembly begins its movement from the Fig. 1 position and reaches its Fig. 2 position at which time the movable contact 196 becomes disengaged from fixed contact 198 and moves in contact with the contact 194 to close switch SW-3. With switch SW-4 open, the motor can only be ener-

gized by closing switch SW-2, and this normally does not occur until after the gears 90, 82 mesh with gear teeth 86.

After switch SW-4 opens, and before switch SW-2 closes, there is an instant of time when the camera operator cannot operate the zoom lens drive mechanism even though operator 62 is depressed. This, however, is ordinarily an extremely brief period of time, and may not even be noticed by the camera operator. Thus if the zoom lens drive is engaged and the motor running at the time the operator moves lever 140 to initiate advancement of film, switch SW-4 opens to briefly stop motor 32 but switch SW-2 normally is closed an instant later to again start the motor. Thus if the operator continues to press the zoom control member 62, the zoom lens will momentarily pause and then continue its movement. Of course, after the switch SW-2 is closed, switch SW-4 may remain open since there is no longer any need to use switch SW-1 to adjust the lens system. In other words, after the motor is energized through switch SW-2, adjustment of the lens system requires only a mechanical operation that is independent of the closing of switch SW-1.

The operation of the camera including a drive mechanism of the invention will now be summarized. Initially it will be assumed that the various parts are in the position illustrated in Fig. 1 where both the zoom lens drive mechanism and the film advance mechanism are at rest and the exposure control system is de-energized. Thus switches SW-1, SW-2, and SW-3 are open and switch SW-4 is closed. Referring to Fig. 4, if the camera operator wishes to adjust the zoom lens mechanism without effecting advancement of film through the camera, the control member 62 is depressed to rock plate 42 and to close switch SW-1, thereby energizing the motor and driving gears 48 and 50 through the gear train described hereinbefore. The zoom drive mechanism is then driven in either one of two opposite directions, depending upon which one of the gears 48 or 50 is engaged with gear 30. (Fig. 4 illustrates gear 40 engaged with gear 30.) Movement of the zoom lens mechanism continues until the control member is released or until the rack 24 reaches one extreme end of its movement where the clutch (not shown) in the gear train begins to slip.

Assuming now that the various parts are in the position illustrated in Fig. 1 and that the camera operator desires to operate the film pull down mechanism without adjustment of the zoom lens. The operator first determines the rate at which film will be advanced in the camera by moving the speed control member 100 to the position shown in Figs. 1-5 or to its other position

(not shown) wherein tab 97 is positioned within the confines of notch 104. Then the operator depresses the trigger lever 140 to effect its movement from the position shown in Fig. 1 through the position shown in Fig. 2 to the position shown in Fig. 3. As this occurs, spring 160 biases the slider assembly 114 to the right from its Fig. 1 position for opening switch SW-4 and closing switch SW-3, thereby normally to energize the exposure control system before exposure of film begins. This travel of the lever 140 brings the finger portion 154 thereof into engagement with the portion 168 of lever 162 to urge lever 162 about the axis of pin 132. However, movement of the lever 162 cannot occur (due to the tab 176 on the slider assembly) until the slider assembly 114 moves to the right to close switch SW-3. After tab 176 is moved to the right with the slider assembly to a point that permits pivotal movement of the lever 162, the lever swings to the position shown in solid lines in Fig. 3 against the bias of spring 166 to bring the stop 164 out of the elongated portion 88b of the recess and into the circular portion 88a. Simultaneously, switch SW-2 is closed, thereby energizing the motor 32 to drive gears 90 and 92.

As the slider assembly 114 moves to the right it engages one of the tabs 95 or 97 on plate 94, thereby swinging the plate about the axis of shaft 36 to bring gear 92 or gear 90 into engagement with the teeth 86 for driving the film pull down mechanism. Normally, the gears become engaged before the closing of switch SW-2 to avoid any difficulty that might result from trying to mesh gear 90 or 92 while they are rotating and while the gear teeth 86 are stationary. With motor 32 running and film being advanced in the manner described, the camera operator can also operate the zoom mechanism from the motor by manipulating the control member 62 to bring gear 48 or gear 50 into engagement with gear 30. This can be accomplished even though switch SW-4 is open because the motor 32 is being driven through switch SW-2.

When lever 140 is released by the operator, it is urged to its Fig. 1 position by spring 150. Lever 162 can then return to its Fig. 1 position. Slider 114 is moved to the left by tab 156 on lever 140 which engages the slider finger 158 and moves the slider with the lever.

Ordinarily the teeth 86 on cam 80 and the teeth on gears 90 and 92 will be brought into meshing engagement with each other in response to the movement of plate 94 in the manner described hereinbefore. However, the gear teeth may be positioned with respect to each other so that the gear teeth

do not mesh, i.e., the outer extremities of the teeth 86 are engaged by the outer extremities of the teeth on gear 90 and 92, such being illustrated in Fig. 5 of the drawings. This relative position between the gear teeth could be changed by releasing the lever 140 and engaging the mechanism for adjusting zoom lens system since such adjustment also effects rotation of gears 90 and 92. However, with the mechanism of the invention this is not necessary because, after initial movement of slider assembly 114, the lever 140 can engage and move lever 162 to close switch SW-2 and energize the motor. When the motor is energized, gears 90 and 92 are rotated to bring the gear teeth into meshing engagement with teeth 86. This is made possible by the spring 160 which establishes an elastic connection between lever 140 and slider assembly 114.

Referring now to the embodiment of the invention illustrated in Figs. 8-10, a slider assembly generally designated 210 is similar to the assembly 114 described hereinbefore. Thus assembly 210 is resiliently urged to the right by spring means (such as spring 160) in response to the camera operator depressing lever 140, and the assembly is urged to the left upon release of lever 140 by the biasing force exerted by a spring shown diagrammatically at 212. Movement of the slider assembly to the right is limited by a stop 214 which projects through an opening 216 in slider assembly 210, the stop being mounted on mechanism plate 11, for example. Movement of the slider assembly to the position illustrated in Fig. 9 closes a switch designated SW-3a comprising a contact member 218 mounted on a suitable support member 220 and a contact member defined by the right end 222 of the slider assembly. Switch SW-3a is connected in a circuit to the exposure control system of the camera in the manner described hereinbefore in connection with switch SW-3.

Slider assembly 210 has a notch 224 which opens to its left end and is elongated in the same direction as the slider assembly normally moves. A lever 226 is mounted on a pin 228 for pivotal movement about the axis of the pin. A tab 230 at one end of lever 226 projects into the notch 224 in the slider assembly when the slider assembly is in the position illustrated in Fig. 8. The edge 224a of notch 224 prevents counterclockwise movement of the lever 226 about pin 228 until such time as the slider assembly moves to the right past its Fig. 9 position to its Fig. 10 position. The length of notch 224 in slider assembly 210 is such that the switch SW-3a is closed before the tab 230 is clear of the left end of the notch. The lever is urged upwardly by a spring diagrammatically shown at 232.

Another lever 234 is mounted on pin 228 beneath lever 226 for pivotal movement about the pin. Lever 234 comprises a tab 236 defining a switch contact which is engageable with another switch contact 238 mounted on support 220 when the lever swings from its Fig. 8 to its Fig. 10 position. Contacts 236 and 238 define a switch SW-2a that can be connected in a circuit to motor 32 in a manner shown for switch SW-2 in Fig. 7. A lug 237 on lever 234 projects from the lower side edge of the lever into the plane of lever 236 and adjacent the upper edge of lever 236 so that the lever 226 is moved clockwise with lever 234 as the lever 234 is swung from its Fig. 10 to its Fig. 8 position.

Lever 234 includes a tab 240 which projects downwardly through opening 165 in plate 11. Tab 240, like tab 164, cooperates with recessed portion 88 in cam 80 to permit the cam to stop only when the shutter is across the optical path and between the lens system and the film.

Lever 234 has a flange 239 projecting into the path of movement of finger 154 of the trigger lever 140 so that the lever is swung from its Fig. 8 to its Fig. 10 position when the trigger lever is depressed. The various parts are arranged with respect to each other so that normally the slider 210 moves to close switch SW-2a, then lever 234 is swung to its Fig. 10 position (closing SW-2a), and then lever 226 is released by slider 210 and swung by spring 232 to the position shown in Fig. 10 wherein lever 234 blocks movement of slider 210 to the left (and thereby prevents uncoupling of the gear drive to cam 80) until tab 240 enters recess portion 88b on the cam under the influence of spring 244.

When trigger lever 140 is released at the end of a sequence of filming, slider assembly 210 is urged to left by spring 212. Such movement of the slider assembly is prevented initially due to the engagement between the tab 230 on lever 236 and the edge 233 of the slider assembly immediately above the notch 224. However, when the lug 240 on lever 234 becomes aligned with the portion 88b of the recess in the cam, lever 234 swings to the right under the influence of spring 244 to bring the tab into the recess portion 88b. As this clockwise motion of lever 234 occurs, switch SW-2a is opened, and the lug 237 on lever 234 moves lever 226 downwardly from its Fig. 10 position to its Fig. 8 position, thereby bringing the tab 230 into alignment with the notch 224. This releases the slider assembly 210 and permits it to move to the left under the biasing force exerted by spring 212. Thus the slider assembly returns to its Fig. 8 position and switch SW-3a is opened. This movement of the

slider assembly disengages gears 90 or 92 from the gear teeth on the cam member.

Because levers 226 and 234 are independently movable in a counterclockwise direction as explained hereinbefore, lever 234 can be swung to the position illustrated in Fig. 10 to close switch SW-2a and thereby energize motor 32 for driving gears 90 or 92 even in those rare situations when the tops of the gear teeth engages each other as shown in Fig. 5 rather than mesh in a normal driving relation. In the absence of such independent movement, the slider assembly 210 could not move to the right by a sufficient distance to permit lever 226 to move upwardly until such time as the gears properly meshed. This avoids the necessity of having to drive gear 90 or 92 by operation of the zoom drive mechanism in order to adjust the relative position of gear teeth with the teeth 86 on the cam.

The invention has been described in detail with particular reference to preferred embodiments thereof, but it will be understood that variations and modifications can be effected within the scope of the invention as defined in the appended claims.

WHAT WE CLAIM IS:—

1. A drive mechanism, for a motion picture camera, comprising a motor, first gear means drivable by the motor and selectively movable to provide an output for driving a cam to operate a pull-down claw, second gear means drivable by the motor and selectively movable to provide an output for driving a cam to operate a pull-down claw, second gear means drivable by the motor and selectively movable to provide an output in either of two opposite directions for driving a lens element of a variable focus lens, either, neither or both of the outputs being selectable.

2. A mechanism as claimed in Claim 1 wherein the first gear means comprises first and second gears on a drive shaft of the motor respectively engaging third and fourth gears mounted for alternate engagement with peripheral gear teeth on the cam.

3. A mechanism as claimed in Claim 2 wherein the third and fourth gears are mounted on a plate pivotal about the axis of the drive shaft, the plate having first, second and third positions corresponding respectively to the third gear, no gear, and the fourth gear engaging with the cam.

4. A mechanism as claimed in Claim 3 including a manually operable selector for determining which of the third and fourth gears will be selected.

5. A mechanism as claimed in any preceding claim wherein the second gear means comprises a fixedly mounted gear in constant mesh with a drive gear on the motor shaft, a first movably mounted gear in constant mesh with and driven by the fixedly

Another lever 234 is mounted on pin 228 beneath lever 226 for pivotal movement about the pin. Lever 234 comprises a tab 236 defining a switch contact which is engageable with another switch contact 238 mounted on support 220 when the lever swings from its Fig. 8 to its Fig. 10 position. Contacts 236 and 238 define a switch SW-2a that can be connected in a circuit to motor 32 in a manner shown for switch SW-2 in Fig. 7. A lug 237 on lever 234 projects from the lower side edge of the lever into the plane of lever 236 and adjacent the upper edge of lever 236 so that the lever 226 is moved clockwise with lever 234 as the lever 234 is swung from its Fig. 10 to its Fig. 8 position.

Lever 234 includes a tab 240 which projects downwardly through opening 165 in plate 11. Tab 240, like tab 164, co-operates with recessed portion 88 in cam 80 to permit the cam to stop only when the shutter is across the optical path and between the lens system and the film.

Lever 234 has a flange 239 projecting into the path of movement of finger 154 of the trigger lever 140 so that the lever is swung from its Fig. 8 to its Fig. 10 position when the trigger lever is depressed. The various parts are arranged with respect to each other so that normally the slider 210 moves to close switch SW-2a, then lever 234 is swung to its Fig. 10 position (closing SW-2a), and then lever 226 is released by slider 210 and swung by spring 232 to the position shown in Fig. 10 wherein lever 234 blocks movement of slider 210 to the left (and thereby prevents uncoupling of the gear drive to cam 80) until tab 240 enters recess portion 88b on the cam under the influence of spring 244.

When trigger lever 140 is released at the end of a sequence of filming, slider assembly 210 is urged to left by spring 212. Such movement of the slider assembly is prevented initially due to the engagement between the tab 230 on lever 236 and the edge 233 of the slider assembly immediately above the notch 224. However, when the lug 240 on lever 234 becomes aligned with the portion 88b of the recess in the cam, lever 234 swings to the right under the influence of spring 244 to bring the tab into the recess portion 88b. As this clockwise motion of lever 234 occurs, switch SW-2a is opened, and the lug 237 on lever 234 moves lever 226 downwardly from its Fig. 10 position to its Fig. 8 position, thereby bringing the tab 230 into alignment with the notch 224. This releases the slider assembly 210 and permits it to move to the left under the biasing force exerted by spring 212. Thus the slider assembly returns to its Fig. 8 position and switch SW-3a is opened. This movement of the

slider assembly disengages gears 90 or 92 from the gear teeth on the cam member.

Because levers 226 and 234 are independently movable in a counterclockwise direction as explained hereinbefore, lever 234 can be swung to the position illustrated in Fig. 10 to close switch SW-2a and thereby energize motor 32 for driving gears 90 or 92 even in those rare situations when the tops of the gear teeth engages each other as shown in Fig. 5 rather than mesh in a normal driving relation. In the absence of such independent movement, the slider assembly 210 could not move to the right by a sufficient distance to permit lever 226 to move upwardly until such time as the gears properly meshed. This avoids the necessity of having to drive gear 90 or 92 by operation of the zoom drive mechanism in order to adjust the relative position of gear teeth with the teeth 86 on the cam.

The invention has been described in detail with particular reference to preferred embodiments thereof, but it will be understood that variations and modifications can be effected within the scope of the invention as defined in the appended claims.

WHAT WE CLAIM IS:—

1. A drive mechanism, for a motion picture camera, comprising a motor, first gear means drivable by the motor and selectively movable to provide an output for driving a cam to operate a pull-down claw, second gear means drivable by the motor and selectively movable to provide an output for driving a cam to operate a pull-down claw, second gear means drivable by the motor and selectively movable to provide an output in either of two opposite directions for driving a lens element of a variable focus lens, either, neither or both of the outputs being selectable.

2. A mechanism as claimed in Claim 1 wherein the first gear means comprises first and second gears on a drive shaft of the motor respectively engaging third and fourth gears mounted for alternate engagement with peripheral gear teeth on the cam.

3. A mechanism as claimed in Claim 2 wherein the third and fourth gears are mounted on a plate pivotal about the axis of the drive shaft, the plate having first, second and third positions corresponding respectively to the third gear, no gear, and the fourth gear engaging with the cam.

4. A mechanism as claimed in Claim 3 including a manually operable selector for determining which of the third and fourth gears will be selected.

5. A mechanism as claimed in any preceding claim wherein the second gear means comprises a fixedly mounted gear in constant mesh with a drive gear on the motor shaft, a first movably mounted gear in constant mesh with and driven by the fixedly



mounted gear and a second movably mounted gear in constant mesh with the first movably mounted gear.

6. A mechanism as claimed in Claim 5 wherein the first and second movably mounted gears are mounted on a plate pivotally mounted on the axis of the fixedly mounted gear, the plate having three positions in a first and third of which, respectively, the first and second movably mounted gears are in engagement with a fixed gear for driving a lens element.

7. A mechanism as claimed in Claim 6 further including a rack to which the fixed gear for driving the lens element is connected, the rack engaging the fixed gear to be driven thereby, depending upon the direction of rotation of the fixed gear, in either of the opposite directions.

8. A mechanism as claimed in Claim 6 or 7 further including a manually operable control member connected to the plate carrying the first and second movably mounted gears, the control member being movable between a first position wherein the plate is pivoted to bring the first movably mounted gear into engagement with the fixed gear to rotate the same in a first direction, a second position corresponding to the rest position in which neither the first nor the second movably mounted gear engages the fixed gear, and a third position in which the plate is pivoted to bring the second movably mounted gear into engagement with the second gear to rotate the same in the opposite direction.

9. A mechanism as claimed in Claim 8 including a normally open switch closable in the first or third position of the control member to energize the motor.

10. A motion picture camera including a mechanism as claimed in any preceding claim.

11. A camera as claimed in Claim 10 further including a cam driven by the first gear means, a release member arranged to be moved manually to initiate operation of a pull-down claw driven by the cam, and a slider assembly movable upon manual movement of the release member to move the first gear means into engagement with the cam.

12. A camera as claimed in Claim 11 as appendant to Claim 4 wherein the manually operable selector is movably transversely of and with the slider assembly, the selector having means for engaging a first or a second projection on the plate so that movement of the slider assembly pivots the plate thereby to move the third or the fourth gear into engagement with the cam.

13. A camera as claimed in Claim 11 or

12 wherein the cam is arranged to drive a shutter blade having a rest position obstructing the optical axis of the camera, the cam having a concentrically arranged annular rebate with a radially extending recess, there being a lever bearing a stop locatable in the recess to arrest the cam in a position corresponding to the rest position of the shutter blade and pivotable by the release member, against spring means, into alignment with the annular rebate to permit the cam to rotate.

14. A camera as claimed in Claim 13 further including switch means closed by the lever, when the stop is in the annular rebate, to connect the motor to a source of electricity and opened upon movement of the stop into the radial recess to deenergize the motor.

15. A camera as claimed in Claim 13 or 14 further including an interlock between the slider assembly and the lever to prevent movement of the stop from the recess until the third or fourth gear has engaged with the cam.

16. A camera as claimed in Claim 13 or 14 including a further interlock preventing return of the slider assembly to a rest position until the stop has entered the recess.

17. A camera as claimed in Claim 11 or any claim appendant thereto including second switch means operated by the slider assembly to energize an automatic exposure control prior to engagement of the first gear means with the cam.

18. A camera as claimed in Claim 17 wherein the second switch means further includes normally closed contacts serially connected with normally open contacts of a third switch means for energizing the motor.

19. A camera as claimed in Claim 9 or any claim appendant thereto and Claim 18 wherein the normally open switch constitutes the third switch means so that the third switch means is ineffective when the slider assembly has been moved from its rest position.

20. A drive mechanism for a motion picture camera substantially as hereinbefore described with reference to and as illustrated in Figs. 1 to 7 or Figs. 1 to 7 as modified by Figs. 8 to 10 of the accompanying drawings.

21. A motion picture camera substantially as hereinbefore described with reference to and as illustrated in Figs. 1 to 7 or Figs. 1 to 7 as modified by Figs. 8 to 10 of the accompanying drawings.

L. A. TRANGMAR, B.Sc., C.P.A.
Agents for the Applicants.

