



- (51) **International Patent Classification:**
H04L 12/46 (2006.01)
- (21) **International Application Number:**
PCT/IL2012/050321
- (22) **International Filing Date:**
22 August 2012 (22.08.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
214830 25 August 2011 (25.08.2011) IL
- (71) **Applicant (for all designated States except US):** ELTA SYSTEMS LTD. [IL/IL]; 100 Yitzchak Hanassi Blvd. P.O.B. 330, 77102 Ashdod (IL).
- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** WEINSBERG, Udi [IL/IL]; 5/16 Citrin St., 77067 Ashdod (IL).
- (74) **Agent:** REINHOLD COHN AND PARTNERS; P.O.Box 13239, 61131 Tel Aviv (IL).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

- (88)
- Date of publication of the international search report:**

4 July 2013


(54) **Title:** NETWORK ENVIRONMENT SEPARATION

Fig. 2

(57) **Abstract:** The presently disclosed subject matter includes, inter alia, a separation module being operatively connectible to a network device operable to facilitate data communication in a communication network, the separation module being configured to control data communication in the communication network, the separation module being assigned with a network-id associating the separation module with a given network environment; the separation module being further configured to tag a data packet received by the network device from a first direction, in order to associate the data packet with a given network environment; and determine whether a tag, associated with a data packet received by the network device from a second direction, is compatible with the assigned network-id, and if it is, remove the tag from the data packet and allow transmission of the data packet.