

9

Description

This invention relates to a textile supply package for feeding a plurality of elastomeric strands to a machine for making fabrics, covered yarns or the like. More particularly, the invention concerns such a package which comprises a bundle of elastomeric strands around which is sewn a connected series of chain stitches.

In most weaving, knitting or yarn-covering operations, large numbers of strands are fed simultaneously to a textile machine. Usually, the strands are supplied from a creel frame on which numerous yarn packages are mounted. Each package contains one wound-up strand. Another conventional method involves supplying the fabric-making machine with a multiplicity of strands from one large beam. These known strand supply devices usually are very large and require much floor space. To reduce these space requirements, suggestions have been made that the required number of strands be supplied in the form of a knitted package from which the strands can be unravelled and fed to the fabric-making machine. Rupprecht, U.S. Patent 3,827,261 discloses one such knit package made of spandex strands. However, the speed with which packages of spandex yarns can be fabricated is limited by the slow speed of the knitting machines on which the packages must be made. The slow speeds of fabrication add to the cost of the unravellable package, as well as to the cost of the fabrics made therefrom.

It is also known to supply strands of slitted rubber in the form of a package wherein the strands have been readhered to each other and then dusted with talc. However, this method is not generally applicable to other elastomeric yarns.

The purpose of the present invention is to provide an elastomeric yarn supply package which can be made simply, economically and at high speeds and which is especially useful with spandex filaments.

The present invention provides an elastomeric yarn supply package comprising a bundle of substantially parallel elastomeric strands held together by a succession of connected chain stitches extending along the length of the said bundle wherein the said chain stitches are formed of a non-elastomeric thread and are capable of being unravelled from the bundle to free the elastomeric strands from each other, the spacing between successive chain stitches being from 1 to 30 centimeters, preferably 1.8 to 8 centimeters. Preferably the chain stitches are formed with one nonelastomeric strand.

The invention will be more readily understood by reference to the drawings wherein:

Figure 1 depicts a length of the supply package of the invention; and

Figure 2 is a schematic representation of a succession of chain stitches suitable for use in making the supply package.

As shown in Figure 1, a plurality of substantially parallel elastomeric strands 10 are held together

as a bundle by a single nonelastomeric thread 20 which forms a succession of connected chain stitches around the bundle. The succession of stitches extends along substantially the entire length of the bundle. For ease of visualization, the stitches are depicted looser than in actual practice.

The supply package of the invention can be handled without adjacent lengths of the bundle becoming entangled, as for example, when the supply package is shipped coiled up in a container. When it is necessary to release the individual elastomeric strands from the bundle for feeding to a textile machine, the succession of chain stitches is unravelled by pulling out the stitches in the reverse order of their fabrication.

The size and number of elastomeric strands 10 in the bundle can vary widely; for example, from less than 80 to over 4500 dtex and from fewer than six to over several hundred. The choice depends almost entirely on the requirements of the textile product being made.

There is also considerable latitude in the choice of nonelastomeric thread 20. Threads of natural or synthetic fibers, monofilaments, textured yarns, and the like are generally satisfactory. Usually, a low denier, inexpensive sewing thread is used, such as a 16-2 c.c. polyester or a 36-4 c.c. cotton thread ("c.c." means cotton count). A textured yarn is sometimes preferred for thread 20 when a tighter succession of chain stitches is required around the bundle.

The spacing between successive chain stitches, shown as "S" in the drawings, usually can be selected from a wide range of values. Stitch spacings of 30 cm or more, or of 1 cm or less can be used, as long as the elastomeric strands are held together well enough for handling in subsequent operations. However, average spacings of less than 1 cm usually are avoided in the interest of economy. Larger spacings employ less thread for the chain stitches and, at any given stitching speed, permit more meters of package length to be fabricated per unit time. The preferred range of average spacings is from 1.8 to 8 cm.

Figure 2 depicts a typical chain stitch which is suitable for use in the supply packages of the present invention. The stitches shown in Figure 2 are of Stitch Type 501 (Federal Standard No. 751a, January 25, 1965) and can be formed with a conventional chain-stitching, sewing machine with one needle thread. The formation of two successive stitches can be followed in Figure 2, by progressing in the direction of stitch formation indicated by the arrow, from A through J for one stitch and then from A' through J' for the second stitch. As can be seen from the figure, the succession of stitches can be unravelled by pulling on the last-formed link in the chain, thereby reversing the chain-forming process. Other chain stitches than the one just discussed can be used in the present invention, such as those that require two threads to form the chain stitches. Also, two or more series of Type 501 chain stitches could be formed around a single bundle of strands. How-

the simpler and more economical use of one single-thread series of chain stitches is preferred.

A conventional, industrial, chain-stitching sewing machine, such as an "over-edge" Merrow Model 70 Sewing Machine (made by the Merrow Machine Company of Hartford, Connecticut), is suitable with minor modifications, for use in making the elastomeric strand supply package of the present invention. The machine ordinarily is designed to sew two pieces of fabric together or to sew closures for bags. Usually, the machine operates with relatively small stitch spacings (e.g., 2 cm or less) and at rates of about 1800 to 2250 stitches per minute. Thus, with a 2-cm stitch spacing, the machine can produce supply packages of the invention at rates of about 45 meters per minute. Increases in the speed of producing supply packages can be achieved by increasing the stitch spacing.

A convenient method for modifying an industrial sewing machine of the above-described type for use in preparing the supply packages involves the attachment of a "feed tube" and the substitution of puller rolls for the feed mechanism of the machine. The feed tube can be a short tube through which the elastomeric strands are gathered together and fed through the sewing machine. The tube is placed between the upper and lower looper positions of the sewing machine such that the tube projects about 2-1/2 cm behind (i.e., downstream of) the looper. The desired number of elastomeric strands can be fed from a conventional source (e.g., creels, warp beams), through a guide, and into the feed tube. As the elastomeric strands are pulled through the feed tubes by the puller rolls, the machine sews a series of chain stitches around the outside of the tube. The puller rolls are located downstream of the outlet of the feed tube and are driven at a speed that is fixed with respect to the stitching speed to provide the desired stitch length. As the strands emerge from the tube, the chain stitches are pulled progressively along the axis of the tube until they slip off the outside of the tube onto and around the strands. The thusly formed bundle of strands, with the chain-stitched thread holding it together, then passes through the puller rolls and is collected in a container.

Instead of a feed tube, a groove can be ground between the lower and upper finger of the sewing machine to provide a passage for the elastomeric strands as the succession of chain stitches is sewn around them. Other methods of equivalently modifying or adapting chain-stitching sewing machines, or designing special machines, for the purposes of making the supply packages of this invention will readily be apparent to those skilled in the art.

Use of the package of the invention for feeding multiple elastomeric strands to a fabric-making machine is quite simple. The last-formed end of the package is removed from its container. The end of the chain-stitched thread is gently pulled to start the unravelling of the chain-stitches and to free the individual strands of the bundle from

each other. The separated strands are then strung-up on the feed mechanisms of the fabric-making machine. The end of the chain-stitched thread is connected to an "unraveller", which can be in the form of a sucker gun or puller rollers which are fixed in speed with respect to the strand-feeding mechanisms of the fabric-making machine.

To demonstrate the present invention a yarn supply package was made and then used to knit a narrow elastic tape. Forty strands, each of 1120 denier Lycra® Type 121 spandex yarn (manufactured by E. I. du Pont de Nemours and Company) were unwound from a creel, combined into a bundle of substantially parallel strands and then wound with no twist onto an aluminum spool. The bundle of strands was then unwound from the spool and fed through a groove ground between the upper and lower "finger" of a Merrow Model 70 which had been fitted with a 1-1/4-cm wide finger on which the feed mechanism was replaced by puller rolls. A 40-tex polyester sewing thread was stitched around the strands to provide an average chain-stitch spacing of two centimeters. The thusly formed supply package was collected in a plastic bag. The bag was then placed at the rear of a 14-gauge crochet knitting machine (Model PB-800, made by Comez SpA of Cilavegna, Italy). Six of the spandex strands from the supply package were strung up on the knitting machine, along with six ends of a 150-33 textured polyester yarn and then knit into a 0.95-cm-wide elastic tape. The chain-stitched polyester sewing thread of the supply package was readily unravelled and separated from the spandex strands by the application of a 55 to 85 gram pull along the axis of the package. In this demonstration, the thirty-four spandex strands that were not part of the knit tape, along with the unravelled sewing thread, were fed to waste containers. In this demonstration no difficulties were encountered in feeding the spandex strands from the supply packages to the knitting machine or in controlling the unravelling of the chain stitches from around the strand bundle.

An alternative to using a sewing machine for making the supply packages of the invention, is to use a needle or rapier loom. In using such looms, a multiplicity of parallel elastomeric strands would be formed into a bundle. The bundle would be fed as a unit to the loom where it would form one "warp yarn". The needle or rapier of the loom would carry a nonelastomeric thread or "weft". No binder thread would be used in conjunction with the weft. The bundle of elastomeric strands would be moved up and down in the conventional manner as a single warp thread and loops of the nonelastomeric weft thread would be formed over and under the bundle by the conventional movement of the needle or rapier. Successive loops of nonelastomeric thread would be connected by the latch needle of the loom to form a connected series of chain stitches around and along the length of the bundle. A loose weave, wherein successive loops are spaced about 2 or

more centimeters apart, would be employed. In a similar manner, several elastomeric strand bundles (e.g., 2, 3, 4 or so) could be fed simultaneously to the loom. In such cases, supply packages would be woven wherein the loops of the succession of chain stitches penetrate the package in the manner of weft yarns. Such chain stitches however, would still be unravellable in the same manner as those formed with the sewing machine or those formed with the loom when only one bundle of elastomeric strands is fed.

Claims

1. An elastomeric yarn supply package comprising a bundle of substantially parallel elastomeric strands (10) held together by a succession of connected chain stitches extending along the length of the said bundle wherein the said chain stitches are formed of a nonelastomeric thread (20) and are capable of being unravelled from the bundle to free the elastomeric strands from each other, the spacing between successive chain stitches being from 1 to 30 cm.

2. A yarn supply package as claimed in claim 1 wherein the spacing between successive chain stitches is from 1.8 to 8 cm.

3. A process for making an elastomeric yarn supply package wherein a succession of connected chain stitches is formed by a nonelastomeric thread (20) around and along the length of a bundle of substantially parallel elastomeric strands (10), the spacing between the successive chain stitches being from 1 to 30 cm and the chain stitches being capable of being unravelled from the bundle to free the elastomeric strands from each other.

4. A process as claimed in claim 3 wherein the chain stitches are formed by sewing with a single thread.

5. A process as claimed in claim 3 or claim 4 wherein a bundle of substantially parallel elastomeric strands is passed into a feed tube located between an upper and lower looper position of an over-edge chain-stitching sewing machine and projecting downstream of said looper positions, a connected succession of chain stitches is formed around the outside surface of the feed tube and the strand bundle is forwarded through the tube while simultaneously pulling the chain stitches in the same direction so that the stitches slip off the tube and onto and around the strand bundle.

6. The method of use of a yarn supply package as claimed in claim 1 to feed a textile machine wherein the strands are supplied from a package which comprises a bundle of substantially parallel elastomeric strands held together by a succession of connected chain stitches along the length of the bundle and the chain stitches are unravelled from the bundle to free the elastomeric strands from each other while feeding the freed portions of the strands to the textile machine.

Patentansprüche

1. Elastomergarn-Lieferspule, umfassend ein Bündel im wesentlichen paralleler elastomerer Stränge (10), die durch eine Aufeinanderfolge miteinander verknüpfter Kettmaschen, die sich über die Länge des Bündels erstrecken, zusammengehalten werden, wobei die Kettmaschen aus einem nichtelastomeren Faden (20) gebildet werden und auf das Bündel aufgezogen werden können und dadurch die elastomeren Stränge voneinander freigeben, wobei der Abstand zwischen aufeinanderfolgenden Kettmaschen 1 bis 30 cm beträgt.

2. Lieferspule nach Anspruch 1, bei der der Abstand zwischen aufeinanderfolgenden Kettmaschen 1,8 bis 8 cm beträgt.

3. Verfahren zur Herstellung einer Elastomergarn-Lieferspule, bei dem über die Länge eines Bündels von im wesentlichen parallelen elastomeren Strängen (10) und um dieses herum eine Aufeinanderfolge miteinander verknüpfter Kettmaschen durch einen nichtelastomeren Faden (20) gebildet werden, wobei der Abstand zwischen aufeinanderfolgenden Kettmaschen 1 bis 30 cm beträgt und sich die Kettmaschen auf dem Bündel aufziehen lassen, um die elastomeren Stränge voneinander freizugeben.

4. Verfahren nach Anspruch 3, bei dem die Kettmaschen durch Nähen mit einem einzigen Faden gebildet werden.

5. Verfahren nach Anspruch 3 oder 4, bei dem ein Bündel im wesentlichen paralleler elastomerer Stränge in ein Speiserohr geführt wird, das zwischen einer oberen und einer unteren Looperposition einer Überwendlich-Kettmaschen-Nähmaschine angeordnet ist und abstromseitig der Looperpositionen hervorsteht, eine Aufeinanderfolge miteinander verknüpfter Kettmaschen, um die Aussenfläche des Speiserohrs gebildet wird und das Strangbündel durch das Rohr gefördert wird, während gleichzeitig die Kettmaschen in der gleichen Richtung gezogen werden, so dass die Maschen vom Rohr herunter und auf das Strangbündel und um dieses herum gleiten.

6. Verfahren zur Verwendung einer Lieferspule nach Anspruch 1 zur Beschickung einer Textilmaschine, bei dem die Stränge von einer Spule abgezogen werden, wobei ein Bündel im wesentlichen paralleler elastomerer Stränge durch eine Aufeinanderfolge von miteinander verknüpfter Kettmaschen über die Länge des Bündels zusammengehalten wird und die auf dem Bündel befindlichen Kettmaschen aufgezogen werden, um die elastomeren Stränge voneinander freizugeben, während die freigegebenen Teile der Stränge der Textilmaschine zugeführt werden.

Revendications

1. Ensemble d'alimentation en fils élastomères constitué par un faisceau de fils élastomères à peu près parallèles (10) maintenus ensemble par une succession de points de chaîne s'étendant suivant la longueur dudit faisceau, dans lequel

(11)

more centimeters apart, would be employed. In a similar manner, several elastomeric strand bundles (e.g., 2, 3, 4 or so) could be fed simultaneously to the loom. In such cases, supply packages would be woven wherein the loops of the succession of chain stitches penetrate the package in the manner of weft yarns. Such chain stitches however, would still be unravellable in the same manner as those formed with the sewing machine or those formed with the loom when only one bundle of elastomeric strands is fed.

Claims

1. An elastomeric yarn supply package comprising a bundle of substantially parallel elastomeric strands (10) held together by a succession of connected chain stitches extending along the length of the said bundle wherein the said chain stitches are formed of a nonelastomeric thread (20) and are capable of being unravelled from the bundle to free the elastomeric strands from each other, the spacing between successive chain stitches being from 1 to 30 cm.

2. A yarn supply package as claimed in claim 2 wherein the spacing between successive chain stitches is from 1.8 to 8 cm.

3. A process for making an elastomeric yarn supply package wherein a succession of connected chain stitches is formed by a nonelastomeric thread (20) around and along the length of a bundle of substantially parallel elastomeric strands (10), the spacing between the successive chain stitches being from 1 to 30 cm and the chain stitches being capable of being unravelled from the bundle to free the elastomeric strands from each other.

4. A process as claimed in claim 3 wherein the chain stitches are formed by sewing with a single thread.

5. A process as claimed in claim 3 or claim 4 wherein a bundle of substantially parallel elastomeric strands is passed into a feed tube located between an upper and lower looper position of an over-edge chain-stitching sewing machine and projecting downstream of said looper positions, a connected succession of chain stitches is formed around the outside surface of the feed tube and the strand bundle is forwarded through the tube while simultaneously pulling the chain stitches in the same direction so that the stitches slip off the tube and onto and around the strand bundle.

6. The method of use of a yarn supply package as claimed in claim 1 to feed a textile machine wherein the strands are supplied from a package which comprises a bundle of substantially parallel elastomeric strands held together by a succession of connected chain stitches along the length of the bundle and the chain stitches are unravelled from the bundle to free the elastomeric strands from each other while feeding the freed portions of the strands to the textile machine.

Patentansprüche

1. Elastomergarn-Lieferspule, umfassend ein Bündel im wesentlichen paralleler elastomerer Stränge (10), die durch eine Aufeinanderfolge miteinander verknüpfter Kettmaschen, die sich über die Länge des Bündels erstrecken, zusammengehalten werden, wobei die Kettmaschen aus einem nichtelastomeren Faden (20) gebildet werden und auf das Bündel aufgezogen werden können und dadurch die elastomeren Stränge voneinander freigeben, wobei der Abstand zwischen aufeinanderfolgenden Kettmaschen 1 bis 30 cm beträgt.

2. Lieferspule nach Anspruch 1, bei der der Abstand zwischen aufeinanderfolgenden Kettmaschen 1,8 bis 8 cm beträgt.

3. Verfahren zur Herstellung einer Elastomergarn-Lieferspule, bei dem über die Länge eines Bündels von im wesentlichen parallelen elastomeren Strängen (10) und um dieses herum eine Aufeinanderfolge miteinander verknüpfter Kettmaschen durch einen nichtelastomeren Faden (20) gebildet werden, wobei der Abstand zwischen aufeinanderfolgenden Kettmaschen 1 bis 30 cm beträgt und sich die Kettmaschen auf dem Bündel aufziehen lassen, um die elastomeren Stränge voneinander freizugeben.


4. Verfahren nach Anspruch 3, bei dem die Kettmaschen durch Nähen mit einem einzigen Faden gebildet werden.

5. Verfahren nach Anspruch 3 oder 4, bei dem ein Bündel im wesentlichen paralleler elastomerer Stränge in ein Speiserohr geführt wird, das zwischen einer oberen und einer unteren Looperposition einer Überwendlich-Kettmaschen-Nähmaschine angeordnet ist und abstromseitig der Looperpositionen hervorsteht, eine Aufeinanderfolge miteinander verknüpfter Kettmaschen, um die Aussenfläche des Speiserohrs gebildet wird und das Strangbündel durch das Rohr gefördert wird, während gleichzeitig die Kettmaschen in der gleichen Richtung gezogen werden, so dass die Maschen vom Rohr herunter und auf das Strangbündel und um dieses herum gleiten.

6. Verfahren zur Verwendung einer Lieferspule nach Anspruch 1 zur Beschickung einer Textilmaschine, bei dem die Stränge von einer Spule abgezogen werden, wobei ein Bündel im wesentlichen paralleler elastomerer Stränge durch eine Aufeinanderfolge von miteinander verknüpfter Kettmaschen über die Länge des Bündels zusammengehalten wird und die auf dem Bündel befindlichen Kettmaschen aufgezogen werden, um die elastomeren Stränge voneinander freizugeben, während die freigegebenen Teile der Stränge der Textilmaschine zugeführt werden.

Revendications

1. Ensemble d'alimentation en fils élastomères constitué par un faisceau de fils élastomères à peu près parallèles (10) maintenus ensemble par une succession de points de chaîne s'étendant suivant la longueur dudit faisceau, dans lequel



7
Lesdits points de chaîne sont formés d'un fil non élastomère (20) et sont aptes à être démaillés du faisceau pour libérer les fils élastomères les uns des autres, l'écartement entre les points de chaîne successifs étant de 1 à 30 cm.

2. Ensemble d'alimentation en fils suivant la revendication 1, dans lequel l'écartement entre les points de chaîne successifs est de 1,8 à 8 cm.

3. Procédé de fabrication d'un ensemble d'alimentation en fils élastomères, caractérisé en ce qu'une succession de points de chaîne reliés est formée par un fil non élastomère (20) autour et le long de la longueur d'un faisceau de fils élastomères (10) à peu près parallèles, l'écartement entre les points de chaîne successifs étant de 1 à 30 cm, et les points de chaîne étant aptes à être démaillés du faisceau pour libérer les fils élastomères les uns des autres.

4. Procédé suivant la revendication 3, caractérisé en ce que les points de chaîne sont formés par couture avec un fil unique.

5. Procédé suivant la revendication 3 ou 4, caractérisé en ce qu'on fait passer un faisceau de fils élastomères à peu près parallèles dans un

12
tube d'alimentation disposé entre une position supérieure et inférieure du boucleur d'une machine à coudre à points de chaîne et à points de surjet et on le fait dépasser en aval desdites positions du boucleur, on forme une succession de points de chaîne reliés autour de la surface externe du tube d'alimentation et le faisceau de fils est avancé à travers le tube tout en tirant simultanément les points de chaîne dans la même direction de manière que les points glissent du tube et sur et autour du faisceau de fils.

6. Procédé d'utilisation d'un ensemble d'alimentation en fils suivant la revendication 1, pour alimenter une machine textile, caractérisé en ce que les fils sont amenés à partir d'un ensemble qui est constitué par un faisceau de fils élastomères à peu près parallèles et maintenus ensemble par une succession de points de chaîne reliés suivant la longueur du faisceau et les points de chaîne étant démaillés du faisceau pour libérer les fils élastomères les uns des autres tout en amenant les parties libérées des fils à la machine textile.

