

DESCRIPTION

SUCTION MUFFLER FOR A HERMETIC COMPRESSOR

This Sheet Has Been Replaced



5 Technical Field

The present invention relates to a closed motor-driven compressor for use in refrigerators, air conditioners or the like.

Background Art

Recently, closed motor-driven compressors are demanded to have a
10 high energy efficiency, and it is well known that a suction muffler having a low thermal conductivity and made of, for example, synthetic resin is suited for use in such compressors.

Japanese Laid-Open Patent Publication (unexamined) No. 10-47248
discloses a closed motor-driven compressor as shown in Figs. 11 and 12. This
15 compressor includes a compression component 2 and an electric component 3, both elastically supported within a closed vessel 1. The compression component 2 includes a cylinder 4, a piston 5 reciprocatingly accommodated in the cylinder 4, a valve plate 6 mounted on the cylinder 4 so as to cover an opening defined therein, and a cylinder head 7 secured to the cylinder 4. A suction muffler 8 made of synthetic
20 resin and made up of three elements is mounted on the cylinder head 7 for introducing a refrigerant gas into the cylinder 4. The suction muffler 8 is connected to a suction pipe 9 extending through a side wall of the closed vessel 1 to introduce the refrigerant gas into the closed vessel 1.

As shown in Fig. 13, the muffler 8 includes a first element 29, a second
25 element 30 to which the first element 29 is secured, and a third element 31 secured to the second element 30. As shown in Fig. 14, the first element 29 has an inwardly protruding guide rib 32 integrally formed therewith. The guide rib 32 acts to facilitate the assembling of the first and second elements 29, 30. After the first and second

elements 29, 30 have been assembled using the guide rib 32, they are assembled with the third element 31, and all of them are joined together by ultrasonic welding.

In the closed motor-driven compressor of the above-described construction, the refrigerant gas from the low-pressure side in a refrigerating cycle is introduced into the closed vessel 1 through the suction pipe 9 and then into the cylinder 4 through the suction muffler 8 before the refrigerant gas is compressed by the piston 5.

In the above-described construction, however, because the suction muffler 8 is made of synthetic resin, it is apt to be deformed after injection molding. Accordingly, a difficulty is encountered in assembling the first and second elements 29, 30 with the use of the guide rib 32.

The present invention has been developed to overcome the above-described disadvantages.

It is accordingly an objective of the present invention to provide a closed motor-driven compressor having an improved suction muffler that facilitates the assembling work of its elements.

Disclosure of the Invention

In accomplishing the above and other objectives, the closed motor-driven compressor according to the present invention includes a closed vessel, a compression component elastically supported within the closed vessel, an electric component elastically supported within the closed vessel for driving the compression component, and a suction muffler mounted on the compression component and including a plurality of elements assembled together and each made of synthetic resin.

One (first element) of the plurality of elements has a guide rib integrally formed therewith that is tapered down toward adjoining one (second element) of the plurality of elements. The tapered guide rib acts to reform deformation of the second element into which it is inserted, thus facilitating an assembling work of the first and second elements.

This Sheet Has Been Replaced





Advantageously, the guide rib is formed discontinuously or intermittently along a peripheral edge of the first element. By so doing, stains caused by the cooling of the first element after injection molding are relatively small, thus reducing deformation of the first element.

5 The first element may have first and second peripheral portions and third and fourth peripheral portions each interposed between the first and second peripheral portions, wherein the first and second peripheral portions have first and second radii of curvature, respectively, while the third and fourth peripheral portions have third and fourth radii of curvature, respectively, that are smaller than the first and
10 second radii of curvature, and wherein the guide rib is formed at the third or fourth peripheral portion and at the first and second peripheral portions adjacent thereto.

 In assembling the first and second elements, the first and second portions of the second element having large radii of curvature are subjected to relatively small deformation, while the third and fourth portions of the second element
15 having small radii of curvature are subjected to larger deformation. Accordingly, the guide rib formed at the first and second peripheral portions of the first element can be readily inserted into the corresponding portions of the second element, and the guide rib gradually reforms the deformation of the second element. Such insertion facilitates subsequent insertion of the guide rib into the third and fourth portions of the
20 second element, making it possible to realize automated assembling of suction mufflers.

 The plurality of elements are secured to one another by welding. The welding reduces a leakage of suction gas from the suction muffler.

 Alternatively, the plurality of elements are secured to one another by
25 fastening means such, for example, as rivets, screws, or the like. The use of such fastening means requires no expensive welding machine or the like.

 Again alternatively, the plurality of elements are secured to one another by introducing projections formed therewith into openings defined therein. The

assembling of the elements by engagement of the projections with the openings requires no fastening means referred to above.

Brief Description of the Drawings

5 The above and other objectives and features of the present invention will become more apparent from the following description of a preferred embodiment thereof with reference to the accompanying drawings, throughout which like parts are designated by like reference numerals, and wherein:

Fig. 1 is a top plan view of a closed motor-driven compressor according to the present invention with a closed vessel partially removed;

10 Fig. 2 is a vertical sectional view of the closed motor-driven compressor of Fig. 1;

Fig. 3 is an exploded view of a suction muffler mounted in the closed motor-driven compressor of Fig. 1;

Fig. 4 is an enlarged cross-sectional view of a portion A in Fig. 3;

15 Fig. 5 is a view similar to Fig. 3, but depicting a modification thereof;

Fig. 6 is a view similar to Fig. 3, but depicting another modification thereof;

Fig. 7 is a front view of one of a plurality of elements constituting the suction muffler of Fig. 6;

20 Fig. 8 is a bottom plan view of the element of Fig. 7;

Fig. 9 is a view similar to Fig. 3, but depicting a further modification thereof;

Fig. 10 is a view similar to Fig. 3, but depicting a still further modification thereof;

25 Fig. 11 is a top plan view of a conventional closed motor-driven compressor with a closed vessel partially removed;

Fig. 12 is a vertical sectional view of the closed motor-driven compressor of Fig. 11;

Fig. 13 is an exploded view of a suction muffler mounted in the closed motor-driven compressor of Fig. 11; and

Fig. 14 is an enlarged cross-sectional view of a portion A in Fig. 13.

Detailed Description of the Preferred Embodiments

5 This application is based on application No. 11-147955 filed May 27, 1999 in Japan, the content of which is incorporated hereinto by reference.

Referring now to the drawings, there is shown in Figs. 1 and 2 a closed motor-driven compressor embodying the present invention. The compressor shown therein includes a compression component 2 and an electric component 3 for driving
10 the compression component 2, both of which are elastically supported within a closed vessel 1. The compression component 2 includes a cylinder 4, a piston 5 reciprocatingly accommodated in the cylinder 4, a valve plate 6 mounted on the cylinder 4 so as to cover an opening defined therein, and a cylinder head 7 secured to the cylinder 4. A suction muffler 8 is mounted on the cylinder head 7 for introducing
15 a refrigerant gas into the cylinder 4. The suction muffler 8 is made of synthetic resin and includes three elements assembled together. The suction muffler 8 is connected to a suction pipe 9 extending through a side wall of the closed vessel 1 to introduce the refrigerant gas into the closed vessel 1.

As shown in Fig. 3, the suction muffler 8 includes a first element 10, a
20 second element 11 to which the first element 10 is secured, for example, by welding, and a third element 12 secured to the second element 11, for example, by welding. The welding reduces a leakage of suction gas from the suction muffler 8. Each of the first to third elements 10, 11, 12 is injection-molded from polybutylene terephthalate (PBT).

25 As shown in Fig. 4, the first element 10 has an inwardly or downwardly protruding guide rib 13 integrally formed therewith. The guide rib 13 is formed continuously along the peripheral edge of the first element 10 and is tapered down inwardly or downwardly. More specifically, the inner surface of the guide rib 13

extends substantially straight in the vertical direction, while the outer surface of the guide rib 13 is inclined such that the thickness of the guide rib 13 gradually decreases inwardly or downwardly.

By the above-described construction, in assembling the first and second elements 10, 11, the guide rib 13 of the first element 10 reforms deformation of the second element 11. Accordingly, the first and second elements 10, 11 can be assembled together merely by inserting the guide rib 13 into an associated end portion of the second element 11, thus facilitating the assembling work.

Fig. 5 depicts a modification 8A of the suction muffler 8 shown in Fig. 3.

10 This suction muffler 8A includes first to third elements 14, 15, 16 assembled together, just like the suction muffler 8. The suction muffler 8A, however, differs from the suction muffler 8 in that the first element 14 has an inwardly or downwardly protruding guide rib 17 that is formed discontinuously along the peripheral edge of the first element 14.

15 Because the tapered guide rib 17 is formed intermittently along the peripheral edge of the first element 14, stains caused by the cooling of the first element 14 after the injection molding are relatively small, thus reducing deformation of the first element 14.

Fig. 6 depicts another modification 8B of the suction muffler 8, and as shown therein, the suction muffler 8B includes first to third elements 18, 19, 20 assembled together.

The second element 19 has a generally crescent-shaped open end portion (upper end portion in this case), which has first and second portions opposite to each other and third and fourth portions opposite to each other and each interposed between the first and second portions. The first and second portions have respective relatively large radii of curvature, while the third and fourth portions have respective relatively small radii of curvature.

As shown in Figs. 7 and 8, the first element 18 has a shape

corresponding to that of the generally crescent-shaped open end portion of the second element 19 and, hence, has first and second peripheral portions having respective large radii of curvature and third and fourth peripheral portions having respective small radii of curvature and each interposed between the first and second
5 peripheral portions. The first element 18 also has inwardly or downwardly protruding tapered guide ribs 21 each integrally formed therewith at the third or fourth peripheral portion and at the first and second peripheral portions adjacent thereto.

In assembling the first and second elements 18, 19, the first and second portions of the second element 19 having the large radii of curvature are subjected to
10 relatively small deformation, while the third and fourth portions of the second element 19 having the small radii of curvature are subjected to larger deformation. Accordingly, the guide ribs 21 formed at the first and second peripheral portions of the first element 18 can be readily inserted into the corresponding portions of the second element 19, and the former gradually reform the deformation of the second element
15 19. Such insertion facilitates subsequent insertion of the guide ribs 21 into the third and fourth portions of the second element 19, making it possible to realize automated assembling of suction mufflers.

As is the case with the suction muffler 8A shown in Fig. 5, the first element 18 has separated or discontinuous guide ribs 21 and, hence, stains caused
20 by the cooling of the first element 18 after the injection molding are relatively small, thus reducing deformation of the first element 18.

As shown in Fig. 9 depicting a further modification 8C of the suction muffler, first to third elements 22, 23, 24 may have respective tabs 22a, 23a, 24a integrally formed therewith and extending laterally outwardly therefrom so that the
25 three elements 22, 23, 24 may be assembled together by means of rivets 25. The assembling of the elements 22, 23, 24 by the rivets 25 requires no expensive welding machine or the like. Screws may be used in place of the rivets 25.

Alternatively, as shown in Fig. 10 depicting a still further modification 8D

of the suction muffler, first to third elements 26, 27, 28 may have respective tabs and/or projections integrally formed therewith. In the case of Fig. 10, the first element 26 has downwardly extending tabs 29 each having an opening defined therein, while the second element 27 has projections 31 each formed at an upper portion thereof. Likewise, the second element 27 has downwardly extending tabs 30 each having an opening defined therein, while the third element 28 has projections 32 each formed at an upper portion thereof.

In assembling the three elements 26, 27, 28, each of the projections 31 of the second element 27 is introduced into and received in the opening of the associated tab 29 of the first element 26, while each of the projections 32 of the third element 28 is introduced into and received in the opening of the associated tab 30 of the second element 27. The assembling of the elements 26, 27, 28 by the engagement of the projections 31, 32 with the tabs 29, 30 requires no additional fastening means such, for example, as screws, rivets, or the like.

Although the present invention has been fully described by way of examples with reference to the accompanying drawings, it is to be noted here that various changes and modifications will be apparent to those skilled in the art. Therefore, unless such changes and modifications otherwise depart from the spirit and scope of the present invention, they should be construed as being included therein.

This Sheet Has Been Replaced



This Sheet Has Been Replaced



CLAIMS



1. A closed motor-driven compressor comprising:
a closed vessel;
5 a compression component elastically supported within the closed vessel;
an electric component elastically supported within the closed vessel for driving the compression component; and
a suction muffler mounted on the compression component and
10 comprising a plurality of elements assembled together and each made of synthetic resin, one of the plurality of elements having a guide rib integrally formed therewith that is tapered down toward adjoining one of the plurality of elements, thereby facilitating an assembling work of the two elements.
2. The closed motor-driven compressor according to claim 1, wherein the
15 guide rib is formed discontinuously along a peripheral edge of the one element.
3. The closed motor-driven compressor according to claim 2, wherein the one element has first and second peripheral portions and third and fourth peripheral portions each interposed between the first and second peripheral portions, the first and second peripheral portions having first and second radii of curvature, respectively,
20 the third and fourth peripheral portions having third and fourth radii of curvature, respectively, that are smaller than the first and second radii of curvature, and wherein the guide rib is formed at the third or fourth peripheral portion and at the first and second peripheral portions adjacent thereto.
4. The closed motor-driven compressor according to any one of claims 1 to
25 3, wherein the plurality of elements are secured to one another by welding.
5. The closed motor-driven compressor according to any one of claims 1 to 3, wherein the plurality of elements are secured to one another by fastening means.
6. The closed motor-driven compressor according to any one of claims 1 to

3, wherein the plurality of elements are secured to one another by introducing projections formed therewith into openings defined therein.



This Sheet Has Been Replaced

