

## **FLUID ENCLOSURE AND METHODS RELATED THERETO**

### **CLAIM OF PRIORITY**

Benefit of priority is hereby claimed to U.S. Patent Application Serial Number 11/473,591, filed on June 23, 2006, which is herein incorporated by reference.

### **TECHNICAL FIELD**

Embodiments of the present invention relate to fluid enclosures. More specifically, embodiments relate to fluid enclosures for small or micro scale systems.

### **BACKGROUND**

Currently, fluid enclosures are designed and built independently of the fluid being stored, or of any storage material that would be inserted within the enclosure. In its simplest form, a conventional pressure vessel can be used to contain a fluid, such as a compressed gas or a liquefied gas. The pressure vessel must be designed to accommodate the maximum pressure of the fluid without failure. Such simple design approaches can be extended to incorporate a storage material by filling the pressure vessel with storage material. In this case, the pressure vessel must now withstand the fluid pressure, as well as any stress potentially induced by the storage material exerting force on the internal pressure vessel walls. Presently, these vessels tend to be of a cylindrical shape.

When very small storage systems are required, or when irregular (i.e. non-cylindrical) shapes are called for, the overall approach of employing conventional pressure vessels becomes problematic. In order to contain the internal pressures and mechanical stresses induced by a storage material, wall thickness and material properties of the enclosure must be sufficient to prevent failure, such as rupture. Material properties considered include tensile strength, ductility, material compatibility, enclosure geometry, stress factors, etc. As a result, the range of materials that can be

used to construct the enclosure is limited, and only vessel geometries which do not overly amplify the internal pressures as enclosure stress can be considered.

Challenges to fluid enclosure design are amplified when incorporated in small systems, such as in a small or micro scale fuel cell. In small systems, fluid enclosure wall thickness consumes a significant portion of the volume of the enclosure. Prismatic shapes or irregular form factors are very difficult to utilize since they will bow outward under even modest fluid pressure. When absorbing materials (e.g. hydrides) are used, the mechanical strain on the tank walls can induce large stresses.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, which are not necessarily drawn to scale, like numerals describe substantially similar components throughout the several views. Like numerals having different letter suffixes represent different instances of substantially similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

FIG. 1 illustrates a cross-sectional view of a fluid enclosure, according to some embodiments.

FIG. 2 illustrates a cross-sectional view of a portion of a fluid enclosure utilizing a composite hydrogen storage material, according to some embodiments.

FIG. 3 illustrates a cross-sectional view of a portion of a fluid enclosure utilizing a composite hydrogen storage material including a feature, according to some embodiments.

FIG. 4 illustrates a perspective view of a fluid enclosure, according to some embodiments.

FIG. 5 illustrates a perspective view of a fluid enclosure system, according to some embodiments.

FIG. 6 illustrates a block flow diagram of a method of manufacturing a fluid enclosure, according to some embodiments.

FIG. 7 illustrates a block flow diagram of a method of storing a fluid, according to some embodiments.

FIG. 8 illustrates a block flow diagram of a method of using a fluid enclosure, according to some embodiments.

## SUMMARY

Embodiments of the invention relate to a fluid enclosure comprising a structural  
5 filler and an outer enclosure wall conformably coupled to the structural filler.

Embodiments of the present invention further relate to a method of manufacturing a fluid enclosure. The method includes conformably coupling an outer enclosure wall to a structural filler.

Embodiments of the invention relate to a method of storing a fluid. The method  
10 includes contacting a fluid enclosure with a fluid, wherein the fluid enclosure includes a structural filler and an outer enclosure wall conformably coupled to the structural filler. Embodiments further relate to a method of using a fluid enclosure. The method includes releasing a fluid from a fluid enclosure, wherein the fluid enclosure includes a structural filler and an outer enclosure wall conformably coupled to the structural filler.

15 Embodiments of the invention relate to a fluid enclosure system. The system includes a fluid enclosure and an external device coupled to the fuel enclosure, wherein the fluid enclosure includes a structural filler and an outer enclosure wall conformably coupled to the structural filler.

## 20 DETAILED DESCRIPTION

The following detailed description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the invention may be practiced. These  
embodiments, which are also referred to herein as “examples,” are described in enough  
25 detail to enable those skilled in the art to practice the invention. The embodiments may be combined, other embodiments may be utilized, or structural, and logical changes may be made without departing from the scope of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined by the appended claims and their equivalents.

30 In this document, the terms “a” or “an” are used to include one or more than one and the term “or” is used to refer to a nonexclusive or unless otherwise indicated. In addition, it is to be understood that the phraseology or terminology employed herein, and not otherwise defined, is for the purpose of description only and not of limitation.

In the event of inconsistent usages between this document and those documents so incorporated by reference, the usage in the incorporated reference should be considered supplementary to that of this document; for irreconcilable inconsistencies, the usage in this document controls.

5           Embodiments of the present invention relate to a fluid enclosure. The  
embodiments of the present invention allow for a fluid enclosure in which a structural  
filler within the enclosure supports the stress applied by the internal fluid pressure rather  
than having that pressure be fully supported by the enclosure wall as is the case for  
traditional fluid enclosures. The enclosure may include a structural filler with an outer  
10   enclosure wall conformably coupled to it. Since the outer enclosure wall bonds to the  
structural filler, the fluid pressure applied to the enclosure is fully supported as isostatic  
tensile stress in the structural filler. The only significant stress that the outer enclosure  
wall experiences may be due to straining of the structural filler. The burst pressure of  
the enclosure is therefore limited to the ultimate tensile strength of the structural filler or  
15   the bond between the structural filler and the outer enclosure wall. This architecture  
allows compact, lightweight, and conformable fluid enclosures to be built that can  
support significant internal pressures without the encumbrance of thick enclosure walls.

## 20   Definitions

As used herein, "fluid" refers to a continuous, amorphous substance  
whose molecules move freely past one another and that has the tendency to assume the  
shape of its container. A fluid may be a gas, liquefied gas, liquid or liquid under  
pressure. Examples of fluids include hydrogen, methanol, ethanol, formic acid, butane,  
25   borohydride compounds, etc.

As used herein, "structural filler" refers to a material with a sufficient tensile  
strength to withstand the internal pressure of a fluid enclosure, when pressurized with a  
fluid. Structural fillers may be solid. Structural fillers may include metallic or plastic  
lattices, composite hydrogen storage materials, clathrates, nano-structured carbon  
30   foams, aerogels, zeolites, silicas, aluminas, graphite, activated carbons, micro-ceramics,  
nano-ceramics, boron nitride nanotubes, borohydride powder, hydrogen occluding metal

alloys (for example, metal hydride), palladium-containing materials or combinations thereof, for example.

As used herein, “conformably coupled” or “conformally coupled” refers to forming a bond that is substantially uniform between two components and are attached in such a way as to chemically or physically bind in a corresponding shape or form. A structural filler may be conformably coupled to an outer enclosure wall, for example, in which the outer enclosure wall chemically or physically binds to the structural filler and takes its shape.

As used herein, “outer enclosure wall” refers to the outermost layer within a fluid enclosure that serves to at least partially slow the diffusion of a fluid from the fluid enclosure. The outer enclosure wall may include multiple layers of the same or differing materials. The outer enclosure wall may include a polymer, metal, or composite, for example.

As used herein, “feature” refers to a component associated with a fluid enclosure. A feature may be a fluidic component. A feature may act to communicate between an enclosure and an external device or ambient environment, to observe or control a fluid, or act as a structural component. Examples of a feature may be a valve, regulator, pressure relief device, flow element, cap, fitting, vent, etc.

As used herein, “structural feature” refers to an element that may be associated with the shape, positioning or alignment of the structural filler, the outer enclosure wall or the overall fluid enclosure. A structural feature may be formed to allow space for external components or to create more efficient alignment between the fluid enclosure and an external device, for example. Structural features include convex protrusions, concave recesses, mountings, flanges, fittings, bosses, smoothed or radiused corners, etc.

As used herein, “metal hydride particles” or “metal hydrides” refer to metal or metal alloy particles that are capable of forming metal hydrides when contacted with hydrogen. Examples of such metal or metal alloys are  $\text{LaNi}_5$ ,  $\text{FeTi}$ ,  $\text{Mg}_2\text{Ni}$  and  $\text{ZrV}_2$ . Such compounds are representative examples of the more general description of metal hydride compounds:  $\text{AB}$ ,  $\text{AB}_2$ ,  $\text{A}_2\text{B}$ ,  $\text{AB}_5$  and  $\text{BCC}$ , respectively. When bound with hydrogen, these compounds form metal hydride complexes, such as  $\text{MgH}_2$ ,  $\text{Mg}_2\text{NiH}_4$ ,  $\text{FeTiH}_2$  and  $\text{LaNi}_5\text{H}_6$ , for example. Examples of metals used to form metal hydrides

include vanadium, magnesium, lithium, aluminum, calcium, transition metals, lanthanides, and intermetallic compounds and solid solutions thereof.

As used herein, "composite hydrogen storage material" refers to active material particles mixed with a binder, wherein the binder immobilizes the active material particles sufficient to maintain relative spatial relationships between the active material particles. Examples of composite hydrogen storage materials are found in commonly-owned U.S. Patent Application Serial No.11/379,970, filed April 24, 2006.

As used herein, "relative spatial relationships" refers to three-dimensional relationships between particles. Such three-dimensional relationships between particles in the context of the present invention will remain substantially unchanged. For example, the distance between particles may change during the hydriding/dehydriding cycle, but the particles return to substantially the same position relative to the other particles over the course of one complete cycle. The particle structure may have, e.g., an elastic property, in that the particles may move, but maintain substantially the same three-dimensional positioning substantially relative to other particles as they move. An exemplary indicator of whether a material meets the above characteristics is a qualitative measurement based upon, e.g., the volume, packing density or porosity or a dimension (e.g. length) of the composite material over repeated cycles. As such, when length of the formed composite is used as the indicator, the length of the formed composite will be at least about 80% and not more than about 120% of the parent length measured.

As used herein, "active material particles" refer to material particles capable of storing hydrogen or to material particles that may occlude and desorb hydrogen, such as metal hydrides, for example. The active material may be a metal, metal alloy or metal compound capable of forming a metal hydride when in contact with hydrogen. For example, the active material may be  $\text{LaNi}_5$ ,  $\text{FeTi}$ , a mischmetal, a mixture of metals or an ore, such as  $\text{MmNi}_5$ , wherein Mm refers to a mixture of lanthanides. The active material particles may occlude hydrogen by chemisorption, physisorption or a combination thereof. Active material particles may also include silicas, aluminas, zeolites, graphite, activated carbons, nano-structured carbons, micro-ceramics, nano-ceramics, boron nitride nanotubes, palladium-containing materials or combinations thereof.

As used herein, "clathrate" refers to a crystal formed from the bonding of a molecule with water. More generally, a clathrate may be a lattice-type compound used to trap or hold another compound. A clathrate may be an organic addition compound comprising an internal space which is enclosed. A clathrate may be formed by the inclusion of molecules in cavities formed by crystal lattices or present in large molecules. Examples of clathrates include methanol clathrates, methane clathrates or hydrogen clathrates. The guest molecule may be held by the host molecule via physical, chemical or intermolecular forces. Host molecules may include urea, thiourea, hydroquinone, deoxycholic acid, triphenylcarbinol, perhydrotriphenylene, 18-crown-6 or 2,2,2-cryptand, for example. Examples of guest molecules include methanol, methane or hydrogen, for example.

As used herein, "polymer" refers to any of numerous natural and synthetic compounds of usually high molecular weight consisting of up to millions of repeated linked units, each a relatively light and simple molecule. Examples of polymers include polypropylene, Kynar Flex® (vinylidene fluoride hexafluoropropylene copolymer), polyethylene, polyester, polyvinylidene fluoride (PVDF), hexafluoropropylene vinylidene fluoride copolymer, cross-linked copolymers, polytetrafluoroethylene (PTFE), perfluoro alkoxy (PFA), polyimides, polyamides, poly ether ether ketone (PEEK), polyetherimide (e.g., Ultem™) and thermoplastic polymers (for example, Nylon™).

As used herein, "forming" refers to creating, manufacturing, giving shape or any method that produces the desired end product from starting materials.

As used herein, "contacting" refers to physically, chemically or electrically touching. A fluid may contact an enclosure, in which the fluid is physically forced inside the enclosure, for example.

As used herein "releasing" refers to freeing from something that binds, fastens or holds back, either physically or chemically. A fluid may be physically released from an enclosure, for example. A fluid may chemically be released from a metal hydride, for example.

As used herein, "occlude" or "occluding" or "occlusion" refers to absorbing or adsorbing and retaining a substance. Hydrogen may be the substance occluded, for example. A substance may be occluded chemically or physically, such as by chemisorption or physisorption, for example.

As used herein, “desorb” or “desorbing” or “desorption” refers to the removal of an absorbed or adsorbed substance. Hydrogen may be removed from active material particles, for example. The hydrogen may be bound physically or chemically, for example.

5 As used herein, “occluding/desorbing material” refers to a material capable of absorbing, adsorbing or retaining a substance and further capable of allowing the substance to be removed. The occluding/desorbing material may retain the substance chemically or physically, such as by chemisorption or physisorption, for example. Examples of such a material include metal hydrides, composite hydrogen storage  
10 materials, clathrates, etc.

Referring to FIG. 1, a cross-sectional view of a fluid enclosure 100 is shown, according to some embodiments. A structural filler 104 may be surrounded by an outer enclosure wall 102. The structural filler 104 may be conformably coupled to the outer enclosure wall 102, which may be represented by a bond 108. One or more optional  
15 features 106 may be utilized.

#### Structural Filler

The structural filler 104 may include a material with a sufficient tensile strength to withstand the internal pressure of the fluid enclosure 100, when pressurized with a  
20 fluid. Structural fillers may be solid. Structural fillers 104 may include metallic or plastic lattices, composite hydrogen storage materials, nano-structured carbon foams, aerogels, zeolites, silicas, aluminas, graphite, activated carbons, micro-ceramics, nano-ceramics, boron nitride nanotubes, borohydride powder, palladium-containing materials or combinations thereof, for example.

25 The structural filler 104 may include a material capable of occluding/desorbing a fluid, such as a metal hydride. This results in a material with sufficient tensile strength and fluid occluding/desorbing properties, such as composite hydrogen storage material, nano-structured carbon foams, aerogels or zeolites, for example. In addition, the fluid enclosure 100 may include a structural filler 104 and a separate, fluid  
30 occluding/desorbing material, such as a metal hydride powder or clathrate. For example, the structural filler 104 may be inert to the fluid being stored and the fluid enclosure may separately include a fluid occluding/desorbing material. If a lattice, the structural filler 104 may include small pores. Pores in the structural filler 104 may be

used to hold fluid occluding/desorbing materials, such as metal hydrides or clathrates, for example. A methane clathrate may be used to store methane efficiently at high pressure and could be used in conjunction with a structural filler 104, such as a metal lattice.

5           The structural filler 104 may be conformably coupled to the outer enclosure wall 102, creating a bond 108. As the force due to internal pressure within the fluid enclosure 100 increases, the load may be transferred directly into a tensile load on the structural filler 104, rather than internal pressure being amplified into tensile load on the outer enclosure wall 102. The internal pressure of the fluid enclosure 100 may be  
10       affected by the amount of fluid stored. In addition, the amount of stress applied to the fluid enclosure 100 may be affected by the mechanical stress associated with contacting/releasing a fluid from a storage material, such as hydrogen occluding/desorbing from a metal hydride, for example.

          The structural filler 104 may have a continuous, uniform thickness throughout  
15       the fluid enclosure 100. Alternatively, the structural filler 104 may include pockets or areas of discontinuous thickness or density, for example. One case may be where an irregularly shaped fluid enclosure 100 calls for more structural support, such as in a corner, the structural filler 104 may be more dense or include a greater portion of the available space within that area of the fluid enclosure 100.

20

#### Outer Enclosure Wall

          The outer enclosure wall 102 may include a multitude of materials due to the low stress applied to the outer enclosure wall 102. The outer enclosure wall 102 may include a polymer or metal or multiple layers of each, for example. The outer enclosure  
25       wall 102 may be polypropylene, Kynar Flex® (vinylidene fluoride hexafluoropropylene copolymer) (available through Arkema Inc, Philadelphia, PA), polyethylene, polyester, polyvinylidene fluoride (PVDF), hexafluoropropylene vinylidene fluoride copolymer, cross-linked copolymers, polytetrafluoroethylene (PTFE), perfluoro alkoxy (PFA), polyimides, polyamides, poly ether ether ketone  
30       (PEEK), polyetherimide (e.g., Ultem™) and thermoplastic polymers (for example, Nylon™). The outer enclosure wall 102 may be a metal such as aluminum, steel, or any other metal, alloys thereof, or combinations thereof. The outer enclosure wall 102 may be a composite, such as a carbon fiber based composite.

The outer enclosure wall 102 may be formed of the same material as at least a portion of the structural filler 104, for example. The outer enclosure wall 102 may be a sheet or a solution, prior to application. The outer enclosure wall 102 does not have to be rigid or in any pre-formed shape. The outer enclosure wall 102 may act as a barrier to the exit of a fluid from the structural filler 104.

Because the structural filler 104 may be bonded to the outer enclosure wall 102, the stresses induced on the outer enclosure wall 102 become independent of the geometry chosen. In conventional enclosure designs, the geometry of the enclosure strongly dictates the relationship between the stress in the enclosure wall and the internal pressure. If a structural filler 104 is conformably coupled to the outer enclosure wall 102, virtually any geometry of the fluid enclosure 100 may be utilized, so long as the tensile strength of the structural filler 104 and the bond 108 between the structural filler 104 and outer enclosure wall 102 is larger than the internal pressure. The structural filler 104 may be formed into a desired shape before the outer enclosure wall 102 is conformably coupled to it.

The outer enclosure wall 102 may have a uniform or a varying wall thickness, for example. The outer enclosure wall 102 may have a greater wall thickness around a feature, for example. The outer enclosure wall 102 may have an average wall thickness of less than about 5000 microns, less than about 1500 microns, less than about 500 microns, less than about 300 microns, less than about 100 microns, less than about 50 microns, less than about 10 microns or less than about 1 micron, for example.

Referring to FIG. 2, a cross-sectional view of a portion of a fluid enclosure 200 utilizing a composite hydrogen storage material is shown, according to some embodiments. Active particles 204 are immobilized by a binder 206, making up the composite hydrogen storage material, which is an example of a structural filler 104. The outer enclosure wall 202 penetrates within the interface region 208, conformably coupling to the structural filler.

#### Interface Region

The interface region 208 includes the bond 108 between the structural filler 104 and outer enclosure wall 202 and may vary in thickness. The outer enclosure wall 202 may be uniformly or near uniformly bonded to the structural filler 104 so that a homogeneous or near homogenous interface 208 may be formed, which prevents

localized stress concentrations building up at the outer enclosure wall 202. The outer enclosure wall 202 material may be applied to the structural filler 104 and allowed to penetrate the surface, creating a bond 108 in the interface region 208. The interface region 208 may become stronger than the structural filler 104, so that a failure of the fluid enclosure 300 may be a failure from the structural filler 104 and not from the bond 108 found at the interface 208. The interface region 208 may be less than about 50 microns, about 50-100 microns, about 100-150 microns, about 150-200 microns or more than 200 microns thick, for example.

Referring to FIG. 3, a cross-sectional view of a portion of a fluid enclosure 300 utilizing a composite hydrogen storage material including a feature is shown, according to some embodiments. Active particles 204 are immobilized by a binder 206, making up the composite hydrogen storage material, which is an example of a structural filler 104. The outer enclosure wall 202 penetrates within the interface region 208, conformably coupling to the structural filler. One or more features 302 are positioned within the outer enclosure wall 202.

### Features

The one or more features 302 may be adapted to control the movement of a fluid into or out of the fluid enclosure 300, may observe or control the fluid or may be used as a structural component, for example. The one or more features 302 may be used to communicate between the fluid enclosure 300 and an external device, such as a fuel cell. Examples of a feature 302 may be a valve, vent, cap, fitting, regulator, pressure relief device, flow element (i.e., flow restrictor), etc. Examples of the one or more features 302 may include fluidic components sold by Swagelok Co. or Beswick Engineering Co., for example. In the case where the feature may be a pressure relief device, it may be a pressure-activated PRD or a thermally-activated PRD. Further, it may be a self-destructive type PRD, such as fusible trigger, rupture disk or diaphragm, or a re-sealable type, such as spring-loaded pressure relief valve (PRV). Alternately, the outer enclosure wall may be engineered to have a pressure relief feature engineered in/integrated into the wall itself.

The one or more features 302 may be structural features associated with the shape, positioning or alignment of the structural filler, the outer enclosure wall or the overall fluid enclosure. A structural feature may be formed to allow space for external

components or to create more efficient alignment between the fluid enclosure and an external device, for example. Structural features may include convex protrusions, concave recesses, mountings, flanges, fittings, bosses, smoothed or radiused corners, threaded standoffs, latching or locking features, etc.

5           The one or more features 302 may include safety enhancing aspects. For example, the feature may include a small, recessed valve that may only be activated with the proper tool. Further, an example may be features of such size as to make them inaccessible to inadvertent activation, such as small features within a recessed area. The one or more features 302 may also include connecting hardware, in which the fluid  
10 enclosure 300 may be coupled to an external device, such that during connecting/disconnecting of the fluid enclosure 300, little to no leakage occurs. Exemplary connecting hardware may be found, for example, in Adams, et al., U.S. Patent Application No. 2005/0022883, entitled "FUEL CARTRIDGE WITH CONNECTING VALVE,". The connecting hardware may include a first valve  
15 component connectable to one of either a fuel supply or a fuel cell, a second valve component connectable to the other of either a fuel supply or a fuel cell, wherein each valve component comprises a housing and a biased slidable inner body, and wherein the slidable inner body cooperates with a sealing member to form an internal seal in each valve component, and wherein during connection the first valve component and the  
20 second valve component form an inter-component seal at least before the internal seals open to create a fluid flow path through the connecting hardware, such as a valve.

Referring to FIG. 4, a perspective view of a fluid enclosure 400 is shown, according to some embodiments. The fluid enclosure 400 displayed includes a largely prismatic form factor including a concave feature 402 and convex feature 406, such as a  
25 protrusion. The concave feature 402 may be utilized to accommodate an external valve or pressure regulator, for example. The convex feature 406 and rounded corners 404 may be utilized such that the fluid enclosure 400 may fit an available space, such as that provided by an external device, for example. The convex feature 406 may also be used to lock, latch or securely hold the fluid enclosure 400 to or within an external device.  
30 Some structural features, like the convex feature 406, allow for the dual function of fluid storage and efficient alignment/positioning of the fluid enclosure 400.

#### Fluid Enclosure Shape

The fluid enclosure 400 may have a regular or irregular shape. Regular shapes may include cylindrical, prismatic, or polyhedral shapes (i.e., tetrahedral shapes), for example. Irregular shapes may be chosen to conform to fitting within a confined volume or space available, such as to fit within the interior volume of an enclosure of an electronic device. Irregular shapes may also be chosen so as to accommodate features, such as external fittings or fluid control devices. Other form factors, such as irregularly shaped polyhedrons, for example, are also possible.

#### Fluid Enclosure System

Referring to FIG. 5, a perspective view of a fluid enclosure system 500 is shown, according to some embodiments. The fluid enclosure system 500 includes a fluid enclosure 400 coupled to an external device 502. The convex feature 406 and rounded corners 404 of the fluid enclosure 400 may be utilized such that the fluid enclosure 400 may fit the available space provided by the external device 502. Examples of an external device 502 may be a fuel cell, heat pump, battery, compressor or air conditioning unit, for example. Further, the external device may additionally be coupled to an electronic device, such as a portable electronic device, or to the electronics of an electronic device. Examples of portable electronic devices include cellular phones, satellite phones, PDAs (personal digital assistants), laptop computers, ultramobile personal computers, computer accessories, displays, personal audio or video players, medical devices, televisions, transmitters, receivers, lighting devices including outdoor lighting or flashlights, battery chargers or portable power sources, and electronic toys.

The concave feature 402 may house such features 504, 506 as connectors, valves or regulators, for example. The concave feature 402 may also provide a space for electronic/power conditioning associated with a fuel cell power pack.

Referring to FIG. 6, a block flow diagram of a method of manufacturing 600 a fluid enclosure is shown, according to some embodiments. An outer enclosure wall 602 may be conformably coupled 604 to a structural filler 606.

30

#### Conformably Coupling

The outer enclosure wall 602 may be conformably coupled 604 to the structural filler 606 by a variety of methods. Such methods include spraying, painting, dip

coating, inset molding, electrostatic deposition, compression molding, transfer molding, injection molding, thermoset injection molding, vacuum forming, sintering, extrusion, pultrusion, thermoforming, vacuum over-molding, powder coating, solution casting, etc. The wall thickness may be increased by duplicating the coupling process or using a  
5 different coupling process in order to create multiple layers. Not only can multiple layers of the outer enclosure wall 602 be applied, but one or more layers of other materials may be added. For example, if a thin outer enclosure wall is formed, fluid may slowly diffuse through the wall. A sealing layer may be applied to prevent such diffusion. Examples of a sealing layer may be a thin metallic layer, such as aluminum,  
10 copper, gold or platinum. The outer enclosure wall 602 may be comprised of the same or similar material as the structural filler 606, or a portion of the structural filler 606, in order to increase the bond strength, for example. The layers may be heated or sintered after application.

One or more features, including but not limited to structural features, may be  
15 formed in the structural filler 606, formed with the outer enclosure wall 602 or formed during the coupling of the structural filler and outer enclosure wall. Examples of such features include fittings, regulators, fasteners, mounting flanges, bosses, valves, vents, caps, flow elements, etc.

## 20 Fluid Enclosure Size/Volume

Embodiments of the invention allow for a fluid enclosure or fluid enclosure system to be manufactured at sizes not previously contemplated. Although readily usable at large sizes, the fluid enclosure may be as thin as less than about 10mm, for example. The fluid enclosure may have a volume of less than about 1000 cm<sup>3</sup>, less than  
25 about 500 cm<sup>3</sup>, less than about 120 cm<sup>3</sup>, less than about 10 cm<sup>3</sup>, less than about 5 cm<sup>3</sup>, less than about 2 cm<sup>3</sup> or less than about 1 cm<sup>3</sup>, for example. A fluid enclosure system, including an external device, may be less than about 1000 cm<sup>3</sup>, less than about 500 cm<sup>3</sup>, less than about 120 cm<sup>3</sup>, less than about 25 cm<sup>3</sup>, less than about 15 cm<sup>3</sup>, less than about 10 cm<sup>3</sup> or less than about 5 cm<sup>3</sup> for the total system, for example.

30

## Storing Fluid

Referring to FIG. 7, a block flow diagram of a method of storing 700 a fluid is shown, according to some embodiments. A fluid enclosure 702 of the embodiments of

the present invention may be contacted 704 with a fluid, sufficient to provide a fluid enclosure storing fluid 706. The fluid may then be stored for a desired amount of time. After contacting 704 the fluid enclosure 702, the fluid may be released. After releasing the fluid, the fluid enclosure 702 may be contacted again with fluid. The fluid enclosure  
5 702 may be contacted with a fluid and released of fluid multiple times. The fluid enclosure may be contacted with a fluid and the fluid released once, at least about 3 times, at least about 50 times, at least about 300 times, at least about 500 times, at least about 1000 times or at least about 10,000 times, for example.

#### 10 Using Fluid Enclosure

Referring to FIG. 8, a block flow diagram of a method of using 800 a fluid enclosure is shown, according to some embodiments. A fluid enclosure storing a fluid 802 may release 804 a fluid. Releasing 804 all or a portion of the fluid from the fluid enclosure storing a fluid 802 provides a fluid enclosure 806 which may contain less  
15 fluid. The fluid enclosure storing a fluid 802 may be coupled to an external device, such that the fluid is released 804 to the external device for its use or to power the device, for example. Examples of an external device may be a fuel cell, heat pump or electrolyser. The fluid enclosure may also accept fluid from an external device coupled to it, such as an electrolyser, or waste fluid from some types of fuel cells (i.e. spent  
20 electrolyte from a direct borohydride fuel cell, CO<sub>2</sub> produced from any hydrocarbon fuel based fuel cell, such as a formic acid fuel cell, direct methanol fuel cell, reformed methanol fuel cell, etc.).

After releasing 804 the fluid, the fluid enclosure 806 may be contacted with a fluid. The fluid may then be released again. The releasing and contacting of fluid to the  
25 fluid enclosure 806 may be repeated multiple times. The releasing and contacting of fluid to the fluid enclosure may occur once, at least about 3 times, at least about 50 times, at least about 300 times, at least about 500 times, at least about 1000 times or at least about 10,000 times, for example.

Embodiments of the present invention describe a fluid enclosure that may be  
30 used in a portable galvanic or electrochemical cell, such as a fuel cell system, as a fuel reservoir. Other embodiments describe a fluid enclosure that may be used as a storage reservoir for use in a device, such as in heat pumps, hydrogen compressors or air conditioners, for example. Some examples of portable electronics for use with the fuel

cell include, but are not limited to, cellular phones, satellite phones, PDAs, laptop computers, ultra mobile personal computers, computer accessories, displays, personal audio or video players, medical devices, televisions, transmitters, receivers, lighting devices including outdoor lighting or flashlights, electronic toys, battery chargers or  
5 portable power sources, or any device conventionally used with batteries.

The present invention will now be described with the following non-limiting examples.

## 10 Examples

### Example 1

Wafers of a structural filler made from a composite hydrogen storage material were formed by heat and pressure sintering as detailed in U.S. Patent Application Serial No.11/379,970, with densities between about 5 g/cc and about 6.1 g/cc. The wafers  
15 with densities from about 5 to about 5.5 g/cc included about 6% by weight of Kynar Flex® 2851 as a binder. Wafers with densities of about 5.5 to about 6.1 g/cc included about 4% by weight of Kynar Flex® 2851 as a binder. The wafers were substantially free of dust and were substantially free of surface roughness features exceeding about 50 microns ( $\mu\text{m}$ , or  $10^{-6}\text{m}$ ).

20 Components were attached using a Kynar Flex® interface. A solvent solution of about 40 to about 80 g/L Kynar Flex® 2751 was used as a glue for connecting the components to the enclosure. A fluid port or opening was fitted with a 2-micron filter and a small hole (about 0.8 micron) was drilled into the wafer (about 7 microns) to facilitate fluid diffusion into and out of the enclosure.

25 Kynar Flex® 2851 dissolved in acetone was applied as a coating in multiple layers. The first layer was applied by dipping a wafer into a solution of about 40 g/L Kynar Flex® 2851 dissolved in acetone. The solution then penetrated the surface pores of the wafer. Subsequent layers were painted on using about 80 g/L Kynar Flex® 2851 in acetone and were allowed to fully dry between applications. A total of about 20 to  
30 about 30  $\text{mg}/\text{cm}^2$  of coating was disposed uniformly on the wafer. After drying, the remaining coating (outer enclosure wall) was about 100 to about 150 microns thick. The fluid enclosure was then sintered at about 190° C for about 20 minutes.

### Example 2

A prismatic format block of a composite hydrogen storage material was formed with dimensions of about 5cm x 3cm x 0.5cm, corners were radiused and smoothed. Two sheets of polypropylene were formed with approximate dimensions of the prismatic block and placed on either side of the prismatic format block. The three layer structure was then isostatically pressed at about 150 psi (1.03MPa or about 1MPa) and heated to about 180° C for about 30 minutes. Once cooled, the polypropylene sheets had been conformably bonded to the structural filler. An opening was cut in to the conformably formed enclosure wall, and a gas fitting inserted and held in place with adhesive material.

### Example 3

A similar prismatic format block of composite hydrogen storage material, as in Example 2, was formed. RTV Silicone (Dow Corning) was applied as a coating of a thermoset elastomeric polymer. The coating was applied and cured at about 120° C.

The Abstract is provided to comply with 37 C.F.R. §1.72(b) to allow the reader to quickly ascertain the nature and gist of the technical disclosure. The Abstract is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims.

CLAIMS

What is claimed is:

1. A fluid enclosure, comprising:  
a structural filler; and  
an outer enclosure wall, conformably coupled to the structural filler.
2. The fluid enclosure of claim 1, wherein the structural filler comprises a metallic or plastic lattice, composite hydrogen storage material, nano-structured carbon foam, aerogel, zeolite, silica, alumina, graphite, activated carbon, micro-ceramic, nano-ceramic, boron nitride nanotube, borohydride powder, palladium-containing material or combinations thereof.
3. The fluid enclosure of claim 1, wherein the structural filler comprises a composite hydrogen storage material.
4. The fluid enclosure of claim 3, wherein the composite hydrogen storage material comprises a metal hydride.
5. The fluid enclosure of claim 1, wherein the structural filler comprises a lattice including pores.
6. The fluid enclosure of claim 5, wherein the pores support an occluding/desorbing material.
7. The fluid enclosure of any one of claims 1-6, further comprising an occluding/desorbing material.
8. The fluid enclosure of any one of claims 1-7, further comprising a metal hydride.
9. The fluid enclosure of any one of claims 1, 7 or 8, wherein the structural filler comprises occluding/desorbing material.

10. The fluid enclosure of any one of claims 1, 7 or 8, wherein the structural filler comprises a metal hydride.
11. The fluid enclosure of any one of claims 1-10, further comprising a clathrate.
12. The fluid enclosure of any one of claims 1-11, further comprising a methane clathrate.
13. The fluid enclosure of any one of claims 1-12, wherein the structural filler comprises a continuous, uniform thickness throughout the fluid enclosure.
14. The fluid enclosure of any one of claims 1-12, wherein the structural filler comprises a non-uniform thickness throughout the fluid enclosure.
15. The fluid enclosure of any one of claims 1-14, wherein the outer enclosure wall comprises a polymer.
16. The fluid enclosure of any one of claims 1-15, wherein the outer enclosure wall comprises polypropylene, vinylidene fluoride hexafluoropropylene copolymer, polyethylene, polyvinylidene fluoride (PVDF), hexafluoropropylene vinylidene fluoride copolymer, cross-linked copolymers, polytetrafluoroethylene (PTFE), perfluoro alkoxy (PFA), polyimides, polyamides, poly ether ether ketone (PEEK), polyetherimide (e.g., Ultem™), thermoplastic polymers (for example, Nylon™) or combinations thereof.
17. The fluid enclosure of any one of claims 1-15, wherein the outer enclosure wall comprises vinylidene fluoride hexafluoropropylene copolymer.
18. The fluid enclosure of any one of claims 1-17, wherein the outer enclosure wall comprises the same material as at least a portion of the structural filler.
19. The fluid enclosure of any one of claims 1-18, wherein the outer enclosure wall comprises multiple layers.

20. The fluid enclosure of claim 19, wherein the multiple layers are comprised of the same material.
21. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 5000 microns.
22. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 1500 microns.
23. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 500 microns.
24. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 300 microns.
25. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 100 microns.
26. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 10 microns.
27. The fluid enclosure of any one of claims 1-20, wherein the outer enclosure wall has an average thickness of less than about 1 micron.
28. The fluid enclosure of any one of claims 1-27, further comprising one or more features, positioned within the outer enclosure wall.
29. The fluid enclosure of claim 28, wherein the one or more features are selected from the group of a valve, a regulator, a vent, a cap, a pressure relief device, a flow element and combinations thereof.

30. The fluid enclosure of any one of claims 1-29, further comprising one or more structural features.
31. The fluid enclosure of claim 30, wherein the one or more structural features are selected from the group of a boss, a mounting flange, a fastener, a fitting, a concave recess, a radiused corner, a convex protrusion and combinations thereof.
32. The fluid enclosure of claim 31, wherein the one or more structural features comprises a concave recess.
33. The fluid enclosure of 31, wherein the one or more structural features comprises a convex protrusion.
34. The fluid enclosure of any one of claims 1-33, further comprising a fluid, in contact with the structural filler.
35. The fluid enclosure of claim 34, wherein the fluid comprises a gas, a liquefied gas, a liquid or a combination thereof.
36. The fluid enclosure of claim 34, wherein the fluid comprises a gas.
37. The fluid enclosure of any one of claims 1-36, wherein the fluid enclosure comprises a cylindrical shape, a prismatic shape or a polyhedral shape.
38. The fluid enclosure of any one of claims 1-36, wherein the fluid enclosure comprises a tetrahedral shape.
39. The fluid enclosure of any one of claims 1-36, wherein the fluid enclosure comprises an irregular shape, adapted to substantially fit an allotted space.
40. The fluid enclosure of any one of claims 1-39, further comprising one or more sealing layers, conformably coupled to the outer enclosure wall.

41. The fluid enclosure of any one of claims 1-40, further comprising one or more sealing layers, conformably coupled to the structural filler.
42. The fluid enclosure of any one of claims 40 or 41, wherein the one or more sealing layers comprise a metallic layer.
43. The fluid enclosure of any one of claims 40-42, wherein the one or more sealing layers comprise an aluminum layer.
44. The fluid enclosure of any one of claims 1-43, wherein the fluid enclosure comprises a volume of less than about 1000 cubic centimeters.
45. The fluid enclosure of any one of claims 1-43, wherein the fluid enclosure comprises a volume of less than about 10 cubic centimeters.
46. The fluid enclosure of any one of claims 1-43, wherein the fluid enclosure comprises a volume of less than about 5 cubic centimeters.
47. The fluid enclosure of any one of claims 1-43, wherein the fluid enclosure comprises a volume of less than about 2 cubic centimeters.
48. The fluid enclosure of any one of claims 1-43, wherein the fluid enclosure comprises a volume of less than about 1 cubic centimeter.
49. A method of manufacturing a fluid enclosure, the method comprising:  
conformably coupling an outer enclosure wall to a structural filler.
50. The method of claim 49, further comprising before conformably coupling, coupling one or more features to the structural filler or the outer enclosure wall.
51. The method of any one of claims 49 or 50, further comprising after conformably coupling, coupling one or more features to the structural filler, the outer enclosure wall or both.

52. The method of any one of claims 49-51, wherein conformably coupling the outer enclosure wall to the structural filler includes spraying, painting, dip coating, inset molding, electrostatic deposition, compression molding, transfer molding, injection molding, thermoset injection molding, vacuum forming, sintering, extrusion, pultrusion, thermoforming, vacuum over-molding, powder coating, solution casting or combinations thereof.

53. The method of any one of claims 49-51, wherein conformably coupling the outer enclosure wall to the structural filler includes dip coating.

54. The method of any one of claims 49-53, further comprising after conformably coupling, forming one or more sealing layers.

55. The method of claim 50, further comprising before coupling, forming one or more features.

56. A method of storing a fluid, the method comprising:

contacting a fluid enclosure with a fluid, sufficient to provide a fluid enclosure storing a fluid,

wherein the fluid enclosure comprises:

a structural filler; and

an outer enclosure wall, conformably coupled to the structural filler.

57. The method of claim 56, further comprising after contacting, releasing the fluid from the fluid enclosure.

58. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid multiple times.

59. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid at least about 3 times.

60. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid at least about 50 times.

61. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid at least about 300 times.

62. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid at least 500 times.

63. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid at least about 1000 times.

64. The method of claim 57, further comprising after releasing the fluid, contacting and releasing the fluid at least about 10,000 times.

65. A method of using a fluid enclosure, the method comprising:  
releasing a fluid from a fluid enclosure,  
wherein the fluid enclosure comprises:  
a structural filler; and  
an outer enclosure wall, conformably coupled to the structural  
filler.

66. The method of claim 65, further comprising after releasing, contacting the fluid enclosure with a fluid.

67. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure multiple times.

68. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure at least about 3 times.

69. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure at least about 50 times.

70. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure at least about 300 times.

71. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure at least about 500 times.

72. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure at least about 1000 times.

73. The method of claim 66, further comprising after contacting the fluid enclosure, releasing and contacting the fluid enclosure at least about 10,000 times.

74. A fluid enclosure system, the system comprising:  
a fluid enclosure; and  
an external device, coupled to the fluid enclosure;  
wherein the fluid enclosure comprises:  
a structural filler; and  
an outer enclosure wall, conformably coupled to the structural filler.

75. The fluid enclosure system of claim 74, wherein the external device comprises a fuel cell, a heat pump, a hydrogen compressor or an air conditioner.

76. The fluid enclosure system of claim 74, wherein the external device comprises a fuel cell.

77. The fluid enclosure system of claim 76, wherein the fuel cell is further coupled to an electronic device.

78. The fluid enclosure system of claim 77, wherein the electronic device comprises a cellular phone, satellite phone, PDA, laptop computer, ultra mobile personal computer, computer accessory, display, personal audio or video player, medical device, television, transmitter, receiver, lighting device, flashlight, battery charger, portable power source, or electronic toy.

79. The fluid enclosure system of any one of claims 74-78, wherein the fluid enclosure system comprises a volume of less than about 1000 cubic centimeters.

80. The fluid enclosure system of any one of claims 74-78, wherein the fluid enclosure system comprises a volume of less than about 120 cubic centimeters.

81. The fluid enclosure system of any one of claims 74-78, wherein the fluid enclosure system comprises a volume of less than about 25 cubic centimeters.

82. The fluid enclosure system of any one of claims 74-78, wherein the fluid enclosure system comprises a volume of less than about 15 cubic centimeters.

83. The fluid enclosure system of any one of claims 74-78, wherein the fluid enclosure system comprises a volume of less than about 10 cubic centimeters.

84. The fluid enclosure system of any one of claims 74-78, wherein the fluid enclosure system comprises a volume of less than about 5 cubic centimeters.