Powder inhaler

The invention relates to an inhaler for inhaling powdered medicament from capsules which are inserted in a capsule holder arranged in the inhaler before use. After the capsule has been placed in the capsule holder the patient can press an actuating member, which can be set in motion from a resting position and thereby interacts with at least one pin adapted to be pushed into the capsule holder. Using the minimum of one pin the capsule is pierced and the medicament is released.

An inhaler of this kind is described for example in EP 0 703 800 B1 or EP 0 911 047 A1. The inhaler known from the above-mentioned specifications comprises a dish-shaped lower part and an equally dish-shaped cover which fits it, the two parts being adapted to be flipped apart for use by means of a hinge provided at the edge region. Engaging between the lower part and the cover in the hinge are a mouthpiece which can also be flipped out and a plate located below it with a capsule holder provided underneath. After the individual parts have been opened out the patient can place a capsule filled with medicament in the capsule holder, pivot the plate with the capsule holder and the mouthpiece back into the lower part and pierce the capsule by means of a spring-loaded actuating member projecting laterally from the lower part. Sucking on the mouthpiece then causes the medicament to be delivered to the respiratory tract of the patient being treated.

The intention is to improve the known inhalers further in terms of their handling.

In accordance with an aspect of the present invention, there is provided an inhaler for inhaling powdered medicament from capsules, comprising: a lower part, a plate capable of latching to the lower part, with which the lower part can be closed, and a capsule holder for receiving the capsules which can be countersunk in the lower part, a mouthpiece capable of latching to the plate, a cover which covers the mouthpiece in a closed position and latches it by means of a closure element, the lower part, the plate, the mouthpiece and the cover being jointed to one another by a single joint, and an actuating member which can be set in motion from a resting position and thereby co-operated with at least one pin that can be pushed into the capsule holder, characterised in that in the lower part there is at least one operating window with functional elements formed thereon, the minimum of one operating window being capable of being pressed into the lower part in guided and spring-loaded manner and releasing the mouthpiece latched to the plate from said plate by means of the functional elements.

To assist in the understanding of the invention it will now be described more fully by reference to the three Figures that follow, wherein:

Fig. 1: is an exploded view with multi-functional actuating member of an embodiment with main body and thrust projection mounted thereon;

Fig. 1a: is an enlarged detail of the plate, capsule holder and multi-functional actuating member according to Fig. 1;

Fig. 2: is an exploded view of an embodiment with operating windows in the lower part which are capable of being pressed in;

Fig. 3: is an exploded view with multi-functional actuating member of a embodiment with main body and pivot member.

Fig. 1 shows the inhaler in an exploded view. The essential assemblies are the lower part 1 which accommodates the plate 2 and is covered by the latter, the mouthpiece 4 which can be latched to the lower part 1 via the retaining lug 22 and the cover 5 which is formed to complement the lower part 1.

In the closed position of the inhaler the closure element 6 engages on the plate 2 and is held there by frictional engagement. It is also possible to obtain interlocking engagement by the provision of bead-like structures. For the closure element 6 to engage on the plate 2, the main body 10 of the multi-functional actuating member 8a comprises a recess 15, as can be seen most clearly from the enlarged view in Fig. 1a. The recess 15 is provided with an inclined side wall 16 and is located in the area 14 of the upper grooved surface

12 nearest the cover. For particularly reliable operation the multi-functional actuating member 8a is also provided with a lateral grooved surface 13.

To open the cover 5 first of all the multi-functional actuating member 8a is pushed forward into a first functional position. The closure element 6 then makes contact with the inclined side wall 16, which acts as a sliding surface 17 as the main body 10 continues to advance and ensures that the cover 5 is released.

The lower part 1 is cup-shaped and accommodates the whole of the capsule holder 3 arranged on the underside of the plate 2. However, in order to insert a capsule filled with medicament (not shown) the mouthpiece 4 must also be flipped out of the way. In the embodiment according to Fig. 1 this is done by pressing the multi-functional actuating member 8a further into a second functional position. A thrust projection 21 mounted on the main body 10 and aligned in the direction of movement of the main body 10 makes contact, by means of its front edge 23 (Fig. 1a) underneath the plate 2, with a retaining lug 22 projecting through the plate 2, fixedly mounted on the mouthpiece 4. The plate 2 comprises a retaining lug opening 37 in the region where the retaining lug 22 projects through.

As a result of the advancing movement of the thrust projection 21 the retaining lug 22 bends and escapes through the retaining lug opening 37, thereby pivoting the mouthpiece 4 away. This pivoting movement is assisted by an elastic spring 34.

In this opened position of the cover 5 and mouthpiece 4 the capsule can be placed in the capsule holder 3. For releasing the active substance two perpendicularly offset, parallel pins 9 are mounted on the main body, moving continuously as the main body 10 is pushed in towards the capsule (not shown) and perforating it. The perforation process can be observed through an inspection window 24a. Then the mouthpiece 4 is swivelled back again.

In the capsule holder 3 there are tubular pin passages 9a which are aligned axially in accordance with the direction of movement of the pins 9. On the one hand these ensure that the pins are correctly aimed at the capsule (not shown) and on the other hand they provide additional guidance of the multi-functional actuating member 8a. However, the essential guiding is done by two guide arms 11a, 11b arranged laterally on the main body 10. The guide arms 11a, 11b also have the task of holding the multi-functional actuating member 8a under spring bias. For this purpose the guide arms 11a, 11b are provided at their end remote from the main body 19 with end stops 20 which abut on the guide sleeves 18a, 18b in the resting position of the multi-functional actuating member 8a. The guide sleeves 18a, 18b are located on the outside of the capsule holder 3. Between the pins 9 is arranged a helical spring 38 which extends parallel to the pins 9 in its axial direction, the helical spring 38 being matched to the length of the guide arms 11a, 11b such that the multi-functional actuating member 8a is under tension even in the resting position.

The individual assemblies made up of the lower part 1, plate 2, mouthpiece 4 and cover 5 are connected by means of hinge recesses 7a, 7b, 7c 7d and a hinge bolt 7e.

Fig. 2 shows a view similar to Fig. 1, wherein the opening of the cover 5 occurs as the first functional position is reached by actuating the main body 10 of the actuating member 8, similar to the embodiment shown in Fig. 1.

Once the cover 5 has been opened it is necessary to flip the mouthpiece 4 out of the way as well so that a capsule filled with medicament (not shown) can be placed in the capsule holder 3. For this purpose, the patient presses the operating window 24 provided on both sides in the lower part 1. As a result of the pressing action on the operating window 24b the functional elements 25, which are formed in Fig. 2 as upright posts integral with the window, bend inwards into the cavity of the lower part 1. On the ends of the functional

elements there are hooks 26 which project outwards beyond the lower part 1 and when the plate 2 is closed make it possible to engage in the retaining elements 27 located on the inside of the mouthpiece 4 when said mouthpiece 4 is located on the plate 1. As for the mouthpiece 4 which has to be flipped out of the way, when a compressive force is applied to the operating window 24b the hooks 26 slide out of the retaining elements 27, which consist of a retaining collar 28, as in the case shown.

When the capsule (not shown) has been placed in the capsule holder 3 the mouthpiece 4 is swivelled back until it latches with the hooks 26 protruding through the hook passage 36. Then the capsule (not shown) can be pierced by pressing the main body 10. For this, two parallel pins 9 secured to the main body 10 project towards the capsule holder 3. After use the cover 5 is closed again. Meanwhile, the closure element 6 latches on the plate 2.

Fig. 3 shows another embodiment in which the mouthpiece 4 is flipped out of the way in a different way. For this purpose the multi-functional actuating member 8a is made in two pieces. In addition to the main body 10 which is movably mounted for opening the cover 5, on the exterior thereof, rotatable with respect to the main part 10, is the pivot member 29. The pivot member 29 is fixed centrally on the main part 10 on a peg. Eccentrically mounted above the mounting bore 39 is the impact cam 30 which projects into the interior of the lower part 1 when the inhaler is assembled and when rotated in the direction of the arrow in Fig. 3 comes into contact with the retaining arm 31 pointing vertically upwards. In this way, the upper end 32 of the retaining arm 31 in turn is deflected and the retaining hook 33 provided thereon slides out of the retaining element 27 located in the mouthpiece 4, which is also in the form of a retaining collar 28. To allow the retaining hook 33 to slide unobstructed out of the retaining collar 28, the plate 2 has a retaining arm passage 35 of sufficiently large dimensions.

To close the mouthpiece 4 it is pivoted back into the original position. Thanks to the pointed shape of the retaining hook 33 in the direction of the cover 5 it slides through the retaining arm passage 35 onto the inside of the mouthpiece 4 and there it engages behind the retaining collars 28, as a result of the restoring forces present in the retaining hook 33.

List of reference numerals

1	lower part
2	plate
3	capsule holder
4	mouthpiece
5	cover
6	closure element
7a, 7b, 7c, 7d	hinge recesses
7e	hinge bolt
8	actuating member
8a	multi-functional actuating member
9	pin
9a	pin passages
10	main body
11a, 11b	guide arm
12	upper grooved surface
13	lateral grooved surface
14	area nearest the cover
15	recess
16	side wall of the recess
17	sliding surface
18a, 18b	guide sleeve
19	end of the guide arm remote from the main body
20	end stops
21	thrust projection
22	retaining lug
23	front edge thrust projection
24a	inspection window
24b	operating window
25	functional elements
26	hook

27	retaining elements
28	retaining collar
29	pivot member
30	impact cam
31	retaining arm
32	upper end of retaining arm
33	retaining hook
34	elastic spring (housing)
35	retaining arm passage
36	hook passage
37	retaining lug opening
38	helical spring
39	mounting bore

CLAIMS

1. An inhaler for inhaling powdered medicament from capsules, comprising:

a lower part,

a plate capable of latching to the lower part, with which the lower part can be closed, and a capsule holder for receiving the capsules which can be countersunk in the lower part,

a mouthpiece capable of latching to the plate,

a cover which covers the mouthpiece in a closed position and latches it by means of a closure element, the lower part, the plate, the mouthpiece and the cover being jointed to one another by a single joint, and

an actuating member which can be set in motion from a resting position and thereby co-operates with at least one pin that can be pushed into the capsule holder,

characterised in that in the lower part there is at least one operating window with functional elements formed thereon, the minimum of one operating window being capable of being pressed into the lower part in guided and spring-loaded manner and releasing the mouthpiece latched to the plate from said plate by means of the functional elements.

2. The inhaler according to claim 1, characterised in that operating windows are provided opposite one another in the lower part.

3. The inhaler according to claim 1 or claim 2, characterised in that the functional elements comprise hooks and retaining elements constructed to complement them.

4. The inhaler according to any one of the preceding claims, characterised in that the hooks are integrally formed with the minimum of one operating window.

5. The inhaler according to any one of the preceding claims, characterised in that the hooks extend in the manner of crosspieces in the direction of the mouthpiece.

6. The inhaler according to any one of the preceding claims, characterised in that the retaining elements are constructed as eyelets or retaining collars.

7. The inhaler according to any one of the preceding claims, characterised in that the plate latched to the lower part can be released from the lower part such that the plate can be pivoted away from the lower part.

8. The inhaler according to any one of the preceding claims, characterised in that the actuating member is attached to the plate such that it can be released from the lower part and pivoted away together with the plate latched to the lower part.

Powder Inhaler

Abstract

An inhaler is described for inhaling powdered medicament from capsules which are placed in a capsule holder (3) provided in the inhaler before use. Once the capsule has been placed in the capsule holder (3) the patient can press an actuating member (8), which can be set in motion from a resting position and thereby interacts with at least one pin (9) adapted to be pushed into the capsule holder (3). By means of the minimum of one pin the capsule is pierced and the medicament is released.

The intention is to improve inhalers of this kind in terms of ease of operation.

The objective is achieved according to one embodiment of the invention with an inhaler wherein in the lower part (1) there is at least one operating window (24b) with functional elements (25) formed thereon, the minimum of one operating window (24b) being capable of being pressed into the lower part (1) in a guided and spring-loaded manner and releasing the mouthpiece (4) latched to the plate (2) from said plate (2) by means of the functional elements (25).

Fig. 2