

CLAIMS:

1. A convertible baby safety car seat assembly comprising:

an upper seat having a backrest portion and a feet portion, the upper seat being manipulable between an upright state, in which the backrest and feet portions form a first angle therebetween, and an extended state, in which the backrest and feet portions form a second angle therebetween greater than the first angle; and

legs having distal ends with wheels and manipulable between a storage state, and an operational state allowing the seat assembly to be rolled by means of said wheels; the extended state of the upper seat being combinable only with the operational state of the legs, and the operational state of the legs and the upright state of the upper seat being also combinable at least with each other;

characterized in that the storage state of the legs is combinable only with the upright state of the upper seat in a first mode of the seat assembly, the extended state of the upper seat being combinable only with the operational state of the legs in a second mode of the seat assembly.

2. The convertible baby safety car seat assembly according to Claim 1, wherein the operational state of the legs is combinable with the upright state of the upper seat in a third mode of the seat assembly, and the seat assembly can be brought into its first and second modes only from its third mode.

3. The convertible baby safety car seat assembly according to Claim 1 or 2, wherein:

- manipulation of the legs in the second mode of the seat assembly is prevented at least indirectly by the upper seat being in the extended state.

4. The convertible baby safety car seat assembly according to any one of Claims 1 to 3, wherein:

- manipulation of the upper seat in the first mode of the seat assembly is prevented at least indirectly by the legs being in the storage state.

5. The convertible baby safety car seat assembly according to any one of Claims 1 to 4, further comprising:

a seat manipulation prevention arrangement operative to prevent manipulation of the upper seat from the upright state to the extended state at least when the legs are in the storage state.

6. The convertible baby safety car seat assembly according to any one of Claims 1 to 5, further comprising:

a leg manipulation prevention arrangement operative to prevent manipulation of the legs from the operational state to the storage state at least when the upper seat is in the extended state.