

AUTOMATIC SYSTEM FOR GUIDING, RETAINING AND TIGHTENING STEEL WIRE ROPE IN CRANES

Field of the Art

Industrial field: container transport and movement.

5 Steel wire ropes for cranes.

State of the Art

Load ropes in container transport cranes are responsible for hoisting the load, hoisting the jib and, in the most frequent variants, translating the trolley. They are thick gauge, very long ropes without splicing that are subjected to strong loads and which must be periodically renewed. The ropes are anchored by means of
10 fixed wedge terminals and fixed, screwed-in grips or clamps.

The rope changing operation (hoisting the load) currently requires many hours and is done with the jib of the crane in the horizontal position. This situation interferes with the maneuvers of contiguous vessels and cranes: it prevents
15 docking maneuvers and changes in the position of the cranes while the rope changing operation lasts.

The ropes must be tightened such that the spreader (engaging element) is perfectly aligned and level with the container. Since the anchoring of the ropes is fixed, this operation has a significant cost in terms of hours and manual labor.

Description of the Invention

Technical problem considered

The rope changing operation requires immobilizing the crane for a considerable time. During this maneuver it is necessary to remove all the rope anchoring points and allow them to pass through the crane as easily as possible.

25 The position of the crane and jib in the dock creates interference problems with the remaining operations: vessel maneuvers and positioning of other cranes.

Anchoring the ropes at the end of the jib requires using equipment and tools for disassembling/assembling the clamps. This area has little space for personnel; it is pounded against by the wind and is exposed to problems due to falling objects
30 and other risks inherent to working at elevated heights.

Brief Description of the Invention

A system (10) is described which allows automatic, instant and remote-controlled actuation.

The assembly (Figure 1) includes sliding clamps (Figure 2), the actuation of
35 these clamps (11), additional guidance system and automatic tightening device

(14) for tightening the ropes (13).

The clamps (Figure 2) are based on a wedge mechanism having a suitable shape and angles so as to be self-blocking, to exert enough pressure without damage the rope (13) and to be actuated with a force that is much lower than the strain of the rope (13) they support. If the clamp actuator was to fail, the friction between the rope (13) and wedges would keep the latter in the closed position.

Automatic operations and the jib in the vertical position make better guidance of the run of the rope (13) necessary. The tightening device (14) in turn increases the force on the sheaves (12); therefore said sheaves (12) and their support shafts must be reinforced.

Detailed Description of the Invention

The proposed system (Figure 1) requires an automatic clamp for each end of each rope. Only one tightening device needs to be used, although variants could be designed with independent tightening devices or with common actuations for the clamps.

The system (10) consists of: four clamps (11), one for each end, with their respective actuations. The clamp (11) is formed by two sliding wedges and a rigid casing. The actuation is gauged such that it can close or open the wedges.

The sheaves (12) guide the rope (13), preventing the clamps (11) from receiving transverse stresses and preventing the rope from being rubbed or from experiencing heavy bending. Furthermore, the slack portions that are formed aid in tightening the rope and leveling the spreader increasing or decreasing the run of the rope by means of the tightening device (14) and the selective closing of the corresponding clamp (11).

Brief Description of the Drawings

Figure 1 shows the arrangement of the device. It is depicted with the direct linear arrangement of the tightening device and of the four clamps (11) by means of hydraulic cylinders (15). It should be mentioned that this is only one variant among many possible variants (pneumatic cylinders, solenoids, electric motors, worm gear transmission, etc).

The sheaves (12), with the additional guidance device, are arranged such that both ropes (13) are maintained in parallel planes, without the possibility of rubbing against one another when they are under load.

The tightening device (14) has a relatively broad run, the effect of which is increased by the arrangement of the inner sheaves (12).

The outer sheaves (12) maintain the coaxiality between the ropes (13) and the axis of the clamps (11).

Immediate variants of the proposed system are obtained by changing the order between components, changing the number of clamps (11) or tightening devices (14), or by placing the latter in other directions and maintaining guidance by means of sheaves, bolts or other suitable elements.

Figure 2 is a detail of Figure 1 showing a possibility of operating the clamps (11), located in the open position. There are two independent wedges inside the casing (20), sliding on inclined planes. The actuator of the wedges is a hydraulic cylinder (15), the rod (22) of which has been located close to the axis of the clamps (11) to minimize bending stresses.

The casing (20) is very robust since it must resist high normal forces which tend to open its side walls. A variant with two milled plates screwed together is shown, although there are many other possibilities.

Preferred Embodiment of the Invention

The figures shown correspond with a specific embodiment. The five actuations are hydraulic cylinders (15), forming part of the same circuit. The hydraulic station (not shown) is arranged in the same area.

The mobile wedges have two clearly different faces. The outer wall slides on the casing (20) and is rectified in order to reduce friction. The inner wall braces the rope (13) and has a groove machined therein such that the closure of the two clamps is hexagonal, with 4 areas of pressure on the rope (13), so as to prevent damaging it. This wall is knurled to assure the grip and to cause self-locking in the event of a malfunction in the actuation.

The casing (20) has special grooving (21) to allow the pins moving the wedges when such wedges are shifted to transversely come close to one another.

The sheaves (12), with additional guidance device, are arranged such that both ropes (13) are maintained in parallel planes, without the possibility of rubbing against one another when they are under load. The frames of the sheaves (12) and their support shafts are calculated to resist the full rope load (full break hypothesis of the clamps).

For economic, space and simplicity reasons, a single tightening device (14) is used in the embodiment, however this is not an essential feature of the proposed system.

Almost all the elements are subjected to heavy loads, and are exposed to

the elements under tough climate conditions. They are therefore designed in steel having suitable features.

CLAIMS

1.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes, characterized in that it comprises:

- at least one self-blocking clamp for engaging each end of each rope;
- at least one tightening element that engages each rope at a position between said self-blocking clamps; and
- sheaves for guiding the ropes between said self-blocking clamps and said tightening element.

2.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claim 1, characterized in that the clamps comprise a rigid casing inside which there are two independent sliding wedges.

3.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claim 2, characterized in that the wedges comprise an outer wall sliding on the casing and an inner wall bracing the rope.

4.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claim 3, characterized in that the outer wall sliding on the casing is rectified to reduce friction.

5.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claim 3, characterized in that the inner wall bracing the rope has a machining in the form of a groove to prevent damaging the rope and knurling to assure the grip, causing the self-locking.

6.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claim 2, characterized in that the casing has grooving to allow pins moving the wedges when such wedges are shifted to transversely come close to one another.

7.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claim 1, characterized in that the sheaves comprise an additional guidance device to maintain the ropes parallel without the possibility of rubbing against one another when they are under load.

8.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to claims 1 or 7, characterized in that the sheaves are located to avoid that the rope rubs or experiences considerable damages and the clamps receive transverse stresses.

9.- Automatic system for guiding, retaining and tightening steel wire ropes in cranes according to any of the preceding claims, characterized in that it comprises a hydraulic actuation system for the tightening device and the clamps.