



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: B22F 3/12, 3/16, 5/00	A1	(11) International Publication Number: WO 98/02266 (43) International Publication Date: 22 January 1998 (22.01.98)
(21) International Application Number: PCT/US97/06970 (22) International Filing Date: 25 April 1997 (25.04.97) (30) Priority Data: ① 08/678,776 / 11 July 1996 (11.07.96) / US (71) Applicant (for all designated States except US): SCM METAL PRODUCTS, INC. [US/US]; 2601 Weck Drive, Research Triangle Park, NC 27709-2166 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): ① NADKARNI, Anil, V. [US/US]; 105 Thetford Court, Chapel Hill, NC 27516 (US). ② ABRAMS, John, T. [US/US]; 8908 Wellsley Way, Raleigh, NC 27613 (US). ③ KELLY, Roy [US/US]; 1667A South Hayes Street, Arlington, VA 22202 (US). (74) Agents: KALOW, David, A. et al.; Kalow, Springut & Bressler, 43rd floor, 380 Lexington Avenue, New York, NY 10168 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, (SG) SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: LEAD-FREE FRANGIBLE BULLETS AND PROCESS FOR MAKING SAME (57) Abstract The invention relates to bullets having increased frangibility (or which can be easily fragmented) and to materials and processes for the manufacture of such bullets. The bullets of the present invention are typically made from copper or copper alloy powders (including brass, bronze and dispersion strengthened copper) which are pressed and then sintered under conditions so as to obtain bullets with the desired level of frangibility. In preferred embodiments of the invention, the bullets also contain several additives that increase or decrease their frangibility.		