

ATM PARTIAL CUT-THROUGH

The present invention concerns transmission of data over networks.

5

The most traditional network is the telephone network. The arrival of ISDN has greatly enhanced the capabilities of telephony and in particular the bandwidth available to users. Telecommunication networks such as
10 telephony, FR (Frame Relay) and X25 are what is known as "connection-oriented". Thus prior to sending information across a connection-oriented network a user must be allocated a circuit either by provision or demand. Once this has been achieved the user can then send and receive
15 information across the network between host machines.

In parallel with the arrival of broadband telephony there has been a very substantial growth in what are known as "connectionless" networks. Connectionless
20 networks encompass LANs but in particular the most significant connectionless network is the Internet.

In a connectionless network a user does not have to obtain a circuit connection with a desired destination
25 prior to sending the information across the network. This is because information is sent in datagrams which contain header field information which intermediate nodes

use for routing purposes. There are a number of data networking protocols which have been designed for connectionless network paradigms. These include the Internet Protocol (IP), SNA (Systems Network
5 Architecture), Appletalk and IPX and all transport data in the form of datagrams. Such datagrams will hereinafter be referred to as connectionless datagrams.

In addition to the above two basic types of network,
10 the arrival of broadband networks heralded by the introduction of optical fibres has substantially increased the range and nature of data which can be transmitted over telephone lines. Thus while some users may be content with merely maintaining voice connections
15 at constant bit rates other users might wish to have access to other connection types such as video and data at variable bit rates. Thus users now require the ability to select from a number of connection types in accordance with their needs. What are known as ATM
20 (Asynchronous Transfer Mode) networks have been developed to meet this demand. In a typical ATM network a user can choose between a plurality of potential connection types, for example a fixed rate voice link, a variable bandwidth link peaking at 10 megabits and with a mean of
25 5 megabits, and a third variable bandwidth link peaking at 20 megabits and having a mean of 8 megabits. The second of these connection types can be used for high

speed data transfer and the third for the transmission of video images.

In order to maximise the potential bandwidth available to users the telecommunications industry has developed what are known as virtual path (VP) networks. VP networks differ in two ways from the traditional telephone network already described. In a VP network each user is allocated a bandwidth appropriate to his assumed needs in the various connection types and the ATM network management provide bandwidth by selecting a route from all of the available paths in the network. It will be appreciated that it would be uneconomic to provide each user all the time with all the maximum bandwidth that that user might require. Accordingly, in VP network the sum of the nominal bandwidths allocated to the users connected in the network is substantially greater than the total bandwidth of the network.

Thus, ATM networks provide a high speed technology that is likely to become fundamental in telephony because of its multi service capabilities. However, ATM still has difficulty in supporting traffic which is based on the connectionless paradigm of the Internet and other LAN-type networks.

In accordance with one aspect of the present

invention there is provided a method of transmitting across a network a connectionless datagram in a packet structure having the form of a series of packets, the header including the routing information of the connectionless datagram being mapped into the payload of the first packet structure, and wherein at an intermediate node of the network a connectionless routing function is carried out on said first packet.

10 In accordance with a second aspect there is provided a switching node for a data network, the switching node comprising:

an ATM switch;

means for accepting a connectionless datagram and
15 converting the datagram into a plurality of ATM cells in which header information in the connectionless datagram is inserted into the payload of the first cell of the ATM cell structure; and

means for detecting the length of the header fields
20 of the connectionless datagram and if the length of these fields is too great to be contained in the payload of the first cell of the ATM cell structure generating a partial header checksum and inserting this checksum into the payload of the first ATM cell together with only the
25 header fields of the connectionless datagram up to and including the destination address.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

In accordance with a third aspect there is provided a switching node for a data network, the switching node comprising:

an ATM switch;

5 means for accepting a connectionless datagram and converting the datagram into a plurality of ATM cells in which header information in the connectionless datagram is inserted into the payload of the first cell of the ATM cell structure; and

10 means for detecting the length of the header fields of the connectionless datagram and if the length of these fields is too great to be contained in the payload of the first cell of the ATM cell structure generating a partial header checksum and inserting this checksum into the
15 payload of the first ATM cell together with only the header fields of the connectionless datagram up to and including the destination address.

The present invention is also directed to a data
20 network incorporating switching nodes as set out hereinbefore.

In order that the present invention may be more readily understood an embodiment thereof will now be
25 described by way of example and with reference to the accompanying drawings in which:

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

6

Figure 1 shows a typical ATM network;

Figure 2 shows a typical ATM cell;

5 Figure 3 is a diagram showing a known method of transporting IP over an ATM network;

Figure 4 is a similar diagram showing a method of achieving direct connection between originating and
10 destination hosts;

Figure 5 is a similar diagram to Figures 3 and 4 showing a process of integrating connectionless datagram traffic and ATM in accordance with the present invention;
15

Figures 6 and 7 show protocols respectively for IP v 4 and IP v 6; and

Figures 8 and 9 show ATM cells generated in
20 accordance with the present invention.

Referring now to Figure 1 of the accompanying drawings, there is shown a block diagram of a conventional ATM network. The ATM network consists of
25 a network of partially interconnected switching nodes in the form of ATM switches 10 to 18. Traffic in an ATM network consists of cells which are transmitted from node

to node in the network. In the network of Figure 1, switches 10, 11, 12, 13, 15, 16, 17 and 18 also function as access switches. Each of the access switches is connected to a set of access lines which connect the switch to other networks or directly to customer equipment. By way of illustration, Figure 1 shows switch 17 connected by one access line to a computer 22 and by another access line to a multiplexer 24. The computer 22 is provided with an ATM card which enables it to transmit and receive data in the form of ATM cells. The multiplexer 24 can receive video, data and speech signals and convert these in a multiplexed manner into ATM cells. Likewise, it can receive ATM cells from the switch 17 and convert these to video, data and voice signals. Typically, the multiplexer 24 will be located at the premises of a user of the ATM network.

As is known to those skilled in the art, when transmitting an ATM cell between the ATM input interface and the ATM output interface, initial values are inserted into the virtual path identifier (VPI) and virtual channel identifier (VCI) fields in the header. The ATM input or output interface may be in an access node or outside the ATM network, for example in computer 22 or multiplexer 24. Then, at each switching node, the values of the VPI and/or VCI fields are read and one or both of the values are used together with a routing table to

select an output port. Before the ATM cell leaves the switch, the values of one or both of the VPI and VCI fields are updated in accordance with data contained in a routing table. The VPI field provides a coarse level
5 of routing whereas the VCI field provides a fine level of routing. The routing tables are set up partly by network management and partly during call set up. Mainly, but not entirely, virtual path routing tables are set up by network management and virtual channel routing
10 tables are set up by signalling during call set up.

The structure of a basic ATM cell and the header fields will now be described.

15 Referring now to Figure 2, a basic ATM cell comprises a five-octet header 40 and a 48-octet user payload section 42. The cell header 40 is used to route the cell between switches across the network and the user payload section 42 contains the user's data and it is
20 carried transparently across the network and delivered unchanged at the far end. As will become apparent this basic cell is generally much smaller than a connectionless datagram.

25 Referring now to Figure 3 of the drawings, this shows a network of IP routers 200 connected to ATM switches 201. The classic approach to supporting IP over

ATM is to establish, at the ATM layer, a permanent virtual circuit (PVC), permanent virtual path (PVP) or switched virtual circuit (SVC) link between adjacent routers within a chain. Therefore, when the originating
5 host sends a connectionless datagram to the destination host, ATM cells of the kind shown in Figure 2 are used to transport the datagram information on a hop-by-hop basis between the intermediate nodes within the chain, the original datagram being segmented into a plurality
10 of ATM cells when travelling between the ATM switches at the intermediate nodes. In this mode the ATM network is being used to provide leased line or LAN-to-LAN interconnect type services. In order to generate the ATM cells what is known as an ATM Adaptation Layer is used
15 to decompose the IP datagram into ATM cells.

The problem with this approach is that at each of the nodes the original IP datagram has to be reassembled so that the IP router 200 at the intermediate node can
20 utilise the header field information and then returned through the AAL layer for onward transmission by the ATM switch to the next node. As can be seen in Figure 3 this involves using the IP layer router at the IP layer to determine the output port of the router which is to be
25 used, and resegmenting the IP datagram into ATM cell format using an AAL process for onward transmission by the associated ATM switch. This approach has the



10

drawback that the end-to-end delay increases with the number of intermediate nodes due to the time it takes for them to reassemble the IP datagram and resegment it into ATM cells. Accordingly this known approach involving IP over ATM is unsuitable for IP flows that have a short delay requirement and/or a long duration, and a direct connection between the two hosts may become preferable as this is more efficient in both end-to-end delay and network resource utilisation. Additionally, each of the IP routers 200 at the intermediate nodes in the chain has to buffer data which it does not directly need to process.

Figure 4 of the accompanying drawings shows an approach which has been proposed to meet the problems of the arrangement shown in Figure 3. This approach is known as ATM cut-through and proposes the use of a direct connection over the ATM layer between the originating and destination hosts. It is achieved by providing a mapping between IP and ATM addresses. This mapping allows the originating host in Figure 4 to discover the address of the ATM switch connected to the destination host and then to route all cells directly across the ATM network to this switch, thus bypassing all of the intermediate nodes. However, this approach still has problems. Firstly, it is not suited to all IP sessions. In particular, advantages of ATM cut-through are only

THIS SHEET HAS BEEN REPLACED

realised where the IP sessions are of a suitably long duration for them to benefit from cut-through being applied. Additionally, after setting up a connection the datagrams are not sent to intermediate routers so router
5 functionality such as re-routing, header error checking etc. become inaccessible. A third problem is that in order to achieve ATM cut-through mapping is required between the IP and ATM network addressing schemes. The result of this is that ATM cut-through is only useful for
10 long-term sessions and does not address the requirements of shorter and increasingly higher data-rate sessions.

The problems of both of these known approaches are met in the system and method disclosed in Figure 5 of the
15 accompanying drawings. In order to distinguish the method of the present invention from the previously described methods, it will be referred to hereinafter as ATM partial cut-through.

20 As shown in Figure 5, the ATM partial cut-through system occupies the middle ground between the two extremes of classic IP over ATM in which every intermediate node is fully involved, and ATM cut-through in which there is a direct mapping between host and
25 destination. As seen in Figure 5, each node consisting of an IP layer router 200 and an ATM switch 201 has an additional functionality provided at 202 which will be

referred to hereinafter as "first cell processing". Thus in the system shown in Figure 5, when the originating host initiates an IP session in which data is to be sent to the destination host via datagrams, the ATM cell structure is arranged so that only the first cell of the structure derived from the original datagram carries routing information and all the cells following this first cell carry only the payload information of the original datagram. At each intermediate node the router at that node uses the first cell processing functionality to determine the route of the entire datagram as represented by the plurality of ATM cells whilst data forwarding of the ATM cells is left to the ATM layer (layer 2 or the data link layer of the OSI reference model). Thus based on the knowledge that the payload of the first ATM cell contains all of the relevant routing information within the IP header, it becomes possible by detecting the first cell and opening the payload to extract IP layer information which is capable of routing all of the ATM cells. This enables very efficient datagram forwarding as the datagram does not have to be reassembled and resegmented at each intermediate node and, as will be described later, also enables datagram discarding within the ATM layer.

25

In order to implement partial cut-through additional software and hardware functions will be needed to

implement the "first cell processing features". These features include the identification of cells containing IP headers, the reading of the IP fields and the consequences of such reading, the buffering of the ATM
5 cells containing the rest of the datagram, the calculation of the forwarding path and managing the forwarding process. However, this functionality does not affect standard ATM processes so it can be implemented within each ATM switch without affecting standard ATM
10 VPI/VCI cell forwarding processes.

In accordance with the embodiment being described, the means for detecting the first cell of an IP datagram is provided by using one of the ATM Adaptation Layer
15 (AAL) processes which have already been established for the transmission of IP data over an ATM network. Examples of these already existing AAL processes are AAL3/4 and AAL5.

20 Referring now to Figure 6 of the accompanying drawings, this figure represents a datagram having fields which conform with the IP v 4 protocol and in the figure the fields bounded by the bold lines constitute the IP datagram header. The key for the fields is set out in
25 Table 1 below.

14

TABLE 1

	V	Version
	HL	Head Length
	ST	Service Type
5	TL	Total Length
	Id	Identification
	FB	Flag Bits
	FO	Fragment Offset
	TtL	Time to Live
10	Pr	Protocol
	HC	Header Checksum
	SIPA	Source IP Address
	DIPA	Destination IP Address
	O	Options (if any)
15	P	Padding (if any)
	IP DP	IP Datagram Payload

The payload of a typical connectionless diagram can be substantially larger than the payload capacity of an ATM cell. For example, the IP protocol allows payloads of up to approximately 65 kilobytes.

Figure 7 of the drawings is a similar representation to Figure 6 and shows a datagram having fields which correspond to the IP v 6 Protocol. Again the fields bounded by the bold line represent the IP Datagram header. Table 2 below sets out those fields which differ

15

from the fields of Figure 6.

TABLE 2

	Py	Priority
5	FL	Flow Label
	HL	Hop Limit

When a connectionless datagram, in the present embodiment an IP datagram, is processed at the AAL layer
10 the variable length datagram is segmented into ATM cells of the kind described in Figure 2. Thus the AAL layer will generate ATM cells of the kind shown in Figures 8 and 9. In these figures the bold lines encompass the ATM cell header. Other fields which are not common to the
15 IP datagrams described with reference to Figure 6 and 7 are set out in Table 3.

TABLE 3

	VPI	Virtual Path Indicator
20	VCI	Virtual Circuit Indicator
	PT	Payload Type
	CLP	Cell Loss Priority
	HEC	Header Error Check
	PCRC	Partial Cylic Redundancy Code

25

The cell shown in Figure 8 is generated at the AAL layer from an IP v 4 datagram using AAL5. As already

explained, an IP datagram and any other type of connectionless datagram is likely to be substantially larger than an ATM cell.

5 At the AAL layer the IP datagram is segmented into ATM cells of the kind described in Figure 2 and as a result of this segmentation the header section of the IP datagram is inserted into the payload of the first ATM cell along, in many cases, with some of the payload, i.e.

10 the first 48 octets of the IP datagram will become the payload of the first ATM cell, the second 48 octets of the IP datagram will become the payload of the second ATM cell and so on until the whole IP datagram has been converted into the ATM cell structure. Each ATM cell

15 will, of course, have the appropriate ATM header as shown in bold lines.

The cell structure shown in Figure 9 has been generated from an IP v 6 datagram also using AAL 5 and

20 similar considerations apply.

In both cases it will be seen that the header of the IP datagram which includes all the IP routing information has been included within the payload of the first of the

25 ATM cells generated at the AAL layer. As will also be appreciated, the information from the original IP datagram also contains a field which indicates the total

length of the original datagram. Note that in this embodiment, the IP header does not include header options (IP v 4) or header extensions (IP v 6). These extend the size of the header such that they will not necessarily
5 reside completely within the first cell of the ATM structure after the IP datagram has been processed at the AAL. For the purposes of partial cut-through, these options and extensions are therefore treated as part of the payload and, as in ATM cut-through, are not processed
10 by the immediate routers.

Subsequent cells generated at the AAL layer are not shown as these cells will be conventional ATM cells with the 48 octet payload sections of the cells carrying the
15 IP datagram payload.

Once the IP datagram has been converted into the ATM cell structure it will be transported from the first ATM switch shown in Figure 5 to the first of the intermediate
20 nodes. At this intermediate node the first cell of the ATM cell structure is subjected to the first cell processing function 202 at that node. This function will include the identification of cells containing IP header information, the reading of the IP fields, the
25 calculation of the forwarding path and managing the forwarding process. This can be achieved by copying the IP header contents of the first of the ATM cells to the

first cell processing function carrying out the recording process whilst buffering the ATM cells. It will thus be seen that when carrying out partial cut-through only the IP header information is processed at the IP layer.

5 Consequently the additional first cell processing functionality carried out on the extracted IP header information has no effect on the standard ATM switching processes support from the requirements to buffer the following cells. As the first cell processing function

10 has access to the length of the original datagram and this datagram, including the IP header information, has been broken into 48 octet segments, the first cell processing function will also know the number of ATM cells which had been generated at the AAL layer of the

15 originating node. This has the result that the first cell processing functionality provides the ability to implement datagram discard at the ATM layer as it is possible to calculate the total number of cells arriving at the ATM switch and check whether or not there is

20 sufficient spare buffer capacity to store all of the datagram's cells.

Another feature provided by the system shown in Figure 5 is that error checking can be carried out at the

25 intermediate node by the IP layer router. When ATM cut-through is applied, as in the system shown in Figure 4, the IP header error check feature supported by IP v 4 is

lost. However with ATM partial cut-through as shown in Figure 5 the usual IP header error checking processes are preserved provided the first ATM cell contains all of the IP header information, including all options. This is
5 necessary because the IP v 4 CRC check is across the header and all options, and some of these options could be in the second cell.

In certain circumstances this condition may be
10 violated. Because of this the source and destination hosts shown in Figure 5 may include a Service Specific Convergence Sublayer (SSCS) process within the AAL to detect over-length headers, IP v 4 headers, or any request for the insertion of an optical CRC for the
15 IP v 6 header. This CRC is optional because, unlike IP v 4, the IP v 6 header has no CRC of its own. Optional insertion of a CRC might be useful to detect header corruption within the ATM network so that the cells associated with the header corruption and carrying
20 the payload of the complete datagram can be discarded.

In such a case the SSCS process inserts a new CRC field into the original IP header. This new field is a partial header checksum calculated only for the IP header fields up to and including the destination address. When this
25 new field is inserted into the IP header field it is placed immediately after the destination address field, as is shown in Figure 8.

The processing that needs to be invoked by the originating host, intermediate nodes, and destination host when using ATM partial cut-through are listed below. Purely for illustrative purposes, it has been assumed
5 that the SSCS process is being applied for both IP v 4 and IP v 6 using a standard AAL type. It is also being assumed that the availability of buffer space will be checked against the number of cells within each datagram and then either reserved or all of the cells discarded
10 as necessary.

Originating Node

Receive IP datagram

Forward to AAL Processing

SSCS Part of Process

15 if IP CRC processing being used at intermediate nodes then

Read datagram Version field

if IP v 6 then

calculate partial_CRC

20 insert partial_CRC field after destination address

end

if IP v 4 then

if Header Length field > available payload
25 space in the ATM cell then

calculate partial_CRC

insert partial_CRC field after destination address

21

end

end

end

ATM transmission

5

Intermediate Node

ATM reception

Identify first cell in datagram

Copy and forward payload from the first cell to the

10 'first cell processing' functionality

Read datagram Version field

While buffering incoming cells do

if IP v 6 then

calculate number of cells in datagram using

15 the Payload Length field

end

if IP v 4 then

calculate number of cells in datagram using

Header Length and Total Length fields

20 end

check whether or not sufficient buffer space is available
to store the datagram's cells

if sufficient buffer space available then reserve buffer
25 space if IP CRC processing being used at intermediated
node then

if IP v 6 then

calculate partial_CRC for partial
header

22

compare with partial_CRC field
contents

if compared CRC values are not
equal then

5 indicate datagram cells
 are to be discarded

end

end

if IP v 4 then

10 if Header Length field >
 available payload space within
 the ATM cell then

 calculate partial_CRC for
 partial header

15 compare with partial_CRC
 field contents

 if compared CRC values
 are not equal then

20 indicate datagram
 cells are to be
 discarded

end

else

 calculate header checksum

25 compare with Header
 Checksum field contents

 if compared Header
 Checksum values are not
 equal then

23

indicate datagram
cells are to be
discarded

end

5

end

end

end

if IP CRC processing is not being used at
intermediate nodes then

10

indicate datagram cells are not to
be discarded

end

if datagram cells are to be discarded then

15

release buffer space reserved for the
datagram's cells

initiate discard of all received cells
stored in the cache buffer

discard all remaining cells associated
with this datagram

20

else

Forward IP address information to routing
function

Read address

25

Identify forwarding parameters (eg VPI,
VCI and output port number)

Switch all of the datagram's cells
through the ATM switch

ATM transmission

24

```

    end
  end
  if insufficient buffer space available then
    initiate discard of all received cells stored
5    in the cache buffer
    discard all remaining cells associated with
    this datagram
  end
end
10
Destination Node
  ATM reception
  Forward to AAL processing
  SSCS Part of the AAL Process
15  if IP CRC processing being used at intermediate nodes
    then
      Read datagram Version field
      if IP v 6 then
        remove partial_CRC field
20      else
        if Header Length field > available payload
        space in the ATM cell then
          remove partial_CRC field
          end
25      end
    end
  end
  Forward datagram.
```

The system described as partial cut-through has a

number of advantages over ATM cut-through.

Firstly the ATM switches are able to forward ATM cells based on IP addresses and routing information

5 Secondly access to the IP datagram length information fields allows the ATM switch to check buffer resource availability and to apply a datagram discard policy at the ATM layer.

10 Thirdly access to IP header checksum information allows the ATM switch to discard immediately all of the datagram's cells if the header is errored.

Fourthly IP addresses are used to determine the route across the ATM network thus removing the need for an address resolution processes (ARP): consequently there
15 is no requirement for IP to E164 address mappings.

Fifthly normal ATM processes are unaffected.

It may be appreciated that the invention may be used to transmit a connectionless datagram across a network
20 as a series of packets. When using the invention to transmit a connectionless datagram in this manner, the header of the connectionless datagram is mapped into the payload of the first packet of the series of packets. At the intermediate nodes of the network, a
25 connectionless routing function is carried out on the first packet of the series of packets and the remaining packets remain in the layer which corresponds to layer 2 (the data link layer) of the OSI reference model.

CLAIMS


1. A method of transmitting across a network a connectionless datagram in a packet structure having the form of a series of packets, the header including the routing information of the connectionless datagram being mapped into the payload of the first packet structure, and wherein at an intermediate node of the network a connectionless routing function is carried out on said first packet.

2. A method according to claim 1, wherein the connectionless datagram comprises a plurality of ATM cells, and at an intermediate node of the network the connectionless routing function is carried out on the first cell of the ATM cells with the remaining cells remaining in the ATM layer.

3. A method according to claim 1 or claim 2, wherein the connectionless datagram is segmented into the ATM cell structure by an AAL (ATM Adaptation Layer) process carried out at the originating node.

4. A method according to any preceding claim, including means for detecting the length of said cell structure, for reserving buffer space at the intermediate node, and for discarding the cells of the cell structure if the





reserved space is insufficient to hold the entire ATM cell structure.

5. A method according to claim 3 or claim 4, wherein
5 at the or each intermediate node a connectionless datagram header error checking process is carried out on the payload of the first cell of said cell structure.
6. A method according to any one of claims 1 to 5,
10 wherein all the datagram cells are discarded at an intermediate node if an error in the connectionless datagram header is detected at that node.
7. A method according to any one of claims 1 to 6,
15 wherein at the originating node the length of the header is checked, and if this length is over a set value, a new partial CRC field is inserted into the original connectionless datagram header field, and at the or each intermediate node this partial CRC field is checked for
20 errors.
8. A switching node for a data network, the switching node comprising:
an ATM switch;
25 means for accepting a connectionless datagram and converting the datagram into a plurality of ATM cells in which header information in the connectionless datagram

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



is inserted into the payload of the first cell of the ATM cell structure; and

means for detecting the length of the header fields of the connectionless datagram and if the length of these fields is too great to be contained in the payload of the first cell of the ATM cell structure generating a partial header checksum and inserting this checksum into the payload of the first ATM cell together with only the header fields of the connectionless datagram up to and including the destination address.

9. A switching node for a data network, the switching node comprising:

an ATM switch;

means for accepting a connectionless datagram and converting the datagram into a plurality of ATM cells in which header information in the connectionless datagram is inserted into the payload of the first cell of the ATM cell structure; and

means for detecting the length of the header fields of the connectionless datagram and if the length of these fields is too great to be contained in the payload of the first cell of the ATM cell structure generating a partial header checksum and inserting this checksum into the payload of the first ATM cell together with only the header fields of the connectionless datagram up to and including the destination address.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



29

10. A node according to claim 8 or claim 9 including means for discarding all the cells if the extracted header instruction is faulty.


- 5 11. A system for transmitting connectionless datagrams across a multi-layer network comprising a switching node as claimed in claim 8 in combination with a switching node as claimed in any one of claims 8 to 10.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

1/5



2/5

FIG. 2





FIG. 3



3/5

FIG. 4





FIG. 5



4/5

FIG. 6

V	HL	ST	TL	
Id			FB	FO
TIL		Pr	HC	
SIPA				
DIPA				
O				P
IPDP				

FIG. 7

V	P	FL		
PL		Py	HL	
		SIPA		
		SIPA		
		SIPA		
		SIPA		
		DIPA		
		DIPA		
		DIPA		
		DIPA		
		IPDP		

5/5

FIG. 8

VPI		VCI		PT	CLP
HEC					
V	HL	ST	TL		
Id			FB	FO	
TIL		Pr	HC		
SIPA					
DIPA					
PCRC			O	P	
IPDP					
IPDP					
IPDP					
IPDP					
IPDP					
IPDP					


FIG. 9

VPI		VCI		PT	CLP
HEC					
V	P	FL			
PL		Pr	HL		
SIPA					
SIPA					
SIPA					
SIPA					
DIPA					
DIPA					
DIPA					
DIPA					
PCRC				P	
IPDP					

drawback that the end-to-end delay increases with the number of intermediate nodes due to the time it takes for them to reassemble the IP datagram and resegment it into ATM cells. Accordingly this known approach involving IP
5 over ATM is unsuitable for IP flows that have a short delay requirement and/or a long duration, and a direct connection between the two hosts may become preferable as this is more efficient in both end-to-end delay and network resource utilisation. Additionally, each of the
10 IP routers 200 at the intermediate nodes in the chain has to buffer data which it does not directly need to process.

Pages 1409-1424 of Document Computer Networks and
15 ISDN Systems, 1994, Vol. 26, No. 11, describe the above method of operation. In the method described in this document all connectionless datagram cells leave the ATM to undergo payload processing prior to being forwarded.

20 Figure 4 of the accompanying drawings shows an approach which has been proposed to meet the problems of the arrangement shown in Figure 3. This approach is known as ATM cut-through and proposes the use of a direct connection over the ATM layer between the originating and
25 destination hosts. It is achieved by providing a mapping between IP and ATM addresses. This mapping allows the originating host in Figure 4 to discover the address of the ATM switch connected to the destination host and then to route all cells directly across the ATM network to
30 this switch, thus bypassing all of the intermediate nodes. However, this approach still has problems. Firstly, it is not suited to all IP sessions. In particular, advantages of ATM cut-through are only

CLAIMS

1. A method of transmitting a connectionless datagram across a network, said connectionless datagram having a header which includes its routing information, said network having an input interface and an output interface and at least one intermediate node, said method comprising the steps of:

at the input interface, decomposing the connectionless datagram into a packet structure comprising a series of packets, each packet having a header and a payload, the header of the connectionless datagram being mapped into the payload of the first packet of the packet structure; and

at an intermediate node of the network, performing a connectionless routing function on the first packet of the packet structure with the remaining cells of the packet structure remaining in the data link layer.

2. A method as claimed in claim 1 wherein:

the network is an ATM network;

at the input interface, the connectionless datagram is decomposed into a cell structure comprising a series of ATM cells, each cell having a header and a payload, the header of the connectionless datagram being mapped into the payload of the first cell; and

at the intermediate node, the connection routing



function being performed on the first cell of the cell structure with the remaining cells remaining in the ATM layer.

- 5 3. A method according to claim 2, wherein the connectionless datagram is segmented into the ATM cell structure by an AAL (ATM Adaptation Layer) process carried out at the originating node.
- 10 4. A method according to claim 2 or claim 3, including detecting the length of said cell structure, reserving buffer space at the intermediate node, and discarding the cells of the cell structure if the reserved space is insufficient to hold the entire ATM cell structure.
- 15 5. A method according to claim 3 or claim 4, wherein at the or each intermediate node a connectionless datagram header error checking process is carried out on the payload of the first cell of said cell structure.
- 20 6. A method according to any preceding claim, wherein all the datagram cells are discarded at an intermediate node if an error in the connectionless datagram header is detected at that node.
- 25 7. A method according to any preceding claim, wherein at the originating node the length of the header is




checked, and if this length is over a set value, a new partial CRC field is inserted into the original connectionless datagram header field, and at the or each intermediate node this partial CRC field is checked for errors.

8. A multi-layer data network for transmitting connectionless gatagrams in which a connectionless datagram has a header which includes its routing information, said network having an input interface and an output interface and at least one intermediate node, said input interface being adapted to decompose a connectionless datagram into a packet structure comprising a series of packets, each packet having a header and a payload and to map the header of the connectionless datagram into the payload of the first packet of the packet structure; and said intermediate node of the network being adapted to perform a connectionless routing function on the first packet of the packet structure with the remaining cells of the packet structure remaining in the data link layer.

9. A network as claimed in claim 8 wherein, the network is an ATM network; and said input interface is adapted to decompose the connectionless datagram into a cell structure comprising a series of ATM cells, each cell having a header and a





payload, the header of the connectionless datagram being mapped into the payload of the first cell; and

intermediate node is adapted to the connectionless perform routing function on the first cell of the cell structure with the remaining cells remaining in the ATM layer.

10. A switching node for a data network, the switching node comprising:

10 an ATM switch;

means for accepting a connectionless datagram and converting the datagram into a plurality of ATM cells in which header information in the connectionless datagram is inserted into the payload of the first cell of the ATM cell structure; and

means for detecting the length of the header fields of the connectionless datagram and if the length of these fields is too great to be contained in the payload of the first cell of the ATM cell structure generating a partial header checksum and inserting this checksum into the payload of the first ATM cell together with only the header fields of the connectionless datagram up to and including the destination address.

25 11. A node according to claim 10, including means for discarding all the cells if the extracted header instruction is faulty.

invention there is provided a method of transmitting a connectionless datagram across a network, said connectionless datagram having a header which includes its routing information, said network having an input interface and an output interface and at least one intermediate node, said method comprising the steps of:

5 at the input interface, decomposing the connectionless datagram into a packet structure comprising a series of packets, each packet having a header and a payload, the header of the connectionless datagram being mapped into the payload of the first packet of the packet structure; and

 at an intermediate node of the network, performing a connectionless routing
10 function on the first packet of the packet structure with the remaining cells of the packet structure remaining in the data link layer.

 In accordance with a second aspect there is provided a multi-layer data network for transmitting connectionless datagrams in which a connectionless datagram has a header which includes its routing information, said network having an
15 input interface and an output interface and at least one intermediate node, said input interface being adapted to decompose a connectionless datagram into a packet structure comprising a series of packets, each packet having a header and a payload and to map the header of the connectionless datagram into the payload of the first packet of the packet structure; and said intermediate node of the network being
20 adapted to perform a connectionless routing function on the first packet of the packet structure with the remaining cells of the packet structure remaining in the data link layer.

 In accordance with a third aspect there is provided a switching node for a data network, the switching node comprising:

25 an ATM switch;

 means for accepting a connectionless datagram and converting the datagram into a plurality of ATM cells in which header information in the connectionless datagram is inserted into the payload of the first cell of the ATM cell structure; and


 means for detecting the length of the header fields of the connectionless
30 datagram and if the length of these fields is too great to be contained in the payload of the first cell of the ATM cell structure generating a partial header checksum and inserting this checksum into the payload of the first ATM cell together with only the

REPLACEMENT SHEET

18 AUG 1999

header fields of the connectionless datagram up to and including the destination address.

In order that the present invention may be more readily understood an embodiment thereof will now be described by way of example and with reference to
5 the accompanying drawings in which:






checked, and if this length is over a set value, a new partial CRC field is inserted into the original connectionless datagram header field, and at the end or each intermediate node this partial CRC field is checked for errors.

- 5 8. A multi-layer data network for transmitting connectionless datagrams in which a connectionless datagram has a header which includes its routing information, said network having an input interface and an output interface and at least one intermediate node, said input interface being adapted to decompose a connectionless datagram into a packet structure comprising a series of packets, each packet having
- 10 a header and a payload and to map the header of the connectionless datagram into the payload of the first packet of the packet structure; and said intermediate node of the network being adapted to perform a connectionless routing function on the first packet of the packet structure with the remaining cells of the packet structure remaining in the data link layer.

15

9. A network as claimed in Claim 8 wherein, the network is an ATM network; and said interface is adapted to decompose the connectionless datagram into a cell structure comprising a series of ATM cells, each cell having a header and a

20






PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 11/04		A1	(11) International Publication Number: WO 97/50276
			(43) International Publication Date: 31 December 1997 (31.12.97)
(21) International Application Number: PCT/GB97/01681 (22) International Filing Date: 20 June 1997 (20.06.97) (30) Priority Data: 9613020.8 21 June 1996 (21.06.96) GB (71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): HODGKINSON, Terence, Geoffrey [GB/GB]; 46 Melton Grange Road, Melton, Woodbridge, Suffolk IP12 1SD (GB). O'NEILL, Alan, William [GB/GB]; 2 Rachael's Court, 36 Cemetery Road, Ipswich IP4 2JA (GB). (74) Agents: BERESFORD, Keith, Denis, Lewis et al.; Beresford & Co., 2-5 Warwick Court, High Holborn, London WC1R 5DU (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: **ATM PARTIAL CUT-THROUGH**



(57) Abstract

A method of transmitting across an ATM network a connectionless datagram in a cell structure having the form of a plurality of ATM cells, the first cell of which carries in its payload the routing information of the connectionless datagram, and wherein at an intermediate node of the network a connectionless routing function is carried out on said first cell with the remaining cells remaining in the ATM layer.