

Description

This invention relates in general to nestable and extendable pouring spouts for containers and in particular to such spouts having a venting means for reducing pulsations in the outflowing liquid.

There are a number of prior known nestable and extendable pouring spouts. Representative examples are shown in the following U.S. Patent Nos: 2,561,596 to Rieke, July 24, 1951; 2,565,699 to Rieke, August 28, 1951; 2,661,128 to Rieke, December 1, 1953; 2,895,654 to Rieke, July 21, 1959; 3,040,938 to Smith, June 26, 1962; 3,250,428 to Rieke, May 10, 1966; 3,604,740 to Summers, September 14, 1971; 3,613,966 to Summers, October 19, 1971; 3,804,305 to Rieke, April 16, 1974; and 4,295,583 to Schurr, October 20, 1981.

Of the above listed patents, Nos. 3,040,938 and 4,295,583 relate particularly to vented spouts.

In many cases a smooth outflow of liquid from spout of a container is particularly important. Examples are where it is desired to decant a precise amount of liquid from a large stock container into a smaller container or where the liquid is corrosive or toxic and splashing must therefore be avoided.

Smooth, pulsation-free outflow may be obtained with a conventional spout by carefully controlling the angle of the spout with regard to the fluid level in the container so that the spout never flows full, thereby maintaining an air passageway through the spout into the container. One disadvantage of this method is that the required degree of control is often difficult to maintain, especially where the container is heavy. Another disadvantage is that only a fraction of the cross sectional area of the spout is available for fluid outflow when the container is near full, thus increasing the time necessary to decant the liquid.

As a solution to the aforementioned problems, prior nestable and extendable spouts have been fitted with venting devices for maintaining an air passageway through the spout regardless of the angle of pouring, enabling venting of the container even though the opening of the container is completely submerged (see Smith, 3,040,938 and Schurr, 4,295,583). These prior venting devices are essentially tubes mounted concentrically within the neck of the spout so as to form an annular air space between the tube and the neck. The base of the tube is fitted with a flange having a plurality of small peripheral channels, which flange is drawn up against the base of the spout when the spout is in its extended orientation. In this orientation, air may enter the container through the annular space and the peripheral channels while the fluid exits through the central tube.

Although the venting devices exemplified in Smith ('938) and Schurr ('583) function well, they have non-functional disadvantages associated with their structure. For instance, the venting device must be manufactured as a separate piece which is then mounted within the neck of the

spout and secured thereto by welding or adhesive. This is a relatively expensive manufacturing process. Additionally, the venting device adds to the overall axial length of the spout when it is in its nested orientation, thus increasing the handling, packaging and shipping costs of such a spout.

It would be desirable to provide a nestable and extendable pouring spout with a self contained venting means which may be inexpensively manufactured and which maintains the compact configuration of such spouts.

Another example of a prior known nestable and extendable pouring spout is shown in German patent No. 1924824. This spout includes a deformable "bellows" part by means of which an outer socket end part may take up a nested orientation or an extended pouring orientation with respect to a base flange by means of which the spout is secured to the mouth of a container. The spout includes four projections which extend inwardly when the seal is in its extended orientation. The spout is intended to reduce splashing of contents when a container is righted, by means of the four projections. The projections do not touch or overlap. According to the invention there is provided a pouring spout for use with a container, comprising a spout having extending means for alternately disposing said spout in a nested orientation or in an extended pouring orientation;

means for securing the pouring spout to the container; and

a plurality of ears attached to the spout, which extend inwardly within the spout when the spout is disposed in the extended pouring orientation (see DE-C-1924824) characterised in that when the spout is disposed in the extended pouring orientation, the plurality of ears cooperates to define a central flow aperture for the outflow of liquid and each pair of adjacent ears defines a peripheral vent opening therebetween for the inflow of air, the cross-section of said central flow aperture being smaller than the interior flow cross-section of any subsequent spout outflow portion.

One object of the present invention is to provide an improved self-venting nestable pouring spout which is compact and inexpensive to manufacture.

One embodiment of the invention will now be described by way of example only and with reference to the accompanying drawings, in which:

FIG. 1 is an elevation view in full section of one embodiment of the vented nestable pouring spout of the present invention, shown in its nested orientation.

FIG. 2 is an elevation view in full section of the spout of FIG. 1, shown in its extended orientation.

FIG. 3 is a bottom plan view of the spout of FIG. 2 in its extended orientation, particularly showing the venting structure.

FIG. 4 is a top plan view of the spout of FIG. 1, particularly showing the tamper indicating seal.

FIG. 5 is a bottom plan view of an alternate embodiment of a vented nestable pouring spout

in its extended orientation, particularly showing the venting structure.

Referring to Figs. 1 and 2, there is illustrated nestable pouring spout 10 having as its principle components a mounting portion 11, a body portion 12, and a neck portion 13. In the preferred embodiment, mounting portion 11, body portion 12, and neck portion 13, together with ears 19, seal 24 and pull ring 25 which are described below, are integrally molded from a low density flexible polyethylene plastic.

Mounting portion 11 is an annular U-shaped channel configured to mount on an annular lip 14 which encompasses a generally circular opening in a container 20. Lip 14 may be made of plastic or metal. Anchor ring 15, which is preferably constructed of zinc plated steel, is crimped over mounting portion 11 to compress it about and secure it to lip 14, thereby effecting an air-tight, liquid-tight seal between mounting portion 11 and lip 14.

Body portion 12 is a generally funnel shaped member which is secured at its larger circumferential edge to mounting portion 11 and at its smaller circumferential edge to neck portion 13. Body portion 12 includes invertible fold portions 16 and 17, which folds cause body portion 12 to be generally S-shaped in section along a plane parallel to the longitudinal axis 18 of nestable pouring spout 10. Body portion 12 is substantially circular in cross-section along a plane perpendicular to axis 18. Attached at the outside surface of invertible fold portion 16 is a plurality of circumferentially spaced ears 19, each of which extends downwardly substantially parallel to longitudinal axis 18 when nestable pouring spout 10 is in its nested orientation. In this orientation the ears do not restrict the opening of the container and do not interfere with the attainment of a fully nested orientation by the neck and body portions. Ears 19 provide a self-venting action for spout 10, which will be described in greater detail below.

Neck portion 13 is a generally cylindrical tube having threads 21 near its upper end for threadedly receiving a cap 23 having corresponding threads 22. Disposed within the opening of neck portion 13 is a disk-like seal 24 having a pull ring 25 attached proximate one edge of seal 24. Seal 24 is provided with an annular peripheral groove 26 which provides a weakened point at which seal 24 will break away when pull ring 25 is pulled.

Cap 23, which is preferably molded from a high density polyethylene plastic, includes integrally molded flexible bail handles 27 which, when cap 23 is threadedly attached to neck portion 13, provide a convenient means for grasping neck portion 13 and pulling it out into its extended orientation, as is shown in Fig. 2.

When nestable pouring spout 10 is in its initial nested orientation prior to opening, there is disposed over cap 23 and neck portion 13 a tamper indicating seal 28 which, if it is intact and undeformed, provides a quick visual indication that

there has been no attempt to open nestable pouring spout 10.

A nestable pouring spout which is generally of the type shown herein, but without ears 19, is more fully disclosed in United States Patent No. 3,619,966 issued to Summers on October 19, 1971, which disclosure is hereby incorporated by reference.

The user of a container having a nestable pouring spout 10 mounted thereon first grasps pull-tab 29 on tamper indicating seal 28 (see Fig. 4), pulls the seal free and discards it. Bail handles 27 on cap 23 are then grasped and pulled in order to draw neck portion 13 out into its extended orientation. Cap 23 is then unscrewed and removed to gain access to seal 24. Pull ring 25 is grasped by the user and pulled, causing seal 24 to break free along groove 26. The contents of the container can then be poured out and cap 23 can be screwed back onto neck portion 13 to reseal the container in the event that the container is only partially emptied.

As neck portion 13 is drawn outwardly, invertible fold portions 16 and 17 of body portion 12 invert such that the S-shaped curvature of body portion 12 is reversed when neck portion 13 is in its fully extended orientation, as is shown in Fig. 2. In particular, as invertible fold portion 16 inverts, each ear 19, which is securely attached thereto, will rotate inwardly substantially about its point of attachment. When neck portion 13 and body portion 12 reach their fully extended orientations, ears 19 extend inwardly from mounting portion 11 substantially perpendicular to longitudinal axis 18.

As is shown most clearly in Fig. 3, in the extended orientation of spout 10, end portions 32 of adjacent ears 19 are contiguous so as to define a central flow aperture 33. In this orientation ears 19 also define a plurality of generally triangular peripheral vent openings 34, one located between each pair of adjacent ears 19.

Because flow aperture 33 is of a somewhat smaller diameter than the interior diameter of neck portion 13, the outward flow of liquid from the container does not fill neck portion 13. It should be noted that liquid will flow out of some of the submerged peripheral vent openings also, especially those at the lowest elevation for a particular pouring angle. Therefore, the area of the peripheral openings must be taken into account in determining the best relationship of the diameter of aperture 33 to the diameter of neck portion 13 to insure that neck portion 13 does not flow full at any pouring angle. This insures that air may always enter through neck portion 13, through the uppermost peripheral vent openings 34, and into the container, thereby equalizing the pressure within and without the container and permitting the smooth outflow of liquid.

The incoming air enters the container peripherally of the outflowing liquid stream so that the liquid stream is not interrupted and pulsation and splashing are kept to a minimum while

mitting full flow through flow aperture 33. Although the precise dynamics of the liquid and air flow are not fully understood, it is believed that the optimum ratio between the area of the peripheral vent openings 34 and the central aperture 33 is a function of the viscosity and surface tension characteristics of the liquid.

It has been observed that when high viscosity liquids are being decanted, a portion of the incoming air will pass through central flow aperture 33. The air which enters through aperture 33 tends to form large bubbles which span the diameter of aperture 33, causing pulsations and discontinuities in the liquid outflow. This phenomenon may be partially controlled by increasing the area of each peripheral vent opening to enable a greater portion of the incoming air to pass through the peripheral vent openings rather than through the central flow aperture. One way to make each peripheral vent opening larger is to use a lesser number of ears. The area of each peripheral vent opening can also be increased by specially shaping the ears, such as by making each ear relatively narrow at its base where it is attached to the invertible fold, with each ear increasing in width toward its end portion.

One embodiment particularly suited for viscous liquids is illustrated in FIG. 5. The members shown in FIG. 5 which correspond to similar previously described members are designated with corresponding primed numerals. For example, ears 19' in FIG. 5 correspond to similar ears 19 in FIG. 3. As shown, the embodiment of FIG. 5 includes cylindrically shaped nibs 35 which are molded integrally with and project from ears 19' inwardly into aperture 33' when the spout is in its extended pouring orientation. Nibs 35 in combination with ears 19' define a central flow aperture 33' which has a dentated perimeter in the sense that the aperture has perimetrically located toothlike projections which extend inwardly. The dentated perimeter serves to break up any large bubble which might otherwise tend to pass whole through aperture 33'. By breaking up large bubbles into smaller bubbles, the outflow of liquid is made more nearly continuous with fewer and smaller pulsations. It is to be understood that nibs 35 need not be of the particular shape shown. For example, nibs 35 could be triangularly or rectangularly shaped, and there could be more or fewer nibs per ear.

Claims

1. A pouring spout for use with a container, comprising: a spout (10) having extending means for alternately disposing said spout (10) in a nested orientation or in an extended pouring orientation; means for securing the pouring spout (10) to the container (20); and a plurality of ears (19) attached to the spout (10), which extend inwardly within the spout (10) when the spout (10) is disposed in the extended pouring orientation, characterised in that when the spout (10) is disposed in the extended pouring orientation, the

plurality of ears (19) cooperates to define a central flow aperture (33) for the outflow of liquid and each pair of adjacent ears (19) defines a peripheral vent opening (34) therebetween for the inflow of air, the cross-section of the central flow aperture (33) being smaller than the interior flow cross-section of any subsequent spout outflow portion.

2. The spout of claim 1, characterised in that said plurality of ears (19) are circumferentially spaced when the spout (10) is disposed in the nested orientation and are substantially perpendicular to the longitudinal axis of said spout (10) when the spout is in the extended pouring orientation.

3. The spout of claim 1 or 2, characterised in that said ears (19) are oriented to avoid interference with said spout (10) when said spout (10) is disposed in the nested orientation.

4. The spout of claim 1, 2 or 3, characterised in that the spout (10) comprises an annular mounting portion (11); the securing means (15) for securing said annular mounting portion (11) to said container (20) at an opening in the container (20); a neck portion (13) located concentrically with and inwardly of said mounting portion (11); a body portion (12) disposed between said neck portion (13) and said annular mounting portion (11) and of integral construction therewith.

5. The spout of claim 4, characterised in that said body portion (12) has an invertible fold portion (16) adjacent said mounting portion.

6. The spout of claim 5, characterised in that said ears (19) are attached directly to the outer surface of said invertible fold portion (16).

7. The spout of claim 6, characterised in that said ears (19) rotate inwardly substantially about their point of attachment as the invertible fold (16) inverts when said spout (10) is drawn into its extended orientation.

8. The spout of any preceding claim, characterised in that said ears (19) are substantially rectangular plates, each having a width and a length dimension such that the end portions (32) of adjacent ears (19) are contiguous when said spout (10) is in its extended orientation whereby a substantially triangular vent opening (34) is provided between adjacent ears (19).

9. The spout of any preceding claim, characterised in that the central flow aperture (33) has a dentated perimeter.

10. The spout of claim 9, characterised in that said dentated perimeter is defined by said ears (19') and a plurality of nibs (35) extending from said ears (19').

11. The spout of claim 10, characterised in that said plurality of nibs (35) includes a pair of cylindrical shaped nibs (35) extending from the end portion (32') of each ear (19').

12. The spout of any preceding claim, characterised in that said extending means (27) includes a removable, resealable cap (23) having an attached bail handle (27).

13. The spout of claim 12, characterised in that the spout (10) includes a tamper indicating seal

mitting full flow through flow aperture 33. Although the precise dynamics of the liquid and air flow are not fully understood, it is believed that the optimum ratio between the area of the peripheral vent openings 34 and the central aperture 33 is a function of the viscosity and surface tension characteristics of the liquid.

It has been observed that when high viscosity liquids are being decanted, a portion of the incoming air will pass through central flow aperture 33. The air which enters through aperture 33 tends to form large bubbles which span the diameter of aperture 33, causing pulsations and discontinuities in the liquid outflow. This phenomenon may be partially controlled by increasing the area of each peripheral vent opening to enable a greater portion of the incoming air to pass through the peripheral vent openings rather than through the central flow aperture. One way to make each peripheral vent opening larger is to use a lesser number of ears. The area of each peripheral vent opening can also be increased by specially shaping the ears, such as by making each ear relatively narrow at its base where it is attached to the invertible fold, with each ear increasing in width toward its end portion.

One embodiment particularly suited for viscous liquids is illustrated in FIG. 5. The members shown in FIG. 5 which correspond to similar previously described members are designated with corresponding primed numerals. For example, ears 19' in FIG. 5 correspond to similar ears 19 in FIG. 3. As shown, the embodiment of FIG. 5 includes cylindrically shaped nibs 35 which are molded integrally with and project from ears 19' inwardly into aperture 33' when the spout is in its extended pouring orientation. Nibs 35 in combination with ears 19' define a central flow aperture 33' which has a dentated perimeter in the sense that the aperture has perimetricaly located toothlike projections which extend inwardly. The dentated perimeter serves to break up any large bubble which might otherwise tend to pass whole through aperture 33'. By breaking up large bubbles into smaller bubbles, the outflow of liquid is made more nearly continuous with fewer and smaller pulsations. It is to be understood that nibs 35 need not be of the particular shape shown. For example, nibs 35 could be triangularly or rectangularly shaped, and there could be more or fewer nibs per ear.

Claims

1. A pouring spout for use with a container, comprising: a spout (10) having extending means for alternately disposing said spout (10) in a nested orientation or in an extended pouring orientation; means for securing the pouring spout (10) to the container (20); and a plurality of ears (19) attached to the spout (10), which extend inwardly within the spout (10) when the spout (10) is disposed in the extended pouring orientation, characterised in that when the spout (10) is disposed in the extended pouring orientation, the

plurality of ears (19) cooperates to define a central flow aperture (33) for the outflow of liquid and each pair of adjacent ears (19) defines a peripheral vent opening (34) therebetween for the inflow of air, the cross-section of the central flow aperture (33) being smaller than the interior flow cross-section of any subsequent spout outflow portion.

2. The spout of claim 1, characterised in that said plurality of ears (19) are circumferentially spaced when the spout (10) is disposed in the nested orientation and are substantially perpendicular to the longitudinal axis of said spout (10) when the spout is in the extended pouring orientation.

3. The spout of claim 1 or 2, characterised in that said ears (19) are oriented to avoid interference with said spout (10) when said spout (10) is disposed in the nested orientation.

4. The spout of claim 1, 2 or 3, characterised in that the spout (10) comprises an annular mounting portion (11); the securing means (15) for securing said annular mounting portion (11) to said container (20) at an opening in the container (20); a neck portion (13) located concentrically with and inwardly of said mounting portion (11); a body portion (12) disposed between said neck portion (13) and said annular mounting portion (11) and of integral construction therewith.

5. The spout of claim 4, characterised in that said body portion (12) has an invertible fold portion (16) adjacent said mounting portion.

6. The spout of claim 5, characterised in that said ears (19) are attached directly to the outer surface of said invertible fold portion (16).

7. The spout of claim 6, characterised in that said ears (19) rotate inwardly substantially about their point of attachment as the invertible fold (16) inverts when said spout (10) is drawn into its extended orientation.

8. The spout of any preceding claim, characterised in that said ears (19) are substantially rectangular plates, each having a width and a length dimension such that the end portions (32) of adjacent ears (19) are contiguous when said spout (10) is in its extended orientation whereby a substantially triangular vent opening (34) is provided between adjacent ears (19).

9. The spout of any preceding claim, characterised in that the central flow aperture (33) has a dentated perimeter.

10. The spout of claim 9, characterised in that said dentated perimeter is defined by said ears (19') and a plurality of nibs (35) extending from said ears (19').

11. The spout of claim 10, characterised in that said plurality of nibs (35) includes a pair of cylindrical shaped nibs (35) extending from the end portion (32') of each ear (19').

12. The spout of any preceding claim, characterised in that said extending means (27) includes a removable, resealable cap (23) having an attached bail handle (27).

13. The spout of claim 12, characterised in that the spout (10) includes a tamper indicating seal



(28) attached to said spout (10) and disposed over the cap (23) when said spout (10) is in its initial nested orientation.

14. The spout of any preceding claim, characterised in that the spout (10) includes a removable seal (24) within the neck portion (13).

Patentansprüche

1. Ausgießtülle zur Verwendung in Verbindung mit einem Behälter, umfassend eine Tülle (10) mit Ausziehmitteln zur wahlweisen Anordnung der Tülle (10) in einer zusammengeschobenen Stellung oder in einer ausgezogenen Ausgießstellung, Mittel zum Befestigen der Ausgießtülle (10) an dem Behälter (20), und eine Vielzahl von an der Tülle (10) angeschlossenen Lappen (19), die sich innerhalb der Tülle (10) nach innen erstrecken, wenn sich die Tülle (10) in der ausgezogenen Ausgießstellung befindet, dadurch gekennzeichnet, daß bei ausgezogener Ausgießstellung der Tülle (10) die Vielzahl der Lappen (19) so zusammenwirkt, daß sie eine zentrale Durchflußöffnung (33) für das Ausfließen von Flüssigkeit begrenzt, und jedes Paar nebeneinanderliegender Lappen (19) eine dazwischenliegende periphere Lüftungsöffnung (34) für das Einströmen von Luft bildet, wobei der Querschnitt der zentralen Durchflußöffnung (33) kleiner ist als der innere Strömungsquerschnitt jeglichen folgenden Ausflußabschnittes der Tülle.

2. Tülle nach Anspruch 1, dadurch gekennzeichnet, daß die Vielzahl von Lappen (19) in Umfangsrichtung beabstandet sind, wenn die Tülle (10) sich in der zusammengeschobenen Stellung befindet, und im wesentlichen im rechten Winkel zur Längsachse der Tülle (10) stehen, wenn sich die Tülle in der ausgezogenen Ausgießstellung befindet.

3. Tülle nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Lappen (19) so ausgerichtet sind, daß sich Lappen und Tülle (10) nicht in die Quere kommen, wenn die Tülle (10) in der zusammengeschobenen Stellung angeordnet wird.

4. Tülle nach Anspruch 1, 2 oder 3, dadurch gekennzeichnet, daß die Tülle (10) umfaßt: einen ringförmigen Befestigungsabschnitt (11), die Befestigungsmittel (15) zur Befestigung des ringförmigen Befestigungsabschnittes (11) am Behälter (20) an einer Öffnung im Behälter (20), einen konzentrisch zu dem Befestigungsabschnitt (11) und innerhalb desselben angeordneten Halsabschnitt (13) und einen zwischen dem Halsabschnitt (13) und dem ringförmigen Befestigungsabschnitt (11) angeordneten und mit letzterem einstückigen Rumpfabschnitt (12).

5. Tülle nach Anspruch 4, dadurch gekennzeichnet, daß der Rumpfabschnitt (12) angrenzend an den Befestigungsabschnitt einen umstülpbaren Faltabchnitt (16) besitzt.

6. Tülle nach Anspruch 5, dadurch gekennzeichnet, daß die Lappen (19) unmittelbar an der Außenfläche des umstülpbaren Faltabchnittes (16) angeschlossen sind.

7. Tülle nach Anspruch 6, dadurch gekennzeichnet, daß die Lappen (19) sich im wesentlichen um ihren Anschlußpunkt nach innen drehen, wenn die umstülpbare Falte (16) beim Ausziehen der Tülle (10) in ihre ausgezogene Stellung umgestülpt wird.

8. Tülle nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Lappen (19) im wesentlichen rechteckige Platten sind, die jeweils eine solche Breiten- und Längenabmessung haben, daß die Endabschnitte (32) benachbarter Lappen (19) aneinanderliegen, wenn sich die Tülle (10) in ihrer ausgezogenen Stellung befindet, wodurch sich eine im wesentlichen dreieckige Lüftungsöffnung zwischen benachbarten Lappen (19) ergibt.

9. Tülle nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die zentrale Durchflußöffnung (33) eine gezackte Peripherie aufweist.

10. Tülle nach Anspruch 9, dadurch gekennzeichnet, daß die gezackte Peripherie durch die Lappen (19') und eine Vielzahl von sich von den Lappen (19') wegerstreckenden Nasen (35) gebildet ist.

11. Tülle nach Anspruch 10, dadurch gekennzeichnet, daß die Vielzahl von Nasen (35) ein Paar von sich vom Endabschnitt (32') jedes Lappens (19') wegerstreckender, zylinderförmiger Nasen (35) umfaßt.

12. Tülle nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Ausziehmittel (27) eine abnehmbare, wiederaufsetzbare Kappe (23) mit einem daran angeschlossenen Griffbügel (27) umfassen.

13. Tülle nach Anspruch 12, dadurch gekennzeichnet, daß die Tülle (10) einen Originalitätsverschluß (28) aufweist, der an der Tülle befestigt und über der Kappe (23) angeordnet ist, wenn die Tülle (10) sich in der zusammengeschobenen Ausgangsstellung befindet.

14. Tülle nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Tülle (10) einen abnehmbaren Verschluß (24) innerhalb des Halsabschnittes (13) aufweist.

Revendications

1. Bec verseur destiné à être utilisé avec un récipient, comprenant: un bec (10) doté de moyens prolongateurs permettant de disposer le bec (10) soit selon une orientation emboîtée soit selon une orientation sortie de versement;

des moyens de fixation du bec verseur (10) sur le récipient (20) et

une pluralité d'oreilles (19) attachées au bec (10) et s'étendant vers l'intérieur à l'intérieur du bec (10) lorsque le bec (10) est disposé selon l'orientation sortie de versement, caractérisé en ce que, quand le bec (10) est dans l'orientation sortie de versement, la pluralité d'oreilles (19) coopèrent afin de délimiter un orifice d'écoulement central (33) permettant la sortie de liquide et chaque paire d'oreilles voisines (19) délimite entre elles un orifice d'aération périphérique (34)



pour l'admission d'air, la section de passage de l'orifice d'écoulement central (33) étant inférieure à la section de passage intérieure de n'importe laquelle des portions suivantes du bec d'écoulement.

2. Bec selon la revendication 1, caractérisé en ce que ladite pluralité d'oreilles (19) sont espacées selon une circonférence lorsque le bec (10) est disposé selon l'orientation emboîtée et sont ultérieurement perpendiculaires à l'axe longitudinal du bec (10) lorsque le bec se présente selon l'orientation sortie de versement.

3. Bec selon la revendication 1 ou 2, caractérisé en ce que les oreilles (19) sont orientées de façon à ne pas gêner le bec (10) lorsque le bec (10) est disposé selon son orientation emboîtée.

4. Bec selon la revendication 1, 2 ou 3, caractérisé en ce que le bec (10) comprend une portion de montage annulaire (11); les moyens (15) de fixation de la portion de montage annulaire (11) sur le récipient (20) au niveau d'une ouverture du récipient (20); une portion formant col (13) disposée concentriquement et à l'intérieur par rapport à la portion de montage (11); une portion formant corps (12) disposée entre la portion formant col (13) et la portion de montage annulaire (11) et étant solidaire de celles-ci.

5. Bec selon la revendication 4, caractérisé en ce que la portion formant corps (12) présente une portion pliable apte à s'inverser (16) à proximité de la portion de montage.

6. Bec selon la revendication 5, caractérisé en ce que lesdites oreilles (19) sont fixées directement sur la surface extérieure de la portion pliable apte à s'inverser (16).

7. Bec selon la revendication 6, caractérisé en ce que lesdites oreilles (19) tournent vers l'intérieur sensiblement autour de leur point de fixation lors de l'inversement du pli (16) lors-

que le bec (10) est retiré dans son orientation sortie.

8. Bec selon l'une quelconque des revendications précédentes, caractérisé en ce que les oreilles (19) sont des plaques sensiblement rectangulaires, présentant chacune une dimension en largeur et en longueur telle que les portions extrêmes (32) des oreilles voisines (19) sont contiguës lorsque le bec (10) occupe une orientation sortie, ménageant ainsi un orifice d'aération sensiblement triangulaire (34) entre des oreilles voisines (19).

9. Bec selon l'une quelconque des revendications précédentes, caractérisé en ce que l'orifice d'écoulement central (33) présente un pourtour denté.

10. Bec selon la revendication 9, caractérisé en ce que le pourtour denté est délimité par lesdites oreilles (19') et une pluralité de dents (35) partant desdites oreilles (19').

11. Bec selon la revendication 10, caractérisé en ce que ladite pluralité de dents (35) comprend une paire de dents de forme cylindrique (35) partant de la portion d'extrémité (32') de chaque oreille (19').

12. Bec selon l'une quelconque des revendications précédentes, caractérisé en ce que les moyens prolongateurs (27) comprennent une coiffe amovible pouvant être refermée de manière étanche (23) sur laquelle est fixée une anse (27).

13. Bec selon la revendication 12, caractérisé en ce que le bec (10) comprend un joint indicateur de manipulation (28) fixé sur le bec (10) et disposé au-dessus de la coiffe (23) lorsque le bec (10) occupe son orientation initiale emboîtée.

14. Bec selon l'une quelconque des revendications précédentes, caractérisé en ce que le bec (10) comprend un joint amovible (24) situé à l'intérieur de la portion formant col (13).

