CLAIMS

1.BICYCLE SADDLE, which has two identical portions (30, 31) arranged symmetrically with respect to its longitudinal axis, a channel (15) being foreseen at said longitudinal axis, said channel being open from above to below, which separates said two portions that extends from the intermediate part of the saddle up to the front part thereof, said channel having the width of its rear part substantially wider than that of its front part, said two portions being separated at the rear by a recess (6), defined at the side by two points (7, 8), which give the rear part of the saddle the dovetail shape, said recess continuing with a depression (5), which ends in the rear edge of the central channel, said two portions continuing with extensions (9, 10 and 11, 12) intended to gradually narrow, which laterally define the channel (15), said extensions joining together with a substantially circular-shaped front end (13) that, seen from the side, takes on a bird's beak configuration, said saddle being characterised in that the two portions (30, 31), at the rear ends, until they reach the extensions (9, 10) that are beside the central channel, have substantially flat areas (1, 2), on which the gluteal muscles of the user are intended to be placed while the saddle is being used, which are substantially parallel to the ground on which the wheels of the bicycle rest.

2. SADDLE, according to claim 1, characterised in that it does not have any padding at the entire upper surface.

3. SADDLE, according to claim 1, characterised in that it has a padding (40) in some areas (3, 4).

4. SADDLE, according to claim 3, characterised in that it has a bearing body (5), above which there is a padding (40), with it being foreseen that in

the body, right in the part corresponding to that in which there are the areas (3, 4) that have a padding, there are concavities (16, 17) facing upwards.

5. SADDLE, according to claim 1, characterised in that it has a bearing body (50), above which there is a padding (40), said bearing body being supported at the bottom by a fork (14) to be fixed to the seat post of the bicycle, wherein in the body there are two front pockets (21, 22), inside which the ends of the fork (14) are slotted and, at the rear, some plates (18, 19), fixed through screws (23) to keep it firmly fixed to the body (50).

CLAIMS

1. A bicycle saddle, including two identical portions (30,31) arranged symmetrically about a longitudinal axis of the saddle, a channel (15) open from top to bottom separating the two identical portions and extending from an intermediate part of the saddle to a front end (13) of the saddle at the longitudinal axis, the channel having a width at a rear part substantially greater than at the front part, a recess (6), arranged at a rear part of said saddle separating said two identical portions and having a dovetail shape defined by two lateral points (7,8), on the rear part of the saddle, a depression (5), continuing from said recess up to the rear part of said channel, laterally of the recess are first areas (1,2), intended to support the the gluteal muscles of a user seated on the saddle, the first areas continue towards the front end of the saddle with respective second areas intended to support the ischiatic tuberositiies of the user, the second areas continue towards the front end of the saddle with respective first extensions (9,10) followed by respective second extensions (11,12) which join together at the front end of the saddle in a substantially circular shape at the front end, wherein the first areas intended to support the ischiatic tuberositiies of the user, and the first extensions are substantially planar and disposed substantially parallel to the ground.

2. The bicycle saddle, according to claim 1, characterised in that it further includes a bearing body (50), an upper surface of which is covered with a padding (40), the bearing body being supported at a bottom surface thereof by a support fork (14) adapted to be fixed to a seat post of a bicycle, wherein the bearing body includes at the bottom surface two front pockets (21,22), adapted to receive in a slotted fashion respective front ends of the support fork and, at the rear plates (18,19), secured to the bearing body by a series of screws (20) so as to fix the support fork to the bearing the body.

3. The bicycle saddle, according to claim 1, characterised in that the upper

surface of the saddle is devoid of padding.

4. The bicycle saddle, according to claim 1, characterised in that the second areas (3,4) are provided with padding (40) on which a rider's ischiatic tuberosities are supported.

5. The bicycle saddle, according to claim 4 wherein the saddle comprises a bearing body (50) including in the second areas of the two identical portions of the saddle respective upward facing concavities (16,17) adapted to house the ends of the ischiatic tuberosities of a rider.