



IMAGE FORMING APPARATUS

FIELD OF THE INVENTION AND RELATED ART

The present invention relates to an image
5 forming apparatus for forming an image on a recording
material, to which a process cartridge is detachably
mountable.

The image forming apparatus includes a laser
beam printer, an LED printer, an electrophotographic
10 copying machine, a facsimile machine and a word
processor or the like.

In an image forming apparatus such as a
printer, a uniformly charged image bearing member is
selectively exposed to light to form a latent image,
15 and the latent image is visualized with toner, and
thereafter, the toner image is transferred onto a
recording material.

In such an apparatus, a toner has to be
supplied upon shortage thereof by an operator, which
20 is cumbersome and which may result in contamination.
Maintenance operations for various parts have to be
carried out by an expert service man with the result
of inconveniences imposed to the user.

In view of this, the image bearing member,
25 the charger, the developing device and the cleaning
device or the like is unified into a cartridge. In
this case, by the user mounting the cartridge into the

main assembly of the apparatus, the toner is supplied,
and the parts having reached the ends of the service
lives of various parts such as image bearing member,
are automatically exchanged, thus facilitating the
5 maintenance operation.

Recently, a higher quality image is desired.
In an apparatus using such a process cartridge, the
positioning of an electrophotographic photosensitive
member relative to the main assembly or a correct
10 positioning of a feeding reference for a recording
material, are to be accurate to provide the high
quality images.

SUMMARY OF THE INVENTION

15 Accordingly, it is a principal concern of the
present invention to provide an image forming
apparatus in which an image quality is improved.

It is another concern of the present invention
to provide an image forming apparatus in which toner
20 image formation and toner image transfer can be
carried out with high positional accuracy.

These and other concerns, features and
advantages of the present invention will become more
apparent upon a consideration of the following
25 description of the preferred embodiments of the
present invention taken in conjunction with the
accompanying drawings.



BRIEF DESCRIPTION OF DRAWINGS

Figure 1 is a sectional view of an embodiment of the image forming apparatus according to the present invention, depicting the general structure.

5 Figure 2 is an oblique external view of the same image forming apparatus as the one in Figure 1.

Figure 3 depicts the structure of a process cartridge.

10 Figure 4 is an oblique external view of the process cartridge.

Figure 5 is an exploded view of the image forming apparatus, depicting how various components are assembled together.

15 Figure 6 is an oblique view of a process cartridge installation guide portion, depicting its structure.

Figure 7 depicts the state of the cartridge during the cartridge installation.

20 Figure 8 depicts the state of the cartridge during the cartridge installation.

Figure 9 depicts the state of the cartridge during the cartridge installation.

Figure 10 is an oblique view of the cartridge installation guide portion in a prior type apparatus.

25 Figure 11 is a sectional view of the cartridge installation guide portion in the prior type apparatus.

This Sheet Has Been Replaced



Figure 12 depicts the installed state of the process cartridge, with a lid being open.

Figure 13 depicts the installed state of the process cartridge, with the lip being closed.

5 Figure 14 depicts forces exerted on the process cartridge during the image forming operation.

Figure 15 depicts rotational moments exerted on the process cartridge during the image forming operation.

10 Figure 16(a) depicts a state in which a laser shutter is closed, and Figure 16(b) depicts a state in which the laser shutter is open.

Figure 17 is a plan view of the laser shutter.

15 Figure 18 is an exploded view of a feeder cassette.

Figure 19 is a plan view of the feeder cassette.

20 Figure 20 depicts the structures of a conveying roller, and auxiliary rollers.

Figure 21 is a sectional view of a conveyer unit, depicting its structure.

Figure 22 is a plan view of the conveying unit.

25 Figure 23 depicts an essential portion of the conveying unit.

Figure 24 depicts a registration sensor.





Figure 25 depicts a structure for de-curling a recording medium after a fixing operation.

Figure 26 depicts a gear train.

Figure 27 is an oblique view of the gear
5 unit.

Figure 28 depicts how the gears are attached.

Figure 29 depicts how the gear unit is mounted on the lateral side surface of the frame.

Figure 30 depicts how a main motor is
10 mounted.

Figure 31 is an exploded view of an electrical component unit.

Figure 32 is a block diagram of an electrical component mounting board.

Figure 33 depicts how an AC connector is
15 affixed with a metallic inlet plate.

Figure 34 depicts an air flow generated by a cooling fan.

Figure 35 depicts the air flow generated over
20 the circuit board.

Figure 36 is an oblique view of a holder cover for retaining contact pins.

Figure 37 is a sectional view of the contact pins and holder cover.

Figure 38 is an oblique view of an
25 intermediary connector.

Figure 39 depicts how the electrical



component mounting board and the image processing circuit board are connected with use of the intermediary connector.

Figure 40 is an oblique view of an
5 alternative embodiment of the intermediary connector.

Figure 41 is an exploded view of the cooling fan assembly.

Figure 42 depicts how the cooling fan is mounted on the frame.

10 Figure 43 is a sectional view of the cooling fan mounted on the frame.

Figure 44 is an oblique front view of an external case.

Figure 45 is an oblique rear view of an
15 external case.

Figure 46 depicts a locking mechanism of the top lid.

Figure 47 depicts the structure of a side lid.

20 Figure 48 is a sectional view of a structure for offering double protection to a reflection mirror.

Figure 49 is an oblique view of a light conducting member.

Figure 50 is an oblique view of the light
25 conducting member.

Figure 51 is a schematic of an exemplary structure in which a conveyance reference, a cartridge

reference, and a scanning starting reference are all provided on the same side.

Figure 52 is a block diagram of a scanning sequence of a scanning unit.

5 Figure 53 is an oblique view of an alternative embodiment of the second guide portion for guiding the process cartridge.

 Figure 54 is an oblique view of an alternative embodiment of a bearing for a transferring
10 roller.

 Figure 55 is a schematic plan view of an alternative embodiment in which one of the second guide portions is shortened, and an auxiliary guide is provided.

15 Figure 56 is a schematic sectional view of an alternative embodiment in which the auxiliary guide is provided.

 Figure 57 is a schematic sectional view of an alternative embodiment in which the transferring
20 roller and guide portions can be integrally moved.

 Figure 58 is an oblique schematic view of the alternative embodiment in which the transferring roller and guide portions can be integrally moved.

 Figure 59 is an oblique schematic view of an
25 alternative embodiment in which the transferring roller and a discharging needle can be integrally moved.

This Sheet Has Been Replaced



Figure 60 depicts an alternative embodiment comprising a locking mechanism for locking the shutter mechanism in the open state.

Figure 61 is an oblique view of an image forming apparatus comprising an alternative embodiment of a pressure generating structure based on the drum shutter, and a process cartridge for such an apparatus.

Figure 62 depicts the structure of the image forming apparatus comprising an alternative embodiment of a pressure generating structure based on the drum shutter, and the structure of the process cartridge for such an apparatus.

Figure 63 presents a plan view and a side view, of the alternative embodiment of the pressure generating structure based on the drum shutter, depicting the initial stage of the cartridge installation into the image forming apparatus.

Figure 64 presents a plan view and a side view of the alternative embodiment of the pressure generating structure based on the drum shutter, depicting the stage at which the cartridge mains assembly has been pulled out of the case.

Figure 65 is a plan view of a locking lever mechanism of the alternative embodiment of the pressure generating structure based on the drum shutter.





Figure 66 depicts the state of the locking lever in the alternative embodiment of the pressure generating structure based on the drum shutter.

Figure 67 is a block diagram of the
5 electrical component mounting board for an alternative embodiment.

Figure 68 depicts versatility of the electrical component mounting board which can be used with either an apparatus in which the recording medium
10 P is horizontally conveyed or an apparatus in which the recording medium P is vertically conveyed.

Figure 69 is an oblique view of an alternative embodiment in which a fan cover of the cooling fan and a filter are integrally formed.

15 Figure 70 is an oblique view of an alternative embodiment in which the fan cover of the cooling fan, the filter, and a shield plate are integrally formed.

20 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiment 1

A process cartridge according to the first embodiment of the present invention, and an image forming apparatus comprising such a process cartridge
25 will be described, referring to drawings.

{General Description of Process Cartridge and Image Forming Apparatus Comprising Such Process Cartridge}

First, referring to Figures 1 - 5, an overall structure of an image forming apparatus will be described in general terms.

Figure 1 is a sectional view of a laser
5 printer, a typical image forming apparatus, comprising a process cartridge. Figure 2 is an oblique external view of the laser printer. Figure 3 is a sectional view of the process cartridge. Figure 4 is an oblique external view of the process cartridge. Figure 5 is
10 an exploded view the laser printer, depicting how the various components are assembled into the frame.

Referring to Figure 1, this image forming apparatus A is used with a process cartridge B to form electrophotographically images, wherein a device for
15 recording the images on a recording medium P has been downsized to an extraordinary degree.

The process cartridge B comprises a photosensitive drum 2 as an image bearing member on which a latent image is formed as it is exposed to an
20 optical image which reflects image data, a charging means 3 for charging uniformly the surface of the photosensitive drum 2, a developing means 4 for developing the latent image, with a developer (hereinafter, toner), into a visible toner image, and
25 a cleaning means for removing the residual toner on the surface of the photosensitive drum 2 after the toner image is transferred onto the recording medium



P, wherein they are integrally assembled into a frame 1, in such a manner that the photosensitive drum 2 is surrounded by the rest, constituting thereby a cartridge.

5 On the other hand, the image forming apparatus A is provided with an installing means 7 for installing the process cartridge B into the apparatus main assembly 6. In the top portion of the apparatus main assembly 6, an optical system 8 is disposed for
10 projecting onto the photosensitive drum 1 an optical image bearing the image data, and at the bottom, a cassette installation space is provided for accommodating a cassette 9 in which the recording medium P is stored. The recording medium P stored in
15 the cassette 9 is fed out one by one by a conveying means 10.

 Further, the apparatus main assembly 6 is provided with a transferring means 11 for transferring onto the recording medium P the toner image formed on
20 the photosensitive drum 2, and a fixing means 12 for fixing the toner image having been transferred onto the recording medium P, wherein the transferring means 11 is disposed so as to face the photosensitive drum 2 and the fixing means 12 is disposed on the downstream
25 side of the transferring means 11, relative to the direction in which the recording medium is conveyed.

Referring to Figures 1 - 5, on the internal



surface of the apparatus main assembly, a gear unit 13 for transmitting the driving force of a main motor 20 is disposed, and above the cassette 9, an electrical component unit 14 for controlling the main motor 20 or
5 the like is disposed, wherein all of the aforementioned components are mounted on a frame 15, being assembled as a unit, and are covered with an external case 16.

The structures of various components within
10 the process cartridge B will be described in detail, along with those within the image forming apparatus A for forming images in cooperation with the process cartridge B having been installed in it.

{Process Cartridge}

15 To begin with, the structures of the various components of the process cartridge B will be described in the order of the photosensitive drum 2, charging means 3, developing means 4, and cleaning means 5.

20 (Photosensitive Drum)

The photosensitive drum 2 in this embodiment comprises a cylindrical aluminum drum as a base member, and an organic photosensitive layer coated on the circumferential surface of the base member. This
25 photosensitive drum 2 is rotatively mounted on the frame 1 and is rotated in the direction indicated by an arrow in Figure 1 by a driving force transmitted to





a gear affixed to one of the longitudinal ends of the photosensitive drum 2, from the main motor 20 mounted on the apparatus main assembly side.

(Charging Means)

5 Referring to Figure 3, the charging means 3 in this embodiment is based on so-called contact charging method in which a charging roller 3a mounted rotatively on the frame 1 is placed in contact with the photosensitive drum 2. The charging roller 3a
10 comprises a metallic roller shaft 3b, an electrically conductive elastic layer placed thereon, a high resistance elastic layer laminated thereon, and a protecting film coated thereon. The electrically conductive layer is of elastic rubber material such as
15 EPDM, NBR, or the like with dispersed carbon, and functions to conduct a bias voltage supplied to the roller shaft 3b. The high resistance elastic layer is of urethane rubber or the like in which an extremely small amount of electrically conductive micro-particle
20 powder is contained, and functions to restrict leakage current, which flows through pin holes or the like of the photosensitive drum 2 being in contact with the highly conductive charging roller, so that the bias voltage is prevented from dropping suddenly. The
25 protective layer is of N-methylmethoxy Nylon, and functions to prevent the surface of the photosensitive drum 2 from being deteriorated by coming into contact

with the plastic material of the electrically conductive elastic layer or high resistance elastic layer.


When the image is formed, a superposed
5 voltage composed of a DC voltage and an AC voltage is applied to the charging roller 3a, being placed in contact with the photosensitive drum 2 and rotated by the rotation of the photosensitive drum 2, whereby the surface of the photosensitive drum 2 is uniformly
10 charged.

(Developing Means)

Referring to Figure 3, the developing means 4 is provided with a toner storage 4a for storing toner, and in the toner storage 4a, a toner feeding member 4b
15 is provided, which reciprocates in the direction indicated by an arrow to feed the toner. The developing means 4 is also provided with a developing sleeve 4d, which contains a magnet 4c and is disposed so as to face the photosensitive drum 2, with a macro-
20 gap between them. As the developing sleeve is rotated, a thin toner layer is formed on it.

While the toner layer is formed on the surface of the developing sleeve 4d, a sufficient amount of frictional charge potential for developing
25 the electrostatic latent image on the photosensitive drum 2 is obtained through the friction between the toner and the developing sleeve 4d. Also, the





developing means 4 is provided with a developing blade 4e for regulating the thickness of the toner layer.

(Cleaning Means)

Referring to Figure 5, the cleaning means 5 comprises a cleaning blade 5a, a receptor sheet 5b, and a waste toner storage 5c. The cleaning blade 5a is placed in contact with the surface of the photosensitive drum 2 and scrapes off the residual toner on the photosensitive drum 2. The receptor sheet 5b is disposed below the cleaning blade 5, contacting gently on the surface of the photosensitive drum 2 in order to scoop up the scraped-off toner. The waste toner storage 5c stores the waste toner scooped up by the receptor sheet 5b.

{Image Forming Apparatus}

Next, the structure of the image forming apparatus A will be described referring to the cartridge installing means 7, optical system 8, cassette 9, recording medium conveying means 10, transferring means 11, fixing means 12, gear unit 13, electrical component unit 14, cooling fan 19, frame 15, and external case 16, in this order.

(Cartridge Installing Means)

<Structure of Process Cartridge Installation Guide>

In this embodiment, the frame 15 of the image forming apparatus A is provided with a guide portion for facilitating the installation of the process



cartridge B. Referring to Figures 5 and 6, this guide portion comprises a pair of first guide portions 7a and a pair of second guide portions 7b, which are symmetrically disposed on respective internal surfaces of the side walls. The first guide portion 7a declines toward the rear portion of the apparatus (leftward in Figure 6) and a groove portion 7a1 having an arc-shape section is provided at the bottom end of it. The second guide portion 7b is disposed inward of the first guide portion 7a in the lateral direction of the apparatus, and declines at a steeper angle than the first guide portions 7a, being different from the first guide 7a in height and location.

On the other hand, the process cartridge B is provided with a pair of cylindrical projections 7c1 and 7c2, which have substantially the same radius as that of the groove portion 7a1 provided in the frame 15 and project from the respective external side surfaces in the longitudinal direction. At each of the respective ends of these projections 7c1 and 7c2, a first engagement portion 7d is attached, ascending rearward, relative to the cartridge installation direction (right in Figure 6), and at the bottom-forward portion relative to the cartridge installation direction, a second engagement portion 7b is provided.

Referring to Figures 7 and 8, when the process cartridge B is installed in the image forming



-17-

apparatus A, first, a top lid 16b provided on the external case 16 is opened, and then, the cylindrical projections 7c1 and 7c2 are placed on the corresponding first guide portion 7a and the second engagement portion 7e is placed on the second guide portion 7b. At this time, the cylindrical projections 7c1 and 7c2 and the second engagement portion 7e are guided by the guide portions 7a and 7b, and the first engagement portion 7d is guided by the first guide 7a.

During this installation, when an attempt is made to push the process cartridge B diagonally forward in the downward direction (to pivot it about the cylindrical projection 7c1 and 7c2 in the counterclockwise direction as shown in Figure 8), relative to the installation direction, the process cartridge B will not go down since the second engagement portion 7e and second guide portion 7b are in contact with each other. On the other hand, when another attempt is made, during the installation, to press the process cartridge B in the back and downward direction (to pivot it about the cylindrical projections 7c1 and 7c2 in the clockwise direction as shown in Figure 9), relative to the installation direction, the first engagement portion 7d comes in contact with the first guide portion 7a, preventing thereby the process cartridge B from going down further. Therefore, the process cartridge B is

smoothly inserted, being guided by the guide portions 7a and 7b, and as the cylindrical projections 7c1 and 7c2 engage with the groove portions 7a1, the process cartridge B is properly installed as shown in Figure


5 1.

In the case of a structure which vertically lowers the process cartridge B into the image forming apparatus A, the process cartridge B collides with the reflection mirror or the like mounted on the apparatus
10 main assembly. Therefore, in a prior type apparatus, the forward end of the process cartridge B is lowered first, with the cylindrical projections 7c1 and 7c2 of the process cartridge B being guided by the guide portion 7a as shown in Figure 10, in a manner so as to
15 avoid the reflection mirror or the like, and then, its rear end portion is lowered.

In such a case, when the forward end of the process cartridge B is lowered too far, the process cartridge B is liable to collide with the transferring
20 roller 11, discharging needle, or the like as shown in Figure 11, and damage it. Also, foreign matter adhering to the process cartridge B is liable to be transferred onto the transferring roller 11 when the collide occurs, and then, this transferred foreign
25 matter is liable to travel to the photosensitive drum 2 and deteriorate image quality.

However, in this embodiment, when the process





cartridge B is inserted, with the cylindrical
projections 7c1 and 7c2 being guided along the first
guide portion 7a, the first engagement portion 7d, and
second engagement portion 7e, being provided at the
5 fore and aft portions of the process cartridge B, are
guided by the first guide 7a and second guide 7b of
the frame 15; therefore, the process cartridge B does
not contact the transferring roller 11 or the like.
In other words, the process cartridge B in this
10 embodiment is not liable to damage them.

<Pressure Generated by Drum Shutter>

The process cartridge B is provided with a
drum shutter for protecting the photosensitive drum 2.
This drum shutter automatically opens as the process
15 cartridge B is installed in the image forming
apparatus A, and automatically closes as the process
cartridge B is taken out. In this embodiment, an
elastic member which exerts a closing pressure on the
shutter drum is also used to make it easier to take
20 out the process cartridge B.

More specifically, referring to Figure 7, a
drum shutter 17a is attached to the frame 1 so as to
cover the photosensitive drum 2. To each end of this
drum shutter 17a, an arm 17b is attached, which is
25 allowed to rotate about an axis 17c provided on the
frame 1. The axis 17c is provided with a torsional
coil spring 17d (Figure 4), one end of which engages

with the arm 17b and the other end of which engages with the frame 1. The drum shutter 17a is under constant pressure exerted in the closing direction by this spring 17d.

5 The arm 17b is provided with an engagement projection 17e (Figure 4), and this projection 17e engages with the upper edge of the frame 15 when the process cartridge B is installed.

 Therefore, while the process cartridge B is
10 inserted along the guide portions provided on the frame 15, as shown in Figures 8 and 9 and described hereinbefore, the engagement projection 17e engages with the upper edge of the frame 15, and as the process cartridge B is further inserted, the arm 17b
15 is rotated in the counterclockwise direction, against the elastic force of the spring 17d, whereby the drum shutter 7a is automatically opened.

<Pressure Generated during Process Cartridge
Installation>

20 When the process cartridge B is inserted along the guide portions 7a and 7b, and then, the top lid 16b is closed, the process cartridge B must be reliably stabilized. Therefore, in this embodiment, it is designed so that when the top lid 16b is closed,
25 the process cartridge B is subjected to the pressure from the frame 15.

Referring to Figure 12, a pressing member 18a





having a shock absorbing spring 18a1 is attached to the top cover 16b, on the internal surface of the top wall portion of the top lid 16b, and a plate spring 18b, which is another pressing member, is attached to the frame 15, adjacent to the rotational center of the top lid 16b. When the top lid 16b is open, the plate spring 18b is not in contact with the process cartridge B, as shown in Figure 12.

With such a structure in place, when the top lid 16b is opened, the process cartridge B is inserted along the guide portions 17a and 17b, then the top lid 16b is closed, the pressing member 18a provided on the internal surface of the ceiling portion of the top lid 16b presses down on the top surface of the process cartridge B, and at the same time, a leg portion 16b1 of the top lid 16b also presses down on the plate spring 18b, which in turn presses down on the top surface of the process cartridge B.

Therefore, the cylindrical projections 7c1 and 7c2 are pressed down in the groove portion 7a1, whereby the position of the process cartridge B is fixed, and at the same time, projections 1a1 and 1a2 projecting downward from the bottom surface of the frame 1 come in contact with abutment portions 7b1 and 7b2 provided at respective predetermined locations on the second guide portions 7b, being positionally fixed, whereby the rotation of the process cartridge B

is regulated.

Referring to Figure 6, two projections 1a1 and 1a2 are provided at the bottom of the frame 1, and two abutment portions 7b1 and 7b2 are provided on the guide portions 7b, at locations which correspond to the locations of the projections 1a1 and 1a2 on the frame 1, wherein two abutment portions 7b1 and 7b2 are equal in height, whereas the projections 1a1 and 1a2 are different, that is, the projection 1a1 is taller than the projection 1a2. Therefore, when the cartridge is in the normal state of installation, only one projection 1a1 is in contact with the abutment portion 7b1, fixing thereby the position of the cartridge, and other projection 1a2 remains slightly lifted from the abutment portion 7b2. When the process cartridge B is deformed by an external force such as vibration, or in a like situation, this floating projection 1a2 comes in contact with the abutment portion 7b2 and functions as a stopper.

Since the plate spring 18b is to be directly mounted on the frame 15, it can be mounted so as to press the process cartridge B on a more precise spot, and also, since this plate spring is to be pressed by the leg portions 16b1 of the top lid 16b, a relatively small space is needed for pressing; therefore, the apparatus can be downsized. Further, referring to Figure 13, since a distance from a fulcrum P1 of the





-23-

plate spring 18b to a pressure application point P3 at which the plate spring 18b is pressed is longer than a distance from a fulcrum P1 of the plate spring 18b to a point of action P2 at which the process cartridge is pressed, the process cartridge B can be pressed down with a small pressure. Therefore, the load exerted on the top lid 16b is reduced, preventing thereby the deformation of the top lid 16b which occurs when it is closed.

10 Referring to Figures 12 and 13, the plate spring 18 is elastically deformed as the top lid 16b is opened or closed. Therefore, this plate spring 18b can be rendered to function as an actuator of a switch, in which the plate spring 18b presses the
15 switch when the top lid 16b is closed and releases it when the top lid 16b is opened. With this arrangement, the plate spring 18b doubles as a detection switch for detecting whether the top lid 16b is open or closed, reducing thereby the component
20 count. As a result, a manufacturing cost can be saved.

<Force Exerted on Installed Process Cartridge>

When the top lid 16b is closed after the installation of the process cartridge B, an upward
25 force is also exerted on the cartridge B in addition to the downward pressure imparted by the pressure generating member 18a or the like, as described

hereinbefore. Therefore, in order to stabilize the installed process cartridge B, the downward pressure exerted on the process cartridge B must be larger than the upward pressure.

5 The upward force exerted on the process cartridge B is generated by the electrical contact pins, transferring roller 11, and drum shutter 17a. Referring to Figure 13, on the bottom surface of the cartridge B, electrical contacts are exposed. These
10 contacts make contact with contact pins provided on an electrical component unit 14. More specifically, the electrical component unit 14 is provided with a development bias contact pin 14d1 for applying the development bias to the developing sleeve, a ground
15 contact pin 14d2 for grounding the photosensitive drum 2, and a charge bias contact pin 14d3 for applying the charge bias to the charging roller. Each of these pins 14d1, 14d2, and 14d3 is fitted within a holder cover 14e in such a manner that it can project without
20 coming out all the way, wherein the wiring pattern of the electrical component unit 14 to which the holder cover 14e is attached is electrically connected to each of the contact pins 14d1, 14d2, and 14d3 with an electrically conductive compression spring 14g.

25 During the installation of the process cartridge B, the electrical contact pins 14d1, 14d2, and 14d3 are pushed in, and the transferring roller 11



comes to press on the photosensitive drum 9.

Therefore, the process cartridge B is pressured upward by the forces F_{c1} , F_{c2} , and F_{c3} from the contact springs 14g of respective contact pins as shown in
5 Figures 13 and 14, as well as by the force F_t from the transferring roller 11 (Figure 1). Further, the opened drum shutter 17a remains pressured constantly in the closing direction by the torsional coil spring 17d. This force F_d is exerted on the process
10 cartridge B in the same direction as that in which the process cartridge B is pulled when it is taken out, whereby the process cartridge B is pressured upward by the vertical components F_{d1} and F_{d2} of the force F_d .

On the other hand, the process cartridge B is
15 pressured downward by the forces F_{s1} and F_{s2} from the pressure generating member 18a, and the force F_s from the plate spring 18b, as described previously. In addition, it is also pressured downward by the self weights F_{k1} , F_{k2} , and F_{k3} , and the rotation of the
20 gear for transmitting the driving force to the photosensitive drum 2.

More specifically, referring to Figure 13, when the process cartridge B is installed, the drum gear 2a attached to one of the longitudinal ends of
25 the photosensitive drum 2 engages with a driving gear 13c2 provided in the apparatus main assembly 6, for transmitting the driving force of a main motor 20. At



this time, the direction of the operating pressure angle between the both gears 2a and 13c2 is set downward by an angle $\theta = 1^\circ - 6^\circ$ (approximately 4° in this embodiment), relative to the horizontal line.

- 5 Therefore, during the image forming operation, a component FG1 of the operating pressure FG between the driving gear 13c2 and drum gear 2a works to pressure the process cartridge B downward. By directing the operating pressure FG of the gears downward, relative
10 to the horizontal line, the process cartridge B is prevented from being pushed up.

- Further, having the operating pressure angle being directed downward relative to the horizontal line, even when the operator closes the top lid 16b
15 without inserting the process cartridge B all the way (but enough to allow the top lid 16b to be closed), the process cartridge B is pulled in by the rotational force of the driving gear 13c2 as the main motor 20 rotates after the closing of the top lid 16b is
20 detected, and the cylindrical projections 17c1 and 17c2 engage into the groove portions 7a1, whereby the process cartridge B is properly installed.

- When the process cartridge B is inserted so improperly that the drum gear 2a and driving gear 13c2
25 fail to engage, the process cartridge B sticks out upward from the apparatus main assembly 6 and prevents the top lid 16b from being closed. Therefore, the



operator will notice that the process cartridge B has been improperly inserted.

Further, even when the process cartridge B is subjected to a force directed in the diagonally left-downward direction in Figure 13 during the image forming operation, the cylindrical projections 7c1 and 7c2 are abutted in the grooves 7a1 because of the aforementioned operating pressure angle; therefore, the process cartridge B remains stable. However, when the operating pressure angle is set diagonally left-downward in relation to the horizontal line as described in the foregoing, the positional arrangement becomes such that the drum gear 2a has to ride over the driving gear 13c2. Therefore, when the downward operating pressure angle is increased, the drum gear 2a is liable to collide with the driving gear 13c2 during the installation of the process cartridge B. In addition, the process cartridge B must be lifted higher before it can be pulled, during the removal; otherwise, both of the gears 2a and 13c2 are liable to collide with each other, hampering thereby their disengagement. Therefore, the aforementioned diagonally left-downward operating pressure angle θ is preferred to be in a range of approximately $1^\circ - 6^\circ$.

As for the relationship between the upward and downward forces exerted on the process cartridge B as described in the foregoing, it has to satisfy the



following conditions in order for the process cartridge B to be properly installed and for each of the contact pins to come and remain reliably in contact with the counterparts of the process cartridge

5 B.

(1) An overall pressure exerted on the process cartridge B manifests as a downward pressure.

(2) The left side projection 1a1 is not allowed to be pivoted about an axis connecting both
10 cylindrical projections 7c1 and 7c2 and lifted up.

(3) Both cylindrical projections 7c1 and 7c2 are not allowed to be pivoted about an axis connecting both projections 1a1 and 1a2, and to be thereby lifted up.

15 (4) The left cylindrical projection 7c1 and left projection 7c1 are not allowed to be pivoted about an axis connecting the right cylindrical projection 7c2 and right projection 1a2, and to be thereby lifted up.

(5) The right cylindrical projection 7c2 and
20 right projection 1a2 are not allowed to be pivoted about an axis connecting the left cylindrical projection 7c1 and left projection 7c1, and to be thereby lifted up.

(6) The left cylindrical projection 7c1 is not
25 allowed to be pivoted about an axis connecting the right cylindrical projection 7c2 and left projection 1a1 and lifted up.





(7) The right cylindrical projection 7c2 is not allowed to be pivoted about an axis connecting the left cylindrical projection 7c1 and right projection 1a2, and to be thereby lifted up.

5 However, in the case of this embodiment, since the right projection 1a2 is slightly lifted above the abutment portion 7b2 anyway, Condition (7) may be eliminated; therefore, it is only necessary to satisfy Conditions (1) - (6).

10 More specifically, in order to meet Condition (1), for example, only the following relation has to be satisfied:

$$\begin{aligned} &F_{s1} + F_{s2} + F_{s3} + F_{G1} + F_{k1} + F_{k2} + F_{k3} \\ &> F_{c1} + F_{c2} + F_{c3} + F_t + F_{d1} + F_{d2} \end{aligned}$$

15 Further, referring to Figure 15, in order to meet Condition (3), it suffices if a rotational moment about a point p of the projection 1a1 on the driven side satisfies the following mathematical expression, wherein M(T) in the expression is a reaction force
20 generated by the cartridge torque, that is, a clockwise moment of the process cartridge B about the point p in the drawing.

$$\begin{aligned} &M(F_{s1} + F_{s2}) + M(F_{s3}) + M(F_{G1}) + M(F_{k1} + F_{k2}) > \\ &M(F_{c1}) + M(F_{c2}) + M(F_{c3}) + M(F_t) + M(F_{d1} + F_{d2}) + \\ 25 \quad &M(T) \end{aligned}$$

where M() is a moment.

Similarly, expressions which satisfy

Conditions (1) - (6) are obtained, and the pressures
Fs1, Fs2, and Fs3 are determined so as to satisfy all
the conditions. As a result, the process cartridge B
remains stabilized within the frame 15 during the
5 image forming operation.

On the contrary, in the case of the prior
structure in which the process cartridge B is
installed in the top lid 16b assembly, when the
operating pressure angle is set diagonally downward
10 relative to the horizontal line, the drum gear 2a and
driving gear 13c2 remain engaged when the top lid 16b
is opened. As a result, the process cartridge B
cannot be smoothly pulled out. Therefore, the driving
gear 13c2 must be provided with a one-way clutch or
15 the like. However, in the case of this embodiment,
when the top lid 16b is opened, the force pressuring
upward the cartridge B automatically works to
disengage the drum gear 2a and driving gear 13c2,
which eliminates the need for the provision of the
20 one-way clutch, allowing thereby the component count
to be reduced.

Also, when the process cartridge B is lifted,
and the cylindrical projections 7c1 and 7c2 are
disengaged from the groove portion 7a1, as described
25 previously, the process cartridge B is pushed in the
same direction as that in which the process cartridge
B is pulled out, by the pressure from the spring 17d



exerting the pressure for closing the drum shutter 17a. Therefore, it becomes easier to remove the process cartridge B.

(Optical System)

5 <Scanner Unit>

The optical system 8 projects the light beam carrying the imaging information read in from the external apparatus or the like, onto the photosensitive drum 2. As shown in Figure 1, it
10 comprises a scanner unit 8e and a mirror 8f, which are disposed in the frame 15, wherein the scanner unit 8e comprises a laser diode 8a for emitting a laser beam, a polygon mirror 8b molded of metallic or resin material, a scanner motor 8c, and an image forming
15 lens 8d molded of glass or resin.

When an imaging signal is sent in by an external equipment such as a computer or word processor, the laser diode 8a emits light in response to the imaging signal, and the emitted light is
20 projected as the imaging beam to the polygon mirror 8b, which is being rotated at a high speed by the scanner motor 8c. The imaging beam reflected by the polygon mirror 8b is projected through the image forming lens 8d and is reflected by the mirror 8f onto
25 the photosensitive drum 2, exposing selectively the surface of the photosensitive drum 2. As a result, a latent image according to the imaging information is



formed on the photosensitive drum 2. The reflection mirror 8f is mounted on the frame 15, with screws or the like, at a predetermined angle.

The scanner unit 8e and reflection mirror 8f
5 are disposed to be substantially in the middle of the apparatus main assembly 6. This is because of the following reason.

That is, the apparatus main assembly 6 of the image forming apparatus is generally provided with
10 legs, one at each of four bottom corners (unshown), and when the apparatus is in use, only these four legs contact the surface where the apparatus is placed. When this surface is not flat, a torsional force is generated. This torsional force is exerted on the
15 apparatus main assembly 6, which is liable to twist the optical system. When the optical system is twisted, it cannot precisely project the optical image no matter how slightly it is twisted; therefore, the image is distorted.

20 When the torsional force generated due to the unevenness of the surface on which the apparatus is placed is exerted on the apparatus main assembly through the legs located on four corners, the closer to the center of the apparatus main assembly it is,
25 the less the effects of the torsional force is. For this reason, the image distortion can be suppressed to a minimum by disposing the scanner unit 8e and





reflection mirror 8f substantially in the middle of the apparatus main assembly, which is least affected by the torsional force.

Further, the reflection mirror 8f is disposed
5 approximately above and adjacent to the photosensitive drum 2, and vibrates substantially in synchronism with it. Therefore, the amount by which the writing position of the laser beam is shifted by the vibration can be reduced. Further, the reflection mirror 8f is
10 mounted with use of a holding member, adjacent to a wall 15k of the main frame and adjacent to the scanner unit 8e, which affords a very vibration resistant structure.

The scanner unit 8e is surrounded by the
15 fixing means 12, cover guide 10e, process cartridge B, reflection mirror 8f and mirror holding portion 15g (Figure 15), external case 16, and frame 15. Therefore, the structure surrounding the scanner unit 83 is provided with high rigidity and strength to
20 protect the scanner unit 8 against the deformation or vibration caused by the external force.

Referring to Figure 1, the scanner unit 8e is inclined diagonally upward so that the light coming out of the resin molded image forming lens 8d is
25 directed diagonally upward. Also, the scanner unit 8e is inclined in the same direction as the discharge tray 10j which is provided on the top surface of the



apparatus main assembly 6, being inclined diagonally upward, so that the scanner unit 8e becomes substantially parallel to the inclined surface of the discharge tray 10j. With this arrangement, even when
5 the height of the apparatus main assembly 6 is reduced as much as possible, the inclination angle of the discharge tray 10j can be increased so that a sufficient number of recording medium P can be accumulated in the discharge tray 10j.

10 Here, the inclination of the discharge tray 10j relative to the horizontal line is approximately 15° - 45° , preferably approximately 20° - 40° , in consideration of the discharge performance. In this embodiment, it is set at approximately 20° . As for
15 the mounting angle of the scanner unit 8e relative to the horizontal line, it is approximately 9° - 12.5° .

<Opening and Closing Operation of Laser Shutter>

The scanner unit 8e, which is the projecting means of the laser beam, is provided with a laser
20 shutter 8g constituting a shutter means which takes a closed position as shown in Figure 16(a), at which it blocks the laser beam passage to prevent the laser beam from being unintentionally leaked, and a opened position as shown in Figure 16(b), to which it
25 retracts from the closed position to unblock the laser beam passage when the scanner is in use.

Next, the opening and closing operation of



this laser shutter 8g will be described. Referring to Figures 16 and 17, the scanner unit 8e is provided with a unit opening 8el which constitutes a passage for the laser beam, and this unit opening 8el is
5 provided with the laser shutter 8g which is rotatable about axes 8g1 and 8g2. As this shutter 8g is rotated, the opening 8el is exposed or covered. One of the axis 8g1 is provided with a torsional coil spring 8h which constantly pressures the shutter 8g in
10 the closing direction.

Adjacent to the laser shutter 8g, a shutter lever 8i is disposed. This shutter lever 8i is rotatable about an axis 8i1. Further, a projection 1b which serves as an actuator is provided at the forward
15 edge of the process cartridge B. As the cartridge B is installed, the projection 1b is inserted through the inserting portion 8g3 of the laser shutter 8g and presses the lever 8i, whereby the lever 8i is rotated in the clockwise direction, pushing up the laser
20 shutter 8g to open, as shown in Figure 16(b). As the process cartridge B is pulled out of the apparatus main assembly, the pressure from the projection 1b is eliminated, allowing thereby the laser shutter 8g to be automatically closed by the pressure from the
25 torsional coil spring 8h. In other words, the laser shutter 8g is automatically opened or closed as the process cartridge B is installed or taken out.



Referring to Figure 17, a pair of protective guide members 8j are provided adjacent to the inserting portion 8g3 through which the projection 1b is inserted. The distance between these two
5 protective guide members 8j is set to be approximately 5 mm, and their lengths are set to be approximately 6 mm, preventing thereby a finger or the like from being inserted through the gap between two members 8j while allowing the cartridge projection 1b to be inserted.

10 Further, the gap between two protective guide members 8j tapers out toward the free end side from which the cartridge projection 1b is inserted. Therefore, when the process cartridge B is inserted, being guided by the guide portions 7a and 7b, these
15 two protective guide members 8j can also function as guides for facilitating the insertion of the projection 1b into the inserting portion 8g3. In other words, even when the process cartridge B is inserted at a slightly wrong angle, the projection 1b
20 is guided by the tapered portions of the protective guide members 8j to be properly inserted into the inserting portion 8g3.

Also in this embodiment, the top surface of the laser shutter 8g is curved as shown in Figure 16
25 so that the laser shutter 8g cannot be easily opened with a finger or the like object. When the shape of this shutter 8g is rectangular, for example, the

shutter 8g can be easily opened by placing a finger or the like object on corner portions, but when the shutter contour is a curvature, the finger placed on the shutter to pry open it slips, preventing thereby
5 it from being easily opened. In this matter, it is even more effective if the curved surface of the shutter 8g is made smoother and more slippery.

(Feeder Cassette)

Next, the structure of the feeder cassette 9
10 will be describe. Referring to Figure 1, within the apparatus main assembly 6, an installation space 6a for the feeder cassette 9 is provided at the bottom, where the feeder cassette 9 storing the recording medium P is installed. The feeder cassette 9
15 comprises, as shown in Figure 1, a cassette main assembly 9a having a guide portion 9a1 which serves as a guide when the recording medium is fed, and a cassette auxiliary assembly 9b which is an assembly independent from the cassette main assembly 9a,
20 wherein the cassette auxiliary assembly 9b has a conveying guide portion 9b1, a cassette auxiliary assembly surface 9b2, and a hand feeding guide portion which serves as a table used for inserting the recording medium P during a hand feeding operation.
25 Referring to Figure 18, the cassette main assembly 9a and cassette auxiliary assembly 9b are joined with rivets 9c.

This Sheet Has Been Replaced





Incidentally, when the feeder cassette 9 is in the apparatus main assembly 6, the only portion exposed outward from the apparatus main assembly 6 is a cassette auxiliary assembly 9b. Therefore, the exterior design of the feeder cassette 9 can be matched to that of the apparatus main assembly 6 just by replacing this cassette auxiliary assembly 9b.

Referring to Figures 18 and 19, a middle plate 9d on which two or more recording mediums P are loaded, a spring 9c for providing the middle plate 9c with upward pressure, and a separating claw 9f for separating one by one the recording medium P by regulating the forward corner of a stack of the recording mediums P loaded on the middle plate 9d, on the aligning reference side, are provided within the cassette main assembly 9a.

The separating claw 9f is provided with an axis hole 9f1 for a separating claw axis (unshown) provided on the cassette main assembly 9a, wherein the separating claw 9f is attached to the cassette main assembly 9a by means of engaging the axis hole 9f1 with the separating claw axis, and pivots about the mounting axis, following one by one the movement of the uppermost sheet of the stacked recording mediums P, at the forward corner on the alignment reference side. This separating claw 9f is provided with a separating portion 9f2 for separating one by one the



-39-

recording mediums P stacked on the middle plate 9d. In addition, the separating claw 9f is provided, on the opposite side across the axis hole 9f1, with a pressuring portion 9f3 for pressuring upward the separating portion 9f2. By holding down this pressing portion 9f3 while placing a stack of the recording mediums P in the feeder cassette 9, the separating portion 9f2 is lifted to allow the recording mediums P to be easily inserted.

10 Adjacent to the separating claw 9f provided within the cassette main assembly 9a, a metallic aligning plate 9g is attached. When the recording medium P is fed out of the cassette 9 by a pickup roller 10a, it is guided along the aligning plate 9g, 15 on the lateral side.

Referring to Figure 19, a movable regulating member 9h is disposed within the cassette main assembly, adjacent to the corner diagonally opposite to where the separating claw 9f is disposed. This 20 movable regulating member 9h regulates the recording medium P, at the rearward end as well as on the lateral side opposite to the one regulated by the aligning plate 9g, and also, is capable of accommodating the recording medium P in several 25 different sizes. This regulating member 9h has lateral side pressing portions 9h1 and 9h2 for pressing the lateral side in order to regulate the



-40-

recording medium P, a rearward end pressing portion 9h5 for regulating the recording medium P by pressing the rearward end, a grasping portion 9h3 to be grasped by an operator when the size of the recording medium P
5 to be loaded is changed, and a hooking portion 9h4 to be used for engaging the regulating portion 9h with the cassette main assembly 9a.

The pressing portions 9h1 and 9h2 function to press the recording medium P against the aligning
10 plate 9g, and the pressing portion 9h5 serves to hold the rearward end of the recording medium P, so that the recording medium P can be steadily fed out of the feeder cassette 9. The regulating member 9h is
15 movable along the engagement slot 9i provided on the cassette main assembly 9a and can be set at two or more locations on the cassette main assembly 9a, which allows an operator to use a single feeder cassette 9 for several types of recording mediums different in size. This regulating member 9h can be adjusted so
20 that the rearward end pressing portion 9h5 protrudes beyond the cassette main assembly 9a, allowing thereby the feeding of a recording medium P longer than the cassette main assembly 9a.

Further, the pressing portion 9h1 is provided
25 with a recording medium size pointer 9j, adjacent to the forward end, and the cassette main assembly 9a is provided with a recording medium size index (B5, EXE,



LTR, A4) 9k. Therefore, the operator can easily set the regulating member 9 at a proper location corresponding to the size of the recording medium P to be fed, just by aligning the size pointer 9j with a
5 desired index mark on the recording medium size index 9k.

(Recording Medium Conveying Means)

Next, the recording medium conveying means 10 will be described, referring to Figure 1. The
10 recording medium conveying means 10 conveys the recording medium P stored in the feeder cassette 9 to an image forming station, and then, to the discharge tray 10j after the recording medium comes out of the fixing means 12. More specifically, as the conveyance
15 of the recording medium P begins after the installation of the feeder cassette 9, the pickup roller 10a is rotated to separate and feed out, one by one from the top, the recording medium P from the feeder cassette 9. The fed-out recording medium P is
20 conveyed rearward through the first reversing sheet path comprising conveying roller 10b, guide 10c, auxiliary rollers 10b, 10d2, and 10d3, and the like, whereby the recording medium P is reversed. Then, the recording medium P is conveyed to a pressure nip
25 formed between the photosensitive drum 2 and the transferring roller 11, where the toner image having been formed on the drum 2 surface is transferred onto

the recording medium P. The recording medium P having received the toner image is delivered, being guided by the cover guide 10e provided on the electrical component mounting board 14, to the fixing means 12, where the toner image is fixed. After being passed through the fixing means 12, the recording medium P is conveyed to the second reversal path, through the relay roller 10f. While being passed through this second reversing sheet path 10g, the recording medium P is reversed again, and then, is discharged by the discharge roller pair 10h and 10i onto the discharge tray 10j provided above both the scanner unit 8e and the installed process cassette B.

Next, referring to Figures 20 - 24, description is given as to a conveying unit for delivering the recording medium P from the cassette 9 to the image forming station. The aforementioned auxiliary rollers 10d1, 10d2, and 10d3 are slightly slanted by angles of α_1 , α_2 , and α_3 , respectively, relative to the axis of the conveying roller 10b. The presence of these angles generates a lateral pressure to shift laterally the recording medium P toward the conveying guide aligning surface 31 formed integrally on the frame 15.

As is evident from Figure 20, the conveying roller 10b does not have a length to cover the entire width of the recording material P, but instead, it



covers only a small width of the recording medium P, adjacent to the aligning surface 31.

As for the definitions of angles α_1 , α_2 , and α_3 , they are the axial angles of the auxiliary rollers 10d1, 10d2, and 10d3 relative to a circumferential surface of an phantom cylinder, which shares the same axis as the conveying roller 10, and the circumferential surface of which contains the centers of the auxiliary rollers. In this embodiment, these angles are set approximately as follows: $\alpha_1 = 0.5^\circ$; $\alpha_2 = 4.0^\circ$; and $\alpha_3 = 4.0^\circ$. The overall pressure exerted on the conveying roller 10b by the auxiliary rollers 10d1, 10d2 and 10d3 are set to be approximately 400 g, wherein the pressure exerted by the auxiliary rollers 10d1, 10d2, and 10d3 for shifting laterally the recording material P is approximately 150 g, and the maximum pressure of the compression spring is set to be approximately 70 gf.

The apparatus main assembly is provided with the main motor 20, which is linked to a conveying gear 10b1 and a pickup gear 10a1, through a gear train. In particular, a gear which engages with the pickup gear 10a1 is disposed so as for its meshing portion to correspond to the toothless portion of the pickup gear 10a1. An unshown feeding roller solenoid is hooked up with a stopper portion 10a2 of the pickup roller 10a, preventing thereby the rotation.

This Sheet Has Been Replaced





Referring to Figure 21, reference numeral 32 designate a clutch comprising a known built-in planetary gear train. A sun gear is rotated or stopped by a latch claw 32a which is rotated by a solenoid 32b about an axis 32c in the direction indicated by an arrow m, whereby the transmission of the driving force to the conveying roller 10 mounted on the axis of the clutch 32 is controlled. Referring to Figure 22, a reference numeral 32d designates a solenoid terminal to which a lead wire from the solenoid 32b is crimped.

The pickup roller 10a for separating and feeding out, one by one, the recording medium P stacked in the cassette 9, is linked to the pickup gear 10a1 through a roller axis 10a3.

A reference numeral 10m designates a conveying roller lever, which is rotatable about the axis of clutch 32. Together with a conveying roller lever spring 10m1, the conveying roller lever 10m pressures a cam portion provided on the pickup roller 10a, in the rotational direction indicated by an arrow n in Figure 20.

Referring to Figure 22, a reference numeral 30 designates a recording medium sensor, which detects the absence of the recording medium by pivoting in the direction indicated by an arrow o in Figure 23 when the recording medium P is not present on the middle



plate 9d of the cassette 9.

These components described in the preceding paragraphs are mounted on a feeder frame 10n. In addition, a sensor arm is rotatively mounted on a boss
5 portion of the feeder frame 10n, constituting all together the feeder unit.

In this embodiment, the passage for conveying the recording medium P comprises the first and second sheet reversing paths, forming thereby a so-called S-
10 shape. Therefore, not only can the space occupied by the apparatus be further reduced, but also, after the image is recorded, the recording medium P is stacked in the normal paginal order, with the image facing downward.

15 Referring to Figure 1, sensors S1, S2, and S3 are provided along the recording medium P conveying passage, for detecting the presence, absence, or the like, of the recording medium P.

The sensor S1 is a registration sensor, which
20 detects the leading end of the recording medium P being delivered to the transferring roller 11 from the cassette 9, providing thereby the laser scanner 8 with a timing for laser beam writing, and also, when the image forming apparatus is started, it detects whether
25 or not the recording medium P had been left within the apparatus main assembly.

Referring to Figure 24, the registration

sensor S1 is rotatable about an axis Sol, and is provided with edge portions Sla, S1b, and S1c for generating three signals. The edge portion Sla generates a signal to indicate whether or not a manually fed recording medium is present. The edge portion S1b generates a signal to indicate the presence of a recording medium P having been picked up and being on stand-by. The edge portion S1c generates a signal for providing the writing timing for the laser. More specifically, each signal is generated as a photointerruptor FC disposed on the electrical component mounting board detects each of the edge portions Sla, S1b, and S1c.

The sensor S2 is a discharge sensor, which not only detects the leading and trailing ends of the recording medium P after the recording medium P has passed the fixing means 12, but also, when the image forming apparatus is started, it detects whether or not the recording medium P had been left behind in the apparatus main assembly.

The sensor S3 is a sensor provided along the sheet path from the toner image transferring point to the fixing means 12, for detecting whether or not the recording medium P had been left behind, and at the same time, it serves as a sensor for detecting whether or not a rear lid 16f is open.

With the provision of these sensors, when the

This Sheet Has Been Replaced





apparatus is jammed, a main control detects the occurrence of the jam, based on the relation between the recording medium feeding timing and the signals from the sensors S1 and S2, bringing thereby the
5 apparatus to an emergency stop and displaying a jam symbol.

More specifically, whether or not the recording medium P has been jammed in the fixing means is determined following manner: when the control does
10 not receive from the discharge sensor S2 a signal indicating that the discharge sensor S2 has detected the arrival of the leading end of the recording medium P, it counts the time which has elapsed since the recording medium had been fed, and when it finds that
15 the elapsed time is longer than the time required for the leading end of the recording material P to reach the discharge sensor S2, it determines that the recording medium P has been jammed in the fixing means, bringing thereby the apparatus to an emergency
20 stop.

(Transferring Means)

The transferring means 11 transfers the toner image formed on the photosensitive drum 2 in the image forming station, onto the recording medium P. The
25 transferring means 11 of this embodiment comprises a transferring roller 11, as shown in Figure 1. The transferring roller 11 presses the recording medium P

onto the photosensitive drum 2 of the installed process cartridge B. With the recording medium P being pressed upon the photosensitive drum 2, a voltage having the polarity opposite to that of the toner image is applied to the transferring roller 11, whereby the toner image on the photosensitive drum 2 is transferred onto the recording medium P. A reference numeral 11a designates a spring, which pressures the transferring roller 11 onto the photosensitive drum 2.


On the upstream side of the transferring roller 11, relative to the recording medium conveyance direction, there is a guide member 11b, which stabilizes the recording medium P as the recording medium P enters into the nip between the photosensitive drum 2 and the transferring roller 11, and at the same time, shields the surface of the transferring roller 11 to prevent the toner from being scattered.

After being passed through the nip between the photosensitive drum 2 and transferring roller 11, the recording medium P is conveyed in the downward direction, at an approximate angle of 20° relative to the horizontal line, so that it can be surely separated from the photosensitive drum 2 after the transfer operation.

(Fixing Means)

This Sheet Has Been Replaced





-49-

The fixing means 12 fixes the toner image, which has been transferred onto the recording medium P by the voltage application to the transferring roller 11. Its structure is as shown in Figure 1. In the

5 fixing means 12, a reference numeral 12a designates a heat resistant film guide member shaped like a trough, the cross section of which forms a substantial semicircle. On the under side surface of this guide member 12a, a low thermal capacity ceramic heater 12b

10 of a flat plate shape is disposed, extending along the approximate longitudinal center line. Further, around the guide member 12a, a cylindrical (endless) thin film 12c of heat resistant resin is loosely fitted. This film 12c comprises three layers: an approximately

15 50 μ m thick polyimide base film, an approximately 4 μ m thick primer layer, and an approximately 10 μ m fluorine coat layer. The base layer material has a high tensile strength and it is thick enough to withstand various stresses or wear inflicted upon the

20 film. This primer layer is made of the mixture of polyamideimide resin, fluorinated resin, and carbon; therefore, it is electrically conductive.

Also on the under side of the guide member 12a, a pressure roller 12d is disposed in contact with

25 the ceramic heater 12b, with constant pressure provided by a spring (not shown), and the film 12c being interposed. In other words, the ceramic heater

12b and pressure roller 12d form a fixing nip, with the film 12c being interposed. The pressure roller 12d comprises a metallic core and soft silicone rubber, and the silicone rubber is fluorine coated on its peripheral surface.

The ceramic heater 12b is provided with a thermistor chip (unshown), and the power supply to the ceramic heater 12b is controlled by the temperature control system of a control portion, which will be described later, in response to the signal from the thermistor, so that a predetermined fixing temperature can be obtained. The pressure roller 12d is fitted with a gear at one axial end, and is rotated counterclockwise as indicated by an arrow in Figure 1, at a predetermined peripheral velocity. As the pressure roller 12d is rotatively driven, the cylindrical film 12c is clockwise rotated at a predetermined peripheral velocity around the film guide member 12a as indicated by the arrow mark in Figure 1, by the friction between the roller 12d and film 12c, through the fixing nip, remaining tightly in contact with and sliding on the downward facing surface of the ceramic heater 12b.

After undergoing the image transfer process, the recording medium P is delivered to the fixing means 12, where it is guided by an entrance guide 12f into the fixing nip formed between the temperature



controlled ceramic heater 12b and pressure roller 12d.

In the fixing nip, the recording medium P is fed

between the cylindrical film 12c which is being

rotatively driven, and pressure roller 12d, and is

5 passed through the nip together with the film 12c in a manner of being laminated together, remaining tightly pressed upon the downward facing surface of the ceramic heater 12b, with the film 12c being interposed.

10 While passing through the fixing nip, the unfixed toner image on the recording medium P receives, through the film 12c, the heat from the ceramic heater 12b, whereby the toner image is thermally fixed on the recording medium P. After
15 coming out of the fixing nip, the recording medium P is separated from the surface of rotating film 12c, and is guided by an exit guide 12g to the conveying roller 10f.

(De-curling after Fixing Operation)

20 The recording medium P is curled while being heated by the fixing means 12. Therefore, in this embodiment, after being passed through the fixing means 12, the recording medium P is de-curled before it is discharged onto the discharge tray 10j.

25 More specifically, referring to Figure 25, when a plain paper which is commonly used as the recording medium P is heated by the plate-shaped

This Sheet Has Been Replaced





heater 12b, it curls toward the non-heated side due to the temperature difference between the heated and non-heated surfaces. The plain paper is easiest to curl by the application of a curvature when the paper
5 temperature is in an approximate range of 60°C - 90°C. Therefore, in this embodiment, the recording medium P, having been curled downward in the fixing nip, is conveyed by a distance L1 of approximately 40 mm in a straight line, and then, is passed through the second
10 sheet path 10g forming a curvature having a radius R of approximately 30 mm, so that the recording medium P is subjected to a curvature opposite to that of the curl caused in the fixing nip.

Through this process, the recording medium P
15 having been heated to approximately 120°C by the heater 12b cools down to approximately 75°C, that is, an appropriate paper temperature, while being conveyed a straight distance L1. Then, as the recording medium P is conveyed so as to be curled in the reverse
20 direction, the curl generated in the fixing means 12 is effectively corrected and the recording medium P is discharged onto the discharge tray 10j. Therefore, this embodiment does not require a special component such as a de-curling roller dedicated to correction of
25 the curl.

(Gear Unit)

The gear train which transmits the rotational




driving force to the photosensitive drum 2, pickup roller 10a, or the like will be described.

(Creation of Gear Train Unit)

In the image forming apparatus of this embodiment, all the mechanical components, except for those in the scanner unit 8a and a cooling fan 19, are driven by a single driving force source, the main motor 20. This driving force from the main motor 20 is transmitted to each operational member through the gear train illustrated in Figures 26 - 28, wherein Figure 26 is a plan view of the gear train; Figure 27 is an oblique view of the gear unit; and Figure 28 is a sectional view depicting how the gears are mounted.

Most of gears in the gear train of this embodiment are concentrated on one of the lateral sides of the frame 15. Referring to Figure 26, among these gears of this gear train, the ones that transmit the driving force are the following five gears: (1) pickup gear 10a1 mounted on the same axle as that for the pickup roller 10a, for conveying the recording medium P from the cassette 9; (2) conveying gear 10b1 mounted on the same axle as that for the conveying roller 10b, for conveying the recording medium P having been delivered by the pickup roller 10a; (3) drum gear 2a attached to the photosensitive drum 2; (4) relay roller gear 10f1 for transmitting the driving force to the fixing gear mounted on the same



axle as that for the pressure roller 12d of the fixing means 12; and (5) discharging gear 10h1 mounted on the same axle as that for the discharging roller 10h.

In order to form images by driving the image forming apparatus, the developing sleeve 4d, toner feeding member 4b, transferring roller 11, polygon mirror 8b, and cooling fan 19 must be mechanically driven in addition to those mentioned in the foregoing, wherein the developing sleeve 4d, toner feeding member 4b, and transferring roller 11 receive the driving force from a gear meshed with the drum gear 2a when the photosensitive drum 2 is rotated, whereas the polygon mirror 8b is driven by the scanner motor 8c, and the cooling fan 19 is driven by its own fan motor.

In the gear train shown in Figure 26, the driving force generated by the main motor 20 is divided into the left and right forces through a motor pinion gear 20a, that is, one for a system which drives the drum and conveying means and the other for a system which drives the fixing means and discharging means. The drum and conveying means driving system is a system for driving the photosensitive drum 2 and conveying means 10 and is in charge of the operational range starting from the feeding of the recording medium P to the image formation. The drum driving gear train comprises: motor pinion 20a, large diameter



gear 13a1 and small diameter gear 13a2 of double gear 13a, idler gear 13b, large diameter gear 13c1 and small diameter gear 13c2 of double gear 13c which is the drum driving gear, being engaged to each other in this order, wherein the small diameter gear 13c2 transmits the driving force to the photosensitive drum 2 by engaging as the driving gear with the drum gear 2a.

The conveying means driving gear train comprises: idler gear 13b, small diameter gear 13d2 and large diameter gear 13d1 of double gear 13d, idler gear 13e, conveying means driving gear 13f, being engaged in this order, wherein this conveying means driving gear 13f transmits the driving force to the conveying roller 10b by engaging with the conveying gear 10b1. As described hereinbefore, this conveying roller 10b is united with the conveying gear 10b1, pickup roller 10a, feeding gear 10a1, and the like, being formed into a feeding unit, and is assembled as a unit into the apparatus main assembly 6. In this feeding unit, a clutch 32 (Figure 51) is provided, by which the conveying roller 10b is rotated in reverse, relative to the conveying gear 10b1.

The conveying means driving gear 13f is meshed with the large diameter gear 13g1 of the double gear 13g which is the feeding means driving gear, and the small diameter gear 13g2 of the double gear 13g is

meshed with the pickup gear 10a1, whereby the driving force is transmitted to the pickup roller 10a.

The gears of the gear train are made of resin material, wherein, since the double gear 13a, idler gear 13b, and double gear 13c transmits the driving force to the photosensitive drum 2 which carries a larger rotational load, they are made of special resin filled with glass fiber to increase their strength.

The fixing means and discharging means driving system, that is, the other system, drives the fixing means and the driving means. The fixing means driving gear train comprises: motor pinion 20a, large diameter gear 13h1 and small diameter gear 13h2 of double gear 13h, large diameter gear 13i1 and small diameter gear 13i2 of double gear 13i, idler gear 13j, small diameter gear 13k1 of double gear 13k which is a fixing means driving gear, being engaged to each other in this order, wherein the large diameter gear 13k2 is meshed with the relay roller gear 10f1, transmitting the driving force to the pressure roller 12d.

The idler gear 13j is meshed with the discharging means driving gear 13m, and this gear 13m is meshed with the discharging roller 10h, transmitting thereby the driving force to the discharging roller 10h.

Referring to Figure 27, the gears of the gear train are mounted on a supporting member 13n made of a

This Sheet Has Been Replaced





sheet of steel plate, being united as the gear unit. Referring to Figure 28, as for a method for mounting each of these gears on the supporting member 13n, a gear axle 13p having a flange 13o is crimped onto the supporting member 13n, and then, each of gears 13a - 13m is mounted on the gear axle 13p. Adjacent to the ends of some axles 13p, ring-like grooves 13p1 are cut, and the axle hole portion of the double gear 13h, for example, through which the axle 13p is put through, is provided with an elastically deformable projection 13q which can fit into the groove 13p1. When this gear 13h is mounted on the axle 13p, the projection 13q elastically deforms to ride over a straight portion 13p2 and drop into the groove 13p1. With the projection 13q being fitted in the groove 13p1, the gear 13h is not likely to easily come off the axle 13p.

Further, the gears such as the gear 13h having the projection 13q are strategically disposed so that when a force is exerted in a manner to cause other gears, which do not have a projective portion (for example, gear 13i), to come off the axle 13p, the gears with the projection 13q can serve as a deterrent for preventing them from easily coming off. Because of such an arrangement, each gear of this gear unit is not likely to come off after it is mounted on the gear axle 13p of its own; therefore, the gear unit is



easier to handle during transportation or the like.

Also, since all the gear axles 13p are provided with the flange 13o, not only are their chances of falling down during the crimping operation
5 minimized, but they are also reinforced against the load inflicted upon them in a manner so as to collapse them during the transmission of the driving force. Further, since the driving force from the main motor 20 is dividedly transmitted to the left and right
10 sides, balance is improved among the loads inflicted upon the pinion gear 20a in a manner to collapse it; therefore, the motor pinion gear 20 is more difficult to collapse.

Since the gears of the gear train are united
15 into a gear unit by means of mounting them on a single-piece supporting member 13n, occurrence of gear pitch error among a large number of gears is minimized; therefore, the driving force can be precisely transmitted. As for the transmission
20 efficiency per gear of the gear unit in this embodiment, it has been increased to approximately 95% or higher.

Out of all the gears in the gear train, all of the gears 13a - 13c of the gear train portion for
25 transmitting the driving force to the photosensitive drum 2 are helical gears, and the rest (gears other than those meshing with the helical gears) are spur



gears. The direction of the helix angle of the helical gear is determined based on the rotational direction of the photosensitive drum 2. More specifically, it is determined so that the thrust generated by the helical gear is directed to pressure the photosensitive drum 2 toward the aligning reference surface of the frame. The aligning reference surface of the frame will be described later.

10 Right after the process cartridge B has been installed, it is impossible to tell where the process cartridge B is located in the gap between the frame 15 and the process cartridge in the thrust direction of the drum axle, but when the gear train begins to rotate for the image formation, the entire process cartridge B is pushed toward the aligning reference surface of the frame 15 by the thrust generated by the meshing helical gears, being abutted on the aligning reference surface. Also, within the process cartridge B, the photosensitive drum 2, which is allowed some play in the thrust direction, is abutted on the aligning reference surface by the same thrust, whereby the positions of the process cartridge B and photosensitive drum 2 relative to the apparatus main assembly 6 are fixed. The reference for fixing the position of the cartridge will be described later.

The helix angle of the helical gear is



necessary to be large enough to produce a stable pressure in the thrust direction for keeping the photosensitive drum 2 abutted on the aligning reference surface while allowing the gear to rotate stably. However, too large a thrust is liable to reduce the transmission efficiency, to cause gear damage, or to trigger like situations. In consideration of such concerns, in this embodiment, the helix angle at the meshing portion between the drum driving gear 13c2 and drum gear 2a is set at approximately 14.6°.

The thrust generated by the helical gear abuts the process cartridge B and photosensitive drum 2 on the aligning reference surface, as well as causes the driving force transmission efficiency to drop. Therefore, where the thrust is not needed, a spur gear is used, or in the case of the double gear comprising the helical gears, the directions of the helix angles of the large and small gears are rendered to be the same so that the thrusts can be canceled.

<Sandwiching of Gear Train>

The gear unit 13 is mounted on the lateral wall of the frame 15. More specifically, referring to Figure 29, the surface of the left lateral wall of the frame 15, which serves as the aligning reference surface, is provided with holes 15a for fitting the gear axles 13p to which the gears 13a - 13m of the



gear unit 13 have been mounted, respectively. After fitting the gear axles 13p into these holes 15a, the supporting member 13n is screwed to the frame 15, with the screws put through screw holes provided at
5 predetermined locations of the supporting member 13n, completing thereby the mounting of the gear unit.

Out of these gear axles 13p, a gear axle 13p1 for supporting the drum driving gear 13c (Figure 26) and a gear axle 13p2 for supporting the double gear
10 13h are put through the holes 15a1 and 15a2 of the frame 15 and fixed there, respectively, whereby the position of the gear unit 13 relative to the frame 15 is fixed. Since the drum driving gear 13c is a gear for transmitting the driving force to the
15 photosensitive drum 2, the gear axle 13p1 for supporting this gear 13c is subjected to the largest load. However, the gear axle 13p1 is put through the frame hole 15a1 and fixed there, whereby the gear axle 13p1 is supported at both ends, by the frame hole 15a1
20 and supporting member 13n, respectively; therefore, the collapsing of the gear axle 13p1 or a like incident is unlikely to occur.

The gear axles 13p other than the two axles mentioned in the foregoing are also fitted in the
25 frame holes 15a, but the states of engagements between these gear axles 13p and holes 15a are rather rough compared to those of the aforementioned two gear



axles. In other words, these axles and holes serve as a sort of guide when the gear unit 13 is mounted on the frame 15.

As the gear unit 13 is mounted on one of the
5 lateral walls of the frame 15, the driving gears (more specifically, drum driving gear 13c, feeding means driving gear 13f, conveying means driving gear 13g, fixing means driving gear 13k, and discharging means driving gear 13m) for transmitting the driving force
10 to the drum gear 2a and the like project into the frame interior through the windows 15b provided on the lateral wall of the frame 15, being exposed within the frame interior, either entirely or partially, and become meshed with the counterpart gears such as the
15 drum gear 2a.

Also, the driving gears are mounted on the gear unit in such a manner that when the gear unit 13 is mounted on the frame 15, they are going to be disposed within the frame, at more inward locations
20 than where the gears (drum gear 2a and the like) driven by these driving gear are going to be disposed. In other words, after the gear unit 13 has been mounted on the frame 15, the driving gears are disposed at more inward locations than where the
25 driven gears are going to be disposed, so that when the driven gears are mounted, the driving gears will be waiting within the frame, being disposed at the



more inward locations. Therefore, the positional relationship between the gear unit 13 and each of the driven gears is such that either one can be mounted first, and any of them can be independently removed.

5 By uniting the gears of the gear train, in the form of a gear unit 13, and mounting them as the gear unit 13 on the frame 15, the gear train can be mounted, extremely simply and precisely. In addition, the gear train becomes interposed between (sandwiched
10 by) the lateral side wall and supporting member 13n. Therefore, there is no possibility that the gear trains are touched by fingers or the like, that the state of gear meshing is disturbed by a collision with foreign matter, nor that the oil from the gear train
15 is scattered to the external case 16 or the like. Further, since the gear train is sandwiched between the frame 15 and supporting member 13n, the noises generated as the gears of the gear train rotate can be reduced.

20 After the gear unit 13 is mounted on the frame 15, the main motor 20 for supplying the driving force to the gear train of the gear unit is mounted. On the left lateral wall of the frame 15, a U-shaped groove 15c is provided as shown in Figures 29 and 30.
25 As the motor 20 is lowered in a manner so as for the bearing portion of the motor 20 to be fitted into this U-shaped groove 15c, a motor pinion 20a drops into the



valley formed between the double gears 13a and 13h of the gear unit 13, becoming meshed with both gears 13a and 13h (Figure 26). The main motor 20 is provided with a mounting plate 20b, and is fixed by screwing
5 this mounting plate 20b to the left lateral wall of the frame 15.

The mounting plate 20b is provided with a leg portion 20b1 which extends downward as shown in Figure 30, and at the end of the leg portion, a connector 20c
10 is attached. As the motor bearing portion is lowered into the U-shape groove 15c in order to mount the main motor 20 on the frame 15, the connector 20c engages with a motor connector 14f2 provided on the electrical component mounting board 14a.

15 As the motor 20 is mounted, the mounting plate 20b partially overlaps with the supporting member 13n, whereby the heat generated by the rotating motor 20 is conducted to the supporting member 13n made of metallic plate, through the mounting plate 20
20 also made of the metallic plate, to be dissipated. In other words, the supporting member 13n functions as a radiating plate.

Referring to Figures 27 and 29, with the presence of thin stainless steel plates 13r screwed on
25 the supporting member 13n, the supporting member 13n of the gear unit 13 is electrically connected to the shield plate of the electrical component unit 14 which



is mounted at the bottom portion of the frame 15 .
Therefore, the electrical potential of the supporting
member 13n remains at ground level, and the aligning
reference surface of the frame 15 is entirely shielded
5 by the supporting member 13n. Further, as described
previously, the metallic mounting plate 20b of the
main motor 20 overlaps with the supporting member 13n;
therefore, the potential of the surface of the motor
20 remains at the ground level. Though the supporting
10 member 13n of this embodiment is made of steel plate,
it may be made of material other than steel plate, for
example, stainless steel plate, aluminum plate or the
like. As long as the material is electrically
conductive, it functions as the shield plate.

15 Since the supporting member 13n functions as
the shield plate as described in the foregoing, it is
preferable to mount an interface or the like on this
supporting member 13n and cover it with metallic
plate. With this arrangement, the interface or the
20 like is disposed between the metallic plates, which
simplifies the shielding.

(Electrical Component Unit)

Next, referring to Figures 31 - 33, the
electrical component unit 14 for controlling the
25 driving operation of each of the aforementioned
operational members will be described. Figure 31 is
an exploded view of the electrical component unit;




-66-

Figure 32 is a block diagram of the electrical component mounting board; and Figure 33 depicts how an AC inlet is mounted.

(Single Piece Electrical Component Mounting Board)

5 Referring to Figure 31, the electrical component unit 14 of this embodiment comprises an electrical component mounting board 14a, a case 14b, and a shield plate 14c, wherein the electrical component mounting board 14a is mounted in the case
10 14b, and the shield plate 14 c is attached to the bottom surface of the case 14b.

The electrical component mounting board 14a comprises: (1) an AC input portion 14a1 for receiving an AC power from an external commercial power source
15 21 and filtering noises; (2) a DC power source portion 14a2 for converting the AC power into the DC power of 5 V, 12 V, or the like; (3) a high voltage source 14a3 for supplying the power to the process cartridge B (developing means and charging roller) and
20 transferring roller 11; (4) a control circuit portion 14a7 comprising: a CPU 14a4 such as a microprocessor for controlling the overall operation of the image forming apparatus in response to the signals received from a group of sensors such as the registration
25 sensor S1, discharge sensor S2, remainder recording medium sensor S3, and the like; an ROM 14a5 for storing control programs of the CPU 14a1 and various .



data, and a RAM 14a6 to be used as the work area of the CPU 14a5 as well as to be used for storing temporarily various data; and (5) various switch sensors and connectors, wherein all of the listed
5 components are fixedly mounted on a single piece printed circuit board, whereas corresponding components to be connected with these components are provided with floating connectors.

Referring to Figures 31 and 32, it will be
10 described how the AC input portion 14a1, DC power source portion 14a2, high voltage source portion 14a3, and control circuit portion 14a7 are arranged on the single piece electrical component mounting board 14a. Referring to Figure 32, the left side relative to the
15 recording medium P conveyance direction is the driven side where the gear unit 13 is mounted for transmitting the mechanical driving force, and the right side is the non-driven side.

As shown in Figure 32, the AC input portion
20 14a1 belongs to the non-driven side and is disposed on the downstream side relative to the conveyance direction, and the high voltage source portion 14a3 also belongs to the non-driven side and is disposed on the upstream side. The control circuit portion 14a7
25 is disposed on the driven side, and the DC power source portion 14a2 is disposed approximately in the middle, being slightly offset to the driven side.



Adjacent to the non-driven side end of the high voltage source, the development bias contact pin 14d1, drum ground contact pin 14d2, and primary bias contact pin 14d3 are disposed, projecting out of the
5 holder cover 14e.

At the non-driven side end of the AC input portion, an AC connector 14f1 (AC inlet) is provided; adjacent to the driven side end of the control circuit portion 14a7, a motor connector 14f2 to which the
10 connector 20c of the main motor 20 is engaged, a scanner connector 14f3 for supplying the power to the scanner unit 8e, and an image signal connector 14f4 for receiving the image signal are provided; and at the downstream end of the board, a DC connector 14f5
15 for receiving the signal from the thermistor which detects the heater temperature of the fixing means, and an AC connector 14f6 for supplying the power to the heater, are provided.

The reason why the arrangement is made as
20 described in the foregoing is for the following advantage. It is conceivable that when the contact pins through which the power is supplied to the process cartridge B are on the driven side, the pins are liable to be displaced due to the changes in the
25 meshing state of the gears, causing thereby contact failures. However, when the high voltage source 14a3 provided with the contact pins 14d1, 14d2, and 14d3 is



disposed on the non-driven side, such contact failures do not occur.

The control circuit portion 14a7, that is, a low voltage circuit, is disposed on the driven side, that is, the side opposite to where the high voltage source 14a3 and the AC input portion 14a1 which supplies the power to the high voltage source 14a3 are disposed; therefore, the control circuit portion 14a7 is less likely to be affected by the noise from the high voltage source 14a3 or the like. Further, the control circuit portion 14a7 having the motor connector 14f2 is disposed on the driven side; therefore, the wiring of the main motor 20 connected mechanically to the gear unit does not run across the high voltage side, which also helps the control circuit portion 14a7 be less susceptible to the noise.

The connectors 14f1 - 14f6 of the electrical component mounting board 14a are directly coupled (direct train) with corresponding connectors attached directly to the main motor 20, fixing unit, or the like, wherein the electrical connection is realized through the electrical component mounting board; therefore, a conventional wiring harness is unnecessary. As a result, not only is it extremely simple to mount the electrical components onto the electrical component mounting board 14a, but also, there will be less connection mistakes. In addition,



since no wiring harness is laid out, the noise can be reduced. Further, the absence of the wiring harness improves the efficiency of the maintenance checkup operation.

5 When the electrical component mounting board 14a is joined with the case 14b, a positioning boss 14b1 provided on the case 14b is fitted into a positioning hole 14a8 provided on the electrical component mounting board 14a, and then, the board 14a
10 and case 14b are fixed to each other with screws placed at predetermined locations. Next, the shield plate 14c made of electrically conductive metallic plate is screwed on the bottom surface of the case 14b, completing thus the electric component unit 14.

15 The electrical component unit 14 must also serve as the upper surface guide for the recording medium P fed out of the cassette 9 (Figure 1); therefore, an R-shaped curved surface 14h is provided at the one end of the shield plate 14c, so that the
20 recording medium P being passed by this curved surface 14h can be smoothly conveyed to be reversed. Also, the electrical component mounting board 14a is covered with the cover guide 10e comprising the electrically conductive plates 10e1 and 10e2, and this cover guide
25 10e guides the bottom surface of the recording medium P having been reversed. Being covered by the cover guide 10e (10e1 and 10e2) and shield plate 14c, which



-71-

are made of the electrically conductive metallic plate, the electrical component mounting board 14a is provided with a higher degree of shielding effects.

Referring to Figure 33, the AC connector 14f1
5 is affixed to the shield plate 14c by means of screwing the electrically conductive metallic plate inlet 14i to the shield plate 14c, with the use of screws 14j in combination with lock face nuts. This arrangement of the metallic plate 14i and shield plate
10 14c creates an electrical single turn coil around the AC connector, whereby the noise from the AC input portion 14a1 is effectively suppressed.

<Cooling Duct>

In the image forming apparatus, the
15 electrical elements or the like mounted on the electrical component mounting board 14a generate heat, and also, the fixing means is provided with a heater; therefore, the heat sensitive electrical elements must be prevented from being deteriorated by the heat. In
20 this embodiment, the frame 15 is provided with the fan 19 for blowing air over the electrical component mounting board 14a.

In order to cool effectively the interior of the apparatus, a suction type fan is used as the
25 cooling fan 19. Referring to Figure 34, the air drawn in by the fan 19 is separated into sub-air ducts W1 and W2. The air duct is formed in such a manner that



one of the sub-air ducts, W1, is routed to the scanner unit 8e mounted in the upper portion of the frame 15, and the other, W2, is routed over the electrical component mounting board 14a, passing by the main
5 motor 20, and to an exit.

Referring to Figure 35, the sub-air duct W2 for sending the air to the electrical component mounting board 14a is further divided into the first duct W21 for cooling the hot spot of the DC power
10 source portion 14a2 and the second duct W22 for cooling the high voltage source portion 14a3. In order to accomplish such a duct arrangement, an air duct 14e1 is provided within the holder cover 14e which holds the contact pints. At the air entrance
15 and air exit of this air duct 14e1, air stream guide walls 14e2 are integrally formed with the holder cover 14e, whereby the air is smoothly flowed in and out of the duct 14e1.

Since the air duct 14e1 is formed as a part
20 of the holder cover 14e, no specific space is necessary for dividing the air duct W2 into the first and second air ducts W21 and W22.

<Holder Cover>

The holder cover 14e is attached to the case
25 14b, with the use of the so-called snap-in design. More specifically, referring to the oblique view in Figure 36 and the sectional view in Figure 37, the



-73-

case 14b is provided with the engagement hooks 14b2,
and the holder cover 14e is provided with the
engagement portions 14e3 engageable with the hooks
14b2. Further, the holder cover 14e is provided with
5 engagement projections 14e4 to come in contact with
the contact pins.

With this arrangement in place, as the holder
cover 14e is lowered so as for the end portions of the
contact pins 14d1 - 14d3 to be exposed from the pin
10 covers 14e5, and the engagement hooks 14b2 are
elastically deformed to be engaged with the engagement
portions 14e3, accomplishing the mounting of the
holder cover 14e by a single action. After the holder
cover 14e has been mounted, the engagement projections
15 14e4 are in contact with cylindrical spring covers
14d4 being integral with contact pins 14d1 - 14d3,
preventing the contact pins 14d1 - 14d3 from wobbling
sideways.

Three contact pins 14d1 - 14d3 are non-
20 linearly disposed relative to the installing direction
of the cartridge B (the same direction as the
recording medium conveyance direction), that is, the
upward direction in Figure 35. More specifically, in
relation to the development bias contact pin 14d1, the
25 ground contact pin 14d2 is offset to the left and the
charge bias contact pin 14d3 is offset to the right.
Therefore, the charge bias contact, drum ground



-74-

contact, and development bias contact which are provided on the bottom surface of the process cartridge B corresponding to the locations of these contact pins 14d1 - 14d3 do not make contact with the
5 wrong contact pins. In other words, with the contact pins 14d1 - 14d3 being disposed non-linearly, the charge bias contact of the cartridge B does not come in contact with the ground contact pin 14d2, and the drum ground contact of the cartridge B does not come
10 in contact with the development bias contact pin 14d3, during the insertion of the cartridge B. Therefore, the unnecessary contacts between the contacts and contact pins are eliminated.

By having the holder divide the passage of
15 the air flowing over the electrical component mounting board 14a, the heat generating portions of electrical component mounting board 14a can be effectively cooled without adding to the component count.

Further, being provided with the so-called
20 snap-in structure, the holder cover 14e can be mounted with a single action. Though the charge bias contact pins 14d1 is disposed on the side opposite to the ground contact pin 14d2 across the charging roller 11, these contact pins 14d1 - 14d3 are covered with the
25 single piece holder cover 14e; therefore, even when the toner leaks out of the transferring station, the holder cover 14e catches the toner, preventing thereby




the toner from adhering to the surface of electrical component mounting board 14a or contact pins and causing a high voltage leak.

<Structure of Intermediary Connector>

5 The electrical connection is established by coupling the connectors provided on the electrical component mounting board 14a with the connectors of various electrical components, wherein in this embodiment, the coupling of the connectors is
10 simplified by using the intermediary connectors. For example, referring to Figure 32, the image signal connector 14f4 is first coupled with an image processing circuit board 22 as the interface, and is indirectly coupled with a host computer 23 through
15 this circuit board 22, wherein the connection between this image signal connector 14f4 and image processing circuit board 22 is established with use of an intermediary connector 24 as shown in Figure 38.

 This intermediary connector 24 comprises a
20 connector main frame 24b, a number of connecting pins 24a supported by the connector main frame 24b, and a plug portion 24c for plugging one end of each connecting pin into the image signal connector 14f4 of electrical component mounting board 14a. Also, the
25 connector main frame 24b is provided with a pair of guide hook portions 24d, which serve as a guide when the other end of each connecting pin 24a is inserted



-76-

into the connector 22a of image processing circuit board 22, as shown in Figure 39. The ends of the guide hook portions 24d project beyond those of the connecting pins and are in the form of a hook
5 engageable with through holes 22b provided on the image processing circuit board 22.

Referring to Figure 39, when the electrical component mounting board 14a is electrically connected to the image processing circuit board 22, with the use
10 of the intermediary connector 24 having the aforementioned structure, the plug portion 24c is first inserted into the image signal connector 14f4 of the electrical component mounting board 14a, and then, the connecting pins 24a are inserted into the
15 connector 22a of the image processing circuit board 22. At this time, before the connecting pins 24a come to be inserted into the connector 22a, the guide hook portions 24d are engaged into the through holes 22b of the image processing circuit board 22, guiding the
20 connecting pins 24a into the connector 22a while being elastically deformed, and as soon as the pins 24a are completely inserted into the connector 22a, the guide hook portions 24d spring back to their original shapes, preventing themselves from disengaged.

25 In other words, the intermediary connector 24 having the guide hook portions 24d can be also coupled with the connector 22a of the image processing circuit



-77-

board 22, with the so-called snap-in structure. All that is needed for establishing this connection is to simply engage the guide hook portions into the through holes 22b, which not only provide visible guidance, but also give a feel of clicking at the moment the connection is completed. Therefore, the connecting operation is very easy. Further, since the guide hook portions 24 becomes disengagement-proof once they become engaged with the through holes 22b, the image processing circuit board 22 and intermediary connector 24 do not disengage from each other, offering thereby improved connectional reliability. Further, the presence of the guide hook portions 24d allows the stresses exerted on the intermediary connector by external disturbances or the like to be dissipated to the guide hook portions 24d, preventing thereby the connecting pins 24a from being directly subjected to the stresses. Therefore, the connecting pins 24a can be prevented from being damaged through deformation caused by external disturbances or the like.

Further, by forming asymmetrically the pair of guide hook portions 24d provided on the intermediary connector 24, relative to the center line of the connector 24, the intermediary connector 24 can be prevented from being reversely inserted. For example, the pair of guide hook portions 24d may be differentiated in shape or size, wherein the through

holes 24b may be correspondingly changed in shape or size.

In this embodiment, the guide hook portions 24d are provided at only one end of the intermediary connector 24, that is, on the side where the connection is made with the connector 22a of the image processing circuit board 22, whereas on the side where the connection is made with the connector 14f4 of the electrical component mounting board 14a, the plain plug portion 24c is provided. However, an intermediary connector 24 as shown in Figure 40 may be employed. This intermediary connector 24 shown in Figure 40 is provided with the guide hook portions 24d also on the side where the connection is made with the connector 14f4 of the electrical component mounting board 14a, with the provision of corresponding through holes 22b on the electrical component mounting board 14a, so that the connector 14f4 and intermediary connector 24 can be also coupled with the so-called snap-in structure. With this arrangement, the electrical connection can be more easily made between the electrical component mounting board 14a and image processing circuit board 22.

Further, in this embodiment, the intermediary connector 24 is used for the connection of the image processing circuit board 22, but it can be also used for making connections between other connectors, as

This Sheet Has Been Replaced





well as for establishing electrical connections between the components in electrical or electronic apparatuses other than the image forming apparatus.

(Cooling Fan)

5 Next, referring to Figures 41 - 43, the structure of the cooling fan 19 will be described. Referring to Figure 41, the cooling fan 19 comprises a fan main assembly 19a, a fan cover 19b for covering the fan main assembly, a mesh filter 19c attached to
10 the fan cover 19b for preventing dust or foreign matter from entering the apparatus, and metallic shield plate 19d attached to the fan cover 19b for preventing electrostatic noise.

 The fan main assembly 19a comprises a frame
15 19a2 and a fan mounted on the frame 19a2. This frame 19a2 is provided with engagement portions 19a3 around its side walls. The fan cover 19b is molded of flexible resin material such as ABS, PP, PC, or PPPO, in the form of a cylinder having an opening at both
20 ends, and its side walls are provided with elastic engagement plates 19b1 which look as if they were made by cutting the side walls and bending slightly inward the cut portions. These engagement plates 19b1 engage with the engagement portions 19a3.

25 The right and left walls of the fan cover 19b are provided with pressing portions 19b2 which can elastically deformed inward, and the exterior surface



of each pressing portion 19b2 is provided with a tapered projection 19b3 which is integrally formed with the pressing portion 19b3. Further, at the edge portions of one of the open ends of the fan cover 19b
5 (left side in Figure 41), molded spring portions 19b4 are provided, which are elastically deformable by pressure.

The top and bottom walls of the fan cover 19b are provided with engagement hook portions 19b5 used
10 for fixing the cover 19b to the frame 15. These hook portions 19b5 have elasticity and engage with the engagement hole portions provided on the frame 15.

At the edge portions of the intake side opening (right side in Figure 41) of the fan cover
15 19b, contact portions 19b7 where the filter 19c makes contact are provided, wherein the contact portions have an engagement projection 19b8. The filter contact surface of the contact portion 19b7 slightly (approximately 1 mm - 2 mm) projects above the end of
20 the intake side opening 19b6.

The mesh filter 19c is provided with holes 19c2 in which the engagement projection 19b8 is fitted. The shield plate 19d is provided with a shield arm portions 19d2 and engagement portions 19d1
25 with cut-and-raised locking tabs, in which the engagement projection 19b8 is to be locked in.

As for the assembling process of the cooling



fan 19, first, the fan main assembly 19a is fitted in the fan cover 19b, whereby the end portion of the engagement plate 19b1 of the cover 19b automatically engages with the engagement portions 19a3, locking
5 together the fan main assembly 19a and fan cover 19b. In other words, the fan main assembly 19a and fan cover 19b are locked together with the so-called snap-in structure.

At the intake side opening of the fan cover
10 19b, the engagement projection 19b8 is put through the hole 19c1 of the filter 19c and is engaged with the engagement portion 19d1 of the shield plate 19d, whereby the filter 19c and shield plate 19d are attached. This filter 19c and shield plate 19d can be
15 also attached by a single action.

Next, referring to Figure 42 and 43, a fan attachment portion 15m of the frame 15 is provided with a circular air passage hole 15m1, and above and below this hole 15m1, an engagement hole 15m2 is
20 provided, into which the engagement hook portion 19b5 of the fan cover 19b is engaged. Therefore, as the engagement hook portion 15b5 is engaged into the engagement hole 15m2, the cooling fan 19 is automatically mounted on the frame 15. In other
25 words, the cooling fan 19 is mounted with the so-called snap-in structure.

When the fan is mounted, the tapered



projection 19b3 is pressed on the frame surface 15m3, whereby the pressing portion 19b2 is elastically deformed inward to be pressed down on the fan main assembly 19a. With this arrangement, even when a
5 certain amount of play is found between the fan main assembly 19a and fan cover 19b after the installation of a commercially available general purpose fan, the play can be eliminated as they are assembled into the frame 15. Further, when the cooling fan 19 is mounted
10 on the frame 15, the molded spring portion 19b4 is pressed on the frame 15m4 and is elastically deformed. This elastic deformation keeps the fan cover 19b and frame 15 rattle free. Having elasticity as described in the foregoing, the pressing portion 19b2 and molded
15 spring 19b4 constitute a vibration preventing means which effectively absorbs the vibrations during the fan operation.

When the cooling fan 19 mounted on the frame 15 is on, cooling air is sent into the apparatus as
20 indicated by an arrow mark W0 in Figure 48, through the filter 19c, and the main air duct which extends as far as the air passage hole 15m1. After the accumulation of usage time, the filter 19c may be clogged with dust or foreign matter. When such a
25 situation occurs in this embodiment, the cooling air is sent into the apparatus through the sub-air duct indicated by an arrow mark W01 in Figure 43. In other



words, the end portion of the intake side opening of the fan cover 19b is not perfectly in contact with the filter 19c, but instead, a small amount of gap is provided between them (equivalent to the amount by which the filter contact portion 19b7 projects above the end of the intake side opening 19b6). Thus, when the filter 19c is clogged, the cooling air is drawn into the apparatus, through the gap and the sub-air duct indicated by the arrow mark W01. Therefore, the cooling system of this embodiment can afford the minimum cooling capacity even when the filter 19c is clogged.

(Frame)

Next, description will be given as to the frame 15 on which the process cartridge B, scanner unit 8e, gear unit 13, electrical component unit 14 and the like are mounted. Referring to Figure 5, the frame 15 of this embodiment has an integral monocoque structure. In consideration of rigidity, dimensional stability, heat resistance and the like properties, it is injection-molded of PC (polycarbonate), PPO (polyphenylene oxide), ABS (acrylonitrile-butadiene-styrene), HIPS (high impact styrene) or a like resin, in the form of a three-dimensional, highly precise single piece component with high rigidity. The frame 15 may be made of composite material composed by mixing glass fiber or carbon fiber into the preceding



-84-

resin material by approximately 30% - 50%, which can further increase the rigidity.

Referring to Figures 1 and 5, the frame 15 is provided with the following portions formed integrally with the frame 15: cassette guide portion 15d for
5 guiding and supporting the cassette 9 which stores the recording medium P; motor supporting portion 15e for supporting the main motor 20; guide portions 7a and 7b for guiding and supporting the process cartridge B;
10 supporting portion 15f for the scanner unit 8e; supporting portion 15g for the reflection mirror 8f; supporting portion 15h for the transferring portion 11; supporting portion 15i for the cover guide 10e; positioning-supporting portions (unshown) for pickup
15 roller 10a, conveying roller 10b, and discharging rollers 10h and 10i; positioning portion for the electrical component unit 14 on which various sensors and the like are mounted; and cassette inserting guide portion. Therefore, the positional relation among the
20 various units described hereinbefore can be highly precisely fixed.

Since the guide portion 15j which guides the recording medium P from the conveying roller 10b to the transferring roller 11 is integrally formed with
25 the frame 15, a precise and stable positional relationship is always maintained between the recording medium P and the transfer nip portion



created by the pressure contact between the
photosensitive drum 2 and the transferring roller 11.
Therefore, high quality images, with no sign of image
shifting slanting or the like which occurs during the
5 transfer operation, can be produced.

Further, the sheet path 10g for reversing the
recording medium P after the image fixing process is
also integrally formed with the frame 15; therefore,
the positional relation of the fixing means 12 to the
10 relaying roller 10f and discharging roller 10h is also
highly precisely maintained. As a result, the sheet
reversing path which reverses as well as de-curls the
curled recording medium after the fixation can be
precisely structured as described previously.

15 Since the positions of the scanner unit 8e,
reflection mirror 8f, and process cartridge B are
fixed by the frame 15, the distances among these units
can be precisely maintained; therefore, the degree of
positional accuracy by which the laser beam is
20 projected on the photosensitive drum 2 is improved
along with the degree of positional accuracy by which
the image is transferred onto the recording medium P.

The position of the scanner unit 8e is fixed
by the scanner supporting portion 15f of the frame 15.
25 This scanner supporting portion 15f is formed in such
a manner as to bridge the left and right walls of the
frame 15, being in a form least susceptible to the



frame 15 distortion.

More specifically, the rigidity of the frame 15 is provided by the beams bridging the left and right side walls. The first of the beams is constituted by the fixing means supporting portion 15n and sheet path 10g, and the second is constituted by the guide portion 15j. Further, the electrical component unit 14 is screwed on in such a manner as to bridge the fixing means supporting portion 15n and guide portion 15j, reinforcing thereby the preceding two cross beams. In other words, the guide portion 15j, sheet path 10g, fixing means supporting portion 15n, and scanner supporting portion 15f constitute beam structures for improving the frame 15 strength by bridging the left and right side walls.

The scanner supporting portion 15f is disposed between the guide portion 15j and fixing means supporting portion 15n, while being above both fixing means supporting portion 15n and guide portion 15j, covering the area from the approximate middle of the apparatus, relative to the recording medium P conveying direction, to the fixing means supporting portion 15n. This location is approximately the center of the frame 15, which coincides with the location of the node of the torsional vibration, that is, the portion with high rigidity.

Since the main motor 20 generates vibrations



when rotates, it must be disposed at a location with higher rigidity in the frame 15; therefore, the motor supporting portion 15e for supporting the motor 20 is disposed at the location where the scanner supporting
5 portion 15f meets the side wall, that is, a location with high rigidity. Further, with the main motor being disposed adjacent to the apparatus center, the driving force can be effectively proportioned for conveying the recording medium P, for driving the
10 fixing means, and for driving the photosensitive drum 2.

Further, having a three-dimensional structure, the frame 15 of this embodiment offers such advantages that its rigidity is high, and that the
15 vibrations from the main motor 20, scanner motor 8c, and cooling fan 19 more easily attenuate, being unlikely to cause the frame 15 to resonate.

While problems related to erroneous image formation, faulty recording medium P conveyance or the
20 like can be prevented by inspecting the frame 15, the frame 15 of this embodiment is a single piece frame; therefore, only a single piece is needed to be inspected in order to take quickly appropriate measures for correcting the predictable problems,
25 improving thereby the productivity.

When a metallic filler (stainless steel, copper, or the like) is used as the filler material to



be mixed with the resin material for the frame 15, not only can the frame 15 rigidity be further improved, but also some conductivity equivalent to a resistance value of approximately 10 Ω can be given. With this
5 composition, the electrical noise generated from the electrical component mounting board 14a within the apparatus can be prevented from leaking outward from the apparatus.

When highly elastic rubber material is mixed
10 into the resin material for the frame 15, the vibration attenuating properties of the frame 15 can be enhanced. In other words, various complex functions can be given to the frame 15, by means of mixing various material or materials having specific
15 relevant properties, into the resin material for the frame 15.

(External Case)

After the various components or units are mounted on the frame 15, the assembly is covered with
20 the external case 16 to finish the image forming apparatus. This external case 16 will be described next.

(Integral External Case)

Referring to Figure 44, an oblique front
25 view, and Figure 45, an oblique rear view, the external case 16 comprises a main cover 16a, a top lid 16b, side lids 16c, 16d, and 16e, and a rear lid 16f,



-89-

all of which are united into an external case unit.
The main cover 16a of this embodiment is different
from that for the prior type image forming apparatus,
in that a total of five walls, that is, top wall,
5 front and rear walls, and left and right walls, are
integrated, whereas the prior type comprises two or
more separate pieces. It is molded of resin material.
On the top surface of the main cover 16a, the
recording medium P discharge tray 10j is provided at
10 the rear, being molded integrally with the main cover
16a, and the cartridge inserting opening 16j is
provided at the front. This opening 16j is exposed or
covered by the top lid 16b.

On the interior surface of each of the front
15 and rear walls of the main cover 16a, a pair of
engagement claws 16a1 are provided, and on the
interior surface of each of the lateral walls, an
engagement portion 16a4 is provided at each of
predetermined locations. As the main cover 16a is
20 lowered from above onto the frame 15, the claws 16a1
and engagement portions 16a4 engage with the frame.
Then, the main cover 16a is fixed to the frame 15,
with use of screws 25. These screws 25 are placed
where they cannot be seen when the top lid 16b is
25 closed.

Since the cover 16a which is the main
structure of the external case 16 is integrated as



-90-

described in the foregoing, it can be simply mounted on the frame 15 just by lowering it from above. In other words, all that is needed to finish the apparatus exterior of this embodiment is to cover the
5 frame 15 with the main cover 16a, whereas the prior external case comprises several separate pieces and each must be individually mounted with the use of screws or the like. Therefore, it becomes extremely simple to mount the external case of this embodiment,
10 reducing the assembly time.

The size of the main cover 16a has been reduced to a range presented hereinafter. Downsizing of the image forming apparatus has been accomplished to a point where an image forming apparatus for
15 printing images on the recording medium P of A4 size (210 mm x 297 mm) can be fitted into a main cover 16a of this size.

	(1) Height	approx. 130 mm - 145 mm
	(2) Depth	approx. 350 mm - 370 mm
20	(3) Width	approx. 350 mm - 360 mm

<Top Lid>

The top lid 16b is provided with leg portion 16b1 which is rotatable about the a rotational axis provided within the main cover 16b. This rotational
25 axis (unshown) is provided with a torsional hinge spring so that the top lid 16b automatically opens when the lock is released for exchanging the process



cartridge B or dealing with the problem of jamming.

The lock of the top lid 16b is released by an eject button 16g attached on the surface of the right wall of the main cover 16a. As shown in Figure 46(a),
5 the eject button 16g is provided with a guide member 16g1, allowing the eject button 16g to be pushed in or out. The guide member 16g1 is provided with a compression spring 16h, which pressures the eject button 16g outward from the external case 16g to the
10 normal position.

The guide member 16g1 is disposed so as to face the sliding member 26 when the external case 16 is covering the frame 15, as shown in Figure 46(a). This sliding member 26 is provided with a pair of claw
15 portions 26a which engage with the frame 15 as shown in Figure 46(b) to allow the sliding member 26 to be slid in the directions indicated by arrows a or b without dropping out. This sliding member 26 is always under the pressure from a spring (unshown) in
20 the direction indicated by the arrow mark a.

The sliding member 26 is also provided with engagement portions 26b. When the top lid 16b is closed, the engagement hook portion 16b2 provided on the cover 16b engages with the engagement portion 26b
25 and locks shut the top lid 16b. When the eject button 16g is pressed, the guide member 16g1 slides the sliding member 26 in the direction indicated by the



arrow b in Figure 46(b), whereby the locked engagement hook portion 16b2 is disengaged from the engagement portion 26b. As a result, the top lid 16b is opened by the aforementioned hinge spring.

5 <Side Lids>

On the right wall of the main cover 16a, an inlet connection window is provided at the rear, along with a side lid 16c to cover this window. On the left wall of the main cover, an I/O connection window is provided at the rear, along with a side lid 16d to cover this window. Also on the left wall of the main cover 16a, a module exchange window is provided approximately in the middle, along with a side lid 16e to cover this window.

15 Next, the structures for opening or closing these side lids will be described. Since all three side lids 16c, 16d, and 16e have basically the same structures for opening or closing them, only the lid 16c for covering the inlet window will be described as
20 their representative, for the sake of convenience.


Referring to Figure 47(a), one edge of the side lid 16c is provided with a pair of hinge claws 16c1. These hinge claws are inserted through the window 16i of the main cover 16a and are pivoted about
25 the edge of the window 16i where the edge of the side lid 16 makes contact as shown in Figure 47(a), and a pair of engagement claws 16c2 provided on the other



edge of the side lid 16c are hooked onto a pair of engagement ribs 16a1 provided on the internal surface of the main cover 16a, fixing thereby the side lid 16 in place.

5 The cover 16c and window 16i are provided with a power cord cutaway 16c3 and 16i1, at the edge adjacent to the ribs 16a1 and at the edge adjacent to the engagement claws 16c2, respectively, so that a power cord can be put through a hole formed by these cutaways. Further, the side lid 16c is provided with
10 a knurled surface 16c4 on the rearward facing portion so that it is easier to be opened or closed.

 The portions of the side lid 16c and main cover 16a, where the power cord cutaways 16c3 and 16i1
15 are provided, have half the thickness of the other portions, at the areas indicated by solidus in Figure 47(c), and these solidus areas with half the thickness overlap each other when the side lid 16c is closed. This arrangement is made to cause the cord 27 put
20 through the hole formed by the power cord cutaway 16c3 and 16i1 of the side lid 16c and main cover 16a, respectively, to hang up on the projecting thin wall portion 16a2 of the main cover 16a, when the cord 27 is pulled by mistake in the direction indicated by an
25 arrow mark c in Figure 47(b), so that the side lid 16c is prevented from being accidentally opened by the cord 27 pulled in the wrong direction by mistake.



-94-

Needless to say, the measurement d of the opening of the cutaway portion 16i1 is made to be larger than the diameter of the cord 27.

Similarly, the I/O connection side lid 16d is
5 provided with the same structure, that is, the cord cutaway and knurled surface.

With provision of the side lids 16c, 16d, and 16e, the connectors for the cord 27 or the like are not exposed, which prevents dust or foreign matter
10 from settling down on the connector portions. Also, this arrangement of placing the cord 27 to be pulled out rearward favorably affects the apparatus design.

<Double Protection for Reflection Mirror>

While the external case 16 covering the
15 apparatus constitutes the apparatus exterior, this external case 16 offers double protection to the reflection mirror 8f of the optical system. The reflection mirror 8f is mounted on the frame 15, and when this reflection mirror 8f is shifted even by a
20 slightest amount, the optical image projected on the photosensitive drum is distorted, which results in the distorted image or the like. Therefore, the positional accuracy of the reflection mirror 8f must be strictly controlled, and it is preferable to
25 prevent as much as possible the reflection mirror 8f from being subjected to impact.

Therefore, in this embodiment, when the frame



15 is covered with the external case 16, the top portion of the reflection mirror mounted on the frame 15 is covered with the mirror protecting portion 16a3 of the main frame 16a as shown in Figure 44 and 48.

5 Further, this mirror protecting portion 16a3 is covered with the top lid 16b when the top lid 16b is closed.

Therefore, when the top lid 16b is at a normal position, that is, when it is closed, the
10 reflection mirror 8f is under double protection, being covered by the mirror protecting portion 16a3 and top lid 16b. With this arrangement in place, even when the something is dropped on the apparatus by mistake, its impact is unlikely to be transmitted to the
15 reflection mirror 8f.

<LED Light Conducting Member>

On the top surface of the external case 16, a display portion is provided for displaying whether the power is on or off, whether the line connecting the
20 host computer and image forming apparatus is on or off, or the like state of the image forming apparatus, which is indicated by whether the light from the LED is on or not. This light from the LED is conducted to the top surface of the external case 16 through an
25 optically conductive member 28 shown in Figures 49 and 50.

This optically conductive member 28 is

composed of material such as acrylic material having a high light transmissivity, being provided with an extremely smoothly formed surface, and is attached to the internal surface of the external cover 16, wherein
5 each of the light exiting ends of four light pipes 28a, 28b, 28c, and 28d is exposed at the top surface of the external case 16 (Figure 44 and 45). When the external case 16 is in place, each of the light entering ends of the aforementioned four light pipes
10 28a, 28b, 28c, and 28d is disposed to face a corresponding LED 28f, which comes on or off in response to the control from the control circuit portion 14a7, so that the light is conducted to be displayed at the top surface of the external case 16.

15 The line between the host computer and image forming apparatus is switched on or off by pressing an access button 29 exposed outward the external case 16, as shown in Figure 44. This access button 29 is attached so as to be pivotable about an axis 29a as
20 shown in Figure 49. As for the location of the access button 29, it is on the internal surface of the external case, approximately at the same location as the optically conductive member 28, and a portion of the optically conductive member 28 pivotally supports
25 the axis 29a of the access button 29.

When the access button 29 is pressed, a pressing portion 29a is pivoted and presses a contact

This Sheet Has Been Replaced





switch (unshown) connected to the electrical component mounting board 14a. Then, an operational mode is switched through this switch, and the LED 28f is turned on or off in response to this mode switching.

5 (Assembling Process)

The aforementioned assembly process is centered around the frame 15. Next, the assembling order will be described referring to Figures 1 and 5.

To begin with, the cover guide 10e is mounted
10 from underneath (in actuality, the frame 15 is placed upside down, and the assembly takes place downward from the top), and then, the electrical component unit 14 is mounted from underneath the cover guide 10e. Further, the conveying unit 30 in which the pickup
15 roller 10a, conveying gear 10a1, conveying roller 10b and the like are united, is mounted.

Since the electrical component unit 14 is mounted from underneath as described in the foregoing, the recording medium P guiding portion 15j (Figure 1)
20 to be located above the electrical component unit 14 can be integrally molded with the frame 15, which in turn makes it easy to establish the positional relationship of the recording medium P to the transfer nip formed between the photosensitive drum 2 and
25 transferring roller 11 by their contact pressure, to be always highly precise.

When the assembly process is structured so as




-98-

for the electrical component unit 14 to be mounted from above as it is done in the prior assembly process, the conveying guide portion 15j cannot be integrally formed with the frame 15, and as a result, the conveying guide portion is required to be highly precisely positioned relative to the frame 15, in order to achieve a high degree of accuracy in the positional relation of the recording medium P to the transfer nip, which makes a simple assembly process impossible, whereas in this embodiment, such a problem does not exist.

Diagonally downward from above the front side of the frame 15 (putting the upside down frame 15 back to the normal position), guide 10c, rollers 10d1, 10d2, and 10d3 (Figure 1) are mounted. Then, after the gear unit 13 are mounted on the left lateral wall of the frame 15, the main motor 20 is mounted. At the same time as this main motor 20 is mounted, the connector 20c of the main motor 20 is fitted into the motor connector 14f2 of the electrical component mounting board 14a. Next, after the transferring unit comprising the transferring roller 11, guide member 11b, and the like are mounted, the scanner unit 8e is mounted.

Further, the fixing means 12 in which the film guide member 12a, pressure roller 12d and the like are united, is mounted, and during this step, the



-99-

connectors of the fixing means 12 are inserted into the DC and AC connectors 14f5 and 14f6. Then, after the discharging members such as the discharging roller pairs 10h and 10i, and the cooling fan 19 are mounted, 5 the reflection mirror 8f is mounted last.

After all the components are thus mounted on the frame 15, the external case 16 is mounted from above the frame 15, completing the assembly process of the image forming apparatus A. Then, the cassette 9 10 and process cartridge B are inserted to complete the entire assembly process.

(Image Forming Operation)

Next, referring to Figure 1, the image forming operation of the aforementioned image forming apparatus A will be described. First, the process 15 cartridge B is installed, along with the cassette 9 storing the recording medium P. When the apparatus in this state receives a recording start signal, the pickup roller 10a along with the conveying roller 10b 20 are rotated, whereby the recording medium P is separated one by one by the separating claw 9f, is fed out of the cassette 9, with its top surface being guided by the shield plate 14c of the electrical component unit 14, and is delivered to the conveying 25 roller 10b. After being reversed along the conveying roller 10b, it is conveyed to the image forming station, with its bottom surface being guided by the




guide portion 15j and the top side being guided by the guide member 10k.

When the leading end of the recording medium P is detected by the registration sensor S1, an image
5 is formed in the image forming station in synchronism with the conveying timing with which the leading end of the recording medium P travels from the sensor to the transfer nip portion.

More specifically, the photosensitive drum 2
10 is rotated in the direction indicated by an arrow in Figure 1 in a manner so as to synchronize with the recording medium P conveying timing, and in response to this rotation, a charge bias is applied to the charging roller 3a, whereby the surface of the
15 photosensitive drum 2 is uniformly charged. Then, a laser beam modulated by the imaging signal is projected from the optical system 8 onto the surface of the photosensitive drum 2, whereby a latent image is formed on the drum surface in response to the
20 projected laser beam.

At the same time as when the latent image is formed, the developing means 4 of the process cartridge B is driven, whereby the toner feeding mechanism 4b is driven for feeding the toner within
25 the toner storage 4a out to the developing sleeve 4d, and the toner layer is formed on the rotating developing sleeve 4d. The latent image on the



photosensitive drum 2 is developed by the toner by applying to the developing sleeve 4d a voltage having the same polarity and substantially the same amount of electric potential as those of the photosensitive drum 2. Then, the toner image on the photosensitive drum 2 is transferred onto the recording medium P having been delivered to the transfer nip portion, by applying to the transferring roller 11 a voltage having the polarity opposite to that of the toner.

While the photosensitive drum 2 from which the toner image has been transferred onto the recording medium P is further rotated in the arrow direction in Figure 1, the residual toner on the photosensitive drum 2 is scraped off by the cleaning blade 5a. The scraped toner is collected in the waste toner storage 5c.

On the other hand, the recording medium P on which the toner image has been transferred is guided by the cover guide 10e, by the bottom surface, and is conveyed to the fixing means 12. In this fixing means 12, the toner image on the recording medium is fixed by applying heat and pressure. Next, the recording medium P is reversed by the discharge relay roller 10f and the sheet path 10g, being thereby de-curved as it is reversely curved, and is discharged by the discharge roller 10h and 10i into the discharge tray 10j.



-102-

(Image Formation References)

In the image forming apparatus of this embodiment, (1) recording medium P conveyance reference, (2) process cartridge B installation position reference, and (3) scanning start reference, based on which the optical system 8 begins projecting the optical image onto the photosensitive drum 2, are provided on the same side of the image forming apparatus A (in this embodiment, the left lateral side of the apparatus main assembly, that is, the side on which the gear unit 13 is disposed). This arrangement will be more specifically described referring to a schematic plan view in Figure 51.

First, the recording medium P conveyance reference will be described. While, after having been fed out by the pickup roller 10a, the recording medium P is conveyed forward by the conveying roller 10b and rollers 10d1, 10d2, and 10d3 being pressed thereupon (Figure 1), the angular conveyance angles α (angle at which the rollers press the recording medium P onto the referential surface of the conveying guide), at which three rollers 10d1, 10d2, and 10d3 are angled to the left, are set at $\alpha_1 = 0.5^\circ$, $\alpha_2 = 4.0^\circ$, and $\alpha_3 = 4.0^\circ$. Also, their contact pressures upon the conveying roller 10b are set at 400 g, 400 g, and 300 g, respectively. As described hereinbefore, the driving force is transmitted to the conveying roller



-103-

10b, by way of the clutch 32, from the conveying gear 10b1 meshed with the conveyance drive gear 13f of the gear unit 13.

With this arrangement, while the recording medium P is conveyed by the conveying roller 10b, one of the lateral sides of the recording medium P is pressed against the conveying guide referential surface 31 provided on the frame 15. In other words, the recording medium P is conveyed using the so-called single conveyance reference. The conveying guide referential surface 31 is provided on the internal surface of the left lateral wall of the frame 15, on which the gear unit 13 is mounted.

The process cartridge B positioning reference will be described. As described previously, when the process cartridge B is installed, it is inserted with its cylindrical projections 7c1 and 7c2 being guided by the first guide portions 7a provided on the frame 15, and as it is further inserted, these projections 7c1 and 7c2 drop into the groove portion 7a1, completing the installation process. One of the first guide portions 7a located on the internal surface of the left lateral wall of the frame 15 is provided with the cartridge positioning referential surface 33 which projects inward adjacent to the groove portion 7a1. Having one of the first guide portions 7a1 project inward adjacent to the groove portion 7a1, the process



cartridge B is unlikely to rattle in the lateral direction.

The photosensitive drum 2 within the process cartridge B is rotated as the driving force is transmitted to the drum gear 2a meshed with the gear 13c2 of the gear unit 13. Since the gear 13c2 and drum gear 2a are helical gears, their rotation generates thrust which pressures the photosensitive drum 2 toward the cartridge installation referential surface 33. More specifically, the drum gear 2a is provided with a right helix angle of approximately 14.6°; therefore, when the driving force is transmitted to the photosensitive drum 2, the entire process cartridge B is pressured toward the left side of the apparatus in the thrust direction of the photosensitive drum 2, whereby the left surface of the frame 1 is placed in contact with the cartridge installation referential surface 33. Normally, while coming in contact with the referential surface 33, the process cartridge B shifts approximately 1 mm - 3 mm in the thrust direction, within the range of the play allowed for the installation.

Therefore, as the left surface of the frame 1 comes in contact with the cartridge installation referential surface 33 during the image forming operation, the photosensitive drum 2, which has been positionally fixed in the front and rear direction



-105-

when the cylindrical projections 7c1 and 7c2 dropped into the groove portion 7a1, comes in contact with this frame 1, with the left surface (more precisely, the drum gear 2a mounted on the left end of the
5 photosensitive drum 2), whereby the photosensitive drum 2 is positionally fixed in the lateral direction also. With this arrangement in place, the position of the photosensitive drum 2 of this embodiment is always fixed at the same spot.

10 Further, since the cartridge installation referential surface 33 is provided on the frame 15, on the same side, the left side, where the gear unit 13 for transmitting the driving force to the drum gear 2a is provided, the distance between the drum gear 2a and
15 referential surface 33 is small compared to an arrangement in which the gear unit 13 is disposed, for example, on the left side wall of the frame 15; therefore, even when the helical drum gear 2a is slightly shifted toward the referential surface 33,
20 the amount of shift is smaller. As a result, the accuracy in distances among the components and assembly accuracy can be improved.

The optical image scanning start reference will be described. When the optical image is
25 projected on the surface of the photosensitive drum 2 from the optical system 8, this optical image is scanned side to side in the longitudinal direction of



-106-

the photosensitive drum 2, by the rotation of the polygon mirror 8b. In this embodiment, this scanning action is started at the left side relative to the longitudinal direction of the photosensitive drum 2.

5 More specifically, referring to Figure 51, a scanning starting reference point X1 is provided at one end of the optical image scanning range G (image forming range), on the same side as the side where the
10 aforementioned conveyance referential surface 31 and cartridge positioning referential surface 33 are disposed, that is, on the side where the gear unit 13 is disposed, and the scanning is started at the scanning start referential point X1 and is carried out toward X2.

15 At this time, referring to Figure 52, the scanning structure will be described. The most important portion of the scanner unit 8e is the polygonal mirror 8b, which is mounted on the rotational axle of the scanner motor 8c and is rotated
20 as the scanner motor 8e rotates. The rotational velocity of the scanner motor 8c is controlled by the scanner driver 8k, so that the laser beam reflected by the polygon mirror 8b scans the surface of the photosensitive drum 2 at a constant speed, starting
25 from the side where the gear unit 13 is disposed.

More specifically, when a scanner drive command (SCNON) is sent from the CPU 14a1 to the



scanner driver 8k, the scanner driver 8k sends a scanner motor rotation signal (SMC) to the scanner motor 8c to start the motor 8c. Also, the scanner driver 8k controls the voltage of the motor rotation
5 signal, so that the rotational velocity of the scanner motor 8c remains constant. At this time, the polygonal mirror 8b of this embodiment is rotated in the clockwise direction, whereby the laser beam sequentially scans the surface of the photosensitive
10 drum 2 in the thrust direction from the side where the gear unit 13 is disposed, that is, from X1 to X2 in Figure 51, at a constant speed.

Since the referential surface for recording medium P conveyance, the reference surface for fixing
15 positionally in the thrust direction the process cartridge B which forms the toner image and transfers it onto the recording medium P, and the reference point at which the laser beam scanning is started for forming the latent image on the photosensitive drum 2
20 of the process cartridge B are all provided on the same side of the apparatus main assembly (that is, the side on which the gear unit 13 is disposed), an image shift or the like is unlikely to occur. As a result, high quality images can be produced.

25 [Alternative Embodiments]

Next, an alternative embodiment of each of the components of the aforementioned image forming



apparatus and process cartridge will be described.

{Cartridge Installing Means}

(Process Cartridge Installation Guide)

The first embodiment exemplifies the case in
5 which the first guide portion 7a and second guide
portions 7b are provided on the frame 15 of the
apparatus main assembly 6, as shown in Figure 6, for
guiding the process cartridge B during the
installation, wherein the second guide portion 7b is
10 continuous. However, this second guide portion 7b may
have a structure as shown in Figure 53, in which the
second guide portion 7b is disposed across the bearing
portion of the transferring roller 11. At this time,
the structure shown in Figure 53 will be concretely
15 described, wherein the components having the same
functions as those in the first embodiment will be
designated by the same symbols.

A shaft 34a of the transferring roller 11 is
supported by the bearing 34b, and a single piece
20 transfer gear 34c comprising a flange portion 34c1 and
a gear portion 34c is attached to one end of the shaft
34a. The roller shaft 34a extends across the second
guide portion 7b, rendering the second guide portion
7b discontinuous at the locations of the flange
25 portion 34c1 and roller shaft 34a.

In the case of this structure, when the
process cartridge B is inserted in such a manner as



for the second engagement portion 7e of the process cartridge B to be guided by the second guide portion 7b, the second engagement portion 7e comes to be guided by the flange portion 34c and roller shaft 11c, 5 at the locations where the second guide portion 7b is discontinuous. While riding over the roller shaft 11c, the second engagement portion 7e presses down the roller shaft 11c. Therefore, when the process cartridge B is installed, the transferring roller 11 10 escapes downward. As a result, the collision between the cartridge frame 1 and transferring roller 11 which occurs during the cartridge installation can be surely prevented even without strict control over the vertical distance between the second guide portion 7b 15 and transferring roller 11, or the like.

In addition to this structural arrangement in which the flange portion 34c1 and shaft 34a of the transferring roller 11 are pressed down by the second engagement portion 7e of the process cartridge B, 20 another alternative structure may be employed in which the second engagement portion 7e presses down the bearing 34b. In such a case, a bearing 34d shaped to cover the entire circumference of the roller shaft 34a as shown in Figure 54 affords a better operational 25 efficiency during the cartridge installation than the U-shaped bearing 34b as shown in Figure 53, since the former does not hang up with the second engagement



portion 7e.

Further, the first embodiment exemplifies an arrangement in which the second guide portion 7b is disposed in the apparatus inward of the first guide portion 7a, and also, is extended rearward beyond the transferring roller 11, as shown in Figure 6. However, a structure as shown in Figures 55 and 56 may be employed. In this structure, one of the second guide portions 7b described in connection with the first embodiment (second guide portion 7b on the left in Figure 55) is shortened, extending as far as only the front side of the flange portion 34c1 of the transferring roller 11, and instead, an auxiliary guide portion 35 is provided above the other second guide portion 7b on the right side. This auxiliary guide portion 35 guides the top end of the first engagement portion 7d as shown in Figure 56 during the process cartridge installation.

At the initial stage of the process cartridge B insertion being guided by such a guide, the first engagement portion 7d is guided by the first guide portion 7a, and the second engagement portion 7e is guided by the second guide portion 7b. However, after the second engagement portion 7e has reached beyond the transferring roller 11, the second engagement portion 7e on the left side loses contact with the shorter second guide portion 7e, sticking out in the



-111-

air; therefore, the cartridge B comes to be supported at three points: both left and right first engagement portions 7d and the second engagement portion on the right side. Therefore, without the auxiliary guide
5 portion 35, the cartridge B is allowed to rotate about a line U connecting the first engagement portion 7d on the left side and the second engagement portion 7e on the right side, as shown in Figure 55.

With the provision of the auxiliary guide 35,
10 the top end of the first engagement portion 7d on the right comes in contact with the auxiliary guide portion 35 as shown in Figure 56, regulating thereby the rotational movement of the cartridge B. Therefore, the cartridge B does not collide with the
15 transferring roller 11 or the like during the cartridge installation.

The embodiment illustrated in Figure 55 exemplifies a case in which the auxiliary guide portion 35 is provided on the internal surface of the
20 right side wall and the second guide portion 7b on the left is shortened, but the auxiliary guide portion 35 may be provided on the left side, or on both sides. Further, the second guide portion 7b on the right may be shortened.

25 In the first embodiment, the guide member 11b for guiding the recording medium P to the transferring roller 11 is positionally fixed (Figure 1), but an




alternative structure may be employed in which the guide member 11b is allowed to move vertically along with the transferring roller 11. With such an arrangement, when the transferring roller 11 escapes downward during the process cassette B installation, the guide member 11b also escapes downward; therefore, the collision which occurs between the cartridge frame 1 and guide member 11b can be surely prevented without a need for strict control over the vertical distance between the second guide portion 7b and guide member 11b, or the like.

Further, a discharging needle as a discharging member for discharging the recording medium P after the toner transfer is provided adjacent to the transferring roller 11, and this discharging needle may be mounted as shown in Figure 59 so that it is moved along with the transferring roller 11 in the same manner as described in the foregoing. In this case, the same effects as described in the foregoing are obtained.

(Pressure Generation by Drum Shutter)

In the first embodiment, the drum shutter 17a is designed to be automatically opened as the process cartridge B is installed, and to be automatically closed by the torsional coil spring 17d as the cartridge B is pulled out. Therefore, when the process cartridge B is in the image forming apparatus,



the drum shutter 17a is pressured in the closing direction by the spring 17d, whereby the process cartridge B is pressured in the direction in which the process cartridge B is to be lifted out of the frame
5 15, which is one of the advantages of such a design. However, when the pressure from the torsional spring 17d is too strong, the process cartridge B becomes positionally instable. Therefore, a locking mechanism may be provided for locking the drum shutter 17a when
10 the drum shutter 17a is opened.

As for the locking mechanism, referring to Figure 60, a lever 37b pressured by a compression spring 37a is provided at a predetermined location of the process cartridge B, wherein this lever 37b
15 engages into an engagement hole 37c provided on the drum shutter 17a when the shutter mechanism opens all the way. By this arrangement, the drum shutter 17a is locked in the open state; therefore, the pressure from the torsional coil spring 17d is prevented from
20 working to lift the process cartridge B.

The locked shutter mechanism is released by an eject button 38 shown in Figure 60. More specifically, the apparatus main assembly 6 is provided with the eject button 38, which is pressured
25 by a compression spring 38c in the direction to stick out of the apparatus main assembly. As this ejection button 38 is pressed, a pressing projection 38a



-114-

located at the end of the button pushes in the lever 37b, whereby the lever 37b is disengaged from the engagement hole 37c, releasing thereby the shutter mechanism from the locked state.

5 The eject button 38 is provided with an engagement claw 38b. When the top lid 16b is closed, this engagement claw 38b engages with the engagement hook 39 provided on the top lid 16b, locking thereby the top lid 16b in the closed state. On the other
10 hand, when the eject button 38 is pressed, the engagement is broken and the top lid 16b is opened by the pressure from the torsional coil spring provided at the rotational center of the top lid 16b. In other words, as the ejection button 38 is pressed, the top
15 lid 16b is automatically opened, and at the same time, the process cartridge B is lifted, as if floating out of the frame 15, by the pressure from the spring 17d, which makes it easier to take out the process cartridge B.

20 Referring to Figures 61 - 65, the pressure which is provided by the drum shutter in the first embodiment can be provided by an alternative structure, which is totally different from that in the first embodiment. Hereinafter, the structure of the
25 alternative structure shown in Figures 61 - 65 will be described.

In this embodiment, a process cartridge 40



-115-

shown in Figure 61 is installed in the image forming apparatus 41 by inserting it through an inserting window 42 provided in front of the apparatus. The process cartridge 40 and image forming apparatus 41
5 have the same functions as those of the first embodiment, and the process cartridge 40 comprises a cartridge main assembly 40a and a case 40b which functions as the shutter mechanism.

The cartridge inserting window 42 is blocked
10 with a thin plate 44 imparted with the pressure from a spring 43 in the closing direction, and this thin plate 44 is pushed open by the process cartridge 40 to be inserted. The process cartridge 40 is inserted until its flange portion 40c becomes substantially
15 level with the front surface of the image forming apparatus main assembly, as shown in Figure 63. As the cartridge main assembly 40a is pushed in further, the case 40b remains where it is. As a result, a forward portion of the cartridge main assembly 40a is
20 projected out of the process cartridge 40. Then, the projected cartridge main assembly 40a is detected by an unshown sensor, and a gear 44 engaged with an unshown motor begins to rotate.

The gear 44 engages with a rack 40a1 provided
25 on the top surface of the cartridge main assembly 40a, and the cartridge main assembly 40a is pulled out further from the case 40b by the rotation of the gear



44. At this time, an axle 45 that is the extension of the axle of the photosensitive drum contained in this cartridge main assembly engages into a guide groove 46 provided within the image forming apparatus 41, being
5 thereby guided forward by this guide groove 46.

Referring to Figure 64, a contact 47 for making an electrical contact is provided at the rear (left side in Figure 64) of the cartridge main assembly 40a. As the cartridge main assembly 40a is further pulled out,
10 the contact 47 comes in contact with a contact pin 49 which is provided on the image forming apparatus 41 side and is under downward pressure from a spring 48. At this time, the cartridge main assembly 40a is subjected to the downward pressure from the contact
15 pin 49, and as a result, the rear portion of the cartridge main assembly 40a slightly drops down along the guide groove 46.

Also, as the cartridge main assembly 40a is inserted, a shaft 50 provided on the image forming
20 apparatus 41 side is projected into a hole 40b1 of the case 40b. This shaft 50 is pressured by a compression spring 52, by way of a lever 51, in the direction to be projected into the hole 40b1, wherein the lever 51 is exposed outward the image forming apparatus 41.
25 When the cartridge main assembly 40a is further pulled out to a predetermined point, the shaft 51 drops into a concave 40a2 provided on the side surface of the



-117-

cartridge main assembly 40a, whereby the cartridge
main assembly 40a is locked at this location against
the pressure of a tension spring 40d working to pull
the cartridge main assembly 40a back into the case
5 40b. In other words, in this locked state, the force
of the tension spring 40d is prevented from working to
move the cartridge main assembly 40a out of the normal
position; therefore, the process cartridge 40 is
positionally stabilized in the image forming apparatus
10 41.

The lever 51 is pivotable about an axis 51a,
and when a force is exerted in the direction of an
arrow in Figure 65, the shaft 51 is pushed out of the
concave 40a2 by the pressure from the tension spring
15 40d, and the cartridge main assembly 40a is pulled
back into the case 40b. During this pull-back, since
the gear 44 and rack 40a1 remain engaged, the gear 44
serves as a damper to prevent the cartridge main
assembly 40a from being snappingly pulled back into
20 the case 40b.

After the cartridge main assembly 40a has
been pulled back into the case 40b, the cartridge main
assembly 40a protrudes a predetermined amount from the
image forming apparatus 41 as shown in Figure 63,
25 making it easy to pull it out.

As described in the foregoing, the provision
of the tension spring 40d with an adequate force for



-118-

pulling back the cartridge main assembly 40a into the case 40b, as well as the provision of the locking mechanism make it extremely easy to take out the cartridge 40.

5 Further, with this arrangement in place, the installation related status of the cartridge 40 can be monitored by observing the condition of the lever 51. More specifically, referring to Figure 66, when the process cartridge 40 is not in the image forming
10 apparatus 41, the lever 51 looks as shown in Figure 66(a); when the process cartridge 40 has been properly installed and the shaft 51 has dropped into the concave 40a2, it looks as shown in Figure 66(b); and when the cartridge 40 has been improperly installed in
15 the image forming apparatus 41, it looks as shown in Figure 66(c). Therefore, the installation related status of the cartridge can be determined just by observing externally the position of the lever 51.

{Electrical Component Unit}

20 Next, alternative embodiments for the electrical component mounting board will be described. Referring to Figure 32, the first embodiment exemplifies a case in which the AC input portion 14a1 and high voltage source portion 14a3 are disposed on
25 the non-driven side, and the DC power source 14a2 and control circuit portion 14a7 are disposed on the driven side, but in the some image forming



apparatuses, for example, in an image forming apparatus which does not require the process cartridge B, it is unnecessary to limit the internal component arrangement to those described hereinbefore.

5 For example, referring to Figure 67, when a 12 V DC and a 5 V DC are used as the DC power source, the high voltage source 53a, DC source 53b, control circuit portion 53c, and AC input portion 53d may be disposed in this order from the upstream side relative
10 to the recording medium P conveying direction.

 The reason for this arrangement is as follows. The charge bias and development bias for forming the toner image on the photosensitive drum, and the transfer bias, which are applied during the
15 image forming operation, must have a high voltage, and these image forming members are likely to be disposed on the upstream side relative to the recording medium P conveying direction in many cases. Therefore, having the high voltage source 53a disposed adjacent
20 to these members eliminates a need for a long wiring, effectively preventing leakage.

 The purpose of disposing the DC power source 53b substantially in the middle of the electrical component mounting board 53 is for using short wiring
25 to supply the electrical power from this DC power source 53b to the main motor which drives the photosensitive drum or the like. More specifically,



the driving force is transmitted from the main motor to the photosensitive drum, conveying roller, fixing roller, or the like, which are disposed at appropriate locations on both upstream and downstream sides of the main motor; therefore, when the main motor is disposed substantially in the middle of the apparatus, the gear train is divided into two sub-trains, one on each side, preventing thereby excessive load concentration which occurs on specific gears on the upstream side in the different type apparatuses without the gear train division. This dissipation of the load is advantageous not only from the standpoint of gear damage prevention, but also from the standpoint of maintenance of the strength of the frame on which the gear train is mounted. Further, since the gears are arranged so as for the main motor to be disposed in the middle of the gear train, a higher latitude is allowed for the gear train arrangement in the front and rear direction of the apparatus, which in turn facilitates the downsizing of the apparatus. Further, the central portion of the apparatus has mechanically higher strength; therefore, it is preferable to place the main motor substantially in the center of the apparatus, which in turn renders it preferable for the DC power source 53b, which supplies the power to the main motor disposed substantially in the middle, to be disposed substantially in the middle of the electrical



component mounting board 53.

In order for the power to be supplied from the AC input portion 53d to the heater of the fixing device, the AC input portion 53d is preferred to be
5 disposed adjacent to the fixing device disposed at the rear portion of the apparatus. Also, in order to prevent the noises or the like, the image signal or the like is preferred to be inputted from the side opposite to the AC input portion 53d; therefore, the
10 control circuit portion 53c for inputting the image signal or the like is preferred to be disposed on the side opposite to the AC input portion 53d.

The electrical component mounting board 53 can be used with either an apparatus in which the
15 recording medium P is horizontally conveyed by the conveying roller pair 54a and 54b as shown in Figure 68(a), or an apparatus in which the recording medium P is conveyed upward from below by the conveying roller pair 54a and 54b as shown in Figure 68(b).

20 While the first embodiment contains two boards, the electrical component mounting board 14 and image processing circuit board 22, this image processing circuit board is to be exchanged so that it matches the host computer, and conceptually speaking,
25 it belongs to the control circuit portion within the electrical component mounting board.

(Cooling Fan)



-122-

Next, alternative embodiments of the cooling fan will be described. The first embodiment exemplifies a case in which the fan cover 19b and filter 19c are composed of different materials as shown in Figure 41, but it may be structured as shown in Figures 69 and 70. In Figures 69 and 70, the components having the same function as those in the first embodiment are designated by the same symbols.

First, referring to Figure 69, the cooling fan 19 and filter 19c are integrally molded of resin material with excellent fluidity. With this molding arrangement, one of the steps in the first embodiment, that is, the step in which the filter 19c is attached to the fan cover 19b, can be eliminated, and also, the component count is reduced. Therefore, the manufacturing cost can be decreased.

In the case of the cooling fan 19 illustrated in Figure 70, the fan cover 19b and filter 19c are integrally molded of resin, and their surfaces are plated (for example, aluminum, nickel, or the like) to create integrally the shield plate 19c. Such a design can further reduce the number of assembly steps and the component count.

The fan cover 19b and filter 19c may be integrally molded of electrically conductive flexible resin or may be formed of springy metal (spring steel or the like) by drawing, so that the fan cover itself,



being integral with the filter, can be imparted with the shielding effects. This gives the same effects as those described in the forgoing.

{Miscellaneous}

5 The process cartridge described hereinbefore refers to a process cartridge comprising an electrophotographic photosensitive member or the like as the image bearing member and at least one processing means. However, many other cartridge
10 designs are possible beside those of the embodiments described hereinbefore. For example, the process cartridge is available in the form of an exchangeable process cartridge in which: an image bearing member and a charging means are integrally assembled; an
15 image bearing member and a developing means are integrally assembled; or an image bearing member and a cleaning means are integrally assembled. Further, the process cartridge is also available in the form of an exchangeable process cartridge in which an image
20 bearing member and two or more processing means are integrally assembled.

 In other words, the process cartridge described hereinbefore refers to an exchangeable process cartridge for an image forming apparatus,
25 comprising a charging means, developing means, and cleaning means, which are integrally assembled with an electrophotographic photosensitive member, in the form

of a cartridge; comprising at least one of a charging means, developing means, and cleaning means, which are integrally assembled with an electrophotographic photosensitive member, in the form of a cartridge; or
5 comprising at least a developing means, which is integrally assembled with an electrophotographic photosensitive member, in the form of a cartridge.

During the descriptions of the embodiments of the present invention, a laser beam printer is
10 selected as an example of the image forming apparatus, but the present invention does not need to be limited by this choice. It is needless to say that the present invention is applicable to many other image forming apparatuses such as an electrophotographic
15 copying machine, facsimile apparatus, LED printer, word processor, or the like.

This Sheet Has Been Replaced



20

25




According to the embodiments described above,
a latent image formation starting position to form a
latent image by application of light to said image
bearing member, a position where the toner image is
5 formed by development of the latent image, and a sheet
feed reference position for a recording sheet onto
which the toner image is to be transferred, are at the
same side, and therefore, the latent image formation,
the toner image formation and the image transfer can
10 be carried out with deviation, and therefore, high
quality images can be provided.

By providing a gear train for transmitting
the driving force to the image bearing member or the
like, are provided at the same side as the reference,
15 and therefore, the distance between the reference and
the gear is shortened. For this reason, when the drum
gear comprising the helical gear is displaced to the
reference surface side, the error can be reduced.

As described in the foregoing, according to
20 this invention, an image forming apparatus with which
the image quality is improved, can be provided.

While the invention has been described with
reference to the structures disclosed herein, it is
not confined to the details set forth and this
25 application is intended to cover such modifications or
changes as may come within the purposes of the
improvements or the scope of the following claims.



WHAT IS CLAIMED IS:

1. An image forming apparatus for forming an image on a recording material, to which a process cartridge is detachably mountable, said image forming
5 apparatus comprising:
 mounting means for mounting a process cartridge having an image bearing member comprising a helical gear, and process means actable on said image bearing member;
10 feeding means for feeding the recording material;
 projection means for projecting image information light onto said image bearing member in a direction from a projection reference disposed at one
15 side of an axis of said image bearing member to the other side;
 a positioning reference for positioning said image bearing member in its axial direction;
 feed guide reference for guiding the
20 recording material fed by said feeding means; and
 wherein said positioning reference, said feed guide reference and said projection reference are disposed in a same side of a main assembly of said image forming apparatus.
25
2. An apparatus according to Claim 1, wherein said image bearing member is rotated by a driving





force from a motor of the main assembly, transmitted to a helical gear of said image bearing member.

3. An apparatus according to Claim 1, wherein
5 said projecting means sequentially emits a laser beam in accordance with image information toward the axis of said image bearing member from said projection reference.

10 4. An apparatus according to Claim 1, wherein the recording material is fed along said feed guide reference by a slanted feeding roller.

5. An apparatus according to any one of Claims
15 1 - 4, further comprising first drive transmission means for transmitting driving force to said image bearing member, and second drive transmission means for transmitting a driving force to said feeding means, wherein said first and second transmission
20 means are also disposed in the same side as said positioning reference, feed guide reference and the projection reference.

6. An apparatus according to Claim 2, wherein
25 said first and second transmission means are in the form of a gear train for transmitting a driving force from a motor.





7. An apparatus according to Claim 5, wherein said first and second transmission means transmit the driving force from one and the same motor.

5 8. An apparatus according to Claim 1, wherein said image forming apparatus is a laser beam printer.

9. An apparatus according to Claim 1, further comprising mounting means for mounting a process
10 cartridge integrally containing charging means, developing means or cleaning means, as said process means, and an electrophotographic photosensitive member as said image bearing member.

15 10. An apparatus according to Claim 1, further comprising mounting means for mounting a process cartridge integrally having at least one of charging means, developing means and cleaning means as process means, and an electrophotographic photosensitive
20 member as said image bearing member.

11. An apparatus according to Claim 1, further comprising mounting means for mounting a process cartridge integrally having at least one of developing
25 means as process means and an electrophotographic photosensitive member as said image bearing member.



12. Image forming apparatus to which a process cartridge having a photosensitive member, can be detachably mounted and wherein reference means for guiding recording material on which an image is to be reproduced, and
5 reference means for positioning the photosensitive member of the process cartridge when mounted in the apparatus the two reference means being located on the same side of the apparatus.

10 13. Image forming apparatus substantially as hereinbefore described with reference to any one of the figures of the accompanying drawings.



This Sheet Has Been Replaced

