

DEVICES, SYSTEMS AND METHODS FOR REFUELING AIR VEHICLES

TECHNOLOGICAL FIELD

The presently disclosed subject matter relates to systems and methods for refueling air vehicles, especially aircraft, in particular for refueling aircraft during flight.

5 BACKGROUND

Airborne refueling (also referred to interchangeably herein as air refueling, in-flight refueling, air to air refueling (AAR), aerial refueling, tanking, and the like) refers to the process of transferring fuel from a tanker aircraft to a receiver aircraft during flight.

10 Two types of airborne refueling systems are currently in use for refueling airborne military aircraft:

- the so-called “hose and drogue” system, used by the US Navy and many non-US air forces;
- the so-called “boom and receptacle” or “flying boom” system, used by the
15 US Air Force, and also used by Israel, Turkey and the Netherlands.

In the hose and drogue system, the refueling aircraft is provided with one or more non-rigid refueling lines, at the end of each of which there is a drogue which functions as a stabilizer and includes a receptacle, while the receiver aircraft is fitted with a probe that is configured for engaging with the receptacle. In use, the drogue is
20 not actively controlled, but rather aligns itself freely in the airflow aft of the tanker. The pilot of the receiver aircraft controls the flight path thereof to ensure engaging contact between the probe and the receptacle. Thereafter, the receiver aircraft is refueled via the refueling line and probe.

In the boom and receptacle system, the tanker includes a so-called “flying
25 boom”, which is a rigid tube that telescopes outwardly and is gimbaled to the rear of the tanker aircraft, and is otherwise retracted into the tanker fuselage when not in use. The

- 2 -

boom carries a fuel line and comprises a fuel transfer nozzle at the end thereof, and the boom is equipped with adjustable flight control surfaces. Once the tanker and receiver aircraft are in close proximity and flying in formation, with the receiver aircraft at a position behind the tanker within an air refueling envelope (i.e., safe limits of travel for the boom with respect to the receiver aircraft and within which contact between the receiving aircraft and the boom is safe), a dedicated operator in the tanker controls the position of the boom via the control surfaces, and inserts the end of the boom including the nozzle into a receptacle provided on an upper part of the receiving aircraft, ensuring proper mating between the nozzle and receptacle, after which fuel transfer can begin.

During refueling, and while the boom is engaged with the receptacle, the pilot of the receiver aircraft must continue to fly within the air refueling envelope, and if the receiver aircraft approaches these limits the operator in the tanker requires the receiver aircraft pilot to correct the position thereof, and if necessary the boom is disconnected to prevent accidents. All current tankers of this type carry a single boom and can refuel a single receiver aircraft of this type at a time.

In addition, there are some tankers that comprise a flying boom system and at least one hose and drogue system as well, and are commonly known as Multi-Point Refueling Systems (MPRS). In some cases a hose and drogue system is provided at the aircraft tail, and thus only this system or the flying boom system may be used at any one time. In other cases, two under-wing hose and drogue pods, known as Wing Air Refueling Pods (WARPs), can be provided, one under each wing, in addition to the flying boom system.

US 7,562,847 discloses an autonomous in-flight refueling hose end unit including a first end configured to be coupled to a fuel hose of a tanker aircraft. and a second end configured to be coupled to receiver aircraft and adjustable control surfaces, and a flight control computer autonomously controls the control surfaces to fly the refueling hose end into contact with the receiver aircraft.

In GB 2,237,251 an in flight refueling apparatus mountable on a tanker aircraft has a probe receptor coupled with a fuel line and is arranged to be deployed outboard of the aircraft, and can be provided on a drogue or a boom. In one mode, the apparatus is arranged to provide a parameter which is representative of the deviation of the path of the receptor from a predetermined initial path for actuating control means for changing

- 3 -

automatically the position of the receptor relative to the initial path. In another mode, a parameter which is representative of the relative angular position of the receptor with respect to the probe of an approaching refueling aircraft for actuating control means for changing automatically the relative angular position to achieve alignment of receptor
5 and probe.

Additional references considered to be relevant as background to the presently disclosed subject matter are listed below: US 2007/108339, US 2007/084968, US 2006/065785, US 2006/043241, US 2006/060710, US 2006/060709, US 2005/224657, US 2004/102876, US 7,097,139, US 6,966,525, US 6,994,294, US 6,644,594, US
10 5,906,336, US 5,785,276, US 5,499,784, US 5,326,052, US 4,282,909, US 4,126,162, US 4,072,283, US 3,948,626, US 3,091,419, US 3,059,895, US 2,954,190, US 2,582,609, USD 439,876, DE 100 13 751.

Acknowledgement of the above references herein is not to be inferred as meaning that these are in any way relevant to the patentability of the presently disclosed
15 subject matter

GENERAL DESCRIPTION

In accordance with an aspect of the presently disclosed subject matter, there is provided a variety of refueling devices, systems and methods for use in in-flight
20 refueling. In at least one example one such device is towed by a tanker aircraft via a fuel hose at least during in-flight refueling, and has a boom member with a boom axis. The boom member enables fuel to be transferred from the fuel hose to a receiver aircraft along the boom axis during in-flight refueling. The device maintains a desired non-zero angular disposition between the boom axis and a forward direction at least when the
25 refueling device is towed by the tanker aircraft in the forward direction via the fuel hose.

In accordance with an aspect of the presently disclosed subject matter, there is provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising automatically steering a refueling device to an engagement
30 enabling position, including:

- 4 -

- 5 (i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
- (ii) repeatedly calculating steering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- 10 (iii) sending the steering commands to the spatial control system;

whereby at the engagement enabling position, the boom member of the refueling device is capable of engaging with the fuel receptacle to enable refueling of the receiver aircraft.

The method can optionally further comprise one or more of the features (c1) to 15 (c15), in any desired combination or permutation:

- (c1) providing an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory for automatically engaging with the fuel receptacle.
- 20 (c2) wherein the boom member has a boom axis and wherein at least a final part of the predetermined trajectory is parallel to the boom axis.
- (c3) determining an engagement area specification condition; repeatedly calculating maneuvering instructions for the receiver aircraft based on the spatial dispositions and an engagement area specification; and invoking the automatic steering 25 in response to meeting the engagement area specification condition.
- (c4) wherein the refueling device is connected to a tanker aircraft by a fuel hose, and further comprising providing the maneuvering instructions to at least one of a pilot of the receiver aircraft pilot or a pilot of the tanker aircraft.
- (c5) wherein providing the maneuvering instructions comprises activating a 30 signaling system, optionally mounted on the refueling device or the tanker aircraft.

- 5 -

(c6) activating a force generating arrangement in the refueling device for generating force in the direction of the fuel receptacle of the receiver aircraft in response to receiving an engagement command for enabling refueling.

(c7) wherein the determining a spatial disposition comprises acquiring an image
5 of said receiver aircraft, comparing the image with a reference image depicting a desired spatial disposition of the refueling device with respect to a receiver aircraft, and determining, based on the comparing, the spatial disposition of the refueling device with respect to the receiver aircraft.

(c8) wherein the spatial control system characteristics are related to operation
10 parameters of aero-dynamic control surfaces of the refueling device.

(c9) wherein the aero-dynamic control surfaces are one or more vanes.

(c10) wherein the spatial control system characteristics are related to operation parameters of reaction control thrusters associated with the refueling device and capable of steering the refueling device.

(c11) wherein the engagement area specification condition is a spatial
15 disposition within a pre-determined volume with respect to the refueling device and wherein the pre-determined volume is optionally substantially in the shape of a cube or substantially in the shape of a sphere.

(c12) wherein the calculating steering commands comprises obtaining data of an
20 initial trail position of the refueling device and wherein the steering commands are based also on the data of an initial trail position.

(c13) wherein the data of an initial trail position includes at least one of a pitch angle of the refueling device, a yaw angle of the refueling device, and a deployment length of a fuel hose connecting the refueling device to the tanker aircraft.

(c14) wherein the automatic steering and the automatic engaging are performed
25 autonomously by the refueling device.

(c15) wherein said refueling device is non-aircraft-fixed.

In accordance with an aspect of the presently disclosed subject matter, there is
30 yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

(a) automatically steering a refueling device to an engagement enabling position, including:

- 6 -

- 5 (i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
- (ii) repeatedly calculating steering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- 10 (iii) sending the steering commands to the spatial control system;
- (b) providing an instruction to the refueling device, when it arrives at the engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory for automatically engaging with the fuel receptacle.

15 The method can optionally further comprise one or more of the features (c2) and/or (c4) to (c15) detailed hereinabove and/or one or more of the features (d1) to (d2), in any desired combination or permutation:

(d1) invoking the automatic steering in response to a spatial disposition between the refueling device and the receiver aircraft meeting an engagement area specification condition.

20

(d2) repeatedly calculating maneuvering instructions for the receiver aircraft based on spatial dispositions and an engagement area specification, for establishing the spatial disposition between the refueling device and the receiver aircraft that meets the engagement area specification condition.

25

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising :

(a) repeatedly calculating maneuvering instructions for the receiver aircraft based on spatial dispositions of the receiver aircraft and an engagement area specification until an engagement area specification condition is met;

30

- 7 -

(b) in response to meeting the engagement area specification condition, automatically steering a refueling device to an engagement enabling position, including:

5 (i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the refueling device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

10 (ii) repeatedly calculating steering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

(iii) sending the steering commands to the spatial control system;

15 (c) providing an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory for automatically engaging with the fuel receptacle.

The method can optionally further comprise one or more of the features (c2) and/or (c4) to (c15) detailed hereinabove, in any desired combination or permutation.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising a steering control module configured to automatically steer a refueling device to an engagement enabling position, including:

25 (i) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

30

- 8 -

- (ii) repeatedly calculate steering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- (iii) send the steering commands to the spatial control system for automatically steering the refueling device to the engagement enabling position;

whereby at the engagement enabling position, the boom member of the refueling device is capable of engaging with the fuel receptacle to enable refueling of the receiver aircraft.

The system can optionally further comprise one or more of the features (c2) and/or (c8) to (c11) and/or (c13) and/or (c15) detailed hereinabove and/or one or more of the features (e1) to (e10), in any desired combination or permutation:

(e1) an engagement/disengagement module configured to provide an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory to automatically engage with the fuel receptacle.

(e2) a maneuvering instructions module configured to determine an engagement area specification condition, to repeatedly calculate maneuvering instructions for the receiver aircraft based on the spatial dispositions and an engagement area specification, and to invoke the steering control module to automatically steer the refueling device to the engagement enabling position in response to meeting the engagement area specification condition.

(e3) wherein the refueling device is connected to a tanker aircraft by a fuel hose, and wherein the maneuvering instructions module is further configured to provide the maneuvering instructions to at least one of a pilot of the receiver aircraft pilot or a pilot of the tanker aircraft.

(e4) wherein the maneuvering instructions module is configured to activate a signaling system in order to provide the maneuvering instructions, the signaling system is optionally mounted on the refueling device or the tanker aircraft.

(e5) wherein the engagement/disengagement module is further configured to activate a force generating arrangement in the refueling device for generating force in

- 9 -

the direction of the fuel receptacle of the receiver aircraft in response to receiving an engagement command for enabling refueling.

(e6) wherein the steering control module is configured to perform the following steps in order to determine a spatial disposition: acquire an image of the receiver
5 aircraft; compare the image with a reference image depicting a desired spatial disposition of the refueling device with respect to a receiver aircraft; determine, based on the comparing, the spatial disposition of the refueling device with respect to the receiver aircraft.

(e7) wherein the steering control module is further configured to obtain data of
10 an initial trail position of the refueling device and wherein the calculate steering commands is based also on the obtained data of an initial trail position.

(e8) wherein at least the steering control module and the engagement/disengagement module are fitted within the refueling device for enabling autonomously controlling in-flight refueling of the receiver aircraft by the refueling
15 device.

(e9) wherein at least the steering control module and the engagement/disengagement module are fitted within the receiver aircraft.

(e10) wherein at least the steering control module and the engagement/disengagement module are fitted within the tanker aircraft.

20

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising a steering control module configured to automatically steer a refueling device to an engagement enabling position, including:

- 25 (i) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with
30 respect to the fuel receptacle of the receiver aircraft;
- (ii) repeatedly calculate steering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

- 10 -

- (iii) send the steering commands to the spatial control system for automatically steering the refueling device to the engagement enabling position;

the system further comprises an engagement/disengagement module configured to provide an instruction to the refueling device, when it arrives at the engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory to automatically engage with the fuel receptacle.

The system can optionally further comprise one or more of the features (c2) and/or (c7) to (c11) and/or (c13) and/or (c15) and/or (e3) to (e5) and/or (e7) to (e10) detailed hereinabove and/or one or more of the features (f1) to (f2), in any desired combination or permutation:

- (f1) a maneuvering instructions module configured to invoke the steering control module to automatically steer the refueling device to the engagement enabling position in response to meeting an engagement area specification condition.
- (f2) wherein the maneuvering instructions module is further configured to repeatedly calculate maneuvering instructions for the receiver aircraft based on spatial dispositions and an engagement area specification, for establishing the spatial disposition between the refueling device and the receiver aircraft that meets the engagement area specification condition.

20

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising a maneuvering instructions module configured to repeatedly calculate maneuvering instructions for the receiver aircraft based on spatial dispositions of the receiver aircraft and an engagement area specification until an engagement area specification condition is met, and in response to meeting the engagement area specification condition, activate a steering control module; the steering control module is configured to automatically steer a refueling device to an engagement enabling position, including:

- (i) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when

- 11 -

the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

- (ii) repeatedly calculate steering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- (iii) send the steering commands to the spatial control system for automatically steering the refueling device to the engagement enabling position;

the system further comprises an engagement/disengagement module configured to provide an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory to automatically engage with the fuel receptacle.

The system can optionally further comprise one or more of the features (c2) and/or (c7) to (c11) and/or (c13) and/or (c15) and/or (e3) to (e5) and/or (e7) to (e10) detailed hereinabove, in any desired combination or permutation.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

automatically maneuvering a refueling device to an engagement enabling position, including:

- (i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

- 12 -

(ii) repeatedly calculating maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

(iii) sending the maneuvering commands to the spatial control system;

5 whereby at the engagement enabling position, the boom member of the refueling device is capable of engaging with the fuel receptacle to enable refueling of the receiver aircraft.

The method can optionally further comprise one or more of the features (c1) and/or (c2) and/or (c5) and/or (c7) and/or (c9) and/or (c11) detailed hereinabove and/or
10 one or more of the features (g1) to (g12), in any desired combination or permutation:

(g1) wherein the refueling device is non-aircraft-fixed and wherein the maneuvering commands are steering commands for steering the refueling device in six degrees of freedom.

(g2) wherein the refueling device is aircraft fixed and wherein the maneuvering
15 commands are alignment commands for aligning the refueling device in three degrees of freedom.

(g3) determining an engagement area specification condition; repeatedly calculating maneuvering instructions for the receiver aircraft based on the spatial dispositions and an engagement area specification; and invoking the automatically
20 maneuvering in response to meeting the engagement area specification condition.

(g4) providing the maneuvering instructions to at least one of a pilot of the receiver aircraft or a pilot of a tanker aircraft.

(g5) wherein the refueling device is non-aircraft-fixed and wherein the method further comprising activating a force generating arrangement in the refueling device for
25 generating force in the direction of the fuel receptacle of the receiver aircraft in response to receiving an engagement command for enabling refueling.

(g6) wherein the determining a spatial disposition comprises: acquiring an image of the receiver aircraft, the image comprising depth data and electromagnetic data; comparing the depth data and the electromagnetic data with look-up tables comprising
30 reference depth data and reference electromagnetic data relating to reference spatial

- 13 -

dispositions with respect to the receiver aircraft; determining, based on the comparing, the spatial disposition of the refueling device with respect to the receiver aircraft.

(g7) wherein the image is acquired by a Light Detection And Ranging (LIDAR) unit.

5 (g8) wherein the refueling device is non-aircraft-fixed and wherein the spatial control system characteristics are related to operation parameters of aero-dynamic control surfaces of the refueling device.

(g9) wherein the refueling device is non-aircraft-fixed and wherein the spatial control system characteristics are related to operation parameters of reaction control
10 thrusters associated with the refueling device and capable of maneuvering the refueling device.

(g10) wherein the calculating maneuvering commands comprises obtaining data of an initial trail position of the refueling device and wherein the maneuvering commands are based also on the data of the initial trail position.

15 (g11) wherein the refueling device is non-aircraft-fixed and wherein the data of the initial trail position includes at least one of a pitch angle of the refueling device, a yaw angle of the refueling device, and a deployment length of a fuel hose.

(g12) wherein the automatically maneuvering and the automatically engaging are performed autonomously by the refueling device.

20

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

(a) automatically maneuvering a refueling device to an engagement enabling
25 position, including:

(i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling
30 position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

- 14 -

- (ii) repeatedly calculating maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
 - (iii) sending the maneuvering commands to the spatial control system;
- 5 (b) providing an instruction to the refueling device, when it arrives at the engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory for automatically engaging with the fuel receptacle.

The method can optionally further comprise one or more of the features (c2) and/or (c5) and/or (c7) and/or (c9) and/or (c11) and/or (g1) to (g12) detailed
10 hereinabove, in any desired combination or permutation.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising :

- 15 (a) repeatedly calculating maneuvering instructions for the receiver aircraft based on spatial dispositions of the receiver aircraft and an engagement area specification until an engagement area specification condition is met;
- (b) in response to meeting the engagement area specification condition, automatically maneuvering a refueling device to an engagement enabling
20 position, including:
- (i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the refueling device arrives to the engagement
25 enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
 - (ii) repeatedly calculating maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a
30 spatial control system of the refueling device;

- 15 -

(iii) sending the maneuvering commands to the spatial control system;

(c) providing an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory for automatically engaging with the fuel receptacle.

The method can optionally further comprise one or more of the features (c2) and/or (c5) and/or (c7) and/or (c9) and/or (c11) and/or (g1) and/or (g2) and/or (g4) to (g12) detailed hereinabove, in any desired combination or permutation.

10 In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

a steering control module configured to automatically maneuver a refueling device to an engagement enabling position, including:

- 15 (i) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with
20 respect to the fuel receptacle of the receiver aircraft;
- (ii) repeatedly calculate maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- (iii) send the maneuvering commands to the spatial control system for
25 automatically maneuvering the refueling device to the engagement enabling position;

whereby at the engagement enabling position, the boom member of the refueling device is capable of engaging with the fuel receptacle to enable refueling of the receiver aircraft.

30 The system can optionally further comprise one or more of the features (c2) and/or (c9) and/or (c11) and/or (e4) and/or (e6) and/or (e8) to (e10) and/or (g1) to (g2)

- 16 -

and/or (g7) and/or (g9) and/or (g11) detailed hereinabove and/or one or more of the features (h1) to (h7), in any desired combination or permutation:

(h1) an engagement/disengagement module configured to provide an instruction to the refueling device, in response to its arriving at the engagement enabling position,
5 causing the refueling device to move the boom member in a predetermined trajectory to automatically engage with the fuel receptacle.

(h2) wherein the boom member has a boom axis and wherein at least a final part of the predetermined trajectory is parallel to the boom axis.

(h3) a maneuvering instructions module configured to determine an engagement
10 area specification condition, to repeatedly calculate maneuvering instructions for the receiver aircraft based on the spatial dispositions and an engagement area specification, and to invoke the steering control module to automatically maneuver the refueling device to the engagement enabling position in response to meeting the engagement area specification condition.

15 (h4) wherein the maneuvering instructions module is further configured to provide the maneuvering instructions to at least one of a pilot of the receiver aircraft or a pilot of a tanker aircraft.

(h5) wherein the refueling device is non-aircraft-fixed and wherein the engagement/disengagement module is further configured to activate a force generating
20 arrangement in the refueling device for generating force in the direction of the fuel receptacle of the receiver aircraft in response to receiving an engagement command for enabling refueling.

(h6) wherein the steering control module is configured to perform the following steps in order to determine a spatial disposition: acquiring an image of the receiver
25 aircraft, the image comprising depth data and electromagnetic data; comparing the depth data and the electromagnetic data with look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft; determining, based on the comparing, the spatial disposition of the refueling device with respect to the receiver aircraft.

30 (h7) wherein the steering control module is further configured to obtain data of an initial trail position of the refueling device and wherein the calculate maneuvering commands is based also on the obtained data of the initial trail position.

- 17 -

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

5 a steering control module configured to automatically maneuver a refueling device to an engagement enabling position, including:

- 10 (i) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
- (ii) repeatedly calculate maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- 15 (iii) send the maneuvering commands to the spatial control system for automatically maneuvering the refueling device to the engagement enabling position;

the system further comprises an engagement/disengagement module configured to provide an instruction to the refueling device, when it arrives at the engagement enabling position, for causing the refueling device to move the boom member along
20 a predetermined trajectory to automatically engage with the fuel receptacle.

The system can optionally further comprise one or more of the features (c2) and/or (c9) and/or (c11) and/or (e4) and/or (e6) and/or (e8) to (e10) and/or (g1) to (g2) and/or (g7) and/or (g9) and/or (g11) and/or (h2) to (h7) detailed hereinabove, in any
25 desired combination or permutation.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

30 a maneuvering instructions module configured to repeatedly calculate maneuvering instructions for the receiver aircraft based on spatial dispositions of the

- 18 -

receiver aircraft and an engagement area specification until an engagement area specification condition is met, and in response to meeting the engagement area specification condition, activate a steering control module;

the steering control module is configured to automatically maneuver a refueling
5 device to an engagement enabling position, including:

- (i) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
10
- (ii) repeatedly calculate maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- (iii) send the maneuvering commands to the spatial control system for automatically maneuvering the refueling device to the engagement enabling position;
15

the system further comprises an engagement/disengagement module configured to provide an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory to automatically engage with the fuel receptacle.
20

The system can optionally further comprise one or more of the features (c2) and/or (c9) and/or (c11) and/or (e4) and/or (e6) and/or (e8) to (e10) and/or (g1) to (g2) and/or (g7) and/or (g9) and/or (g11) and/or (h2) and/or (h4) to (h7) detailed
25 hereinabove, in any desired combination or permutation.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a non-aircraft-fixed refueling device for use in in-flight refueling operation between a tanker aircraft and a receiver aircraft, comprising:
30

- 19 -

a selectively steerable body configured for being towed by the tanker aircraft via a fuel hose at least during in-flight refueling, and comprising a boom member having a boom axis and configured to enable fuel to be transferred from the fuel hose to the receiver aircraft along the boom axis during the in-flight refueling operation;

a controller configured for selectively maneuvering the body to an engagement enabling position spaced with respect to the receiver aircraft and for aligning the boom axis in an engagement enabling orientation at the spaced position, and for subsequently moving the boom member along the boom axis towards the receiver aircraft for enabling fuel communication therebetween.

In accordance with an aspect of the presently disclosed subject matter, there is provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising automatically aligning a refueling device at an engagement enabling position, including:

(i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

(ii) repeatedly calculating alignment commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

(iii) sending the alignment commands to the spatial control system;

whereby at the engagement enabling position, the boom member of the refueling device is capable of engaging with the fuel receptacle to enable refueling of the receiver aircraft.

The method can optionally further comprise one or more of the features (c1) to (c3) and/or (c5) and/or (c7) and/or (c11) detailed hereinabove and/or one or more of the features (i1) to (i6), in any desired combination or permutation:

- 20 -

(i1) wherein the maneuvering commands are alignment commands for aligning said refueling device in three degrees of freedom.

(i2) providing the maneuvering instructions to at least one of a pilot of the receiver aircraft pilot or a pilot of the tanker aircraft.

5 (i3) determining an engagement area specification condition; repeatedly calculating maneuvering instructions for said receiver aircraft based on said spatial dispositions and an engagement area specification; and invoking said automatically aligning in response to meeting said engagement area specification condition.

(i4) wherein the calculating alignment commands comprises obtaining data of an
10 initial trail position of the refueling device and wherein the alignment commands are based also on the data of an initial trail position.

(i5) wherein the automatic aligning and the automatic engaging are performed autonomously by the refueling device.

(i6) wherein said refueling device is aircraft fixed.
15

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

(a) automatically aligning a refueling device at an engagement enabling
20 position, including:

(i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with
25 respect to the fuel receptacle of the receiver aircraft;

(ii) repeatedly calculating alignment commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

30 (iii) sending the alignment commands to the spatial control system;

- 21 -

- (b) providing an instruction to the refueling device, when it arrives at the engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory for automatically engaging with the fuel receptacle.

5 The method can optionally further comprise one or more of the features (c2) and/or (c5) and/or (c7) and/or (c11) and/or (i1) to (i6) detailed hereinabove and/or feature (11), in any desired combination or permutation:

 (11) invoking the automatic aligning in response to a spatial disposition between the refueling device and the receiver aircraft meeting an engagement area specification
10 condition.

 In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising :

15 (a) repeatedly calculating maneuvering instructions for the receiver aircraft based on spatial dispositions of the receiver aircraft and an engagement area specification until an engagement area specification condition is met;

 (b) in response to meeting the engagement area specification condition, automatically aligning a refueling device at an engagement enabling
20 position, including:

 (i) repeatedly determining a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when the refueling device arrives to the engagement enabling position at which
25 the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;

 (ii) repeatedly calculating alignment commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

30 (iii) sending the alignment commands to the spatial control system;

- 22 -

(c) providing an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory for automatically engaging with the fuel receptacle.

5 The method can optionally further comprise one or more of the features (c2) and/or (c5) and/or (c7) and/or (c11) and/or (i1) to (i2) and/or (i4) to (i6) detailed hereinabove, in any desired combination or permutation.

 In accordance with an aspect of the presently disclosed subject matter, there is
10 yet further provided a system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising a steering control module configured to automatically align a refueling device at an engagement enabling position, including:

- (iv) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of
15 engaging and refueling the receiver aircraft via a boom member, when the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
- (v) repeatedly calculate alignment commands based at least on the
20 repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- (vi) send the alignment commands to the spatial control system for automatically steering the refueling device to the engagement enabling position;

25 whereby at the engagement enabling position, the boom member of the refueling device is capable of engaging with the fuel receptacle to enable refueling of the receiver aircraft.

 The system can optionally further comprise one or more of the features (c2) and/or (c11) and/or (i1) to (i2) and/or (i4) to (i6) detailed hereinabove and/or feature
30 (o1), in any desired combination or permutation:

- 23 -

(o1) a maneuvering instructions module configured to determine an engagement area specification condition, to repeatedly calculate maneuvering instructions for the receiver aircraft based on the spatial dispositions and an engagement area specification, and to invoke the steering control module to automatically align the refueling device at
5 the engagement enabling position in response to meeting the engagement area specification condition.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft
10 having a fuel receptacle, comprising a steering control module configured to automatically align a refueling device at an engagement enabling position, including:

- (iv) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when
15 the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
- (v) repeatedly calculate alignment commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial
20 control system of the refueling device;
- (vi) send the alignment commands to the spatial control system for automatically steering the refueling device to the engagement enabling position;

the system further comprises an engagement/disengagement module configured
25 to provide an instruction to the refueling device, when it arrives at the engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory to automatically engage with the fuel receptacle.

The system can optionally further comprise one or more of the features (c2) and/or (c7) and/or (c11) and/or (e4) to (e5) and/or (e8) to (e10) and/or (f2) and/or (i1) to
30 (i2) and/or (i4) to (i6) detailed hereinabove and/or one or more of the features (p1) to (p2), in any desired combination or permutation:

- 24 -

(p1) wherein the steering control module is further configured to obtain data of an initial trail position of the refueling device and wherein the calculate alignment commands is based also on the obtained data of an initial trail position.

(p2) a maneuvering instructions module configured to invoke the steering
5 control module to automatically align the refueling device to the engagement enabling position in response to meeting an engagement area specification condition.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a system for controlling in-flight refueling of a receiver aircraft
10 having a fuel receptacle, comprising a maneuvering instructions module configured to repeatedly calculate maneuvering instructions for the receiver aircraft based on spatial dispositions of the receiver aircraft and an engagement area specification until an engagement area specification condition is met, and in response to meeting the engagement area specification condition, activate a steering control module; the steering
15 control module is configured to automatically align a refueling device at an engagement enabling position, including:

- (iv) repeatedly determine a spatial disposition of the refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling the receiver aircraft via a boom member, when
20 the device arrives to the engagement enabling position at which the boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of the receiver aircraft;
- (v) repeatedly calculate alignment commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial
25 control system of the refueling device;
- (vi) send the alignment commands to the spatial control system for automatically steering the refueling device to the engagement enabling position;

the system further comprises an engagement/disengagement module configured
30 to provide an instruction to the refueling device, in response to its arriving at the engagement enabling position, causing the refueling device to move the boom

- 25 -

member in a predetermined trajectory to automatically engage with the fuel receptacle.

The system can optionally further comprise one or more of the features (c2) and/or (c7) and/or (c11) and/or (e4) to (e5) and/or (e8) to (e10) and/or (i1) to (i2) and/or
5 (i4) to (i6) and/or (p1) detailed hereinabove, in any desired combination or permutation.

In accordance with an aspect of the presently disclosed subject matter, there is yet further provided a refueling device for use in in-flight refueling operation between a tanker aircraft and a receiver aircraft, comprising a selectively steerable body
10 configured for being towed by a tanker aircraft via a fuel hose at least during in-flight refueling, and comprising a boom member having a boom axis and configured to enable fuel to be transferred from the fuel hose to a receiver aircraft along the boom axis during the in-flight refueling operation; a controller configured for selectively steering the body to an engagement enabling position spaced with respect to the receiver aircraft
15 and for aligning the boom axis in an engagement enabling orientation at the spaced position, and for subsequently moving the boom member along the boom axis towards the receiver aircraft for enabling fuel communication therebetween.

According to at least one aspect of the presently disclosed subject matter, there is provided a refueling device for use in in-flight refueling operation between a tanker
20 aircraft and a receiver aircraft, comprising:

- a selectively steerable body configured for being towed by a tanker aircraft via a fuel hose at least during in-flight refueling, and comprising a boom member having a boom axis and configured to enable fuel to be transferred from said fuel hose to a receiver aircraft along said boom axis during said in-flight refueling operation;
- 25 - a controller configured for selectively steering the body to an engagement enabling position spaced with respect to the receiver aircraft and for aligning said boom axis in an engagement enabling orientation at said spaced position, and for subsequently moving the boom member along said boom axis towards the receiver aircraft for enabling fuel communication therebetween.

- 26 -

For example, moving the boom member along said boom axis towards the receiver aircraft for enabling fuel communication therebetween can be achieved by any one of the following, for example:

- 5 - by moving the body towards the fuel receptacle of the receiver aircraft along the direction of the boom axis,
- by telescopically extending the boom member towards the towards the fuel receptacle of the receiver aircraft along said boom axis while the body is maintained at the engagement enabling position,
- 10 - partially by moving the body towards the fuel receptacle of the receiver aircraft along the direction of the boom axis, and partially by telescopically extending the boom member towards the towards the fuel receptacle of the receiver aircraft along said boom axis while the body is maintained at the engagement enabling position.

The refueling device according to this aspect of the presently disclosed subject matter can optionally comprise a spatial control system configured for selectively ensuring maintaining a desired non-zero angular disposition between said boom axis and said forward direction at least when said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose.

Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (A) to (S) below, additionally or alternatively including one or more of features (j1) to (j6) below, additionally or alternatively including one or more of features (k1) to (k15) below, additionally or alternatively including one or more of features M1 and or M2 and/or (m1) to (m4) below, 25 additionally or alternatively including one or more of features (n1) to (n4) below, additionally or alternatively including one or more of features (q1) to (q6) below, *mutatis mutandis*, in any desired combination or permutation.

Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject matter can optionally 30 comprise a force generating arrangement configured for selectively generating a force along said boom axis in a direction generally away from said fuel hose, i.e., towards the fuel delivery end of the boom member. Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject

- 27 -

matter can optionally comprise one or more of features (AA) to (LL) below, *mutatis mutandis*, in any desired combination or permutation.

Additionally or alternatively to the above features, the body according to this aspect of the presently disclosed subject matter can optionally comprise a fuel delivery
5 lumen configured for fluid communication with said fuel hose at least during the in-flight refueling operation, said lumen being configured to enable fuel to be transferred from the fuel hose to a receiver aircraft during said in-flight refueling operation, and the fuel delivery device comprises a coupling having a hose interface configured for connecting said lumen to the fuel hose, said coupling configured for allowing relative
10 rotation between the hose and said body in at least one degree of freedom while maintaining said fuel communication. Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (AAA) to (LLL) below, *mutatis mutandis*, in any desired combination or permutation.

15

According to at least one aspect of the presently disclosed subject matter, there is provided a refueling device for use in in-flight refueling operation, comprising:

- a body having a longitudinal axis and configured for being towed by a tanker aircraft via a fuel hose at least during in-flight refueling operation, and
20 comprising a boom member having a boom axis and configured to enable fuel to be transferred from said fuel hose to a receiver aircraft along said axis during said in-flight refueling operation;
- said boom member being pivotable with respect to said body, between a
25 retracted position and a deployed position, wherein in said retracted position said boom axis is at a smaller angular disposition with respect to said longitudinal axis than in said deployed position
- spatial control system including two sets of longitudinally spaced control
30 surfaces configured for enabling selectively steering said refueling device while concurrently selectively maintaining a desired non-zero angular disposition between said boom axis and said longitudinal axis at least when

- 28 -

said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose.

The refueling device according to this aspect of the presently disclosed subject matter can optionally comprise a spatial control system configured for selectively
5 ensuring maintaining a desired non-zero angular disposition between said boom axis and said forward direction at least when said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose.

Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject matter can optionally
10 comprise one or more of features (A) to (S) below, additionally or alternatively including one or more of features (j1) to (j6) below, additionally or alternatively including one or more of features (k1) to (k15) below, additionally or alternatively including one or more of features M1 and or M2 and/or (m1) to (m4) below, additionally or alternatively including one or more of features (n1) to (n4) below,
15 additionally or alternatively including one or more of features (q1) to (q6) below, *mutatis mutandis*, in any desired combination or permutation.

Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject matter can optionally comprise a force generating arrangement configured for selectively generating a force
20 along said boom axis in a direction generally away from said fuel hose, i.e., towards the fuel delivery end of the boom member. Additionally or alternatively to the above features, the refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (AA) to (LL) below, *mutatis mutandis*, in any desired combination or permutation.

25 Additionally or alternatively to the above features, the body according to this aspect of the presently disclosed subject matter can optionally comprise a fuel delivery lumen configured for fluid communication with said fuel hose at least during the in-flight refueling operation, said lumen being configured to enable fuel to be transferred from the fuel hose to a receiver aircraft during said in-flight refueling operation, and the
30 fuel delivery device comprises a coupling having a hose interface configured for connecting said lumen to the fuel hose, said coupling configured for allowing relative rotation between the hose and said body in at least one degree of freedom while maintaining said fuel communication. Additionally or alternatively to the above

- 29 -

features, the refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (AAA) to (LLL) below, *mutatis mutandis*, in any desired combination or permutation.

5 According to at least one aspect of the presently disclosed subject matter, the refueling device comprises:

- a) a body configured for being towed by a tanker aircraft via a fuel hose at least during in-flight refueling operation, and comprising a boom member having a boom axis and configured to enable fuel to be transferred from said fuel hose to
10 a receiver aircraft along said axis during said in-flight refueling operation;
- (b) spatial control system configured for selectively ensuring maintaining a desired non-zero angular disposition between said boom axis and a forward direction at least when said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose.

15 The above refueling device can optionally comprise one or more of the following features, in any desired combination or permutation:

A. A controller configured for selectively steering the body to an engagement enabling position spaced with respect to the receiver aircraft and for aligning said boom axis in an engagement enabling orientation at said spaced
20 position, and for subsequently moving the boom member along said boom axis towards the receiver aircraft for enabling fuel communication therebetween.

B. The boom member comprises a nozzle at a terminus thereof in fluid communication with a fuel delivery lumen comprised in said body, said nozzle being configured for reversible engagement with a fuel receptacle of a receiver
25 aircraft.

C. The fuel hose is substantially non-rigid and/or said body is selectively steerable.

D. The desired non-zero angular disposition is selectively controllable and/or said angular disposition is defined on a vertical plane.

30 E. The spatial control system configured for at least maintaining a selectively controllable non-zero angular disposition between said boom axis and a datum direction (different from said boom axis); the datum direction can be a

- 30 -

forward direction of the body, i.e., direction of motion of the body when towed via the hose; the said angular disposition can be or comprise an angle of attack of said boom axis with respect to said forward direction.

5 F. The said angular disposition is such as to ensure that the boom axis is at a predetermined design angle with respect to the receiver aircraft, in particular with respect to a longitudinal axis of the receiver aircraft; the design angle is such as to ensure proper alignment and engagement between the nozzle and the fuel receptacle; for example, the design angle may be between about 25° and about 35°, for example about 30°.

10 G. The said angular disposition is defined about a pitch axis of said refueling device. Additionally or alternatively, said angular disposition is defined about at least one of a yaw axis and a roll axis of said refueling device. Additionally or alternatively, the said angular disposition is in a range between about 5° and about 85°; preferably between about 10° and about 80°; more preferably between about 15° and about 70°; more preferably between about 20° and about 60°; more preferably between about 25° and about 50°; more preferably between about 20° and about 40°; more preferably between about 25° and about 40°; more preferably between about 28° and about 32°; or said angular disposition is about 30°.

20 H. Wherein said refueling device is configured for maintaining said desired non-zero angular disposition between said boom axis and said forward direction at least prior to engagement of said nozzle with a fuel receptacle of a receiver aircraft that flying in formation aft of the tanker aircraft.

25 I. Wherein said spatial control system is further configured for selectively providing control moments in at least one of pitch, yaw and roll wherein to enable the refueling device to be flown while towed by the tanker aircraft in said forward direction via said fuel hose.

J. Wherein said device can optionally comprise one or more of the following features, in any desired combination or permutation:

30 (j1) wherein said body is elongate having a longitudinal axis generally aligned with said boom axis.

(j2) wherein said body comprises a longitudinal axis, and said boom member is pivotably mounted with respect to said body, and pivotable between a

- 31 -

retracted position and a deployed position, wherein in said retracted position said boom axis is at a smaller angular disposition with respect to said longitudinal axis than in said deployed position.

(j3) wherein in said retracted position said boom axis is at an angular disposition with respect to said longitudinal axis of between 0° and 15° , and wherein in said deployed position, said angular disposition is greater than 15° .

(j4) wherein in said deployed position said boom axis is at an angular disposition with respect to said longitudinal axis between 20° to 40° .

(j5) wherein said boom member is in said deployed position during said in-flight refueling operation.

(j6) wherein said body comprises a longitudinal axis, and said boom member is mounted with respect to said body (for example fixedly mounted, or non-pivotably mounted, or mounted for relative translation therebetween), such as to maintain a generally parallel spatial disposition between said boom axis and said longitudinal axis at least during said in-flight refueling operation.

K. Wherein said spatial control system comprises selectively controllable aerodynamic control system. The selectively controllable aerodynamic control system can optionally comprise one or more of the following features, in any desired combination or permutation:

(k1) wherein said selectively controllable aerodynamic control system comprises a forward set of aerodynamic control surfaces mounted to said body, and an aft set of aerodynamic control surfaces mounted to said body in longitudinally aft spaced relationship with respect to said forward set of aerodynamic control surfaces.

(k2) a center of gravity of said body is disposed in longitudinally intermediate said forward set of aerodynamic control surfaces and said aft set of aerodynamic control surfaces.

(k3) wherein said aft set of aerodynamic control surfaces comprises at least two said control surfaces mounted to said body in Vee configuration; or wherein said aft set of aerodynamic control surfaces comprises a high H-tail configuration, comprising two vertical stabilizers, one each on either side of a horizontal stabilizer – the H-tail configuration

- 32 -

can be mounted to the upper side of the body, and optionally: each vertical stabilizer comprises a controllably pivotable rudder, and/or the horizontal stabilizer comprises one, two or more pivotable elevators, which optionally are controllably actuated by an actuator system for example controlled by a controller.

(k4) wherein said aft set of aerodynamic control surfaces further comprises at least one said control surfaces mounted to said body in vertical configuration.

(k5) wherein said forward set of aerodynamic control surfaces comprises at least two said control surfaces mounted to said body in Vee configuration.

(k6) wherein said forward set of aerodynamic control surfaces comprises at least four said control surfaces mounted to said body in cruciform configuration, for example cruciform "X" configuration or cruciform "+" configuration.

(k7) wherein at least one said control surface is pivotably mounted to said body via a respective boss laterally projecting from an outer surface of said body.

(k8) wherein each said boss houses an actuator configured for actuating the respective control surface.

(k9) wherein each said boss comprises an aerofoil shaped cross-sectional shape having a respective chord.

(k10) wherein each said chord is angularly displaced from said boom axis such as to become generally aligned with said forward direction when said boom axis is at said non-zero angular disposition with respect to said forward direction.

(k11) wherein said forward set of aerodynamic control surfaces comprises a canard configuration, and said aft set of aerodynamic control surfaces comprises one or more wing elements.

(k12) wherein said aft set of aerodynamic control surfaces comprises an H-tail configuration, comprising two vertical stabilizers, one each on either side of a horizontal stabilizer; and/or wherein said forward set of

- 33 -

aerodynamic control surfaces comprises at least four said control surfaces mounted to said body in cruciform configuration.

5 (k13) wherein said spatial control system is configured for enabling the refueling device to be steered in one, or two, or three degrees of freedom in translation, and in one, or two, or three degrees of freedom in rotation, independently of the tanker aircraft or of the refueling aircraft.

(k14) wherein said spatial control system is configured for providing at least one of:

- 10
- one or more of: sideslip, up/down translation, forward-aft translation, relative to the tanker aircraft and/or to the refueling aircraft, independently of rotational moments in roll pitch and/or yaw;
 - rotational moments in one or more of roll pitch and/or yaw, relative to the tanker aircraft and/or to the refueling aircraft, independently of sideslip, up/down translation, forward-aft translation.

15 (k15) wherein said spatial control system is configured for providing an angle of attack for the body with respect to the forward direction, between -10° and $+10^{\circ}$.

L. Wherein said spatial control system comprises a thrust vector system.

M. A force generating arrangement including one or more of:

20 M1 - a force generating arrangement configured for selectively generating a force along said boom axis in an aft direction, i.e., a direction towards said nozzle. The force generating arrangement can optionally comprise one or more of the following features, in any desired combination or permutation:

25 (m1) wherein said force generating arrangement comprises a selectively deployable and/or actuable drag inducing arrangement.

(m2) wherein said force generating arrangement comprises a selectively deployable and/or actuable air brake arrangement.

30 (m3) wherein said air brake arrangement comprises a plurality of airbrakes laterally mounted to at least one of said body and said boom member.

- 34 -

(m4) wherein said force generating arrangement is configured for selectively generating said force along said boom axis in a direction towards said nozzle responsive to said nozzle being in predetermined proximity to the fuel receptacle of the receiver aircraft whereby to force said nozzle into engagement with the fuel receptacle.

M2 - an aerodynamic stabilizer arrangement, different from the spatial control system, for example wherein said aerodynamic stabilizer arrangement is in the form of a drogue structure having a stowed configuration, in which drogue structure generates a minimum drag, and a deployed configuration in which drogue structure generates greater drag than in the inactive configuration.

N. Said body comprises a fuel delivery lumen configured for fluid communication with said fuel hose and said boom member at least during the in-flight refueling operation, and said body comprises a coupling having a hose interface configured for connecting said lumen to the fuel hose, said coupling configured for allowing relative rotation between the hose and said body in at least one degree of freedom while maintaining said fuel communication. The coupling can optionally comprise one or more of the following features, in any desired combination or permutation:

(n1) wherein said coupling configured for allowing relative rotation between the hose and said body in at least two degrees of freedom.

(n2) wherein said coupling configured for allowing relative rotation between the hose and said body in three degrees of freedom.

(n3) wherein at least one said rotational degree of freedom has the respective axis of rotation generally orthogonal to a plane defining said non-zero angular disposition between said boom axis and said forward direction.

(n4) wherein said coupling comprises a universal coupling.

O. Wherein said boom member is selectively reversibly telescopically deployable along said boom axis with respect to said body or wherein said boom member is not reversibly telescopically deployable along said boom axis with respect to said body.

P. Wherein said boom member is pivotably mounted to said body.

- 35 -

Q. A data acquisition system configured for providing spatial data relating to a relative spatial disposition between a fuel delivery nozzle of the refueling device and a fuel receptacle of the receiver aircraft, to enable selectively controlling the refueling device to provide automatic and/or autonomous and/or manual engagement of the fuel delivery nozzle to the fuel receptacle of the receiver aircraft. In at least one example, the system comprises an imaging system for providing said data including at least image data corresponding to a field of regard with respect to the refueling device. The data acquisition system can be in the form of an imaging system, and can optionally comprise one or more of the following features, in any desired combination or permutation:

(q1) wherein said imaging system is configured for providing at least one of 2D images, stereoscopic images, and 3D images of a volume defined by said field of regard.

(q2) wherein said imaging system is configured for providing said image data in real time.

(q3) wherein said imaging system comprises or is operatively connected to a computing system configured for identifying a fuel receptacle of a receiver aircraft within said field of regard from said image data, and for determining a spatial disposition of said nozzle with respect to the fuel receptacle.

(q4) wherein said imaging system comprises a first set of electromagnetic energy modules configured for illuminating said field of regard with electromagnetic energy (for example laser energy), and a second set of electromagnetic energy modules configured for receiving electromagnetic energy from said illuminated field of regard.

(q5) wherein said imaging system comprises a first set of electromagnetic energy modules configured for transmitting electromagnetic energy in a direction generally along said boom axis and generally opposed to said forward direction, and a second set of electromagnetic energy modules configured for receiving electromagnetic energy from a direction generally along said boom axis and generally along said forward direction.

- 36 -

(q6) wherein said imaging system comprises at least one flash lidar unit and/or at least one LIDAR unit.

R. The controller can comprise, for example, a computer system, operatively connected to said spatial data acquisition system and/or to said spatial control system, and/or optionally configured as an automatic or autonomous system for enabling refueling device to be steered to an engagement enabling position to provide engagement of the nozzle with the fuel receptacle of the receiver aircraft, and thereafter enable refueling of the receiver aircraft.

S. A suitable communication system to transmit image data and to receive control commands/signals. For example, the communications system can be operatively connected to the controller for controlling operation of the refueling device.

According to at least one aspect of the presently disclosed subject matter, the refueling device comprises:

- a body configured for connection to a tanker aircraft via a fuel hose at least during in-flight refueling operation thereof while said body is in towed configuration with respect to the tanker aircraft via said fuel hose, and further comprising a substantially rigid boom member having a boom axis and configured to enable fuel to be transferred from the tanker aircraft to a receiver aircraft during said in-flight refueling operation;

- spatial control system configured for selectively maintaining a desired non-zero angular disposition between said boom axis and a datum direction.

The refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of the following features, in any desired combination or permutation:

- Wherein said datum direction is parallel to a longitudinal axis of the receiver aircraft.
- The desired non-zero angular disposition is selectively controllable.
- The datum direction is different, i.e. non-parallel, from said boom axis.
- The datum direction can be parallel to a forward direction of the body, i.e., direction of motion of the body when towed via the hose.

- 37 -

- The spatial control system is also configured for selectively ensuring maintaining a desired non-zero angular disposition between said boom axis and said forward direction at least when said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose.
- 5 - The boom member comprises a nozzle at a terminus thereof in fluid communication with a fuel delivery lumen comprised in said body, said nozzle being configured for reversible engagement with a fuel receptacle of a receiver aircraft.

Additionally or alternatively to the above features, the refueling device
10 according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (A) to (S), additionally or alternatively including one or more of features (j1) to (j6), additionally or alternatively including one or more of features (k1) to (k15), additionally or alternatively including one or more of features M1 and/or m2 and/or (m1) to (m4), additionally or alternatively including
15 one or more of features (n1) to (n4), additionally or alternatively including one or more of features (q1) to (q6), *mutatis mutandis*, in any desired combination or permutation.

According to at least one other aspect of the presently disclosed subject matter,
20 the refueling device comprises:

- (aa) a body configured for being towed by a tanker aircraft via a fuel hose at least during in-flight refueling operation, and comprising a boom member having a boom axis and configured to enable fuel to be transferred from said fuel hose to a receiver aircraft along said axis during said in-flight refueling
25 operation;
- (bb) a force generating arrangement configured for selectively generating a force along said boom axis in a direction generally away from said fuel hose.

A fuel delivery nozzle is comprised at a terminus of the boom member and is in fluid communication with a fuel delivery lumen comprised in said body, the lumen
30 configured for fluid communication with said fuel hose and said fuel member at least during in flight refueling operation, said nozzle being configured for reversible engagement with a fuel receptacle of a receiver aircraft.

- 38 -

The refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of the following features, in any desired combination or permutation:

5 (AA) Wherein said force generating arrangement comprises a selectively deployable drag inducing arrangement.

(BB) Wherein said force generating arrangement comprises a selectively deployable air brake arrangement.

(CC) Wherein said air brake arrangement comprises a plurality of airbrakes laterally mounted to at least one of said body and said boom member.

10 (DD) Wherein said force generating arrangement is configured for selectively generating a force along said boom axis in a direction towards said nozzle responsive to said nozzle being in predetermined proximity to the fuel receptacle of the receiver aircraft wherein to force said nozzle into engagement with the fuel receptacle.

15 (EE) Wherein the fuel hose is substantially non-rigid and/or wherein said body is selectively steerable.

(FF) Wherein said boom member is selectively reversibly telescopically deployable along said boom axis with respect to said body.

(GG) Wherein said boom member is pivotably mounted to said body.

20 (HH) a controller configured for selectively steering the body to an engagement enabling position spaced with respect to the receiver aircraft and for aligning said boom axis in an engagement enabling orientation at said spaced position, and for subsequently moving the boom member along said boom axis towards the receiver aircraft for enabling fuel communication therebetween.

25 (II). A suitable communication system to transmit image data and to receive control commands/signals. For example, the communications system can be operatively connected to the controller for controlling operation of the refueling device.

30 (JJ) A spatial control system configured for selectively ensuring maintaining a desired non-zero angular disposition between said boom axis and said forward direction at least when said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose, and/or configured for at least providing directional stability at least during deployment of drag generating

- 39 -

system, the spatial control system being different from said force generating arrangement. The spatial control system according to at least this aspect of the presently disclosed subject matter can optionally comprise one or more of features (B) to (L), optionally including one or more of features (k1) to k(15), *mutatis mutandis*, in any desired combination or permutation.

(KK) A coupling having a hose interface configured for connecting said lumen to the fuel hose, said coupling configured for allowing relative rotation between the hose and said body in at least one degree of freedom while maintaining said fuel communication. The coupling according to at least this aspect of the presently disclosed subject matter can optionally comprise one or more of features (n1) to (n4), *mutatis mutandis*, in any desired combination or permutation.

(LL) A data acquisition system configured for providing spatial data relating to a relative spatial disposition between said fuel delivery nozzle and a fuel receptacle of the receiver aircraft, to enable selectively controlling the refueling device to provide automatic or autonomous or manual engagement of the fuel delivery end to the fuel receptacle, said system optionally comprising an imaging system configured for providing said data including image data corresponding to a field of regard aft of the refueling device, and wherein optionally said imaging system comprises or is operatively connected to a computing system configured for identifying a fuel receptacle of a receiver aircraft within said field of regard from said image data, and for determining a spatial disposition of said fuel delivery nozzle with respect to the fuel receptacle. The data acquisition system can be in the form of an imaging system, and can optionally comprise one or more of features (q1) to (q6), *mutatis mutandis*, in any desired combination or permutation.

According to at least one other aspect of the presently disclosed subject matter, the refueling device comprises:

(aaa) a body configured for being towed by a tanker aircraft via a fuel hose at least during in-flight refueling operation, and comprising a fuel delivery lumen configured for fluid communication with said fuel hose at least during the in-flight refueling operation, said lumen being configured to

- 40 -

enable fuel to be transferred from the fuel hose to a receiver aircraft during said in-flight refueling operation;

(bbb) a coupling having a hose interface configured for connecting said lumen to the fuel hose, said coupling configured for allowing relative rotation between the hose and said body in at least one degree of freedom while maintaining said fuel communication.

The refueling device according to this aspect of the presently disclosed subject matter can optionally comprise one or more of the following features, in any desired combination or permutation:

(AAA) Wherein said coupling is configured for allowing relative rotation between the hose and said body in at least two degrees of freedom.

(BBB) Wherein said coupling is configured for allowing relative rotation between the hose and said body in three degrees of freedom.

(CCC) Wherein said body comprises a boom member having a boom axis, and wherein said lumen is configured to enable fuel to be transferred from the fuel hose to a receiver aircraft via said boom member during said in-flight refueling operation, and/or at least one said degree of freedom has the respective axis of rotation generally orthogonal to a plane defining said non-zero angular disposition between said boom axis and said forward direction.

(DDD) Wherein said coupling comprises a universal coupling.

(EEE) Wherein the fuel hose is substantially non-rigid.

(FFF) Wherein said boom member is selectively reversibly telescopically deployable along said boom axis with respect to said body.

(GGG) Wherein said boom member is pivotably mounted to said body.

(HHH) A data acquisition system configured for providing spatial data relating to a relative spatial disposition between a fuel delivery end of said boom member and a fuel receptacle of the receiver aircraft, to enable selectively controlling the refueling device to provide automatic or autonomous or manual engagement of the fuel delivery end to the fuel receptacle, said system optionally comprising an imaging system configured for providing said data including image data corresponding to a field of regard aft of the refueling device, and wherein optionally said imaging system comprises or is operatively connected to a computing system configured for identifying a fuel receptacle of a receiver

- 41 -

aircraft within said field of regard from said image data, and for determining a spatial disposition of said fuel delivery end with respect to the fuel receptacle.

(III) A suitable communication system to transmit image data and to receive control commands/signals. For example, the communications system can be operatively connected to the controller for controlling operation of the refueling device.

(JJJ) A spatial control system configured for selectively ensuring maintaining a desired non-zero angular disposition between said boom axis and said forward direction at least when said refueling device is towed by the tanker aircraft in said forward direction via said fuel hose, and/or, configured for at least providing directional stability. The spatial control system according to at least this aspect of the presently disclosed subject matter can optionally comprise one or more of features (B) to (L), optionally including one or more of features (k1) to k(15), *mutatis mutandis*, in any desired combination or permutation.

(KKK) A force generating arrangement configured for selectively generating a force along said boom axis in a direction towards said nozzle. The force generating arrangement according to at least this aspect of the presently disclosed subject matter can optionally comprise one or more of features M1 and/or M2 and/or (m1) to (m4), *mutatis mutandis*, in any desired combination or permutation.

(LLL) A data acquisition system configured for providing spatial data relating to a relative spatial disposition between a fuel delivery nozzle of the refueling device and a fuel receptacle of the receiver aircraft, to enable selectively controlling the refueling device to provide automatic and/or autonomous and/or manual engagement of the fuel delivery nozzle to the fuel receptacle of the receiver aircraft. In at least one example, the system comprises an imaging system for providing said data including at least image data corresponding to a field of regard with respect to the refueling device. The data acquisition system can be in the form of an imaging system, and can optionally comprise one or more of features (q1) to (q6), *mutatis mutandis*, in any desired combination or permutation.

According to at least one other aspect of the presently disclosed subject matter, there is provided a refueling system comprising a refueling fuel reservoir connected to a

- 42 -

refueling device via a hose, the refueling device being as defined in the examples herein, in particular as defined above and optionally including one or more of the features listed above in A to S, AA to LL, and AAA to LLL, in any desired combination or permutation. Optionally, the refueling system can be housed in a suitable pod
5 configured to be fixedly attached to a tanker aircraft.

According to at least one other aspect of the presently disclosed subject matter, there is provided a tanker aircraft comprising at least one refueling system as defined herein, for example comprising one refueling system as defined herein, or comprising two refueling systems as defined herein, or comprising three refueling systems as
10 defined herein, or comprising more four or more refueling systems as defined herein.

According to the tanker aircraft may be a manned tanker aircraft or a UAV, and/or at least one receiver aircraft may be a manned aircraft or a UAV.

Optionally, a tanker aircraft according to the presently disclosed subject matter can comprise one or two such refueling systems mounted to the wings (e.g. via pods)
15 and additionally comprise one conventional “flying boom” system in the aft fuselage. Thus, it is readily apparent that existing tanker aircraft already fitted with conventional “flying boom” systems can be retrofitted with refueling systems according to the first aspect of the presently disclosed subject matter, for example one such refueling system fitted onto each wing, thereby effectively tripling the refueling efficiency/capability of
20 such a tanker aircraft, enabling up to three receiver aircraft having fuel receptacles to be refueled concurrently.

Optionally, a tanker aircraft according to the presently disclosed subject matter can comprise one or more such refueling systems, as well as at least one conventional “hose and drogue” system, enabling receiver aircraft of both types to be refueled
25 concurrently.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the presently disclosed subject matter and to see how it may be carried out in practice, examples will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

5 **Fig. 1** is a top view of an example of a tanker system according to the presently disclosed subject matter.

Fig. 2 is a side view of the tanker system of Fig. 1.

Fig. 3 is an isometric view of an example of a refueling device according to the presently disclosed subject matter.

10 **Fig. 4** is a side view of the refueling device of Fig. 3.

Fig. 5 is a top view of the refueling device of Fig. 3.

Fig. 6(a) is a front view of the refueling device of Fig. 3; **Fig. 6(b)** is an aft view of the refueling device of Fig. 3.

15 **Fig. 7** is a cross-sectional side view of the refueling device of Fig. 5 taken along B'-B'.

Fig. 8 is a cross-sectional side view of the refueling device of Fig. 4 taken along A'-A'.

20 **Fig. 9(a)** is an isometric view of the refueling device of Fig. 3, with the airbrakes and boom member in the deployed positions; **Fig. 9(b)** is a top view of the refueling device of Fig. 9(a).

Fig. 10(a) is a partial side view of the example of the boom member of the refueling device of Fig. 3 in proximity to a fuel receptacle of a receiver aircraft; **Fig. 10(b)** is an alternative variation of the example of Fig. 10(a).

25 **Fig. 11** is an isometric view of the refueling device of Fig. 3, further schematically illustrating a volume aft thereof.

Figs. 12(a) to 12(d) are respective isometric, side, top and front views of an alternative variation of the example of refueling device of Fig. 3.

Figs. 13(a) to 13(e) are respective isometric views of other alternative variations of the example of refueling device of Fig. 3.

Figs. 14(a) and **14(b)** are respective isometric views of other alternative variations of the example of refueling device of Fig. 3.

Figs. 15(a) to 15(d) illustrate another alternative variation of the example of
5 refueling device of Fig. 3, in isometric view, top view, side view and aft view, respectively.

Figs. 16(a) to 16(d) illustrate another example of a refueling device according to the presently disclosed subject matter, in isometric view, side view, top view and front view, respectively.

10 **Figs. 17(a) to 17(e)** illustrate an alternative variation of the example of the refueling device Figs. 16(a) to 16(d), in isometric view (stowed configuration), isometric view (deployed configuration), side view (deployed configuration), front view (deployed configuration), and top view (deployed configuration), respectively; **Figs. 17(f) to 17(g)** illustrate an alternative variation of the example of the refueling device
15 Figs. 16(a) to 16(d), in isometric view, in stowed configuration and in deployed configuration, respectively; **Fig. 17(h)** illustrates another alternative variation of the example of the refueling device Figs. 16(a) to 16(d), in isometric view, in deployed configuration.

Fig. 18 is a block diagram schematically illustrating a system for controlling in-
20 flight refueling, according to certain examples of the presently disclosed subject matter;

Fig. 19 is a flowchart illustrating a sequence of operations carried out for performing in-flight refueling, according to certain examples of the presently disclosed subject matter;

Fig. 20 is a flowchart illustrating a sequence of operations carried out for
25 providing maneuvering commands for positioning a receiver aircraft within an engagement area related thereto, according to certain examples of the presently disclosed subject matter;

Fig. 21 is a flowchart illustrating a sequence of operations carried out for providing steering commands to a refueling device for maneuvering to an engagement
30 enabling position, according to certain examples of the presently disclosed subject matter;

Fig. 22 is a flowchart illustrating a sequence of operations carried out for determining the receiver aircraft spatial disposition with respect to the engagement area related thereto, according to certain examples of the presently disclosed subject matter;

Fig. 23 is a flowchart illustrating a sequence of operations carried out for
5 determining the refueling device spatial disposition with respect to the engagement enabling position, according to certain examples of the presently disclosed subject matter;

Fig. 24 is an illustration of an example of a receiver aircraft positioned outside a virtual engagement area, according to certain examples of the presently disclosed
10 subject matter;

Fig. 25 is an illustration of an example of a receiver aircraft positioned inside a virtual engagement area, according to certain examples of the presently disclosed subject matter;

Fig. 26 is an illustration of an example of a refueling device not in an
15 engagement enabling position, according to certain examples of the presently disclosed subject matter;

Fig. 27 is an illustration of an example of a refueling device positioned in an engagement enabling position, according to certain examples of the presently disclosed subject matter;

Fig. 28 is an illustration of an example of a sensed image indicating that the
20 refueling device is not positioned in an engagement enabling position, according to certain examples of the presently disclosed subject matter;

Fig. 29 is an illustration of an example of a sensed image indicating that the refueling device is positioned in an engagement enabling position, according to certain
25 examples of the presently disclosed subject matter;

Fig. 30 is a partial side view of another example of a tanker system according to certain examples of the presently disclosed subject matter;

Fig. 31 is a schematic illustration of an image acquisition system according to certain examples of the presently disclosed subject matter;

- 46 -

Fig. 32 is a schematic illustration of a scene sensed the LIDAR unit according to certain examples of the presently disclosed subject matter;

Fig. 33 is a schematic representation of the depth and electromagnetic data relating to the boom refueling device and to the fuel receptacle of the receiver aircraft as
5 acquired by the LIDAR unit according to certain examples of the presently disclosed subject matter.

DETAILED DESCRIPTION OF THE DRAWINGS

In the drawings and descriptions set forth, identical reference numerals indicate those components that are common to different embodiments or configurations.

10 Unless specifically stated otherwise, as apparent from the following discussions, it is appreciated that throughout the specification discussions utilizing terms such as "steering", "determining", "calculating", "providing", "causing", "activating", "receiving", "acquiring", "comparing", "obtaining", or the like, include action and/or processes of a computer that manipulate and/or transform data into other data, said data
15 represented as physical quantities, e.g. such as electronic quantities, and/or said data representing the physical objects. The term "computer" should be expansively construed to cover any kind of electronic device with data processing capabilities, including, by way of non-limiting example, a personal computer, a server, a computing system, a communication device, a processor/processing unit (e.g. digital signal processor (DSP),
20 a microcontroller, a microprocessor, a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), etc.), any other electronic computing device, and or any combination thereof.

The operations in accordance with the teachings herein may be performed by a computer specially constructed for the desired purposes or by a general purpose
25 computer specially configured for the desired purpose by a computer program stored in a computer readable storage medium.

As used herein, the phrase "for example," "such as", "for instance" and variants thereof describe non-limiting embodiments of the presently disclosed subject matter. Reference in the specification to "one case", "some cases", "other cases", "one
30 example", "some examples" or variants thereof means that a particular feature, structure or characteristic described in connection with the embodiment(s) is included in at least one embodiment of the presently disclosed subject matter. Thus the appearance of the

- 47 -

phrase "one case", "some cases", "other cases", "one example", "some examples" or variants thereof does not necessarily refer to the same embodiment(s).

It is appreciated that certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the presently disclosed subject matter, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

In embodiments of the presently disclosed subject matter, fewer, more and/or different stages than those shown in **Figs. 19 to 23** can be executed. In embodiments of the presently disclosed subject matter one or more stages illustrated in **Figs. 19 to 23** can be executed in a different order and/or one or more groups of stages may be executed simultaneously. **Fig. 7** and **18** illustrate a general schematic of the system architecture in accordance with an embodiment of the presently disclosed subject matter. Each module in **Fig. 7** and **18** can be made up of any combination of software, hardware and/or firmware that performs the functions as defined and explained herein. The modules in **Figs. 7** and **18** can be centralized in one location or dispersed over more than one location. In other embodiments of the presently disclosed subject matter, the system may comprise fewer, more, and/or different modules than those shown in **Fig. 7** and **18**.

According to a first aspect of the presently disclosed subject matter, there are provided systems and devices for in-flight refueling of aircraft.

Referring to **Figs. 1 and 2**, a tanker system according to one example of the presently disclosed subject matter, generally designated **10**, comprises a tanker aircraft **12** comprising one or more in-flight refueling systems **50**. In this example, the tanker aircraft **12** has three such in-flight refueling systems **50**, one comprised on each one of the port wing **14** and starboard wing **16**, and a third one comprised on the rear portion of the fuselage **15**, and the tanker aircraft **12** is configured for in-flight concurrent refueling of up to three receiver aircraft **20**. In alternative variations of this example the tanker aircraft **12** can have at least one, or two, or more than three in-flight refueling systems **50**, arranged in any suitable configuration with respect to the tanker aircraft **12**.

By way of non-limiting example, such a tanker aircraft **12** can be a suitably equipped Boeing 767 and each receiver aircraft **20** can include any one of suitably equipped F-15, or F-16, or B2 stealth bomber, or other suitably equipped fighter, bomber

- 48 -

or other aircraft. Alternatively, and also by way of non-limiting example, the tanker aircraft may be a UAV, and/or at least one of the receiver aircraft may be a UAV.

Also by way of non-limiting example, a refueling flight envelope for use with such a tanker system can include a forward speed of between about 220 knots and about 320 knots (typically about 280 knots), and an altitude of between 500ft and between about 30,000ft and about 40,000ft, and in general not below about 10,000ft, in which refueling can take place between the tanker aircraft **12** and each receiver aircraft **20**, flying in formation, depending on the operating limits of the tanker aircraft and of the receiver aircraft, as well as other factors.

Each in-flight refueling system **50** comprises an elongate, non-rigid, fuel delivery hose **52**, reversibly extendible from the tanker aircraft **12**. A first end (not shown) of the hose **52** is connected to a refueling fuel tank (not shown) carried by the tanker aircraft **12**. For example, such a refueling fuel tank can be an internal fuel tank of the tanker aircraft **12**, for example the tanker aircraft's own fuel tanks, or a special fuel reservoir mounted internally in the tanker aircraft **12**, for example in the fuselage, or externally and carried in fuel pods, for example.

The hose **52** is flexible and can be retracted into a roll up drum (not shown), suitably provided in the tanker aircraft **12**, and selectively deployed therefrom when required.

The second (aft) end **54** of hose **52** is operatively connected to a respective refueling device that is towed in a forward direction **A** by the tanker aircraft **12** via hose **52** when the hose **52** is extended and the tanker aircraft **12** is in flight.

In this example, one in-flight refueling system **50** is centrally-located and mounted with respect to the rear fuselage of the tanker aircraft **12**, and each of the other two in-flight refueling systems **50** is comprised in a respective pod **51** that is attached to the underside of the respective wing.

Figs. 3 to 11 illustrate a refueling device according to a first example of the presently disclosed subject matter, generally designated **100**, for use with an in-flight refueling system, for example at least one of the in-flight refueling systems **50** illustrated in Figs. 1 and 2.

- 49 -

For convenience, and referring to Fig. 3 for example, a roll axis **R**, a pitch axis **P** and a yaw axis **Y** can be conventionally defined with respect to the refueling device **100**. The roll axis **R** is parallel to or co-axial with the longitudinal axis **111** of the device **100**; the pitch axis **P** is generally in lateral and orthogonal relationship to the roll axis **R** (i.e.,
5 parallel to the horizontal when the body is at a zero roll angle); and yaw axis **Y** is in orthogonal relationship to the roll axis **R** the pitch axis **P** (i.e., parallel to the vertical when the body is at a zero pitch angle).

Refueling device **100** is affixed to the end **54** of hose **52** and comprises an elongate body **110** comprising a longitudinal axis **111** and a general oval cross section (as best seen
10 in Figs. 6(a) and 6(b)), although in alternative variations of this example the body **110** can have any suitable cross-sectional shape, for example circular cross-section, polygonal cross-section, and so on. Referring in particular to Figs. 7 and 8, the body **110** comprises a fuel delivery lumen **120** and a boom member **130** (which at least in the disclosed examples is a substantially rigid boom member) in fluid communication therewith. The boom
15 member **130** defines a boom axis **131** and comprises a fuel delivery nozzle **135** at a terminus **136** of the boom member **130**. The nozzle **135** is configured for reversibly engaging with the fuel receptacle **22** of a receiver aircraft **20** (see also Figs. 1, 2 and 11), and thus can comprise any conventional design of such nozzles, which are well known, or indeed can comprise any other current or future design of such an in-flight refueling
20 nozzle.

The boom member **130** is telescopically mounted to body **110**, and is reversibly extendable from a stowed position illustrated in Figs. 3 to 8 in which most of the boom member **130** is accommodated in a sleeve within the body **110**, to the fully extended position illustrated in Figs. 9(a) and 9(b), by means of a controllable actuation mechanism
25 (not shown). Optimally, the boom member **130** is telescopically extendable to a controllably variable extended position in a general aft direction from the aft end **112** of body **110**, up to the aforesaid the fully extended position. While in this example the boom axis **131** is parallel and co-axial with longitudinal axis **111**, in at least some alternative variations of this example the boom axis can be parallel but not co-axial with the body
30 longitudinal axis, or the boom axis can be non-parallel with respect to the body longitudinal axis.

- 50 -

Thus, the boom member **130** is mounted with respect to the body **110** such as to maintain a generally parallel spatial disposition between the boom axis **131** and the longitudinal axis **111**, at least during in-flight refueling operation of device **100**.

In an alternative variation of this embodiment, the boom member **130** is
5 permanently extended with respect to the body **110**, and is not telescopically or reversibly extendible therefrom. In another alternative variation of this example, the boom member **130** is permanently retracted with respect to the body **110**, and is not telescopically or reversibly extendible therefrom, and thus may only comprise a relatively short section extending aft from the body **110** to connect to the nozzle **135**.

10 In alternative variations of this example, or in other examples, the boom member may have any other suitable structure configured for coupling with the receiver aircraft, in particular the fuel receptacle thereof.

The body **110** comprises a coupling **140** at forward end **114** thereof. The coupling **140** comprises a hose interface **142** configured for connecting the lumen **120**
15 to the hose **52**, and thereby to the tanker aircraft **12**. The coupling **140** is configured for allowing relative rotation between the body **110** and the hose **52** while maintaining fluid communication between the lumen **120** and the hose **52** and thus the refueling tank. In this example, the coupling **140** is in the form of a universal joint or the like (also referred to as a universal coupling, a Cardan joint, a Hardy-Spicer joint or a Hooke's
20 joint, and so on), and is thus configured for allowing relative rotation between the body **110** and the hose **52** in three degrees of freedom. In alternative variations of this example and in other examples, the coupling can instead be configured for allowing relative rotation between the body **110** and the hose **52** in one degree of freedom, or in two degrees of freedom. In particular, the coupling allows the body **110**, and in
25 particular the boom member **130** and the boom axis **131** to freely pivot with respect to the hose **52**, in particular the second end **54**, about at least one axis **B** (see Figs. 3 and 5, for example), so that the spatial orientation of the refueling device **100** can be controllably changed without significant mechanical resistance thereto being generated by the hose **52** about axis **B**, which is typically parallel the pitch axis **P** of the refueling
30 device **100**, but may be alternatively inclined to the pitch axis **P** and/or to the roll axis **R** and/or to the yaw axis **Y**.

- 51 -

The body **110** can optionally be formed as an integral and/or unitary structure incorporating the boom member **130** and the coupling **140**.

In alternative variations of this example the coupling **140** can be omitted and replaced with a fixed coupling that is configured to maintain a fixed relative spatial disposition between the body **110** and the hose **52** while maintaining fluid communication between the lumen **120** and the hose **52**. For example such a spatial disposition may be an angle ϕ (see Fig. 1) of about 0° ; or about 30° ; or in a range between about 5° and about 85° ; or in a range between about 10° and about 80° ; or in a range between about 15° and about 70° ; or in a range between about 20° and about 60° ; or in a range between about 25° and about 50° ; or in a range between about 20° and about 40° ; or in a range between about 25° and about 40° ; or in a range between about 28° and about 32° .

The refueling device **100** further comprises a spatial control system **160**, configured for controlling a spatial disposition of the refueling device **100** when towed aft of the tanker aircraft **12** via the hose **52**, and enables the refueling device **100** to be steered and/or to adopt any desired stable spatial disposition while being towed at the end **54** of hose **52**.

In particular, spatial control system **160** is configured for selectively and controllably providing a non-zero angular disposition, angle θ , between the boom axis **131** and the forward direction A, and enables this angle θ to be selectively maintained between the boom axis **131** and the forward direction A at least for a part of the time when the refueling device **100** is being towed by the tanker aircraft **12** via hose **52**, in particular during the engagement operation of the fuel device **100** to the receiver aircraft **20** and during refueling thereof. In particular, angle θ is in pitch, i.e., about a pitch axis P of the refueling device **100** and is defined on a plane including the roll axis R and the yaw axis Y of the refueling device **100**. Angle θ is thus representative of an angle of attack of the refueling device **100** in the airflow, or at least of the boom axis **131** with respect to forward direction A (which is typically, but not exclusively, parallel to the horizontal direction). Nevertheless, and depending on specific conditions during any particular refueling operation, angle θ can include an angular displacement component between the boom axis **131** and the forward direction A in yaw (i.e., about yaw axis Y),

- 52 -

for example due to sideslip angle, and/or in roll (i.e. about roll axis R), instead of or in addition to an angular displacement component in pitch (i.e., about pitch axis P).

The refueling device **100**, in particular the boom member **130**, nozzle **135** and lumen **120** can be sized to allow suitable fuel flow rates for refueling a wide range of receiver aircraft. By way of non-limiting example, relative high fuel flow rates (for example up to 1000 US gallons/6,500 lb per minute) can be provided for refueling operations of large aircraft (for example transport aircraft, bombers, etc), while for fighter aircraft that cannot accept fuel at the maximum flow rate of the refueling device **100**, the refueling pressure can be correspondingly reduced. Alternatively the refueling device **100**, in particular the boom member **130**, nozzle **135** and lumen **120** can be sized to allow suitable fuel flow rates for refueling a narrow range of receiver aircraft., for example only fighter aircraft or only larger aircraft (for example about 400 US gallons/2,600 lb per minute).

Thus, the spatial control system **160** is configured for providing stability to the refueling device **100**, while tethered to and towed by the tanker aircraft **12** via the hose **52**, and while the boom axis **131** is at any desired pitch and/or yaw and/or roll angle corresponding to the aforesaid angle θ .

In particular, and referring to Fig. 10(a) and Fig. 10(b), angle θ is such as to provide a design angle (angle θ_{des}) that is within a particular angular range which corresponds to the design relative angular position of the boom member **130** (and boom axis **131**) with respect to the receiver aircraft **20**.

In particular, design angle θ_{des} is the design relative angular position of the boom axis **131** with respect to the longitudinal axis of the receiver aircraft **20** (the receiver aircraft **20** being at a predetermined spatial orientation relative to the forward direction, typically in horizontal forward flight), to enable the boom member **130** to align and engage the nozzle **135** with respect to the fuel receptacle **22**. Thus, angle θ (which can have an angular component in yaw and/or in pitch and/or in roll) compensates for any off-nominal pitch of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction **A** at a non-zero angle of attack) and/or for any off-nominal roll of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction **A** at a non-zero roll angle) and/or for any off-nominal yaw of the receiver

- 53 -

aircraft **20** (for example if the receiver aircraft **20** is traveling along direction A at a non-zero sideslip angle) to ensure that the actual angular disposition between the boom axis **131** and the receiver aircraft longitudinal axis is maintained at design angle θ_{des} even as the relative spatial orientation between the receiver aircraft **20** and the forward direction
5 changes.

Thus, design angle θ_{des} the boom axis **131** is in an engagement enabling orientation with respect to the receiver aircraft **20**, and in particular with respect to the fuel receptacle **22**.

In non-limiting examples, angle θ (and in particular angle θ_{des}) can be in a range
10 between about 5° and about 85° ; or in a range between about 10° and about 80° ; or in a range between about 15° and about 70° ; or in a range between about 20° and about 60° ; or in a range between about 25° and about 50° ; or in a range between about 20° and about 40° ; or in a range between about 25° and about 40° ; or in a range between about 28° and about 32° .

15 In one non-limiting example, angle θ_{des} can be about 30° , and operation of the refueling device **100** to adopt this angle automatically renders it compatible for use with existing receiver aircraft **20**, in which the fuel receptacles **22** are configured for receiving and engaging with a nozzle at the end of a boom where the boom is at about 30° to the longitudinal axis of the receiver aircraft, without the need for modifying the
20 configuration of the fuel receptacle thereof.

Thus, when angle θ is equal to design angle θ_{des} , the receiver aircraft travelling along direction A with zero angle of attack and zero sideslip and zero roll, and boom axis **131** is at the required spatial orientation to the forward direction A of the tanker aircraft and the receiver aircraft such as to ensure engagement between the nozzle **135**
25 in the fuel receptacle **22**, without the need for modifying the configuration of the fuel receptacle thereof.

In this example, the spatial control system **160** comprises a selectively controllable aerodynamic control system **170**, comprising a forward set **172** of aerodynamic control surfaces **173** mounted to body **110** at a forward portion thereof, and an aft set **174** of
30 aerodynamic control surfaces **175** mounted to the body **110** at an aft portion thereof. Referring in particular to Fig. **4**, the aft set **174** is thus in aft spaced relationship with

- 54 -

respect to the forward set **172**, and the center of gravity CG of the body **110** is disposed longitudinally intermediate the aft set **174** and the forward set **172**, noting that the actual longitudinal position of the center of gravity CG can shift between two extreme longitudinal positions according to, *inter alia*, whether the boom member **135** is extended
5 or retracted, and whether fuel is present in the refueling device **100** or absent therefrom. In alternative variations of this example and in other examples, the center of gravity can be forward of both the forward set and the aft set of aerodynamic surfaces, which are configured to provide the required stability to the refueling device **100** with the boom axis **131** at any desired pitch and/or yaw and/or roll angle.

10 In this example, the forward set **172** comprises four aerodynamic control surfaces **173** in cruciform “X” configuration (see in particular Figs. 6(a) and 6(b)). Each aerodynamic control surface **173** is in the form of a vane, pivotably mounted to the body **110** via a respective boss **183** laterally projecting from the surface of body **110**. Each boss **183** houses an actuator (not shown) for controlling the angular position of the respective
15 vane about a respective pivot axis, and is controlled by controller **180**. The pivot axes of the vanes are, in at least this example, orthogonal to at least one of longitudinal axis **111** and boom axis **135**, and can also intersect the respective at least one of longitudinal axis **111** and boom axis **135**.

In this example, controller **180** comprises any suitable computer control system,
20 and is housed in the refueling device **100** (see Fig. 7). In alternative variations of this example and in other examples, the controller **180** or portions thereof can instead comprise any suitable electronic control unit, or any other suitable control unit. Additionally or alternatively, the controller or portions thereof can be comprised elsewhere in the in-flight refueling system **50** or in the tanker aircraft **12**.

25 In this example, the aft set **174** comprises two aerodynamic control surfaces **175** in “Vee” configuration (see in particular Figs. 6(a) and 6(b)). Each aerodynamic control surface **175** is in the form of a vane, pivotably mounted to the body **110** via a respective boss **186** laterally projecting from the surface of body **110**. Each boss **186** houses an actuator (not shown) for controlling the angular position of the respective vane, and is also
30 controlled by controller **180**.

In this example, and referring in particular to Fig. 4, each boss **183** has an aerofoil-shaped cross section defining a chord **185**, and each boss **186** has an aerofoil-shaped cross

- 55 -

section defining a chord **185**. Furthermore the chord **185** is oriented with respect to at least one of the longitudinal axis **111** and the boom axis **131** such as to align the chord **185** with the forward direction A, which is nominally the airflow direction with respect to the refueling device **100**, when the refueling device **100** is at spatial orientation in which the boom axis **131** is at angle θ_{des} with respect to the forward direction A. Similarly, each chord **185** is oriented with respect to at least one of the longitudinal axis **111** and the boom axis **131** such as to align the chord **185** with the forward direction A when the refueling device **100** is at spatial orientation in which the boom axis **131** is at angle θ_{des} with respect to the forward direction A.

In alternative variations of this example or in other examples, the forward set aerodynamic control surfaces can comprise two or three or four or more than four vanes (or any other type of aerodynamic control surfaces), in any suitable configuration, including for example four vanes in cruciform “+” configuration, and/or, each vane (or other type of aerodynamic control surfaces) can be pivotable about a respective axis having any suitable spatial relationship with respect to the longitudinal axis of the refueling device and/or the axis of the boom member. Additionally or alternatively, the aft set aerodynamic control surfaces can comprise two more than two vanes (or any other type of aerodynamic control surfaces), in any suitable configuration. Additionally or alternatively, the respective aerodynamic control surfaces of the spatial control system, in the form of pivotable vanes or any other suitable configuration, are mounted to respective bosses, which can be aerodynamically shaped but at a different orientation with respect to the longitudinal axis **111** and/or the boom axis **131**, or wherein the respective bosses can have a different shape, for example in the form of cylinders or any other prismatic shape or other shape, or wherein the respective aerodynamic control surfaces are directly mounted to the body **110** without bosses (in which case the respective actuators can be provided in the body **110**).

For example, one such alternative variation of the refueling device example of Figs. 3 to 11 is illustrated in Figs. 12(a) to 12(d), in which the respective example of the refueling device, designated **1000**, comprises all the elements and features of the refueling device **100**, *mutatis mutandis*, with the main difference that the aerodynamic control system **170** of the example of the refueling device **100** is replaced with an alternative configuration for the spatial control system **160**, comprising aerodynamic

- 56 -

system **1170**. Thus, the refueling device **1000** comprises a body **1110**, forward end **1114**, aft end **1112**, longitudinal axis **1111**, fuel delivery lumen (not shown), boom member **1130**, boom axis **1131**, fuel delivery nozzle **1135**, terminus **1136**, coupling **1140**, hose interface **1142**, substantially similar to the corresponding components as described herein for the example of the refueling device **100** or alternative variations thereof, *mutatis mutandis*, i.e., respectively: body **110**, forward end **114**, aft end **112**, longitudinal axis **111**, fuel delivery lumen **120**, boom member **130**, boom axis **131**, fuel delivery nozzle **135**, terminus **136**, coupling **140**, hose interface **142**. In addition, the refueling device **1000** optionally comprises a force generating arrangement (not shown) for example substantially similar to force generating arrangement **190** as described hereinbelow, *mutatis mutandis*, and/or a suitable data acquisition system (not shown) for example substantially similar to imaging system **150**, as described hereinbelow, *mutatis mutandis*, and/or a controller **1180**, for example similar to controller **180** as described herein, *mutatis mutandis*, and/or a control computer system (not shown), for example similar to control computer system **155** as described herein, *mutatis mutandis*.

The aerodynamic system **1170** comprises a forward set **1172** of aerodynamic control surfaces **1173** mounted to body **1110** at a forward end **1114** thereof, and an aft set **1174** of aerodynamic control surfaces **1175** mounted to the body **1110** at an aft portion **1112** thereof. The aft set **1174** is thus in aft spaced relationship with respect to the forward set **1172**, and the center of gravity of the body **1110** is disposed longitudinally therebetween, though in alternative variations of this example and in other examples, the center of gravity can be forward or aft of both the forward set and the aft set of aerodynamic surfaces, which are configured to provide the required stability to the refueling device **1000** with the boom axis **1131** at any desired pitch and/or yaw and/or roll angle.

In this example, the forward set **1172** comprises four aerodynamic control surfaces **1173** in cruciform “+” configuration, and each aerodynamic control surface **1173** is in the form of a vane, pivotably mounted to the body **1110** and operatively connected to an actuator system (not shown) for controlling the angular position of the respective vane about a respective pivot axis, and is controlled by controller **1180**. The pivot axes of the vanes are, in at least this example, orthogonal to at least one of longitudinal axis **1111** and boom axis **1135**, and can also intersect the respective at least one of longitudinal axis **1111**

- 57 -

and boom axis **1135**. In alternative variations of this example, the forward set **1172** may comprise any suitable configuration or vanes, wings, RCS, etc.

In this example, the aft set **1174** comprises a high H-tail configuration, comprising two vertical stabilizers **1175**, one on either side of a horizontal stabilizer **1171**, which in turn is mounted to the upper side of the aft end **1112**. Each vertical stabilizer **1175** comprises a controllably pivotable rudder **1178**, and the horizontal stabilizer **1171** comprises a pair of pivotable elevators **1179**, which are controllably actuated by an actuator system (not shown) also controlled by controller **1180**.

For example, four other such alternative example variations are illustrated in Fig. 13(a) to Fig. 13(d), respectively, in which for the respective refueling devices **100''a**, **100''b**, **100''c** and **100''d**, respectively, the respective forward set **172''** comprises two aerodynamic control surfaces **173''** in "Vee" configuration, and the respective aft set **174''** comprises two aerodynamic control surfaces **175''** in "Vee" configuration as in the first example, *mutatis mutandis*. In the example of Fig. 13(a) the aerodynamic control surfaces **173''** are smaller than the aerodynamic control surfaces **175''**, while in the examples of Fig. 13(b) to Fig. 13(d) the aerodynamic control surfaces **173''** are the same size nominally as the aerodynamic control surfaces **175''**. In yet other alternative variations of the example of Figs. 13(a) to 13(d), the aerodynamic control surfaces **173''** are larger than the aerodynamic control surfaces **175''**.

For example, another such alternative example variation is illustrated in Fig. 13(e), in which the respective aft set **174'** for the refueling device **100'** comprises three aerodynamic control surfaces, two aerodynamic control surfaces **175'** in "Vee" configuration as in the first example, *mutatis mutandis*, and a third vane **175''** in vertical and downwardly depending relationship with respect to the respective body **110'**.

For example, two such alternative example variations are illustrated in Figs. 14(a) and 14(b) in which the respective forward set **172'''** for each respective refueling device **100'''a**, **100'''b** comprises two aerodynamic control surfaces **173'''** with zero dihedral, and the respective aft set **174'''** also comprises two aerodynamic control surfaces **175'''** with zero dihedral. In the example of Fig. 14(b), each aerodynamic control surfaces **175'''** further comprises a vertical vane **176'''** in upwardly depending relationship with respect to the aerodynamic control surfaces **175'''** at the respective wing tips.

- 58 -

For example, in the alternative example variations illustrated in Figs. 13(a), 13(c) and 13(d), the respective forward aerodynamic control surfaces **173''** are pivotably mounted to cylindrically shaped bosses **183''**, and the respective aft aerodynamic control surfaces **175''** are pivotably mounted to cylindrically shaped bosses **185''**. On the other hand, in the examples illustrated in Figs. 13(b), 14(a) and 14(b), the respective forward and aft aerodynamic control surfaces are pivotably mounted directly to the body of the respective refueling device.

Referring again to the example of Figs. 3 to 10, the aerodynamic control system **170** is configured for allowing the refueling device **100** to adopt any desired angle θ while maintaining a zero pitching moment (and/or zero yawing moment and/or zero rolling moment), as the forward set **172** of aerodynamic control surfaces **173** is configured for trimming any pitching moment (and/or yawing moment and/or rolling moment, respectively) generated by aft set **174** of aerodynamic control surfaces **175** at a given pitch angle (and/or yaw angle and/or roll angle, respectively) of the body **110**, or vice versa. In this example, where the center of gravity CG is longitudinally intermediate the forward set **172** and the aft set **174**, the trimming pitching moment generated by the forward set **172**, for example is in a counter-rotational direction with respect to the pitching moment generated by aft set **174** to maintain a particular pitch angle for angle θ , while the pitch forces generated by forward set **172** and the aft set **174** are in the same direction. In alternative variations of this example or in other examples in which the center of gravity of the refueling device is forward of both the forward set and the aft set of aerodynamic control surfaces, the trimming pitching moment generated by the forward set of aerodynamic control surfaces, for example, is also in a counter-rotational direction with respect to the pitching moment generated by aft set of aerodynamic control surfaces to maintain a particular pitch angle for angle θ , but the pitch forces generated by forward set of aerodynamic control surfaces and the aft set of aerodynamic control surfaces are in opposite directions. In yet other examples, the refueling device comprises the spatial control system in the form of a single set of aerodynamic control surfaces which are configured for generating zero pitch moment for a desired range of pitch angles corresponding to angle θ , and the spatial control system is self-trimming to provide stable pitch angle corresponding to angle θ .

In the first example, the aft aerodynamic control surfaces **175** are larger than the forward aerodynamic control surfaces **173**, though in alternative variations of this example and in other examples, the aft aerodynamic control surfaces **175** can be the same size or smaller than the forward aerodynamic control surfaces **173**.

5 In other variations of this example and in other examples, the spatial control system **160** comprises a non-adjustable aerodynamic control system that is configured for allowing the refueling device **100** to adopt a particular, pre-set, desired angle θ while maintaining a zero pitching moment (and/or zero yawing moment and/or zero rolling moment), this being the design angle θ_{des} , at least at one set of conditions associated with
10 the refueling – for example at a particular forward speed and altitude. Thus, once the refueling device is towed behind the tanker aircraft **12** via the hose **52**, the boom axis automatically adopts the particular design angle θ_{des} , and stably maintains this relative spatial disposition at the aforesaid set of conditions until the refueling device is retracted back into the tanker aircraft **12**.

15 In other variations of this example and in other examples, the spatial control system **160** comprises a selectively controllable control system that is not based on aerodynamic control surfaces. For example, a plurality of suitable thrust nozzles or other suitable reaction control thruster system (RCS) can be mounted to the body to provide thrust vector control and maintain the boom axis **131** at any desired angle θ . Such thrusters
20 or RCS can be operatively connected to a suitable compressed air supply or compressed gas supply, for example carried by the refueling device itself, or carried by the tanker aircraft and supplied to the refueling device via pneumatic or gas lines, or generated by the tanker aircraft and/or the refueling device using a suitable compressor taking air from the atmosphere.

25 Referring in particular to Figs. 3, 4, 5, 9(a), 9(b) and 10, the refueling device **100** further comprises a force generating arrangement **190**. The force generating arrangement **190** is configured for selectively generating a force F (Figs. 9(a) to 11) along the boom axis **131** in a direction towards nozzle **135**. In this example, the force generating arrangement **190** selectively generates force F as a drag, and is in the form of a selectively and
30 reversibly deployable drag inducing arrangement **192**, comprising a selectively and reversibly deployable air brake system **194**. The air brake system **194** comprises a port air brake **195** and a starboard air brake **196**, each comprising a curved plate **197** pivotably

- 60 -

hinged laterally to the body **110** via hinges **198** between a closed position, in which the plate is received in a recess **199** (best seen in Figs. 9(a) and 9(b)) and the outer surface of the plate **197** is flush with the outer surface of body **110**, and an open position in which the plate offers a maximum frontal surface area to the airflow and thereby generates drag. The
5 hinges **199** are forwardly disposed so that the convex outer surface of each one of the port air brake **195** and of the starboard air brake **196** faces the airflow. Suitable actuators (not shown) are operatively connected to and operate the air brakes **195**, **196**, controlled by controller **180**. Alternatively, and as illustrated for the example of Fig. 13(a), the hinges **199** can be disposed aft of the respective plates **197** so that the convex outer surface of
10 each one of the port air brake **195** and the starboard air brake **196** faces away from the airflow. In the example of Fig. 13(d) the force inducing arrangement **190** is an airbrake in the form of plate **920** that is selectively laterally deployable and retractable with respect to airbrake housing **910**.

The force generating arrangement **190** is in particular configured for selectively
15 generating a force F having a magnitude sufficient for forcing the nozzle **135** into engagement with the fuel receptacle **22** of the receiver aircraft (Fig. 11) when the nozzle **135** (and the boom member **130**) and the fuel receptacle **22** are in a predetermined relative spatial disposition, i.e., when the refueling device **100** reaches an engagement enabling position and the boom axis is in the engagement enabling orientation with respect to the
20 receiver aircraft **20**, and in particular with respect to the fuel receptacle **22**.

The force generating arrangement **190** is further configured for selectively operating in this manner responsive to the nozzle **135** being in a predetermined proximity to the fuel receptacle **22**, i.e. responsive to the nozzle **135** being in a predetermined spacing with respect to the fuel receptacle **22**, typically the engagement enabling spatial position,
25 and can be operated manually or automatically to provide such a force F , as will become clearer herein.

Thus, at the engagement enabling position, when the boom member **130**, or the boom axis **131**, is in a predetermined spatial disposition with respect to the fuel receptacle **22** and the nozzle **135** being in a predetermined spacing with respect to the fuel receptacle
30 **22** (i.e., at the engagement enabling position the boom axis is at the engagement enabling orientation – corresponding to the design angle θ_{des}), the force generating arrangement **190** can be selectively actuated to compel the boom member **130** to follow a predetermined

- 61 -

trajectory, for example aligned with the boom axis **131** in the direction of the receiver aircraft **20**, to ensure alignment and engagement between the nozzle **135** and the fuel receptacle **22**. In this example, the boom **130** is telescopically extended to the extended position in a direction along the boom axis **131**, which is maintained at the engagement enabling orientation – corresponding to the design angle θ_{des} , while the body **110** remains at the same spatial disposition with respect to the receiver aircraft **20**. In alternative variations of this example, the boom **130** is partially or fully telescopically extended towards the receiver aircraft **20** while the device **100** can be moved towards or away from the receiver aircraft **20** to effect engagement between the nozzle **135** and the fuel receptacle **22**. In other alternative variations of this example, the boom member **130** remains retracted, and the body **110** itself is moved towards the receiver aircraft **20** along a the direction of the boom axis, maintaining the boom axis **131** at the engagement enabling orientation – corresponding to the design angle θ_{des} , to effect engagement between the nozzle **135** and the fuel receptacle **22**.

Once the nozzle **135** is forced into engagement with the fuel receptacle **22** of the receiver aircraft **20**, the tanker aircraft **12** can begin refueling the receiver aircraft **20**.

In alternative variations of this example and in other examples, the force generating arrangement **190** can comprise any other suitable drag inducing arrangement, for example spoilers on the vanes **175**.

In yet other variations of this example and in other examples, the force generating arrangement **190** can be configured for generating a thrust force in the required direction. For example, one or a plurality of suitable thrust nozzles can be mounted to the body to provide the required thrust vector parallel to the boom axis **131** towards nozzle **135**. Such thrust nozzle(s) can be operatively connected to a suitable compressed air or compressed gas supply, for example carried by the refueling device itself, or carried by the tanker aircraft and supplied to the refueling device via pneumatic or gas lines, or generated by the tanker aircraft and/or the refueling device.

In yet other alternative variations of this example and in other examples, the force generating arrangement can be omitted, and for example the receiver aircraft and/or the boom member can comprise suitable means for mechanically engaging the nozzle to the fuel receptacle that does not require such a force F to be generated by the device **100**. For example, the fuel receptacle can comprise a suitable mechanical clamp that engages the

- 62 -

terminus **136** of the boom member **130**, and pulls in the nozzle **135** into engagement with the fuel receptacle **22**.

Referring in particular to Figs. 4, 5, 10 and 11 the refueling device **100** further comprises a suitable data acquisition system for providing or enabling the calculation of spatial data relating to the relative spatial dispositions between the refueling device **100** and the receiver aircraft **20**, in particular the relative spatial dispositions between the fuel delivery nozzle of the refueling device **100** and the fuel receptacle of the receiver aircraft, to enable selectively controlling the refueling device to provide automatic (optionally including autonomous) and/or manual steering of the refueling device **100** to the engagement enabling position and subsequent selective engagement of the fuel delivery nozzle to the fuel receptacle of the receiver aircraft. At least in the example of Figs. 4, 5, 10 and 11, the data acquisition system is in the form of imaging system **150**, in particular configured for providing imaging data of any object coming within a field of regard (FOR) aft of the refueling device **100**. Such a field of regard has a predetermined depth aft of the imaging system and in this example comprises sensing volume **159** aft of the imaging system **150**, which while in this example comprises a prismoidal volume in alternative variations of this example the FOR can have any suitable shape, for example conical, frustoconical, cylindrical, spherical, part-spherical (e.g. hemispherical), parallelepiped (for example cubic) or any other regular or irregular shape. The sensing volume **159**, i.e., the predetermined depth of the **FOR**, extends aft further than is required corresponding to the engagement enabling position, i.e., further than the maximum extension of the boom member **130** when this is in its fully deployed position. The imaging system **150** is operatively connected to a control computer system **155**, which can be integral with, connected to, or independent from controller **180** (see Fig. 8). In particular, and referring particularly to Figs. 10 and 11, such an object is the receiver aircraft **20** and more particularly a part **AP** thereof including the fuel receptacle **22**, and the sensing volume **159** defines an outer envelope limit **158** in which image data of part **AP** can be processed, inter alia, by control computer system **155** to provide control signals, for example steering commands, to the spatial control system **160** and/or the force generating arrangement **190**, for example via controller **180** to control operation of the refueling device **100**, in particular the relative spatial position and orientation of the refueling device **100** with respect to the receiver aircraft **20**, in particular the position and orientation of the boom member **130** and nozzle **135** with respect to the fuel receptacle **22**, so that the nozzle **135**

- 63 -

can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and effective manner. The manner of operation of the imaging system **150** and control computer system **155** will be described in greater detail further herein.

In this example, the imaging system **150** comprises two pairs of flash ladar units **151**, also referred to interchangeably herein as FLADAR units, one pair on the trailing edge of each boss **186**. Suitable FLADAR units can include, for example, a PMD [vision]® CamCube 3.0, provided by PMD Technologies, Germany, and adapted for operating within the refueling unit and at the flight conditions thereof.

In operation the FLADAR units **151** illuminate the sensing volume **159** and any object therein, in particular part AP of the receiver aircraft **20** and thereafter acquire suitable image data corresponding thereto which is sent to control computer system **155** for processing to provide the aforesaid control signals for controlling the refueling device **100**. In particular, by means of the FLADAR units **151**, a **3D** image of the areas AP is reconstructed, and manipulated via a computer system to determine the relative position and orientation of the nozzle **135** with respect to the fuel receptacle **22**.

The sensing volume **159** thus includes the engagement enabling position.

In alternative variations of this example and in other examples, the imaging system **150** can comprise any other suitable imaging system (for example, but not limited to, systems providing **2D** images and/or stereoscopic images and/or **3D** images of (including reconstruction of **3D** data corresponding to) the sensing volume **159**, in particular but not limited to images that are updated in real time, for example in the form of a video stream) that operate to provide suitable data to the control computer system **155** to, in turn, enable selectively controlling the refueling device **100** to provide autonomous and/or manual engagement of the nozzle **135** to the fuel receptacle **22** of the receiver aircraft **20**.

In alternative variations of this example, the imaging system **150** can be replaced with any other suitable data acquisition system for providing the aforesaid spatial data.

In yet other alternative variations of this example and in other examples, the refueling device **100** can omit the imaging system **150** and can be actively controlled by an operator, for example, to control the relative spatial position and orientation of the refueling device **100** with respect to the receiver aircraft **20**, in particular the spatial position and orientation of the boom member **130** and/or nozzle **135** with respect to the

- 64 -

fuel receptacle **22**, so that the nozzle **135** can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and effective manner, for example via direct visual tracking of the device by the operator. Alternatively, the refueling device can be operated as a free flying refueling device towed at the end of hose **52**, and the relative spatial position and orientation of the refueling device **100** with respect to the receiver aircraft **20** (in particular the position and orientation of the boom member **130** and nozzle **135** with respect to the fuel receptacle **22**, so that the nozzle can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and effective manner) is achieved by maneuvering the receiver aircraft only. In such a case, the spatial control system **160** can optionally comprise a non-adjustable aerodynamic stability system that is configured for allowing the refueling device **100** to adopt a particular, pre-set, desired angle θ while maintaining a zero pitching moment (and/or zero yawing moment and/or zero rolling moment), this being the design angle θ_{des} as discussed above for example.

Optionally, a suitable air-driven generator can be provided in the refueling device **100** to provide electrical power thereto. Additionally or alternatively, electrical power can be provided to the refueling device **100** by the tanker aircraft **12**. Additionally or alternatively, electrical power can be provided to the refueling device **100** by one or more batteries in the refueling device **100**. Additionally or alternatively, electrical power can be provided to the refueling device **100** by one or more ram air turbines (RAT), affixed internally or externally with respect to the refueling device **100**.

In at least some alternative variations of the first example the refueling device can comprise an aerodynamic stabilizer arrangement, different from the spatial control system **160** or from the force generating arrangement **190**. For example, each one of the alternative example variations illustrated in Figs. 13(c) and 13(d) comprises such an aerodynamic stabilizer arrangement in the form of a respective drogue structure **180''** fixed to the aft portion of the body. Such a drogue structure **180''** can be utilized for generating a drag which in turn induces a tension to the hose **52**, thereby aiding reduction or dampening of vibrations or oscillations in the hose **52** that can otherwise occur. Such a drogue structure can also be provided for other examples, for example the first example illustrated in Fig. 3 or alternative variations thereof.

In the example of Figs. 15(a) to 15(d), the respective refueling device **100E** comprises an aerodynamic stabilizer arrangement in the form of a drogue structure **180E**

- 65 -

forwardly spaced from a forward end **114E** of the frustoconical body **110E** of refueling device **100E** by a length pipe **52E**, which is flexible but can be articulated instead, and the body **110E** comprises a spatial control system **160E** comprising a selectively controllable aerodynamic control system **170E**, comprising a forward set **172E** of two swept back
5 aerodynamic control surfaces **173E** mounted directly to body **110E** at a forward portion thereof, and an aft set **174E** of two aerodynamic control surfaces **175E** directly mounted to the body **110E** at an aft portion thereof in “Vee” configuration, a deployable airbrake system **190E** provided on the aft end of multi-segmented telescopic boom **130E**, which comprises a nozzle **135E** at the terminus **136E** thereof.

10 The in-flight refueling systems **50** including the first example of the refueling device **100** or at least some alternative variations thereof, can be operated in a number of different ways to provide selective engagement of the nozzle **135** with the fuel receptacle **22** of a receiver aircraft **20**, and enable subsequent refueling of the receiver aircraft **20** from the tanker aircraft **12** in flight, for example as disclosed herein.

15 Referring to Figs. 16(a) to 16(d), a second example of the refueling device, designated herein with reference numeral **200**, comprises the elements and features of the first example and/or of at least some alternative variations thereof, *mutatis mutandis*, with some differences, as will become clearer herein, and the refueling device **200** is configured for use with an in-flight refueling system, for example at least one of the in-flight refueling
20 systems **50** illustrated Figs. 1 and 2.

For convenience, and referring to Fig. 16(a) for example, a roll axis **R**, a pitch axis **P** and a yaw axis **Y** can be conventionally defined with respect to the refueling device **200**. The roll axis **R** is parallel to or co-axial with the longitudinal axis **211** of the device **200**; the pitch axis **P** is generally in lateral and orthogonal relationship to the roll axis **R** (i.e.,
25 parallel to the horizontal when the body is at a zero roll angle); and yaw axis **Y** is in orthogonal relationship to the roll axis **R** the pitch axis **P** (i.e., parallel to the vertical when the body is at a zero pitch angle).

Refueling device **200** is affixed to the end **54** of hose **52** and comprises body **210** comprising a longitudinal axis **211**, a fuel delivery lumen **220**, and a substantially rigid
30 boom member **230** in fluid communication therewith. The boom member **230** comprises a plurality of telescopic elements **232**, defines a boom axis **231**, and comprises a fuel delivery nozzle **235** at a terminus **236** of the boom member **230**. The nozzle **235** is

- 66 -

configured for reversibly engaging with the fuel receptacle **22** of a receiver aircraft **20**, and thus can be similar to the nozzle **135** of the first example and as disclosed above, *mutatis mutandis*.

The boom member **230** is telescopically and pivotably mounted to body **210** about
5 axis C (generally parallel to the pitch axis P of the body **210**), and is reversibly movable from a stowed position in which the telescopic elements **232** are retracted and nested in one another and the boom member **230** is pivoted about axis C into a position accommodated in body **210** (wherein optionally the boom axis **231** can be generally parallel to longitudinal axis **211**), to a deployed position illustrated in Figs. 16(a) and
10 16(b). In the deployed position, the boom member **230** can be, by means of a controllable actuation mechanism (not shown), controllably variably extended in an aft direction from the aft end **212** of body **210**, up to the fully extended position illustrated in Figs. 16(a) and 16(b), and/or variably pivoted about pivot axis C in a downward direction to provide a non-zero angular displacement, angle θ' , between boom axis **231** and longitudinal axis
15 **211**. In this example, angle θ' is in pitch, though in alternative variations of this example angle θ' may also include angular components in yaw and/or roll. Such angular components in yaw and/or roll may be additionally provided by suitably orienting the device **200** with respect to the yaw axis **Y** and/or roll axis **R**, respectively. In variations of this example where the boom axis **231** can only be pivoted with respect to the body **210**
20 about an axis parallel to the pitch axis **P**, such angular components in yaw and/or roll may be alternatively and exclusively provided by suitably orienting the device **200** with respect to the yaw axis **Y** and/or roll axis **R**, respectively.

The body **210** optionally comprises a coupling **240** at forward end **214** thereof, similar to the coupling **140** of the first example or alternative variations thereof and as
25 disclosed above, *mutatis mutandis*.

The refueling device **200** further comprises a spatial control system **260**, configured for controlling a spatial disposition of the refueling device **200** when towed aft of the tanker aircraft **12** via the hose **52**. In particular, spatial control system **260** is configured for selectively and controllably providing a non-zero angular disposition,
30 angle θ , between the boom axis **231** and the forward direction A, and enables this angle θ to be selectively maintained between the boom axis **231** and the forward direction A when the refueling device **200** is being towed by the tanker aircraft **12** via hose **52**,

- 67 -

similar to the corresponding feature of the first example or alternative variations thereof and as disclosed above, *mutatis mutandis*. Thus, in particular, angle θ is in pitch, i.e., about a pitch axis **P** of the refueling device **200** and is defined on a plane including the roll axis **R** and the yaw axis **Y** of the refueling device **200**. Nevertheless, and depending on specific conditions during any particular refueling operation, angle θ can instead include an angular displacement component between the boom axis **231** and the forward direction **A** in yaw (i.e., about yaw axis **Y**) for example due to sideslip angle, and/or in roll (i.e. about roll axis **R**), in addition to an angular displacement component in pitch (i.e., about pitch axis **P**).

Thus, the spatial control system **260** is configured for controllably flying the refueling device **200**, and for providing stability to the refueling device **200**, while tethered and towed via the hose **52**, and while the boom axis **231** is at any desired pitch and/or yaw and/or roll angle corresponding to the aforesaid angle θ , and in particular, angle θ is a design angle (angle θ_{des}) is within a particular angular range which corresponds to the design relative angular position of the boom member **230** (and boom axis **231**) with respect to the receiver aircraft **20** similar to the corresponding feature of the first example or alternative variations thereof and as disclosed above, *mutatis mutandis*.

In the second example, though, at least a part of angle θ , in particular a part of the design angle θ_{des} is provided by angle θ' , i.e., by pivoting the boom member **230** about axis **C**, depending on the magnitude of angle ϕ , which is the relative angular disposition between the longitudinal axis **211** and the forward direction **A**. The angle ϕ can be positive (as illustrated in Fig. 16(b)), representing a positive angle of attack of body **210** with respect to forward direction **A**. Alternatively, angle ϕ can be negative, or zero.

In this example, the spatial control system **260** is configured for providing a zero or near zero angle ϕ when the boom member **230** is in its deployed position pivoted at angle θ' , and comprises a selectively controllable aerodynamic control system **270**. The aerodynamic control system **270** comprises a forward set **272** of aerodynamic control surfaces **273** in the form of low aspect ratio wing members fixedly mounted to body **210** at a forward portion thereof and having controllably movable ailerons **271**. The aerodynamic control system **270** further comprises an aft set **274** of aerodynamic control surfaces **275** mounted to the body **210** at an aft portion thereof in “Vee” configuration. The spatial

- 68 -

control system **260** is also configured for providing the required pivoting angle θ' so that angle θ' together with angle ϕ provide the desired angle θ between the boom axis **231** and the forward direction A in order to maintain the required design angle θ_{des} between the boom axis **231** and the longitudinal axis of the receiver aircraft **20**. Thus, angle θ (which
5 can have an angular component in yaw and/or in pitch and/or in roll) compensates for any off-nominal pitch of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction A at a non-zero angle of attack) and/or for any off-nominal roll of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction A at a non-zero roll angle) and/or for any off-nominal yaw of the receiver aircraft **20** (for
10 example if the receiver aircraft **20** is traveling along direction A at a non-zero sideslip angle) to ensure that the actual angular disposition between the boom axis **231** and the receiver aircraft longitudinal axis is maintained at design angle θ_{des} even as the relative spatial orientation between the receiver aircraft **20** and the forward direction A changes.

In other variations of the example and in other examples, the spatial control system
15 **260** can be similar to the corresponding feature of the first example or alternative variations thereof and as disclosed above, *mutatis mutandis*.

The refueling device **200** can optionally further comprise a force generating arrangement (not shown), similar to the corresponding feature of the first example or alternative variations thereof and as disclosed above, *mutatis mutandis*.

20 The refueling device **200** can optionally further comprise a suitable spatial data acquisition system including an imaging system (not shown), similar to the corresponding feature of the first example or alternative variations thereof and as disclosed above, *mutatis mutandis*, or can omit such an imaging system and can be actively controlled by an operator, for example, similar to the corresponding feature of the first example or
25 alternative variations thereof and as disclosed above, *mutatis mutandis*.

The in-flight refueling systems **50** including the second example of the refueling device **200**, and at least some alternative variations thereof, can also be operated in a number of different ways to provide selective engagement of the nozzle **235** with the fuel receptacle **22** of a receiver aircraft **20**, and enable subsequent refueling of the receiver
30 aircraft **20** from the tanker aircraft **12** in flight.

- 69 -

Referring to Figs. 17(a) to 17(e), a variation of the second example of the refueling device, designated herein with reference numeral **200B**, comprises the elements and features of the second example of the refueling device and/or of at least some alternative variations thereof, and/or of the first example of the refueling device and/or of at least
5 some alternative variations thereof, *mutatis mutandis*, with some differences, as will become clearer herein. In a similar manner thereto, the refueling device **200B** is also configured for use with an in-flight refueling system, for example at least one of the in-flight refueling systems **50** illustrated Figs. 1 and 2.

For convenience, and referring to Fig. 17(a) for example, a roll axis **R**, a pitch axis
10 **P** and a yaw axis **Y** can be conventionally defined with respect to the refueling device **200B** in a similar manner to that of the second example of Figs. 16(a) to 16(d), *mutatis mutandis*. Thus, for example, the roll axis **R** is parallel to or co-axial with the longitudinal axis **211B** of the device **200B**, while the pitch axis **P** and the roll axis **R** each are in orthogonal relationship to the roll axis **R**.

Refueling device **200B** is affixed to the end **54** of hose **52** and comprises body
15 **210B** in the form of an elongate fuselage and comprising a longitudinal axis **211B**. The refueling device **200B** also comprises a substantially rigid boom member **230B**, which defines a boom axis **231B**, and comprises a fuel delivery nozzle **235B** at a terminus **236B** of the boom member **230B**. The nozzle **235B** is configured for reversibly engaging with
20 the fuel receptacle **22** of a receiver aircraft **20**, and thus can be similar to the nozzle **235** of the second example of nozzle **135** of the first example, or of alternative variations thereof, and as disclosed above, *mutatis mutandis*.

In this variation of the second example, the boom member **230B** has a fixed axial length and is thus not extensible, providing for a relatively simple construction. However,
25 optionally, the boom member **230B** can instead comprise a plurality of telescopic elements, for example similar to the plurality of telescopic elements **232** of the second example of refueling device **200** illustrated in Figs. 16(a) to 16(d), *mutatis mutandis*.

The boom member **230B** is pivotably mounted to body **210B** about axis **C** (generally parallel to the pitch axis **P** of the body **210B**) at pivot joint **219B**, and is
30 reversibly pivotable between a stowed or retracted position and a deployed position.

- 70 -

In the stowed or retracted position, illustrated in Fig. 17(a), boom member **230B** is pivoted about axis **C** into a position where the terminus **236B** is closest to the underside of body **210**. In this position, the boom axis **231** is generally parallel to and displaced away from longitudinal axis **211B** in a downward direction with respect to body **210B**. In the
5 deployed position illustrated in Fig. 17(b), boom member **230B** is variably pivoted about pivot axis **C** in a downward direction to provide a non-zero angular displacement, angle θ' , between boom axis **231B** and longitudinal axis **211B** (best seen in Fig. 17(c)). In this example, angle θ' is in pitch with respect to the refueling device **200B**.

In any case, in the retracted position, the boom axis **230B** is at a smaller angular
10 disposition with respect to said longitudinal axis **211B** than in the deployed position. For example, in the retracted position the boom axis **230B** is at an angular disposition with respect to said longitudinal axis **211B** of 0° , or 15° , or between 0° and 15° , for example any one of 1° , 2° , 3° , 4° , 5° , 6° , 7° , 8° , 9° , 10° , 11° , 12° , 13° , 14° . For example, in the
15 deployed position the boom axis **230B** is at an angular disposition with respect to said longitudinal axis **211B** of greater than 15° , for example 20° , or 45° , or between 20° and 40° , or between 20° and 45° , for example any one of 21° , 22° , 23° , 24° , 25° , 26° , 27° , 28° , 29° , 30° , 31° , 32° , 33° , 34° , 35° , 36° , 37° , 38° , 39° , 40° , 41° , 42° , 43° , 44° .

In general the boom member **230B** is in the deployed position at least during in-flight refueling operation of the device **200B**.

20 An actuation mechanism **290B** is provided for controllably pivoting the boom member **230B** between the stowed or retracted position and the deployed position. Actuation mechanism **290B** includes an articulated strut **291B** comprising upper strut **292B** connected to lower strut **293B** at pivoting joint **294B**. The upper strut **292B** is pivotably connected to an underside of body **210B**, while the lower strut **293B** is pivotably
25 connected to an upper side of boom member **230B**. An actuator (not shown) operates to selectively and effectively bring close or distance away the pivoting joint **294B** with respect to the body **210B**. At the maximum distancing away of the pivoting joint **294B**, illustrated in Figs 17(b), 17(c) and 17(d), the upper strut **292B** is aligned with (i.e., at about 180° with respect to) the lower strut **293B**, and as the pivoting joint **294** is brought closer
30 to the body **210B**, the articulated strut **291B** adopts a V-configuration, where the pivot angle between upper strut **292B** and the lower strut **293B** at the pivoting joint **294B** progressively reduces from about 180° (at the fully deployed position) to about 0° (at the

- 71 -

stowed or retracted position). The actuator or actuation mechanism **290B** can be configured to selectively lock the articulated strut **291B** only at each one of the stowed/retracted position and the deployed position, to provide a fixed angle θ' ; alternatively, the actuator or actuation mechanism **290B** can be configured to selectively
5 lock the articulated strut **291B** at each one of the stowed/retracted position and the deployed position, and at any angular disposition therebetween, to provide a variable angle θ' .

Other alternative configurations for actuation mechanism **290B** are of course possible.

10 Angular components in yaw and/or roll can be provided to the boom axis **231B** with respect to the forward direction **A** by suitably orienting the device **200B** with respect to the yaw axis **Y** and/or roll axis **R**, respectively.

The boom member **230B** comprises a coupling **240B** at forward end **214B** thereof, fixed to the underside of body **210B**. The coupling **240B** is similar to the coupling **240** of
15 the second example or alternative variations thereof, or of coupling **140** of the first example or alternative variations thereof, and as disclosed above, *mutatis mutandis*. Furthermore, the pivot joint **219B** can be part of coupling **240B**, or integrated therewith, or can be affixed thereto and/or to the body **210**. The coupling **240B** is connected to the body **210B** for example at the underside of the body **210B**.

20 The refueling device **200B** further comprises a spatial control system **260B** and an aerodynamic stabilizer arrangement, different from the spatial control system **260B**. For example, the aerodynamic stabilizer arrangement is in the form of a respective drogue structure **280B** fixed to the aft portion of the body **210**. Referring to Figs. 17(a) and 17(b) respectively, the drogue structure **280B** has an inactive (or stowed) configuration, in which
25 drogue structure **280B** generates minimum drag, and an active (or deployed) configuration in drogue structure **280B** generates more drag than in the inactive configuration, up to a maximum drag. Such a drogue structure **280B** can be utilized for generating a drag (when in the active configuration of Fig. 17(b)) which in turn induces a tension to the hose **52**, thereby aiding reduction or dampening of vibrations or oscillations in the hose **52** that can
30 otherwise occur.

- 72 -

The spatial control system **260B** is configured for controlling a spatial disposition of the refueling device **200B** when towed aft of the tanker aircraft **12** via the hose **52**. In particular, and in a similar manner to the second example illustrated in Figs. 16(a) to 16(d), *mutatis mutandis*, spatial control system **260B** is also configured for
5 selectively and controllably providing a non-zero angular disposition, angle θ , between the boom axis **231B** and the forward direction A, and enables this angle θ to be selectively maintained between the boom axis **231B** and the forward direction A when the refueling device **200B** is being towed by the tanker aircraft **12** via hose **52**, also similar to the corresponding feature of the first example or alternative variations thereof
10 and as disclosed above, *mutatis mutandis*.

Thus, in particular, angle θ is in pitch, i.e., about a pitch axis **P** of the refueling device **200B** and is defined on a plane including the roll axis **R** and the yaw axis **Y** of the refueling device **200B**. Nevertheless, and depending on specific conditions during any particular refueling operation, angle θ can instead include an angular displacement
15 component between the boom axis **231B** and the forward direction A in yaw (i.e., about yaw axis **Y**) for example due to sideslip angle, and/or in roll (i.e. about roll axis **R**), in addition to an angular displacement component in pitch (i.e., about pitch axis **P**).

Thus, the spatial control system **260B** is configured for controllably flying the refueling device **200B**, and for providing stability to the refueling device **200B**, while
20 tethered and towed via the hose **52**, and while the boom axis **231B** is at any desired pitch and/or yaw and/or roll angle corresponding to the aforesaid angle θ , and in particular, angle θ is a design angle (angle θ_{des}) is within a particular angular range which corresponds to the design relative angular position of the boom member **230B** (and boom axis **231B**) with respect to the receiver aircraft **20** similar to the corresponding feature of the first
25 example or alternative variations thereof and as disclosed above, *mutatis mutandis*.

As with the first example of the refueling device or alternative variations thereof, or of the second example of the refueling device or other alternative variations thereof, the spatial control system **260B** of refueling device **200B**, in particular the selectively controllable aerodynamic control system **270B**, is configured for enabling the device **200B**
30 to be steered in one, two, or three degrees of freedom in translation and in one, two, or three degrees of freedom in rotation, independently of the tanker aircraft **12** or of the

- 73 -

refueling aircraft **20**. Thus, the spatial control system **260B**, in particular the selectively controllable aerodynamic control system **270B**, is configured providing:

- one or more of: sideslip, up/down translation, forward-aft translation, relative to the tanker aircraft **12** and/or to the refueling aircraft **20**, independently of rotational moments in roll pitch and/or yaw;
- and/or
- rotational moments in one or more of roll pitch and/or yaw, relative to the tanker aircraft **12** and/or to the refueling aircraft **20**, independently of sideslip, up/down translation, forward-aft translation.

The spatial control system **260B** is also configured for providing an angle of attack for the body **210B** with respect to the forward direction, for example up $\pm 10^\circ$.

In this variation of the second example of refueling device **200B**, though, at least a part of angle θ , in particular a part of the design angle θ_{des} is provided by angle θ' , i.e., by pivoting the boom member **230B** about axis C, depending on the magnitude of the relative angular disposition ϕ between the longitudinal axis **211B** and the forward direction A, referring to Fig. 17(c). This angular disposition can be positive, representing a positive angle of attack of body **210B** with respect to forward direction A, or can be negative, or can be zero. In this variation of the second example, the spatial control system **260B** is configured for providing a zero or near zero said angular disposition when the boom member **230B** is in its deployed position pivoted at angle θ' .

The spatial control system **260B** comprises a selectively controllable aerodynamic control system **270B**. In this variation of the second example of the refueling device **200B**, the aerodynamic control system **270B** comprises a forward set **272B** of aerodynamic control surfaces **273B** and an aft set **274B** of aerodynamic control surfaces **275B**.

Furthermore, in the example of Figs. 17(a) to 17(e), the a forward set **272B** of aerodynamic control surfaces **273B** is in the form of four canards **273K** in cruciform "X" arrangement around a forward part of the body **210**, while the aft set **274B** of control surfaces **275B** is in the form of a H-tail, in particular a high, cropped delta wing **276B**, mounted to the upper aft part of body **210**, and comprising vertical fins **277B** above and below port and starboard wing tip elements **278B** of the cropped delta wing **276B**. The forward canards **273K** can be fixed, or instead can be pivotable, or instead can comprise

- 74 -

pivotal surfaces to provide control moments to the device **200B**. The delta wing **276B**, and/or vertical fins **277B**, are each pivotable or can instead comprise pivotable surfaces to provide control moments to the refueling device **200B**.

However, other arrangements are possible for selectively controllable aerodynamic control system **270B** and/or for the body **210B**.

For example the forward set **272B** of aerodynamic control surfaces **273B** and/or the aft set **274B** of aerodynamic control surfaces **275B** can each be configured to have any one or more of the following features, in any combination:

- 10 - monoplane configuration, including any one of: high wing configuration (or shoulder wing configuration), low wing configuration or mid wing configuration - mounted on or near an upper part, a lower (bottom) part of inbetween the upper and lower part, respectively, of the body **210**; parasol wing configuration - mounted to the body **210B** via cabane struts of the like; shoulder wing configuration;
- 15 - biplane, triplane, quadruplane, multiplane configurations, having two, three four, or more than four wing plane elements, respectively, of similar size or dissimilar size with respect to one another, stacked one above the other in unstaggered, or forward staggered, or backwards staggered arrangement;
- 20 - combined or closed wing configurations, in which two or more wing elements are joined structurally at or near the respective wing tips in some way; for example a box wing configuration, in which at least one set of overlying (staggered or unstaggered) wing elements is joined together between their tips by vertical fins; tandem box wings; rhomboidal wings in which at least one set of overlying wing elements has a forward swept wing plane and a swept back wing plane, joined between the tips directly or via a vertical fins; annular or ring wing, which can be flat (in the form of the rim of a flat disc) or cylindrical (the wing is shaped as a cylinder), for example;
- 25 - at least one wing element is cantilevered (self-supported) and/or externally supported to the body **210** via struts and/or braces;
- 30 - wings elements, wherein each can comprise low aspect ratio, moderate aspect ratio or high aspect ratio;

- 75 -

- 5 - wings elements, wherein each wing element can be swept forward or swept back or have zero sweep, and/or the sweep angle can be fixed or varied along the span, and/or each wing element can have fixed wing geometry or variable wing geometry, for example variable sweep or oblique wing configurations;
- 10 - wings elements, wherein each wing element can have a respective wing chord that can be fixed or varied along the span of the wing element, for example including at least one of the following plan shapes: elliptical plan; constant chord plan, tapered plan; trapezoidal plan; reverse tapered plan; compound tapered plan;
- 15 - wings elements, wherein each wing element can be based on a delta design, including at least one of the following: regular delta; cropped delta (wing tip is cropped) compound delta; double delta; ogival delta;
- wings elements, wherein each wing element can have dihedral or anhedral angle;
- 20 - wings elements, wherein the wing elements can be formed as fins, for example in cruciform "X" or cruciform "+" configuration, or having one, two, three, four, or more than four fins arranged on the body **210B** in any geometrical arrangement;
- 25 - wings elements, wherein the wing elements can comprise vertical fins or the like, attached on the upper part and/or the lower part at any spanwise position including the tip; and/or the fins can be swept forward or swept back or have zero sweep, and/or sweep angle can be fixed or varied along the span, and/or each vertical fin can have fixed wing geometry or variable wing geometry, for example variable sweep or oblique wing configurations;
- 30 - each wing element can be fixed, or can be movably mounted to the body **210** and fully pivotable to operate independently as an integral control surface, or can be fixedly mounted to the body **210** and comprises a pivotal control surface;

- 76 -

- each wing element can be movably mounted to the body **210** to allow for selective relative translational movement therebetween.

For example the forward set **272B** of aerodynamic control surfaces **273B** can have
5 any suitable configuration regarding its geometrical and spatial relationship with respect to the aft set **274B** of aerodynamic control surfaces **275B**, for example as follows:

- conventional configuration, in which the forward set **272B** of aerodynamic control surfaces **273B** forms the main lift-generating wing arrangement of the device **200B**, while the aft set **274B** of aerodynamic control surfaces **275B**,
10 forms part of the stabilizer or tail;
- canard configuration, in which the aft set **274B** of aerodynamic control surfaces **275B** forms the main lift-generating wing arrangement of the device **200B**, while the forward set **272B** of aerodynamic control surfaces **273B** can be in the form of canards or fins as the stabilizer;
- 15 - tandem configuration, in which both the aft set **274B** of aerodynamic control surfaces **275B** and the forward set **272B** of aerodynamic control surfaces **273B** are configured to provide lift and to provide stability;
- tailless configuration, in which the forward set **272B** of aerodynamic control surfaces **273B** is omitted, and the aft set **274B** of aerodynamic control surfaces
20 **275B** is configured to provide lift and to provide stability;
- three-surface or triplet configuration, in which in which the aft set **274B** of aerodynamic control surfaces **275B** forms the main lift-generating wing arrangement of the device **200B**, while the forward set **272B** of aerodynamic control surfaces **273B** can be in the form of canards or fins forming part of the
25 stabilizer, and further comprising a third set of aerodynamic control surfaces aft of the aft set **274B** of aerodynamic control surfaces **275B**, forms part of the stabilizer.

For example the forward set **272B** of aerodynamic control surfaces **273B** and/or the aft set **274B** of aerodynamic control surfaces **275B** can be blended with the body **210B**
30 to provide a blended body configuration.

- 77 -

For example one of the forward set **272B** of aerodynamic control surfaces **273B** and/or the aft set **274B** of aerodynamic control surfaces **275B** can be omitted, and the other one of forward set **272B** of aerodynamic control surfaces **273B** and/or the aft set **274B** of aerodynamic control surfaces **275B** can be formed as a flying wing configuration, incorporating therein the functions of body **210B**, which can then be omitted.

For example the forward set **272B** of aerodynamic control surfaces **273B** and/or the aft set **274B** of aerodynamic control surfaces **275B** can both be omitted, and the body **210** can be formed as a lifting body, integrally providing the functions of the aerodynamic control system **270B**.

For example, the aerodynamic control system **270B** can be replaced with or supplemented by reaction control thrusters.

Thus, for example, and referring to Figs. 17(f) and 17(g), the aerodynamic control system **270B** comprises a canard configuration, in which: the forward set **272B** of aerodynamic control surfaces comprises canards, for example comprising two horizontal, swept, zero taper canards **273C** in mid-wing configuration, one on each side of the body **210B**, and optionally including vertical swept-back zero taper fins **273D** above and/or below the canards **273C** at the respective tips thereof; the aft set **274B** of aerodynamic control surfaces can be in the form of a H-tail, in particular comprising two horizontal, swept, zero-taper wing elements **273E** in high-wing configuration, on the upper part of the body **210B**, and optionally including fins, for example vertical swept-back zero taper fins **273F** above and below the wing elements **273E** at the respective tips thereof. In this example, one or more of the canards **273C**, fins **273D**, wing elements **273E** and fins **273F**, is fully pivotable to operate independently as an integral control surface or is fixedly mounted to the body **210** and comprises a pivotal control surface. Optionally, one or more of the canards **273C**, fins **273D**, wing elements **273E** and fins **273F**, can be movably mounted to the body **210** to allow for selective relative translational movement therebetween.

In another example, and referring to Fig. 17(h), the aerodynamic control system **270B** comprises a canard configuration, in which: the forward set **272B** of aerodynamic control surfaces comprises a canard configuration, for example comprising two horizontal, swept, zero taper canards **273C** in mid-wing configuration, one on each side of the body **210B**, and optionally including vertical swept-back zero taper fins **273D** above and below

- 78 -

the canards **273C** at the respective tips thereof; the aft set **274B** of aerodynamic control surfaces can be in the form of a H-tail, in particular comprising two horizontal, swept, zero-taper wing elements **273G** in mid-wing configuration, one on each side of the body **210B**, and optionally including fins, for example vertical swept-back zero taper fins **273H** 5 above and below the wing elements **273G** at the respective tips thereof. In this example, one or more of the canards **273C**, fins **273D**, wing elements **273G** and fins **273H**, is fully pivotable to operate independently as an integral control surface or is fixedly mounted to the body **210** and comprises a pivotal control surface. Optionally, one or more of the canards **273C**, fins **273D**, wing elements **273G** and fins **273H**, can be movably mounted to 10 the body **210** to allow for selective relative translational movement therebetween.

It is to be noted that in other variations of the second example, and in other examples, of the refueling device **200**, the respective spatial control system **260** can be similar to the spatial control system **260B** the variation of the example of the refueling device **200B** or alternative variations thereof and as disclosed above, *mutatis mutandis*.

15 The refueling device **200B** can optionally further comprise a force generating arrangement (not shown), similar to the corresponding feature of the first example or alternative variations thereof and as disclosed above, *mutatis mutandis*, and/or can be operated in a corresponding manner.

In the variations of the second example illustrated in Figs. 17(a) to 17(h), a 20 respective force generating arrangement **295B** is configured for selectively generating a force **FB** (see Fig. 17(c)) along the boom axis **231B** in a direction towards nozzle **235B**.

In these variations of the second example, the force generating arrangement **290B** comprises (a) at least some elements of the spatial control system **260B**, in particular the selectively controllable aerodynamic control system **270B**; and optionally (b) at least some 25 elements of the aerodynamic stabilizer arrangement, in particular in the form of a respective drogue structure **280B**.

The force generating arrangement **290B** is configured for selectively generating force **FB** in a direction aligned with the boom axis **231B** by generating a negative lift force **LF** (or reducing the lift force by force **LF**) and a drag force **LD**, which together provide 30 force **FB** of the required magnitude and vector. The negative lift force **LF** can be generated by suitably controlling the spatial control system **260B**, in particular the selectively

- 79 -

controllable aerodynamic control system **270B**. For example, appropriately changing an angle of attack, and/or providing a flap angle to the respective control surfaces of the control system **270B** can reduce the lift generated by the control system **270B**, and thus result in a net downwards force corresponding to negative lift force **LF**. Concurrently, in at least some cases, the drag force **LD** can also be generated by suitably controlling the spatial control system **260B**, in particular the selectively controllable aerodynamic control system **270B**. For example, appropriately changing an angle of attack, and/or providing a flap angle to the respective control surfaces of the control system **270B** can also change the drag generated by the control system **270B**, and thus result in an increase in drag corresponding to drag force **LD**. Additional drag force can be generated, where necessary to complement or replace the drag generated by the control system **270B** to provide the appropriate drag force **LD**, by controlling the drag generated by the aerodynamic stabilizer arrangement, in particular in by the drogue structure **280B**.

The force generating arrangement **295B** is in particular configured for selectively generating a force **FB** having a magnitude sufficient for forcing the nozzle **235B** into engagement with the fuel receptacle **22** of the receiver aircraft when the nozzle **295B** (and the boom member **230B**) and the fuel receptacle **22** are in a predetermined relative spatial disposition, i.e., when the refueling device **200B** reaches an engagement enabling position and the boom axis **231B** is in the engagement enabling orientation with respect to the receiver aircraft **20**, and in particular with respect to the fuel receptacle **22**.

The force generating arrangement **295B** is further configured for selectively operating in this manner responsive to the nozzle **235B** being in a predetermined proximity to the fuel receptacle **22**, i.e. responsive to the nozzle **235B** being in a predetermined spacing with respect to the fuel receptacle **22**, typically the engagement enabling spatial position, and can be operated manually or automatically to provide such a force **FB**, as will become clearer herein.

Thus, at the engagement enabling position, when the boom member **230B**, or the boom axis **231B**, is in a predetermined spatial disposition with respect to the fuel receptacle **22** and the nozzle **235B** being in a predetermined spacing with respect to the fuel receptacle **22** (i.e., at the engagement enabling position the boom axis is at the engagement enabling orientation – corresponding to the design angle θ_{des}), the force generating arrangement **295** can be selectively actuated to compel the boom member **230B**

- 80 -

to follow a predetermined trajectory (together with the device **200B**), for example aligned with the boom axis **231B** in the direction of the receiver aircraft **20**, to ensure alignment and engagement between the nozzle **234B** and the fuel receptacle **22**. In this example, the boom member **230B** (and thus the boom axis **231B**) is maintained at the engagement enabling orientation – corresponding to the design angle θ_{des} , while the body **210B** remains at the same spatial disposition with respect to the receiver aircraft **20**. The body **210B** is moved towards the receiver aircraft **20** along a the direction of the boom axis **231B**, maintaining the boom axis **231B** at the engagement enabling orientation – corresponding to the design angle θ_{des} , to effect engagement between the nozzle **235B** and the fuel receptacle **22**. In alternative variations of this example, the boom **230B** is telescopic, and is partially or fully telescopically extended towards the receiver aircraft **20** while the device **200B** can be moved towards or away from the receiver aircraft **20** to effect engagement between the nozzle **235B** and the fuel receptacle **22**.

Once the nozzle **235B** is forced into engagement with the fuel receptacle **22** of the receiver aircraft **20**, the tanker aircraft **12** can begin refueling the receiver aircraft **20**.

In alternative variations of this example and in other examples, the force generating arrangement **295B** can comprise any other suitable drag inducing arrangement, for example spoilers on the boom member **230** and/or on other parts of the device **200B**.

In yet other variations of this example and in other examples, the force generating arrangement **295B** can be configured for generating a thrust force in the required direction. For example, one or a plurality of suitable thrust nozzles can be mounted to the body **210B** and/or to the boom member **230B** to provide the required thrust vector parallel to the boom axis **231B** towards nozzle **235B**. Such thrust nozzle(s) can be operatively connected to a suitable compressed air or compressed gas supply, for example carried by the refueling device itself, or carried by the tanker aircraft and supplied to the refueling device via pneumatic or gas lines, or generated by the tanker aircraft and/or the refueling device.

In yet other alternative variations of this example and in other examples, the force generating arrangement can be omitted, and for example the receiver aircraft and/or the device **200B** can comprise suitable means for mechanically engaging the nozzle **235B** to the fuel receptacle that does not require such a force **FB** to be generated by the device **200B**. For example, the fuel receptacle and/or the boom member **230B** can comprise a suitable mechanical clamp that engages the terminus **236B** of the boom member **230B** to

- 81 -

the fuel receptacle **22**, and pulls in the nozzle **235B** into engagement with the fuel receptacle **22**.

The device **200B** comprises controller **285B** for controlling operation of one or more of the force generating arrangement **290B**, the spatial control system **260B** (in particular the selectively controllable aerodynamic control system **270B**), the aerodynamic stabilizer arrangement (in particular in the form of a respective drogue structure **280B**), for example similar to controller **180** as described herein, *mutatis mutandis*, and thus for example comprises any suitable computer control system, and can be internally or externally mounted in the refueling device **200B**. In alternative variations of this example and in other examples, the controller **285B** or portions thereof can instead comprise any suitable electronic control unit, or any other suitable control unit, and/or the controller **285B** or portions thereof can be comprised elsewhere in the in-flight refueling system **50** or in the tanker aircraft **12**.

The refueling device **200B** further comprises a suitable spatial data acquisition system, also referred to herein as a data acquisition system **299B** for providing or enabling the calculation of spatial data relating to the relative spatial dispositions between the refueling device **200B** and the receiver aircraft **20**, in particular the relative spatial dispositions between the fuel delivery nozzle **235B** of the refueling device **200B** and the fuel receptacle of the receiver aircraft, to enable selectively controlling the refueling device to provide automatic (optionally including autonomous) and/or manual steering of the refueling device **200B** to the engagement enabling position and subsequent selective engagement of the fuel delivery nozzle to the fuel receptacle of the receiver aircraft.

In this variation of the second example of the device **200B**, the data acquisition system is in the form of imaging system **289B**, in particular configured for providing imaging data of any object coming within a field of regard (FOR) aft of the refueling device **200B**.

The imaging system **289B** is operatively connected to a control computer system **255B**, for example similar to control computer system **155** as described herein, *mutatis mutandis*, and which can be integral with, connected to, or independent from controller **285B**. In particular, and referring particularly to Fig. 17(b), such an object is the receiver aircraft **20** and more particularly a part **AP** thereof including the fuel receptacle **22**, and the

- 82 -

sensing volume **259B** defines an outer envelope limit **258B** in which image data of part **AP** can be processed, *inter alia*, by control computer system **255B** to provide control signals, for example steering commands, to the spatial control system **260B** and/or the force generating arrangement **290B**, for example via controller **285B** to control operation
5 of the refueling device **200B**, in particular the relative spatial position and orientation of the refueling device **200B** with respect to the receiver aircraft **20**, in particular the position and orientation of the boom member **230B** and nozzle **235B** with respect to the fuel receptacle **22**, so that the nozzle **235B** can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and effective manner. The manner of
10 operation of the imaging system **289B** and control computer system **255B** will be described in greater detail further herein.

In alternative variations of this example, the imaging system **289B** can be replaced with any other suitable data acquisition system for providing the aforesaid spatial data.

15 In yet other alternative variations of this example and in other examples, the refueling device **200B** can omit the imaging system **289B** and can be actively controlled by an operator, for example, to control the relative spatial position and orientation of the refueling device **200B** with respect to the receiver aircraft **20**, in particular the spatial position and orientation of the boom member **230B** and/or nozzle **235B** with respect to the
20 fuel receptacle **22**, so that the nozzle **235B** can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and effective manner, for example via direct visual tracking of the device by one or more operators (for example, an operator can be in the tanker aircraft **12** and/or an operator can be in the refueling aircraft **20**). Alternatively, the refueling device can be operated as a free flying refueling device towed
25 at the end of hose **52**, and the relative spatial position and orientation of the refueling device **200B** with respect to the receiver aircraft **20** (in particular the position and orientation of the boom member **230B** and nozzle **235B** with respect to the fuel receptacle **22**, so that the nozzle can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and effective manner) is achieved by maneuvering the receiver
30 aircraft **20** only. In such a case, the spatial control system **260B** can optionally comprise a non-adjustable aerodynamic stability system that is configured for allowing the refueling device **200B** to adopt a particular, pre-set, desired angle θ while maintaining a zero

- 83 -

pitching moment (and/or zero yawing moment and/or zero rolling moment), this being the design angle θ_{des} as discussed above for example.

Optionally, a suitable air-driven generator can be provided in the refueling device **200B** to provide electrical power thereto. Additionally or alternatively, electrical power can be provided to the refueling device **200B** by the tanker aircraft **12**. Additionally or
5 alternatively, electrical power can be provided to the refueling device **200B** by one or more batteries in the refueling device **200B**. Additionally or alternatively, electrical power can be provided to the refueling device **200B** by one or more ram air turbines (RAT), affixed internally or externally with respect to the refueling device **200B**.

10 In this variation of the second example of device **200B**, the imaging system **289B** is for example similar to imaging system **350** as described herein, *mutatis mutandis*, and comprises one or more Light Detection And Ranging (LIDAR) units **351**, for example similar as described herein, *mutatis mutandis*, which can utilize eye-safe laser. The imaging system **350** in this example is located on the underside of the body
15 **210B** near the nose of body **210B**, but in alternative variations of this example the imaging system **289B** can be located elsewhere on the device **200B**, for example the at **289B'**, near the tail of the body **201B**, or on the spatial control system **260B**, so long as the respective sensing volume **359** extends beyond the position of the nozzle **235B** to include the nozzle **235B**, and part **AP** of the receiver aircraft **20** when the part **AP** is in
20 close proximity to the nozzle **235B**.

In alternative variations of this example, the LIDAR unit **351** can be replaced with any other suitable imaging system **350** that provides depth data and electromagnetic intensity data of objects within the sensing volume **359** (including, but not limited to, Flash LADAR, 3D Flash LIDAR Camera, etc.). In still further alternative
25 variations of this example, the LIDAR unit **351** can be replaced with other suitable imaging systems such as stereoscopic cameras, conventional cameras, various radar systems, etc.

In any case, the control computer system **355**, included in controller **285B** and/or controller **255B** for example, comprises a memory including geometrical data of the
30 shape of at least part of the receiver aircraft **20**, in particular part **AP** and or the fuel receptacle **22**. The control computer system **355** is further configured for operating on

- 84 -

the depth data and the geometrical data to enable identification of a first part of the depth data that corresponds to the part **AP** and or the fuel receptacle **22**.

According to certain examples of the presently disclosed subject matter the data acquisition system **299B** further includes fuel receptacle marker **342**, comprised on the receiver aircraft **20** in a pre-determined location with respect to the fuel receptacle **22** thereof. The fuel receptacle marker **342** is at a fixed and known geometrical relationship with respect to the fuel receptacle **22**, and is electromagnetically visible to the imaging system **350**, at least during operation thereof.

In this example, the fuel receptacle marker **342** comprises a retro-reflective surface that reflects incident beams along the same path, and thus provides a strong intensity reflection of the respective reflected beam when illuminated by a beam, as compared with the reflection intensity obtained from other surfaces of the receiver aircraft **20**, for example. Such a retro-reflective surface may be provided via a retro-reflective material affixed to a certain known location visible to the imaging system **350** on the receiver aircraft **20**. Such retro-reflective materials are well known in the art, and can include for example retro-reflective tape or retro-reflective paint.

It is to be noted that the data acquisition system **299B** can include any one of the boom tip marker **340** and the fuel receptacle marker **342**, or a combination of both. Alternatively, in some cases, the data acquisition system **299B** can include none of the markers (in this case the natural reflective properties of the surfaces can be used).

The control computer system **355** is further configured for operating on the depth data and the electromagnetic intensity data, as disclosed herein, *mutatis mutandis*, to enable identification of a second part of the depth data that corresponds to the high intensity reflection originating from the boom tip marker **340**, which in turn enables identification of the part of a third depth data that corresponds to nozzle **316** since the relative spatial relationship between the boom tip marker **340** and nozzle **316** is known.

Accordingly, when the aforesaid first part and second part (first part and third part) of the depth data is known, the control computer system **355** can determine the relative disposition between the boom system **300**, and in particular the nozzle **316**, and the receiver aircraft **20**, in particular the fuel receptacle **22** thereof.

The in-flight refueling systems **50** including this alternative variation of the second example of the refueling device **200B**, and at least some alternative variations thereof, can also be operated in a number of different ways to provide selective engagement of the

- 85 -

nozzle **235B** with the fuel receptacle **22** of a receiver aircraft **20**, and enable subsequent refueling of the receiver aircraft **20** from the tanker aircraft **12** in flight, for example as disclosed herein for the first example or alternative variations thereof, or the second example, *mutatis mutandis*.

5 Referring to Fig. 30, a tanker system according to another example of the presently disclosed subject matter, generally designated **10'**, comprises a tanker aircraft **12'** comprising an aircraft-fixed flying boom system, designated by the reference numeral **300**, and may optionally further comprise one or more non-aircraft-fixed in-flight refueling systems. For example, each non-aircraft-fixed in-flight refueling system can comprise an
10 in-flight refueling system **50** as disclosed above with reference to Figs. 1 to 29, *mutatis mutandis*. For example, the tanker aircraft **12** can have two such in-flight refueling systems **50**, one comprised on each one of the port wing and starboard wing, and, together with the fixed flying boom system **300**, the tanker aircraft **12'** is configured for in-flight concurrent refueling of up to three receiver aircraft **20**. In yet other alternative variations of this
15 example the tanker aircraft **12'** can have no such in-flight refueling systems **50**, or at least one, or two, or more than three in-flight refueling systems **50**, arranged in any suitable configuration with respect to the tanker aircraft **12'**.

The fixed flying boom system **300** comprises a refueling device in the form of telescoping boom fuelling unit **310**, which comprises a spatial control system including at
20 least one of a mechanical connection **320** and a motion control system **330**.

The boom fuelling unit **310** is movably affixed at its forward end to an underside of the aft end of the fuselage of the tanker aircraft **12'** via the mechanical connection **320**, such as for example an articulation joint, gimbals, and so on. The mechanical connection **320** is configured for providing the boom fuelling unit **310** with two rotational degrees of
25 freedom about the yaw and pitch axes at mechanical connection **320**, relative to the tanker aircraft **12'**.

The boom fuelling unit **310** comprises an elongate boom member **312**, and a telescoping aft section **314** configured for being selectively telescopically deployed and selectively telescopically retracted into boom member **312**, along boom axis **311**, under the
30 control of controller **390** (that in some cases can be controller **180** or part thereof), providing the boom system **300** with a translational degree of freedom with respect to the tanker aircraft **12'**. At the boom tip or terminus of aft section **314**, the boom fuelling unit

- 86 -

310 comprises a fuel delivery nozzle module **317** including fuel delivery nozzle **316**, which is in selective fuel communication, via a hose, pipe and so on (not shown), with a refueling fuel tank (not shown) carried by the tanker aircraft **12'**. The nozzle **316** is configured for reversibly engaging with the fuel receptacle **22** of a receiver aircraft **20** (in a similar manner to the examples illustrated in Figs. 1 to 29 disclosed herein, *mutatis mutandis*), and thus can comprise any conventional design of such nozzles, which are well known, or indeed can comprise any other current or future design of such an in-flight refueling nozzle.

The boom fuelling unit **310** further comprises motion control system **330** configured for controlling the position of the boom fuelling unit **310** in elevation and azimuth, i.e., about the pitch and yaw axes at mechanical connection **320**. In this example, the motion control system **330** comprises aerodynamic lift/control surfaces, also known as ruddevators **325**, operatively connected to controller **390**. While in this and other examples ruddevators **325** can be in a V-tail type configuration, in yet other alternative variations of this example the aerodynamic lift/control surfaces can have any other suitable configuration. Selectively and controllably changing the incidence angles of the ruddevators **325** via controller **390** generates aerodynamic forces that enable the boom fuelling unit **310** to be aligned or aimed in any particular direction within a predefined envelope. Additionally or alternatively, the motion control system **330** comprises reaction control thrusters, which can also be operatively connected to controller **390**.

In particular, motion control system **330** is configured for selectively and controllably providing a non-zero angular disposition, angle θ , between the boom axis **311** and the longitudinal axis of the receiver aircraft **20**.

The boom system **300**, in particular the nozzle **316** can be sized to allow suitable fuel flow rates for refueling a wide range of receiver aircraft. By way of non-limiting example, relative high fuel flow rates (for example up to 1000 US gallons/6,500 lb per minute) can be provided for refueling operations of large aircraft (for example transport aircraft, bombers, etc), while for fighter aircraft that cannot accept fuel at the maximum flow rate of the boom system **300**, the refueling pressure can be correspondingly reduced. Alternatively the boom system **300** can be sized to allow suitable fuel flow rates for refueling a narrow range of receiver aircraft., for example only fighter aircraft or only larger aircraft (for example about 400 US gallons/2,600 lb per minute).

- 87 -

In operation of boom system **300**, angle θ can be chosen such as to be a nominal design angle (angle θ_{des}) that is within a particular allowable angular range which corresponds to the range of relative angular positions of the boom system **300** (and boom axis **311**) with respect to the receiver aircraft **20**, which allow for engagement
5 between the nozzle **316** and the fuel receptacle **22**.

In practice, the actual pitch, roll and yaw angles of the boom axis (and the extension of the telescoping aft section **314** with respect to boom member **312**) determine the spatial position of the boom tip including the nozzle **316** with respect to the tanker aircraft **12'**. In order to allow for engagement, the boom tip including the
10 nozzle **316** needs to be within the respective refueling geometrical envelope and this position needs to be matched with the position of receptacle **22** of the receiver aircraft **20**. The refueling geometrical envelope represents the safe limits of movement for the boom fuelling unit **310** with respect to the receiver aircraft **20** and within which contact between the receiving aircraft **20** and the boom fuelling unit **310** is permitted, and can
15 correspond to at least part of the sensing volume **359**. This position for the boom tip including the nozzle **316** can be achieved by adjusting angular alignment of the boom axis in elevation and azimuth, i.e., about the pitch and yaw axes at mechanical connection **320**, together with axial extension along the boom axis via extension/retraction of the telescoping aft section **314** with respect to boom member
20 **312**. Thus, at a particular engagement enabling position, the boom tip and nozzle **316** can be positioned close to the receptacle **22**, with the boom axis being aligned at an angle θ which can deviate from the nominal design angle (angle θ_{des}) by a allowable angular clearance ($+\Delta\theta$, $-\Delta\theta$), but nevertheless still within the aforesaid allowable angular range (angle θ_{max} to angle θ_{min}). The structure of the nozzle **316** and the
25 receptacle **22** can be such as to allow for such deviations of angle θ from angle θ_{des} within the aforesaid allowable angular range. For example, the nozzle **316** can incorporate a ball joint and the receptacle **22** can include a funnel guide for the nozzle **316** to provide the allowable angular clearance ($+\Delta\theta$, $-\Delta\theta$), for example in a similar manner to that schematically illustrated in Fig. 10(b) regarding other examples, *mutatis*
30 *mutandis*. By way of non-limiting example, where the nominal design angle θ_{des} is +30 degrees, engagement between the nozzle **316** and receptacle **22** can occur even when the boom axis has an angle of +40 degrees in elevation and +8 degrees in azimuth,

- 88 -

assuming that the nozzle **316** can engage with the receptacle **22** with a relative spatial disposition therebetween of -10 degrees in elevation and -8 degrees in azimuth.

In at least some cases, angle θ (which can have an angular component in yaw and/or in pitch and/or in roll) can be further compensated for any off-nominal pitch of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction **A** at a non-zero angle of attack) and/or for any off-nominal roll of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction **A** at a non-zero roll angle) and/or for any off-nominal yaw of the receiver aircraft **20** (for example if the receiver aircraft **20** is traveling along direction **A** at a non-zero sideslip angle) to ensure that the actual angular disposition between the boom axis **311** and the receiver aircraft longitudinal axis is maintained at design angle θ_{des} even as the relative spatial orientation between the receiver aircraft **20** and the forward direction changes. Such compensation can be achieved, for example, by steering the tanker aircraft **12'** in a corresponding manner.

Thus, at the design angle θ_{des} (and for other angles θ within the aforesaid allowable angular range (angle θ_{max} to angle θ_{min})) the boom axis **311** is in an engagement enabling orientation with respect to the receiver aircraft **20**, and in particular with respect to the fuel receptacle **22**.

In non-limiting examples, angle θ (and in particular angle θ_{des}) can be any suitable angle in a range between about 5° and about 85°; or in a range between about 10° and about 80°; or in a range between about 15° and about 70°; or in a range between about 20° and about 60°; or in a range between about 25° and about 50°; or in a range between about 20° and about 40°; or in a range between about 25° and about 40°; or in a range between about 28° and about 32°.

In one non-limiting example, angle θ_{des} can be about 30°, and operation of the boom system **300** to adopt this angle automatically renders it compatible for use with existing receiver aircraft **20**, in which the fuel receptacles **22** are configured for receiving and engaging with a nozzle at the end of a boom where the boom is at about 30° to the longitudinal axis of the receiver aircraft, without the need for modifying the configuration of the fuel receptacle thereof.

- 89 -

Thus, when angle θ is equal to design angle θ_{des} , or within the aforesaid allowable angular range (angle θ_{max} to angle θ_{min}), the receiver aircraft travelling along direction A with zero angle of attack and zero sideslip and zero roll, and boom axis **311** is at the required spatial orientation to the forward direction A of the tanker aircraft and
5 the receiver aircraft such as to ensure engagement between the nozzle **316** in the fuel receptacle **22**, without the need for modifying the configuration of the fuel receptacle thereof.

The boom system **300** further comprises a suitable data acquisition system **360** for providing or enabling the calculation of spatial data relating to the relative spatial
10 dispositions between the boom system **300** and the receiver aircraft **20**, in particular the relative spatial dispositions between the fuel delivery nozzle module **317** including fuel delivery nozzle **316** of the boom system **300**, and the fuel receptacle **22** of the receiver aircraft, to enable selectively controlling the boom system **300** to provide automatic (optionally including autonomous) and/or manual alignment of the boom system **300** in the
15 engagement enabling position and subsequent selective engagement of the fuel delivery nozzle to the fuel receptacle of the receiver aircraft.

In this example the data acquisition system **360** includes imaging system **350**, in particular configured for providing imaging data of any object coming within a field of regard (FOR), in particular the fuel delivery nozzle module **317** including fuel delivery
20 nozzle **316**, and the fuel receptacle **22**. Such a field of regard has a predetermined depth aft of the imaging system and in this example comprises sensing volume **359** generally aft of the imaging system **350**, which for example comprises a prismoidal volume or any other suitable shape, for example conical, frustoconical, cylindrical, spherical, part-spherical (e.g. hemispherical), parallelepiped (for example cubic) or any other regular or irregular
25 shape. The sensing volume **359**, i.e., the predetermined depth of the FOR, extends beyond the position of the fuel delivery nozzle module **317** further than is required corresponding to the engagement enabling position, i.e., further than the maximum extension of the aft section **314** when this is in its fully deployed position. The imaging system **350** is operatively connected to a control computer system **355**, which can be integral with,
30 connected to, or independent from controller **390**. In particular, such an object is the receiver aircraft **20** and more particularly a part AP thereof including the fuel receptacle **22** and/or another part of the receiver aircraft **20** (including a part that does not include the

- 90 -

fuel receptacle **22**, but, when recognized, can enable estimation of the fuel receptacle **22** position and orientation), and the sensing volume **359** defines an outer envelope limit **358** in which image data of part **AP** can be processed, inter alia, by control computer system **355**. The control computer system **355** can then provide control signals, for example
5 alignment commands, to the motion control system **330**, for example via controller **390**, to control operation of the boom system **300**, in particular the relative orientation of the boom fuelling unit **310** and the relative position of the nozzle **316** with respect to the receiver aircraft **20**, in particular with respect to the fuel receptacle **22**, so that the nozzle **316** can be controllably brought into selective engagement with the fuel receptacle **22** in a safe and
10 effective manner

In this example, the imaging system **350** comprises one or more Light Detection And Ranging (LIDAR) units **351**, which can utilize eye-safe laser. The imaging system **350** in this example is located on the underside of the fuselage of the tanker aircraft **12'**, but in alternative variations of this example the imaging system **350** can be located
15 elsewhere on the tanker aircraft **12'**, for example the wings, elevators, etc., so long as the sensing volume **359** extends beyond the position of the nozzle **316** to include the nozzle module **317** and nozzle **316**, and part **AP** when the part **AP** is in close proximity to the nozzle **316**. One exemplary non-limiting alternative location is shown in the figure under reference numeral **350'**.

20 In particular, and referring also to Fig. 31, the LIDAR unit **351** is configured for providing depth data and electromagnetic data (for example electromagnetic intensity data) relating to any object within the sensing volume **359**, in particular relating to one or more of the nozzle module **317**, nozzle **316** and part **AP**.

In this example, the LIDAR unit **351** comprises a fiber laser unit **352** configured
25 for generating and radiating a laser beam B1 towards horizontally rotated polygon **353**, which in turn deflects the beam B1 to a mirror **354**, which can be controllably moved in elevation. The controlled combined motion of the mirror **354** and polygon **353** scans the outgoing beam B1 in a two-dimensional pattern SC in sensing volume **359**, along azimuth and elevation within sensing volume **359**, for example with respect to one or
30 more planes BB orthogonal to a depth direction radiating from the LIDAR unit **351**. Each time the outgoing beam B1 impinges on an object within the sensing volume **359**, a reflected beam B2 returns along a path similar to that of the outgoing beam **B1**, deflected by the mirror **354** and polygon **353**, and detected by detector **356**.

It is to be noted that in some cases, a single mirror which can be rotated in two dimensions can be used instead of the mirror **354** and polygon **353**.

Control module **369** includes one or more of a fast Analog to Digital Converter (ADC) card, Field Programmable Gate Array (FPGA), Digital Signal Processor (DSP),
5 memory and power supply for operation of the LIDAR unit **351**.

Fast Analog to Digital Converter (ADC) card can be one having a typical conversion speed of about 1.5 GHZ or more. The fiber laser unit **352** can generate a laser pulse having a very fast rising time therefore the returning (i.e. the reflected) beam requires a very fast detector such as an Avalanche Photo Diode. An Avalanche Photo
10 Diode is a very sensitive Photo Diode which enables measuring the time of light with an accuracy of typically about 10 centimeters. Such accuracy can be further increased for example using the known functional time evolution of the laser pulse. Using such algorithm, accuracies of few millimeters can be achieved.

The Field Programmable Gate Array (FPGA) can be used to enable the required
15 processing power for processing the data acquired by the LIDAR unit **351**.

The Digital Signal Processor (DSP) can be a real time processor that can be configured to analyze the data acquired by the LIDAR unit **351** and provide the electromagnetic data and the depth data. Such data can be stored in the memory and can be transferred (e.g. transmitted) for further computations in one or more
20 additional/alternative computers.

The fiber laser unit **352** is a Fiber laser which can comprise an optical fiber to which diode lasers (e.g. having a larger frequency than the required laser radiation) are attached for providing the necessary excited medium (e.g. the light amplifying medium). In some cases, the initiating laser diode at the required frequency is attached
25 to the fiber and starts the laser operation. The laser beam is amplified in the fiber and an amplified beam goes out from the fiber to a collimator device to start the laser operation. A laser beam at 1.5 microns can be used, which is an eye safe light, since it cannot penetrate the cornea of the pilot and hence cannot focus on the retina and cause any damage. The laser beam can be typically composed of about one hundred thousand
30 pulses per second. It is to be noted that the higher the number of pulses is, the higher resolution can be achieved. In some cases, the pulse duration of the laser beam can be about 2 to 10 nanosecond width. The energy of the pulsed laser beam can be set according to the required sampling distance. In some cases, no more than one hundred

- 92 -

meters are needed, and in such cases the required energy is typically about five to twenty micro joules per pulse. The rise time of the laser beam can be of about few tenths of a nanosecond. This allows for accurate measurement of the time of light of the laser to the target. It is to be noted that in some cases gas or solid state laser can be
5 alternatively used.

At any particular position of the mirror **354** and polygon **353** (corresponding to a two-dimensional position on plane BB, for example), the time interval between the outgoing beam B1 and the return beam B2 being detected by the detector **356** provides a measure of the depth of the part of the object which reflected the beam, thereby
10 providing the depth data. In addition, the detector **356** also detects the intensity of the part of the object which reflected the beam to provide the intensity data.

In alternative variations of this example, the LIDAR unit **351** can be replaced with any other suitable imaging system **350** that provides depth data and electromagnetic intensity data of objects within the sensing volume **359** (including, but
15 not limited to, Flash LADAR, 3D Flash LIDAR Camera, etc.). In still further alternative variations of this example, the LIDAR unit **351** can be replaced with other suitable imaging systems such as stereoscopic cameras, conventional cameras, various radar systems, etc.

In any case, the control computer system **355** comprises a memory including
20 geometrical data of the shape of at least part of the receiver aircraft **20**, in particular part **AP** and or the fuel receptacle **22**. The control computer system **355** is further configured for operating on the depth data and the geometrical data to enable identification of a first part of the depth data that corresponds to the part **AP** and or the fuel receptacle **22**.

according to certain examples of examples of the presently disclosed subject
25 matter the data acquisition system **360** further includes boom tip marker **340**, comprised in the fuel delivery nozzle module **317** proximate to the nozzle **316**. The boom tip marker **340** is at a fixed and known geometrical relationship with respect to the nozzle **316**, independently of the relative motion between the boom system **300** and the tanker aircraft **12'**, and is electromagnetically visible to the imaging system **350**, at least during
30 operation thereof.

In this example, the boom tip marker **340** comprises a retro-reflective surface that reflects incident beams along the same path, and thus provides a strong intensity reflection of the respective beam B2 when illuminated by beam B1, as compared with

- 93 -

the reflection intensity obtained from other surfaces of the boom fuelling unit **310**, for example. Such a retro-reflective surface may be provided via a retro-reflective material affixed to the fuel delivery nozzle module **317**. Such retro-reflective materials are well known in the art, and can include for example retro-reflective tape or retro-reflective paint.

According to certain examples of the presently disclosed subject matter the data acquisition system **360** further includes fuel receptacle marker **342**, comprised on the receiver aircraft **20** in a pre-determined location with respect to the fuel receptacle **22** thereof. The fuel receptacle marker **342** is at a fixed and known geometrical relationship with respect to the fuel receptacle **22**, and is electromagnetically visible to the imaging system **350**, at least during operation thereof.

In this example, the fuel receptacle marker **342** comprises a retro-reflective surface that reflects incident beams along the same path, and thus provides a strong intensity reflection of the respective beam B2 when illuminated by beam B1, as compared with the reflection intensity obtained from other surfaces of the receiver aircraft **20**, for example. Such a retro-reflective surface may be provided via a retro-reflective material affixed to a certain known location visible to the imaging system **350** on the receiver aircraft **20**. Such retro-reflective materials are well known in the art, and can include for example retro-reflective tape or retro-reflective paint.

It is to be noted that the data acquisition system **360** can include any one of the boom tip marker **340** and the fuel receptacle marker **342**, or a combination of both. Alternatively, in some cases, the data acquisition system **360** can include none of the markers (in this case the natural reflective properties of the surfaces can be used).

The control computer system **355** is further configured for operating on the depth data and the electromagnetic intensity data to enable identification of a second part of the depth data that corresponds to the high intensity reflection originating from the boom tip marker **340**, which in turn enables identification of the part of a third depth data that corresponds to nozzle **316** since the relative spatial relationship between the boom tip marker **340** and nozzle **316** is known.

Accordingly, when the aforesaid first part and second part (first part and third part) of the depth data is known, the control computer system **355** can determine the relative disposition between the boom system **300**, and in particular the nozzle **316**, and the receiver aircraft **20**, in particular the fuel receptacle **22** thereof.

- 94 -

The tanker **12'** can be configured to provide the maneuvering instructions for enabling positioning of the receiver aircraft **20** within an engagement area, for example in a similar manner to that disclosed herein with reference to the examples of Figs. 1 to 29, *mutatis mutandis*, for example by utilizing a signaling system. Thus, such signaling
5 system can be mounted, for example, on the tanker aircraft **12'**, at any location visible to the receiver aircraft **20** pilot. In some cases, the signaling system can provide the receiver aircraft **20** pilot with maneuvering instructions on three axes: forward-backward, left-right and up-down, thus enabling it to maneuver the receiver aircraft **20** to the corresponding engagement area that allows for engagement between the fuel
10 nozzle **316** and the fuel receptacle **22**. In some cases the signaling system can be a light directing system. Alternatively or additionally, the maneuvering instructions can be provided to by using voice commands (e.g. by utilizing speakers, pilot headset, etc.) or by any other means known *per se*. In some cases, a maneuvering instructions module can be configured to communicate the maneuvering instructions to an auto pilot system
15 of the receiver aircraft **20**, if such system exists, for causing the auto pilot system to maneuver the receiver aircraft **20** accordingly.

The manner of operation of the imaging system **350** and control computer system **355** will be described in greater detail further herein.

In operation, the LIDAR unit **351** illuminates the sensing volume **359** and any
20 object therein, in particular part **AP** of the receiver aircraft **20** and thereafter acquire suitable image data corresponding thereto which is sent to control computer system **355** for processing to provide the aforesaid control signals for controlling operation of the boom system **300**, in particular, to align the boom fuelling unit **310** to provide a desired relative position and orientation of the nozzle **316** with respect to the fuel receptacle **22**, in
25 particular the engagement enabling position..

In alternative variations of this example and in other examples, the imaging system **350** can comprise any other suitable imaging system (for example, but not limited to, systems providing **2D** images and/or stereoscopic images and/or **3D** images of (including reconstruction of **3D** data corresponding to) the sensing volume **359**, in particular but not
30 limited to images that are updated in real time, for example in the form of a video stream) that operate to provide suitable data to the control computer system **355** to, in turn, enable selectively controlling the boom system **300** to provide autonomous and/or manual

- 95 -

engagement of the nozzle **316** to the fuel receptacle **22** of the receiver aircraft **20**. For example the imaging system **350** can be similar to the imaging system disclosed herein with respect to the examples of Figs. 1 to 29.

In alternative variations of this example, the fuelling unit **310** can be replaced with
5 any other conventional or non-conventional so-called “flying boom” systems.

In alternative variations of this example, the part **AP** can also comprise a retro-reflective surface to help identify the part of the depth data corresponding to the part **AP**.

In alternative variations of this example, the boom tip marker **340** and/or the fuel receptacle marker **342** can comprise an electromagnetic source, for example a light source
10 of different wavelength from that of the illumination beam **B1**, and the illumination data received from the respective boom tip marker **340** and/or the respective fuel receptacle marker **342** (via the imaging system **350** and/or a second imaging system).

In alternative variations of this example, the imaging system **350** can be located in alternative locations on the refueling aircraft **12'** and/or on the boom member **312**, or on
15 any other location.

There is now provided a description of certain examples of systems of controlling in-flight refueling.

Reference is now made to **Fig. 18**, which is a block diagram schematically illustrating a system for controlling in-flight refueling, according to certain examples of
20 the presently disclosed subject matter. The system **1805** comprises at least one processing unit **1801**. The processing unit **1801** can be a microprocessor, a microcontroller or any other computing device or module, including distributed and/or multiple processing units, which are adapted to independently or cooperatively process data for controlling relevant system **1805** components and for enabling operations
25 related to system **1805** components.

In some cases, the processing unit **1801** can be the control computer system **155**, or part thereof. In some cases, the processing unit can be the controller **180**. Alternatively, the processing unit **1801** can be a separate component.

In some cases, the processing unit **1801** can be located on-board the refueling
30 device **100**, or on-board the receiver aircraft **20**, or on-board the tanker aircraft **12**. In

- 96 -

some cases, more than one processing unit can be used and the plurality of processors can be cooperatively operated.

In some cases, the system **1805** can be distributed between the refueling device **100** and/or the receiver aircraft **20**, and/or the tanker aircraft **12** and/or any other location, including remote locations. The communication between the various components of the system **1805** can be realized by any communication components, protocols and modules, and can be wired or wireless.

The system **1805** further comprises a sensor control module **1810**. According to some examples of the presently disclosed subject matter, the sensor control module **1810** can be configured to utilize at least one sensor **1890** (possibly according to instructions from the processing unit **1801**) as part of the operation of and control over the refueling process.

The sensor control module **1810** can be operatively connected to at least one sensor **1890** and can be configured to control the operation of the sensor **1890**. The sensor **1890** can be a suitable data acquisition system, for example, any image acquisition means such as a camera (e.g. a digital still camera, a digital video camera, a Flash LADAR camera, etc.). Alternatively, the sensor **1890** can be a Light Detection And Ranging (LIDAR) unit (including one using an eye-safe laser), a radar (including a radar utilizing an eye-safe laser), a laser array (including a laser array that utilizes eye-safe lasers), electro-acoustic sensors, etc. An exemplary non-limiting LIDAR unit that can be used is described herein, inter alia with reference to Figs. 31-33. In some cases, sensor **1890** can be configured inter alia for providing data of any object coming within a field of regard (FOR) aft of the refueling device **100** (and/or the tanker aircraft **12**). In some cases, the sensor **1890** can be the imaging system **150** or imaging system **350** detailed herein. In some cases, multiple sensors can be utilized, including, for example, a combination of the imaging system **150** and the imaging system **350**, or multiple redundant sensors of same type. In some cases, such combination of sensors can enable determination of spatial data also in cases when one of the imaging system **150** and the imaging system **350** does not provide the required data from some reason (e.g. due to a malfunction or due to environmental conditions such as clouds, dazzling light, etc. or due to partial concealment of the FOR by other system components, such as

- 97 -

concealment of receptacle by telescope, that can affect the sensors and/or the data received therefrom, or from any other reason).

In some cases, imaging system **150** can be configured inter alia for providing imaging data (including spatial disposition determination enabling data such as data
5 received from a LIDAR unit, etc.) of any object coming within a field of regard (FOR) aft of the refueling device **100** (and/or the tanker aircraft **12**). The sensor control module **1810** is configured to operate sensor **1890** (or multiple sensors, *mutatis mutandis*) in order to acquire data that enables, inter alia, repeated determination of spatial data such as the spatial disposition of the receiver aircraft **20** with respect to an engagement area
10 related thereto and/or determination of the spatial dispositions of the refueling device **100** with respect to an engagement enabling position, etc. as further detailed herein, inter alia with respect to Figs. 22 and 23.

The system **1805** can further comprise a maneuvering instructions module **1820**,
a steering control module **1830**, a safety module **1840**, and an
15 engagement/disengagement control module **1850**.

Maneuvering instructions module **1820** can be configured to calculate maneuvering instructions for enabling positioning of the receiver aircraft **20** within an engagement area related thereto, and for providing the calculated maneuvering instructions to a pilot of the receiver aircraft **20**, as further detailed, inter alia with
20 respect to Fig. 20.

Steering control module **1830** can be configured, when a non-aircraft-fixed in-flight refueling system is used, to calculate and provide steering commands (e.g. in six degrees of freedom) to the refueling device **100** for steering the refueling device **100** to an engagement enabling position or, when utilizing an aircraft-fixed flying boom
25 system, to calculate and provide alignment commands (e.g. in three degrees of freedom) to the boom fueling unit **310** for aligning the refueling device **100** in an engagement enabling position, as further detailed herein, inter alia with respect to Fig. 21. It is to be noted that the steering commands (e.g. in six degrees of freedom) and the alignment commands (e.g. in three degrees of freedom) are also referred to as maneuvering
30 commands interchangeably.

- 98 -

Safety module **1840** can be configured to monitor hazardous situations in the refueling process, as further detailed herein, inter alia with respect to Fig. 19. The hazardous situations can be defined by a set of thresholds and/or parameters and respective safety conditions. For example, safety module **1840** can be configured to
5 monitor that the refueling device **100** does not approach the receiver aircraft **20** (or vice versa) in an unsafe manner, and/or that the refueling device **100** does not approach the tanker aircraft **12** (or vice versa) in an unsafe manner, etc.

Engagement/disengagement control module **1850** can be configured to provide an engagement command to the refueling device **100** for causing the refueling device
10 **100** to engage with the fuel receptacle **22** of the receiver aircraft **20** for performing refueling, and to provide a command to the refueling device **100** to disengage from the fuel receptacle **22** of receiver aircraft **20**, as further detailed herein. According to examples of the presently disclosed subject matter, engagement/disengagement control module **1850** can be responsive to an indication that the receiver aircraft **20** is
15 positioned in an engagement enabling position. The engagement enabling position, in some cases, can depend on a spatial disposition of the refueling device **100** with respect to the receiver aircraft **20**, as further detailed herein.

The system **1805** can further comprise a configuration data repository **1860** (hereinafter: "Configuration DR") and a reference data repository **1870** (hereinafter:
20 "Reference DR"). Configuration DR **1860** comprises data indicative of various predefined configurations that are used in the refueling process. According to examples of the presently disclosed subject matter, the configuration DR **1860** can include configuration data related to an engagement area and an engagement enabling position. Further, by way of example, the configuration data related to the engagement area and
25 the engagement enabling position can be used to determine the engagement area and/or the engagement enabling position in a given scenario (and for a given set of parameters). Additional data with respect to the configuration data will be provided herein, inter alia with respect to Figs. 22 and 23. Reference DR **1870** comprises reference data to be used, inter alia, for determining (it is to be noted that in some cases
30 such determination is made, for example, repeatedly) the receiver aircraft's **20** spatial disposition with respect to the engagement area related thereto and the refueling device's **100** spatial disposition with respect to the engagement enabling position, etc.

- 99 -

According to some examples, the reference data can be used in combination with dynamic data acquired by the sensor **1890** for enabling evaluation of the sensor's **1890** data. Further explanations regarding the reference data are provided herein, inter alia with respect to Figs. 22 and 23. It is to be noted that in some cases, Reference DR **1870**
5 can also be used by the safety module **1840** for determining hazardous situations.

It is to be noted that according to some examples of the presently disclosed subject matter, some or all of the Configuration DR **1860**, the Reference DR **1870**, the sensor control module **1810**, the maneuvering instructions module **1820**, the steering control module **1830**, the safety module **1840**, and the engagement/disengagement control module **1850** can be combined and provided as a single system/module, or, by
10 way of example, at least one of them can be realized in a form of two or more systems/modules, each of which can in some cases be distributed over more than one location.

The system can still further comprise an interface **1880** for enabling one or more
15 components of the system **1805** to operate in cooperation with auxiliary units, devices, systems or modules. For example, the interface **1880** can implement various protocols, software languages, drive signals, etc. Further, by way of example, the interface **1880** can be used to operate certain auxiliary units, devices, systems or modules on board one or more of the refueling device **100**, the receiver aircraft **20** or the tanker aircraft **12**.

According to another aspect of the presently disclosed subject matter, there are provided methods for in-flight refueling of aircraft. While such methods can be applied to the systems and devices for in-flight refueling of aircraft according to another aspect of the presently disclosed subject matter, and as disclosed herein, for example, the methods can also be applied to other suitable systems and devices for in-flight refueling of aircraft,
25 *mutatis mutandis*.

According to the second aspect of the presently disclosed subject matter, there are at least three alternative operation modes for in-flight refueling of aircraft:

Operation Mode I – in which a refueling device is automatically (and in some cases autonomously) flown to engagement with the receiver aircraft fuel receptacle.

30 Operation Mode II – in which an operator in the tanker aircraft or elsewhere (via suitable communications link – for example satellite link, another aircraft including the

- 100 -

receiver aircraft, ground control, and so on) controls flying of a refueling device while towed behind the tanker aircraft to engagement with the receiver aircraft fuel receptacle.

Operation Mode III – in which the refueling device is not flown or controlled per se, but instead attains a stable configuration with the boom member at the required inclination angle with respect to the forward direction, and the receiver aircraft maneuvers to a position where it can engage the nozzle to the receiver aircraft fuel receptacle.

Examples of these operation modes will now be described in greater detail.

OPERATION MODE I

10 In this operation mode, once the tanker aircraft **12** and receiver aircraft **20** are in close proximity and flying in formation, with the receiver aircraft **20** at a position behind the tanker aircraft **12**, the refueling device **100** automatically (and in some cases, autonomously) flies into engagement with the fuel receptacle **22** of the receiver aircraft **20**.

Turning to **Fig. 19** there is provided a flowchart illustrating a sequence of operations carried out for enabling performance of in-flight refueling, according to certain examples of the presently disclosed subject matter, in particular relating to the example of a system for controlling in-flight refueling, as illustrated in Fig. 18. The sequence of operations begins with performance of an engagement sequence **1905**, comprising 3 blocks: **1910**, **1920** and **1930**.

20 Turning at first to block **1910**, in some cases, maneuvering instructions module **1820** is configured to calculate and provide maneuvering instructions for enabling positioning the receiver aircraft **20**, and more specifically a fuel receptacle **22** thereof, within an engagement area related to the receiver aircraft **20** (as in cases where more than one receiver aircraft **20** exists, each receiver aircraft **20** can be associated with a different engagement area) (block **1910**), as further detailed herein with respect to Figs. 20 and 22. Inter alia, some examples of methods that can be used for providing the maneuvering instructions to the pilot of the receiver aircraft **20** are also provided herein.

It is to be noted that such maneuvering instructions can be required in some cases, where the pilot of the receiver aircraft **20** has no line of sight to the refueling device **100** or boom fuelling unit **310** during all or part of the refueling process, inter alia in light of the receiver aircraft **20** fuel receptacle **22** position. Thus, there can be a

- 101 -

need to provide the pilot of the receiver aircraft **20** with maneuvering instructions, as further detailed herein.

As mentioned above, according to examples of the presently disclosed subject matter, the refueling process can include providing maneuvering instructions for positioning the receiver aircraft **20** within an engagement area related thereto. The engagement area is a virtual volume in which the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) or boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) can be maneuvered in order to engage with the fuel receptacle **22** of the receiver aircraft **20**. According to some examples of the presently disclosed subject matter, the engagement area can be defined by various specifications that depend on several parameters. According to one example, the parameters are associated with maneuvering capabilities of the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system). Such maneuvering capabilities can be defined, for example, by the range and types of motion that can be achieved by utilizing the spatial control system **160** and/or the force generating arrangement **190** of the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) or the mechanical connection **320** and/or the motion control system **330** of the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system), etc.

According to certain examples of the presently disclosed subject matter, the parameters defining the engagement area can further include, inter alia, the length of the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), the length of the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system), the flight speed, the flight altitude, weather conditions, the fuel pressure within the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), the location of the fuel receptacle **22** of the receiver aircraft **20**, etc. In some cases, the engagement area can be substantially in the shape of a cube, a sphere, or any other shape, including a non-regular shape, with a certain volume. The various engagement area specifications can be stored, for example, on configuration DR **1860**. For example, the engagement area specifications can include a set of spatial dispositions between the refueling device **100** and the receiver aircraft **20** or any other volumetric specification. According to further

- 102 -

examples of the presently disclosed subject matter, the engagement area specifications can be used in combination with reference data for enabling the refueling device **100**, based on dynamic data acquired by the sensor **1890**, to identify when the receiver aircraft **20** is within a position that meets the engagement area specification. In this case, correlations can be computed between the data acquired by the sensor **1890** and the reference data, in order to determine if and when the receiver aircraft **20** is within the engagement area, as further detailed herein, inter alia with reference to Fig. 30-32.

Before moving on to describe Fig. 19, and for the purpose of providing a visual illustration of an exemplary engagement area, attention is drawn to **Fig. 24**, showing an illustration of one example of a receiver aircraft positioned outside a virtual engagement area, according to certain examples of the presently disclosed subject matter. The engagement area **2410** in the illustrated example is a virtual pre-determined volume, shaped substantially like a cube, in which the refueling device **100** (or, when utilizing an aircraft-fixed flying boom system – the boom fuelling unit **310**) can navigate until engaging with the fuel receptacle **22** of the receiver aircraft **20**, as detailed herein. Although in this example the virtual engagement area is shaped substantially like a cube, the virtual engagement area can have any other shape with a certain volume. The virtual engagement area can be defined by a set of parameters that correspond to a volumetric shape. It can be further appreciated that in the illustrated example, the receiver aircraft **20** is not positioned within the engagement area **2410**. The illustration of Fig. 24 is provided for clarity of explanation only and is by no means binding.

Returning to **Fig. 19**, in some cases, the engagement area specifications can be defined using, inter alia, a parameter denoting a position of the center of such an engagement area, or any other point within the engagement area, and a set of offset vectors, collectively representing a volume. In some cases, the center (or any other point of reference) of the engagement area can be determined in accordance with one or more of the following parameters: the length of the hose **52** in a deployed position (when a non-aircraft-fixed in-flight refueling system is used), the length of the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system), a given pitch angle between the boom axis **131** (when a non-aircraft-fixed in-flight refueling system is used) or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) and the forward direction **A**, a given yaw angle between the boom axis **131**

- 103 -

(when a non-aircraft-fixed in-flight refueling system is used) or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) and the forward direction **A** and a given fuel pressure within the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), etc. One or more of the parameters which are used to
5 determine the center (or any other point of reference) of the engagement area can vary during flight and/or during the engagement sequence **1905** and the system **1805** can measure the relevant parameters dynamically for determining the center (or any other point of reference) of the engagement area.

In some cases (e.g. when a non-aircraft-fixed in-flight refueling system is used),
10 the point of reference for the engagement area can be positioned in a position from which utilization of the force generating arrangement **190** enables the nozzle **135** to engage with the fuel receptacle **22** of the receiver aircraft **20** and the engagement area is defined with reference to this point. In other cases (e.g. when utilizing an aircraft-fixed flying boom system), the point of reference for the engagement area can be positioned
15 in a position which enables the nozzle **316** to engage with the fuel receptacle **22** of the receiver aircraft **20** (e.g. by extending the telescoping aft section **314** thus applying force on the fuel receptacle **22** due to reaction force on the other side of the boom fuelling unit **310**, at the mechanical connection **320**) and the engagement area is defined with reference to this point.

20 In some examples, this point of reference is defined in the system as an engagement enabling position, and can also be used by an engagement/disengagement control module **1850**, for controlling engagement and of the nozzle **135** (or nozzle **316**) with the fuel receptacle **22** of the receiver aircraft **20**. It will be appreciated that this point can also depend, inter alia, on the parameters described herein, and in some cases,
25 is dynamically calculated according to the relevant parameters during the engagement sequence **1905**.

According to some examples of the presently disclosed subject matter, e.g. when a non-aircraft-fixed in-flight refueling system is used, the engagement enabling position can be characterized by the boom member **130** being in a predetermined maximal
30 spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**. According to some examples of the presently disclosed subject matter, e.g. when utilizing an aircraft-fixed flying boom system, the engagement enabling position

- 104 -

can be characterized by the boom fuelling unit **310** (or nozzle **316** thereof) being in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**.

Throughout the description and the claims, reference is made interchangeably to the terms spatial relationship and spatial disposition. The terms spatial relationship and spatial disposition or the like can relate to spatial distances, spatial angles (including orientations), or any other spatial reference that is used for characterizing a spatial relationship between two objects, e.g. between any two of the following: the tanker aircraft **12**, the receiver aircraft **20** (and a fuel receptacle **22** thereof), the refueling device **100** and the boom fuelling unit **310**. In some cases the spatial relationship can include aligning the boom axis **131** of the boom member **130** (e.g. when a non-aircraft-fixed in-flight refueling system is used) or the boom axis **311** of the boom fuelling unit **310** (e.g. when utilizing an aircraft-fixed flying boom system), in an engagement enabling orientation.

In some cases, when a non-aircraft-fixed in-flight refueling system is used, the maximal spaced relationship between the boom member **130** of the refueling device **100** and the fuel receptacle **22** of the receiver aircraft **20** at the engagement enabling position can depend on various parameters, such as: the hose **52** length and flexibility, the flight speed, the flight altitude, the characteristics of the force generating arrangement **190**, etc., and in such cases, the maximal space can be calculated as necessary, inter alia dynamically during the refueling process, based on current values of the respective parameters. For example, it can be appreciated that the less flexible the hose **52**, the maximal space between the boom member **130** of the refueling device **100** and the fuel receptacle **22** of the receiver aircraft **20** at the engagement enabling position is reduced. In some cases, the maximal space between the boom member **130** of the refueling device **100** and the fuel receptacle **22** of the receiver aircraft **20** at the engagement enabling position can be defined by the movement range of the boom member **130** in the direction of the fuel receptacle **22** of the receiver aircraft **20**.

In some cases, when utilizing an aircraft-fixed flying boom system, the maximal spaced relationship between the boom member **312** of the boom fuelling unit **310** and the fuel receptacle **22** of the receiver aircraft **20** at the engagement enabling position can also depend on various parameters, such as: the flight speed, the flight altitude, etc., and

- 105 -

in such cases, the maximal space can be calculated as necessary, inter alia dynamically during the refueling process, based on current values of the respective parameters. In some cases, the maximal space between the boom member **312** of the boom fuelling unit **310** and the fuel receptacle **22** of the receiver aircraft **20** at the engagement enabling position can be defined by the extension range of the telescoping aft section **314** in the direction of the fuel receptacle **22** of the receiver aircraft **20**.

In some cases, the spatial relationship between the boom member **130** of the refueling device **100** (e.g. when a non-aircraft-fixed in-flight refueling system is used), or the boom fuelling unit **310** (e.g. when utilizing an aircraft-fixed flying boom system), and the fuel receptacle **22** of the receiver aircraft **20** at the engagement enabling position can also depend on various parameters, such as the characteristics of the fuel receptacle **22** of the receiver aircraft **20**, etc. According to examples of the presently disclosed subject matter the spatial relationship with which the engagement enabling position is associated can also include an angle parameter. In this regard, it can be appreciated that in case the fuel receptacle **22** of the receiver aircraft **20** has an entrance angle, the boom axis **131** of the boom member **130** (e.g. when a non-aircraft-fixed in-flight refueling system is used), or the boom axis **311** of the boom fuelling unit **310** (e.g. when utilizing an aircraft-fixed flying boom system), should be in a spatial disposition that enables the nozzle (nozzle **135** or nozzle **316**) to engage therewith (e.g. the boom axis **131** or boom axis **311** needs to be aligned with a fuel receptacle **22** of the receiver aircraft **20**).

It has been explained herein that when a non-aircraft-fixed in-flight refueling system is used spatial control system **160** can, in accordance with certain examples, be configured for selectively and controllably providing a non-zero angular disposition, angle θ , between the boom axis **131** and the forward direction A, that enables this angle θ to be selectively maintained between the boom axis **131** and the forward direction A at least for a part of the time when the refueling device **100** is being towed by the tanker aircraft **12** via hose **52**, and in particular during the engagement operation of the fuel device **100** to the receiver aircraft **20** and during refueling thereof. It is to be noted that such angle θ can be predetermined. In some cases the angle θ can be stored in the configuration DR **1860**.

It is to be noted that when utilizing an aircraft-fixed flying boom system, a mechanical connection **320** and/or a motion control system **330** can be utilized for

- 106 -

selectively and controllably providing a non-zero angular disposition, angle θ , between the boom axis **311** and the receiver aircraft (e.g., between the boom axis **311** and forward direction, A when the receiver aircraft is also aligned with forward direction A) and selectively maintain this angle θ at least for a part of the time during the engagement operation of the boom fuelling unit **310** to the receiver aircraft **20** and during refueling thereof. It is to be noted that such angle θ can be predetermined, and can lie within a range of angles in which such engagement between the boom fuelling unit **310** to the receiver aircraft **20**. In some cases the angle θ can be stored in the configuration DR **1860**.

10 In some examples, it is to be noted that the engagement enabling position is not necessarily a specific x, y, z coordinate, as, under certain conditions, the exact coordinates of the point of reference for the engagement area can vary, or some tolerance can be accepted (for example using tolerance ranges). In addition, there can be more than one engagement enabling position that meets the conditions detailed herein, 15 each of which is an engagement enabling position.

Before moving on to describe Fig. 19, and for the purpose of providing a visual illustration of an exemplary engagement enabling position, attention is drawn to **Fig. 26** and **Fig. 27**. Reverting to **Fig. 26**, there is shown an illustration of an example of a refueling device not in an engagement enabling position, according to certain examples 20 of the presently disclosed subject matter. It can be appreciated that the receiver aircraft **20**, and more particularly a fuel receptacle **22** thereof, is positioned within the engagement area **2410**, however, the refueling device **100** is not positioned in an engagement enabling position. In this example, as illustrated in Fig. 26, it can be appreciated that the refueling device **100** is not aligned with the fuel receptacle **22** of the receiver aircraft **100**. The illustration of Fig. 26 is provided for clarity of explanation 25 only and is by no means binding. Reverting to **Fig. 27**, there is shown an illustration of an example of a refueling device positioned in an engagement enabling position, according to certain examples of the presently disclosed subject matter. It can be appreciated that the refueling device **100** is positioned in an engagement enabling position that can enable engagement with the fuel receptacle **22** of the receiver aircraft 30 **100**. The illustration of Fig. 27 is provided for clarity of explanation only and is by no means binding.

- 107 -

It is to be noted that a refueling device **100** is shown in Figs. 24-27 for illustration purposes only and other refueling systems can also be used, including, but not limited to, a boom fuelling unit **310** as further detailed herein.

Returning to **Fig. 19**, in some cases, maneuvering instructions module **1820** can be configured to provide the maneuvering instructions for enabling positioning of the receiver aircraft **20** within an engagement area, for example by utilizing a signaling system. Such signaling system can be mounted, for example, on the tanker aircraft **12**, at any location visible to the receiver aircraft **20** pilot. In some cases, the signaling system can provide the receiver aircraft **20** pilot with maneuvering instructions on three axes: forward-backward, left-right and up-down, thus enabling it to maneuver the receiver aircraft **20** to the engagement area **2410**. In some cases the signaling system can be a light directing system. Alternatively or additionally, the maneuvering instructions can be provided to by using voice commands (e.g. by utilizing speakers, pilot headset, etc.) or by any other means known *per se*. In some cases, maneuvering instructions module **1820** can be configured to communicate the maneuvering instructions to an auto pilot system of the receiver aircraft **20**, if such system exists, for causing the auto pilot system to maneuver the receiver aircraft **20** accordingly.

Before moving on to describe Fig. 19, and for the purpose of providing a visual illustration of an exemplary engagement area, attention is drawn to **Fig. 25**, showing an illustration of an example of a receiver aircraft positioned inside a virtual engagement area, according to certain examples of the presently disclosed subject matter. It can be noted that the receiver aircraft **20**, and more particularly the fuel receptacle **22** thereof, are positioned within the engagement area **2410**. Also in this illustration the engagement area **2410** is a virtual pre-determined volume, shaped substantially like a cube, in which, when a non-aircraft-fixed in-flight refueling system is used, the refueling device **100** can navigate until arriving at an engagement enabling position (in which the boom member **130** when a non-aircraft-fixed in-flight refueling system is used or the boom fuelling unit **310** (or nozzle **316** thereof) when utilizing an aircraft-fixed flying boom system, is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**) and engaging with the fuel receptacle **22** of the receiver aircraft **20**, as detailed herein.

- 108 -

Although also in this example the virtual engagement area is shaped substantially like a cube, the virtual engagement area can have any other shape with a certain volume. It can be noted that the illustration further illustrates an example of a signaling system **2420** mounted on tanker aircraft **12**. It can be appreciated that such a signaling system can be used by maneuvering instructions module **1820** for providing maneuvering instructions to the pilot of the receiver aircraft **20**. It is to be noted that alternative and/or additional signaling systems can be used. The illustration of Fig. 25 is provided for clarity of explanation only and is by no means binding.

Bearing all this in mind, and returning to **Fig. 19**, it is to be noted that block **1910** can be performed repeatedly (e.g. every pre-determined period) or continuously, at least until the nozzle **135** or nozzle **316** is engaged with the fuel receptacle **22** of the receiver aircraft **20**, as further detailed herein. Thus, while the receiver aircraft **20** is not positioned within the engagement area, maneuvering instructions module **1820** provides the pilot of the receiver aircraft **20** (and, in some cases, an auto pilot system that controls the maneuvering of the receiver aircraft **20**) with maneuvering instructions for positioning the receiver aircraft **20** within an engagement area.

Although the process above (referring to block **1910**) was described with respect to maneuvering of the receiver aircraft **20**, it is to be noted that in some cases, in addition or as an alternative to maneuvering of the receiver aircraft **20** for approaching the refueling device **100** or the boom fuelling unit **310**, the tanker aircraft **12** can approach the receiver aircraft **20**, thus bringing the refueling device **100** or the boom fuelling unit **310** in the direction of the receiver aircraft **20**. In such cases, the maneuvering instructions can be additionally or alternatively provided to the pilot of the tanker aircraft **12** *mutatis mutandis*.

It is to be further noted that the process relating to block **1910** can in some cases be an independent process, and in other cases it can be performed as part of a sequence of processes, such as engagement sequence **1905**.

Turning now to block **1920** in **Fig. 19**, in some cases, when a non-aircraft-fixed in-flight refueling system is used, once an engagement area specification condition is met (e.g. it is determined that the receiver aircraft **20** is positioned within the engagement area), steering control module **1830** can be configured to provide commands for causing the steering of the refueling device **100** to an engagement

- 109 -

enabling position, in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20** (block **1920**), as further detailed herein, inter alia with respect to Figs. 21 and 23.

5 In some cases, the steering commands module **1830** can be operatively connected to the spatial control system **160** and/or to the force generating arrangement **190** of the refueling device **100**. In such cases, the steering commands module **1830** can provide steering commands for controlling the spatial control system **160** and/or to the force generating arrangement **190** and thus enabling steering the refueling device **100** to
10 an engagement enabling position, in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**.

 In some cases, the steering commands can be based, inter alia, on characteristics of the spatial control system **160**. Such characteristics can be, for example, operation
15 parameters of reaction control thrusters associated with the refueling device and capable of steering the refueling device **100** and/or operation parameters of aero-dynamic control surfaces of the refueling device **100**.

 In some cases, based on the steering commands from the steering commands module **1830**, the refueling device **100** can be adapted to steer automatically. In
20 particular, in some cases, using the commands, autonomous steering of the refueling device **100** can be achieved (e.g. when all the necessary components are fitted within the refueling device **100**).

 Thus, in accordance with some examples of the presently disclosed subject matter, there can be provided a refueling device **100** which can bring itself
25 automatically, and in some cases (when all the necessary components are fitted within the refueling device **100**) autonomously, into fluid communication with the fuel receptacle **22** of the receiver aircraft **20**. In further examples, there can be provided a refueling device which can automatically, and in some cases (when all the necessary components are fitted within the refueling device **100**) autonomously, align its boom
30 axis **131** with a fuel receptacle **22** of the receiver aircraft **20**, and move the boom member **130** in a predetermined trajectory towards the receiver aircraft **20** and thus

- 110 -

enable the refueling device **100** to automatically bring itself into engagement with the fuel receptacle **22** of the receiver aircraft **20**.

It is to be noted that block **1920** can be performed repeatedly (e.g. every pre-determined period) or continuously. For example, block **1920** can be performed until
5 engagement of the nozzle **135** to the fuel receptacle **22** of the receiver aircraft **20**, as further detailed herein, and in some cases even after such engagement. While the refueling device **100** is not positioned within an engagement enabling position, steering control module **1830** provides the refueling device **100** with steering commands for maneuvering the refueling device **100** to the engagement enabling position, in which the
10 boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**.

According to some examples of the examples of the presently disclosed subject matter, when utilizing an aircraft-fixed flying boom system, once an engagement area specification condition is met (e.g. it is determined that the receiver aircraft **20** is
15 positioned within the engagement area), steering control module **1830** can be configured to provide commands for aligning the boom fuelling unit **310** in an engagement enabling position, in which the boom member **311** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**.

20 In some cases, the steering commands module **1830** can be operatively connected to the mechanical connection **320** and/or a motion control system **330** and/or to the telescoping aft section **314** of the boom fuelling unit **310**. In such cases, the steering commands module **1830** can provide alignment commands for controlling a mechanical connection **320** and/or a motion control system **330** and/or to a telescoping
25 aft section **314** of the boom fuelling unit **310** and thus enabling aligning the refueling device **100** at an engagement enabling position, in which the boom fuelling unit **310** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**. It is to be noted that the alignment commands can result in motion of the aircraft-fixed flying boom system in three degrees of
30 freedom (e.g. pitch, yaw and translation).

- 111 -

In some cases, the alignment commands can be based, inter alia, on characteristics of the mechanical connection **320** and/or the motion control system **330** and/or the telescoping aft section **314** of the boom fuelling unit **310**.

In some cases, based on the alignment commands from the steering commands
5 module **1830**, the boom fuelling unit **310** can be adapted to align itself automatically. In particular, in some cases, using the commands, autonomous aligning of the boom fuelling unit **310** can be achieved (e.g. when all the necessary components are fitted within the boom fuelling unit **310**).

Thus, in accordance with some examples of the presently disclosed subject
10 matter, there can be provided a boom fuelling unit **310** which can bring itself automatically, and in some cases (when all the necessary components are fitted within the boom fuelling unit **310**) autonomously, into fluid communication with the fuel receptacle **22** of the receiver aircraft **20**. In further examples, there can be provided a boom fuelling unit **310** which can automatically, and in some cases (when all the
15 necessary components are fitted within the boom fuelling unit **310**) autonomously, align itself with a fuel receptacle **22** of the receiver aircraft **20**, and move itself in a predetermined trajectory towards the receiver aircraft **20** and thus enable the boom fuelling unit **310** to automatically bring itself into engagement with the fuel receptacle **22** of the receiver aircraft **20**.

20 It is to be noted that block **1920** can be performed repeatedly (e.g. every pre-determined period) or continuously. For example, block **1920** can be performed until engagement of the boom fuelling unit **310** to the fuel receptacle **22** of the receiver aircraft **20**, as further detailed herein, and in some cases even after such engagement. While the boom fuelling unit **310** is not positioned within an engagement enabling
25 position, steering control module **1830** provides the boom fuelling unit **310** with alignment commands for maneuvering the boom fuelling unit **310** to the engagement enabling position, in which it is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**.

It is to be further noted that the process relating to block **1920** can in some cases
30 be an independent process, and in other cases it can be performed as part of a sequence of processes, such as engagement sequence **1905**.

- 112 -

Attention is now drawn to block **1930** in **Fig. 19**. In some cases, when a non-aircraft-fixed in-flight refueling system is used, once the receiver aircraft **20** is positioned within the engagement area and the refueling device **100** is positioned in an engagement enabling position (in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**), the engagement/disengagement control module **1850** can be configured to provide the refueling device **100** with an engagement command for causing the refueling device **100** to engage to the fuel receptacle **22** of the receiver aircraft **20** for enabling refueling of the receiver aircraft **20** (block **1930**). It is to be noted that at the engagement enabling position the nozzle **135** is properly aligned with the fuel receptacle **22** (the boom member **130** and boom axis **131** being at the design angle θ_{des} to the forward direction A) and sufficiently close thereto, i.e., at a predetermined spacing from the receiver aircraft, said boom axis being aligned in an engagement enabling orientation at said spaced position.

In some cases, the engagement command can cause activation of the force generating arrangement **190**, e.g., by deploying the air brakes **195**, **196**, thus generating a force along boom axis **131** that effectively pushes the nozzle **135** into engagement with the fuel receptacle **22** of the receiver aircraft **20**. Such force can cause the boom member **130** to move in a predetermined trajectory towards the receiver aircraft **20** for enabling engagement between the nozzle **135** and the fuel receptacle **22** of the receiver aircraft **20** (e.g. for enabling fuel communication therebetween). In some cases, prior to deploying the air brakes **195**, **196**, the boom member **130** can be extended, for example until reaching a pre-determined space from the fuel receptacle **22** of the receiver aircraft **20**. In some cases, the engagement command can cause extension of the boom member **130** until connection with the fuel receptacle **22** of the receiver aircraft **20**, with no use of any air brakes mechanism. In other words, once the refueling device **100** is at the aforesaid engagement enabling orientation and spaced position, the boom member is subsequently moved along said boom axis towards the receiver aircraft for enabling fuel communication therebetween. Movement of the boom member can be effected in one of two ways, or combination thereof: the refueling device **100** remains in the spaced position, and the boom member **130** is extended telescopically; the boom member **130**

- 113 -

can be in the retracted or extended position, and the refueling device **100** is bodily moved towards the receiver aircraft for enabling fuel communication therebetween.

In accordance with some examples of the presently disclosed subject matter, there can be provided a refueling device **100** which can bring itself automatically, and in some cases (when all the necessary components are fitted within the refueling device **100**) autonomously, into fluid communication with the fuel receptacle **22** of the receiver aircraft **20**. In further examples, there can be provided a refueling device **100** which can automatically, and in some cases (when all the necessary components are fitted within the refueling device **100**) autonomously, engage the nozzle **135** with the fuel receptacle **22** of the receiver aircraft **20**.

In some cases, prior to providing the refueling device **100** with an engagement command, maneuvering instructions module **1820** can be configured to cause a signaling system to provide the pilot of the receiver aircraft **20** with a notification indicating that the refueling device **100** is about to engage to the fuel receptacle **22**, thus requiring the pilot of the receiver aircraft **20** to stabilize it.

According to some examples of the examples of the presently disclosed subject matter, when utilizing an aircraft-fixed flying boom system, once the receiver aircraft **20** is positioned within the engagement area and the boom fuelling unit **310** is positioned in an engagement enabling position (in which it is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**), the engagement/disengagement control module **1850** can be configured to provide the boom fuelling unit **310** with an engagement command for causing the boom fuelling unit **310** to engage to the fuel receptacle **22** of the receiver aircraft **20** for enabling refueling of the receiver aircraft **20**. It is to be noted that at the engagement enabling position the boom member **312** is aligned such that the nozzle tip is sufficiently close to the fuel receptacle **22** of the receiver aircraft **20**, i.e., at a predetermined spacing from the fuel receptacle **22** of the receiver aircraft **20**, said boom axis **311** being aligned in an engagement enabling orientation at said spaced position.

In some cases, the engagement command can cause extension of the telescoping aft section **314** thus applying force on the fuel receptacle **22** due to reaction force on the other side of the boom fuelling unit **310**, at the mechanical connection **320**.

- 114 -

In accordance with some examples of the presently disclosed subject matter, there can be provided a boom fuelling unit **310** which can bring itself automatically, and in some cases (when all the necessary components are fitted within the boom fuelling unit **310**) autonomously, into fluid communication with the fuel receptacle **22** of the receiver aircraft **20**. In further examples, there can be provided a boom fuelling unit **310** which can automatically, and in some cases (when all the necessary components are fitted within the boom fuelling unit **310**) autonomously, engage the nozzle **316** with the fuel receptacle **22** of the receiver aircraft **20**.

In some cases, prior to providing the boom fuelling unit **310** with an engagement command, maneuvering instructions module **1820** can be configured to cause a signaling system to provide the pilot of the receiver aircraft **20** with a notification indicating that the boom fuelling unit **310** is about to engage to the fuel receptacle **22**, thus requiring the pilot of the receiver aircraft **20** to stabilize it.

It is to be further noted that the process relating to block **1930** can in some cases be an independent process, and in other cases it can be performed as part of a sequence of processes, such as engagement sequence **1905**.

Attention is now drawn to Block **1940** in **Fig. 19**. In some cases, following engagement sequence **1905**, the system **1805** can be configured to provide a command to the refueling device **100** to perform refueling of the receiver aircraft **20** by pumping fuel to the receiver aircraft **20** from the tanker aircraft **12** (block **1940**). In some cases, when a non-aircraft-fixed in-flight refueling system is used, at any time following engagement sequence **1905**, the system **1805** can be further configured to deactivate the force generating arrangement **190**, e.g. by retracting the air brakes **195**, **196**. In one example, the command to deactivate the force generating arrangement **190** and the refueling command can be issued by the engagement/disengagement module **1850**. Further by way of example, engagement/disengagement module **1850** can be configured to provide a deactivation command when an indication is received that the refueling device **100** is engaged with the receiver aircraft **20**. Further by way of example, the refueling command can be issued for example when an engagement indication is issued.

Attention is now drawn to Block **1950** in **Fig. 19**. the engagement/disengagement control module **1850** can be further configured to provide the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) or

- 115 -

the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) with a disengagement command for causing it to disengage from the fuel receptacle **22** of the receiver aircraft **20** in response to receiving an indication that the fuel level in the fuel tank of the receiver aircraft **20** reached a desired level or when an indication of a hazard
5 is issued (block **1950**).

In some cases, prior to providing the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) with a disengagement command, maneuvering instructions module **1820** can be configured to cause the signaling system to provide the
10 pilot of the receiver aircraft **20** with a notification indicating that the refueling is done, and in some cases instruct the pilot of the receiver aircraft **20** to perform a maneuver in order to fly away from the refueling device **100**.

It is to be noted that throughout the refueling process, safety module **1840** can monitor certain parameters, for example parameters that relate to the spatial dispositions
15 between any two or more of the following: the receiver aircraft **20**, the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) and the tanker aircraft **12**, as well as other parameters including the angles, etc., possibly in comparison to predefined reference thresholds or parameters or ranges, to identify possible hazardous situations.
20 Such hazardous situations can include, inter alia, a dangerous approach of the receiver aircraft **20** to the refueling device **100** or to the tanker aircraft **12**, a dangerous movement of the receiver aircraft **20**, and/or the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) and/or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) and/or the tanker aircraft **12**,
25 including such movement when the refueling device **100** or the boom fuelling unit **310** is engaged to the receiver aircraft **20**, etc. It is to be noted that such hazardous situations can be caused for example due to a human error, environmental conditions (weather, wind, etc.), as well as other causes. It is to be further noted that for monitoring such hazardous situations, safety module **1840** can be configured to utilize, inter alia, sensor
30 control module **1810** for sensing the spatial dispositions of the receiver aircraft **20**, and/or the refueling device **100** and/or the boom fuelling unit **310** and/or the tanker aircraft **12**.

- 116 -

In some cases, when safety module **1840** identifies a hazardous situation (e.g. a safety condition is met or, in some cases, is not met), it can be configured, inter alia, to instruct steering control module **1830** to provide steering instructions for causing the refueling device **100** to steer away from the receiver aircraft **20** (when a non-aircraft-
5 fixed in-flight refueling system is used) or to provide commands for maneuvering the boom fuelling unit **310** away from the receiver aircraft **20**, and/or to provide an indication to the pilot of the receiver aircraft **20** that a hazardous situation has been identified, thus enabling the pilot to maneuver the receiver aircraft **20** away from danger, etc. It is to be noted that in case the hazardous situation is identified after the
10 refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) engaged with the receiver aircraft **20**, safety module **1840** can be further configured to instruct engagement/disengagement module **1850** to cause the refueling device **100** or the boom fuelling unit **310** to disengage from the receiver aircraft **20** prior to performing the
15 maneuvering as detailed herein.

It is to be noted that in some cases, when the receiver aircraft **20** is positioned within the engagement area, or at an earlier stage, the refueling device **100** (when a non-aircraft-fixed in-flight refueling system is used) and/or the boom fuelling unit **310** (when utilizing an aircraft-fixed flying boom system) can be deployed to an initial trail
20 position. Such initial trail position can be defined in terms of a spatial disposition with respect to the tanker aircraft **12** and can be characterized, inter alia, by one or more of the following:

- When a non-aircraft-fixed in-flight refueling system is used -a required deployment length of the hose **52** (that in some cases can depend, inter alia,
25 on the flight speed, the flight altitude, the receiver aircraft **20** type, the engagement area specification, etc., whereas in other cases it can be for example pre-determined) or, when utilizing an aircraft-fixed flying boom system, the extension length of the telescoping aft section **314**;
- A required pitch angle between the boom axis **131** or boom axis **311** and the
30 forward direction A is maintained;

- 117 -

- A required yaw angle between the boom axis **131** or boom axis **311** and the forward direction A is maintained.

In some cases, the steering control module **1830** can be configured to monitor the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** with respect to the tanker aircraft **12** and validate that the refueling device **100** and/or the boom fuelling unit **310** is positioned in the initial trail position with respect to the tanker aircraft **12**. For that purpose, steering control module **1830** can utilize, for example, sensor control module **1810** for repeatedly, and in some cases in real time (for example in the form of a video stream) acquiring an image of the area in which the refueling device **100** and/or the boom fuelling unit **310** is expected to be positioned when in the initial trail position. The image can be acquired by a sensor **1890** that can be mounted, for example, on the tanker aircraft **12** in a position that enables it to acquire images of the area in which the refueling device **100** and/or the boom fuelling unit **310** is expected to be positioned when in the initial trail position. Such sensor position can be, for example, on the tanker aircraft **12** wing, elevators, tail, on the underside of the fuselage, etc. Utilization of such an image can enable determination of the refueling device's **100** and/or the boom fuelling unit **310** spatial disposition with respect to the tanker aircraft **12** (it is to be noted that in some cases such determination is made, for example, repeatedly). For example, the acquired image can be compared with a pre-stored image (e.g. stored on reference data repository **1870**) of the refueling device **100** and/or the boom fuelling unit **310**, illustrating a desired spatial disposition with respect to the tanker aircraft **12**, thus enabling determination of the relative spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** with respect to the tanker aircraft **12** (it is to be noted that in some cases such determination is made, for example, repeatedly). Such desired spatial disposition can, in some cases, depend on various factors, such as, inter alia, the flight speed, the flight altitude, the refueling device **100** weight, etc. It can be appreciated that pre-stored images of different spatial dispositions of the refueling device **100** and/or the boom fuelling unit **310** with respect to the tanker aircraft **12** can be stored in reference DR **1870** and a set of parameters, inter alia, flight speed, flight altitude, refueling device **100** weight, etc., can be specified in association with one or more of the pre-stored images.

- 118 -

According to examples of the presently disclosed subject matter, for a given set of parameters, steering control module **1830** can determine which image is to be used as a reference image. For example, the steering control module **1830** can receive a set of measurements which are correlated with the parameters associated with the images and
5 can compare the current measurements to the various sets of parameters and identify which set is, for example, most closely correlated with the measurements and the steering control module **1830** can select the image with which the parameters are associated as the reference image. Following the selection of the reference image, the steering control module **1830** can repeatedly (e.g. every pre-determined period), or
10 continuously, compare images obtained by the sensor **1890** during the refueling process to the selected reference image, and calculate the spatial disposition of the refueling device **100** with respect to the initial trail position.

In some cases, 3-D models can be used instead of images. According to further examples, the reference DR **1870** can store one or more generic 3-D models (e.g. one
15 for each type of aircraft), and as part of determining the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** with respect to the tanker aircraft **12**, an appropriate 3-D model can be selected (for example according to the type of the receiver aircraft **20**) and the 3-D model can be adapted using current measurements (e.g. obtained by the sensor **1890**) and respective parameters of the 3-D
20 model.

According to other examples of the presently disclosed subject matter, steering control module **1830** can search among the different pre stored reference images for an image which most closely correlates with a current image and can determine the spatial disposition using the pre-stored parameters associated with the selected image.

25 In some cases, the sensor **1890** can be a LIDAR unit **351**. In such cases, the sensor can acquire the images as further detailed herein, inter alia with reference to Figs. 30-32. The images obtained by the LIDAR unit **351** can comprise both depth data and electromagnetic data within the sensing volume **359**. In such cases, the depth and electromagnetic data can be compared with look up tables comprising reference depth
30 data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft **20** and/or the boom fuelling unit **310**, optionally based on the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.) and/or the type of the boom

- 119 -

fuelling unit **310**. Based on the comparison, the spatial disposition of the refueling device **100** or the boom fuelling unit **310** with respect to the tanker aircraft **12** and/or to the fuel receptacle **22** of the receiver aircraft **20** can be calculated. In some cases, a full or partial 3-D model of the refueling device **100** and/or the boom fuelling unit **310** can be calculated based on the depth and electromagnetic data received from the LIDAR unit **351** and such full or partial 3-D model can be compared with one or more pre-stored generic full or partial 3-D models (e.g. one for each type of aircraft and/or one for each type of boom fuelling unit). Based on the comparison, the spatial disposition of the refueling device **100** or the boom fuelling unit **310** with respect to the tanker aircraft **12** and/or to the fuel receptacle **22** of the receiver aircraft **20** can be calculated. The look up tables and/or the 3-D models can be stored for example on the reference DR **1870**.

It is to be noted that various other methods and techniques can be used in order to determine the refueling device's **100** and/or the boom fuelling unit **310** spatial disposition with respect to the tanker aircraft **12** and/or to the fuel receptacle **22** of the receiver aircraft **20** (it is to be noted that in some cases such determination is made, for example, repeatedly).

It is to be noted that, with reference to Fig. 19, some of the blocks can be integrated into a consolidated block or can be broken down to a few blocks and/or other blocks may be added. Furthermore, in some cases, the blocks can be performed in a different order than described herein. It should be also noted that whilst the flow diagrams are described also with reference to the system elements that realizes them, this is by no means binding, and the blocks can be performed by elements other than those described herein.

Turning to **Fig. 20**, there is shown a flowchart illustrating a sequence of operations carried out for providing maneuvering commands for positioning a receiver aircraft within an engagement area related thereto, according to certain examples of the presently disclosed subject matter. Maneuvering instructions module **1820** can be configured to determine (it is to be noted that in some cases, as indicated herein, such determination is made, for example, repeatedly) the receiver aircraft's **20** spatial disposition with respect to the engagement area related thereto (block **2005**), as further detailed with respect to Fig. 22.

- 120 -

Following determination of the receiver aircraft's **20** spatial disposition with respect to the engagement area related thereto, maneuvering instructions module **1820** can be configured to check if the receiver aircraft **20** is positioned within the engagement area (block **2010**), based for example on current measurements from
5 sensor/s **1890** as described herein. In some examples, in case the receiver aircraft **20** is positioned within the engagement area, and until the refueling device **100** is engaged with the fuel receptacle **22** of the receiver aircraft **20** (in some cases this process can continue until the refueling process ends), the maneuvering instructions module **1820** can be configured to return to block **2005** and re-determine the receiver aircraft's **20**
10 spatial disposition with respect to the engagement area related thereto.

In some examples, in case the receiver aircraft **20** is not positioned within the engagement area, maneuvering instructions module **1820** can be configured to calculate maneuvering instructions for positioning the receiver aircraft **20** within the engagement area (block **2020**). It can be appreciated that once the maneuvering instructions module
15 **1820** determines the receiver aircraft's **20** spatial disposition with respect to the engagement area related thereto, it can also calculate maneuvering instructions for positioning the receiver aircraft **20** within the engagement area related thereto. Maneuvering instructions module **1820** can also provide the calculated maneuvering instructions for positioning the receiver aircraft **20** (and, in some cases, an auto pilot
20 system that controls the maneuvering of the receiver aircraft **20**) within the engagement area related thereto to the pilot of the receiver aircraft **20** (block **2030**) and return to block **2005**.

It is to be noted that, in some cases, as indicated herein, maneuvering instructions module **1820** can be configured to provide the maneuvering instructions by
25 using a light directing system. Such light directing system can be mounted, for example, on the tanker aircraft **12**, at any location visible to the receiver aircraft **20** pilot. In some cases, the light directing system can provide the pilot of the receiver aircraft **20** with maneuvering instructions on three axes: forward-backward, left-right and up-down, thus enabling it to maneuver the receiver aircraft **20** to the engagement area **2110**.
30 Alternatively or additionally, the maneuvering instructions can be provided by using voice commands (e.g. by utilizing speakers, pilot headset, etc.) or by any other means known per se. In some cases, maneuvering instructions module **1820** can be configured

- 121 -

to communicate the maneuvering instructions to an auto pilot system of the receiver aircraft **20**, if such system exists.

It is to be noted that, with reference to Fig. 20, some of the blocks can be integrated into a consolidated block or can be broken down to a few blocks and/or other blocks may be added. Furthermore, in some cases, the blocks can be performed in a different order than described herein. It should be also be noted that whilst the flow diagrams are described also with reference to the system elements that realizes them, this is by no means binding, and the blocks can be performed by elements other than those described herein.

It is to be further noted that in some cases instead of monitoring that the receiver aircraft **20** is positioned within the engagement area, an alternative light directing system can be used. Such an alternative lighting system can be designed to display alternative light indications depending on the angle from which it is viewed. Thus, in some cases, viewing the light directing system from its bottom side can result in display of light in a certain color, looking at the same light directing system from its upper side can result in display of light in a second color, looking at the same light directing system from its right side can result in display of light in a third color, and looking at the same light directing system from its left side can result in display of light in a fourth color. Additional angles can result in display of additional colors. When using such a light directing system, upon arrival of the receiver aircraft **20** to the engagement area, the light directing system can be automatically directed to the receiver aircraft **20** (based on its current determined spatial disposition) and provide a color indication indicating that it is positioned within the engagement area. If the receiver aircraft **20** does not maintain its position, the pilot will receive appropriate color indications from the light directing system so that he will be able to make the required corrections to maintain the receiver aircraft's **20** spatial disposition.

Turning to **Fig. 21**, there is shown a flowchart illustrating a sequence of operations carried out for providing steering commands to a refueling device for maneuvering to an engagement enabling position, according to certain examples of the presently disclosed subject matter.

When a non-aircraft-fixed in-flight refueling system is used steering control module **1830** can be configured to determine (it is to be noted that in some cases, as

- 122 -

indicated herein, such determination is made, for example, repeatedly) the refueling device's **100** spatial disposition with respect to the engagement enabling position (in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**) related thereto (block **2105**), as further detailed with respect to Fig. 23.

Following determination of the refueling device's **100** spatial disposition with respect to the engagement enabling position related thereto, steering control module **1830** can be configured to check if the refueling device **100** is positioned within the engagement enabling position (block **2110**). In case the refueling device **100** is positioned within the engagement enabling position (in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**), and at least until the refueling device **100** is engaged with the fuel receptacle **22** of the receiver aircraft **20** (in some cases this process can continue until the refueling process ends), the steering control module **1830** can be configured to return to block **2105** and re-determine the refueling device's **100** spatial disposition with respect to the engagement enabling position related thereto.

In case the refueling device **100** is not positioned within the engagement enabling position (in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**), steering control module **1830** can be configured to calculate steering commands for maneuvering the refueling device **100** to an engagement enabling position, in which the boom member **130** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20** (block **2120**). It can be appreciated that once the steering control module **1830** determines the refueling device's **100** spatial disposition with respect to an engagement enabling position related thereto, it can also calculate steering commands for maneuvering the refueling device **100** to an engagement enabling position related thereto. Steering control module **1830** can also provide the refueling device **100** with calculated steering commands for maneuvering the refueling device **100** to an engagement enabling position related thereto (block **2130**) and return to block **2105**. The steering commands can control the operation of components of the spatial control system **160** and/or the force generating arrangement **190**.

- 123 -

When utilizing an aircraft-fixed flying boom system, steering control module **1830** can be configured to determine (it is to be noted that in some cases, as indicated herein, such determination is made, for example, repeatedly) the boom fuelling unit **310** spatial disposition with respect to the engagement enabling position (in which the boom member **312** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**) related thereto (block **2105**), as further detailed with respect to Fig. 23.

Following determination of the boom fuelling unit **310** spatial disposition with respect to the engagement enabling position related thereto, steering control module **1830** can be configured to check if the boom fuelling unit **310** is positioned within the engagement enabling position (block **2110**). In case the boom fuelling unit **310** is positioned within the engagement enabling position (in which the boom member **312** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**), and at least until the boom fuelling unit **310** is engaged with the fuel receptacle **22** of the receiver aircraft **20** (in some cases this process can continue until the refueling process ends), the steering control module **1830** can be configured to return to block **2105** and re-determine the boom fuelling unit **310** spatial disposition with respect to the engagement enabling position related thereto.

In case the boom fuelling unit **310** is not positioned within the engagement enabling position (in which the boom member **312** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**), steering control module **1830** can be configured to calculate alignment commands for maneuvering the boom fuelling unit **310** to an engagement enabling position, in which the boom member **312** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20** (block **2120**). It can be appreciated that once the steering control module **1830** determines the boom fuelling unit **310** spatial disposition with respect to an engagement enabling position related thereto, it can also calculate alignment commands for maneuvering the boom fuelling unit **310** to an engagement enabling position related thereto. Steering control module **1830** can also provide the boom fuelling unit **310** with calculated alignment commands for maneuvering the boom fuelling unit **310** to an engagement enabling position related thereto (block **2130**) and return to block **2105**.

- 124 -

The alignment commands can control the operation of components of the motion control system **330** and/or the mechanical connection **320** and/or the telescoping aft section **314**.

It is to be noted that, with reference to Fig. 21, some of the blocks can be integrated into a consolidated block or can be broken down to a few blocks and/or other blocks may be added. Furthermore, in some cases, the blocks can be performed in a different order than described herein. It should also be noted that whilst the flow diagrams are described also with reference to the system elements that realizes them, this is by no means binding, and the blocks can be performed by elements other than those described herein.

Turning to **Fig. 22**, there is provided a flowchart illustrating a sequence of operations carried out for determining the receiver aircraft's spatial disposition with respect to the engagement area related thereto, according to certain examples of the presently disclosed subject matter. In some cases, maneuvering instructions module **1820** can be configured to acquire an image of the receiver aircraft **20** (block **2210**).

For that purpose, in some cases, maneuvering instructions module **1820** can be configured to utilize sensor control module **1810** for repeatedly (e.g. every pre-determined period) or continuously (e.g. in the form of a video stream) acquiring an image of the area aft the refueling device **100** and/or aft the tanker aircraft **12**, at a predetermined Field of View. Such Field of View can depend, inter alia, on the distance from which a receiver aircraft **20** is to be identified. In some cases, the farther it is required to identify the receiver aircraft, the larger the Field of View is.

It is to be noted that although reference in the description is sometimes made to an image, any other data that can be indicative of presence of a receiver aircraft can be utilized *mutatis mutandis* (e.g. radar data, acoustic signature data, etc.). It is to be further noted that in some cases, when reference is made to an image (throughout the description) it can also include an image based on data acquired by the LIDAR unit **351**.

For the purpose of acquiring an image, sensor control module **1810** can be configured to utilize sensor **1890**. In some cases, one or more sensor/s **1890** can be mounted on the refueling device **100** and/or on the tanker aircraft **12**. As indicated herein, in some cases the imaging system **150** can be used as one or more of the sensor/s

- 125 -

1890. It is to be noted that, as indicated herein, the imaging system **150** can, in some cases, comprise one or more FLADAR units and/or one or more LIDAR units **351**.

It can be appreciated that for acquiring an image of the receiver aircraft **100**, the receiver aircraft **100** should be present in the sensed area (e.g. the sensing volume **159** or the sensing volume **359**). In some cases the receiver aircraft **20** is expected to approach the refueling device **100** and/or the boom fuelling unit **310** and/or the fuel tanker **12** for the refueling process to begin. In some cases, the approach of receiver aircraft **20** to the refueling device **100** and/or the boom fuelling unit **310** is made from a certain direction or through a virtual funnel such as, for example, from the rear and bottom side of the refueling device **100** and/or the boom fuelling unit **310** and/or the fuel tanker **12** while the pilot of the receiver aircraft **20** has a line of sight to the refueling device **100** and/or the boom fuelling unit **310** and/or the fuel tanker **12**. However, in other cases, other directions of approach are also possible (e.g. approach from the front and bottom side of the refueling device **100** and/or the boom fuelling unit **310** and/or the fuel tanker **12**, etc.), depending, inter alia, on the characteristics of the receiver aircraft **20** (e.g. the location of the fuel receptacle **22** of the receiver aircraft **20**, etc.).

In some cases, maneuvering instructions module **1820** can be configured to analyze sensed images in order to determine if a receiver aircraft **20** can be identified within the sensed image. It is to be noted that such analysis can be performed using various known methods and techniques, such as, in the case of digital images - image correlation, in the case of LIDAR based images – comparison with look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft, optionally based on the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.), etc.

In some cases, maneuvering instructions module **1820** can be configured to cause the signaling system to provide the pilot of the receiver aircraft **20** with a notification indicating that its location with respect to the engagement area has been acquired. Such indication can be provided, for example, by a signaling system (e.g. a lighting system mounted on the refueling device **100** and/or the boom fuelling unit **310** and/or on the tanker aircraft **12**, etc.). Additionally or alternatively, the indication can be a voice indication provided to the pilot of the receiver aircraft **20** (e.g. by utilizing

- 126 -

speakers, pilot headset, etc.). Additionally or alternatively, the indication can be any other indication (including visual or voice indication) provided to the pilot of the receiver aircraft **20** (e.g. by utilizing speakers, pilot headset, a display, a light, etc.).

In some cases, maneuvering instructions module **1820** can be further configured to fetch configuration data (block **2220**), including, inter alia, data indicative of the engagement area specification. As detailed herein, the engagement area can be defined by various specifications that depend on several parameters, such as, for example, the length of the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), the extension length of the telescoping aft section **314** (when utilizing an aircraft-fixed flying boom system), the flight speed, the flight altitude, weather conditions, the fuel pressure within the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), the location of the fuel receptacle **22** of the receiver aircraft **20**, etc.

In some cases, maneuvering instructions module **1820** can be further configured to fetch a reference image of a reference receiver aircraft (block **2230**). In some cases the reference image is fetched inter alia according to the fetched configuration data and/or the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.). Such a reference image can be an image of an aircraft similar to the actual receiver aircraft **20**, and in some cases of identical type as the actual receiver aircraft **20**. If necessary, the maneuvering instructions module **1820** can obtain current measurements for certain parameters in the configuration DR **1860**, to compute appropriate engagement area specifications.

It is to be noted that such a reference image should depict a scene in which the reference aircraft is positioned within the engagement area having the fetched specification (fetched in block **2220**). In some cases, the reference image can depict a scene in which the reference aircraft is not positioned within the engagement area having the fetched specification, however the offset of the reference receiver aircraft from the engagement area can be calculated or alternatively is *a-priori* known.

Maneuvering instructions module **1820** can be further configured to utilize the reference image of a reference receiver aircraft within the engagement area having the fetched specification (or not within such engagement area but with data of its offset from the engagement area) for calculating the relative spatial disposition of the receiver aircraft with respect to the engagement area (block **2240**), for example using methods

and techniques known *per se* (such as, in the case of digital images, image correlation, etc.).

In some cases, 3-D models can be used instead of images. According to further examples, the reference DR **1870** can store one or more generic 3-D models (e.g. one for each type of aircraft), and as part of determining the spatial disposition of the receiver aircraft **20** with respect to the engagement area, an appropriate 3-D model can be selected (for example according to the type of the receiver aircraft **20**) and the 3-D model can be adapted using current measurements (e.g. obtained by the sensor **1890**) and respective parameters of the 3-D model.

It is to be noted that various other methods and techniques can be used in order to determine the receiver aircraft's **20** spatial disposition with respect to the engagement area.

One example of such alternative technique is using LIDAR. In such cases, the sensor **1890** can be a LIDAR unit **351** that can acquire the images as further detailed herein, inter alia with reference to Figs. 30-32. As indicated herein, the images obtained by the LIDAR unit **351** can comprise both depth data and electromagnetic data within the sensing volume **359**. In such cases, the depth and electromagnetic data can be compared with one or more look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft, optionally based on the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.). Based on the comparison, the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** and/or the receiver aircraft **20** with respect to the tanker aircraft **12** can be calculated. In some cases, a full or partial 3-D model of the receiver aircraft **20** and/or the refueling device **100** and/or the boom fuelling unit **310** can be calculated based on the depth and electromagnetic data received from the LIDAR unit **351** and such full or partial 3-D model can be compared with one or more pre-stored generic full or partial 3-D models (e.g. one for each type of aircraft). Based on the comparison, the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** and/or the receiver aircraft **20** with respect to the tanker aircraft **12** can be calculated. The look up tables and/or the 3-D models can be stored for example on the reference DR **1870**.

- 128 -

It is to be noted that, with reference to Fig. 22, some of the blocks can be integrated into a consolidated block or can be broken down to a few blocks and/or other blocks may be added. Furthermore, in some cases, the blocks can be performed in a different order than described herein. It should be also be noted that whilst the flow diagrams are described also with reference to the system elements that realizes them, this is by no means binding, and the blocks can be performed by elements other than those described herein.

Turning to **Fig. 23** there is provided a flowchart illustrating a sequence of operations carried out for determining the refueling device's **100** (or boom fuelling unit **310**) spatial disposition with respect to the engagement enabling position, according to certain examples of the presently disclosed subject matter. In some cases, steering control module **1830** can be configured to acquire an image of the receiver aircraft **20** (block **2310**), and, in some cases, more specifically, of the area of the fuel receptacle **22** of the receiver aircraft **20**.

For that purpose, in some cases, steering control module **1830** can be configured to utilize sensor control module **1810** for repeatedly (e.g. every pre-determined period) or continuously acquiring an image (it is to be noted again that although reference in the description is made to an image, any other data that can be indicative of presence of a receiver aircraft can be utilized *mutatis mutandis*). It is to be further noted that in some cases, when reference is made to an image it can also include an image based on data acquired by the LIDAR unit **351**) of the area aft the refueling device **100** or boom fuelling unit **310**, at a predetermined Field of View. Such Field of View can depend, inter alia, on the distance from which a receiver aircraft **20**, and more specifically a fuel receptacle **22** thereof, is to be identified. In some cases, the farther it is required to identify the receiver aircraft, and more specifically a fuel receptacle **22** thereof, the larger the Field of View is.

For the purpose of acquiring an image, sensor control module **1810** can be configured to utilize sensor **1890**. In some cases, one or more sensor/s **1890** can be mounted on the refueling device **100** and/or the boom refueling unit **310** and/or on the tanker aircraft **12**. As indicated herein, in some cases the imaging system **150** can be used as one or more of the sensor/s **1890**. It is to be noted that, as indicated herein, the

- 129 -

imaging system **150** can, in some cases, comprise one or more FLADAR units and/or one or more LIDAR units **351**.

It can be appreciated that for acquiring an image of the receiver aircraft **20**, and more specifically a fuel receptacle **22** thereof, the receiver aircraft **20**, and more specifically a fuel receptacle **22** thereof, must be present in the sensed area (e.g. the sensing volume **159**). In some cases, the receiver aircraft **20** is expected to be positioned within the engagement area related thereto.

In some cases steering control module **1830** can be configured to analyze a sensed image in order to determine if a receiver aircraft **20**, and more specifically a fuel receptacle **22** thereof, can be identified within the sensed image. A series of images can be analyzed, each substantially immediately after it has been captured (for example as described herein), in order for the steering control module **1830** to be able to provide steering or alignment commands that are based on the actual (dynamic) relative position of the refueling device **100** and/or the boom fuelling unit **310** and the engagement enabling position.

In some cases, 3-D models can be used instead of images. According to further examples, the reference DR **1870** can store one or more generic 3-D models (e.g. one for each type of aircraft), and as part of determining the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** with respect to the engagement enabling position, an appropriate 3-D model can be selected (for example according to the type of the receiver aircraft **20**) and the 3-D model can be adapted using current measurements (e.g. obtained by the sensor/s **1890**) and respective parameters of the 3-D model.

It is to be noted that such analysis can be performed using various known methods and techniques, such as, in the case of digital images - image correlation, in the case of LIDAR based images – comparison with look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft, optionally based on the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.), etc.

In some cases, steering control module **1830** can be further configured to fetch configuration data (block **2320**), including, inter alia, data indicative of the engagement

- 130 -

enabling position specification. As detailed herein, the engagement enabling position can be defined by a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**. As further indicated herein, such configuration data can depend on several parameters, such as, for example, the length of the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), the extension length of the telescoping aft section **314** (when utilizing an aircraft-fixed flying boom system), the flight speed, the flight altitude, weather conditions, the fuel pressure within the hose **52** (when a non-aircraft-fixed in-flight refueling system is used), the location of the fuel receptacle **22** of the receiver aircraft **20**, etc. The configuration data is fetched according to current measurements and respective parameters stored in association with each set of configuration data.

In some cases, steering control module **1830** can be further configured to fetch a reference image of a reference receiver aircraft, and more specifically a fuel receptacle thereof (block **2330**). In some cases the reference image is fetched inter alia according to the fetched configuration data (which, in turn, was fetched according to current measurements and respective parameters stored in association with each set of configuration data). Such a reference image can be an image of an aircraft, and more specifically a fuel receptacle thereof, similar, and in some cases identical to, the actual receiver aircraft **20**, and more specifically, an actual fuel receptacle **22** of the actual receiver aircraft **20**.

It is to be noted that such a reference image should depict a scene in which the reference aircraft, and more specifically a fuel receptacle thereof, is positioned within an engagement enabling position having the fetched specification (fetched in block **2320**). In some cases, the reference image can depict a scene in which the reference aircraft, and more specifically a fuel receptacle thereof, is not positioned within the engagement enabling position having the fetched specification, however the offset of the reference receiver aircraft from the engagement enabling position can be calculated or alternatively is *a-priori* known.

In some cases, steering control module **1830** can be further configured to utilize the reference image of a reference receiver aircraft, and more specifically a fuel receptacle thereof, within the engagement area having the fetched specification (or not within such engagement area but with data of its offset from the engagement area) for

- 131 -

calculating the relative spatial disposition of the receiver aircraft **20**, and more specifically the fuel receptacle **22** thereof, with respect to an engagement enabling position (block **2340**), for example using methods and techniques known *per se* (such as, in the case of digital images, image correlation, etc.).

5 In some cases, 3-D models can be used instead of images. According to further examples, the reference DR **1870** can store one or more generic 3-D models (e.g. one for each type of aircraft), and as part of determining the spatial disposition of the refueling device **100** with respect to engagement enabling position, an appropriate 3-D model can be selected (for example according to the type of the receiver aircraft **20**) and
10 the 3-D model can be adapted using current measurements (e.g. obtained by the sensor **1890**) and respective parameters of the 3-D model.

It is to be noted that various other methods and techniques can be used in order to determine the refueling device **100** and/or the boom fuelling unit **310** spatial disposition with respect to the engagement area.

15 One example of such alternative technique is using LIDAR. In such cases, the sensor **1890** can be a LIDAR unit **351** that can acquire the images as further detailed herein, inter alia with reference to Fig. 30-32. As indicated herein, the images obtained by the LIDAR unit **351** can comprise both depth data and electromagnetic data within the sensing volume **359**. In such cases, the depth and electromagnetic data can be
20 compared with one or more look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft, optionally based on the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.). Based on the comparison, the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** and/or the receiver aircraft **20** with respect to the
25 tanker aircraft **12** can be calculated. In some cases, a full or partial 3-D model of the receiver aircraft **20** and/or the refueling device **100** and/or the boom fuelling unit **310** can be calculated based on the depth and electromagnetic data received from the LIDAR unit **351** and such full or partial 3-D model can be compared with one or more pre-stored generic full or partial 3-D models (e.g. one for each type of aircraft). Based
30 on the comparison, the spatial disposition of the refueling device **100** and/or the boom fuelling unit **310** and/or the receiver aircraft **20** with respect to the tanker aircraft **12** can

- 132 -

be calculated. The look up tables and/or the 3-D models can be stored for example on the reference DR **1870**.

It is to be noted that, with reference to Fig. 23, some of the blocks can be integrated into a consolidated block or can be broken down to a few blocks and/or other blocks may be added. Furthermore, in some cases, the blocks can be performed in a different order than described herein. It should be also be noted that whilst the flow diagrams are described also with reference to the system elements that realizes them, this is by no means binding, and the blocks can be performed by elements other than those described herein.

Looking, by way of example, at **Fig. 28**, there is shown an illustration of an example of a sensed image indicating that the refueling device is not positioned in an engagement enabling position, according to certain examples of the presently disclosed subject matter. In some cases, the sensed image of the receiver aircraft **20**, and more specifically a fuel receptacle **22** thereof, and the reference image of the reference receiver aircraft, and more specifically a fuel receptacle thereof, can contain some elements (e.g. **2810**, **2820**, **2830**, **2840**, etc.) that enable determination of the sensed image offset from the reference image (thereby enabling determination of the offset of the refueling device **100** or the boom fuelling unit **310** from an engagement enabling position, in which the boom member **130** or boom member **312** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**). It is to be noted that virtual cross **2850** indicates the center of the image. Such elements (e.g. **2810**, **2820**, **2830**, **2840**) can be used for example by various known *per se* image correlation algorithms in order to determine the spatial disposition of the receiver aircraft **20**, and more specifically the fuel receptacle **22** thereof, with respect to an engagement enabling position. The illustration of Fig. 28 is provided for clarity of explanation only and is by no means binding.

Attention is now drawn to **Fig. 29**, showing an illustration of an example of a reference image indicating that the refueling device is positioned in an engagement enabling position, according to certain examples of the presently disclosed subject matter. Looking at the illustration, it can be appreciated that the fuel receptacle of a receiver aircraft should be aligned with the cross **2850** (that indicates the center of the image) and that elements **2810**, **2820**, **2830**, and **2840** should also be aligned with the

- 133 -

cross **2850** vertical and horizontal axis, thus indicating that a refueling device is positioned in an engagement enabling position, in which the boom member **130** or boom member **312** is in a predetermined maximal spaced and spatial relationship with respect to the fuel receptacle **22** of the receiver aircraft **20**. It can be appreciated that
5 there is an offset between the sensed image shown in **Fig. 28** and the reference image shown in **Fig. 29**, thus indicating that at the time the sensed image shown in **Fig. 28** was sensed, the refueling device **100** or the boom fuelling unit **310** was not in an engagement enabling position. The illustration of Fig. 29 is provided for clarity of explanation only and is by no means binding.

10 It has been indicated herein that when a non-aircraft-fixed in-flight refueling system is used the engagement enabling position is a position from which utilization of the force generating arrangement **190** enables the nozzle **135** to engage with the fuel receptacle **22** of the receiver aircraft **20**. When utilizing an aircraft-fixed flying boom system, the engagement enabling position is a position from which the nozzle **316** is
15 able to engage with the fuel receptacle **22** of the receiver aircraft **20**. Therefore, in some cases, there can be more than one engagement enabling position that meets such criteria and thus, in some cases, a certain offset between the sensed image and the reference image can be allowed, as long as the refueling device is in a position from which, when a non-aircraft-fixed in-flight refueling system is used, utilization of the force generating
20 arrangement **190** enables the nozzle **135** to engage with the fuel receptacle **22** of the receiver aircraft **20** or from which, when utilizing an aircraft-fixed flying boom system, the nozzle **316** is able to engage with the fuel receptacle **22** of the receiver aircraft **20**.

It is to be noted that various other methods and techniques can be used in order to determine the receiver aircraft's **20** spatial disposition with respect to the engagement
25 enabling position, including the known *per se* 3-D modeling adaptation and/or the selection of the reference image which provides the highest correlation to the sensed data.

OPERATION MODE II

In this operation mode, once the tanker aircraft **12** and receiver aircraft **20** are in
30 close proximity and flying in formation, with the receiver aircraft **20** at a position behind the tanker aircraft **12**, the refueling device is flown into engagement with the fuel receptacle **22** of the receiver aircraft **20** by an operator.

- 134 -

In a first example of Operation Mode II, the operator is stationed in the tanker aircraft **12**, which comprises a suitable control station operatively connected to the refueling device, which can be refueling device **100** according to the first example or alternative variations thereof, or refueling device **200** according to the second example or alternative variations thereof, or a refueling device according to other suitable examples thereof according to the first aspect of the presently disclosed subject matter. The control station comprises a display device for suitably displaying data relating to the spatial disposition of the refueling device at least with respect to the receiver aircraft **20** and the fuel receptacle **22** thereof, and an output device for providing control signals to the refueling device for controlling the flight thereof.

For example, and referring to refueling device **100** according to the first example or alternative variations thereof, the display device can comprise a screen display that displays real time images (2D, and/or stereoscopic images, and/or 3D images), for example in video streams, provided by the imaging system **150**. Additionally or alternatively, such imaging can be provided or augmented via suitable cameras or other imaging units, provided on the tanker aircraft **12** and/or the receiver aircraft **20** and/or any other suitable air vehicle in the vicinity of the refueling device **100**, and thus in at least some such examples the refueling device **100** can omit the imaging system **150**.

The output device can comprise, for example, a joystick that is hand-manipulated by the operator to provide the required control signals to the spatial control system **160**, in particular the controllable aerodynamic surfaces thereof, to provide the required design angle θ_{des} between the boom axis **131** and the forward direction A, while flying the refueling device **100** into proximity with the receiver aircraft **20** and the fuel receptacle **22** thereof.

The operator first ensures that the refueling device **100** is being towed behind the tanker aircraft **12** at a suitable distance therefrom, and can control this spacing by extending or retracting the hose **52** with respect to the tanker aircraft **12**.

When the operator determines that the nozzle **135** is properly aligned with the fuel receptacle **22** (the boom member **130** and boom axis **131** being at the design angle θ_{des} to the forward direction A) and sufficiently close thereto, i.e., at the engagement enabling position at a predetermined spacing from the receiver aircraft, said boom axis being aligned in an engagement enabling orientation at said spaced position, the operator

- 135 -

provides a suitable control signal to the refueling device **100** to activate the force generating arrangement **190**, i.e., by deploying the air brakes **195, 196**, generating a force along boom axis **131** that effectively pushes the nozzle into engagement with the receptacle **22**. In other words, once the refueling device **100** is at the aforesaid engagement
5 enabling orientation and spaced position, the boom member is subsequently moved along said boom axis towards the receiver aircraft for enabling fuel communication therebetween. Movement of the boom member can be effected in one of two ways, or combination thereof: the refueling device **100** remains in the spaced position, and the boom member **130** is extended telescopically; the boom member **130** can be in the
10 retracted or extended position, and the refueling device **100** is bodily moved towards the receiver aircraft for enabling fuel communication therebetween.

Thereafter, the air brakes **195, 196** are retracted, and fuel is pumped to the receiver aircraft **20** from the tanker aircraft **12**. The refueling device **100** can be automatically or manually controlled to maintain the required design angle θ_{des} between then boom axis **131**
15 and the forward direction A during refueling.

Once refueling is completed, the operator disengages the nozzle **135** from the fuel receptacle **22** and flies the refueling device **100** at least to a safe position away from the receiver aircraft **20**, and/or the receiver aircraft **20** maneuvers to such a position, and the refueling device **100** can be retracted back into the tanker aircraft **12**, or reused with
20 another receiver aircraft **20**.

It is to be noted that the same operator can carry out Operation Mode II with each of the plurality of refueling systems **50** of the tanker aircraft **12**. Alternatively, the tanker aircraft **12** can comprise a dedicated control station operatively connected to each refueling device **100**, and operated by a respective dedicated operator; thus different operators
25 control each of the refueling devices **100**.

In an alternative variation of this example of Operation Mode II, the operator is stationed in another aircraft different from the receiver aircraft **20** or tanker aircraft **12**, or is located in a ground station, and Operation Mode II can be carried out in a similar; manner to that described above for the first example, *mutatis mutandis*, with the main
30 difference that the operator receives the data relating to the spatial disposition of the refueling device at least with respect to the receiver aircraft **20** and the fuel receptacle **22** thereof, and provides control signals to the refueling device for controlling the flight

- 136 -

thereof, via a suitable communications link respect to the refueling device **100**, which is correspondingly equipped with suitable communication system.

In another alternative variation of this example of Operation Mode II, the operator is stationed in the receiver aircraft **20** rather than in tanker aircraft **12**, and Operation Mode
5 II can be carried out in a similar; manner to that described above for the first example, *mutatis mutandis*, with the main difference that the operator receives the data relating to the spatial disposition of the refueling device at least with respect to the receiver aircraft **20** and the fuel receptacle **22** thereof, and provides control signals to the refueling device for controlling the flight thereof, via a suitable communications link with respect to the
10 refueling device **100**, and the receiver aircraft **20** and the refueling device **100** are each correspondingly equipped with a suitable communication system. Alternatively, in at least some circumstances, the operator can have the refueling device **100** in particular the boom member **130** and nozzle **135**, and the fuel receptacle **22** in the operator's visual field of view, and does not require the aforesaid spatial disposition data in order to control the
15 refueling device **100**, and thus in such cases the refueling device **100** can omit the imaging system **150**.

Clearly, Operation Mode II can be applied to other variations of the first example of refueling device **100**, or to the second example of refueling device **200** or alternative variations thereof, in a similar manner to that described above for the first example of
20 refueling device **100**, *mutatis mutandis*.

It is to be noted that according to Operation Mode I and/or Operation Mode II, the refueling unit can be selectively controlled to adopt an aligned configuration with the hose **52**. By way of non-limiting example, such a situation is illustrated in Fig. **2** for the fuselage-mounted system **50**. Such a configuration can include controlling the spatial
25 control system **160** to align the longitudinal axis **111** with the forward direction A in the case of the first example of refueling device **100** or alternative variations thereof, or maintaining the boom **230** in a retracted configuration accommodated in body **210** in the case of the second example of refueling device **200** or alternative variations thereof, for example.

OPERATION MODE III

In this operation mode, the tanker aircraft **12** and receiver aircraft **20** are maneuvered to be in close proximity and flying in formation, with the receiver aircraft **20** at a position behind the tanker aircraft **12**. It is first ensured that the refueling device **100** is being towed behind the tanker aircraft **12** at a suitable distance therefrom, and an operator (typically in the tanker aircraft) can control this spacing by extending or retracting the hose **52** with respect to the tanker aircraft **12**.

In a first example of Operation Mode III, the refueling device **100** is not flown or controlled per se, but attains a stable configuration with the boom member **135** at the required angle with respect to the forward direction A, design angle θ_{des} . Accordingly the refueling device **100** can optionally omit the controllable spatial control system **160**, and instead comprises a suitable configuration that provides stability to the boom member **135** at this spatial disposition.

The receiver aircraft **20** maneuvers to a position where it can engage the nozzle to the receiver aircraft fuel receptacle, and when an operator in the receiver aircraft (for example the pilot) determines that the nozzle **135** is properly aligned with the fuel receptacle **22** and sufficiently close thereto, the operator provides a suitable control signal to the refueling device **100** to activate the force generating arrangement **190**, i.e., by deploying the air brakes **195, 196**, generating a force along boom axis **131** that effectively pushes the nozzle into engagement with the receptacle **22**. Thereafter, the air brakes **195, 196** are retracted, fuel is pumped to the receiver aircraft **20** from the tanker aircraft **12**, and the refueling device **100** maintains the required design angle θ_{des} between then boom axis **131** and the forward direction A during refueling.

The receiver aircraft can comprise a display device for suitably displaying data relating to the spatial disposition of the refueling device at least with respect to the receiver aircraft **20** and the fuel receptacle **22** thereof.

For example, and referring to refueling device **100** according to the first example or alternative variations thereof, the display device can comprise a screen display that displays to the operator (for example the pilot or navigator of the receiver aircraft) real time images (2D, and/or stereoscopic images, and/or 3D images), for example in video streams, provided by the imaging system **150**. Additionally or alternatively, such imaging

- 138 -

can be provided or augmented via suitable cameras or other imaging units, provided on the tanker aircraft **12** and/or the receiver aircraft **20** and/or any other suitable air vehicle in the vicinity of the refueling device **100**, and thus in at least some such examples the refueling device **100** can omit the imaging system **150**.

5 Alternatively, in at least some circumstances, the operator can have the refueling device **100** in particular the boom member **130** and nozzle **135**, and the fuel receptacle **22** in the operator's visual field of view, and does not require the aforesaid spatial disposition data, and thus in such examples the refueling device **100** can omit the imaging system **150**.

 In at least some circumstances, the operator/pilot can maneuver the receiver aircraft
10 **12** such as to provide a suitable force via the fuel receptacle **22** to engage the nozzle **135** thereto, or alternatively the receiver aircraft can comprise a suitable arrangement configured for engage the nozzle **135** to the fuel receptacle **22** without the need to generate such a force, and thus in such examples the refueling device **100** can omit the force generating arrangement **190**.

15 Once refueling is completed, the operator disengages the nozzle **135** from the fuel receptacle **22** and the receiver aircraft **20** maneuvers to at least a safe position spaced from the refueling device **100**, and the refueling device **100** can be retracted back into the tanker aircraft **12**, or reused with another receiver aircraft **20**.

 It is to be noted that Operation Mode III can be carried out with each of the
20 plurality of refueling systems **50** of the tanker aircraft **12**.

 Clearly, Operation Mode III can be applied to other variations of the first example of refueling device **100**, or to the second example of refueling device **200** or alternative variations thereof in a similar manner to that described above for the first example of refueling device **100**, *mutatis mutandis*.

25 Reference is made to **Fig. 32**, showing a schematic illustration of a scene sensed by the LIDAR unit according to certain examples of the presently disclosed subject matter.

 In this example, the LIDAR unit **351** scans the sensing volume **359**, while at least one scan line intersects with the fuel receptacle **22** (or another recognizable part
30 from which the position and orientation of the fuel receptacle **22** can be estimated) of the receiver aircraft **20** and at least one scan line intersects with a certain location on the

- 139 -

boom member **312** (e.g. a boom tip marker **340** located thereon) or refueling device **100**.

It is to be noted that although in this example the scan lines are horizontal alternative scan pattern can be used as well.

5 Turning to **Fig. 33**, there is shown a representation of the depth and electromagnetic data relating to the boom refueling device and to the fuel receptacle of the receiver aircraft as acquired by the LIDAR unit according to certain examples of the presently disclosed subject matter.

The boom fueling device **310** electromagnetic data, shown as element **405** in the figure, shows that at a certain area, having a certain width, within a certain scan line of the LIDAR unit **351**, the electromagnetic value was higher than the electromagnetic value in its surrounding area, thus indicating that the boom member **312** (or, sometimes, more specifically, boom tip marker **340**) is located in this area. As indicated above, in some cases the intensity can be affected, for example, by a fuel receptacle marker **342** located at a pre-determined location on the boom member **312** and causing strong intensity reflection of the respective beam B2 when illuminated by beam B1, as compared with the reflection intensity obtained from other surfaces of the boom fuelling unit **310**, for example.

The boom fueling device **310** depth data, shown as element **410** in the figure, shows that at a certain area, having a certain width, within a certain scan line of the LIDAR unit **351**, the depth value was lower than the depth value in its surrounding area, thus also indicating that the boom member **312** is located in this area. The area in which the boom member **312** is located is closer to the LIDAR unit **351** in comparison to its surrounding area, and thus the time interval between the outgoing beams and the return beams associated with the area comprising the boom member **312** is lower than the time interval between the outgoing beams and the return beams associated with areas surrounding it.

The fuel receptacle **22** electromagnetic data, shown as element **415** in the figure, shows that at a certain area, having a certain width, within a certain scan line of the LIDAR unit **351**, the electromagnetic value was lower than the electromagnetic value in its surrounding area, thus indicating that the fuel receptacle is located in this area. The electromagnetic value is lower at that area, for example since the fuel receptacle **22** located within the corresponding area is deeper than its surrounding area.

- 140 -

As indicated above, in some cases the intensity can be affected by a fuel receptacle marker **342** comprised on the receiver aircraft **20** in a pre-determined location with respect to the fuel receptacle **22** thereof and causing strong intensity reflection of the respective beam B2 when illuminated by beam B1, as compared with the reflection
5 intensity obtained from other surfaces of the receiver aircraft **20**, for example.

The fuel receptacle **22** depth data, shown as element **420** in the figure, shows that at a certain area, having a certain width, within a certain scan line of the LIDAR unit **351**, the depth value was higher than the depth value in its surrounding area, thus also indicating that the fuel receptacle **22** is located in this area. The area in which the
10 fuel receptacle **22** is located is farther from the LIDAR unit **351** in comparison to its surrounding area, and thus the time interval between the outgoing beams and the return beams associated with the area comprising the boom member **312** is lower than the time interval between the outgoing beams and the return beams associated with areas surrounding it.

15 It is to be noted that, as any person of ordinary skill in the art can appreciate, the depths and width of the fuel receptacle depth data and/or the boom fueling device depth data can enable calculation of the spatial dispositions of the fuel receptacle **22** and/or the boom fueling device **310** (and its tip) with respect to the fuel tanker **12** and with respect to each other.

20 It is to be further noted that the boom fueling device **310** electromagnetic data shown as element **405**, the boom fueling device **310** depth data shown as element **410**, the fuel receptacle **22** electromagnetic data shown as element **415** and the fuel receptacle **22** depth data shown as element **420** can be compared with pre-stored look-up tables comprising reference depth data and reference electromagnetic data relating to
25 reference spatial dispositions with respect to the receiver aircraft, optionally based on the type of the receiver aircraft **20** (e.g. F-15, F-16, etc.), thus enabling calculation of various spatial relationships, e.g. between any two of the following: the boom fueling device **310**, the fuel receptacle **22**, the refueling device **100**, the receiver aircraft **20**, the engagement enabling position, the engagement area.

30 It is to be further noted that although the description of Fig. 33 refers to a boom fueling device **310** the same also applies to a non-aircraft-fixed in-flight refueling system (e.g. refueling device **100**, etc.).

- 141 -

In the method claims that follow, alphanumeric characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any particular order of performing the steps.

It should be noted that the word “comprising” as used throughout the appended
5 claims is to be interpreted to mean “including but not limited to”.

While there has been shown and disclosed examples in accordance with the presently disclosed subject matter, it will be appreciated that many changes may be made therein without departing from the spirit of the presently disclosed subject matter.

It is to be understood that the presently disclosed subject matter is not limited in
10 its application to the details set forth in the description contained herein or illustrated in the drawings. The presently disclosed subject matter is capable of other embodiments and of being practiced and carried out in various ways. Hence, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that
15 the conception upon which this disclosure is based may readily be utilized as a basis for designing other structures, methods, and systems for carrying out the several purposes of the present presently disclosed subject matter.

It will also be understood that the system according to the presently disclosed subject matter may be a suitably programmed computer. Likewise, the presently disclosed
20 subject matter contemplates a computer program being readable by a computer for executing the method of the presently disclosed subject matter. The presently disclosed subject matter further contemplates a machine-readable memory tangibly embodying a program of instructions executable by the machine for executing the method of the presently disclosed subject matter.

- 142 -

CLAIMS:

1. A method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:
 - automatically maneuvering a refueling device to an engagement enabling
5 position, including:
 - (i) repeatedly determining a spatial disposition of said refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling said receiver aircraft via a boom member, when the device arrives to said engagement enabling position at which said
10 boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of said receiver aircraft;
 - (ii) repeatedly calculating maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
 - 15 (iii) sending said maneuvering commands to said spatial control system;
 - whereby at said engagement enabling position, the boom member of said refueling device is capable of engaging with said fuel receptacle to enable refueling of said receiver aircraft.
2. The method according to claim 1 wherein said refueling device is non-aircraft-fixed
20 and wherein the maneuvering commands are steering commands for steering said refueling device in six degrees of freedom.
3. The method according to claim 1 wherein said refueling device is aircraft fixed and wherein the maneuvering commands are alignment commands for aligning said refueling device in three degrees of freedom.
- 25 4. The method according to claim 1, comprising providing an instruction to the refueling device, in response to its arriving at said engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory for automatically engaging with said fuel receptacle.

- 143 -

5. The method according to claim 4, wherein the boom member has a boom axis and wherein at least a final part of said predetermined trajectory is parallel to the boom axis.
6. The method according to any one of the preceding claims, further comprising:
 - 5 determining an engagement area specification condition;
repeatedly calculating maneuvering instructions for said receiver aircraft based on said spatial dispositions and an engagement area specification; and
invoking said automatically maneuvering in response to meeting said engagement area specification condition.
- 10 7. The method according to claim 6, further comprising providing said maneuvering instructions to at least one of a pilot of said receiver aircraft or a pilot of a tanker aircraft.
8. The method according to claim 7, wherein said providing said maneuvering instructions comprises activating a signaling system, optionally mounted on said
15 refueling device or said tanker aircraft.
9. The method according to any one of claims 4 to 8, wherein said refueling device is non-aircraft-fixed and wherein the method further comprising activating a force generating arrangement in the refueling device for generating force in the direction of the fuel receptacle of the receiver aircraft in response to receiving an engagement
20 command for enabling refueling.
10. The method according to any one of the preceding claims, wherein said determining a spatial disposition comprises:
 - acquiring an image of said receiver aircraft;
comparing said image with a reference image depicting a desired spatial
25 disposition of said refueling device with respect to said receiver aircraft;
determining, based on said comparing, the spatial disposition of said refueling device with respect to said receiver aircraft.

- 144 -

11. The method according to any one of the preceding claims, wherein said determining a spatial disposition comprises:
- acquiring an image of said receiver aircraft, said image comprising depth data and electromagnetic data;
- 5 comparing said depth data and said electromagnetic data with look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft;
- determining, based on said comparing, the spatial disposition of said refueling device with respect to said receiver aircraft.
- 10 12. The method according to claim 11 wherein the image is acquired by a Light Detection And Ranging (LIDAR) unit.
13. The method according to any one of the preceding claims, wherein said refueling device is non-aircraft-fixed and wherein said spatial control system characteristics are related to operation parameters of aero-dynamic control surfaces of the refueling
- 15 device.
14. The method according to claim 13, wherein said aero-dynamic control surfaces are one or more vanes.
15. The method according to any one of the claims 1 to 12, wherein said refueling device is non-aircraft-fixed and wherein said spatial control system characteristics
- 20 are related to operation parameters of reaction control thrusters associated with the refueling device and capable of maneuvering the refueling device.
16. The method according to any one of the claims 6 to 8, wherein said engagement area specification condition is a spatial disposition within a pre-determined volume with respect to the refueling device and wherein said pre-determined volume is
- 25 optionally substantially in the shape of a cube or substantially in the shape of a sphere.
17. The method according to any one of the preceding claims, wherein said calculating maneuvering commands comprises obtaining data of an initial trail position of said

- 145 -

refueling device and wherein said maneuvering commands are based also on the data of said initial trail position.

18. The method according to claim 17, wherein said refueling device is non-aircraft-fixed and wherein said data of said initial trail position includes at least one of a
5 pitch angle of said refueling device, a yaw angle of said refueling device, and a deployment length of a fuel hose.
19. The method according to any one of the claims 4 to 18, wherein said automatically maneuvering and said automatically engaging are performed autonomously by the refueling device.
- 10 20. A method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:
- (a) automatically maneuvering a refueling device to an engagement enabling position, including:
 - 15 (i) repeatedly determining a spatial disposition of said refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling said receiver aircraft via a boom member, when the device arrives to said engagement enabling position at which said boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of said
20 receiver aircraft;
 - (ii) repeatedly calculating maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
 - (iii) sending said maneuvering commands to said spatial control system;
 - 25 (b) providing an instruction to the refueling device, when it arrives at said engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory for automatically engaging with said fuel receptacle.

- 146 -

21. A method for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising :

- 5 (a) repeatedly calculating maneuvering instructions for said receiver aircraft based on spatial dispositions of said receiver aircraft and an engagement area specification until an engagement area specification condition is met;
- (b) in response to meeting said engagement area specification condition, automatically maneuvering a refueling device to an engagement enabling position, including:
 - 10 (i) repeatedly determining a spatial disposition of said refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling said receiver aircraft via a boom member, when the refueling device arrives to said engagement enabling position at which said boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of said receiver aircraft;
 - 15 (ii) repeatedly calculating maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
 - (iii) sending said maneuvering commands to said spatial control system;
- 20 (c) providing an instruction to the refueling device, in response to its arriving at said engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory for automatically engaging with said fuel receptacle.

22. A system for controlling in-flight refueling of a receiver aircraft having a fuel
25 receptacle, comprising:

a steering control module configured to automatically maneuver a refueling device to an engagement enabling position, including:

- 147 -

- 5 (i) repeatedly determine a spatial disposition of said refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling said receiver aircraft via a boom member, when the device arrives to said engagement enabling position at which said boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of said receiver aircraft;
- (ii) repeatedly calculate maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;
- 10 (iii) send said maneuvering commands to said spatial control system for automatically maneuvering said refueling device to said engagement enabling position;

whereby at said engagement enabling position, the boom member of said refueling device is capable of engaging with said fuel receptacle to enable refueling of said receiver aircraft.

15

23. The system according to claim 22 wherein said refueling device is non-aircraft-fixed and wherein the maneuvering commands are steering commands for steering said refueling device in six degrees of freedom.

24. The system according to claim 22 wherein said refueling device is aircraft fixed and wherein the maneuvering commands are alignment commands for aligning said refueling device in three degrees of freedom.

20

25. The system according to claim 22, further comprising an engagement/disengagement module configured to provide an instruction to the refueling device, in response to its arriving at said engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory to automatically engage with said fuel receptacle.

25

26. The system according to claim 25, wherein the boom member has a boom axis and wherein at least a final part of said predetermined trajectory is parallel to the boom axis.

- 148 -

27. The system according to any one of claims 25 to 26, further comprising a maneuvering instructions module configured to determine an engagement area specification condition, to repeatedly calculate maneuvering instructions for said receiver aircraft based on said spatial dispositions and an engagement area specification, and to invoke said steering control module to automatically maneuver said refueling device to said engagement enabling position in response to meeting said engagement area specification condition.
28. The system according to claim 27, wherein said maneuvering instructions module is further configured to provide said maneuvering instructions to at least one of a pilot of said receiver aircraft or a pilot of a tanker aircraft.
29. The system according to claim 28, wherein said maneuvering instructions module is configured to activate a signaling system in order to provide said maneuvering instructions, said signaling system is optionally mounted on said refueling device or said tanker aircraft.
30. The system according to any one of claims 25 to 29, wherein said refueling device is non-aircraft-fixed and wherein said engagement/disengagement module is further configured to activate a force generating arrangement in the refueling device for generating force in the direction of the fuel receptacle of the receiver aircraft in response to receiving an engagement command for enabling refueling.
31. The system according to any one of claims 22 to 30, wherein said steering control module is configured to perform the following steps in order to determine a spatial disposition:
- acquire an image of said receiver aircraft;
 - compare said image with a reference image depicting a desired spatial disposition of said refueling device with respect to said receiver aircraft;
 - determine, based on said comparing, the spatial disposition of said refueling device with respect to said receiver aircraft.

- 149 -

32. The system according to any one of claims 22 to 30, wherein said steering control module is configured to perform the following steps in order to determine a spatial disposition:

5 acquiring an image of said receiver aircraft, said image comprising depth data and electromagnetic data;

 comparing said depth data and said electromagnetic data with look-up tables comprising reference depth data and reference electromagnetic data relating to reference spatial dispositions with respect to the receiver aircraft;

10 determining, based on said comparing, the spatial disposition of said refueling device with respect to said receiver aircraft.

33. The system according to claim 32 wherein the image is acquired by a Light Detection And Ranging (LIDAR) unit.

34. The system according to any one of claims 22 to 33, wherein said refueling device is non-aircraft-fixed and wherein said spatial control system characteristics are related to operation parameters of aero-dynamic control surfaces of the refueling device.

35. The system according to claim 34, wherein said aero-dynamic control surfaces are one or more vanes.

36. The system according to any one of the claims 22 to 33, wherein said refueling device is non-aircraft-fixed and wherein said spatial control system characteristics are related to operation parameters of reaction control thrusters associated with the refueling device and capable of maneuvering the refueling device.

37. The system according to any one of the claims 27 to 29, wherein said engagement area specification condition is a spatial disposition within a pre-determined volume with respect to the refueling device and wherein said pre-determined volume is optionally substantially in the shape of a cube or substantially in the shape of a sphere.

38. The system according to any one of claims 22 to 37, wherein said steering control module is further configured to obtain data of an initial trail position of said

- 150 -

refueling device and wherein said calculate maneuvering commands is based also on the obtained data of said initial trail position.

39. The system according to claim 38, wherein said refueling device is non-aircraft-fixed and wherein said data of said initial trail position includes at least one of a
5 pitch angle of said refueling device, a yaw angle of said refueling device, and a deployment length of a fuel hose.
40. The system according to any one of claims 26 to 30, wherein at least said steering control module and said engagement/disengagement module are fitted within said refueling device for enabling autonomously controlling in-flight refueling of said
10 receiver aircraft by said refueling device.
41. The system according to any one of claims 25 to 30, wherein at least said steering control module and said engagement/disengagement module are fitted within said receiver aircraft.
42. The system according to any one of claims 28 to 29, wherein at least said steering
15 control module and said engagement/disengagement module are fitted within said tanker aircraft.
43. A system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:
- 20 a steering control module configured to automatically maneuver a refueling device to an engagement enabling position, including:
- (i) repeatedly determine a spatial disposition of said refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling said receiver aircraft via a boom member, when the device arrives to said engagement enabling position at which said boom member is in a predetermined spaced and spatial relationship with
25 respect to the fuel receptacle of said receiver aircraft;
 - (ii) repeatedly calculate maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial control system of the refueling device;

- 151 -

- (iii) send said maneuvering commands to said spatial control system for automatically maneuvering said refueling device to said engagement enabling position;

5 said system further comprises an engagement/disengagement module configured to provide an instruction to the refueling device, when it arrives at said engagement enabling position, for causing the refueling device to move the boom member along a predetermined trajectory to automatically engage with said fuel receptacle.

44. A system for controlling in-flight refueling of a receiver aircraft having a fuel receptacle, comprising:

10 a maneuvering instructions module configured to repeatedly calculate maneuvering instructions for said receiver aircraft based on spatial dispositions of said receiver aircraft and an engagement area specification until an engagement area specification condition is met, and in response to meeting said engagement area specification condition, activate a steering control module;

15 said steering control module is configured to automatically maneuver a refueling device to an engagement enabling position, including:

- (i) repeatedly determine a spatial disposition of said refueling device with respect to the receiver aircraft, the refueling device being capable of engaging and refueling said receiver aircraft via a boom member, when
20 the device arrives to said engagement enabling position at which said boom member is in a predetermined spaced and spatial relationship with respect to the fuel receptacle of said receiver aircraft;
- (ii) repeatedly calculate maneuvering commands based at least on the repeatedly determined spatial dispositions and characteristics of a spatial
25 control system of the refueling device;
- (iii) send said maneuvering commands to said spatial control system for automatically maneuvering said refueling device to said engagement enabling position;

30 said system further comprises an engagement/disengagement module configured to provide an instruction to the refueling device, in response to its arriving at said

- 152 -

engagement enabling position, causing the refueling device to move the boom member in a predetermined trajectory to automatically engage with said fuel receptacle.

45. A non-aircraft-fixed refueling device for use in in-flight refueling operation between
5 a tanker aircraft and a receiver aircraft, comprising:

a selectively steerable body configured for being towed by said tanker aircraft via a fuel hose at least during in-flight refueling, and comprising a boom member having a boom axis and configured to enable fuel to be transferred from said fuel hose to said receiver aircraft along said boom axis during said in-flight refueling
10 operation;

a controller configured for selectively maneuvering the body to an engagement enabling position spaced with respect to the receiver aircraft and for aligning said boom axis in an engagement enabling orientation at said spaced position, and for subsequently moving the boom member along said boom axis towards the receiver
15 aircraft for enabling fuel communication therebetween.

46. A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform a method of claim 1.

47. A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform a method of claim 20.

20 48. A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform a method of claim 21.