

OPTICAL SYSTEM FOR MONITORING PLASMA REACTIONS AND REACTORS

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to plasma generators, and more particularly to devices
5 for monitoring plasma in plasma reactors.

2. Discussion of the Related Art

[0002] In recent years, microwave technology has been applied to generate various types of plasma. Typically, a microwave discharge, which is used as a plasma source, is achieved by coupling microwave energy into a discharge chamber containing gas to be processed. In the
10 conventional microwave-based plasma systems that are used for hydrocarbon gas reformation, variations in the feed stock composition can cause plasma instability, undesirable depositions on the reactor wall and other surfaces, and other phenomena that degrade system performance or damage components in the systems. To prevent damage to the plasma systems under fault conditions and to maximize throughput and efficiency of the systems, the plasma health and
15 operational conditions need to be continuously monitored and assessed during the operation of the systems.

[0003] As such, there is a need for a device that can continuously monitor and assess the plasma health and operational conditions of the plasma systems in a reliable manner.

SUMMARY OF THE INVENTION

[0004] According to one aspect of the present invention, a plasma generating system includes:
20 a waveguide; a plasma cavity coupled to the waveguide and configured to generate a plasma therewithin by use of microwave energy; a hollow cylinder protruding from the wall of the waveguide and having a bottom cap that has an aperture; a detection unit for receiving the light emitted by the plasma through the aperture and configured to measure intensities of the light in
25 an ultraviolet (UV) range and an infrared (IR) range; and a controller for controlling the detection unit.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Figure 1 (“FIG. 1”) shows a schematic diagram of a plasma generating system according to embodiments of the present disclosure.

5 [0006] FIG. 2 shows a cross sectional view of a plasma chamber in FIG. 1, taken along the line 2-2, according to embodiments of the present disclosure.

[0007] FIG. 3 shows a perspective view of a forward flow inlet according to embodiments of the present disclosure.

[0008] FIG. 4 shows a cross sectional view of the forward flow inlet in FIG. 3, taken along the line 4-4, according to embodiments of the present disclosure.

10 [0009] FIG. 5 shows a perspective view of an adaptor according to embodiments of the present disclosure.

[0010] FIG. 6 shows a cross sectional view of the adaptor in FIG. 5, taken along the line 6-6, according to embodiments of the present disclosure.

15 [0011] FIG. 7 shows a perspective view of an inner vortex flow according to embodiments of the present disclosure.

[0012] FIG. 8 shows a perspective view of an outer vortex flow according to embodiments of the present disclosure.

[0013] FIG. 9 shows a cross sectional view of the plasma chamber in FIG. 2, taken along the line 9-9, according to embodiments of the present disclosure.

20 [0014] FIG. 10 shows a cross sectional view of a detection unit according to embodiments of the present disclosure.

[0015] FIG. 11 shows a cross sectional view of a plasma chamber according to embodiments of the present disclosure.

25 [0016] FIG. 12 shows a perspective view of an adaptor according to embodiments of the present disclosure.

[0017] FIG. 13 shows a perspective view of a forward flow inlet according to embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0018] In the following description, for purposes of explanation, specific details are set forth in order to provide an understanding of the disclosure. It will be apparent, however, to one skilled in the art that the disclosure can be practiced without these details. Furthermore, one skilled in the art will recognize that embodiments of the present disclosure, described below, may be implemented in a variety of ways.

[0019] Components, or modules, shown in diagrams are illustrative of exemplary embodiments of the disclosure and are meant to avoid obscuring the disclosure. It shall also be understood that throughout this discussion that components may be described as separate functional units, which may comprise sub-units, but those skilled in the art will recognize that various components, or portions thereof, may be divided into separate components or may be integrated together, including integrated within a single system or component. It should be noted that functions or operations discussed herein may be implemented as components.

[0020] Reference in the specification to “one embodiment,” “preferred embodiment,” “an embodiment,” or “embodiments” means that a particular feature, structure, characteristic, or function described in connection with the embodiment is included in at least one embodiment of the disclosure and may be in more than one embodiment. Also, the appearances of the above-noted phrases in various places in the specification are not necessarily all referring to the same embodiment or embodiments.

[0021] The use of certain terms in various places in the specification is for illustration and should not be construed as limiting. The terms “include,” “including,” “comprise,” and “comprising” shall be understood to be open terms and any lists the follow are examples and not meant to be limited to the listed items.

[0022] Figure 1 (“FIG. 1”) shows a schematic diagram of a plasma generating system **10** according to embodiments of the present disclosure. As depicted, the plasma generating system **10** includes: a microwave cavity/waveguide **20** having a shape of a hollow tube; a plasma

chamber **22** connected to the waveguide **20**; and a microwave supply unit **12** connected to the waveguide **20** and operative to provide microwave energy to the plasma chamber **22** via a microwave waveguide **20**. In embodiments, the plasma chamber **22** receives the microwave energy and processes gas by use of the received microwave energy. In embodiments, a gas tank
5 **26** provides gas to the plasma chamber **22** via a gas line **24**, and a gas tank **30** provides gas to the plasma chamber **22** via a gas line **28**.

[0023] The microwave supply unit **12** provides microwave energy to the plasma chamber **22** and includes: a microwave generator **14** for generating microwaves; a power supply **16** for supplying power to the microwave generator **14**; and a tuner **18** for reducing the microwave
10 energy reflected from the plasma chamber **22** and travelling toward the microwave generator **14**. In embodiments, the microwave supply unit **12** may include other components, such as an isolator having a dummy load for dissipating reflected microwave energy that propagates toward the microwave generator **14** and a circulator for directing the reflected microwave energy to the dummy load and a sliding short circuit disposed at the end of the waveguide **20**.

15 [0024] FIG. 2 shows a cross sectional view of a plasma chamber **22** in FIG. 1, taken along the line **2-2**, according to embodiments of the present disclosure. As depicted, the plasma chamber **22** includes: an inner wall(s) **40**; a plasma stabilizer **38**; a forward flow inlet (which is also referred to as “vortex flow generator”) **42** connected to the gas line **24** and configured to introduce the forward flow into the plasma chamber; and a reverse flow inlet (which is also
20 referred to as “adaptor”) **44** connected to the gas line **28** and configured to introduce the reverse flow into the plasma chamber. Here, the term plasma cavity refers to the enclosed space that is surrounded by the inner wall **40**, waveguide **20**, forward flow inlet **42** and reverse flow inlet (adaptor) **44**, where the reverse flow gas and forward flows are processed/reformed by plasma plume (or shortly, plasma) **46** in the plasma cavity using the microwave energy transmitted via
25 the waveguide **20**.

[0025] In embodiments, the inner wall **40** is formed of a material that is transparent to the microwave energy, such as quartz or ceramic. In embodiments, the inner wall **40** is formed of any other suitable dielectric material that is desirable for uniform flow, thermal resistance, chemical resistance, and electromagnetic transparency. Also, as discussed below, in

embodiments, the inner wall **40** is formed of material that is transparent to UV and IR light. In embodiments, the inner wall **40** has preferably, but not limited to, a shape of hollow circular cylinder.

[0026] FIG. 3 shows a perspective view of the forward flow inlet **42** according to
5 embodiments of the present disclosure. FIG. 4 shows a cross sectional view of the forward flow inlet **42**, taken along the line **4-4**, according to embodiments of the present disclosure. As depicted, the forward flow inlet **42** has a hole/adaptor **47** for coupling to the gas line **24** and one or more gas passageways **48** that are formed in the wall thereof. In embodiments, the exits of the gas passageways **48** are located inside the plasma stabilizer **38** so that the plasma stabilizer **38**
10 forms an inner vortex flow **43** using the flow exiting the gas passageways **48**. In embodiments, the inner diameter of the plasma stabilizer **38** may be varied to adjust the outer diameter of the inner vortex flow **43**. In embodiments, as discussed above, the plasma stabilizer **38** may have a shape of hollow circular cylinder and disposed concentrically to the forward flow inlet **42**.

[0027] In embodiments, each gas passageway **48** is arranged to impart spiral motion to the
15 forward flow as the forward flow enters the plasma cavity via the gas passageway **48**. In embodiments, each gas passageway **48** may be curved to enhance the vorticity of the forward flow. In embodiments, the forward flow inlet **42** is formed of any suitable material, such as metal or dielectric material, so that the inlet is electrically isolated from the waveguide **20** and withstand the heat energy from the plasma **46**.

[0028] In embodiments, the plasma stabilizer **38** is formed of material that is transparent to
20 the microwave energy, and preferably formed of the same material as the inner wall **40**. In embodiments, the plasma stabilizer **38** is attached to the waveguide **20**, protruding into the plasma cavity, where the axial direction of the plasma stabilizer **38** is parallel to the y-axis. In embodiments, as discussed above, the inner wall **40** may have a shape of a hollow circular
25 cylinder and the plasma stabilizer **38** may be installed concentrically to the inner wall **40**. In embodiments, the forward flow inside the plasma stabilizer **38** forms the inner vortex flow **43** and proceeds toward the other end of the waveguide **20**, more specifically toward the gas outlet **32**. FIG. 7 shows a perspective view of the inner vortex flow **43** according to embodiments of the present disclosure. As depicted, the forward flow (or equivalently, inner vortex flow) travels

the length of the inner wall **40** in a helical motion until the inner vortex flow exits the gas outlet **32**.

[0029] In embodiments, upon ignition of the plasma **46**, the plasma **46** is sustained by the microwave energy transmitted by the microwave generator **14**. In embodiments, the plasma **46** is located within the inner vortex flow **43** so that the gas particles of the inner vortex flow **43** pass through the plasma **46**. In embodiments, the plasma stabilizer **38** determines the outer diameter of the inner vortex flow **43**, preventing the forward flow from bypassing the plasma **46** before exiting the plasma cavity through the gas outlet **32**. In embodiments, the plasma stabilizer **38** aids in keeping the plasma **46** stable by separating the inner vortex flow **43** from the outer vortex flow **45**.

[0030] FIG. 5 shows a perspective view of the reverse flow inlet (adaptor) **44** according to embodiments of the present disclosure. FIG. 6 shows a cross sectional view of the reverse flow inlet (adaptor) **44**, taken along the line **6-6**, according to embodiments of the present disclosure. As depicted, the reverse flow inlet (adaptor) **44** has a hole/adaptor **52** for coupling to the gas line **28**, a hole to form the gas outlet **32**, and one or more gas passageways **51** that are formed in the wall thereof. In embodiments, each gas passageway **51** is arranged to impart spiral motion to the reverse flow as the reverse flow enters the plasma cavity via the gas passageway **51**. In embodiments, each gas passageway **51** may be curved to enhance the vorticity of the reverse flow. In embodiments, the reverse flow inlet (adaptor) **44** is formed of preferably, but not limited to Ni alloy, such as Inconel or Hastelloy.

[0031] In embodiments, the reverse flow exiting the reverse flow inlet (adaptor) **44** travels toward to the inner wall **40** and then proceeds upwardly (y-axis direction) toward the other end of the waveguide **20** along the inner wall **40** in a helical motion. Subsequently, the reverse flow reverses the flow direction to proceed downwardly and form an outer vortex flow **45**. In embodiments, the rotational axis of the outer vortex flow **45** is substantially parallel to the y-axis. FIG. 8 shows a perspective view of the outer vortex flow **45** according to embodiments of the present disclosure. As depicted, the outer vortex flow **45** has a hollow cylinder shape and has two flow regions: inner downward flow region **45-1** and an outer upward flow region **45-2**. In embodiments, the inner vortex flow **43** is disposed in the middle hollow portion of the outer

vortex flow **45** and surrounded by inner downward flow region **45-1**. It is noted that the gas from the forward flow inlet **42** is mixed with the flow from the reverse flow inlet (adaptor) **44** to form the inner vortex flow **43**.

5 [0032] In embodiments, the outer vortex flow **45** surrounds the inner vortex flow **43**, to thereby shield the inner wall **40** from the plasma **46**. In embodiments, the reverse flow exiting the reverse flow inlet (adaptor) **44** may have the ambient temperature and take heat energy from the inner wall **40** as the outer vortex flow **45** travels upwardly along the inner wall **40** in the helical motion.

10 [0033] In embodiments, as discussed above, the inner diameter of the plasma stabilizer **38** determines the radial dimension of the inner vortex flow **43**. As such, in embodiments, the inner diameter of the plasma stabilizer **38** may be adjusted so that the outer vortex flow **45** surrounds the inner vortex flow **43** and maintain the flow regime of the inner vortex flow **43** in a stable manner to thereby stabilize the plasma and yield improved throughput and efficiency

15 [0034] In embodiments, the plasma **46** is used to reform the inlet gas to the desired product gas, where the inlet gas is introduced into the plasma cavity by the forward flow inlet **42** and reverse flow inlet (adaptor) **44**. In embodiments, the gas composition of the inner vortex flow exiting the forward flow inlet **42** includes CO₂, CH₄ and O₂, and the gas exiting the gas outlet **32** includes CO and H₂ as well as a non-reacted portion of forward flow gas. In embodiments, the preferred distribution for the forward flow is 5%-95% by mass of the total flow into the
20 plasma chamber **22**. In embodiments, the reverse flow may have the same gas composition of the forward flow. In alternative embodiments, the forward flow may have different gas composition from the reverse flow. Also, the gas composition of the forward flow (and/or reverse flow) may be changed during operation. For instance, the forward flow may include a slug of argon to aid ignition of the plasma **46**. In embodiments, the gas compositions and flow
25 rates of the forward and reverse flows may be adjusted to enhance the plasma stability and efficiency of the chemical reaction in the plasma chamber **22**.

[0035] It is noted that the plasma chamber **22** may have different components and arrangement of the components. For instance, the plasma chamber **22** may not include the forward flow inlet **42**, i.e., the waveguide **20** does not have any hole for receiving the forward

flow inlet. In another example, the plasma stabilizer **38** may be mounted on the reverse flow inlet (adaptor) **44**. The description of various embodiments of the plasma chamber **22** can be found in a copending U.S. Patent Application Ser. No. 16/752,689, entitled "Plasma reactor for processing gas," filed on January 26, 2020, which is hereby incorporated by reference in its entirety.

[0036] As discussed above, the gas compositions and flow rates of the forward and reverse flows may affect the plasma stability and efficiency of the chemical reaction in the plasma chamber **22**. In embodiments, the plasma **46** emits a broad spectrum of light that can be an indicator of proper operation of the system **10** and therefore can be used to monitor the plasma health/stability and plasma-based process, such as gas dissociation, among others, as an example. Also, in embodiments, depending on the input gas composition, operating pressure, and power input (which refers to the energy absorbed by the gases), the light emitted by the plasma **46** has a unique characteristic "signature" within the electromagnetic spectrum as well as in the intensity of light output and stability (flickering or movement of the plasma plume). For instance, when the input gas includes CO₂, CH₄ and O₂, properly operating plasma **46** may have a very strong emission in the range of 200nm - 500nm. Also, in cases where there is carbon deposition on the inner wall **40**, emission in the range of 635nm - 700nm is present in the spectrum. In another example, at low power inputs, the emission intensity in the range of 200nm - 500nm become less bright. In yet another example, when the reactor gas pressure in the plasma chamber **22** is low or inconsistent, the plasma **46** may flicker or fluctuate (like a candle flame disturbed by wind) from the center position while a stable plasma plume is very narrow beam and located at the center of the inner vortex **43**.

[0037] FIG. 9 shows a cross sectional view of the plasma chamber **22** in FIG. 2, taken along the line **9-9**, according to embodiments of the present disclosure. In FIG. 9, the inset diagram **59** shows the enlarged view of the optical arrangement near a detection unit **61**. As depicted, the optical measurement system includes: a hollow cylinder **13** protruding from a side wall of the waveguide **20** with a bottom cap; an aperture/opening **66** formed in the bottom cap; and the detection unit **61** for detecting the light that passed through the aperture **66**. In embodiments, the dimension of the aperture is small enough to meet safety requirements with respect to electromagnetic radiation leakage therethrough but large enough to allow the detection unit **61** to

receive enough light for monitoring the plasma stability and operational conditions of the system
10. For instance, the aperture is a circular hole having a diameter of 0.1 – 4 mm.

[0038] In embodiments, the light emission from the plasma 46 travels through the inner wall
40 to reach the detection unit 61. As such, the inner wall 40 is formed of material that is
5 transparent to the UV and IR light. In alternative embodiments, the aperture 66 is replaced by a
window that is formed of material transparent to the UV and IR light.

[0039] In embodiments, the light emission from the plasma 46 and the light reflected from
various components of the plasma chamber travel through the hollow cylinder 13 and exit the
cylinder through the aperture 66. In embodiments, the detection unit 61 continuously monitors
10 the emission during the startup (ignition) phase as well as the operation (reforming) phase. In
embodiments, the detection unit 61 detects the emissions in the ultraviolet (UV) range, such as
UVA, UVB and UVC, as well as in the near and mid infrared (IR) ranges. For instance, the UV
range refers to 10 nm – 400 nm, and the near and mid IR range refers to 750 nm – 950 nm. In
embodiments, the average intensity of two or more UV emissions (UVA, UVB and UVC)
15 measured during the operation phase is indicative of the quality of the input gases (i.e., the gases
introduced by the adaptor 44 and the forward flow inlet 42) and resulting plasma stability. In
embodiments, the maximum and minimum intensities of one or more UV emissions (UVA, UVB
and UVC) measured during the operation phase is also indicative of the quality of the input gases
and resulting plasma stability.

[0040] In embodiments, the light emission from the plasma 46 travels through the inner wall
20 40, and thus, the intensity of near and/or mid IR emission(s) during the startup phase prior to
formation of the plasma 46 is symptomatic of depositions (i.e., carbon) on the inner wall 40. As
such, in embodiments, the combination of both UV and IR emissions of varying amplitudes
during the operation phase are characteristics of input gas issues and/or damage to components
25 of the plasma chamber 22.

[0041] In embodiments, the detection unit 61 includes: a sensor 64 that converts light into an
electrical signal; a switchable bandpass filter 65 disposed in front of the sensor 64 and having
one or more bandpass filters; an electrical circuit 62 for conditioning the electrical signal
generated by the sensor and sending the conditioned signal to a controller 69; an electrical wire

70 for communicating electrical signals between the electrical circuit 62 and controller 69; and optionally, a lens 68 (or any other suitable optical element) for collecting light onto the sensor 64. In embodiments, an electrical circuit 62 is preferably (but not limited to) formed on a circuit board. In embodiments, the controller 69 is a computing device that controls the detection unit
5 61 and processes the electrical signals from the detection unit 61.

[0042] It is noted that the sensor 64 is a wideband detector and each of the one or more bandpass filters of the switchable bandpass filter 65 passes light in a predetermined wavelength range. For instance, the switchable bandpass filter 65 includes four bandpass filters that respectively pass through UVA, UVB, UVC and near/mid IR light.

10 [0043] In alternative embodiments, the sensor 64 includes multiple detectors that each detect light in a predetermined wavelength range, and the detection unit 61 does not include any filter. For instance, the sensor 64 includes a first detector for measuring the intensity of UVA light; a second detector for measuring the intensity of UVB light; a third detector for measuring the intensity of UVC light; and a fourth detector for measuring the intensity of IR light.

15 [0044] It is noted that the sensor 64 and electrical circuit 62 may be arranged in different manners. For instance, the sensor 64 is physically separated from the electrical circuit 62 and communicates electrical signals to the electrical circuit 62 via an electrical wire or a wireless channel. In another example, the electrical circuit 62 communicates electrical signals to the controller 69 via a wireless channel

20 [0045] In embodiments the controller 69 performs processing the signals from the detection unit 61, such as averaging the intensities of UV light and/or determining the maximum and minimum intensities of light for each wavelength range to thereby determine the plasma health/stability and operations conditions of the system 10.

[0046] FIG. 10 shows a cross sectional view of a detection unit 71 according to embodiments
25 of the present disclosure. As depicted, the detection unit 71 includes: sensors 74a and 74b that each convert light into an electrical signal; optical filters 75a and 75b mounted on the sensors 74a and 74b, respectively, and configured to selectively pass light of predetermined wavelength ranges; an electrical circuit 72 for processing the electrical signal; and optionally a lens 78 for collecting light onto the optical filters 75a and 75b. In embodiments, the electrical circuit 72

communicates electrical signals to a controller **82** via wireless communication channel **80**. In alternative embodiments, the detection unit **71** may include an electrical wire that is similar to the electrical wire **70**.

[0047] In embodiments, the sensors **74a** and **74b** are broadband detectors, and each of the filters **75a** and **75b** is a bandpass filter that passes through light of a predetermined wavelength range. For instance, the filter **75a** passes through UV light while the filter **75b** is a bandpass filter that passes through IR light. It is noted that the detection unit **71** includes any other suitable number of sensors/filters so that each sensor detects the light in a specific wavelength range. For instance, the detection unit **71** may include at least three broadband detectors and bandpass filters for detecting UVA, UVB, and UVC emissions, respectively.

[0048] In embodiments, as the plasma **46** is turned off, the UV emission is extinguished, and the intensity of IR emission detected by the detection unit **61** (or **71**) is diminished. As such, the present of UV indicates the existence of plasma **46** and time-resolved character of the UV emission detected by the detection unit **61** (or **71**) is descriptive of plasma health/stability. In embodiments, the amplitude of IR emission detected by the detection unit **61** (or **71**) is used to detect the process-gas composition-related specifications and undesirable depositions on the components of the plasma chamber **22**, such as inner wall **40**. For instance, the detected intensity of IR emission is used to determine abnormal conditions, such as, but not limited to, carbon depositions. In embodiments, the detection unit **61** (or **71**) generates and sends an electrical signal at each predetermined interval so that the plasma status/health and operational condition of the system **10** are continuously monitored.

[0049] In embodiments, the detection unit **61** (or **71**) is disposed outside the aperture **66** to avoid intrusion into the plasma chamber **22**, which significantly reduces the workload of installation and maintenance of the detection unit as well as the possibility of electromagnetic radiation leakage through the plasma chamber **22**. In embodiments, the measurement of the UV and IR emissions may be performed without using the protruding cylinder **13**. FIG. 11 shows a cross sectional view of a plasma chamber according to embodiments of the present disclosure. As depicted, the optical measurement system includes: at least one optical fiber **170** installed in the wall of a waveguide **120**; and a detection unit **161** coupled to the optical fiber **170**. In

embodiments, one end of the optical fiber **170** is configured to receive the light emitted by the plasma **146** as well as the light reflected from various components of the plasma chamber, and the collected light travels through the optical fiber to the detection unit **161**. In embodiments, the optical fiber **170** is formed of material that can transmit the UV and IR light therethrough.

5 **[0050]** The detection unit **161** is similar to the detection unit **61** (or **71**) and communicatively coupled to a controller **169** via a wire or a wireless channel. In alternative embodiments, the detection unit **161** and controller **169** are formed in one integral body.

10 **[0051]** It should be apparent to those of ordinary skill in the art that one or more optical fibers may be installed in other suitable locations within the plasma chamber. FIG. 12 shows a perspective view of an adaptor **244** according to embodiments of the present disclosure. As depicted, the adaptor **244** includes an optical fiber **270**, where one end of the optical fiber **270** is configured to receive the UV and IR light inside the plasma chamber and the other end of the optical fiber **270** is coupled to a detection unit that is similar to the detection unit **161**. Since the optical fiber **270** is installed in the adaptor **244**, the light emitted by the plasma **146** does not pass
15 through the inner wall **140** before the light reaches the optical fiber, i.e., the inner wall **140** is outside the line of sight of the optical fiber, and as such, it is not necessary that the inner wall **140** is formed of material that is transparent to the UV light.

20 **[0052]** FIG. 13 shows a perspective view of a forward flow inlet **342** according to embodiments of the present disclosure. As depicted, the forward flow inlet **342** includes an optical fiber **370**, where one end of the optical fiber **370** is configured to receive the UV and IR light inside the plasma chamber and the other end of the optical fiber **370** is coupled to a detection unit that is similar to the detection unit **161**. Since the optical fiber **370** is installed in the forward flow inlet **342**, the light emitted by the plasma **146** does not pass through the inner wall **140** before the light reaches the optical fiber, i.e., the inner wall **140** is outside the line of
25 sight of the optical fiber, and as such, it is not necessary that the inner wall **140** is formed of material that is transparent to the UV light.

[0053] It will be appreciated to those skilled in the art that the preceding examples and embodiments are exemplary and not limiting to the scope of the present disclosure. It is intended that all permutations, enhancements, equivalents, combinations, and improvements thereto that

are apparent to those skilled in the art upon a reading of the specification and a study of the drawings are included within the true spirit and scope of the present disclosure. It shall also be noted that elements of any claims may be arranged differently including having multiple dependencies, configurations, and combinations.

What is claimed is:

1. A plasma generating system, comprising:
a plasma cavity for generating a plasma therewithin by use of microwave energy;
5 a detection unit for measuring intensities of light emitted by the plasma in an ultraviolet
(UV) range and an infrared (IR) range; and
a controller for controlling the detection unit.
2. A plasma generating system as recited in claim 1, further comprising:
10 a waveguide coupled to the plasma cavity; and
a hollow cylinder protruding from a wall of the waveguide and having a bottom cap that
includes an aperture,
wherein the detection unit is arranged to receive the light through the aperture.
- 15 3. A plasma generating system as recited in claim 2, wherein the aperture is dimensioned
to prevent leakage of the microwave energy therethrough.
4. A plasma generating system as recited in claim 1, wherein the detection unit includes:
a sensor for converting light into an electrical signal; and
20 a board having an electrical circuit, the sensor being mounted on the board,
wherein the electrical circuit conditions the electrical signal and sends the electrical
signal to the controller.
5. A plasma generating system as recited in claim 4, further comprising:
25 a switchable bandpass filter disposed in front of the sensor and having one or more
bandpass filters that each pass light in a wavelength range.
6. A plasma generating system as recited in claim 1, further comprising:
a lens for collecting the light onto the detection unit.

30

7. A plasma generating system as recited in claim 1, wherein the detection unit includes:
a first sensor for measuring intensity of the light in the UV range; and
a second sensor for measuring intensity of the light in the IR range.

5 8. A plasma generating system as recited in claim 7, further comprising:
a first bandpass filter disposed in front of the first sensor and configured to pass the light
in the UV range; and
a second bandpass filter disposed in front of the second sensor and configured to pass the
light in the IR range.

10 9. A plasma generating system as recited in claim 1, further comprising:
a waveguide coupled to the plasma cavity; and
an optical fiber installed in the waveguide and having one end for receiving the light and
an other end coupled to the detection unit.

15 10. A plasma generating system as recited in claim 1, further comprising:
a waveguide for transmitting the microwave energy therethrough;
an inner wall disposed within the waveguide to define the plasma cavity;
an adaptor mounted on the waveguide and configured to introduce a gas into the plasma
20 cavity and generate a vortex flow within the plasma cavity using the gas, the adaptor having a
through hole through which a gas processed by the plasma exits the plasma cavity; and
an optical fiber installed in the adaptor and having one end for receiving the light and an
other end coupled to the detection unit

25 11. A plasma generating system as recited in claim 1, further comprising:
a waveguide for transmitting the microwave energy therethrough;
a forward flow inlet mounted on the waveguide and configured to introduce a gas into the
plasma cavity and generate a vortex flow within the plasma cavity using the gas; and
an optical fiber installed in the forward flow inlet and having one end for receiving the
30 light and an other end coupled to the detection unit.