

(43) International Publication Date
31 March 2011 (31.03.2011)(10) International Publication Number
WO 2011/038105 A2

(51) International Patent Classification:

F25B 1/00 (2006.01) *F28D 7/10* (2006.01)
F25B 39/04 (2006.01) *F28F 13/00* (2006.01)

(21) International Application Number:

PCT/US2010/049976

(22) International Filing Date:

23 September 2010 (23.09.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/246,239 28 September 2009 (28.09.2009) US

(71) Applicant (for all designated States except US): **CARRIER CORPORATION** [US/US]; One Carrier Place, Farmington, CT 06034 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HUFF, Hans-Joachim** [DE/US]; 7721 Farley Lane, Manlius, New York 13104 (US). **ASPROVSKI, Zvonko** [US/US]; 7730 Treeline Drive, Liverpool, New York 13090 (US).

(74) Agent: **MANNA, Barry F.**; 250 South Clinton Street, Suite 300, Syracuse, New York 13202 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: LIQUID-COOLED HEAT EXCHANGER IN A VAPOR COMPRESSION REFRIGERATION SYSTEM




FIG. 1

(57) Abstract: A refrigerant vapor compression system includes a compressor having a suction port and a discharge port, an air-cooled heat exchanger operatively coupled to the discharge port, a liquid-cooled heat exchanger operatively coupled to the air-cooled heat exchanger, a coolant pump operatively coupled to a liquid coolant inlet conduit of the liquid-cooled heat exchanger, an evaporator heat exchanger unit operatively coupled to the liquid-cooled heat exchanger and the suction port, a coolant pump operatively coupled to the liquid coolant inlet conduit for pumping a liquid coolant, and a controller operatively associated with the liquid coolant inlet conduit for controlling the flow of liquid coolant into the liquid-cooled heat exchanger. In one embodiment, the liquid-cooled heat exchanger comprises a low-profile enclosure defining an interior volume. The enclosure has a liquid coolant inlet port and a liquid coolant discharge port fluidly coupled to the interior volume, and a continuous refrigerant tube sealingly disposed within the enclosure. The refrigerant tube is fluidly isolated from and in heat exchange relationship with the interior volume in which the liquid coolant flows.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*