[0034]

In addition, the grip members 50 and 60 can be formed by using a soft material such as natural cork, urethane, EVA, thermoplastic elastomer, and rubber that can improve the touch and the gripping performance when the grip members 50 and 60 are gripped, and appearance, and that can reduce weight, or by applying these materials.

[0035]

While the embodiment of the present invention has been described above, the present invention is not limited to the above-described embodiment and can be variously modified.

[0036]

In the present invention, as for the opening hole 2A formed in the reel seat main body 1A, the position of the bottom 2a is not limited as long as the rod 100 to be inserted into and fixed to the opening hole 2A is on the lower side of the reel leg placing portion 7 (placing surface 7a), and the position of the rear end edge 100a of the rod 100 is located further on the rear side than the front end edge 201a' of the reel leg 201 to be attached. Therefore, the opening hole 2A may be formed deep to the vicinity of the rear end 201b of the reel leg 201. Also, the inclination angle of the inclined surface 20 formed on the seat main body 1A is freely selected, and the surface shape thereof can appropriately be changed to a curved shape, a flat surface, a composite surface of these, or the like. In addition, the surface shape of the recessed portion formed on the inclined surface can also be appropriately changed to a partially recessed shape, a recessed shape in a composite surface in which flat and curved hollows are combined, a partially bulged shape, or the like. Further, the configuration of the