

RUNNING TOOL FOR DEEP WATER

1. Field of the Invention:

This invention relates in general to production of oil and gas wells, and in particular to a device and method for delivery and/or retrieval of modules used in conjunction with subsea hydrocarbon production.

2. Description of Related Art

Subsea wellbores are formed from the seafloor through subterranean formations lying underneath. Systems for producing oil and gas from subsea wellbores typically include a subsea wellhead assembly set over a wellbore opening. A typical subsea wellhead assembly includes a high pressure wellhead housing supported in a lower pressure wellhead housing and secured to conductor casing that extends downward past the wellbore opening. Wells are generally lined with one or more casing strings coaxially inserted through, and significantly deeper than, the conductor casing. The casing strings are suspended from casing hangers landed in the wellhead housing. One or more tubing strings are provided within the innermost casing string; that among other things are used for conveying well fluid produced from the underlying formations. A production tree mounts to the upper end of the wellhead housing for controlling the well fluid. The production tree is typically a large, heavy assembly, having a number of valves and controls mounted thereon

Controls mounted on a production tree may be in the form of a subsea control module. Typically, subsea control modules are modular devices that regulate a supply of hydraulic fluid to subsea actuators, where the actuators are generally used to open and/or close a valve or valves. A choke bridge module is another type of module that is sometimes found on a production tree. Choke bridge modules generally regulate production flow from a production tree with an integrated flow restriction. Subsea control modules and choke bridge modules typically require replacement, installation, or removal during the operational life of the subsea wellhead assembly.

Summary of the Invention:

Disclosed herein is a running tool for handling a control module attachable to a subsea production tree. In an example embodiment the running tool includes a body having a connector that attaches to a subsea wellhead assembly. Also included is a swivel on the body distal from the connector that rotates about an axis of the body. A hoist assembly is included that couples with the swivel.

Also disclosed is a method of handling a control module subsea. In an example embodiment the method includes providing a running tool, where the running tool includes a body having an axis and a hoist assembly. The running tool is deployed subsea on a wire line to a subsea wellhead assembly and a control module is retrieved from the wellhead assembly using the hoist assembly.

Brief Description of the Drawings:

Figure 1 is a side partial sectional view of an example embodiment of a running tool being lowered to a subsea wellhead assembly.

Figures 2 – 4 are side partial sectional views of the running tool of Figure 1 coupled to the subsea wellhead assembly and replacing a subsea module on the wellhead assembly.

Figure 5 is a side partial sectional view of the running tool of Figure 1 removing a subsea module from the wellhead assembly.

Detailed Description of the Invention:

The apparatus and method of the present disclosure will now be described more fully hereinafter with reference to the accompanying drawings in which embodiments are shown. This subject of the present disclosure may, however, be embodied in many different forms and should not be construed as limited to the illustrated embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout. For the convenience in

referring to the accompanying figures, directional terms are used for reference and illustration only. For example, the directional terms such as "upper", "lower", "above", "below", and the like are being used to illustrate a relational location.

It is to be understood that the subject of the present disclosure is not limited to the exact details of construction, operation, exact materials, or embodiments shown and described, as modifications and equivalents will be apparent to one skilled in the art. In the drawings and specification, there have been disclosed illustrative embodiments of the subject disclosure and, although specific terms are employed, they are used in a generic and descriptive sense only and not for the purpose of limitation. Accordingly, the subject disclosure is therefore to be limited only by the scope of the appended claims.

Referring now to Figure 1, a side view of a running tool 10 is shown being deployed subsea on lift line 12. In the example of Figure 1, the lift line 12 is being reeled from a vessel 14 shown at the sea surface. In the example of Figure 1, the vessel 14 is a workboat of the type typically used for subsea operations. Optionally, the vessel 14 can be an offshore rig, a floating production storage and offloading vessel (FPSO), or any type of vessel used for operations associated with a subsea assembly.

The running tool 10 is shown being lowered towards a subsea wellhead assembly 16 shown disposed at the sea floor. The running tool 10 includes a body 18, which in an example embodiment, is an elongate substantially cylindrical member. Shown on an upper end of the body 18 is a swivel portion 20 that is substantially coaxial with the body 18 and rotatable about an axis. A portion of a hoist assembly 22 attaches to a side of the swivel portion 20 and includes a jib or boom 24 shown as an elongated member that projects radially outward from the swivel portion 20. Supported on the jib 24 is a pulley 26 that is selectively movable along the length of the jib 24. A line 28, separate from the lift line 12, extends between the pulley 26 and the body 18. The running tool 10 attaches to the lift line 12 with a lift line attachment 29 shown coupled between the lift line 12 and swiveling portion 20. A replacement choke bridge module 30 is shown attached on a lateral side of the body 18. Choke bridge module 30 is releaseably parked on the body 18 and is a component to be attached to subsea equipment. In an example embodiment, the

choke bridge module 30 can be deployed with the running tool 10 and used to replace an existing choke bridge module 31 shown provided with the wellhead assembly 16. The choke bridge modules 30, 31 can be used for regulating and/or diverting flow produced or otherwise flowing from the subsea wellhead assembly 16.

Still referring to Figure 1, the wellhead assembly 16 includes a wellhead housing 32 set over a well bore 34 bored through formation beneath the sea floor. A production tree 36 attaches to an upper end of the wellhead housing 36. A main bore 38 (shown in phantom line) extends substantially vertically through the wellhead housing 32 and production tree 36. A swab valve in the main bore 38 controls access through the main bore 38. An annular tree mandrel 39 is shown projecting upward from the production tree 36 from the main bore 38 and through a rectangular top plate 40. Column struts 42 support the top plate 40 over the production tree 36. Also included with the subsea wellhead assembly 16 are flow lines 44 coupled to lateral sides of the production tree 36. The flow lines 44 each include a wing valve 46 therein for controlling and regulating flow through the flow lines 44.

In Figure 2 the running tool 10 is shown landed on the wellhead assembly 16 with the body 18 substantially coaxial with the main bore 38 and tree mandrel 39. The running tool 10 is shown having a funnel 50 on its lower most portion to facilitate landing onto the tree mandrel 39. The funnel 50 is a conically shaped annular member with an opening on a lower end and an inner circumference that narrows with distance away from the opening. The funnel 50 can help to guide the running tool 10 to a desired orientation with the tree mandrel 39. Shown adjacent the funnel 50 is a connector 52 that can be manipulated to grapple the outer circumference of the tree mandrel 39 to rigidly attach the running tool 10 to the wellhead assembly 16. In an example embodiment the connector 52 is annular and includes clamps on an inner circumference that can selectively attach on the outer circumference of the tree mandrel 39. One example embodiment the connector 52 is a Vetco MDH4 connector.

The example of Figure 2 further illustrates the line 28 having been reeled out from the running tool 10 to have an attachment end extending past the hoist assembly 22. The

attachment end of the line 28 is connected with the existing choke bridge module 31. In an example embodiment, an actuator 54 is illustrated set within the body 18 for supplying the line 28 from the running tool 10. In one example, the actuator 54 includes gears (not shown) connected to a spool or reel 55 within the body 18. The line 28 can be stored on the reel 55 within the body 18 and then reeled out for connection to the choke bridge module 31, or other object. The actuator 54 may be powered by a motor 56, also shown within the housing 18 and connected to the actuator 54 via a shaft. Other connection means such as belts or chains may be employed as well. To effectuate connection between the line 28 and choke bridge module 31 a connector 57 is illustrated that can selectively couple to the original or existing choke bridge module 31 as well as the replacement choke bridge module 30.

Referring now to Figure 3 the existing choke bridge module 31 has been released and lifted from its original location on the subsea wellhead assembly 16 and parked on the top table 40. Additionally, the hoist assembly 22 is further manipulated so that the swivel 20 rotates about the axis A_X thereby aligning the line 28 with the replacement choke bridge module 30. Also optionally, as indicated by the arrow A, the reel 26 has been moved radially inward along the boom 24 for a precise alignment with the replacement choke bridge module 30. Additionally, the line 28 is shown connected to the replacement choke bridge module 30 via connector 57. Arrow A_R illustrates one example direction of swiveling rotation of the swivel 20.

Referring to Figure 4, the hoist assembly 22 is further actuated in a position to land the replacement choke bridge module 30 in the same location where the original choke bridge module 31 was located. Rotational swiveling movement of the swivel 20 is shown by arrow A_R and lateral movement of the pulley 26 is illustrated by arrow A. A remotely operated vehicle 58 is illustrated that may be used to assist in positioning the replacement choke bridge module 30 on the production tree 36. A control tether 60 attaches to an end of the ROV and used for powering and/or control of the ROV. In the example of Figure 4, the original choke bridge module 31 and replacement control module are modules

having a choke bridge for regulating flow from the production tree 36 to processing or other terminal locations.

Optionally, as shown in Figure 5, the procedures described herein may be used to replace a subsea control module 62 shown attached to the production tree 36. The subsea control module 62 can be used for control of actuators associated with the subsea wellhead assembly 16, such as for opening and closing the swab valve and/or wing valves. In an example embodiment, subsea control module 62 includes hardware and software for controlling operation of systems within or associated with the subsea wellhead assembly 16. For example, the flow of electricity or hydraulics may be regulated through the subsea control module 62 for actuating movable devices, such as valves, located on the subsea wellhead assembly 16.

While the invention has been shown or described in only some of its forms, it should be apparent to those skilled in the art that it is not so limited, but is susceptible to various changes without departing from the scope of the invention. For example, in addition to the modules 30, 31, 62 discussed above, other wellhead components may be replaced or installed using the devices and methods provided herein. Such additional components include choke inserts, sand detectors, and flow control devices. Thus, in an example embodiment, a hoist assembly 22 could be deployed having one or more of a choke bridge module, subsea control module, a choke insert, a sand detector, flowmeter control unit, and a flow control device. Moreover, the hoist assembly 22 can also carry with it the tools for replacing any of the components, such as an interface tool. In an example embodiment, an interface tool is included with the connector 57 for interfacing with the component being replaced. One advantage of the device and method described herein is the running tool 10 can be lowered subsea at a rate of descent so it "softly" lands on the wellhead assembly 16 without imparting a damaging impulse in the running tool 10 or component being replaced.

PARTS LIST

10	running tool
12	wireline
14	workboat
16	subsea wellhead assembly
18	body
20	swivel
22	hoist assembly
24	jib/boom
26	pulley/sheave
28	line
29	wireline attachment
30	new choke bridge module
31	existing choke bridge module
32	wellhead housing
34	wellbore
36	production tree
38	main bore
39	tree mandrel
40	top table
42	support
44	flow line
46	wing valve
48	module
50	funnel
52	connector
54	actuator
55	reel
56	motor
57	connector
58	ROV
60	control line
62	module (SCM)

Claims:

What is claimed is:

1. A running tool for replacing a component of a subsea production tree comprising:

a body having an axis;

a connector on an end of the body that selectively attaches to a subsea wellhead assembly;

and

a hoist assembly on the body having a winch and a line.
2. The running tool of claim 1, further comprising a swivel on the body distal from the connector that rotates the hoist assembly selectively about the axis of the body.
3. The running tool of claim 2, further comprising a motor in the body and attached to the swivel for rotating the swivel.
4. The running tool of claim 1, wherein the hoist assembly comprises a jib member that extends radially outward from the body and a line support that is selectively moveable along the jib member, where the line depends from the line support.
5. The running tool of claim 1, further comprising a motor in the body that rotates the winch.
6. The running tool of claim 4, wherein the line support comprises a pulley.
7. The running tool of claim 1, further comprising a replacement component for a subsea well.
8. The running tool of claim 1, further comprising a parking location on the body for releasably carrying a subsea component.

9. The running tool of claim 1, further comprising a lift line attachment on the body for connecting to a lift line of a surface platform to lower the running tool from a surface platform.

10. The running tool of claim 1, further comprising a funnel attachment depending from a lower end of the connector for guiding the running tool onto a production tree mandrel.

11. The running tool of claim 1, further comprising a connector on an end of the line and that is selectively attached to a component for the subsea wellhead tree.

12. A method of handling a control module subsea comprising:

providing a running tool comprising: a body having an axis and a hoist assembly having a winch and line;

deploying the running tool subsea on a lift line to a subsea wellhead assembly;

connecting the body to the subsea wellhead assembly;

deploying the line with the winch and engaging a subsea component on the subsea wellhead assembly;

swiveling the hoist assembly to an angular position about an axis of the body to position the line with the subsea component;

attaching the line to the subsea component and reeling the line to the running tool

releasing the component from the hoist assembly;

disconnecting the running tool; and

retrieving a the running tool from the wellhead assembly.

13. The method of claim 12, further comprising stowing the retrieved component onto the body.

14. The method of claim 12, wherein the running tool further comprises a swivel on the body that is selectively rotated about the axis of the body, wherein the hoist is attached to the swivel, the method further comprising attaching a replacement component to the body that is deployed with the running tool, after rotating the swivel to align the hoist with the replacement control module, and using the hoist to move the replacement subsea component from the body onto the subsea wellhead assembly.

15. The method of claim 12, wherein the subsea component comprises an original subsea component, the method further comprising providing a replacement subsea component on the body, lowering the running tool subsea with the replacement subsea component parked on the running tool.

16. The method of claim 15, further comprising detaching the original subsea component from the line, swiveling the hoist to position the line for attachment to the replacement subsea component, attaching the line to the replacement subsea component, and moving the replacement subsea component from the body to the subsea wellhead assembly in the location from where the original subsea component was retrieved.

17. The method of claim 12, further comprising using a remotely operated vehicle in conjunction with the running tool.

18. The method of claim 12, wherein only the wire line is used for deploying the running tool.