

OXYCOMBUSTION SYSTEMS AND METHODS WITH THERMALLY INTEGRATED AMMONIA SYNTHESIS

BACKGROUND

Field

[0001] The present specification generally relates to combustion systems and, more particularly, to oxycombustion systems and methods in which oxycombustion is conducted together with a thermally integrated ammonia synthesis.

Technical Background

[0002] In a carbon-constrained world, energy efficiency and CO₂ capture play major roles in controlling CO₂ emissions for a sustainable future. The growing worldwide demand for energy is constantly in strife with pushes for protection of the environment. This combination of issues requires ongoing development of systems that are not only energy efficient but also reduce emissions of CO₂ and pollutants. Energy efficient systems are most often the fruit of systems integration and energy fluxes management.

[0003] Oxycombustion with CO₂ capture is a technique to combust fuels with pure oxygen while capturing CO₂ and avoiding numerous pollutants. Oxycombustion uses substantially pure oxygen to combust a fuel, leaving the flue gases substantially nitrogen-free, with primarily CO₂ and water as waste products or flue gases. It is then possible to cool the flue gases to condense the water and recover the CO₂ stream with minimum energy penalty. Typical combustion processes in the presence of nitrogen molecules and oxygen molecules generate nitrogen oxides (NO_x), the harmful pollutants that have led to emissions legislation around the world.

[0004] Most fossil fuels also contain sulfur compounds that lead to the formation of sulfur oxide (SO_x) pollutants when these fuels are combusted or oxidized. In refinery streams, hydrogen produced in the refineries can be used to hydro-treat liquid fuels, for example, and reduce sulfur content. Several processes also exist for post-combustion SO_x removal. For example, ammonia injection into a flue gas stream has been found to

-2-

reduce both NO_x and SO_x emissions. Nevertheless, in such post-combustion processes the ammonia must be purchased or derived from a separate source at a both an energy cost and a monetary cost.

[0005] Ongoing needs exist for fuel combustion systems that operate with increased energy efficiency and that produce fewer harmful emissions of greenhouse gases such as CO_2 and pollutants such as NO_x , and/or SO_x .

SUMMARY

[0006] According to various embodiments, oxycombustion systems with thermally integrated ammonia synthesis are provided. The oxycombustion systems may include an air separation unit that separates an air feed stream into an oxygen stream and a nitrogen stream. The oxycombustion systems may also include an ammonia synthesis unit that synthesizes ammonia from a hydrogen feed stream and the nitrogen stream from the air separation unit to form a crude ammonia stream containing the ammonia and, optionally, unreacted nitrogen and hydrogen. The oxycombustion systems may further include an ammonia separation unit that condenses the crude ammonia stream formed in the ammonia synthesis unit and separates the ammonia from any unreacted nitrogen and hydrogen to form a purified ammonia stream. The oxycombustion systems may further include an oxycombustion reactor that combusts a fuel from a fuel feed stream in the presence of the oxygen stream from the air separation unit to generate combustion heat. In some embodiments, at least one thermal integration is present in the oxycombustion systems. The at least one thermal integration may be chosen from a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor, a separator thermal linkage of the air separation unit with the ammonia separation unit, or both.

[0007] According to further embodiments, methods for performing oxycombustion with thermally integrated ammonia synthesis are provided. The methods may include separating an air feed stream with an air separation unit into an oxygen stream and a nitrogen stream. The oxygen stream may be flowed to an oxycombustion reactor, and the nitrogen stream may be flowed to an ammonia synthesis unit. The nitrogen stream in the ammonia synthesis unit may be combined with a hydrogen feed stream to synthesize

-3-

ammonia and form a crude ammonia stream containing the ammonia and, optionally, unreacted nitrogen or hydrogen. The crude ammonia stream may be condensed in an ammonia separation unit so as to separate the ammonia in the crude ammonia stream from any unreacted nitrogen or hydrogen in the crude ammonia stream and form a purified ammonia stream. The methods may further include combining a fuel from a fuel stream with the oxygen stream from the air separation unit to form a fuel mixture. The fuel mixture may be combusted in the oxycombustion reactor to generate combustion heat. The methods may further include transferring thermal energy through at least one thermal integration while the fuel mixture is being combusted and the ammonia is being synthesized. The at least one thermal integration may be chosen from a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor, a separator thermal linkage of the air separation unit with the ammonia separation unit, or both.

[0008] Additional features and advantages of the embodiments described herein will be set forth in the detailed description which follows, and in part will be readily apparent to those skilled in the art from that description or recognized by practicing the embodiments described herein, including the detailed description which follows, the claims, as well as the appended drawings.

[0009] It is to be understood that both the foregoing general description and the following detailed description describe various embodiments and are intended to provide an overview or framework for understanding the nature and character of the claimed subject matter. The accompanying drawings are included to provide a further understanding of the various embodiments, and are incorporated into and constitute a part of this specification. The drawings illustrate the various embodiments described herein, and together with the description serve to explain the principles and operations of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a schematic representation of an oxycombustion system with thermally integrated ammonia synthesis, according to embodiments described herein;

-4-

[0011] FIG. 2 is a schematic representation of an oxycombustion system with thermally integrated ammonia synthesis and including a urea synthesis unit, according to embodiments described herein; and

[0012] FIG. 3 is a schematic representation of an oxycombustion system with thermally integrated ammonia synthesis and including a urea synthesis unit, according to embodiments described herein, in which urea, ammonia, or both are used by the oxycombustion system to remove pollutants from flue gas generated in the oxycombustion reactor.

DETAILED DESCRIPTION

[0013] Embodiments of oxycombustion systems with thermally integrated ammonia synthesis will now be described with reference to FIGS. 1–3. According to some embodiments, the oxycombustion systems 1, 2, 3 may include an air separation unit 10 that separates an air feed stream 100 into an oxygen stream 101 and a nitrogen stream 500. The oxycombustion systems 1, 2, 3 may also include an ammonia synthesis unit 50 that synthesizes ammonia from a hydrogen feed stream 600 and the nitrogen stream 500 from the air separation unit 10 to form a crude ammonia stream 501 containing the ammonia and, optionally, unreacted nitrogen and hydrogen. The oxycombustion systems 1, 2, 3 may further include an ammonia separation unit 51 that condenses the crude ammonia stream 501 formed in the ammonia synthesis unit 50 and separates the ammonia from any unreacted nitrogen and hydrogen to form a purified ammonia stream 503. The oxycombustion systems 1, 2, 3 may further include an oxycombustion reactor 20 that combusts a fuel from a fuel feed stream 200 in the presence of the oxygen stream 101 from the air separation unit 10 to generate combustion heat that may be used to heat water and form hot water or steam, for example. In some embodiments, at least one thermal integration is present in the oxycombustion systems. The at least one thermal integration may be chosen from a reactor thermal linkage 925, 952 of the ammonia synthesis unit 50 with the oxycombustion reactor 20, a separator thermal linkage 915, 951 of the air separation unit 10 with the ammonia separation unit 51, or both.

-5-

[0014] One embodiment of an oxycombustion system is provided in FIG. 1. An air separation unit **10** separates an air feed stream **100** into an oxygen stream **101** and a nitrogen stream **500**. The air separation unit **10** may include any type of apparatus capable of separating nitrogen and oxygen components of air into separate streams, such as the oxygen stream **101** and the nitrogen stream **500**. For example, the air separation unit **10** may contain a cryogenic distillation apparatus, in which air is cooled until liquefied and the components of the air such as oxygen, nitrogen, and other minor components such as inert gases and carbon dioxide are selectively distilled. Generally, cryogenic distillation apparatus require a refrigeration cycle, whereby thermal energy or heat must be removed from the air and rejected away from the apparatus. Other classes of separation apparatus not involving liquefaction of the air, such as those employing pressure-swing adsorption, vacuum-swing adsorption, or membrane technologies may also be used as the air separation unit **10**. The thermodynamics of the processes used by such types of separation apparatus also involve rejection of heat. The oxygen stream **101** leaving the air separation unit **10** is enriched in oxygen, in that it has a higher volume content of oxygen than that of air, which contains about 21% oxygen by volume. In some exemplary embodiments, the oxygen stream **101** may contain greater than 25% by volume O₂, greater than 40% by volume O₂, greater than 50% by volume O₂, greater than 60% by volume O₂, greater than 70% by volume O₂, or greater than 75% by volume O₂. In further exemplary embodiments, the oxygen stream **101** may be pure oxygen or substantially pure oxygen, such as from 80% to 100% by volume O₂, 90% to 100% by volume O₂, 95% to 100% by volume O₂, or 95% to 99.9% by volume O₂, for example. The precise oxygen content of the oxygen stream **101** may be adjustable based on the operating parameters and configuration of the air separation unit **10** and may also be chosen based on the operational needs of the oxycombustion reactor **20**. Optionally, an atomization medium may be added from an atomization source **800** to the oxygen stream **101** at the oxycombustion reactor **20**, such as into a chamber of the oxycombustion reactor **20** that includes the burner for combusting the fuel. In one embodiment, the atomization medium may include steam or carbon dioxide, for example. Atomization media may facilitate more complete and more efficient combustion of the fuel in the oxycombustion reactor **20**. The nitrogen stream **500** leaving the air separation unit **10** may be pure nitrogen or substantially pure nitrogen, such as from such as from 80% to

100% by volume N₂, 90% to 100% by volume N₂, 95% to 100% by volume N₂, or 95% to 99.9% by volume N₂, for example.

[0015] The ammonia synthesis unit **50** may be any industrial-scale apparatus or vessel that synthesizes ammonia from hydrogen and nitrogen using the Haber process, a modified Haber process, or any other industrial ammonia synthesis process. According to the Haber process, ammonia synthesis from hydrogen and nitrogen may be conducted at high pressure (15 MPa to 25 MPa, for example) and high temperature (300 °C to 550 °C, for example) over one or more catalyst beds. The hydrogen of the hydrogen feed source **600** may be supplied from an independent source or may be derived from petroleum-related processes in other parts of a refinery where the oxycombustion system **1** is being used. The conversion reaction of hydrogen and nitrogen to ammonia is exothermic, and heat is generated in the reactor bed. Nevertheless, an initial heat is required to heat the nitrogen and the hydrogen to the reaction temperature. A single pass of the hydrogen from the hydrogen feed source **600** and the nitrogen from the nitrogen stream **500** through the ammonia synthesis unit **50** does not typically result in full conversion of the source gases to ammonia. As such, a crude ammonia stream **501** is formed that is fed to the ammonia separation unit **51**. The crude ammonia stream **501** contains ammonia, unreacted nitrogen and/or hydrogen, and potentially small amounts of other gases derived from air that may be present in the nitrogen stream **500**.

[0016] The ammonia separation unit **51** condenses at least a portion of the crude ammonia stream **501** formed in the ammonia synthesis unit **50**, separates the ammonia from any unreacted nitrogen and hydrogen or other gases present in the crude ammonia stream **501**, and directs the ammonia into a purified ammonia stream **503**. In some embodiments, the ammonia separation unit **51** condenses only the ammonia in the crude ammonia stream **501**. Because of the low conversion rate of the ammonia synthesis reaction, the crude ammonia stream **501** is cooled to below the boiling point of ammonia (about -33 °C) to condense and recover liquid ammonia, whereupon the hydrogen, nitrogen, and/or other components of the crude ammonia stream **501** that remain in the gaseous state may be recirculated through recirculation line **502** back to the ammonia synthesis unit **50** to increase the overall conversion rate. To condense the ammonia, a

-7-

cold sink is required to remove heat from the crude ammonia stream **501** in the ammonia separation unit **51**. In some embodiments, the purified ammonia stream **503** may be split into an ammonia recovery stream **505** and an ammonia scrubbing stream **504**. The ammonia in the ammonia recovery stream **505** may be collected or used for any further purpose outside the oxycombustion system **1**. The ammonia in the ammonia scrubbing stream **504** may be used to remove pollutants from flue gases, as will be described in greater detail below. In other embodiments, the purified ammonia stream **503** may not be split and may be used exclusively for collection through the ammonia recovery stream **505** or exclusively for scrubbing of flue gas through the ammonia scrubbing stream **504**.

[0017] The oxycombustion reactor **20** combusts a fuel from a fuel feed stream **200** in the presence of the oxygen stream **101** from the air separation unit **10** to generate combustion heat. The oxycombustion reactor **20** may be any apparatus suitable for combusting the fuel at the temperatures reached when the fuel is burned in pure oxygen or substantially pure oxygen. In exemplary embodiments, the fuel may be any type of fossil fuel, such as natural gas, for example, or any type of combustible biomass. Combustion of the fuel in enriched oxygen, for example in an oxygen stream **101** having an oxygen content by volume greater than that of air (about 21 vol.%), in pure oxygen, or in substantially pure oxygen typically generates fewer pollutants, with CO₂ and H₂O being the primary components of flue gases. Also, because nitrogen is absent or substantially absent from the combustion gases, NO_x pollutants are severely reduced. In some embodiments, the oxycombustion reactor **20** may be a boiler, such that the combustion heat generated by the combustion of the fuel may be used to heat or vaporize a fluid such as water, for example. Hot or vaporized liquid (such as hot water or steam, for example) may then be used to transfer the combustion heat elsewhere outside the oxycombustion system **1**, to provide energy to a power generation system such as a turbine, for example, or to provide a thermal integration for the oxycombustion system **1** itself, as will be discussed in greater detail below.

[0018] The oxycombustion system **1** further includes at least one thermal integration. As described above, various operations in the oxycombustion system **1** either produce heat or require heat. For example, the combustion of the fuel in the oxycombustion

-8-

reactor **20** produces a substantial amount of heat. On the other hand, the synthesis of ammonia in the ammonia synthesis unit **50** requires heat to raise the nitrogen and hydrogen to reaction temperature. Likewise, the separation of air in the air separation unit **10** may involve warming liquid air from a temperature lower than the boiling point of liquid nitrogen (78 K; $-195\text{ }^{\circ}\text{C}$) during a distillation process. On the other hand, the condensation of ammonia from the crude ammonia stream **501** in the ammonia separation unit **51** requires a rejection of heat from the crude ammonia stream **501** to lower the temperature of the crude ammonia stream **501** to below the boiling point of ammonia (about $-33\text{ }^{\circ}\text{C}$). The at least one thermal integration of the oxycombustion system **1** takes advantage of the thermal needs of the various components of the oxycombustion system **1** to allow one component with excess heat to provide the excess heat to a component that needs additional heat or, in another sense, to allow one component that is already cold to help another hot component become colder or to allow one component that is already hot to help another colder component become hotter.

[0019] In some embodiments, the at least one thermal integration of the oxycombustion system **1** may include a reactor thermal linkage **925, 952** of the ammonia synthesis unit **50** with the oxycombustion reactor **20**. The reactor thermal linkage **925, 952** may be configured as any industrially feasible mechanism for establishing thermal communication between the ammonia synthesis unit **50** and the oxycombustion reactor **20**. In particular, the reactor thermal linkage provides a mechanism for directing combustion heat produced by the oxycombustion reactor **20** during combustion of the fuel toward the ammonia synthesis unit **50**, which requires the heat to bring the nitrogen from the nitrogen stream **500** and the hydrogen from the hydrogen feed stream **600** up to a temperature suitable for conducting ammonia synthesis. In some embodiments, the reactor thermal linkage **925, 952** of the ammonia synthesis unit **50** with the oxycombustion reactor **20** may be a boiler loop that transfers heat to the ammonia synthesis unit **50**. The combustion heat going into the boiler loop may be obtained from the oxycombustion reactor **20** itself (such as from a chamber in the oxycombustion reactor **20**), from flue gas formed in the oxycombustion reactor **20**, from at least a portion of any hot water or steam heated by the oxycombustion reactor **20**, or a combination thereof. The boiler loop may contain a heat transfer fluid such as water, for

-9-

example, that accepts heat from the oxycombustion reactor **20** then rejects the heat to the ammonia synthesis unit **50**. Thermal transfer to and from the boiler loop may be accomplished by any practical means such as through heat exchanger fins or coils. The heat transfer fluid in the boiler loop may be circulated within the boiler loop by any practical means, such as with a pump, for example.

[0020] In some embodiments, the at least one thermal integration of the oxycombustion system **1** may include a separator thermal linkage **915, 951** of the air separation unit **10** with the ammonia separation unit **51**. The separator thermal linkage **915, 951** may be configured as any industrially feasible mechanism for establishing thermal communication between the air separation unit **10** and the ammonia separation unit **51**. In particular, the separator thermal linkage provides a mechanism for directing heat away from the ammonia separation unit **51** while ammonia is being condensed from the crude ammonia stream **501**. The transfer of heat in this manner is facilitated by the significantly lower temperature of the liquefied air being separated in the air separation unit **10**. Thus, in such embodiments, the air separation unit **10** becomes a cold sink for the ammonia separation unit **51**. In some embodiments, the separator thermal linkage **915, 951** of the air separation unit **10** and the ammonia separation unit **51** may be a separator loop that removes heat from the ammonia separation unit **51**. Thereby, heat from the ammonia separation unit **51** enters the separator loop to be rejected at the air separation unit **10**. The separator loop may contain a heat transfer fluid having an appropriately low freezing point, whereby the heat transfer fluid can accept the heat from the ammonia separation unit **51** and reject the heat at the air separation unit **10**. Thermal transfer to and from the separator loop may be accomplished by any practical means such as through heat exchanger fins or coils. The heat transfer fluid in the separator loop may be circulated within the separator loop by any practical means, such as with a pump, for example.

[0021] In some embodiments, the at least one thermal integration of the oxycombustion system **1** may include both a reactor thermal linkage **925, 952** of the ammonia synthesis unit **50** with the oxycombustion reactor **20**, as described above, and a

separator thermal linkage **915**, **951** of the air separation unit **10** with the ammonia separation unit **51**, as described above.

[0022] In addition to the air separation unit **10**, oxycombustion reactor **20**, the ammonia synthesis unit **50**, and the ammonia separation unit **51**, the oxycombustion system **1** according to some embodiments may also include a flue-gas treatment system **30** that treats a flue gas formed by the combustion of the fuel in the oxycombustion reactor **20**. The flue gas may exit the oxycombustion reactor **20** through flue gas stream **102**. Depending on the type of fuel being combusted in the oxycombustion reactor **20**, and also depending on the types of impurities that may be present in the fuel or the oxygen stream **101**, the flue gas stream **102** may contain various pollutants such as particulates, NO_x and SO_x gases, or heavy metals. These pollutants are preferably scrubbed from the flue gas stream to avoid their release into the atmosphere or environment. In some embodiments, the purified ammonia stream **503** may be in fluidic communication with the flue-gas treatment system **30**, and at least a portion of the ammonia separated in the ammonia separation unit **51** may be used in the flue-gas treatment system **30** to remove pollutants from the flue gas. To use the ammonia in the flue-gas treatment system **30**, the purified ammonia stream **503** may be split to include the ammonia scrubbing stream **504**, which may be directed to the flue-gas treatment system **30**. The ammonia from the ammonia scrubbing stream **504** may then be used in processes such as selective catalytic reduction (SCR) or electron-beam flue-gas treatment (EBFGT) to remove NO_x species from the flue gas. Example systems for removing pollutants such as NO_x, SO_x, and heavy metals from flue gases in general are described in U.S. Pat. Nos. 8,323,602 and 5,695,616, and in European Patents EP2156878 and EP0818232.

[0023] The flue gas treated in the flue-gas treatment system **30** may leave the flue-gas treatment system **30** through a scrubbed stream **103**. The scrubbed stream **103** may contain carbon dioxide (CO₂), water, and possibly also may contain nitrogen and inert gases. In such cases, the CO₂ leaves the oxycombustion reactor **20** in the flue gas stream **102** and, in turn, the flue-gas treatment system **30** outputs the CO₂. In some embodiments, the scrubbed stream **103** may simply be exhausted to the atmosphere. In

-11-

other embodiments, the scrubbed stream **103** may be directed through a capture stream **105** into a carbon dioxide capture unit **40**. In other embodiments, the scrubbed stream may be directed into a reactor recirculation stream **104** that adds the components of the scrubbed stream **103** (such as CO₂ and water, for example) back into the oxycombustion reactor **20** to moderate the combustion temperature of the fuel. In other embodiments, the scrubbed stream **103** may be split such that a first portion of the scrubbed stream **103** flows into the capture stream **105** for CO₂ capture in the carbon dioxide capture unit **40**, while a second portion of the scrubbed stream **103** flows into the reactor recirculation stream **104**.

[0024] In the carbon dioxide capture unit **40**, if one is present in the oxycombustion system **1**, the capture stream **105** may be treated by cooling, for example, to separate the carbon dioxide in the capture stream **105** from any additional components of the capture stream **105** such as water, for example. In exemplary embodiments, the carbon dioxide may be captured in a gaseous state, while the water is condensed out in a liquid state. The carbon dioxide may then be recovered from a carbon dioxide recovery stream **400** for further uses inside or outside the oxycombustion system **1**, and the water may be released or reused from water recovery stream **300**. For example, in one embodiment the carbon dioxide recovered from the carbon dioxide recovery stream **400** may be reused inside the oxycombustion system **1** as an atomizing medium to be introduced into the oxycombustion reactor **20** via the atomization source **800**. Any additional gases that remain in the capture stream **105** after passing through the carbon dioxide capture unit **40**, typically only nitrogen and noble gases such as argon, may be vented from the oxycombustion system **1** through a system exhaust **499**. It should be understood that the oxycombustion system **1** of FIG. **1** may additionally require the implementation of process apparatus such as compressors, recirculation fans, pumps, and controllers using configurations that should be readily apparent to those having ordinary skill in the art, even though they may not be explicitly shown in FIG. **1**.

[0025] In some embodiments, when the carbon dioxide capture unit **40** is included in the oxycombustion system **1**, the oxycombustion system **1** may further include at least one capture-unit thermal integration. As noted above, the carbon dioxide capture unit **40**

-12-

may be operated by cooling flue gases to low temperatures to condense water from the carbon dioxide recovery stream **400**. For example, the flue gases may be cooled to temperatures such as from $-30\text{ }^{\circ}\text{C}$ to $-55\text{ }^{\circ}\text{C}$, depending on the initial concentration of CO_2 in the carbon dioxide recovery stream **400**, on the types of and amounts of expected impurities that may be present in the carbon dioxide recovery stream **400**, and also on a desired purity of any CO_2 to be recovered and put to use inside or outside the oxycombustion system **1**. As such, the carbon dioxide capture unit **40** may be utilized as a cold sink for other components of the oxycombustion system **1**. In some exemplary embodiments, the oxycombustion system **1** may include an air-separator capture-unit thermal linkage **914**, **941** between the carbon dioxide capture unit **40** and the air separation unit **10** as a capture-unit thermal integration. In other exemplary embodiments, the oxycombustion system **1** may include an ammonia-separator capture-unit thermal linkage **956**, **965** between the carbon dioxide capture unit **40** and the ammonia separation unit **51** as a capture-unit thermal integration. In still other exemplary embodiments, the oxycombustion system **1** may include both an air-separator capture-unit thermal linkage **914**, **941** and an ammonia-separator capture-unit thermal linkage **956**, **965** as capture-unit thermal integrations.

[0026] When present, the at least one capture-unit thermal integration such as the air-separator capture-unit thermal linkage **914**, **941**, the ammonia-separator capture-unit thermal linkage **945**, **954**, or both, may be configured as any industrially feasible mechanism for establishing thermal communication between the carbon dioxide capture unit **40** and the air separation unit **10** or the ammonia separation unit **51**, as applicable. In particular, the air-separator capture-unit thermal linkage **914**, **941** may provide a mechanism for directing heat away from the air separation unit **10** while air is being condensed from air feed stream **100**. Likewise, the ammonia-separator capture-unit thermal linkage **945**, **954** may provide a mechanism for directing heat away from the ammonia separation unit **51** while ammonia is being condensed from the crude ammonia stream **501**. In both the air-separator capture-unit thermal linkage **914**, **941** and the ammonia-separator capture-unit thermal linkage **945**, **954**, the transfer of heat is facilitated by the significantly lower temperature of the carbon dioxide being condensed in the carbon dioxide capture unit **40**. Thus, with capture-unit thermal integrations, the

carbon dioxide capture unit **40** becomes a cold sink for the air separation unit **10** or the ammonia separation unit **51**. The at least one capture-unit thermal integration may be configured as any industrially feasible thermal-transfer loop that can bring about the desired transfer of heat. Such a thermal-transfer loop may contain a heat transfer fluid having an appropriately low freezing point, for example. Thermal transfer to and from the thermal-transfer loop may be accomplished by any practical means such as through heat exchanger fins or coils. The heat transfer fluid in the separator loop may be circulated within the thermal-transfer loop by any practical means, such as with a pump, for example.

[0027] Referring to FIG. 2, the oxycombustion system described above may additionally be configured as an integrated urea-synthesis oxycombustion system **2**. The integrated urea-synthesis oxycombustion system **2** may include components of the oxycombustion system **1** of FIG. 1 and in addition may include a urea synthesis unit **60**. When a urea synthesis unit **60** is present, the ammonia recovery stream **505** may be split, such that at least a portion of the ammonia in the ammonia recovery stream **505** is directed through a urea-precursor ammonia stream **507** into the urea synthesis unit **60**. Any remaining ammonia not required by the urea synthesis unit **60** may be directed from the ammonia recovery stream **505** to ammonia recovery outlet **506**. The urea-precursor ammonia stream **507** may then be combined in the urea synthesis unit **60** with CO₂ from the carbon dioxide recovery stream **400** to form urea that may be recovered from a urea recovery stream **700**. The urea may be formed in the urea synthesis unit **60** using any well known process parameters, which typically may involve elevated temperatures such as from 150 °C to 250 °C, for example and elevated pressures such as from 12 MPa to 40 MPa, for example. During urea synthesis, typically two molar parts of ammonia combine with one molar part of CO₂ to form an ammonium carbamate such as H₂N–CO–ONH₄, which is then dehydrated to yield urea and water. Urea formed by this reaction may be an aqueous solution or a melt that can be subjected to further processing such as prilling, granulation, pelletizing, or compacting. It should be understood that the integrated urea-synthesis oxycombustion system **2** of FIG. 2 may additionally require the implementation of process apparatus such as compressors, recirculation fans, pumps, and

controllers using configurations that should be readily apparent to those having ordinary skill in the art, even though they may not be explicitly shown in FIG. 2.

[0028] In some embodiments, the integrated urea-synthesis oxycombustion system **2** may further include an air-separator capture-unit thermal linkage **914, 941**, an ammonia-separator capture-unit thermal linkage **945, 954**, or both, as described above with respect to the oxycombustion system **1** of FIG. 1. In further embodiments, the integrated urea-synthesis oxycombustion system **2** with or without the air-separator capture-unit thermal linkage **914, 941**, an ammonia-separator capture-unit thermal linkage **945, 954** may also include a urea synthesis thermal integration such as a urea synthesis thermal linkage **926, 962** between the urea synthesis unit **60** and the oxycombustion reactor **10**. With the urea-synthesis thermal linkage **926, 962** in place, excess heat from the oxycombustion reactor **10** may be used as an energy source for bringing the ammonia in the urea-precursor ammonia stream **507** and the carbon dioxide from the carbon dioxide recovery stream **400** up to a reaction temperature that facilitates or enables their reaction to form urea. Thereby, any contemplated additional heating unit at the urea synthesis unit **60** may be designed to use less energy or may even be eliminated entirely. The urea synthesis thermal linkage **926, 962** may be configured as any industrially feasible thermal-transfer loop that can bring about the desired transfer of heat from the oxycombustion reactor **10** to the urea synthesis unit **60**. Such a thermal-transfer loop may contain a heat transfer fluid with appropriate thermal properties such as boiling point, for example. Thermal transfer to and from the thermal-transfer loop may be accomplished by any practical means such as through heat exchanger fins or coils. The heat transfer fluid in the separator loop may be circulated within the thermal-transfer loop by any practical means, such as with a pump, for example.

[0029] Referring to FIG. 3, the integrated urea-synthesis oxycombustion system **2** described above may be further configured as a urea flue-gas treatment system **3**. The urea flue-gas treatment system **3** may include components of the oxycombustion system **1** and the integrated urea-synthesis oxycombustion system **2** and, in addition, the urea recovery stream **700** may be modified or added to. In one embodiment, the urea recovery stream **700** may be directed entirely to a urea scrubbing stream **701** that adds

-15-

urea into the flue-gas treatment system **30** for use in scrubbing technologies that use urea to remove pollutants. In such embodiments, the urea from the urea scrubbing stream **701** may be used in addition to or in place of ammonia from the ammonia scrubbing stream **504**. That is, at least one of the urea scrubbing stream **701** and the ammonia scrubbing stream **504** may be in fluidic communication with the flue-gas treatment system **30**, such that at least a portion of the ammonia from the purified ammonia stream **503** or at least a portion of the urea from the urea recovery stream **700**, or both, may be used to remove pollutants from the flue gas in the flue-gas treatment system **30**. In other embodiments, a first portion of the urea recovery stream **700** may be directed to the urea scrubbing stream **701** while a second portion of the urea recovery stream **700** may be directed to a urea collection stream **702**, such that any urea that is not required by the operation of the flue-gas treatment system **30** may be used for other purposes outside the urea flue-gas treatment system **3**. It should be understood that the urea flue-gas treatment system **3** of FIG. **3** may additionally require the implementation of process apparatus such as compressors, recirculation fans, pumps, and controllers using configurations that should be readily apparent to those having ordinary skill in the art, even though they may not be explicitly shown in FIG. **3**.

[0030] In some embodiments, the urea flue-gas treatment system **3** may further include an air-separator capture-unit thermal linkage **914**, **941**, an ammonia-separator capture-unit thermal linkage **945**, **954**, a urea synthesis thermal linkage **926**, **962**, any combination of two of these, or all of these, each as described above with respect to the oxycombustion system **1** of FIG. **1** or the integrated urea-synthesis oxycombustion system **2** of FIG. **2**.

[0031] Thus, various embodiments of the oxycombustion system **1** of FIG. **1**, the integrated urea-synthesis oxycombustion system **2** of FIG. **2**, and the urea flue-gas treatment system **3** of FIG. **3** have been described. These systems make efficient use not only of nitrogen and oxygen components of air to simultaneously feed ammonia synthesis, oxycombustion, and, optionally, urea synthesis, but also in some embodiments use the ammonia and/or urea to clean flue gases that result from the oxycombustion. When ammonia and/or urea are generated in an integrated system, it is not necessary to

-16-

procure the ammonia and/or urea from external sources when they are required or desired for use in scrubbing flue gas and removing pollutants from the flue gas. Additionally, the systems make efficient use of thermal energy through their at least one thermal integration such as a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor, a separator thermal linkage of the air separation unit with the ammonia separation unit, or both. Thermal integrations in this manner can eliminate needs in the oxycombustion systems for additional components such as refrigeration systems to condense ammonia or heaters to heat hydrogen and nitrogen in for ammonia synthesis, thereby potentially lowering an overall carbon footprint of the oxycombustion systems according to embodiments herein, as compared to separate combustion, ammonia synthesis, and urea synthesis systems without any thermal integration.

[0032] Having described above several embodiments of the oxycombustion systems, various embodiments of methods for performing oxycombustion with thermally integrated ammonia synthesis will now be described. In some embodiments, the methods for performing oxycombustion with thermally integrated ammonia synthesis may be performed using the oxycombustion system **1** of FIG. **1**, the integrated urea-synthesis oxycombustion system **2** of FIG. **2**, or the urea flue-gas treatment system **3** of FIG. **3** according to embodiments described above.

[0033] Referring generally to FIGS. **1–3** with regard to components of oxycombustion systems **1, 2, 3** that may be applicable to the embodiments of methods described below, the methods for performing oxycombustion with thermally integrated ammonia synthesis may include separating an air feed stream **100** with an air separation unit **10** into an oxygen stream **101** and a nitrogen stream **500**. The oxygen stream **101** may be flowed to an oxycombustion reactor **20**, and the nitrogen stream **500** may be flowed to an ammonia synthesis unit **50**. The nitrogen stream **500** in the ammonia synthesis unit **50** may be combined with a hydrogen feed stream **600** to synthesize ammonia and form a crude ammonia stream **501** containing the ammonia and, optionally, unreacted nitrogen or hydrogen. The crude ammonia stream **501** may be condensed in an ammonia separation unit **51** so as to separate the ammonia in the crude ammonia stream **501** from any unreacted nitrogen or hydrogen in the crude ammonia

stream **501** and form a purified ammonia stream **503**. The methods may further include combining a fuel from a fuel feed stream **200** with the oxygen stream **101** from the air separation unit **10** to form a fuel mixture. The fuel mixture may be combusted in the oxycombustion reactor **20** to generate combustion heat, which optionally may be transferred for direct external use or to water to produce hot water or steam. The methods may further include transferring thermal energy through at least one thermal integration while the fuel mixture is being combusted and the ammonia is being synthesized. The at least one thermal integration may be chosen from a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor, a separator thermal linkage of the air separation unit with the ammonia separation unit, or both.

[0034] The air feed stream **100** may be separated by the air separation unit **10** using any method applicable to the type of air separation unit **10** employed in the oxycombustion systems **1, 2, 3**. In exemplary embodiments, the air feed stream **100** may be separated by the air separation unit **10** by cryogenic distillation, by pressure-swing adsorption, by vacuum-swing adsorption, or a membrane technology, all of which are within the grasp of the person having ordinary skill in the art. The oxygen stream **101** may contain pure oxygen or substantially pure oxygen, such as from 80% to 100% by volume O₂ or from 90% to 100% by volume O₂ or from 90% to 99% by volume O₂, for example. Likewise, the nitrogen stream may contain pure nitrogen or substantially pure nitrogen such as from 80% to 100% by volume N₂ or from 90% to 100% by volume N₂ or from 90% to 99% by volume N₂, for example.

[0035] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include flowing the oxygen stream **101** to the oxycombustion reactor **20**. To flow the oxygen stream **101** to the oxycombustion reactor **20**, the oxygen stream **101** may be pressurized with a pump or compressor, for example.

[0036] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include flowing the nitrogen stream **500** to the ammonia synthesis unit **50**. The nitrogen stream **500** may also be pressurized with a compressor or other suitable apparatus, for example, for injection into the ammonia synthesis unit **50**.

-18-

[0037] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include combining the nitrogen stream **500** in the ammonia synthesis unit **50** with a hydrogen feed stream **600** to synthesize ammonia and form a crude ammonia stream **501** containing the ammonia and, optionally, unreacted nitrogen or hydrogen. Synthesizing the ammonia may additionally include raising the temperature of the mixture of nitrogen and hydrogen in the ammonia synthesis unit to a reaction temperature, pressurizing the mixture of nitrogen and hydrogen to a reaction pressure, or both. In general, suitable reaction pressures and reaction temperatures for ammonia synthesis may depend on a number of factors such as the configuration and construction materials of the ammonia synthesis unit **50**, and optionally, the presence or absence of any reaction modifiers such as catalysts that may be added to the ammonia synthesis unit **50**. In a non-limiting exemplary embodiment, a suitable reaction temperature for the ammonia synthesis may be from 300 °C to 550 °C, and a suitable reaction pressure for the ammonia synthesis may be from 15 MPa to 25 MPa. It should be understood that other reaction temperatures and reaction pressures may be suitable, and that the selection of such reaction temperatures and reaction pressures is well within the grasp of the skilled artisan.

[0038] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include condensing at least a portion of the crude ammonia stream **501** in the ammonia separation unit **51**. In some embodiments, only the ammonia in the crude ammonia stream **501** is condensed by cooling the crude ammonia stream to a temperature below the boiling point of ammonia, such as below -33 °C, for example. The liquefied ammonia may then be separated from the unreacted nitrogen or hydrogen to form the purified ammonia stream **503**.

[0039] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include combining a fuel from a fuel feed stream **200** with the oxygen stream **101** to form a fuel mixture, then combusting the fuel mixture in the oxycombustion reactor **20** to generate combustion heat. The fuel mixture may be formed either inside the oxycombustion reactor **20** or outside the oxycombustion reactor **20**.

[0040] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include transferring thermal energy such as heat through at least one thermal integration of the oxycombustion system **1, 2, 3** while the fuel mixture is being combusted in the oxycombustion reactor **20** and the ammonia is being synthesized in the ammonia synthesis unit **50**. The at least one thermal integration may be chosen from a reactor thermal linkage **925, 952** of the ammonia synthesis unit **50** with the oxycombustion reactor **20**, a separator thermal linkage **915, 951** of the air separation unit **10** with the ammonia separation unit **51**, or both.

[0041] In some embodiments in which the at least one thermal integration includes a reactor thermal linkage **925, 952**, the reactor thermal linkage **925, 952** may be configured as a boiler loop that transfers heat to the ammonia synthesis unit **50** from the oxycombustion reactor **20** itself (for example, from a chamber in the oxycombustion reactor **20**), from flue gas formed in the oxycombustion reactor **20**, from hot water or steam that has been heated by combustion heat from the oxycombustion reactor **20**, or a combination of any of these. The transferring of the thermal energy may then include circulating a heat transfer fluid through the boiler loop while the fuel mixture is being combusted and the ammonia is being synthesized. The heat transfer fluid for the boiler loop may be a fluid such as a gas or liquid, for example water or steam.

[0042] In some embodiments in which the at least one thermal integration includes a separator thermal linkage **915, 951** of the air separation unit **10** with the ammonia separation unit **51**, the separator thermal linkage **915, 951** may be configured as a separator loop that transfers heat to the air separation unit from the ammonia separation unit. The transferring the thermal energy may then include circulating a heat transfer fluid through the separator loop while the fuel mixture is being combusted and the ammonia is being synthesized. The heat transfer fluid for the separator loop may be a fluid, such as a gas or liquid, with an appropriate boiling point and freezing point to enable the heat transfer fluid to circulate around the separator loop freely.

[0043] In some embodiments, the at least one thermal integration may include both a reactor thermal linkage **925, 952** of the ammonia synthesis unit **50** with the

-20-

oxycombustion reactor **20** and a separator thermal linkage **915, 951** of the air separation unit **10** with the ammonia separation unit **51**. As in the embodiments described above, the reactor thermal linkage **925, 952** may be configured as a boiler loop and the separator thermal linkage **915, 951** may be configured as a separator loop. In such embodiments, the transferring of the thermal energy may include both circulating a first heat transfer fluid through the boiler loop and circulating a second heat transfer fluid through the separator loop while the fuel mixture is being combusted and the ammonia is being synthesized.

[0044] In some embodiments, the methods for performing oxycombustion with thermally integrated ammonia synthesis may further include transferring thermal energy such as heat through at least one additional thermal integration of the oxycombustion system **1, 2, 3** in addition to the reactor thermal linkage **925, 952** of the ammonia synthesis unit **50** with the oxycombustion reactor **20**, the separator thermal linkage **915, 951** of the air separation unit **10** with the ammonia separation unit **51**, or both. The at least one additional thermal integration may include an air-separator capture-unit thermal linkage **914, 941** between the air separation unit **10** and the carbon dioxide capture unit **40**, an ammonia-separator capture-unit thermal linkage **945, 954** between the ammonia separation unit **51** and the carbon dioxide capture unit **40**, a urea synthesis thermal linkage **926, 962** between the urea synthesis unit **60** and the oxycombustion boiler **20**, any combination of two of these, or all of these, each as described above with respect to the oxycombustion system **1** of FIG. 1 the integrated urea-synthesis oxycombustion system **2** of FIG. 2, or the urea flue-gas treatment system **3** of FIG. 3. The transference of thermal energy in any of these thermal integrations may include circulating a heat transfer fluid through a heat-transfer loop that serves as the respective thermal linkage.

[0045] The methods for performing oxycombustion with thermally integrated ammonia synthesis may further include treating in a flue-gas treatment system **30** a flue gas formed by the combustion of the fuel in the oxycombustion reactor **20**. The treating of the flue gas may include removing pollutants from the flue gas and may also include using at least a portion of the ammonia in the purified ammonia stream **503**, such as from the ammonia scrubbing stream **504** to remove the pollutants from the flue gas.

[0046] In some embodiments, the flue-gas treatment system **30** used to treat the flue gas formed by the combustion of the fuel in the oxycombustion reactor **20** outputs carbon dioxide. In such embodiments, the methods for performing oxycombustion with thermally integrated ammonia synthesis may further include capturing the carbon dioxide in a carbon dioxide capture unit **40** such as by cooling scrubbed flue gas from the flue-gas treatment system **30** until water present in the scrubbed flue gas condenses and the CO₂ is left in the gaseous state, for example.

[0047] In some embodiments, at least a portion of any carbon dioxide captured in the carbon dioxide capture unit **40** may be combined with the ammonia in the purified ammonia stream **503** to form a urea reactant mixture. The methods may then include synthesizing urea from the urea reactant mixture in a urea synthesis unit **60** (FIGS. **2** and **3**), for example. The methods may also include pressurizing the ammonia, the CO₂, or the urea reactant mixture to from 12 MPa to 40 MPa, for example, and heating the ammonia, the CO₂, or the urea reactant mixture to from 150 °C to 250 °C to enable the urea synthesis reaction to commence or be maintained.

[0048] In some embodiments, the methods for performing oxycombustion with thermally integrated ammonia synthesis may further include treating the flue gas in the flue-gas treatment system **30**, and treating the flue gas may include using at least a portion of the ammonia from the purified ammonia stream **503**, at least a portion of the urea in the urea recovery stream **700** (see FIG. **3**), or both, to remove the pollutants from the flue gas. In such embodiments, the flue-gas treatment system **30** may include technologies, as described above, for removing NO_x, SO_x, particulates, and other impurities with the aid of ammonia, urea, or both.

[0049] Thus, various embodiments of methods for performing oxycombustion with thermally integrated ammonia synthesis have been described. The methods may be performed using the oxycombustion system **1** of FIG. **1**, the integrated urea-synthesis oxycombustion system **2** of FIG. **2**, the urea flue-gas treatment system **3** of FIG. **3**, modifications thereof, or other suitable oxycombustion systems. These methods make efficient use not only of nitrogen and oxygen components of air to simultaneously feed

-22-

ammonia synthesis, oxycombustion, and, optionally, urea synthesis, but also in some embodiments use the ammonia and/or urea to clean flue gases that result from the oxycombustion. When ammonia and/or urea are generated in an integrated system, it is not necessary to procure the ammonia and/or urea from external sources when they are required or desired for use in scrubbing flue gas and removing pollutants from the flue gas. Additionally, by employing the systems according to embodiments herein, the methods make efficient use of thermal energy through the at least one thermal integration in the oxycombustion systems, such as a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor, a separator thermal linkage of the air separation unit with the ammonia separation unit, or both. Thermal integrations in this manner can eliminate needs in the oxycombustion systems for additional components such as refrigeration systems to condense ammonia or heaters to heat hydrogen and nitrogen in for ammonia synthesis, thereby potentially lowering an overall carbon footprint of the oxycombustion systems according to embodiments herein, as compared to separate combustion, ammonia synthesis, and urea synthesis systems without any thermal integration.

[0050] It should be apparent to those skilled in the art that various modifications and variations can be made to the embodiments described herein without departing from the spirit and scope of the claimed subject matter. Thus it is intended that the specification cover the modifications and variations of the various embodiments described herein provided such modification and variations come within the scope of the appended claims and their equivalents.

CLAIMS

1. An oxycombustion system with thermally integrated ammonia synthesis, the oxycombustion system comprising:

5 an air separation unit that separates an air feed stream into an oxygen stream and a nitrogen stream;

an ammonia synthesis unit that synthesizes ammonia from a hydrogen feed stream and the nitrogen stream from the air separation unit to form a crude ammonia stream containing the ammonia and, optionally, unreacted nitrogen and hydrogen;

10 an ammonia separation unit that condenses at least a portion of the crude ammonia stream formed in the ammonia synthesis unit and separates the ammonia from any unreacted nitrogen and hydrogen to form a purified ammonia stream;

an oxycombustion reactor that combusts a fuel from a fuel feed stream in the presence of the oxygen stream from the air separation unit to produce combustion heat;

15 a flue-gas treatment system that treats a flue gas formed by the combustion of the fuel in the oxycombustion reactor; and

thermal integrations comprising a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor and a separator thermal linkage of the air separation unit with the ammonia separation unit,

20 wherein the purified ammonia stream is in fluidic communication with the flue-gas treatment system and at least a portion of the ammonia separated in the ammonia separation unit is used in the flue-gas treatment system to remove pollutants from the flue gas.

25 2. The oxycombustion system of claim 1, wherein the reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor comprises a boiler loop that transfers combustion heat to the ammonia synthesis unit from the oxycombustion reactor, from flue gas formed in the oxycombustion reactor, from hot water or steam that has been heated from the combustion heat, or a combination thereof.

30

3. The oxycombustion system of claim 1, wherein the separator thermal linkage of the air separation unit with the ammonia separation unit comprises a

separator loop that transfers heat to the air separation unit from the ammonia separation unit.

4. The oxycombustion system of claim 1, wherein the flue-gas treatment
5 system outputs carbon dioxide, the oxycombustion system further comprising a carbon dioxide capture unit that captures the carbon dioxide generated in the flue-gas treatment system.

5. The oxycombustion system of claim 4, further comprising at least one
10 capture-unit thermal integration chosen from an air-separator capture-unit thermal linkage between the air separation unit and the carbon dioxide capture unit, an ammonia-separator capture-unit thermal linkage between the ammonia separation unit and the carbon dioxide capture unit, or both.

6. The oxycombustion system of claim 4, further comprising a urea
15 synthesis unit that synthesizes urea to produce a urea stream from carbon dioxide captured in the carbon dioxide capture unit and the ammonia in the ammonia stream.

7. The oxycombustion system of claim 6, wherein the urea stream is in
20 fluidic communication with the flue-gas treatment system and at least a portion of the urea in the urea stream is used to remove pollutants from the flue gas in the flue-gas treatment system.

8. The oxycombustion system of claim 6, further comprising at least one
25 additional thermal integration chosen from an air-separator capture-unit thermal linkage between the air separation unit and the carbon dioxide capture unit, an ammonia-separator capture-unit thermal linkage between the ammonia separation unit and the carbon dioxide capture unit, a urea synthesis thermal linkage between the urea synthesis unit and the oxycombustion reactor, or combinations thereof.

30

9. The oxycombustion system of claim 1, wherein the fuel that is
combusted in the oxycombustion reactor is a fossil fuel or a biomass.

10. A method for performing oxycombustion with thermally integrated ammonia synthesis, the method comprising:

- 5 separating an air feed stream with an air separation unit into an oxygen stream and a nitrogen stream;
- flowing the oxygen stream to an oxycombustion reactor;
- flowing the nitrogen stream to an ammonia synthesis unit;
- combining the nitrogen stream in the ammonia synthesis unit with a hydrogen feed stream to synthesize ammonia and form a crude ammonia stream containing the ammonia and, optionally, unreacted nitrogen or hydrogen;
- 10 condensing at least a portion of the crude ammonia stream in an ammonia separation unit;
- separating the ammonia in the crude ammonia stream from any unreacted nitrogen or hydrogen in the crude ammonia stream, to form a purified ammonia stream;
- 15 combining a fuel from a fuel stream with the oxygen stream to form a fuel mixture;
- combusting the fuel mixture in the oxycombustion reactor to generate combustion heat;
- and
- transferring thermal energy through thermal integrations while the fuel mixture is being combusted and the ammonia is being synthesized, the thermal
- 20 integrations comprising a reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor and a separator thermal linkage of the air separation unit with the ammonia separation unit; and
- treating in a flue-gas treatment system, a flue gas formed by the combustion of the fuel in the oxycombustion reactor to remove pollutants from the flue gas, wherein
- 25 treating the flue gas comprises using at least a portion of the ammonia in the purified ammonia stream to remove the pollutants from the flue gas.

11. The method of claim 10, wherein:

- the reactor thermal linkage of the ammonia synthesis unit with the
- 30 oxycombustion reactor comprises a boiler loop that transfers combustion heat to the ammonia synthesis unit from the oxycombustion reactor, from flue gas formed in the

oxycombustion reactor, from at least a portion of the hot water or steam formed in the oxycombustion reactor, or a combination thereof; and

transferring the thermal energy comprises circulating a heat transfer fluid through the boiler loop while the fuel mixture is being combusted and the ammonia is
5 being synthesized.

12. The method of claim 10, wherein:

the separator thermal linkage of the air separation unit with the ammonia separation unit comprises a separator loop that transfers heat to the air separation unit
10 from the ammonia separation unit; and

transferring the thermal energy comprises circulating a heat transfer fluid through the separator loop while the fuel mixture is being combusted and the ammonia is being synthesized.

15 13. The method of claim 10, wherein:

the reactor thermal linkage of the ammonia synthesis unit with the oxycombustion reactor comprises a boiler loop that transfers combustion heat to the ammonia synthesis unit from flue gas formed in the oxycombustion reactor, from hot water or steam that has been heated by the combustion heat, or a combination thereof;
20 and

the separator thermal linkage of the air separation unit with the ammonia separation unit comprises a separator loop that transfers heat to the air separation unit from the ammonia separation unit; and

transferring the thermal energy comprises circulating a first heat transfer
25 fluid through the boiler loop and circulating a second heat transfer fluid through the separator loop while the fuel mixture is being combusted and the ammonia is being synthesized.

14. The method of claim 10, wherein the treating of the flue gas in the flue-
30 gas treatment system outputs carbon dioxide, the method further comprising:

capturing the carbon dioxide in a carbon dioxide capture unit;

combining at least a portion of the carbon dioxide captured in the carbon dioxide capture unit with the ammonia in the ammonia stream to form a urea reactant mixture;

synthesizing urea from the urea reactant mixture in a urea synthesis unit.

5

15. The method of claim 14, wherein treating the flue gas in the flue-gas treatment system comprises using at least a portion of the urea in the urea stream, to remove the pollutants from the flue gas.