

FOLDABLE PERSONAL VEHICLE

TECHNOLOGICAL FIELD

The subject matter of the present application relates to foldable personal vehicles, in particular in the field of children's toys and vehicle products.

BACKGROUND

Foldable personal vehicles such as scooters, vehicles and bicycles are well known for both adults and children. For children, it may sometimes be beneficial that the vehicle can be folded for compact storing and carrying.

There are known a great variety of such foldable vehicles, centered around two basic principles: disassembly and folding. Under the first group, the vehicle is disassembled to basic parts, which can be fitted compactly together. Under the second group, most parts of the vehicle maintain their inter-connections but can assume an operational state, in which they function as a vehicle and a storage, folded state, in which the orientation and/or position of the parts changes with respect to one another.

Vehicles of the above second group are described, for example in U.S. Patent No. 6152473, U.S. Patent No. 6530589, and http://www.iimo-life.com/vehicle2_01.htm, the latter being a product sold as IIMO Folding Tricycle.

The presently disclosed subject matter refers to vehicles of the second group described above.

GENERAL DESCRIPTION

The subject matter of the present application refers to a foldable personal vehicle having an operational state and a storage state, in which it can take an extremely compact form. The vehicle has a longitudinal axis lying in its vertical plane of symmetry and having a horizontal reference plane perpendicular to the plane of symmetry, and it takes its compact form in the storage state both in the direction along its longitudinal axis and in the directions perpendicular to this axis both along the plane of symmetry and a vertical plane perpendicular to the plane of symmetry.

In accordance with a first aspect of the presently disclosed subject matter, the above vehicle can comprise:

- a body member having an upper surface holding a seat, front and rear ends spaced from each other along the longitudinal axis, a right rear side surface and a left rear side surface both disposed adjacent the rear end of the body member and spaced from each other in a direction perpendicular to the plane of symmetry;

- a front bar and a front wheel mounted thereto, the front bar being at least indirectly pivotally articulated to the body member adjacent the front end thereof to take an operational and a storage orientation;

- a right rear leg and a left rear leg each having a leg distal end with a rear wheel and a leg proximal end, at which the leg is pivotally articulated to the respective rear side surface of the body member to take an operational and a storage orientation, at least one of the legs having a connection area between the leg proximal end and the leg distal end; and

- at least one connection member connecting at least indirectly the front bar with the connection area of at least one of the legs so that pivoting the front bar between its operational and storage orientations causes the at least one connection member to pivot the rear legs along the respective rear side surface of the body member, between their respective operational and storage orientations.

Due to the pivotal articulation of the rear legs' proximal ends to the right and left rear side surfaces of the body member and the use of the above connection area/s and connection member/s for such articulation, the rear legs of the vehicle can be free of any common elements extending therebetween at locations thereon spaced from the legs' proximal ends, for pivotally connecting the legs to the body member. This allows the rear legs' pivoting angle to be so large that, in the storage state of the vehicle, they can take a position, in which at least a majority of the area of each leg overlaps with at least a majority of the area of the body member, as seen in a side view of the vehicle, thereby allowing to essentially reduce dimensions of the vehicle in this state both along the longitudinal axis of the vehicle and perpendicular to this axis along its plane of symmetry. This means that in the storage state of the vehicle each rear leg can be fully or almost fully coextensive with the body member at least along a majority of their longitudinal

dimensions, *e.g.*, each rear leg can have its distal end close to the front end of the body member to the extent that this end (not including the associated rear wheel) does not essentially protrude frontward from the front end of the body member. If in this case the front bar is of the kind that in its storage orientation the front wheel is disposed in front of the body member, at least a majority of each rear leg with the associated rear wheel, as seen in the side view of the vehicle in its storage state, can be accommodated between the body member's rear end and the front wheel, allowing thereby to essentially reduce the length of the vehicle in this state along its longitudinal axis.

In view of the above, each leg can have such shape and width relative to those of the body member that, in the storage state of the vehicle as seen in its side view, they can overlap not only along a majority of their lengths as described above but also along a majority of their heights, *i.e.* in the direction perpendicular to the longitudinal axis and along the plane of symmetry, allowing to essentially reduce the overall height of the vehicle in this direction in the storage state.

The pivotal articulation of each of the right and left rear legs of the vehicle relative to the corresponding rear side surface of the body member can be provided by means of a corresponding articulation axle having an outer portion protruding from the associated rear side surface of the body member and freely received in a through-channel formed at the proximal end of the rear leg, which extends between inner and outer side surfaces of the rear leg. The articulation axles can each be unitarily formed with the body member or fixedly mounted thereto by means of an inner portion of the axle. In any case, the outer portion of the each axle, *i.e.* its portion protruding from the associated rear side surface of the body member, can be configured to enter the channel from the inner side surface of the leg at its proximal end and fixedly engage, with its axle free end, a stopper disposed adjacent the outer side surface of the leg, so as to allow pivoting of the leg about the axle while preventing the leg from being disassembled from the axle. This can be done, for example, by the axle engagement end being configured to be threaded into a corresponding nut, which constitutes the stopper and is received within a pocket in the outer side surface of the leg at its proximal end.

Alternatively, each articulation axle can protrude from the inner side surface of the corresponding rear leg at its proximal end, being unitarily formed or fixedly mounted

thereto, and can be pivotally received within the body member at the corresponding rear side surface thereof.

The right and left articulation axles can be spaced from the plane of symmetry of the vehicle or meet thereat. In the latter case, the two articulation axles can be formed as a single axle body having a central inner portion disposed within the body member and two lateral outer portions protruding from the rear side surfaces thereof as described above.

The inner and outer portions of each of the articulation axles can be collinear and extend along a single rear pivot axis or they can be angled with respect to each other.

The articulation axles of the two rear legs, or at least their outer portions, can extend along their respective rear pivot axes at a non-zero angle therebetween, each axis intersecting the rear side surface of the body member at a respective right and left rear articulation point.

The rear pivot axes of the two legs can each form an acute angle with the reference plane when seen in the rear view of the vehicle. This can allow obtaining an increased spacing between the rear legs' distal ends in their operational orientation relative to that, which these legs would have with the pivot axes lying in a plane parallel to the reference plane.

In addition or alternatively, each of the right and left rear pivot axes can be oriented at an acute angle with respect to the plane of symmetry of the vehicle. In this case, the rear legs' pivoting about the rear pivot axes from the operational to the storage orientation can allow their distal ends to get closer to the plane of symmetry, *e.g.*, to become spaced from this plane to the same or about the same extent as their proximal ends, thereby improving the 'storage state' compactness of the vehicle in the direction perpendicular to the plane of symmetry.

In case the pivot axes form the acute angles both with the plane of symmetry and with the plane perpendicular to the plane of symmetry, the above mentioned 'storage state' compactness is achieved in spite of the increased spacing between the rear legs' distal ends in the operational state of the vehicle.

The body member can have a front body portion with its right and left front side surfaces and a rear body portion with its right and left rear side surfaces. The right and

left front side surfaces can be disposed closer to the plane of symmetry than the rear right and left side surfaces, meaning that the rear body portion can be wider than the front body portion in the direction perpendicular to the plane of symmetry.

In addition, the rear portion of the body member can have a converging configuration as seen in at least one of its plan and rear views, provided by the corresponding orientation of the right and left rear side surfaces of the rear body portion. In this case, the inner side surface of each rear leg adjacent its proximal end can be oriented in the same way as, and be coextensive with, the corresponding rear side surface of the body member, so that these surfaces can be in intimate contact with each other in both the storage and the operational state of the vehicle. For example, the orientation of each of the right and left couples of the contacting rear side surface of the body member and inner side surface of the rear leg at its proximal end can be such as to provide one or both of the above acute angles of the right and left pivot axes, in which case these axes can be perpendicular to the corresponding contacting surfaces.

The body member can be in the form of a unitary body or it can be assembled from a number of elements. For example, these elements can include right and left body halves assembled so that their rims meet at the plane of symmetry of the vehicle and so as to define therebetween an at least partially hollow interior.

The front bar can extend along a front bar axis between a front wheel end of the front bar associated with the front wheel, and a handlebar end associated with handlebars. The front bar axis can form an angle with the longitudinal axis of the vehicle in the operational orientation of the bar taken by it in the operational state of the vehicle, which is essentially greater than that in the storage orientation of the front bar taken by it in the storage state of the vehicle. Specifically, the arrangement can be such that in the storage orientation of the front bar, the front bar axis forms with the longitudinal axis an angle not greater than 25 deg., more particularly, not greater than 20 deg., and still more particularly not greater than 15 deg. Optionally, the front bar axis can be parallel or almost parallel to the longitudinal axis in the storage state of the vehicle.

The front bar can constitute a part of a front assembly, which further comprises an articulation member, by virtue of which the front bar is pivotally articulated to the front end of the body member about a front pivot axis, and which is connected to the

connection member/s. The front pivot axis can be spaced from the front bar axis so that in the operational orientation of the front bar in the operational state of the vehicle, the front bar is disposed in front of the body member, and in its storage orientation in the storage state of the vehicle, the front bar is disposed above and extends along the upper surface of the body member along at least a majority of the length of the front bar.

By virtue of the above configuration, the front bar can be so oriented in the storage state of the vehicle as to be upwardly spaced from the longitudinal axis to a distance shorter than that of the highest point of the vehicle, other than any point of the front bar itself. This highest point can be, for example, the highest point of the front wheel and/or the seat in the storage state of the vehicle.

The articulating member can have a front-bar associated portion, which embraces the front bar in a manner allowing the front bar to revolve about the front bar axis, a rear-legs associated portion, to which the at least one connection member is attached at its end opposite the end, at which it is attached to the connection area/s of the rear leg/s, and a body-member associated portion, at which the articulating member is pivotally articulated to the front end of the body member.

The at least one connection member can be made of a rigid material so that its length is maintained constant during operation of the vehicle and when the state of the vehicle is changed. More particularly, the connection member can be rigid enough to be able, when pushed by the articulating member, to push accordingly the rear legs from their storage orientation to their operational orientation. The vehicle can comprise two such connection members, right and left, each connecting the articulating member with the connection area of the respective right and left rear leg.

The vehicle can further comprise pedals detachably mountable to the front wheel or integrally assembled therewith.

The vehicle can further be configured for adjusting the position of the seat along the body member.

The vehicle can be configured for allowing its user occupying the seat, to steer the vehicle by his own or preventing the user from such steering, while allowing the vehicle to be steered from its rear via a steering handle operated by another person. In this case, the vehicle can have one or more of the following features:

- a non-integral design of the front bar, whose upper and lower portions can be locked to each other to behave as a single integral unit steerable by operating the handlebars, and unlocked from each other allowing the lower portion to be steered by a separate steering mechanism not including the upper portion, and allowing a desired functionality of the upper portion without having any influence on the steering of the lower portion;
- a front bar locking clamp for locking at least at least an upper portion the front bar to an element of the vehicle, such as *e.g.*, its securing frame, which is not movable when in the operational state of the vehicle, to prevent the possibility of rotating the front bar or its upper portion about the front bar axis by operating its handlebars;
- a foldable rear steering mechanism for use with a rotatable rear steering handle when mounted to the rear end of the body member, the mechanism connecting the handle with the front bar or at least its lower portion so that manipulation of the handle causes the front bar or its lower portion to rotate about the front bar axis for steering the vehicle;
- a footrest fixedly mountable at least indirectly to the body member at a location closer to the seat than the front wheel; this location can be at the articulating member, more particularly at its body-member associated portion or its rear-legs associated portion or between these two portions; the footrest can be constituted by the above pedals, when detached from the front wheel.

The vehicle can have a steering mechanism of any design allowing the front bar lower portion to be pivoted between its operational and storage orientations. According to one example of such design, the steering mechanism can comprise the following elements:

- a front rotation member fixedly mounted to the front bar;
- a rear rotatable port located at the rear end of the body member and configured for fixedly receiving therein the rear steering handle so that rotation of the handle about the handle axis causes the port to rotate accordingly; and
- at least one pair of cable sections including a right cable section and a left cable section, each extending between the front rotation member and the port and being

so connected thereto that rotation of the port in different directions causes it to pull the left or right section and such pulling yields the rotational movement of the front rotation member and subsequently at least a lower portion of the front bar, wherein the right and left cable sections are configured for bending at a location thereof disposed in the vicinity of the front pivot axis.

The right and left cable sections can extend along and within the body member of the vehicle along a majority of their length. The right and left cable sections can be parts of one cable fixedly attached to the front rotation member and to the rotation port.

In accordance with another aspect of the subject matter of the present application, the vehicle generally described in the first paragraph of the GENERAL DESCRIPTION section, can comprise:

- a body member having an upper surface holding a seat, front and rear ends spaced from each other along the longitudinal axis, a right rear side surface and a left rear side surface both disposed adjacent the rear end of the body member and spaced from each other in a direction perpendicular to the plane of symmetry;

- a front bar and a front wheel mounted thereto, the front bar being at least indirectly pivotally articulated to the body member adjacent its front end, to take operational and storage orientations;

- a right rear leg and a left rear leg each having a leg proximal end and a leg distal end to which a rear wheel is mounted;

- a right and a left rear pivot axis, about which the corresponding right or left rear leg is pivotally articulated to the respective rear side surface of the body member to take an operational and a storage orientation, each of the rear pivot axes being oriented at an acute angle to the plane of symmetry of the vehicle in its plan view so that the rear legs' pivoting about the rear pivot axes from their operational to their storage orientation allows their distal ends to get closer to the plane of symmetry, *e.g.*, to become spaced from this plane to a lesser extent in their storage orientation than in their operational orientation, and, optionally, become spaced from this plane to the same or about the same extent as their proximal ends.

The vehicle in accordance with this aspect of the presently disclosed subject matter can have any of the features specified above with respect to the previously described aspect of the presently disclosed subject matter in any combination thereof.

In accordance with a further aspect of the subject matter of the present application, the vehicle generally described in the first paragraph of the GENERAL DESCRIPTION section, can comprise:

- a body member comprising an upper surface holding a seat, front and rear ends spaced from each other along the longitudinal axis, a right rear side surface and a left rear side surface both disposed adjacent the rear end of the body member and spaced from each other in a direction perpendicular to the plane of symmetry;

- a front bar and a front wheel mounted thereto, the front bar being at least indirectly pivotally articulated to the body member adjacent its front end to take operational and storage orientations;

- a right rear leg and a left rear leg each having a leg proximal end and a leg distal end to which a rear wheel is mounted;

- a right and a left rear pivot axis, about which the corresponding right or left rear leg is pivotally articulated to the respective rear side surface of the body member to take operational and storage orientations, each of the rear pivot axes being oriented at an acute angle with respect to the reference plane in the vehicle's rear view, so as to obtain an increased spacing between the rear legs' distal ends in their operational orientation relative to that, which the legs would have with the pivot axes lying in a plane parallel to the reference plane.

The vehicle in accordance with this aspect of the presently disclosed subject matter can have any of the features specified above with respect to the previously described aspects of the presently disclosed subject matter, in any combination thereof.

In accordance with yet another aspect of the subject matter of the present application matter, the vehicle generally described in the first paragraph of the GENERAL DESCRIPTION section, can comprise:

- a body member having a front portion and a rear portion;

- a front bar pivotally articulated at least indirectly to the front portion of the body via a front pivot axis and holding a front wheel of the vehicle, so as to be pivoted between its operational orientation and storage orientations;
- two rear legs each pivotally articulated to the rear portion of the body via a rear pivot axis to take operational and storage orientations, and holding a rear wheel of the vehicle;
- a rotatable rear steering port configured to fixedly receive therein a rear steering handle for using said handle when the vehicle is in its operational state;
- a steering mechanism connecting said port with the front bar so that rotation of the port by the handle causes at least a lower portion of the front bar to rotate for steering the vehicle when in its operational state, the steering mechanism comprising at least one steering element extending at least partially within the body member and configured to be bent in the vicinity of the front pivot axis, when the front bar is pivoted from its operational orientation to its storage orientation.

The steering mechanism can further comprise a front rotation member fixedly mounted to the front bar, and a pair of bendable right and left cable sections constituting the steering elements, each extending between the front rotation member and the port and so connected thereto that rotation of the port clockwise or counterclockwise causes the port to pull the respective right or left section, and such pulling yields the rotational movement of the front rotation member and subsequently of the front bar. The right and left cable sections can extend along a majority of their length within the body member and are each configured to be bent in the vicinity of the front pivot axis.

The vehicle in accordance with this aspect of the presently disclosed subject matter can have any of the features specified above with respect to the previously described aspects of the presently disclosed subject matter, in any combination thereof.

According to a still further aspect of the presently disclosed subject matter, the vehicle generally described in the first paragraph of the GENERAL DESCRIPTION section, can be convertible into a stroller configured for preventing the child, when desired, from being able to steer the vehicle, the vehicle comprising

- a body member having a front portion and a rear portion;

- a front bar pivotally articulated at least indirectly to the front portion of the body via a front pivot axis so as to be pivoted between its operational orientation and storage orientations, and holding a front wheel of the vehicle to which a pair of pedals can be or are mounted;

- two rear legs each pivotally articulated to the rear portion of the body via a rear pivot axis to take operational and storage orientations, and holding a rear wheel of the vehicle;

the vehicle further having any one, any two, any three or all of the following features:

- a non-integral design of the front bar, whose upper and lower portions can be locked to each other to behave as a single integral unit steerable by operating the handlebars, and unlocked from each other allowing the lower portion to be steered by a separate steering mechanism not including the upper portion, and allowing a desired functionality of the upper portion without having any influence on the steering of the lower portion;
- a front bar locking clamp for locking at least an upper portion of the front bar to an element of the vehicle, such as *e.g.*, its securing frame, which is not movable when in the operational state of the vehicle, to prevent the possibility of rotating the front bar or its upper portion about the front bar axis by operating its handlebars;
- a foldable rear steering mechanism for use with a rotatable rear steering handle when mounted to the rear end of the body member, the mechanism connecting the handle with the front bar so that manipulation of the handle causes at least a lower portion of the front bar to rotate about the front bar axis for steering the vehicle; and
- a footrest fixedly mountable at least indirectly to the body member at a location closer to the seat than the front wheel; this location can be at the articulating member, more particularly at its body-member associated portion or its rear-legs associated portion or between these two portions; the footrest can be constituted by pedals, when detached from the front wheel.

The vehicle in accordance with this aspect of the presently disclosed subject matter can have any of the features specified above with respect to the previously described aspects of the presently disclosed subject matter, in any combination thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, embodiments will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1A is schematic perspective view of a foldable tricycle in accordance with one embodiment of the subject matter of the present application, shown in an operational state thereof;

Fig. 1B is another schematic perspective view of the tricycle shown in Fig. 1A, with its seat arrangement being removed;

Figs. 1C and **1D** are respective schematic side and front views of the tricycle shown in Fig. 1A;

Fig. 1E and **1F** are respective schematic plan and rear views of the tricycle shown in Figs. 1A to 1E;

Fig. 1G is the same plan view of the tricycle as in Fig. 1E but without its seat and securing frame;

Fig. 1H is the same perspective view of the tricycle as in Fig. 1B, with its rear legs being disassembled;

Figs. 2A to **2E** schematically illustrate the process of folding a tricycle as shown in Figs. 1A to 1E for bringing it from the operational state shown in Fig. 2A into its storage state shown in Fig. 2E; and

Fig. 3A is a schematic plan view of the tricycle shown in Fig. 2E;

Fig. 3B is a schematic plan view of the a body member and rear legs of the tricycle shown in Fig. 3A;

Fig. 3C is a schematic side view of the tricycle shown in Fig. 2E; and

Fig. 3D is the same view of the tricycle as shown in Fig. 3C, but without its right rear leg and wheel;

Fig. 3E is the same view of the tricycle as shown in Fig. 3C, but without its front assembly and its rear wheels;

Figs. 4A and **4B** are perspective and side views, respectively, of a foldable tricycle according to another embodiment of the presently disclosed subject matter;

Figs. 5A and **5B** are respective perspective and partially exploded schematic views of a foldable tricycle according to a still further embodiment of the presently disclosed subject matter; and

Fig. 5C is a perspective view of the tricycle shown in Fig. 5A with its pedals constituting a footrest.

DETAILED DESCRIPTION OF EMBODIMENTS

The drawings listed above illustrate a number of tricycles for kids, each referred to throughout the specification as a 'vehicle', including a vehicle **1** illustrated in Figs. 1A to 3E, a vehicle **100** illustrated in Figs. 4A and 4B and vehicle **200** illustrated in Figs. 5A to 5C. Each of the vehicles **1**, **100** and **200** has a longitudinal axis **L** lying in a symmetry plane **SP** of the vehicle, and is foldable between its

- operational state, in which the vehicle can be ridden along a plane perpendicular to the plane of symmetry and referred to in the present specification as a reference plane **RP**, and

- storage state, in which the vehicle can be freely laid on the reference plane **RP** so that its longitudinal axis **L** forms an angle **LR** with that plane, not exceeding or at least not essentially exceeding that formed between them in the operational state of the vehicle.

The longitudinal axis, the plane of symmetry, the reference plane and the storage state of the vehicle are shown in the drawings only with respect to the vehicle **1**, the description of the vehicle **1** being fully applicable to the vehicles **100** and **200**.

Referring to Fig. 1A, the vehicle **1** comprises a rigid body member **10**, a seat arrangement **30**, a front assembly **50** with a front wheel **W_F** having pedals **P**, right and left rear legs **70_R** and **70_L** with respective rear wheels **W_{RR}** and **W_{RL}**, and a connection mechanism **90**. Since the rear legs and their rear wheels have identical design, they are designated in Figures other than Fig. 1A by a single reference numeral **70** and their wheels are designated hereinafter as **W_R**.

Referring to Figs. 1B and 1G, the body member **10** comprises a front body portion **11_F** including a front body end **12_F** and a rear body portion **11_R** including a rear body end **12_R**, the front and rear portions having fixed mutual disposition in both operational and storage state of the vehicle. The body member can be in the form of a unitary body or rather it can be assembled of a number of elements.

As seen in Fig. 1B, the body member **10** comprises an upper surface **13** facing upwardly or away from the reference plane **RP**, a lower surface **14** facing downwardly or towards the reference plane **RP**, right and left front side surfaces **15_F** extending between front portions of the upper and lower surfaces of the body member and defining the front body portion **11_F**, and right and left rear side surfaces **15_R** extending between rear portions of the upper and lower surfaces of the body member and defining the rear body portion **11_R**, to which the rear legs **70** are pivotally articulated. As best seen in Fig. 1G, the right and left front side surfaces **15_F** of the body member **10** are closer to the plane of symmetry **SP** than the rear right and left side surfaces **15_R**, meaning that the rear body portion **11_R** is wider than the front body portion **11_F** in the direction perpendicular to the plane of symmetry **SP**.

As best seen in Figs. 1A and 1C, the seat arrangement **30** comprises a seat **32**, which is mounted to the upper surface **13** of the body member **10** so as to be supported at least partially by the rear body portion **11_R**. The seat arrangement can be configured for being mounted at one of at least two different positions along the body member, with different extent, to which the upper surface of the rear body portion **11_R** is covered by the seat's area.

The seat arrangement **30** further comprises a backrest **34** having a stationary backrest portion **35** integrally assembled or unitarily formed with the seat **32**, and a foldable backrest portion **37**. The backrest portion **37** is pivotable about an axis **X_{BR}**, which is parallel to the reference plane **RP** and is spaced from the seat **32** by the stationary seat portion **35**, between a generally upright orientation of the backrest portion **37** in the operational state of the vehicle **1** and generally horizontal orientation of the backrest portion **37** in the storage state of the vehicle. In addition, the backrest portion can be configured to take at least two different upright positions to allow choosing a more convenient support to the back of a rider/user in the operational state of the vehicle.

The seat arrangement **30** further comprises an optional securing frame **36**, which in the present example can be pivotal about the same axis X_{BR} as the pivotal backrest portion **37** between its generally horizontal operational orientation, in which it can prevent a child seated in the seat **32** from falling off the vehicle **1** and a generally vertical non-operational orientation used in the process of folding the vehicle. The securing frame can be configured for being detachably attachable to the vehicle.

The seat can be formed without the stationary portion and/or the securing frame, and the foldable backrest portion can have different axes, about which they can be pivoted, with the pivotal axis of the backrest being disposed closer to the seat than that of the securing frame in the operational state of the vehicle. The backrest can be made of a rigid material or it can be in the form of a fabric casing configured to be dressed on a backrest frame (not shown), which can be permanently pivotally mounted to the seat, or can be detachably attachable to the seat, when needed to bring the vehicle into its operational state.

The shape of the rear body portion **11R** and manner, in which the rear legs **70** are pivotally articulated thereto, will now be described in more detail with reference to Figs. 1B, 1F, 1G and 1H.

The rear body portion **11R** has a converging configuration as seen in its plan view (Fig. 1G) and rear view (Fig. 1F), due to the corresponding orientation of the right and left rear side surfaces **15R**. More particularly, these surfaces **15R** are so inclined as to become closer to each other in the direction away from the rear body end **12R** (Fig. 1G) and in the direction away from the reference plane **RP** (Fig. 1F).

Referring to Fig. 1H, the rear side surfaces **15R** of the body member **10** are each provided with an articulation axle **16** fixedly mounted to the rear body portion **11R** (only the right axle being seen) so that its outer portion **18** with its free end **19** protrudes from the rear side surface for holding thereon the corresponding rear leg **70**. Each outer portion **18** of the articulation axle **16** extends along a corresponding pivot axis X_{RP} oriented perpendicularly to the associated rear side surface **15R** and intersecting this surface at a rear articulation point **P_{RA}** (only one such point being seen). The rear articulation points **P_{RA}** of the two, right and left, rear side surfaces **15R** can be located so that an imaginary line connecting them intersects the longitudinal axis **L** of the vehicle (not shown).

The rear side surfaces **15R** are oriented so that the rear axes **X_{RP}**, which are perpendicular thereto, form desired angles with the reference plane **RP**. More particularly, as seen in Fig.1F, the rear pivot axes **X_{RP}** each form an acute angle α with the reference plane **RP**. This allows obtaining an increased spacing **S** between the rear legs' distal ends in their operational orientation, relative to that which the same legs would have with their pivot axes **X_{RP}** lying in the plane parallel to the reference plane **RP**. In addition, as seen in Fig. 1G, each pivot axis **X_{RP}** is oriented at an acute angle β with respect to the plane of symmetry **SP** of the vehicle. This ensures that the rear legs' pivoting about the rear pivot axes **X_{RP}** from the operational to the storage orientation results in their distal ends to get closer to the plane of symmetry so as to become spaced from this plane to the same or about the same extent as their proximal ends, despite the above increased spacing. Moreover, in fact, due to the above angle β the distal ends of the rear legs in the storage orientation of the legs can even get closer to each other than their proximal ends, thereby improving the 'storage state' compactness of the vehicle in the direction perpendicular to the plane of symmetry, as explained in more detail below with reference to Figs. 3A and 3B.

Referring to Figs. 1B, 1G and 1H, each of the rear legs **70** has an elongated body **72** with a proximal end **74**, a distal end **76** carrying the rear wheel **W_R**, and a connection area **78** (only one seen in Figs. 1B and 1H) between the leg proximal end and the leg distal end, associated with the connection mechanism **90** (better seen in Fig. 1A). Each rear leg **70** further comprises a rear leg outer surface **75** facing away from the body member and a rear leg inner surface **77** facing in the direction of the body member and comprising the connection area **78**.

Each of the rear legs **70** is formed, adjacent its proximal end, with a through channel **79**, which extends between inner and outer side surfaces **77** and **75** of the rear leg and is configured to receive therein from the inner side surface of the leg the outer portion **18** of the articulation axle **16** and from the outer side surface a stopper (not shown) configured to fixedly engage the free end **19** of the axle **16** so as to allow pivoting of the leg about the axle while preventing the leg from being disassembled from the axle.

Each rear leg inner surface **77** at the proximal end of the leg is oriented in the same manner as, and is coextensive with, the corresponding rear side surface **15R** of the

body member **10** so that these surfaces can be in intimate contact with each other in both storage and operational states of the vehicle.

In the operational state of the vehicle, the legs **70** have an operational orientation, in which the rear wheels **W_R** are disposed at a maximal distance from the front wheel **W_F** along the plane **RP**. The rear wheels **W_R** have their wheel axes **X_{WR}** that are collinear with one another in the operational orientation of the rear legs **70**, allowing the two rear wheels **W_R** to travel functionally together being parallel to each other in the state of the vehicle **1**.

Referring to Fig. 1D, the front assembly **50** comprises a front bar **52** extending along a front bar axis **X_{FB}** lying in the plane of symmetry **SP**, and having a wheel end **52A** associated with the front wheel **W_F** and a handlebar end **52B** associated with handlebars **57**. The front bar **52** with its handlebars **57** can be configured for being revolved about the front bar axis **X_{FB}** for steering the vehicle **1**. In the operational orientation of the front bar **52**, its handlebar end **52B** is disposed at a maximal distance from the reference plane **RP**.

Referring to Fig. 1E, the handlebars **57** in their operational orientation have handle portions **58** extending generally transversely to the plane of symmetry **SP** of the vehicle so that their ends are spaced from the front bar **52** and from the plane **SP** to a maximal extent, and they are each rotatable about a handle bar axis **X_{HB}**, which extends generally parallel to the plane **SP** so that in the storage orientation of the handle portions **58** their ends can be spaced from the plane of symmetry **SP** to a minimal extent.

The wheel end **52A** of the front bar **52** is formed with a fork **54** rotatably holding the front wheel **W_F**. The pedals **P** are each held by a corresponding pedal axle **53** mounted to the front wheel through an opening in the fork **54**, via which it passes freely. Each pedal can be configured to revolve between an operational orientation, in which it is oriented transversely to its axle **53**, and a storage orientation in which it is aligned with this axle. The pedals with their axles can be detachable from the front wheel.

Referring to Fig. 1C, the front assembly **50** further comprises an articulating member **60** for pivotal articulation of the front bar **52** to the front end **12_F** of the body member **10** about a front pivot axis **X_{FP}**, which is perpendicular to the plane of symmetry **SP** (and parallel to the reference plane **RP**) and which meets each side **15** of the front

portion of the body member **10** at a front articulation point **P_F**. The front pivot axis **X_{FP}** crosses the longitudinal axis **L** of the vehicle.

The articulating member **60** comprises a body-member associated portion **62**, which is pivotally connected to the front portion of the body member about the front pivot axis **X_{FP}**, a front-bar associated portion **64** connected to the front bar **52** along a section thereof disposed between the two ends of the front bar, and a rear-legs associated portion **66** constituting a part of the connection mechanism **90**. The front-bar associated portion **64** and the rear-legs associated portion **66** are formed so that, in an operational orientation of the articulating member **60**, the front-bar associated portion **64** is disposed in front of the body-member associated portion **62**, and the rear-legs associated portion **66** is disposed closer to the reference plane **RP** than the body-member associated portion **62**. In the described example, where the front bar **52** is configured for revolving about the front bar axis **X_{FB}**, the front-bar associated portion **64** is in the form of a sleeve receiving therein the front bar **52** in a manner allowing its revolution within the sleeve.

The articulating member **60** can be provided with a locking arrangement comprising a button **61**, ensuring that the articulating member **60** is locked to the body member **10** at least in the operational state of the vehicle and is unlocked therefrom by pressing the button **61** only when it is desired to change the state of the vehicle and pivot the articulating member **60** about the front pivot axis **X_{FP}**.

Referring to Figs. 1A, 1F and 1H, the articulating member **60** connects the front bar **52** with the connection areas **78** of the legs **70** by means of two longitudinal connection elements or bars **92**, each having a front connection end **92A** attached to one side of the rear-legs associated portion **66** of the articulating member **60** so as to enable pivoting of the connection element **92** with respect to the rear-legs associated portion **66** about a front connection axis **X_{FC}**, and a rear connection end **92B** attached to the connection area **78** of one of the legs **70** so as to enable pivoting the connection element **92** with respect to the rear leg **70** about a rear connection axis **X_{RC}**. The connection elements **92** are made of a rigid material so that their dimensions are maintained unchanged during their operation.

Reference is now made to Figs. 2A to 2E, illustrating the process of folding the vehicle **1** in order to bring it from its operational state shown in Figs. 1A to 1F and also

in Fig. 2A, to its storage state shown in Figs. 2E, 3A and 3C. The vehicle is shown in Figs. 1A to 1F and 2A in its operational state, in which it can be ridden along a plane, *i.e.* reference plane **RP** (shown in Fig. 1F), and in Figs. 2E, 3A and 3B in its storage state, in which it can be freely laid on such plane so that its longitudinal axis forms an angle with that plane, which does not exceed that formed between them in the operational state. This process is described below with reference to the axes, about which elements of the vehicle **1** are to be pivoted/revolved when bringing them from their operational into their storage orientation, and with reference to Fig. 2A, these axes are as follows:

- the handlebars axes **X_{HB}**, about which the handlebars **57** are rotated from their operational orientation shown in Fig. 2A, in which the handle portions **58** of the handlebars are disposed at their maximal distance from the front bar **52** and from the plane of symmetry **SP**, into their storage orientation shown in Fig. 2B, in which the handle portions **58** of the handlebars are disposed at their minimal distance from the front bar **52** and from the plane of symmetry **SP**;

- the backrest axis **X_{BR}**, about which

- (a) the securing frame **36** is rotated between its operational orientation shown in Fig. 2A, which also constitutes its storage orientation shown in Fig. 2E and in which it forms with the reference plane **RP** a minimal angle, and its upright orientation shown in Fig. 2B, in which it forms with the reference plane **RP** a maximal angle; and

- (b) the backrest portion **37** is rotated from its operational, generally vertical, orientation shown in Fig. 2A, in which this portion forms with the reference plane a maximal angle, into its storage, generally horizontal orientation shown in Fig. 2E, in which it forms with the reference plane a minimal angle;

- the front pivot axis **X_{FP}**, about which the front bar **52** is pivoted by the articulating member **60** clockwise (CW) between its operational orientation shown in Fig. 2A, in which it forms a maximal angle with the longitudinal axis **L** and with the reference plane **RP**, into its storage orientation shown in Fig. 2D, in which it forms a minimal angle with the longitudinal axis **L** and with the reference plane **RP**; Fig. 2C shows an

intermediate orientation of the front bar **52** taken by it during the above pivoting movement prior to its reaching the storage orientation;

- the rear pivot axes X_{RP} (of which only one such axis is seen), about which the rear legs **70** are pivoted, when pulled by the articulating member **60** via the corresponding connection elements **92**, from the operational orientation of the rear legs shown in Fig. 2A, in which the rear wheels are spaced to a maximal extent from the front wheel W_F , into the storage orientation of the leg shown in Fig. 2E, in which the rear wheels W_R are spaced to a minimal extent from the front wheel W_F ; since the front bar **52** and the rear legs **70** are connected to one another by the connection mechanism **90**, the CW revolution of the front bar about the front pivot axis X_{FP} entails a similar CW revolution of each of the rear legs about their respective axes X_{RP} ;

- the front connection axis X_{FC} , about which each connection element **92** is pivoted relative to the articulating member **60**; and

- the rear connection axis X_{RC} (not seen in Figs. 2A to 2E), about which each connection element **92** is pivoted relative to the rear leg **70**, when the front bar and the rear legs are pivoted as described above.

Thus, when the vehicle **1** is folded from its operational state into its storage state, first its handlebars are brought into their storage orientation and the securing frame is brought into its upright orientation as shown in Fig. 2B, then the front bar and the rear legs are pivoted into their storage orientation, as shown in Figs. 2C and 2D; then the backrest is pivoted into its storage orientation and, simultaneously or subsequently, the securing frame is pivoted into its horizontal orientation, as shown in Fig. 2E. In addition, the pedals **P** are folded in order to conserve space in the folded state of the vehicle. The vehicle can then be returned into its operational state by performing the above steps in the reversed order.

Referring to Fig. 3B, owing to the angle 2β between the rear pivot axes X_{RP} , revolution of the legs **70** about these axes brings their distal ends **76** closer to the plane of symmetry **SP** than their proximal ends, allowing a compact configuration of the vehicle **1** in the storage state thereof such that its lateral extension T_F at the area of the front end of the body member cannot exceed or at least not essentially exceed its lateral extension T_R at the area of the rear end of the body member (Fig. 3A). It is also appreciated that in

the storage state of the vehicle **1**, the rear wheel axes X_{WR} become angled to one another as clearly seen in Fig. 3A.

Referring to Fig. 3A and 3E, owing to the fact that each of the rear legs is individually articulated to the corresponding side of the rear portion of the body member, the angle of pivoting of the legs from their operational to their storage orientation, is so large that in its storage orientation each rear leg has its distal end close to the front end of the body member and it does not protrude essentially frontward from this end. Consequently, as seen in Fig. 3C, in the storage state of the vehicle as seen in its side view, each rear leg and the associated rear wheel are accommodated mainly between the body member's rear end and the front wheel, allowing thereby reducing the length of the vehicle in this state along the reference plane.

Furthermore, referring to Fig. 3E, each rear leg **70** has such shape and width relative to those of the body member **10** that, in the storage state of the vehicle, they can overlap in the side view of the vehicle not only along a majority of their lengths as described above but also along a majority of their heights, allowing the legs **70** not to protrude downwardly from the body member in the storage state of the vehicle.

Referring to Fig. 3D, it is noted that, since the front bar axis X_{FB} does not coincide with the front pivot axis X_{FP} , *i.e.* the bar **52** is at an offset **OS** with respect to the front pivot axis X_{FP} owing to the articulating member **60**, the rotational movement performed by the bar **52** allows positioning it, in the storage state of the vehicle, so that its axis X_{FB} forms an extremely small angle γ with the longitudinal axis **L** and so that its handlebar end **52B** is located above the seat **32** while being positioned so low as to be spaced from the reference plane **RP** to a distance, which at least does not exceed that between the reference plane **RP** and the highest point of the front wheel **WF**. In the present example, the above design allows the foldable backrest portion **37** to close on the handlebar end **52B** from above.

Furthermore, as seen in Fig. 3D, in the storage state of the vehicle, the front wheel **WF** and the rear wheels **WR** (only the left one being shown) do not protrude downwardly from the bottom surface **14** of the body member **10**.

Turning now to Figs. 4A and 4B, a vehicle is shown, generally designated **100**, which is configured for being used both as a vehicle which can be ridden by a child alone

and as a stroller with its entire front bar **52** being steerable by another person, *e.g.*, an adult, from the rear of the vehicle. The components of the vehicle **100** that are the same as those in the previously described vehicle **1**, are designated by the same reference numerals. In addition, the vehicle **100** has a rear steering handle **80** and a rear steering mechanism for converting the rotational movement of the handle **80** into that of the front bar **52**.

In particular, the steering mechanism comprises a front rotation member **86** (schematically shown in dotted lines in Fig. 4B) fixedly attached to the front bar **52** and configured for revolving therewith, a rear port **87** disposed within the body member rear portion and configured to be revolved by the steering handle **80**, and a pair of right and left steering cable sections **84** extending therebetween within the body member **10**, as also shown schematically in dotted lines in Fig. 4B, and fixedly attached with their one end to the front member **86** at two diametrically opposite sides thereof and with their other end to the rear port **87** at its respective diametrically opposite sides.

The arrangement is such that, owing to the fixed attachment of the cable sections **84** to the front member **86** and the rear port **87**, pulling on one of the cable sections **84** will cause revolution of the front piece **86** about the longitudinal axis X_{FB} of the front bar **52**, thereby causing the front bar **52** to revolve, allowing steering of the vehicle.

The cables sections are made of a bendable material, which can be of the same kind as used for bicycle break cables, allowing them to bend adjacent the front pivot axis X_{FP} when the vehicle **100** is folded from its operational state into its storage state.

Fig. 5A illustrates a vehicle **200**, which can also be used as a vehicle configured for being ridden by a child on his own, or as a stroller to be steered via a rear steering handle (not shown) operated by another person. The vehicle **200** generally has the same components as those of the previously described vehicles **1** and **100**, with the difference being in that with respect to some of these components of the vehicle **200**, more details are provided in Fig. 5B regarding one specific manner, in which they can be implemented. It should be understood however that these components can be generally implemented in other manners. Moreover, Fig. 5B should not be considered as presenting all details of the these components but rather only those described below and designated by reference numerals corresponding to the reference numerals used in the description of the vehicles

1 and **100** with the addition of **200**. It should also be noted that Fig. 5B does not show standard or obvious structural elements. It should also be understood that most elements that are shown in this figure in an exploded manner relate to the right side of the vehicle **200** (which is best seen in Figs. 5A and 5B), which is a mirror image of the left side of the vehicle **200** so, if not indicated otherwise, the same elements as shown for the right side of the vehicle are also present in its left side.

Thus, the vehicle **200** comprises a hollow housing having right and left housing parts **210**, each comprising front and rear outer surfaces **215_F** and **215_R** (seen only in the right housing part **210**), and front and rear inner surfaces **215'_F** and **215'_R** (both seen only in the left housing part **210** in Fig. 5B). When the housing parts **210** are assembled along their rims as shown in Fig. 5A, they constitute a body member **210**, with the front side surfaces **215_F** of the two housing parts defining therebetween a body member front portion **211_F** and the rear side surfaces **215_R** of the two housing parts defining therebetween a body member rear portion **211_R**. In the present example, the front and rear body portions are spaced from each other by a body member intermediate portion **211_{Int}**, whose outer and inner surfaces (not designated) are disposed between the respective front and rear side surfaces **215_F** and **215_R**, and front and rear inner surface **215'_F** and **215'_R**, respectively.

With reference to the right housing part **210** and left rear leg **270** as seen in Fig. 5B, the rear outer surfaces **215_R** of the two housing parts each belong to a protrusion **217** constituting a part of the body member rear portion **211_R** formed so that this surface is oriented as described above with reference to the rear surfaces **15_R** of the vehicle **1**. Each protrusion **217** fixedly holds an articulation axle **216** having an outer portion **218** oriented perpendicularly to its rear outer surface **215_R** and having a free end **219**.

Referring to the right and left legs **270** in Fig. 5B, each has a rear leg outer surface **275** and a rear leg inner surface **277** and has a through channel **279** extending therebetween and configured to receive therein from the inner side surface **277** of the leg the outer portion **218** of the articulation axle **216** and from the outer side surface **275** of the leg a stopper **310** configured to be received in a pocket **312**, at which the channel **279** terminates, and to fixedly engage the free end **219** of the axle **216** so as to allow pivoting of the leg about the axle while preventing the leg from being disassembled from the axle.

With further reference to the left rear leg **270** in Fig. 5B, each rear leg comprises, at its inner side surface **277**, a connection area **278**, which in the present example is in the form of a pin protruding therefrom and configured for connecting thereto one of the two longitudinal connection bars **292**, with its rear connection end **292B** so as to enable pivoting of the connection bar **292** with respect to the rear leg **270**. Each connection bar **292** further has front connection end **292A** attached to an articulating member **260**, which constitutes a part of the front assembly **250**.

As shown in Fig. 5B, the articulating member **260** comprises:

- a rear-legs associated portion **266** constituting a part of a connection mechanism **290** (not designated) and having two sides, to which the two connection bars **292** are pivotally connected with their front connection end **292A**;
- a body-member associated portion **262**, which is pivotally connected to the front body portion **211F** (seen in Fig. 5A); and
- a front-bar associated portion **264** rotatably receiving therein a lower portion **252A** of the front bar **252** so that an upper portion **252B** of the front bar is free of direct connection to the articulating member.

The upper and lower portions **252A** and **252B** of the front bar **252** are assembled with each other so that, when locked to each other by a locker **320** (seen in both Figs. 5A and 5B), they are fixedly connected to each other to constitute a single integral front bar unit and, when unlocked from each other, they become functionally disconnected, allowing the lower portion to be steered by a rear steering mechanism described in detail below, and allowing the upper portion to either have a fixed orientation or to be rotatable independently from the lower portion.

As further shown in Fig. 5B, the vehicle **200** is provided with a right and a left locking mechanism for locking the articulating member **260** in its operational orientation, both locking mechanisms operating along the front pivot axis **X_{FP}**, each comprising:

- a spring-loaded locking element **265** having a pattern of protrusions along its circumference (the spring being separately designated at **267**);
- a locking cavity **268** formed at the front inner surface **215F'** of the corresponding housing part **210** (seen in the left housing part in Fig. 5B) and having a circumferential pattern of recesses corresponding to the pattern of protrusions of

the locking element so as to enable the locking cavity to fittingly receive therein the spring loaded locking element **265** in its operational orientation;

- an articulation cavity **271** formed in the body-member associated portion **262** of the articulation member **260** at its side facing the corresponding housing part, and having a circumferential pattern of recesses corresponding to the pattern of protrusions of the locking element **265**; the articulation cavity **271** permanently receives therein the spring **267** and the locking element **265** and is configured to allow the locking element to enter deeper into the articulation cavity when an axial pressing force is exerted thereon and the spring is pressed accordingly;
- a button **261** having prongs **281** and correspondingly shaped through passages **283** formed in the housing part **210** so as to extend between its inner and outer front surfaces **215_F'** and **215_F** thereof, the through passages being configured to receive therein the prongs **281** of the button both when the button is in its outermost position in the operational and storage states of the vehicle **200**, and when it is pressed into its innermost position for exerting, by its prongs **281**, the axial pressing force on the spring-loaded locking element **265**; and
- a cover **299** covering the body-member associated portion **262** and the front-bar associated portion **264** of the articulating member **260** and having an opening **285** for accommodating therein the button **261** so as to allow access thereto by the user for pressing the button, when needed.

Thus, in the operational state of the vehicle **200**, the spring-loaded locking elements **265** are in their locking position, each being accommodated in the locking cavity **268** and protruding into the articulation cavity **271** to a minimal extent. When the state of the vehicle **200** is to be changed from its operational state to its storage state, the right and left locking mechanisms are operated simultaneously to unlock the articulating member **260** and to thereby allow its pivoting about the front pivot axis **X_{FP}** from its operational orientation to its storage orientation as described above with reference to the vehicle **1**.

The unlocking is initiated by pressing the right and left buttons **261**, and thereby causing the prongs **282** to exert the axial pressing force on the locking elements **265** causing them to move out of the locking cavity **268** into the articulation cavity **271** to a

maximal extent. In this unlocking position, the locking elements **265** can no longer prevent the articulating member **260** from being pivoted with respect to the body member **210**, and they pivot together with the articulating member **260** and stay so engaged until the articulating member **260** with the locking elements **265** is pivoted back into its operational orientation, thereby bringing the locking elements into alignment with the locking cavities **268**. When this alignment is achieved, each locking element **265** is pushed by its corresponding spring **267** back into its locking position within the locking cavity **268**.

The vehicle **200** further comprises a rear steering mechanism for use with the handle **80** (not shown in Figs. 5A and 5B) as described with respect to the vehicle **100** shown in Figs. 4A and 4B, converting the pivotal movement of the handle into that of the front bar **252**. The steering mechanism comprises:

- the front rotation member **286** disposed inside the front-bar associated portion **264** of the articulating member **260**, which is fixedly attached to the front bar **252** and configured for revolving therewith,
- a rear port **287** having a pair of right and left steering cable sections **284** fixedly attached thereto at their one end and fixedly attached with their other end to the front rotation member **286** so that pulling on one of the cable sections **284** will cause revolution of the front rotation member **286** with the front bar **252**, allowing steering of the vehicle;
- a rear port cup **289** whose interior merges with a cable passage (not designated), the cup (shown assembled with the housing left part), being fixed within the body member rear portion **211R**, so as to receive therein the rear port **287** in a manner allowing the port to be rotated by the handle **80**, with the cable sections **284** passing through the cable passage, via the interior of the body member **210** towards the front piece **286**.

To ensure that the right and left cable sections **284** will be bent as desired when the vehicle is folded from the operational state into the storage state by pivoting the articulation member **260** together with the front bar **252** and the front member **286**, the cable sections extend within the body member **210** so that each of them passes between

the prongs **281** of the respective right or left button **261** allowing the prongs to fix the locations of the cable sections, at which they are to be bent.

The vehicle **200** further comprises a front bar locking clamp **300** attached to its securing frame **236** for locking the upper portion **252B** of the front bar **252** to the securing frame **236**, when in its operational orientation (as seen in Fig. 5B), allowing this portion to have a fixed orientation when the lower portion of the front is steered.

Finally, the pedals **P** of the vehicle are mountable both to the front wheel **W_F** as described above and shown in Fig. 5A, allowing the vehicle to be ridden by a child accommodated therein, and to the articulating member **260** at its rear-legs associated portion **266** as shown in Fig. 5C, to constitute a footrest disposed closer to the seat arrangement **30** than the front wheel **W_F** and thus facilitate the use of the vehicle **200** as a stroller. The seat arrangement **30** can be configured for mounting in at least two positions one - as shown in Figs. 5A and 5C, and the other (not shown) – closer to the front bar **252**.

CLAIMS:

1. A foldable personal vehicle having an operational state and a storage state and having a longitudinal axis lying in a vertical plane of symmetry of the foldable vehicle, the foldable vehicle comprising:

a body member having an upper surface holding a seat, front and rear ends spaced from each other along the longitudinal axis, a right rear side surface and a left rear side surface both disposed adjacent the rear end of the body member and spaced from each other in a direction perpendicular to the plane of symmetry;

a front bar pivotally articulated at least indirectly to the front portion of the body via a front pivot axis and holding a front wheel of the vehicle, so as to be pivoted between the operational orientation and storage orientations;

two rear legs each pivotally articulated to the rear portion of the body via a rear pivot axis to enable the legs to take operational and storage orientations, and holding a rear wheel of the vehicle;

a rotatable rear steering port configured to fixedly receive therein a rear steering handle for using said handle when the vehicle is in the operational state; and

a steering mechanism connecting said port with the front bar so that rotation of the port by the handle causes at least a lower portion of the front bar to rotate for steering the vehicle when in the operational state, the steering mechanism comprising at least one steering element extending at least partially within the body member and configured to be bent in the vicinity of the front pivot axis, when the front bar is pivoted from the operational orientation to the storage orientation.

2. The foldable vehicle according to Claim 2, wherein the steering mechanism further comprises a front rotation member fixedly mounted to the front bar, and a pair of bendable right and left cable sections constituting the steering elements, each extending between the front rotation member and the port and so connected thereto that rotation of the port clockwise or counterclockwise causes the port to pull the respective right or left section, and such pulling yields the rotational movement of the front rotation member and subsequently of the front bar.

3. The foldable personal vehicle according to Claim 1, wherein the front bar has an upper portion associated with handlebars and a lower portion associated with the

front wheel, the upper and lower portions being configured to be locked to each other to behave as a single integral unit steerable by operating the handlebars, and unlocked from each other allowing the lower portion to be steered by a separate steering independently of the upper portion.

4. The foldable personal vehicle according to Claim 3, wherein the vehicle further comprises a front bar locking clamp for locking the upper portion to an element of the vehicle, which is not movable when in the operational state of the vehicle, to prevent the possibility of rotating the upper portion about the front bar axis by operating the handlebars.

5. The foldable vehicle according to Claim 1, further comprising pedals detachably mountable to the front wheel and to another element of the vehicle disposed closer to the seat than the front wheel along the longitudinal axis of the vehicle.

6. The vehicle according to Claim 1, further comprising right and left articulation axles for pivotal articulation of the corresponding right and left rear legs of the vehicle relative to the associated right and left rear side surfaces of the body member, about a right and a left rear pivot axis, respectively.

7. The foldable vehicle according to Claim 6, wherein each of the rear pivot axes is configured to meet at least one of the following requirements:

- it forms an acute angle with a horizontal reference plane, in the rear view of the vehicle, so as to obtain an increased spacing between the rear legs' distal ends in their operational orientation relative to that, which these legs would have with the pivot axes lying in a plane parallel to the reference plane; or

- it forms an acute angle with the plane of symmetry of the vehicle, in the plan view thereof, so that distal ends of the rear legs in their storage orientation are closer to the plane of symmetry than in their operational orientation.

8. The foldable vehicle according to Claim 1, further comprising a front assembly comprising the front bar and an articulation member, by virtue of which the front bar is pivotally articulated to the front end of the body member about a front pivot axis, and wherein the front pivot axis is spaced from the front bar axis so that in the operational orientation of the front bar in the operational state of the vehicle, the front bar is disposed in front of the body member, and in the storage orientation in the storage state

of the vehicle, the front bar is disposed above and extends along the upper surface of the body member along at least a majority of the length of the front bar.

9. The foldable vehicle according to Claim 8, wherein the articulating member has the following portions: a first, front-bar associated portion, which embraces the front bar in a manner allowing at least a portion of the front bar to revolve about the front bar axis; a second, rear-legs associated portion, to which the rear legs are connected; and a third, body-member associated portion, at which the articulating member is pivotally articulated to the front end of the body member; wherein in the side view of the vehicle, the second portion is disposed closer to the seat than the first and the third portions, whilst the third portion is disposed lower than the first and second portions.

10. The foldable vehicle according to Claim 1, further comprising a right and a left connection member, each connecting the articulating member with connection areas of the respective right and left rear legs so that pivoting the front bar between the operational and storage orientations causes the connection members to pivot the rear legs along the respective rear side surface of the body member, between their respective operational and storage orientations.

11. The foldable vehicle according to Claim 10, wherein at least one of the connection members is configured to be able, when pushed by the articulating member, to push accordingly the rear legs from their storage orientation to their operational orientation.

12. The foldable vehicle according to Claim 1, wherein the vehicle is a tricycle convertible into a stroller configured for accommodating a child therein and for preventing, when desired, the child from being able to steer the vehicle.

13. The foldable vehicle according to Claim 1, wherein the rear legs of the vehicle are free of any common elements extending therebetween at locations thereon spaced from the legs' proximal ends, for pivotally connecting the legs to the body member and, optionally, wherein in the storage state of the vehicle each rear leg is coextensive with the body member at least along a majority of their longitudinal dimensions.