



(51) International Patent Classification:
H01L 21/302 (2006.01) *H01L 21/66* (2006.01)

(21) International Application Number:
PCT/US2011/030262

(22) International Filing Date:
29 March 2011 (29.03.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/755,090 6 April 2010 (06.04.2010) US

(71) Applicant (for all designated States except US): **LAM RESEARCH CORPORATION** [US/US]; 4650 Cushing Parkway, Fremont, CA 94538 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NORTON, Peter** [US/US]; 2400 Dowling Place, #9, Berkeley, CA 94705 (US). **ABBOUD, Charley** [US/US]; 3580 Skyline Dr., Hayward, CA 94542-2504 (US).

(74) Agents: **KLINTWORTH, Timothy, K.** et al.; Klintworth & Rozenblat IP LLC, 850 West Jackson Boulevard, Suite 660, Chicago, IL 60607 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:
19 January 2012

(54) Title: NON-CONTACT DETECTION OF SURFACE FLUID DROPLETS




Fig.1

(57) Abstract: A system for detecting fluid on a substrate is provided. The system includes, but is not limited to, a sensor board, a first capacitive sensor, and a platform upon which the substrate is to be placed. The first capacitive sensor is mounted on the sensor board. The first capacitive sensor has a transmit sensor pad for transmitting a signal, a receive sensor pad for receiving the signal, and an analog-to-digital convertor connected with the receive sensor pad for analyzing the received signal. The platform is a first distance from the transmit and receive sensor pads.

