

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



PCT



(10) 国际公布号

WO 2010/043116 A1

(43) 国际公布日
2010 年 4 月 22 日 (22.04.2010)

- (51) 国际专利分类号:
C07C 11/04 (2006.01) C10G 9/18 (2006.01)
C07C 4/02 (2006.01)
- (21) 国际申请号: PCT/CN2009/001145
- (22) 国际申请日: 2009 年 10 月 15 日 (15.10.2009)
- (25) 申请语言: 中文
- (26) 公布语言: 中文
- (30) 优先权:
200810224277.7 2008 年 10 月 16 日 (16.10.2008) CN
- (71) 申请人 (对除美国外的所有指定国): 中国石油化工股份有限公司 (CHINA PETROLEUM & CHEMICAL CORPORATION) [CN/CN]; 中国北京市朝阳区朝阳门北大街 22 号, Beijing 100728 (CN)。中国石化工程建设公司 (SINOPEC ENGINEERING INCORPORATION) [CN/CN]; 中国北京市朝阳区安慧北里安园 21 号, Beijing 100101 (CN)。中国石油化工股份有限公司北京化工研究院 (BEIJING RESEARCH INSTITUTE OF CHEMICAL INDUSTRY, CHINA PETROLEUM & CHEMICAL CORPORATION) [CN/CN]; 中国北京市朝阳区北三环东路 14 号, Beijing 100013 (CN)。

天华化工机械及自动化研究设计院南京工业炉设计研究所 (NANJING INDUSTRIAL FURNACE INSTITUTE OF TIANHUA INSTITUTE OF CHEMICAL MACHINERY & AUTOMATION) [CN/CN]; 中国江苏省南京市宁海路 125 号, Jiangsu 310024 (CN)。

- (72) 发明人: 及
- (75) 发明人/申请人 (仅对美国): 何细藕 (HE, Xiou) [CN/CN]; 中国北京市朝阳区安慧北里安园 21 号, Beijing 100101 (CN)。王国清 (WANG, Guoqing) [CN/CN]; 中国北京市朝阳区北三环东路 14 号, Beijing 100013 (CN)。李昌力 (LI, Changli) [CN/CN]; 中国北京市朝阳区安慧北里安园 21 号, Beijing 100101 (CN)。张利军 (ZHANG, Lijun) [CN/CN]; 中国北京市朝阳区北三环东路 14 号, Beijing 100013 (CN)。李金科 (LI, Jinke) [CN/CN]; 中国江苏省南京市宁海路 125 号, Jiangsu 310024 (CN)。邵晨 (SHAO, Chen) [CN/CN]; 中国北京市朝阳区安慧北里安园 21 号, Beijing 100101 (CN)。李光 (LI, Guang) [CN/CN]; 中国北京市朝阳区安慧北里安园 21 号, Beijing 100101 (CN)。郭玉萍 (GUO, Yuping) [CN/CN]; 中国北京市朝阳区安慧北里安园 21 号, Beijing 100101 (CN)。

[见续页]

(54) Title: A ETHYLENE CRACKING FURNACE

(54) 发明名称: 一种乙烯裂解炉




Fig. 2

(57) Abstract: Disclosed is an ethylene cracking furnace which comprises followings: high pressure vapor-bag (1), convection section (2), radiation section, several furnace tubes (14) which are vertically set out in the radiation section, burner (5), and instant-freezing boiler (6); each furnace tube of radiation section comprises one first stroke pipe (7), one second stroke pipe (8) and one connecting piece (9); the cracking material is fed in through the inlet of the first stroke pipe, and drawn out through the outlet of the second stroke pipe; said first stroke pipe (7) and second stroke pipe (8) are non-branched furnace tubes, and the central lines of each furnace tube are in same plane; said connecting piece (9) is a stereo structure which comprises inlet bend (10), return bend (11) and outlet bend (12); said inlet bend (10) and outlet bend (12) are situated on the both sides of the plane in which are the central lines of the first stroke pipe (7) and the second stroke pipe (8); the side project of said connecting pieces (9) is one symmetrical continual endless curve, the inner diameters of furnace tubes are changed at least once along the length direction of said furnace tube.

[见续页]

WO 2010/043116 A1