CLAIMS

1. A spray head (1), comprising

a fastening body (2),

a spray head body (3) with at least one nozzle (4)

a thermally activated triggering device (5), said spray head body (3) being arranged into the fastening body (2), into its cylinder space (21) to be movable between two positions,

the first of the two positions, being one in which the spray head (1) is in an inactive state, and

the second of the two positions, being one in which the spray head body (3) is extended out, said spray head body (3) being arranged to be movable by a pressurized medium in relation to the fastening body (2) from the first position to the second position, and

a retaining arrangement (18,19,20) adapted to keep the spray head body (3) in the first position, until the pressure of the pressurized medium exceeds a preset value,

characterised in that

the retaining arrangement (18,19,20) comprises

at least one groove (19) that is formed in the spray head body (3),

at least one groove (18) that is formed onto the fastening body (2), and

at least one retaining element (20), being arranged in opposed grooves (18 & 19), when the spray head body (3) is in the first of the two positions.

2. A spray head according to claim 1, wherein the spray head (1) comprises a collar section (11), in which there is an opening (12), through which at least a part of the spray head body (3) extends at least in the second position.

3. A spray head according to claim 1 or claim 2, wherein the lower surface (10) of spray head body (3) is arranged in the first position to extend through opening (12) essentially to the same plane with respect to the fastening body (2) or with respect to the outer surface (10) of the collar section (11), arranged in connection with the fastening body (2).

4. A spray head according to claim 2 or claim 3, wherein the collar section (11)

comprises a ledge section (15), fitted into the fastening body (2), on the outside thereof, for example by means of threaded sections (16,17).

5. A spray head according to claim 2, wherein the collar section (11) is an integral part of the fastening body (2) or of a fastening part (23), or of the spray head body (3).

6. A spray head according to any one of claims 2-5, wherein the collar section (11) and the fastening body (2) are detachable from their installation object, individually or together, or wherein the position of the collar section (11) in relation to the fastening body (2) is adjustable.

7. A spray head according to any one of the preceding claims, wherein the position of the spray head body (3) in relation to the fastening body (2) is adjustable at least in the first position.

8. A spray head according to claim 1, wherein the retaining element (20) of the retaining arrangement (18,19,20) is a ledge section, formed onto the spray head body (3) or the fastening body (2), which in the first position is fitted into the corresponding part, such as a groove.

9. A spray head according to any one of the preceding claims, wherein the pressure medium is the extinguishing medium or a medium of a separate pressure system.

10. The use of a spray head (1) according to any one of the preceding claims, in a fire extinguishing system of a vehicle or a means of transportation, such as a train.

CLAIMS

1. A spray head (1), comprising

a fastening body (2),

a spray head body (3) with at least one nozzle (4)

a thermally activated triggering device (5), said spray head body (3) being arranged into the fastening body (2), into its cylinder space (21) to be movable between two positions,

the first of the two positions, being one in which the spray head (1) is in an inactive state, and

the second of the two positions, being one in which the spray head body (3) is extended out, said spray head body (3) being arranged to be movable by a pressurized medium in relation to the fastening body (2) from the first position to the second position, and

a retaining arrangement (18,19,20) adapted to keep the spray head body (3) in the first position, until the pressure of the pressurized medium exceeds a preset value,

characterised in that

the retaining arrangement (18,19,20) comprises

at least one groove (19) that is formed in the spray head body (3),

at least one groove (18) that is formed onto the fastening body (2), and

at least one retaining element (20), being arranged in opposed grooves (18 & 19), when the spray head body (3) is in the first of the two positions.

2. A spray head according to claim 1, wherein the spray head (1) comprises a collar section (11), in which there is an opening (12), through which at least a part of the spray head body (3) extends at least in the second position.

3. A spray head according to claim 2, wherein the lower surface (10) of spray head body (3) is arranged in the first position to extend through opening (12) essentially to the same plane with respect to the fastening body (2) or with respect to the outer surface (10) of the collar section (11), arranged in connection with the fastening body (2).

4. A spray head according to claim 2 or claim 3, wherein the collar section (11)

comprises a ledge section (15), fitted into the fastening body (2), on the outside thereof, for example by means of threaded sections (16,17).

5. A spray head according to claim 2, wherein the collar section (11) is an integral part of the fastening body (2) or of a fastening part (23), or of the spray head body (3).

6. A spray head according to any one of claims 2-5, wherein the collar section (11) and the fastening body (2) are detachable from their installation object, individually or together, or wherein the position of the collar section (11) in relation to the fastening body (2) is adjustable.

7. A spray head according to any one of the preceding claims, wherein the position of the spray head body (3) in relation to the fastening body (2) is adjustable at least in the first position.

8. A spray head according to claim 1, wherein the retaining element (20) of the retaining arrangement (18,19,20) is a ledge section, formed onto the spray head body (3) or the fastening body (2), which in the first position is fitted into the corresponding part, such as a groove.

9. A spray head according to any one of the preceding claims, wherein the pressure medium is the extinguishing medium or a medium of a separate pressure system.

10. The use of a spray head (1) according to any one of the preceding claims, in a fire extinguishing system of a vehicle or a means of transportation, such as a train.