

INTEGRAL SCROLL AND GEARBOX FOR A COMPRESSOR WITH SPEED CHANGE OPTION

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to U.S. Provisional Patent Application No. 60/921,547, entitled "Integral Scroll and Gearbox for a Compressor with Speed Change Option", filed on April 3, 2007, which is herein incorporated by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention generally relates to centrifugal compressors, such as, for example, assemblies of compressors for multistage compression wherein the integral casting further includes a gearbox and intercooler housings.

BACKGROUND OF THE INVENTION

[0003] Centrifugal compressors supply oil-free compressed gas in a variety of industrial applications. A common application of a centrifugal compressor is in plant air systems, to supply a motive force for valve actuators and pneumatic cylinders used in robotic applications, as one example. Centrifugal compressors typically feature an impeller mounted in a closely-conforming impeller chamber. The chamber features an axial inlet port to allow fluid entry toward the center of the impeller. Fluid is drawn into the impeller due to its rotation at speeds that can exceed 75,000 revolutions per minute (RPM). The rotation of the impeller propels the fluid through an annular diffuser passageway and into a surrounding volute. The energy imparted into the fluid by the impeller's rotation increases the fluid's velocity and, consequently, pressure as the fluid passes the diffuser passageway into the scroll or volute. The diffuser passage way has inside and outside radial dimensions for each circumferential station of the impeller chamber and scroll. By definition, the inside radius of the diffuser section corresponds to the distance to the diffuser throat or the location at which the annular port or passageway has the smallest axial width for the given station, the diffuser section extending outwardly for the remainder of the annular passageway.

[0004] Traditionally, centrifugal compressors have featured a bolt on scroll/volute cover, which encompassed portions of the impeller chamber, the diffuser passageway and the volute-outlet passageway. U.S. Patent No. 4,181,466 is illustrative of a bolt-on component featuring a fluid entry 51 and a volute 50 that is secured to the bearing housing 15 by a V-clamp 49. A difficulty with the bolt-on scroll/volute cover incorporating the volute is the effective control of tip clearance between the impeller and the inlet passageway and the clearance between the impeller and the volute outlet. Due to the bolt-on construction previously employed, machining costs and assembly costs affected the finished cost of the product. The assembly of a plurality of components required the use of greater clearances around the impeller, which sacrificed compressor efficiency. This, in turn, required larger drivers and higher operating costs for electric power. Since each assembled component has a manufacturing tolerance, the final clearance near the impeller has to be sufficiently large to accommodate a situation where all the tolerances in the individual components of the assembly turned out within specification but all dimensions on the individual components were off from the ideal dimension and on the same side of the tolerance allowed.

[0005] Another problem with bolt-on volutes, i.e., 24 and 26, is the extra space and mass taken up by that type of assembly. Such space could become important in situations where ease of installation and maintenance is important to serviceability. For example, as will be explained below, use of bolt-on volutes (such as 24 and 26) hinders access to the driver shaft for an oil pump to be directly driven. The extra housing thickness for each stage in a multi-stage skid could preclude a direct drive on the oil pump and may necessitate a separate electrical drive for the oil pump. This would be undesirable in the event of an electrical failure. In an electrical failure, the impeller bearings need lubrication, as the impeller slows from its operating speed of 75,000 RPM or more. Bearing failure could result with an electrically driven oil pump if it stopped delivering oil too abruptly on power failure. A power takeoff from the main drive shaft, which could involve gears or belts, adds to the complication of packaged systems and tends to complicate access when maintenance is required.

[0006] One issue that remains unresolved by the integral casting of the volute as part of the gearbox is what can be done if the end user needs a capacity change that involves a speed change to one or more stages in a compressor assembly. Normally, such a speed change involves a gear ratio change. Typically, the end user prefers to simply change a pinion **34** shown in FIG. 2 while retaining the much larger bull gear **32**. The reasons for this preference are cost and speed of getting the replacement parts. It is far easier for the original equipment manufacturer to stock a variety of pinions than to have a lot of cash tied up in very large parts such as different bull gears **32**. However, using a different sized pinion with the same bull gear changes the center to center distance between them and the scroll is integrally cast to a fixed center to center distance.

SUMMARY

[0007] In accordance with certain embodiments, the volute is cast integrally with the gearbox base to allow closer radial tolerances to be used to improve efficiency. In one embodiment, compressors for multi-stage compression are assembled with intercoolers and the integral volute is cast together with the impeller housing and the lower gearbox housing and the associated intercooler. Efficiency increases of 2% or more are achievable. In multistage applications, efficiency gains in the early stages are compounded in each subsequent stage. Speed changes that change center distance between bull gear and pinion are accommodated by an offset opening in the inlet and diffuser that can line up with the impeller shaft as well as an offset opening in the fluid seal despite a pinion gear change, by reorientation and remounting of those parts including the bearings that support them. Either the pinion or the bull gear or both can be moved to change the shaft center distance to accommodate the new gear pairing to get the desired speed.

[0008] The present invention, in the exemplary context of an integral scroll and gearbox, provides a way to accommodate the differing center to center distances of the gear drive from a speed change by allowing the scroll to accept an end plate with an eccentric opening that can be mounted in a variety of

positions to accommodate different center to center distances for example. The bearing housing that is placed in the casting at the gearbox location is selected to also accommodate this offset and an insert shown in FIGS. 7 and 8 can also be mounted to maintain the relation of the inlet opening **76** to the position of the shaft **38** that supports the impeller **36** and the pinion gear **34**. Alternatively, the present invention can accommodate changing the center distance between the bull gear and the pinion by moving the bull gear centerline using offset bearing housings for its shaft, for example. As yet another alternative and exemplary embodiment, the present invention, depending on the new desired speed, can have both shafts moved to increase or decrease the center distance to accommodate the new gearing combinations selected to get the desired speed.

[0009] These and other advantages of the present invention will become more apparent to a person of skill in the art from a review of the description of the exemplary embodiments described below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a perspective view a prior art of a three-stage centrifugal compressor skid showing the first stage compressor housing with volute cast integrally with the lower gearbox housing and the first stage intercooler housing.

[0011] FIG. 2 is a section view along line 2--2 of FIG. 1.

[0012] FIG. 3 is a close up view of the first-stage volute-type scroll housing shown at the top of FIG. 2.

[0013] FIG. 4 is a close up view of a prior art bolt on volute-type scroll housing typically used as an industry standard centrifugal compressor;

[0014] FIG. 5 shows an inlet assembly with the opening off center to address a shifted impeller shaft position from a change in pinion gear size on the impeller shaft;

[0015] FIG. 6 is an end view showing the inlet of FIG. 5 assembled to a scroll:

[0016] FIG. 7 shows, the orientation of the inlet with the opening shifted right;

[0017] FIG. 8 shows the orientation of the inlet with the opening shifted left;
and

[0018] FIG. 9 is an exploded view showing how a change in pinion size can be addressed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0019] Referring to FIG. 1, this figure, which is in a perspective view, has portions removed for clarity. For example, the motor driver for the package is omitted. The illustrated package comprises a first stage **10**, a second stage **12**, and a third stage **14**. In essence, FIG. 1 is a drawing of a casting, which further comprises a first-stage intercooler housing **16**, a second-stage intercooler housing **18** and the lower end of the gearbox **20**. An after-cooler (not shown) can be used after the third stage **14**. The first stage **10** has an inlet **22** omitted from FIG. 1 but shown in section in FIG. 2. Second stage **12** has a differently configured inlet section **24** as compared to the first stage inlet **22**. Third stage **14** has an inlet **26** similarly configured to inlet **24**. The present invention, in certain instances, relates to the configuration of volute scroll **74** and its complementary inlet **22**. That configuration can also be used in second stage **12** and third stage **14** within the scope of the invention.

[0020] The first stage **10** has been configured differently than stages **12** and **14** to illustrate the difference between the prior-known technique (illustrated in stages **12** and **14**) from the technique of the present invention exemplified in the first stage **10**. It is also different than another known technique as described in FIG. 4, item **90**. It should be noted that the invention does not presuppose multiple stages and the details of the first stage **10** can be employed in a single stage installation or in a multi-stage installation, on one or more of the stages, all within the scope of the invention.

[0021] Referring again to FIG. 2, shaft **28** has a coupling **30** connected at its end. The motor driver (not shown) is coupled to coupling **30**. Shaft **28** supports bull gear **32** in gear box **20**. Pinion gear **34** meshes with gear **32** to drive impeller **36** in first stage **10**. Shaft **38** supports the impeller **36** as well as pinion gear **34** and seals **40** along with bearings **42**, disposed on either side of pinion gear **34**. On the other side of the gear box **20**, another pinion gear **44** is supported on a shaft **46** to operate impellers **48** and **50** on the second stage **12** and third stage **14** in tandem. Similar seal and bearing arrangements are used on shaft **46** as on shaft **38**. Mounted to the end of shaft **28** is an oil pump **52**, directly connected by a coupling **54**.

[0022] As seen in FIGS. 1 and 2, the second and third stages, **12** and **14** are different than the first stage **10**. The housings **56** and **58** are cylindrically shaped and receive a combination inlet/volute **24** and **26** respectively. Bolts **64** and **66**, respectively secure the combination inlet/volute respectively to housings **56** and **58**. The housings **56** and **58** are cast integrally with the lower gear box **20** and the intercooler housings **16** and **18**. Second and third stages **12** and **14** illustrate the prior known technique and are included in the illustrated three-stage system to provide contrast for a clearer understanding of the advantages of the present invention. FIG. 4 also illustrates a prior art technique, which provides further contrast and understanding of the advantages of the present invention. In the illustrative stage **90** of FIG. 4, the machined scroll/volute **90** is a complicated piece having numerous machined surfaces, each of which necessarily has a tolerance on one or both sides of the ideal dimension. Impeller **92** has a plurality of blades **96** extending radially from near its center. A clearance in the radial direction is required as between the blades **96** and surface **98** on inlet/volute **94**. The location and orientation of this clearance is also seen in FIG. 3, which is a close-up of first stage **10**, illustrating the clearance in the case of the present invention. The clearance **72** in the first stage **10** can be reduced to less than 0.020 inches as compared to the stage **90** where the counterpart clearance can run in the range of 0.024-0.035 inches or greater. The clearance **72** is obtained solely as a result of a casting followed by a machining process. To date,

commercially available equipment of the type shown in FIG. 4 has not been built with smaller clearances. While, theoretically, a coating process can be employed to further reduce clearances in the prior FIG. 4 design below 0.024 inches, practically, these techniques have not been employed in centrifugal compressor applications for reasons of quality control problems and prohibitive cost.

[0023] The reason a smaller clearance is obtained in the first stage **10** is that it incorporates a volute type scroll as the housing **74**. Inlet **22** has an opening **76** made of a surface **78**, which conforms to the outer periphery of blades **80**. The radial clearance **72** eventually becomes an axial clearance in conformity to the shape of blades **80**. Since the volute is cast integrally to the housing **74** there are fewer surfaces to machine on the casting and on inlet **22** to fit them up. The ultimate blade clearance **72** can be smaller than in the stage 90 because there are fewer opportunities for the accumulated tolerances on the various machined surfaces to add up when the volute type scroll is cast integrally as housing **74**. There are also reduced man-hours for assembly of the first stage **10** as well as labor savings in reduced machining. The disadvantage of the second stage **12** is that by combining the volute into the inlet **60** and then inserting the inlet **60** into the cylindrically shaped housing **56** the outer profile of housing **56** is increased due to a near doubling of the wall thickness at the periphery. To illustrate the concept, had the first stage **10** been built in the same manner as the second stage **12** using the same exterior dimensions for the casting shown in FIG. 1, there would have been no room to mount the oil pump **52** and coupling **54** to the shaft **28** between the first and second stages **10** and **12** respectively. As previously stated, being able to power the oil pump **52** off of shaft **28** becomes an issue if there is a power failure from the perspective of protecting the bearings such as **42**. The other alternative of simply making the entire casting larger adds significant cost to the finished product.

[0024] It should be noted that with regard to the first stage **10**, that the diffuser plate **82** is secured to inlet **22** with bolts **84** before fitting up inlet **22** to the volute type scroll housing **74** using bolts **86**. The clearance **72** minimization allows the first stage to achieve an efficiency improvement of 1-2% and slightly more. This

improvement is magnified in the subsequent stages of compression. Operating expenses can be reduced and a smaller driver utilized because of the reduction in internal leakage from use of smaller clearances. Of course, even greater efficiency can be obtained from using the volute type scroll cast integrally as the housing in all stages in a multi-stage assembly such as shown in FIG. 1. The oil pump **52**, even if there is a power failure, continues to deliver enough oil to all the bearings as shaft **28** slows down but continues to drive the oil pump **52**.

[0025] Referring to FIG. 2 it can be seen that gearbox **20** is made integrally with housing **74** to accept a predetermined spacing between shaft **28** for bull gear **32** and shaft **38** for the pinion gear **34**. To make all the parts go together, the air seal **40** has a properly located bore (not shown) through which the pinion shaft **38** extends. The inlet assembly **22** has an inlet opening **76** to align it with the impeller **36**. Referring to FIG. 3, it can be seen that the diffuser **82** is part of the inlet assembly **22** and also features an opening (not shown) in which the impeller **36** resides.

[0026] The question comes up and the present invention addresses, what happens if a compressor assembly is constructed to a given speed for the first stage **10** for example and the operator has experienced a change in conditions and want to increase the speed. The original equipment manufacturer wants to be able to help the customer change the speed but issues arise as to what to stock in inventory and the cost of maintaining a variety of parts to accommodate a variety of selected driven speeds. Typically, the bull gear **32** is the largest gear in the gearbox and is very expensive to produce in a variety of teeth count configurations. If the bull gear **32** is not changed then a speed change involves changing the teeth count of the pinion **34** to reduce teeth for a speedup or increase teeth for a slowing down of the first stage **10** for example. However, fitting a new pinion gear **34** changes the center to center distance between shafts **28** and **38** and the integral casting of the gearbox **20** and the housing **74** was to a fixed center to center distance.

[0027] It is believed the present invention solves this problem. If the pinion **34** is replaced with a smaller gear to speed up the first stage **10**, for example, the bearings **42'** on either side of new pinion **34'** must be relocated within the housing **20** to adapt to the new center to center shaft distance. FIG. 9 shows the bearing housings **43** with offset bores **45** to offset the bearings **42'** for a change in shaft center distance created by use of the new pinion **34'**. In order to allow the shaft **38'** to enter the housing **74** through the air seal **40** the opening in it **47** is made eccentric to its center. This eccentric bore concept for the seal is also addressed for the inlet assembly **22'** and the diffuser **82'** connected to it. FIGS. 5-8 show the inlet assembly **22'** with an off-center opening **76'** relative to the bolt circle diameter that accepts bolts **86** (see FIG. 3). FIG. 6 shows the modified inlet assembly **22'** mounted to housing **74** of the first stage, for example. FIGS. 7 and 8 show the rotated left and rotated right positions for the inlet **76'**, respectively. Those skilled in the art will appreciate that the opening **49** in the diffuser **82** is preferably aligned with opening **76'** in inlet **22'** so that the impeller **36** fits within diffuser **82** while the shaft **38'** goes through an eccentric opening relative to the center of seal **40** so that seal **40** fits in the same opening as before but now creates an offset bore for shaft **38**. The same result occurs for the bearings for shaft **38'**. As a result of the offset opening **76'** in inlet assembly **22'** and the matching opening in the diffuser **82'** attached to it as well as a similar offset in air seal **40** there are now two positions at minimum for the center to center distance between shafts **28** and **38'** if they are kept at the same horizontal plane. Even more center to center distance changes are possible if the shafts are not limited to being in the same horizontal plane. Alternatively, the end user that requires a speed change can also buy a different inlet assembly **22'** with a diffuser **82** having a matching bore offset to accommodate the impeller **38** and just purchase those components with a new air seal **40** and relocate the bearings **42** closer or further away, as needed and everything can go back together and function in the existing equipment that has the integral gear box **74** and housing **74**.

[0028] As an alternative, offset bearing holders similar to those shown for the pinion shaft **38'** can be used for the bull gear shaft **28**. In that way, the bull gear can be relocated closer or further from a pinion shaft **38** that itself can be moved

or left where it is. In a given gearbox and scroll combination housing the speed can be changed with a change of the pinion size, the bull gear size or by changing both depending on the desired end speed for the compressor stage that is desired. The center distance can be increased or decreased by moving one or both pinion and bull gear shafts. Offset mounting for the shafts are made possible by mounts with eccentric capabilities that allow the original components such as bearings and seals to be mounted in a variety of positions to accommodate the new shaft location within an existing gearbox. Speed changes are now possible for such precast units without major expense of obtaining new gearbox with scroll integrated housings.

[0029] While the invention has been described and illustrated in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described and that all changes and modifications that come within the scope of the claims below are the full scope of the invention being protected.

Claims:

1. A rotating equipment assembly, comprising:
an integrally produced combination of a at least a portion of a gearbox housing and at least a portion of a rotating equipment housing with openings at a predetermined distance for a driving shaft into the gearbox housing and a driven shaft from said gearbox housing into said rotating equipment housing;
said rotating equipment housing further comprising a seal assembly through which a driven shaft enters, said driven shaft further comprising a first driven gear and an end element disposed on said driven shaft and located in said rotating equipment housing;
said gear box housing further comprising a driving shaft and a driving gear engaged to said first driven gear;
said seal assembly further comprising an offset opening with respect to a center thereof, whereupon said first driven gear is replaceable with a second driven gear of a different size that changes said shaft to shaft center distance and said seal assembly can accommodate said changed shaft to shaft center distance by reorientation of said offset opening.
2. The assembly of claim **1**, further comprising:
an inlet assembly further comprising an inlet opening located off center thereto, said assembly adapted to be mounted to said rotating equipment housing in a plurality of orientations to change the position of said inlet opening with respect to said rotating equipment housing.
3. The assembly of claim **2**, wherein:
said inlet assembly is mounted to said rotating equipment housing on a side opposite from said seal assembly.
4. The assembly of claim **3**, wherein:
said inlet opening and said offset opening in said seal assembly can be aligned in more than one position with respect to said rotating equipment housing.

5. The assembly of claim **4**, wherein:
said inlet and offset openings are aligned in the same plane as said shafts.
6. The assembly of claim **4**, wherein:
said inlet and offset openings are above or below a plane that intersects said shafts.
7. The assembly of claim **2**, further comprising:
a diffuser comprising a diffuser opening and supported by said inlet assembly;
said diffuser opening aligned with said inlet opening such that both said openings move a like amount on reorientation of said inlet assembly with respect to said rotating equipment housing.
8. The assembly of claim **7**, wherein:
said offset opening is capable of being aligned with said diffuser and inlet openings in a plurality of orientations with respect to said rotating equipment housing.
9. The assembly of claim **8**, wherein:
said offset, diffuser and inlet openings are capable of alignment in a plane defined by said shafts or above or below said plane.
10. The assembly of claim **9**, wherein:
said end element comprises an impeller and said rotating equipment housing comprises at least a single stage centrifugal compressor.
11. A rotating equipment assembly, comprising:
an integrally produced combination of a at least a portion of a gearbox housing and at least a portion of a rotating equipment housing with openings at a predetermined distance for a driving shaft into the gearbox housing and a driven shaft from said gearbox housing into said rotating equipment housing;

said rotating equipment housing further comprising a seal assembly through which a driven shaft enters, said driven shaft further comprising a first driven gear and an end element disposed on said driven shaft and located in said housing;

said gear box housing further comprising a driving shaft and a driving gear engaged to said first driven gear;

an inlet assembly further comprising an inlet opening located off center thereto, said assembly adapted to be mounted to said rotating equipment housing in a plurality of orientations to change the position of said inlet opening with respect to said rotating equipment housing.

12. The assembly of claim **11**, wherein:

a diffuser comprising a diffuser opening and supported by said inlet assembly;

said diffuser opening aligned with said inlet opening such that both said openings move a like amount on reorientation of said inlet assembly with respect to said rotating equipment housing.

13. The assembly of claim **12**, wherein:

said diffuser and inlet openings are capable of alignment in a plane defined by said shafts or above or below said plane.

14. The assembly of claim **13**, wherein:

said seal assembly further comprising an offset opening with respect to a center thereof, whereupon said first driven gear is replaceable with a second driven gear of a different size that changes said shaft to shaft center distance and said seal assembly can accommodate said changed shaft to shaft center distance by reorientation of said offset opening.

15. The assembly of claim **14**, wherein:

said inlet assembly is mounted to said rotating equipment housing on a side opposite from said seal assembly.

16. The assembly of claim **15**, wherein:

said inlet opening and said offset opening in said seal assembly can be aligned in more than one position with respect to said rotating equipment housing.

17. The assembly of claim **16**, wherein:

said offset opening is capable of being aligned with said diffuser and inlet openings in a plurality of orientations with respect to said rotating equipment housing.

18. The assembly of claim **17**, wherein:

said offset, diffuser and inlet openings are capable of alignment in a plane defined by said shafts or above or below said plane.

19. The assembly of claim **18** wherein:

said end element comprises an impeller and said rotating equipment housing comprises at least a single stage centrifugal compressor.

20. A rotating equipment assembly, comprising:

an integrally produced combination of a at least a portion of a gearbox housing and at least a portion of a rotating equipment housing with openings at a predetermined distance for a driving shaft into the gearbox housing and a driven shaft from said gearbox housing into said rotating equipment housing;

said rotating equipment housing further comprising a seal assembly through which a driven shaft enters, said driven shaft further comprising a first driven gear and an end element disposed on said driven shaft and located in said rotating equipment housing;

said gear box housing further comprising a driving shaft and a driving gear engaged to said first driven gear;

said driving shaft comprising bearings with off-center mounts to allow said driving shaft to be moved closer or further from said driven shaft to accommodate a change in at least one of said gears.

21. The assembly of claim **20**, wherein:

said seal assembly further comprising an offset opening with respect to a center thereof, whereupon said first driven gear is replaceable with a second driven gear of a different size that changes said shaft to shaft center distance and said seal assembly can accommodate said changed shaft to shaft center distance by reorientation of said offset opening.

22. The assembly of claim **20**, wherein:

said driven shaft comprises a bearing assembly having bearings movable within an offset mount that allows said driven shaft to be moved closer or further from said driving shaft by reorientation of said bearings in their mount.