(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
28 December 2006 (28.12.2006)

PCT

(10) International Publication Number
WO 2006/137964 A1

(51) International Patent Classification:
G06F 17/50 (2006.01)

(21) International Application Number:
PCT/US2006/014697

(22) International Filing Date: 19 April 2006 (19.04.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/151,045 13 June 2005 (13.06.2005) US

(71) Applicant *(for all designated States except US)*: **ADVANCED MICRO DEVICES, INC.** [US/US]; One AMD Place, Mail Stop 68, P.O. Box 3453, Sunnyvale, CA 94088-3453 (US).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: **HALBUTOGULLARI, Alper** [TR/US]; 2945 Marietta Drive, Santa Clara, CA 95051 (US). **CEYLAN, Timur** [TR/US]; 623 Hickory Place, Santa Clara, CA 95051 (US).

(74) Agent: **DRAKE, Paul, S.**; Advanced Micro Devices, Inc., 5204 East Ben White Boulevard, Mail Stop 562, Austin, TX 78741 (US).


(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

[Continued on next page]

(54) **Title:** MANHATTAN ROUTING WITH MINIMIZED DISTANCE TO DESTINATION POINTS



(57) **Abstract:** For routing points (Pl, P2, P3, P4, P5, P6, P7, P8, P9) to a center point (C), the points are grouped into a respective set disposed within each quadrant (Ql, Q2, Q3, Q4). Each point is Manhattan routed to any other point having a minimum Manhattan distance within a rectangle defined by each point and the center point, to result in at least one initial end point in each quadrant having at least one of the points. The at least one initial end point is Manhattan routed together to result in a respective final end point (EPl, EP2, EP3, EP4) in each quadrant having at least one of the points. The respective final end points are routed to the center point with minimized routing distance.

WO 2006/137964 A1