

OPTICAL FIBRE MONITORING

This invention relates to the monitoring of optical fibres and is particularly concerned with apparatus for detecting whether or not an optical fibre is carrying a light signal.

5 In the specification of our co-pending Patent Application No: 8922079.2 (Serial No: 2226128A) there is described and claimed improved apparatus for detecting whether or not an optical fibre is carrying a light signal, which improved apparatus can be used without
10 causing undue disruption of the signal if one is present. This improved apparatus comprises bending means for subjecting at least a portion of an optical fibre to microbending of a gradually increasing extent; first detecting means for detecting light escaping from
15 the fibre; and, operatively coupled to the first detecting means and to the bending means, a control unit which will give an output indication on receipt of a signal from the first detecting means that light escaping from the fibre has been detected and which, on
20 receipt of said signal, will stop the bending means from further increasing the extent of microbending of said portion of the fibre.

A preferred embodiment of the improved apparatus of our aforesaid co-pending patent application comprises
25 first bending means for subjecting at least a portion of an optical fibre to microbending of a gradually

increasing extent; second bending means for causing a second portion of the optical fibre to be subjected to macrobending to a predetermined fixed extent, the extent of macrobending being insufficient, by itself, to cause
5 a substantial amount of light to escape from the optical fibre; first detecting means for detecting light escaping from the fibre, the first detecting means being in the location of the second bending means; and, operatively coupled to the first detecting means and to
10 the first bending means, a control unit which will give an output indication on receipt of a signal from the first detecting means that light escaping from the fibre has been detected and which, on receipt of said signal, will stop the first bending means from further
15 increasing the extent of microbending of said portion of the fibre.

It is an object of the present invention to provide a modification of the preferred embodiment of the improved apparatus of our aforesaid co-pending
20 patent application in the form of a handtool for detecting whether or not an optical fibre is carrying a light signal, which handtool can be readily manufactured in quantity and can be readily used in the field without causing undue disruption of a signal in an optical fibre
25 if one is present.

According to the invention, the handtool comprises a housing of such a shape and size that it can be held

in the hand; first bending means for subjecting a first portion of an optical fibre to microbending of a gradually increasing extent, which first bending means comprises an anvil fixedly secured in the housing, a pressure member so mounted in the housing that the pressure member is constrained to move towards or away from a face of the anvil in a rectilinear direction substantially normal to said face, said face of the anvil and/or the pressure-imparting face of the pressure member including one or more than one undulation, and a motor-driven operating mechanism mounted in the housing for causing the pressure member to move towards or away from the anvil so that when said first portion of an optical fibre is positioned between the pressure member and the anvil and the pressure member is caused to move towards the anvil said first portion of the optical fibre will be constrained between the anvil and the pressure member and will be subjected to microbending of a gradually increasing extent; second bending means which is fixedly secured in the housing adjacent the anvil and which will cause a second portion of said optical fibre to be subjected to macrobending to a predetermined fixed extent; first detecting means for detecting light escaping from the fibre, the first detecting means being mounted in the housing in the vicinity of the second bending means; second detecting means mounted in the housing for detecting when said

first portion of the fibre has been subjected to a predetermined amount of microbending; and, operatively coupled to the first and second detecting means and to the motor driving the operating mechanism of the first 5 bending means, a control unit which will give a first output indication on receipt of a signal from the first detecting means, the arrangement being such that, on receipt of a signal from the first detecting means, the control unit will stop the motor causing said movement 10 of the pressure member towards the anvil to prevent further increase of the extent of microbending of said first portion of the fibre and that, if the second detecting means detects that said first portion of the fibre has been subjected to its predetermined maximum 15 amount of microbending and no signal has been received from the first detecting means, a signal is sent to the control unit which will stop the motor causing said movement of the pressure member towards the anvil to prevent further increase in the extent of microbending 20 of said first portion of the fibre and will give a second output indication.

The motor-driven operating mechanism of the handtool preferably comprises a screw-threaded shaft which is so supported in the housing that it extends in 25 a direction substantially parallel to the direction of motion of the pressure member and which can be rotatably driven about its axis by said motor in either rotational

direction; two stops in screw-threaded engagement with and longitudinally spaced on the shaft a predetermined fixed distance apart; a substantially rigid elongate member which is secured to and extends from the pressure member in a direction substantially parallel to the shaft and which is so keyed to the stop nearer the pressure member that, when the shaft is rotatably driven about its axis, said elongate member is restrained against rotational movement and said elongate member and said longitudinally spaced stops are constrained to move in said direction with respect to the shaft, the elongate member having an end wall extending transversely of the shaft intermediate of said stops; and a coil spring which surrounds the shaft and extends between and is secured at its ends to said transversely extending end wall and the stop nearer the pressure member. The arrangement is such that, as the shaft is rotatably driven by the motor in one rotational direction, initially the elongate member and the longitudinally spaced stops are constrained to move with respect to the shaft in such a direction that the pressure member is caused to move towards the anvil until it abuts the first portion of an optical fibre disposed between the anvil and pressure member, and, thereafter, as rotation of the shaft continues, the coil spring extending between said transversely extending end wall and the stop nearer the pressure member is

gradually compressed, thereby to subject said first portion of the optical fibre to a gradually increasing pressure and, hence, to microbending of a gradually increasing extent. On receipt of a signal from the first detecting means, the control unit of the handtool will stop the motor rotatably driving the shaft to prevent further compression of the coil spring and hence further increase of the extent of microbending of said first portion of the optical fibre and, subsequently, the control unit will cause the motor to drive the shaft in the opposite rotational direction, initially, to cause the longitudinally spaced stops to move with respect to the rotatably driven shaft in the opposite direction until the pressure to which said first portion of the optional fibre is subjected is substantially zero and, thereafter, the longitudinally spaced stops and the elongate member will continue to move in said opposite direction so that the pressure member moves away from the anvil to enable the optical fibre to be removed and replaced by another optical fibre. If the second detecting means detects that the fibre has been subjected to a predetermined maximum pressure and, hence, to a predetermined maximum amount of microbending and no signal has been received from the first detecting means, then a signal is sent to the control unit which will stop the motor rotatably driving the shaft and hence will prevent further increase in the extent of

of microbending of said first portion of the fibre and will give a second output indication. Subsequently, as previously described, the control unit will cause the motor to drive the shaft in the opposite rotational
5 direction to cause the pressure member to move away from the anvil and enable the optical fibre to be removed and replaced by another optical fibre.

Preferably, if the second detecting means detects that the fibre has been subjected to a predetermined
10 maximum pressure and, hence, to its predetermined maximum amount of microbending and no signal has been received from the first detecting means, the motor is stopped and said first portion of the optical fibre is subjected to said maximum pressure and, hence, to its
15 predetermined maximum amount of microbending for a predetermined period of time, for example 3 seconds, before the motor is caused to drive the shaft in the opposite rotational direction to relieve the pressure on said first portion of the optical fibre.

20 Preferably, also, as the coil spring is being gradually compressed and at a position at which the pressure to which said first portion of an optical fibre and hence the extent of microbending is insufficient for a signal to be detected by the first detecting means,
25 movement of the longitudinally spaced stops is temporarily arrested for a predetermined period of time, for example approximately 1 second, sufficient to enable

the electronics of the handtool to be automatically calibrated, thereby to compensate for any drift that may have resulted from changes in temperature or other causes.

5 It will be appreciated that the pressure to which a first portion of an optical fibre will be subjected will depend upon the material and dimensions of the coil spring. We have found that, for an optical fibre of the kind currently used in optical transmission cables, a
10 coil spring is employed which will impart a predetermined maximum pressure of approximately 900 grammes on a first portion of an optical fibre when constrained between the anvil and pressure member. In this case, automatic calibration of the electronics of
15 the handtool preferably is effected when the pressure on said first portion of an optical fibre is approximately 200 grammes.

Each of the stops preferably is releasably locked on the shaft so that the fixed distance between them can
20 be adjusted as may be required to set a predetermined maximum pressure, and hence a predetermined maximum extent of microbending, to which an optical fibre is to be subjected using a coil spring of a particular material and of particular dimensions.

25 Preferably, to ensure that a light signal can be detected in an optical fibre constrained between the anvil and pressure member of the first bending means

regardless of the direction of travel of the signal along the fibre, the handtool includes two second bending means which are fixedly secured in the housing adjacent transversely opposite sides of the anvil, each
5 of which second bending means will cause one of two second portions of said optical fibre to be subjected to macrobending to a predetermined fixed extent, a first detecting means being mounted in the housing in the vicinity of each second bending means. In a preferred
10 embodiment, the anvil and said two second bending means are parts of a single plate of glass having an edge of a smoothly curved arcuate shape, a central part of said curved edge constituting the anvil and adjoining parts of said edge on opposite sides of the anvil constituting
15 the two second bending means.

The pressure member preferably is secured in a carriage which is separately formed with respect to the pressure member and which is so mounted in the housing that the carriage, and hence the pressure member secured
20 therein, is constrained to move towards or away from said face of the anvil in said rectilinear direction substantially normal to said face. Preferably, also, the carriage also carries on transversely opposite sides of the pressure member bodies of rubber or rubber-like
25 material which, when the pressure member imparts pressure on said first portion of an optical fibre constrained between the anvil and the pressure member,

will press said second portions of the fibre against the two second bending means. The pressure member preferably is adjustably secured in the carriage in such a way that the position of the pressure member with respect to the carriage can be adjusted to and locked in any one of a limited number of positions lying along a line substantially parallel to the direction of motion of the carriage.

The invention is further illustrated by a description, by way of example, of a preferred handtool for detecting whether or not an optical fibre is carrying a light signal, with reference to the accompanying drawings, in which:-

Figure 1 shows a plan view of the preferred handtool with the lid removed and with the pressure member bearing directly against the anvil;

Figure 2 is a fragmental schematic diagram of the preferred handtool shown in Figure 1 with an optical fibre positioned between the pressure member and anvil;

20 and

Figure 3 is a front view of the anvil of the preferred handtool shown in Figure 2.

Referring to the drawings, the preferred handtool comprises a housing 1 comprising a box 2 and a detachable lid (not shown), the housing being of such an elongate shape and size that it can be held in the hand.

Fixedly secured near one end of the box 2 is an anvil 4 having a face 5 towards or away from which a carriage 7 is constrained to move in a rectilinear direction normal to the face 5. A pressure member 9, which is separately
5 formed with respect to the carriage 7, is adjustably secured in the carriage and has a pressure-imparting face which includes a plurality of undulations. The combination of the anvil 4 and movable pressure member 9 constitutes first bending means for subjecting a first
10 portion of an optical fibre F disposed between the anvil and the pressure member to microbending of a gradually increasing extent. The pressure member 9 is so adjustably mounted in the carriage 7 that the position of the pressure member with respect to the carriage can
15 be adjusted and locked in any one of a limited number of positions lying along a line parallel to the direction of motion of the carriage.

Movement of the carriage 7, and hence of the pressure member 9, towards or away from the anvil 4 can
20 be effected by a motor-driven operating mechanism comprising a screw-threaded shaft 12 which is so supported in the box 2 that it extends in a direction parallel to the direction of motion of the carriage 7 and which can be rotatably driven about its axis in
25 either rotational direction by a motor 14 powered by batteries 15. Two stops 17 and 18 are in screw-threaded engagement with and longitudinally spaced on the shaft

12 and can be adjustably locked a predetermined fixed distance apart and a rigid arm 19 is secured to and extends from the carriage 7 in a direction parallel to the shaft and is so keyed to the stop 17 that, when the shaft is rotatably driven about its axis, the arm is restrained against rotational movement and the arm and the stops are constrained to move with respect to the shaft. The rigid arm 19 has an end wall 20 remote from the pressure member 9 through which the shaft 12 passes and a coil spring 21 surrounds the shaft and extends between and is secured at its ends to the end wall 20 and the stop 17.

The anvil 4 is constituted by a central part of an edge of a plate 3 of glass (Figures 2 and 3), adjoining parts 6 of the edge on opposite sides of the anvil being of smoothly curved arcuate shape and constituting two second bending means for subjecting second portions of the optical fibre F to macrobending of a predetermined fixed extent. Each of the second bending means 6 is operatively coupled to a control unit 23 (Figure 2) via a photodetector 8 which is mounted on the glass plate 3 in the vicinity of the second bending means. The control unit 23 includes three microswitches (not shown) indirectly operated in sequence by one of the stops 17, 18 on the motor-driven shaft 12, the first of which microswitches, when the pressure member 9 is spaced sufficiently from the anvil 4 to permit introduction of

an optical fibre, being actuated to cause electronics of the tool to reverse the motor 14 and so drive the shaft in such a rotational direction as to cause the pressure head to move towards the anvil. When the pressure member 9 initially comes into contact with the first portion of the optical fibre F, the second microswitch is actuated to cause the electronics of the tool to arrest temporarily movement of the pressure member to enable the electronics of the tool to be automatically calibrated. The third microswitch of the control unit constitutes the second detecting means and is actuated to cause the electronics of the tool to stop the motor 14 rotatably driving the shaft 12 if the optical fibre F has been subjected to a predetermined maximum pressure and, hence to a predetermined maximum amount of microbending, and no signal has been received from a photodetector 8.

With the exception of the edge 5, 6 of the glass plate 3 and the parts of the glass plate underlying the photodetectors 8, all surfaces of the plate are silvered to seal the glass plate against the ingress of ambient light. A light signal emerging from one of the second portions of the optical fibre F and passing through the second bending means 6 into the plate is reflected by one of two oblique faces 13 of the plate to the adjacent photodetector 8. The electronics of the control unit 23 is also operatively coupled to a display 24. The

display 24 may be a plurality of lamps mounted in the housing 1 and visible through the lid, each lamp being associated with a condition detected by the handtool, e.g. signal present on fibre, no signal present on
5 fibre, modulation signal detected, self-test fail and battery low, and each lamp being of a colour different to and readily distinguished from that of each of the other lamps.

The carriage 7 carries on transversely opposite
10 sides of the pressure member 9 bodies 11 of rubber or rubber-like material which, when the pressure member is caused to impart pressure on the first portion of the optical fibre F disposed between the anvil 4 and the pressure member, will press the second portions of the
15 fibre against the two second bending means 6. Each rubber body 11 has a face having a radius of curvature slightly less than that of the associated second bending means 6 so that, as the pressure member 9 is caused to move towards the anvil, each second portion of the
20 optical fibre F is positively and progressively constrained against the second bending means.

The macrobends to which the second portions of the optical fibre F are subjected by the second bending means 6 are of sufficiently large radius that, without
25 the microbending caused by the pressure member 9 and anvil 4, any light signal in the fibre would not be disrupted. The provision of two second bending means 6 for producing macrobends in the optical fibre F and two

photodetectors 8 has the advantage that a light signal if present can be detected regardless of its direction of travel along the fibre.

In use, an optical fibre F is disposed between the
5 anvil 4 and the undulating face of the movable
pressure member 9 and the screw-threaded shaft 12 is
driven by the motor 14 in the appropriate rotational
direction to cause the rigid arm 19 and the
longitudinally spaced stops 17 and 18 to move with
10 respect to the shaft 12 in such a direction that the
carriage 7, and hence the pressure member 9, is caused
to move towards the anvil 4 until the undulating face
of the pressure member abuts the first portion of the
optical fibre F disposed between the anvil and the
15 pressure member. Thereafter, as rotation of the shaft
12 continues, the coil spring 21 extending between the
transversely extending end wall 20 and the stop 17 is
gradually compressed, thereby to subject the first
portion of the optical fibre F to a gradually increasing
20 pressure and, hence, to microbending of a gradually
increasing extent. If there is a light signal on the
optical fibre F, the gradually increasing pressure
imparted by the pressure member 9 will begin to disturb
the transmission properties of the fibre, causing light
25 to leak from the fibre into its cladding due to
microbending. This light will emerge from the cladding
of the fibre F in the region of one of the second

bending means 6 (depending upon the direction of travel of the light signal in the fibre) and escaping light will be detected by the associated photodetector 8 which will send a signal to the control unit 23. On receipt
5 of a signal from the photodetector 8, the control unit 23 will stop the motor 14 driving the shaft 12 to prevent further compression of the coil spring 21 and hence further increase of the extent of microbending of the first portion of the optical fibre F and,
10 subsequently, the control unit will cause the motor to drive the shaft in the opposite rotational direction, initially to cause the longitudinally spaced stops 17 and 18 to move with respect to the rotatably driven shaft 12 in the opposite direction until the pressure to
15 which the first portion of the optical fibre is subjected is substantially zero and, thereafter, the longitudinally spaced stops and the rigid arm will continue to move in this opposite direction so that the carriage 7, and hence the pressure member 9, move away
20 from the anvil 4 to enable the optical fibre F to be removed and replaced by another optical fibre.

As the coil spring 21 is being gradually compressed and at a position at which the pressure member 9 initially comes into contact with the first portion of
25 the optical fibre F and hence the extent of microbending is insufficient for a signal to be detected by a photodetector 8, movement of the pressure head is

temporarily arrested for a predetermined period of time of approximately one second to enable the electronics of the handtool to be automatically calibrated, thereby to compensate for any drift that may otherwise result from
5 changes in temperature or other causes.

If the the optical fibre F has been subjected to a predetermined maximum pressure and, hence, to a predetermined maximum amount of microbending and no signal has been received from a photodetector 8, then
10 the third microswitch of the control unit constituting the second detecting means will actuate to stop the motor 14 rotatably driving the shaft 12 and so prevent further increase in the extent of microbending of the first portion of the fibre; an appropriate signal is
15 also sent to the display 24. When the motor has stopped, the first portion of the optical fibre F is subjected to this maximum pressure and, hence, to its predetermined maximum amount of microbending, for a predetermined period of time of
20 approximately three seconds before the motor is caused to drive the shaft in the opposite rotational direction to relieve the pressure on the first portion of the optical fibre as previously described.

Claims:

1. A handtool for detecting whether or not an optical fibre is carrying a light signal, which handtool comprises a housing of such a shape and size that it can be held in the hand; first bending means for subjecting a first portion of an optical fibre to microbending of a gradually increasing extent, which first bending means comprises an anvil fixedly secured in the housing, a pressure member so mounted in the housing that the pressure member is constrained to move towards or away from a face of the anvil in a rectilinear direction substantially normal to said face, said face of the anvil and/or the pressure-imparting face of the pressure member including one or more than one undulation, and a motor-driven operating mechanism mounted in the housing for causing the pressure member to move towards or away from the anvil so that when said first portion of an optical fibre is positioned between the pressure member and the anvil and the pressure member is caused to move towards the anvil said first portion of the optical fibre will be constrained between the anvil and the pressure member and will be subjected to microbending of a gradually increasing extent; second bending means which is fixedly secured in the housing adjacent the anvil and which will cause a second portion of said optical fibre to be subjected to macrobending to a predetermined fixed extent; first detecting means for



detecting light escaping from the fibre, the first detecting means being mounted in the housing in the vicinity of the second bending means; second detecting means mounted in the housing for detecting when said first portion of the fibre has been subjected to a predetermined amount of microbending; and, operatively coupled to the first and second detecting means and to the motor driving the operating mechanism of the first bending means, a control unit which will give a first output indication on receipt of a signal from the first detecting means, the arrangement being such that, on receipt of a signal from the first detecting means, the control unit will stop the motor causing said movement of the pressure member towards the anvil to prevent further increase of the extent of microbending of said first portion of the fibre and that, if the second detecting means detects that said first portion of the fibre has been subjected to its predetermined maximum amount of microbending and no signal has been received from the first detecting means, a signal is sent to the control unit which will stop the motor causing said movement of the pressure member towards the anvil to prevent further increase in the extent of microbending of said first portion of the fibre and will give a second output indication.



2. A handtool as claimed in Claim 1, wherein the motor-driven operating mechanism comprises a screw-threaded shaft which is so supported in the housing that it extends in a direction substantially parallel to the direction of motion of the pressure member and which can be rotatably driven about its axis by said motor in either rotational direction; two stops in screw-threaded engagement with and longitudinally spaced on the shaft a predetermined fixed distance apart; a substantially rigid elongate member which is secured to and extends from the pressure member in a direction substantially parallel to the shaft and which is so keyed to the stop nearer the pressure member that, when the shaft is rotationably driven about its axis, said elongate member is restrained against rotational movement and said elongate member and said longitudinally spaced stops are constrained to move in said direction with respect to the shaft, the elongate member having an end wall extending transversely of the shaft intermediate of said stops; and a coil spring which surrounds the shaft and extends between and is secured at its ends to said transversely extending end wall and the stop nearer the pressure member, the arrangement being such that, as the shaft is rotatably driven by the motor in one rotational direction, the elongate member and the longitudinally spaced stops are constrained to move with respect to the shaft in



such a direction that the pressure member is caused to move towards the anvil initially until it abuts the first portion of an optical fibre disposed between the anvil and pressure member, and, thereafter, as the coil spring extending between said transversely extending end wall and the stop nearer the pressure member is gradually compressed, thereby to subject said first portion of the optical fibre to a gradually increasing pressure and, hence, to microbending of a gradually increasing extent, on receipt of a signal from the first detecting means, the control unit will stop the motor rotatably driving the shaft to prevent further compression of the coil spring and hence further increase of the extent of microbending of said first portion of the optical fibre and, subsequently, the control unit will cause the motor to drive the shaft in the opposite rotational direction to cause the longitudinally spaced stops to move with respect to the rotatably driven shaft in the opposite direction, initially until the pressure to which said first portion of optical fibre is subjected is substantially zero and, thereafter, until the pressure member has moved away from the anvil sufficiently to enable the optical fibre to be removed; and that, if the second detecting means detects that said first portion of the fibre has been subjected to its predetermined maximum amount of microbending and no signal has been received from the first detecting means, a signal is sent to the control unit which will stop the motor rotatably driving the shaft and will cause the



motor to drive the shaft in the opposite rotational direction to cause the pressure member to move away from the anvil sufficiently to enable the optical fibre to be removed.

3. A handtool as claimed in Claim 2, wherein, if the second detecting means detects that the fibre has been subjected to a predetermined maximum pressure and, hence to its predetermined maximum amount of microbending and no signal has been received from the first detecting means, the control unit will cause the motor to stop for a predetermined period of time so that said first portion of the optical fibre will be subjected to said maximum pressure and, hence, to its predetermined maximum amount of microbending for said predetermined period of time before the control unit causes the motor to drive the shaft in the opposite rotational direction to relieve the pressure on said first portion of the optical fibre.

4. A handtool as claimed in Claim 2 or 3, wherein, as the coil spring is being gradually compressed and at a position at which the pressure to which said first portion of an optical fibre and hence the extent of microbending is insufficient for a signal to be detected by the first detecting means, the control unit will cause movement of the longitudinally spaced stops to be temporarily arrested for a predetermined period of time sufficient to enable the electronics of the handtool to



be automatically calibrated, thereby to compensate for any drift that may have resulted from changes in temperature or other causes.

5. A handtool as claimed in any one of Claims 2 to 4, wherein each of the stops is releasably locked on the shaft so that the fixed distance between them can be adjusted as may be required to set a predetermined maximum pressure, and hence a predetermined extent of microbending, to which an optical fibre is to be subjected.

6. A handtool as claimed in any one of the preceding Claims, wherein the handtool includes two second bending means which are fixedly secured in the housing adjacent transversely opposite sides of the anvil, each of which second bending means will cause one of two second portions of said optical fibre to be subjected to macrobending to a predetermined fixed extent, a first detecting means being mounted in the housing in the vicinity of each second bending means.

7. A handtool as claimed in Claim 6, wherein the anvil and said two second bending means are parts of a single plate of glass having an edge of a smoothly curved arcuate shape, a central part of said curved edge constituting the anvil and adjoining parts of said edge on opposite sides of the anvil constituting the two second bending means.



24.

8. A handtool as claimed in any one of the preceding Claims, wherein the pressure member is secured in a carriage which is separately formed with respect to the pressure member and which is so mounted in the housing that the carriage, and hence the pressure member secured therein, is constrained to move towards or away from said face of the anvil in said rectilinear direction substantially normal to said face.

9. A handtool as claimed in Claim 8, wherein the carriage also carries on transversely opposite sides of the pressure member bodies of rubber or rubber-like material which, when the pressure member imparts pressure on said first portion of an optical fibre constrained between the anvil and the pressure member, will press said second portions of the fibre against the two second bending means.

10. A handtool as claimed in Claim 8 or 9, wherein the pressure member is adjustably secured in the carriage in such a way that the position of the pressure member with respect to the carriage can be adjusted to and locked in one of a limited number of positions lying along a line substantially parallel to the direction of motion of the carriage.

11. A handtool for detecting whether or not an optical fibre is carrying a light signal substantially as hereinbefore described with reference to and as shown in the accompanying drawings.
