

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 June 2008 (26.06.2008)

PCT

(10) International Publication Number
WO 2008/075067 A1

(51) International Patent Classification:
A61F 6/04 (2006.01)

(74) Agent: **CRAIG, Turner, R.**; A.A. Thornton & Co, 235
High Holborn, London WC1V 7LE (GB).

(21) International Application Number:
PCT/GB2007/004914

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
20 December 2007 (20.12.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0625551.7 21 December 2006 (21.12.2006) GB

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **LRC PRODUCTS LIMITED** [GB/GB]; 205 Science Park, Milton Road, Cambridge CB4 0GZ (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HILL, David, Michael** [GB/GB]; 7 Markwells, Elsenham, Bishops Stortford, Hertfordshire CM22 6LT (GB). **BRODIN, Christophe** [FR/GB]; 225 The Sycamores, Milton, Cambridge, Cambridgeshire CB24 6ZD (GB).

Published:

— *with international search report*

(54) Title: THIN CONDOM

(57) Abstract: A condom comprises natural rubber and polyurethane. Preferably, the condom has a single wall thickness of less than 55 μm . More preferably the condom has a single wall thickness of less than 55 μm and a burst pressure of 1.0kPa or above. A process for making the condom comprises mixing polyurethane and natural rubber latex and forming a condom therefrom.

WO 2008/075067 A1