

Method and Device for Transmitting System Information

Technical Field

Embodiments of the present invention relate to the communication field, in particular to a
5 method and a device for transmitting system information in the communication field.

Background

In the design of the Long Term Evolution (LTE) system, the bandwidth for a base station
to send system information can only be applied to a terminal device for which the minimum
10 bandwidth is applicable, which will cause the transmission of the system information to be
limited by resources.

Summary

Embodiments of the present invention provide a method and a device for transmitting
15 system information, which can improve flexibility of transmitting the system information.

In a first aspect, a method for transmitting system information is provided. The method
includes: determining a resource for sending the system information by a network device, and
sending the system information on the resource for sending the system information by the
network device.

20 In an embodiment of the present invention, the network device can determine the resource
for sending the system information. The network device can send the system information on the
determined resource for sending the system information. In this way, the terminal device can
receive, according to its own capability, the system information on the resource where the
network device sends the system information. For example, if the terminal device supports
25 relatively wide bandwidth, the terminal device can obtain the system information through once
receiving on the resource where the network device sends the system information. If the
terminal device supports relatively narrow bandwidth, the terminal device can sequentially
receive the system information sent by the network device on the bandwidth supported by the

terminal device.

Optionally, the network device can send the system information through broadcast and/or multicast and/or unicast.

Optionally, determining the resource for sending the system information by the network device may include expanding, by the network device, a current resource for sending system information to obtain an expanded resource, and determining the expanded resource as the resource for sending system information. Optionally, the network device can send a part of the system information on a current resource for sending system information and send a remaining part of the system information on an expanded resource.

Optionally, the system information may be all system information that the network device needs to send to at least one terminal device, or may be part of system information that the network device sends to the at least one terminal device. For example, the system information may be a Master Information Block (MIB) in the LTE. In other words, a resource determined by the network device may be used for sending part or all of system information, such as all or part of system information of System Information Block (SIB) 1, SIB 2, SIB 3, SIB 4, SIB 5, SIB 6, SIB 7, SIB 8, etc. in LTE. Optionally, the system information may be all or part of system information in a future communication system. The classification of system information in the future communication system may adopt the classification manner of system information in the LTE system, or may adopt other classification manners of system information. Embodiments of the present invention are not limited thereto. The system information of the future communication system includes the content contained in the system information in the LTE, but is not limited to the content contained in the system information in the LTE, and may also include other content. Embodiments of the present invention are not limited thereto.

In some implementations, before sending the system information on the resource for sending the system information by the network device, the method further includes: sending first indication information to at least one terminal device by the network device, wherein the first indication information is used for the at least one terminal device to determine the resource for sending the system information.

In some implementations, the first indication information is used for indicating location of

the resource where the network device sends the system information, or the first indication information is used for indicating starting location of the resource where the network device sends the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block.

5 Optionally, the first indication information which indicates the resource where the network device sends the system information may indicate locations of several resources, and the sizes of the locations of the several resources may vary. Optionally, the first indication information may indicate that the resource where the network device sends the system information is a specific resource selected from a set of resources. Embodiments of the present
10 invention are not limited thereto.

 In an embodiment of the present invention, the first indication information may be used to indicate the location of the resource where the network device sends the system information. The at least one terminal device determines, according to the resource where the network device sends the system information and which is indicated by the first indication information,
15 the resource for receiving the system information. When the first indication information is used for indicating the starting location of the resource where the network device sends the system information, and at least one of the time domain width of the resource block and the frequency domain width of the resource block, the at least one terminal device can determine a time domain resource for receiving the system information according to the starting location of the
20 resource and the time domain width of the resource block. The at least one terminal device can determine a frequency domain resource for receiving the system information according to the starting location of the resource and the frequency domain width of the resource block. The at least one terminal device can determine a time domain and frequency domain resource for receiving the system information according to the starting location of the resource, the time
25 domain width of the resource block and the frequency domain width of the resource block.

 In some implementations, the first indication information is further used for indicating a transmission periodicity for the network device to send the system information, and/or the first indication information is further used for indicating content information contained in the system information.

In some implementations, the first indication information is further used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information.

5 In an embodiment of the present invention, when the first indication information indicates that the at least one terminal device needs to receive the system information on the resource for sending the system information, the at least one terminal device receives the system information. Specifically, the system information can be received according to the first indication information. When the first indication information indicates that the at least one terminal device does not need to receive the system information on the resource for sending the system
10 information, the at least one terminal device does not receive the system information on the resource for sending the system information.

In some implementations, the first indication information is further used for indicating location of a resource where the network device sends control information of the system information, or the first indication information is used for indicating starting location of the
15 resource where the network device sends control information of the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block.

Optionally, the first indication information which indicates the resource where the network device sends the control information of the system information may indicate locations
20 of several resources, and the sizes of the locations of the several resources may vary. Optionally, the first indication information may indicate that the resource where the network device sends the control information of the system information is a specific resource selected from a set of resources. Embodiments of the present invention are not limited thereto.

In an embodiment of the present invention, the first indication information may also
25 indicate the resource where the network device sends the control information of the system information. In this way, the at least one terminal device receives, according to the indication of the first indication information, the control information of the system information on the resource for sending the control information of the system information. When the at least one terminal device receives the control information of the system information, the resource for

receiving the system information can be determined according to a resource indicated by the control information of the system information, and then the system information can be received according to the determined resource for receiving the system information.

5 In some implementations, the control information of the system information is further used for indicating a transmission periodicity for the network device to send the system information, and/or the control information of the system information is further used for indicating content information contained in the system information sent by the network device.

10 In some implementations, the control information of the system information is further used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information. When the control information of the system information indicates that the at least one terminal device needs to receive the system information on the resource for sending the system information, the at least one terminal device receives the system information on the resource for sending the system information. When the control information of the system information indicates that the at least one terminal
15 device does not need to receive the system information on the resource for sending the system information, the at least one terminal device does not need to receive the system information on the resource for sending the system information.

In some implementations, sending the first indication information to the at least one terminal device by the network device includes: sending the first indication information to the
20 at least one terminal device by the network device through synchronization information.

In some implementations, determining the resource for sending the system information by the network device includes: determining the resource for sending the system information by the network device according to preconfigured information.

25 In an embodiment of the present invention, the configured information may be specified in a protocol or determined by negotiation between the network device and the at least one terminal device. Embodiments of the present invention are not limited thereto.

In some implementations, the preconfigured information is used for indicating a calculation method of the resource where the network device sends the system information.

In other words, the network device calculates the resource, where the network device

sends the system information, according to the method which is indicated by the preconfigured information and which is used for calculating the resource where the network device sends the system information.

5 In some implementations, the configured information is used for indicating a calculation method of the resource where the network device sends control information of the system information.

10 In other words, the network device calculates the resource, where the network device sends the control information of the system information, according to the method which is indicated by the preconfigured information and which is used for calculating the resource where the network device sends the control information of the system information.

In some implementations, the system information includes second indication information, and the second indication information is used for indicating resources for the at least one terminal device to receive other system information than the system information.

15 In an embodiment of the present invention, when the system information is part of the system information sent by the network device, the network device can indicate, in the system information, the resource for the remaining system information not sent to the at least one terminal device. In this way, the at least one terminal device receives the system information, determines the resource for the remaining system information according to the second indication information included in the system information. The other system information herein
20 can be understood as the remaining system information that the network device has not sent to the at least one terminal device yet.

In some implementations, the second indication information is further used for indicating an order in which the at least one terminal device receives the other system information, and/or the second indication information is further used for indicating content information of the other
25 system information.

In an embodiment of the present invention, when the system information is part of the system information sent by the network device, the network device can indicate, in the system information through the second indication information, the transmission sequence for the remaining system information not sent to the at least one terminal device. In this way, when

receiving the system information, the at least one terminal device determines the reception sequence for the remaining system information according to the second indication information included in the system information. The at least one terminal device receives the remaining system information according to the reception sequence. The other system information herein
5 can be understood as the remaining system information that the network device has not sent to the at least one terminal device yet.

In some implementations, the system information is a master information block.

In an embodiment of the present invention, if the system information is the master information block, since the master information block includes the most important system
10 information, such as system bandwidth, system frame number, selection information, initial access information, etc. The master information block may also include information of a base station. In this way, the at least one terminal device can be ensured to normally receive the master system information block.

Optionally, the master information block is further used for indicating whether the at least
15 one terminal device needs to receive the remaining system information not sent by the network device, on the resource for sending the system information.

In a second aspect, a method for transmitting system information is provided. The method includes: receiving system information on a configured first resource by a terminal device.

In an embodiment of the present invention, the first resource where the terminal device
20 receives the system information is configurable. It is avoided that in the prior art, regardless of whether the terminal device is a narrow-band terminal device or a wide-band terminal device, the system information is received on a certain resource for receiving the system information. In an embodiment of the present invention, the first resource where the terminal device receives the system information is configurable. For example, the first indication information sent by the
25 network device can be received to preform configuration of the first resource. Optionally, the terminal device can determine the first resource according to preconfigured information specified in a protocol. When the bandwidth supported by the terminal device is relatively wide, the terminal device can simultaneously receive the system information on a frequency domain resource that is relatively wide. When the bandwidth supported by the terminal device is narrow,

the terminal device can sequentially receive the system information on the narrow bandwidth. This improves the flexibility of the terminal device for receiving the system information, and thus the resource where the terminal device receives the system information is not limited. Assuming that the network device sends multiple pieces of system information on a relatively
5 wide bandwidth, and the terminal device supports a relatively wide bandwidth, in the prior art, the terminal device still needs to sequentially receive the system information sent by the network device in a narrow band, which thus causes a long time delay in receiving the system information. While the terminal device in the embodiment of the present invention can simultaneously receive the multiple pieces of system information on the first resource, thus
10 reducing the time delay in receiving the system information by the terminal device.

Optionally, the terminal device receives the system information sent by the network device on a configured first resource.

Optionally, the system information may be all system information that the network device needs to send to the terminal device, or may be part of system information that the network
15 device sends to the terminal device. For example, the system information may be an MIB. In other words, a resource determined by the network device may be used for sending part or all of system information, such as all or part of system information of SIB 1, SIB 2, SIB 3, SIB 4, SIB 5, SIB 6, SIB 7, SIB 8, etc. in LTE. Optionally, the system information may be all or part of system information in a future communication system.

20 In an embodiment of the present invention, before receiving the system information on the configured first resource by the terminal device, the method further includes: receiving first indication information by the terminal device, and determining the first resource according to the first indication information by the terminal device.

Optionally, the terminal device can receive the first indication information through
25 synchronization information.

Optionally, the terminal device can receive a part or all of the system information through broadcast and/or multicast and/or unicast of the network device.

In an embodiment of the present invention, the terminal device can receive the first indication information, and determine the first resource according to the first indication

information. More specifically, the terminal device can receive the first indication information sent by the network device. Optionally, the terminal device can receive the first indication information sent by other network devices. Embodiments of the present invention are not limited thereto.

5 In some implementations, the first indication information is used for indicating location of the resource for sending the system information, or the first indication information is used for indicating starting location of the resource for sending the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block. Determining the first resource according to the first indication information by the terminal
10 device includes: determining, by the terminal device, the first resource according to the location of the resource for sending the system information indicated by the first indication information; or determining, by the terminal device, the first resource according to the starting location of the resource for sending the system information, and at least one of the time domain width of the resource block and the frequency domain width of the resource block, indicated by the first
15 indication information.

 Specifically, when the first indication information is used for indicating the starting location of the resource for sending the system information, and at least one of the time domain width of the resource block and the frequency domain width of the resource block, the terminal device can determine a time domain resource for receiving the system information according to
20 the starting location of the resource and the time domain width of the resource block. The terminal device can determine a frequency domain resource for receiving the system information according to the starting location of the resource and the frequency domain width of the resource block. The terminal device can determine a time domain and frequency domain resource for receiving the system information according to the starting location of the resource,
25 the time domain width of the resource block and the frequency domain width of the resource block.

 Optionally, the first indication information which indicates the resource for sending the system information may indicate locations of several resources, and the sizes of the locations of the several resources may vary. Optionally, the first indication information may indicate that

the resource for sending the system information is a specific resource selected from a set of resources. Embodiments of the present invention are not limited thereto.

In some implementations, the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first indication
5 information is further used for indicating content information contained in the system information.

For example, the first indication information may also indicate a transmission periodicity for the network device to send an MIB, or a transmission periodicity for an SIB1. Optionally, the first indication information may indicate transmission periodicities for all system
10 information. The transmission periodicities for multiple pieces of system information may be the same or different. Embodiments of the present invention are not limited thereto. In this way, the at least one terminal device may periodically receive the corresponding system information according to the transmission periodicity of the system information. For example, the first indication information may also indicate that the MIB includes such content information as
15 system frame number, downlink system bandwidth, Physical Hybrid ARQ Indicator Channel (PHICH), etc. For example, the content information may be indicated by identification information. For another example, the first indication information may also indicate that the SIB1 includes Public Land Mobile Network Identity (PLMN-ID), Temporal Access Control (TAC), Cell ID (Cell ID), cell selection information, etc. For another example, the first
20 indication information may also indicate that the SIB includes Automatic Call Back (ACB), and common access resources, etc.

In some implementations, the first indication information is further used for indicating location of a resource for sending control information of the system information, or the first indication information is used for indicating starting location of a resource for sending control
25 information of the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block. Determining the first resource according to the first indication information by the terminal device includes: determining, by the terminal device, the resource for sending the control information of the system information according to the location of the resource for sending the control information of the system

information indicated by the first indication information, or according to the starting location of the resource for sending the control information of the system information, and at least one of the time domain of the resource block and the frequency domain width of the resource block, indicated by the first indication information; receiving, by the terminal device, the control
5 information of the system information on the resource for sending the control information of the system information; and determining, by the terminal device, the first resource according to a resource indicated by the control information of the system information.

Optionally, the first indication information which indicates the resource for sending the control information of the system information may indicate locations of several resources, and
10 the sizes of the locations of the several resources may vary. Optionally, the first indication information may indicate that the resource for sending the control information of the system information is a specific resource selected from a set of resources. Embodiments of the present invention are not limited thereto.

In some implementations, the control information of the system information is further
15 used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content information contained in the sent system information. Of course, the control information of the system information can also be used for indicating the order in which the system information is sent, and the embodiments of the present invention are not limited thereto.

In some implementations, the control information of the system information is further
20 used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information. When the control information of the system information indicates that the terminal device needs to receive the system information on the resource for sending the system information, the terminal device receives the
25 system information on the resource for sending the system information. When the control information of the system information indicates that the terminal device does not need to receive the system information on the resource for sending the system information, the terminal device does not need to receive the system information on the resource for sending the system information.

In some implementations, receiving the first indication information by the terminal device includes receiving the first indication information through synchronization information by the terminal device.

5 In some implementations, the first indication information is further used for indicating whether the terminal device needs to send the system information on the first resource for sending. Determining the resource according to the first indication information by the terminal device includes: determining the first resource according to the first indication information by the terminal device when the first indication information is further used for indicating that the terminal device needs to send the system information on the first resource.

10 In some implementations, before receiving the system information on the configured first resource by the terminal device, the method further includes: determining the first resource according to preconfigured information by the terminal device.

15 In an embodiment of the present invention, the configured information may be specified in a protocol or determined by negotiation between the network device and the at least one terminal device. Embodiments of the present invention are not limited thereto.

20 In some implementations, the preconfigured information is used for indicating a calculation method of the first resource. Determining the first resource according to the preconfigured information by the terminal device includes: determining, by the terminal device, the first resource according to the calculation method of the first resource indicated by the preconfigured information.

25 In some implementations, the configured information is used for indicating a calculation method of the resource for sending control information of the system information. Determining the first resource according to the preconfigured information by the terminal device includes: calculating, by the terminal device, the resource for sending the control information of the system information according to the calculation method of the resource for sending the control information of the system information indicated by the preconfigured information; receiving, by the terminal device, the control information of the system information on the resource for sending the control information of the system information; and determining, by the terminal device, the first resource according to a resource indicated by the control information of the

system information.

In some implementations, receiving system information on the configured first resource by the terminal device includes: receiving the system information simultaneously or sequentially by the terminal device according to its own supported bandwidth.

5 In an embodiment of the present invention, when the bandwidth supported by the terminal device is relatively wide, and the first resource is a resource with a relatively wide bandwidth, if the network device sends multiple pieces of system information on the first resource, the terminal device can simultaneously receive the multiple pieces of system information on the first resource. When the bandwidth supported by the terminal device is relatively narrow, and
10 the first resource is a relatively wide resource, if the terminal device sends multiple pieces of system information on the first resource, the terminal device can sequentially receive the multiple pieces of system information on the first resource. Specifically, the multiple pieces of system information may be received according to an order indicated by the second indication information.

15 In some implementations, the system information includes second indication information, and the second indication information is used for indicating to the terminal device resources for receiving other system information than the system information. After receiving the system information on the configured first resource by the terminal device, the method further includes: receiving, by the terminal device, the other system information on the resources for receiving
20 the other system information than the system information according to the second indication information.

In an embodiment of the present invention, when the system information is part of the system information sent by the network device, the network device can indicate, in the system information, the resource for the remaining system information not sent to the terminal device.
25 In this way, the terminal device receives the system information, determines the resource for the remaining system information according to the second indication information included in the system information. The other system information herein can be understood as the remaining system information that the network device has not sent to the terminal device yet.

In some implementations, the second indication information is further used for indicating

an order in which the terminal device receives the other system information, and/or the second indication information is further used for indicating content information of the other system information.

In an embodiment of the present invention, when the system information is part of the system information sent by the network device, the network device can indicate, in the system information through the second indication information, the transmission sequence for the remaining system information not sent to the terminal device. In this way, when receiving the system information, the terminal device determines the reception sequence for the remaining system information according to the second indication information included in the system information. The terminal device receives the remaining system information according to the reception sequence. The other system information herein can be understood as the remaining system information that the network device has not sent to the terminal device yet.

In some implementations, the system information is a master information block.

Optionally, the master information block is further used for indicating whether the terminal device needs to receive the remaining system information not sent on the resource for sending the system information.

In a third aspect, an apparatus for transmitting system information is provided for performing the method in the first aspect or any possible implementation mode of the first aspect described above. Specifically, the apparatus includes units for performing the method in the first aspect or any possible implementation mode of the first aspect described above.

In a fourth aspect, an apparatus for transmitting system information is provided for performing the method in the second aspect or any possible implementation mode of the second aspect described above. Specifically, the apparatus includes units for performing the method in the second aspect or any possible implementation mode of the second aspect described above.

In a fifth aspect, an apparatus for transmitting system information is provided. The apparatus may include a transceiver and a processor. The terminal device may perform the method of the first aspect or the method in any one of optional implementations of the first aspect.

In a six aspect, a system for transmitting system information is provided. The system

includes: the apparatus of the fourth aspect or the apparatus in any one of optional implementations of the fourth aspect, and the apparatus of the fifth aspect or the apparatus in any one of optional implementations of the fifth aspect.

5 In a seventh aspect, an apparatus for transmitting system information is provided. The apparatus may include a transceiver and a processor. The terminal device may perform the method of the second aspect or the method in any one of optional implementations of the second aspect.

10 In an eighth aspect, a computer readable medium is provided. The computer readable medium stores program codes executable by a terminal device, and the program codes include instructions for executing the method of the first aspect or the method in any one of the various implementations of the first aspect.

15 In a ninth aspect, a computer readable medium is provided. The computer readable medium stores program codes executable by a network device, and the program codes include instructions for executing the method of the second aspect or the method in any one of the various implementations of the second aspect.

Brief Description of Drawings

FIG. 1 is a schematic diagram of a method for transmitting system information according to an embodiment of the present invention.

20 FIG. 2 is a schematic diagram of another method for transmitting system information according to an embodiment of the present invention.

FIG. 3 is a schematic diagram of another method for transmitting system information according to an embodiment of the present invention.

25 FIG. 4 is a schematic diagram of another method for transmitting system information according to an embodiment of the present invention.

FIG. 5 is a schematic diagram of another method for transmitting system information according to an embodiment of the present invention.

FIG. 6 is a schematic diagram of another method for transmitting system information

according to an embodiment of the present invention.

FIG. 7 is a schematic diagram of a device for transmitting system information according to an embodiment of the present invention.

FIG. 8 is a schematic diagram of another device for transmitting system information
5 according to an embodiment of the present invention.

FIG. 9 is a schematic diagram of a system for transmitting system information according to an embodiment of the present invention.

FIG. 10 is a schematic diagram of a device for transmitting system information according to an embodiment of the present invention.

10 FIG. 11 is a schematic diagram of another device for transmitting system information according to an embodiment of the present invention.

Detailed Description

It should be understood that the technical schemes of the embodiments of the present
15 invention may be applied to various communication systems, such as a Global System of Mobile communication (GSM) system, a Code Division Multiple Access (CDMA) system, a Wideband Code Division Multiple Access (WCDMA) system, a General Packet Radio Service (GPRS) system, an LTE system, an LTE Frequency Division Duplex (FDD) system, an LTE Time Division Duplex (TDD) system, a Universal Mobile Telecommunication System (UMTS),
20 a Worldwide Interoperability for Microwave Access (WiMAX) communication system, or other communication systems that may emerge in future.

It should also be understood that in embodiments of the present invention, a terminal device may be referred to as a User Equipment (UE), a terminal equipment, a Mobile Station (MS), a Mobile Terminal, or a terminal device in the future 5G network, etc. The terminal
25 device may communicate with one or more core networks via a Radio Access Network (RAN). For example, the terminal may be a mobile phone (or called "cellular" phone) or a computer with a mobile terminal, etc. For another example, the terminal may be a portable, pocket-sized, hand-held, built-in-computer, or vehicle-mounted mobile device that exchanges voice and/or

data with a wireless access network.

A network device may be used for communicating with mobile devices. The network device may be a Base Transceiver Station (BTS) in Global System of Mobile Communication (GSM) or Code Division Multiple Access (CDMA), or a base station (NodeB, NB) in
5 Wideband Code Division Multiple Access (WCDMA), or an Evolution Node B (eNB or eNodeB) in LTE, or a relay station or access point, or a vehicle-mounted device or wearable device, or an access network device in future 5G network.

In an embodiment of the present invention, a signal for transmitting system information, which a terminal device may send to a network device may be a preamble. For example, the
10 signal for transmitting system information may be sent on a Physical Random Access Channel (PRACH). After the network device receives the signal, for transmitting system information, sent by the terminal device, the terminal device may send a response (Random Access Response, RAR) for transmitting system information to the network device, where the response
15 for transmitting system information is used for notifying that the terminal device has successfully accessed.

FIG. 1 illustrates a schematic flowchart of a method 100 for transmitting system information according to an embodiment of the present invention. FIG. 1 illustrates acts or operations of a method for transmitting system information provided in an embodiment of the present invention. However, these acts or operations are merely examples, and other operations
20 or variations of the operations shown in FIG. 1 may be performed in embodiments of the present invention. The method 100 includes acts S110 and S120.

In act S110, a network device determines a resource for sending system information.

In act S120, the network device sends the system information on the resource for sending the system information.

FIG. 2 illustrates a schematic flowchart of a method 200 for transmitting system information according to an embodiment of the present invention. FIG. 2 illustrates acts or operations of a method for transmitting system information provided in an embodiment of the present invention. However, these acts or operations are merely examples, and other operations
25 or variations of the operations shown in FIG. 2 may be performed in embodiments of the

present invention. The method 200 includes act S210.

In act S210, a terminal device receives system information on a configured first resource.

It should be understood that the first resource in act S210 may be the resource for sending the system information in act S110.

5 Therefore, the network device can determine the resource for sending the system information, and the network device can send the system information on the determined resource for sending the system information. In this way, the terminal device can receive, according to its own capability, the system information on the resource where the network device sends the system information. For example, if the terminal device supports relatively
10 wide bandwidth, the terminal device can obtain the system information through once receiving on the resource where the network device sends the system information. If the terminal device supports relatively narrow bandwidth, the terminal device can sequentially receive the system information sent by the network device on the bandwidth supported by the terminal device.

Optionally, act S210 includes: receiving the system information simultaneously or
15 sequentially by the terminal device according to its own supported bandwidth. When the bandwidth supported by the terminal device is relatively wide, and the first resource is a resource with a relatively wide bandwidth, if the network device sends multiple pieces of system information on the first resource, the terminal device can simultaneously receive the multiple pieces of system information on the first resource. When the bandwidth supported by
20 the terminal device is relatively narrow, and the first resource is a relatively wide resource, if the terminal device sends multiple pieces of system information on the first resource, the terminal device can sequentially receive the multiple pieces of system information on the first resource. Specifically, the multiple pieces of system information may be sequentially received according to second indication information.

25 Optionally, the system information may be all system information that the network device needs to send to at least one terminal device, or may be part of system information that the network device sends to the at least one terminal device. For example, the system information may be an MIB in the LTE. In other words, a resource determined by the network device may be used for sending part or all of system information, such as all or part of system information

of SIB1, SIB2, SIB3, SIB4, SIB5, SIB6, SIB7, SIB8, etc. in LTE. Optionally, the system information may be all or part of system information in a future communication system. The classification of system information in the future communication system may adopt the classification manner of system information in the LTE system, or may adopt other
5 classification manners of system information. Embodiments of the present invention are not limited thereto. The system information in the future communication system includes the content contained in the system information in the LTE, but is not limited to the content contained in the system information in the LTE, and may also include other content. Embodiments of the present invention are not limited thereto. It should be understood that the
10 terminal device in act S210 may be any one terminal device among the at least one terminal device.

The manners in which the terminal device determines the first resource may be divided into two parts. The first part is that the first resource is determined according to first indication information that is sent. The second part is that the network device determines the resource for
15 sending the system information according to preconfigured information, and the terminal device determines the first resource for receiving the system information according to the preconfigured information.

In the first part, the network device sends the first indication information to the terminal device, and the terminal device determines the first resource according to the first indication
20 information. The content related to the first part is described below.

In an optional embodiment, before act S110, the method 100 further includes: sending the first indication information to the at least one terminal device by the network device, wherein the first indication information is used for the at least one terminal device to determine the resource for sending the system information. Before act S210, the method 200 further includes:
25 receiving the first indication information by the terminal device, and determining the first resource according to the first indication information by the terminal device. Specifically, the terminal device receives the first indication information sent by the network device. For example, as shown in FIG. 3, the box labeled with “1” in FIG. 3 represents a resource for sending the first indication information, such as a resource for synchronization information. For

example, the first indication information may be sent through system information, and the boxes labeled with “3” in FIG. 3 represent the resources for sending the system information to the at least one terminal device by the network device, and the resources where the terminal device receives the system information.

5 Optionally, the network device sends the first indication information to the at least one terminal device through the synchronization information, the terminal device receives the first indication information through the synchronization information.

Specifically, in order to enable the at least one terminal device to receive the system information on correct resources, the network device may use the first indication information to
10 notify the at least one terminal device of the resource where the network device sends the system information. For example, the first indication information may be sent to the at least one terminal device through the synchronization information, and the at least one terminal device determines, according to the first indication, the resource for receiving the system information. In this way, the at least one terminal device can receive, according to the bandwidth supported
15 by itself and the first indication information, the system information that the network device sends through broadcast and/or multicast and/or unicast, thereby improving the flexibility of the network device for sending the system information and the flexibility of the at least one terminal device for receiving the system information.

Optionally, the first indication information is further used for indicating whether the at
20 least one terminal device needs to receive the system information on the resource for sending the system information. Determining the resource according to the first indication information by the terminal device includes: determining the first resource according to the first indication information by the terminal device when the first indication information is further used for indicating that the at least one terminal device needs to send the system information on the first
25 resource.

It should be understood that control information of the system information or the master information block can also be used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information.

In an optional embodiment, the first indication information is used for indicating location

of the resource where the network device sends the system information, or the first indication information is used for indicating starting location of the resource where the network device sends the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block. Determining the first resource according to the first indication information by the terminal device includes: determining, by the terminal device, the first resource according to the location of the resource for sending the system information indicated by the first indication information; or determining, by the terminal device, the first resource according to the starting location of the resource for sending the system information, and at least one of the time domain width of the resource block and the frequency domain width of the resource block, indicated by the first indication information. Specifically, the first indication information may be used to indicate the location of the resource where the network device sends the system information, and the terminal device determines, according to the resource where the network device sends the system information and which is indicated by the first indication information, the first resource for receiving. When the first indication information is used for indicating the starting location of the resource where the network device sends the system information, and at least one of the time domain width of the resource block and the frequency domain width of the resource block, the terminal device can determine a time domain resource for receiving the system information according to the starting location of the resource and the time domain width of the resource block, and the time domain resource can be considered as the first resource. The terminal device can determine a frequency domain resource for receiving the system information according to the starting location of the resource and the frequency domain width of the resource block, and the frequency domain resource may be considered as the first resource. The terminal device may determine a time domain and frequency domain resource for receiving the system information according to the starting location of the resource, the time domain width of the resource block and the frequency domain width of the resource block, and the time domain and frequency domain resource may be considered as the first resource.

Optionally, the first indication information which indicates the resource where the network device sends the system information may indicate locations of several resources, and the sizes of the locations of the several resources may vary. Optionally, the first indication

information may indicate that the resource where the network device sends the system information is a specific resource selected from a set of resources. Embodiments of the present invention are not limited thereto.

In an optional embodiment, the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first indication information is further used for indicating content information contained in the system information. Particularly, the first indication information is further used for indicating a transmission periodicity for the network device to send the system information.

For example, the first indication information may also indicate a transmission periodicity for the network device to send an MIB, or a transmission periodicity for an SIB1. Optionally, the first indication information may indicate transmission periodicities for all system information. Specifically, the first indication information may also indicate transmission periodicities for all system information or part of system information in a future network system. The transmission periodicities of multiple pieces of system information may be the same or different, but embodiments of the present invention are not limited thereto. In this way, the at least one terminal device may periodically receive the corresponding system information according to the transmission periodicity of the system information. For example, the first indication information may also indicate that the MIB includes such content information as system frame number, downlink system bandwidth, Physical Hybrid ARQ Indicator Channel (PHICH), etc. For example, the content information may be indicated by identification information. For another example, the first indication information may also indicate that the SIB1 includes Public Land Mobile Network Identity (PLMN-ID), TAC, Cell ID, cell selection information, etc. For another example, the first indication information may also indicate that the SIB includes ACB, common access resources, etc.

In an optional embodiment, the first indication information is further used for indicating location of the resource where the network device sends control information of the system information, or the first indication information is used for indicating starting location of the resource where the network device sends control information of the system information, and at least one of time domain width of a resource block and frequency domain width of the resource

block. Determining the first resource according to the first indication information by the terminal device includes: determining, by the terminal device, the resource for sending the control information of the system information according to the location of the resource for sending the control information of the system information indicated by the first indication
 5 information, or according to the starting location of the resource for sending the control information of the system information, and at least one of the time domain of the resource block and the frequency domain width of the resource block, indicated by the first indication information; receiving, by the terminal device, the control information of the system information on the resource for sending the control information of the system information; and
 10 determining, by the terminal device, the first resource according to a resource indicated by the control information of the system information. For example, as shown in FIG. 4, the box labeled with “1” represents a resource for sending the first indication information, such as a resource for synchronization information. The boxes labeled with “2” represent the resources where the network device sends the control information of the system information and which
 15 are indicated by the first indication information. The boxes labeled with “3” represent the resources for sending the system information indicated by the control information of the system information.

Specifically, the first indication information may also indicate the resource where the network device sends the control information of the system information. In this way, the
 20 terminal device receives, according to the indication of the first indication information, the control information of the system information on the resource for sending the control information of the system information. When the terminal device receives the control information of the system information, the resource for receiving the system information can be determined according to the resource indicated by the control information of the system
 25 information, and then the system information can be received according to the determined resource for receiving the system information.

Optionally, the first indication information which indicates the resource where the network device sends the control information of the system information may indicate locations of several resources, and the sizes of the locations of the several resources may vary. Optionally,

the first indication information may indicate that the resource where the network device sends the control information of the system information is a specific resource selected from a set of resources. Embodiments of the present invention are not limited thereto.

5 In an optional embodiment, the control information of the system information is further used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content information contained in the sent system information.

10 In the second part, the network device determines the resource for sending the system information according to preconfigured information, and the terminal device determines the first resource for receiving the system information according to the preconfigured information. The first resource here may be the resource for sending system information. The content related to the second part is described below.

15 In an optional embodiment, act S110 may include determining the resource for sending the system information according to preconfigured information by the network device. Before act S210, the method 200 may include determining the first resource according to preconfigured information by the terminal device. The configured information may be specified in a protocol or determined by negotiation between the network device and the at least one terminal device. Embodiments of the present invention are not limited thereto.

20 In an optional embodiment, the preconfigured information is used for indicating a calculation method of the resource where the network device sends the system information. The network device calculates the resource, where the network device sends the system information, according to the method which is indicated by the preconfigured information and which is used for calculating the resource where the network device sends the system information. Determining the first resource according to the preconfigured information by the terminal
25 device includes: determining, by the terminal device, the first resource according to the calculation method of the first resource indicated by the preconfigured information. For example, as shown in FIG. 5, the boxes labeled with “3” in FIG. 5 represent the resources where the network device sends the system information. The resources where the network device sends the system information are determined according to the preconfigured information.

The terminal device can receive the system information on these resources. Specifically, the terminal device can receive the system information on these resources according to the bandwidth supported by it.

In an optional embodiment, the configured information is used for indicating a calculation
5 method of the resource where the network device sends control information of the system
information. The network device calculates the resource, where the network device sends the
control information of the system information, according to the method which is indicated by
the preconfigured information and which is used for calculating the resource where the network
device sends the control information of the system information. Determining the first resource
10 according to the preconfigured information by the terminal device includes: calculating, by the
terminal device, the resource for sending the control information of the system information
according to the calculation method of the resource for sending the control information of the
system information indicated by the preconfigured information; receiving, by the terminal
device, the control information of the system information on the resource for sending the
15 control information of the system information; and determining, by the terminal device, the first
resource according to a resource indicated by the control information of the system information.
For example, as shown in FIG. 6, the boxes labeled with “2” in FIG. 6 represent resources for
sending and receiving the control information of the system information. The boxes labeled
with “3” in FIG. 6 represent resources for sending and receiving the system information. The
20 network device determines, according to the preconfigured information, the resource where the
network device sends the control information of the system information. The network device
determines, according to the resource for sending the system information indicated by the
control information of the system information, the resource where the network device sends the
system information. The terminal device determines, according to the preconfigured
25 information, the resource for receiving the control information of the system information. The
terminal device receives the system information on the first resource which is used for receiving
the system information and indicated by the control information of the system information.

In an optional embodiment, the system information includes second indication
information, and the second indication information is used for indicating resources for the at

least one terminal device to receive other system information than the system information. After act S210, the method 200 further includes: receiving, by the terminal device, the other system information on the resources for receiving the other system information than the system information according to the second indication information.

5 Specifically, when the system information is part of the system information sent by the network device, the network device can indicate, in the system information, the resource for the remaining system information not sent to the at least one terminal device. In this way, the at least one terminal device receives the system information, determines the resource for the remaining system information according to the second indication information included in the
10 system information. The other system information herein can be understood as the remaining system information that the network device has not sent to the at least one terminal device yet.

 In an optional embodiment, the second indication information is further used for indicating an order in which the terminal device receives the other system information, and/or the second indication information is further used for indicating content information of the other
15 system information. After act S210, the method 200 further includes: receiving, by the terminal device, the other system information in the sequence for receiving the other system information than the system information according to the indication of the second indication information.

 Specifically, when the system information is part of the system information sent by the network device, the network device can indicate, in the system information through the second
20 indication information, the transmission sequence for the remaining system information not sent to the terminal device. In this way, when receiving the system information, the terminal device determines the reception sequence for the remaining system information according to the second indication information included in the system information. The terminal device receives the remaining system information according to the reception sequence. The other system
25 information herein can be understood as the remaining system information that the network device has not sent to the at least one terminal device yet.

 In an optional embodiment, the system information is a master information block. If the system information is the master information block, since the master information block includes the most important system information, such as system bandwidth, system frame number,

selection information, initial access information, etc., the master information block may also include information of a base station. In this way, the at least one terminal device can be ensured to normally receive the master system information block.

5 It should be understood that in Figs. 3 to 6, the x axis represents the time domain (t), and the y axis represents the frequency domain (f).

Fig. 7 is a schematic block diagram of an apparatus 300 for transmitting system information according to an embodiment of the present application. The apparatus may be a network device in the method 100. As shown in Fig. 7, the apparatus 300 includes a determining module 310 and a sending module 320.

10 The determining module 310 is used for determining a resource for sending the system information.

The sending module 320 is used for sending the system information on the resource for sending the system information.

15 In an optional embodiment, the sending module 320 is further used for sending first indication information to at least one terminal device before sending the system information on the resource for sending the system information, wherein the first indication information is used for the at least one terminal device to determine the resource for sending the system information.

20 In an optional embodiment, the first indication information is used for indicating location of the resource for sending the system information, or the first indication information is used for indicating starting location of the resource for sending the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block.

25 In an optional embodiment, the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first indication information is further used for indicating content information contained in the system information.

In an optional embodiment, the first indication information is further used for indicating location of a resource for sending control information of the system information, or the first

indication information is used for indicating starting location of a resource for sending control information of the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block.

5 In an optional embodiment, the control information of the system information is further used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content information contained in the sent system information.

10 In an optional embodiment, the sending module 320 is specifically used for sending the first indication information to the at least one terminal device through synchronization information.

In an optional embodiment, the first indication information is further used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information.

15 In an optional embodiment, the determining module 310 is specifically used for determining the resource for sending the system information according to preconfigured information.

In an optional embodiment, the preconfigured information is used for indicating a calculation method of the resource for sending the system information.

20 In an optional embodiment, the configured information is used for indicating a calculation method of the resource for sending control information of the system information.

In an optional embodiment, the system information includes second indication information, and the second indication information is used for indicating resources for the at least one terminal device to receive other system information than the system information.

25 In an optional embodiment, the second indication information is further used for indicating an order in which the at least one terminal device receives the other system information, and/or the second indication information is further used for indicating content information of the other system information.

In an optional embodiment, the system information is a master information block.

Fig. 8 is a schematic block diagram of an apparatus 400 for transmitting system information according to an embodiment of the present application. The apparatus may be a terminal device in the method 200. As shown in Fig. 8, the apparatus 400 includes a receiving module 410 and a first determining module 420.

5 The receiving module 410 is used for receiving system information on a configured first resource.

 In an optional embodiment, the receiving module 410 is further used for receiving first indication information before receiving the system information on the configured first resource, and the first determining module 420 is used for determining the first resource according to the
10 first indication information.

 In an optional embodiment, the first indication information is used for indicating location of the resource for sending the system information, or the first indication information is used for indicating starting location of the resource for sending the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block.
15 The first determining module 420 is specifically used for determining the first resource according to the location of the resource for sending the system information indicated by the first indication information. Optionally, the first determining module 420 is further specifically used for determining the first resource according to the starting location of the resource for sending the system information, and at least one of the time domain width of the resource block,
20 and the frequency domain width of the resource block, indicated by the first indication information.

 In an optional embodiment, the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first indication information is further used for indicating content information contained in the system
25 information.

 In an optional embodiment, the first indication information is further used for indicating location of a resource for sending control information of the system information, or the first indication information is used for indicating starting location of a resource for sending control information of the system information, and at least one of time domain width of a resource

block and frequency domain width of the resource block. The first determining module 420 is specifically used for determining the resource for sending the control information of the system information according to the location of the resource for sending the control information of the system information indicated by the first indication information, or according to the starting
5 location of the resource for sending the control information of the system information, and at least one of the time domain of the resource block and the frequency domain width of the resource block, indicated by the first indication information. The receiving module 410 is further used for receiving the control information of the system information on the resource for sending the control information of the system information. The first determining module 420 is
10 specifically used for determining the first resource according to a resource indicated by the control information of the system information.

In an optional embodiment, the control information of the system information is further used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content information
15 contained in the sent system information.

In an optional embodiment, the receiving module 410 is specifically used for receiving the first indication information through synchronization information.

In an optional embodiment, the first indication information is further used for indicating whether the apparatus needs to send the system information on the first resource for sending.
20 The first determining module 420 is specifically used for determining the first resource according to the first indication information when the first indication information is further used for indicating that the apparatus needs to send the system information on the first resource.

In an optional embodiment, the apparatus 400 further includes a second determining module, used for determining the first resource according to preconfigured information before
25 receiving the system information on the configured first resource.

In an optional embodiment, the preconfigured information is used for indicating a calculation method of the first resource, the second determining module is specifically used for determining the first resource according to the calculation method of the first resource indicated by the preconfigured information.

In an optional embodiment, the configured information is used for indicating a calculation method of the resource for sending control information of the system information. The second determining module is further specifically used for calculating the resource for sending the control information of the system information according to the calculation method of the resource for sending the control information of the system information indicated by the preconfigured information. The receiving module 410 is further used for receiving the control information of the system information on the resource for sending the control information of the system information. The second determining module is specifically used for determining the first resource according to a resource indicated by the control information of the system information.

In an optional embodiment, the receiving module 410 is further specifically used for receiving the system information simultaneously or sequentially according to bandwidth supported by the apparatus 400.

In an optional embodiment, the system information includes second indication information, and the second indication information is used for indicating resources for the apparatus to receive other system information than the system information. The receiving module 410 is further used for receiving the other system information on the resources for receiving the other system information than the system information according to the second indication information after receiving the system information on the configured first resource.

In an optional embodiment, the second indication information is further used for indicating an order in which the apparatus 400 receives the other system information, and/or the second indication information is further used for indicating content information of the other system information.

In an optional embodiment, the system information is a master information block.

Fig. 9 shows a schematic diagram of a system 500 for transmitting system information provided by an embodiment of the present invention. The system 500 includes the apparatus 300 and the apparatus 400.

Fig. 10 is a schematic block diagram of an apparatus 600 for transmitting system

information according to an embodiment of the present application. For example, the apparatus may be a network device in the method 100. As illustrated in FIG. 10, the apparatus 600 includes a transceiver 610 and a processor 620.

The processor 620 is used for determining a resource for sending the system information.

5 The transceiver 610 is used for sending the system information on the resource for sending the system information.

It should be understood that the apparatus 600 may correspond to the network device in the method 100, and may realize corresponding functions of the network device in the method 100, which will not be described in detail herein for the sake of brevity.

10 Fig. 11 is a schematic block diagram of an apparatus 700 for transmitting system information according to an embodiment of the present application. The apparatus may be a terminal device in the method 200. As illustrated in FIG. 11, the apparatus 700 includes a transceiver 710 and a processor 720. The transceiver 710 is used for receiving system information on a configured first resource.

15 In an optional embodiment, the transceiver 710 is further used for receiving first indication information before receiving the system information on the configured first resource. The processor 720 is used for determining the first resource according to the first indication information.

20 It should be understood that the apparatus 700 may correspond to the terminal device in the method 200, and may realize corresponding functions of the terminal device in the method 200, which will not be described in detail herein for the sake of brevity.

25 It should be understood that in embodiments of the present invention, the processor 620, and the processor 720 may be central processing units (CPU), or other general purpose processors, digital signal processors (DSP), application specific integrated circuits (ASIC), field programmable gate arrays (FPGA) or other programmable logic devices, discrete gate or transistor logic devices, or discrete hardware components, etc. The general purpose processor may be a microprocessor, or the processor may be any conventional processor or the like.

The term "and/or" in this document is merely an association relationship describing associated objects, indicating that there may be three relationships, for example, A and/or B

may indicate three situations: A alone, A and B, and B alone. In addition, the symbol "/" in this document generally indicates that objects of the former and the latter connected by "/" has an "or" relationship.

5 It should be understood that in various embodiments of the present invention, values of sequence numbers of the above-mentioned processes do not indicate an order of execution, and the order of execution of various processes should be determined by their functions and internal logics, and should not constitute any limitation on the execution process of the embodiments of the present invention.

10 Those of ordinary skill in the art will recognize that the exemplary elements and algorithm acts described in connection with the embodiments disclosed herein can be realized in electronic hardware, or a combination of computer software and electronic hardware. Whether these functions are performed in hardware or software depends on specific applications and design constraints of a technical solution. Skilled in the art may use different methods to realize the described functions for each particular application, but such realization should not be
15 considered to be beyond the scope of the present invention.

Those skilled in the art may clearly understand that for convenience and conciseness of description, the specific working process of the system, apparatus and unit described above may refer to the corresponding process in the aforementioned embodiments of methods, and details are not described herein again.

20 In several embodiments provided by the present invention, it should be understood that the disclosed systems, apparatus and methods may be implemented in other ways. For example, the apparatus embodiments described above are only illustrative, for example, the division of the units is only a logical function division, and there may be other division manners in actual implementation, for example, multiple units or components may be combined or integrated into
25 another system, or some features may be ignored or not executed. On the other hand, the mutual coupling or direct coupling or communication connection shown or discussed may be indirect coupling or communication connection through some interface, device or unit, and may be in electrical, mechanical or other forms.

The unit described as a separate unit may or may not be physically separated, and the

component shown as a unit may or may not be a physical unit, i.e., it may be located in one place or may be distributed over multiple network units. Some or all of the units may be selected according to actual needs to achieve the purpose of the embodiments.

5 In addition, various functional units in various embodiments of the present invention may be integrated in one processing unit, or various units may be physically present separately, or two or more units may be integrated in one unit.

10 The functions may be stored in a computer readable storage medium if implemented in the form of software functional units and sold or used as a separate product. Based on this understanding, the technical solution of the present invention, in essence, or the part contributing to the prior art, or the part of the technical solution, may be embodied in the form of a computer software product stored in a storage medium, including a number of instructions for causing a computer device (which may be a personal computer, a server, or a network device) to perform all or part of the acts of the method described in various embodiments of the present invention. The aforementioned storage medium includes U disk, mobile hard disk, 15 read-only memory (ROM), random access memory (RAM), magnetic disk or optical disk, and other medium capable of storing program codes.

20 What are described above are merely exemplary embodiments of the present invention, but the protection scope of the present invention is not limited thereto. Any person skilled in the art may easily conceive variations or substitutions within the technical scope disclosed by the present invention, which should be included within the protection scope of the present invention. Therefore, the protection scope of the present invention should be determined by the scope of the appended claims.

Claims

1. A method for transmitting system information, comprising:

determining, by a network device, a resource for sending the system information; and

sending, by the network device, the system information on the resource for sending the

5 system information.

2. The method of claim 1, wherein before sending, by the network device, the system information on the resource for sending the system information, the method further comprises:

sending, by the network device, first indication information to at least one terminal device, wherein the first indication information is used for the at least one terminal device to determine

10 the resource for sending the system information.

3. The method of claim 2, wherein the first indication information is used for indicating location of the resource where the network device sends the system information, or the first indication information is used for indicating starting location of the resource where the network device sends the system information, and at least one of time domain width of a resource block

15 and frequency domain width of the resource block.

4. The method of claim 3, wherein the first indication information is further used for indicating a transmission periodicity for the network device to send the system information, and/or the first indication information is further used for indicating content information contained in the system information.

20 5. The method of claim 2, wherein the first indication information is further used for indicating location of a resource where the network device sends control information of the system information, or the first indication information is used for indicating starting location of a resource where the network device sends control information of the system information, and at least one of time domain width of a resource block and frequency domain width of the

25 resource block.

6. The method of claim 5, wherein the control information of the system information is further used for indicating a transmission periodicity for the network device to send the system information, and/or the control information of the system information is further used for

indicating content information contained in the system information sent by the network device.

7. The method of any one of claims 2 to 6, wherein sending, by the network device, the first indication information to the at least one terminal device comprises:

5 sending, by the network device, the first indication information to the at least one terminal device through synchronization information.

8. The method of any one of claims 2 to 7, wherein the first indication information is further used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information.

10 9. The method according to claim 1, wherein determining, by the network device, the resource for sending the system information comprises:

determining, by the network device, the resource for sending the system information according to preconfigured information.

15 10. The method according to claim 9, wherein the preconfigured information is used for indicating a calculation method of the resource where the network device sends the system information.

11. The method according to claim 9, wherein the configured information is used for indicating a calculation method of a resource where the network device sends control information of the system information.

20 12. The method according to any one of claims 1 to 11, wherein the system information comprises second indication information, and the second indication information is used for indicating resources for at least one terminal device to receive other system information than the system information.

25 13. The method of claim 12, wherein the second indication information is further used for indicating an order in which the at least one terminal device receives the other system information, and/or the second indication information is further used for indicating content information of the other system information.

14. The method of any one of claims 1 to 13, wherein the system information is a master information block.

15. A method for transmitting system information, wherein the method comprises:
receiving, by a terminal device, system information on a configured first resource.

16. The method of claim 15, wherein before receiving, by the terminal device, the system information on the configured first resource, the method further comprises:

5 receiving, by the terminal device, first indication information; and
determining, by the terminal device, the first resource according to the first indication information.

17. The method of claim 16, wherein the first indication information is used for indicating location of a resource for sending the system information, or the first indication information is
10 used for indicating starting location of the resource for sending the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block;

wherein determining, by the terminal device, the first resource according to the first indication information comprises:

15 determining, by the terminal device, the first resource according to the location of the resource for sending the system information indicated by the first indication information; or

determining, by the terminal device, the first resource according to the starting location of the resource for sending the system information, and the at least one of the time domain width of the resource block and the frequency domain width of the resource block, indicated by the
20 first indication information.

18. The method of claim 17, wherein the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first indication information is further used for indicating content information contained in the system information.

25 19. The method of claim 16, wherein the first indication information is further used for indicating location of a resource for sending control information of the system information, or the first indication information is used for indicating starting location of a resource for sending control information of the system information, and at least one of time domain width of a

resource block and frequency domain width of the resource block;

wherein determining, by the terminal device, the first resource according to the first indication information comprises:

5 determining, by the terminal device, the resource for sending the control information of the system information according to the location of the resource for sending the control information of the system information indicated by the first indication information, or according to the starting location of the resource for sending the control information of the system information, and the at least one of the time domain of the resource block and the frequency domain width of the resource block, indicated by the first indication information;

10 receiving, by the terminal device, the control information of the system information on the resource for sending the control information of the system information; and

determining, by the terminal device, the first resource according to a resource indicated by the control information of the system information.

15 20. The method of claim 19, wherein the control information of the system information is further used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content information contained in the sent system information.

21. The method of any one of claims 16 to 20, wherein receiving, by the terminal device, the first indication information comprises:

20 receiving, by the terminal device, the first indication information through synchronization information.

22. The method of any one of claims 16 to 21, wherein the first indication information is further used for indicating whether the terminal device needs to send the system information on the first resource for sending;

25 wherein determining, by the terminal device, the resource according to the first indication information comprises:

determining, by the terminal device, the first resource according to the first indication information when the first indication information is further used for indicating that the terminal

device needs to send the system information on the first resource.

23. The method of claim 15, wherein before receiving, by the terminal device, the system information on the configured first resource, the method further comprises:

5 determining, by the terminal device, the first resource according to preconfigured information.

24. The method according to claim 23, wherein the preconfigured information is used for indicating a calculation method of the first resource;

wherein determining, by the terminal device, the first resource according to the preconfigured information comprises:

10 determining, by the terminal device, the first resource according to the calculation method of the first resource indicated by the preconfigured information.

25. The method according to claim 23, wherein the configured information is used for indicating a calculation method of a resource for sending control information of the system information;

15 wherein determining, by the terminal device, the first resource according to the preconfigured information comprises:

calculating, by the terminal device, the resource for sending the control information of the system information according to the calculation method of the resource for sending the control information of the system information indicated by the preconfigured information;

20 receiving, by the terminal device, the control information of the system information on the resource for sending the control information of the system information; and

determining, by the terminal device, the first resource according to a resource indicated by the control information of the system information.

26. The method of any one of claims 15 to 25, wherein receiving, by the terminal device, the system information on the configured first resource comprises:

receiving, by the terminal device, the system information simultaneously or sequentially according to bandwidth supported by the terminal device.

27. The method according to any one of claims 15 to 26, wherein the system information comprises second indication information, and the second indication information is used for indicating to the terminal device resources for receiving other system information than the system information;

5 wherein after receiving, by the terminal device, the system information on the configured first resource, the method further comprises:

receiving, by the terminal device, the other system information on the resources for receiving the other system information than the system information according to the second indication information.

10 28. The method of claim 27, wherein the second indication information is further used for indicating an order in which the terminal device receives the other system information, and/or the second indication information is further used for indicating content information of the other system information.

15 29. The method of any one of claims 15 to 28, wherein the system information is a master information block.

30. An apparatus for transmitting system information, comprising:

a determining module, used for determining a resource for sending the system information;
and

20 a sending module, used for sending the system information on the resource for sending the system information.

31. The apparatus of claim 30, wherein the sending module is further used for:

25 sending first indication information to at least one terminal device before sending the system information on the resource for sending the system information, wherein the first indication information is used for the at least one terminal device to determine the resource for sending the system information.

32. The apparatus of claim 31, wherein the first indication information is used for indicating location of the resource for sending the system information, or the first indication information is used for indicating starting location of the resource for sending the system

information, and at least one of time domain width of a resource block and frequency domain width of the resource block.

33. The apparatus of claim 32, wherein the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first
5 indication information is further used for indicating content information contained in the system information.

34. The apparatus of claim 31, wherein the first indication information is further used for indicating location of a resource for sending control information of the system information, or the first indication information is used for indicating starting location of a resource for sending
10 control information of the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block.

35. The apparatus of claim 34, wherein the control information of the system information is further used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content
15 information contained in the sent system information.

36. The apparatus of any one of claims 31 to 35, wherein the sending module is specifically used for:

sending the first indication information to the at least one terminal device through synchronization information.

20 37. The apparatus of any one of claims 31 to 36, wherein the first indication information is further used for indicating whether the at least one terminal device needs to receive the system information on the resource for sending the system information.

38. The apparatus of claim 30, wherein the determining module is specifically used for:
determining the resource for sending the system information according to preconfigured
25 information.

39. The apparatus according to claim 38, wherein the preconfigured information is used for indicating a calculation method of the resource for sending the system information.

40. The apparatus according to claim 38, wherein the configured information is used for

indicating a calculation method of a resource for sending control information of the system information.

41. The apparatus according to any one of claims 30 to 40, wherein the system information comprises second indication information, and the second indication information is
5 used for indicating resources for at least one terminal device to receive other system information than the system information.

42. The apparatus of claim 41, wherein the second indication information is further used for indicating an order in which the at least one terminal device receives the other system information, and/or the second indication information is further used for indicating content
10 information of the other system information.

43. The apparatus of any one of claims 30 to 42, wherein the system information is a master information block.

44. An apparatus for transmitting system information, comprising:

a receiving module, used for receiving system information on a configured first resource.

15 45. The apparatus of claim 44, wherein the receiving module is further used for:

receiving first indication information before receiving the system information on the configured first resource;

wherein the apparatus further comprises:

a first determining module, used for determining the first resource according to the first
20 indication information.

46. The apparatus of claim 45, wherein the first indication information is used for indicating location of a resource for sending the system information, or the first indication information is used for indicating starting location of a resource for sending the system information, and at least one of time domain width of a resource block and frequency domain
25 width of the resource block;

wherein the first determining module is specifically used for determining the first resource according to the location of the resource for sending the system information indicated by the first indication information; or

wherein the first determining module is further specifically used for determining the first resource according to the starting location of the resource for sending the system information, and the at least one of the time domain width of the resource block and the frequency domain width of the resource block, indicated by the first indication information.

5 47. The apparatus of claim 46, wherein the first indication information is further used for indicating a transmission periodicity for sending the system information, and/or the first indication information is further used for indicating content information contained in the system information.

10 48. The apparatus of claim 45, wherein the first indication information is further used for indicating location of a resource for sending control information of the system information, or the first indication information is used for indicating starting location of a resource for sending control information of the system information, and at least one of time domain width of a resource block and frequency domain width of the resource block;

15 wherein the first determining module is specifically used for determining the resource for sending the control information of the system information according to the location of the resource for sending the control information of the system information indicated by the first indication information, or according to the starting location of the resource for sending the control information of the system information, and the at least one of the time domain of the resource block and the frequency domain width of the resource block, indicated by the first
20 indication information;

wherein the receiving module is further used for receiving the control information of the system information on the resource for sending the control information of the system information; and

25 the first determining module is specifically used for determining the first resource according to a resource indicated by the control information of the system information.

49. The apparatus of claim 48, wherein the control information of the system information is further used for indicating a transmission periodicity for sending the system information, and/or the control information of the system information is further used for indicating content information contained in the sent system information.

50. The apparatus of any one of claims 45 to 49, wherein the receiving module is specifically used for:

receiving the first indication information through synchronization information.

51. The apparatus of any one of claims 45 to 50, wherein the first indication information
5 is further used for indicating whether the apparatus needs to send the system information on the first resource for sending;

wherein the first determining module is specifically used for determining the first resource according to the first indication information when the first indication information is further used for indicating that the apparatus needs to send the system information on the first resource.

10 52. The apparatus of claim 44, wherein the apparatus further comprises:

a second determining module, used for determining the first resource according to preconfigured information before receiving the system information on the configured first resource.

53. The apparatus according to claim 52, wherein the preconfigured information is used
15 for indicating a calculation method of the first resource;

wherein the second determining module is specifically used for determining the first resource according to the calculation method of the first resource indicated by the preconfigured information.

54. The apparatus according to claim 52, wherein the configured information is used for
20 indicating a calculation method of a resource for sending control information of the system information;

wherein the second determining module is further specifically used for calculating the resource for sending the control information of the system information according to the calculation method of the resource for sending the control information of the system
25 information indicated by the preconfigured information;

wherein the receiving module is further used for receiving the control information of the system information on the resource for sending the control information of the system information; and

wherein the second determining module is specifically used for determining the first resource according to a resource indicated by the control information of the system information.

55. The apparatus of any one of claims 44 to 54, wherein the receiving module is specifically further used for:

5 receiving the system information simultaneously or sequentially according to bandwidth supported by the apparatus.

56. The apparatus according to any one of claims 44 to 55, wherein the system information comprises second indication information, and the second indication information is used for indicating resources for the apparatus to receive other system information than the
10 system information;

wherein the receiving module is further used for: receiving the other system information on the resources for receiving the other system information than the system information according to the second indication information after receiving the system information on the configured first resource.

15 57. The apparatus of claim 56, wherein the second indication information is further used for indicating an order in which the apparatus receives the other system information, and/or the second indication information is further used for indicating content information of the other system information.

20 58. The apparatus of any one of claims 44 to 57, wherein the system information is a master information block.