WHAT IS CLAIMED IS:

1. A child stroller frame comprising:

a first and a second frame portion, the second frame portion having a front end and a rear end, the front end of the second frame portion being pivotally connected with the first frame portion;

a pivoting part having one end fixedly connected with a rear wheel support member and another end pivotally connected with the rear end of the second frame portion; and

a linkage movably coupling the first frame portion to the pivoting part, the linkage having an intermediate portion pivotally connected with the second frame portion, whereby the first frame portion and the rear wheel support member are movably linked for folding in a concurrent manner toward the second frame portion, wherein the linkage includes:

a first bar assembly respectively connected pivotally with the pivoting part and the second frame portion, the first bar assembly including a first bar pivotally connected with the second frame portion, and a second bar having two opposite ends respectively connected pivotally with the first bar and the pivoting part, wherein the first bar assembly, the pivoting part and the second frame portion form a first bar linkage portion; and

a second bar assembly respectively connected pivotally with the first bar and the first frame portion, wherein the second bar assembly, the first bar, the first frame portion and the second frame portion form a second bar linkage portion.

2. The child stroller frame according to claim 1, wherein the first frame portion includes a handle frame segment and a front leg segment that are pivotally connected with each other.

3. The child stroller frame according to claim 2, wherein the second frame portion

is pivotally connected with any of the front leg segment, the handle frame segment, or a coupling part that pivotally connects the front leg segment with the handle frame segment.

4. The child stroller frame according to claim 2, wherein the linkage has an end that is pivotally connected with any of the front leg segment, the handle frame segment, or a coupling part that pivotally connects the front leg segment with the handle frame segment.

5. The child stroller frame according to claim 2, wherein the child stroller frame is folded either with the handle frame segment and the front leg segment lying at one same side of the second frame portion, or with the handle frame segment and the front leg segment respectively lying at two opposite sides of the second frame portion.

6. The child stroller frame according to any one of claims 1 to 5, wherein the first bar has a first and a second bar portion, the first bar being pivotally connected with the second bar assembly at an end of the first bar portion, and the second bar portion extending toward and pivotally connecting with the second bar.

7. The child stroller frame according to claim 6, wherein the first and second bar portions intersect each other at an angle, a pivot connection between the first bar and the second frame portion being located at a joining region between the first and second bar portions.

8. The child stroller frame according to claim 6 or 7, wherein the first bar has a L-shape.

9. The child stroller frame according to any one of claims 6 to 8, further including a limiting structure disposed between the first bar portion and the second bar assembly, the first bar portion and the second bar assembly forming a substantially straight shape that extends between the first frame portion and the second frame portion when the child stroller frame is in an unfolded state for use.

10. The child stroller frame according to any one of claims 1 to 9, wherein the second bar has a shape configured to prevent obstructing interference with the pivoting part and/or the rear wheel support member during folding movement.

11. The child stroller frame according to claim 10, wherein the second bar includes a curved profile with a concavity facing downward.

12. The child stroller frame according to any one of claims 1 to 11, wherein the second bar assembly includes a third bar having two opposite ends respectively connected pivotally with the first bar and the first frame portion.

13. The child stroller frame according to any one of claims 1 to 12, wherein the rear wheel support member includes a transversal axle or a wheel mount.